

Cribl Search Documentation Manual

Version: v4.20

Generated: 2026-09-15 19:44:31

Copyright (c) 2017- 2026 Cribl, Inc. All rights reserved.

1. About Cribl Search 16
1.1. Cribl Search Concepts 18
1.2. Quick Start 20
1.3. Cribl Search UI Tour 25
2. Get Data Into Cribl Search 27
2.1. Lakehouse Engines in Cribl Search 31
2.2. Create Search Datasets in Cribl Search 37
2.3. Dataset Intelligence 46
2.4. Shape Data with Datatype Rules 49
2.5. Organize Data with Dataset Rules 55
2.6. View Live Data in Cribl Search 61
2.7. Cribl Search Sources 65
2.7.1. Ingest Cribl Stream/Edge Data into Cribl Search 67
2.7.2. Ingest Datadog Agent Data into Cribl Search 72
2.7.3. Ingest Elasticsearch Data into Cribl Search 77
2.7.4. Ingest OpenTelemetry Data into Cribl Search 82
2.7.5. Ingest Prometheus Metrics into Cribl Search 90
2.7.6. Ingest Raw HTTP Data into Cribl Search 97
2.7.7. Ingest Splunk HEC Events into Cribl Search 102
2.7.8. Ingest Splunk Forwarder Data into Cribl Search 108
2.7.9. Ingest Syslog Messages into Cribl Search 113
2.7.10. Ingest JSON Events via TCP into Cribl Search 118
2.7.11. Ingest Raw TCP Data into Cribl Search 123
2.7.12. Ingest Windows Events into Cribl Search 128
2.7.13. Ingest Wiz Security Events into Cribl Search 133
3. Explore Metrics in Cribl Search 138
3.1. Create Monitors in Cribl Search 146
3.2. Manage Monitor Notifications 151
3.3. Add Metrics to Dashboards 157
4. Connect Cribl Search to External Data 159
4.1. Connect Cribl Search to Cribl Lake 162
4.2. Connect Cribl Search to Amazon S3 168
4.3. Connect Cribl Search to Cribl Edge 180
4.4. Connect Cribl Search to AWS 185
4.4.1. Grant Access to AWS 186
4.4.2. Connect Cribl Search to Amazon Security Lake 196

4.4.3. Connect Cribl Search to AWS API 203
4.4.4. Connect Cribl Search to Data Lake Amazon S3 207
4.5. Connect Cribl Search to Azure 215
4.5.1. Connect Cribl Search to Azure Blob Storage 216
4.5.2. Connect Cribl Search to Azure Data Explorer 230
4.5.3. Connect Cribl Search to Azure Log Analytics 232
4.5.4. Connect Cribl Search to Azure API 236
4.6. Connect Cribl Search to Google 239
4.6.1. Connect Cribl Search to Google Cloud Storage 240
4.6.2. Connect Cribl Search to Google Cloud Platform API 247
4.6.3. Connect Cribl Search to Google Workspace API 249
4.7. Connect Cribl Search to ClickHouse 252
4.8. Connect Cribl Search to CrowdStrike NG-SIEM 256
4.9. Connect Cribl Search to Elasticsearch 261
4.10. Connect Cribl Search to a Generic HTTP API 263
4.11. Connect Cribl Search to Microsoft Graph API 269
4.12. Connect Cribl Search to Okta API 274
4.13. Connect Cribl Search to OpenSearch 276
4.14. Connect Cribl Search to Prometheus 278
4.15. Connect Cribl Search to Snowflake 285
4.16. Connect Cribl Search to Tailscale API 288
4.17. Connect Cribl Search to Zoom API 290
4.18. Configure Data Connection Options in Cribl Search 292
4.18.1. Datatypes in Cribl Search 293
4.18.1.1. v1 Datatypes in Cribl Search 296
4.18.1.2. v2 Datatypes in Cribl Search 326
4.18.1.3. Federated Search v2 346
4.18.2. Storage Classes 351
4.18.3. Supported Data Formats 354
5. Explore Your Cribl Search Data 359
5.1. Inspect Your Cribl Search Datasets 360
5.2. View Search History in Cribl Search 363
6. Search Your Data with Cribl Search 367
6.1. Integrated AI Experience (Preview) in Cribl Search 368
6.2. Build a Search 372
6.3. Write Your First Query 384
6.4. Write Cribl Search Queries With Cribl Copilot 397
6.5. Common Query Examples 400

6.6. View Search Results in Cribl Search 409
6.7. Export Cribl Search Results 419
6.8. Save Searches in Cribl Search 424
6.9. Example Searches by Provider 426
6.9.1. Searching Cribl Lake 427
6.9.2. Searching Cribl Edge 430
6.9.3. Built-In Cribl Edge Datasets 434
6.9.4. Searching Amazon S3 438
6.9.5. Searching AWS API 442
6.9.6. Searching Okta API 445
6.9.7. Searching Zoom API 447
6.9.8. Searching Multiple Providers 449
7. Investigate 454
7.1. Run Investigations (Preview) with Cribl Search 457
7.2. Deep Investigations (Preview) 464
7.3. Cribl Search Notebooks 468
7.4. Notebook Templates 481
7.5. Investigative Searching 485
8. Visualize Cribl Search Results 489
8.1. Charts 491
8.1.1. Types of Charts in Cribl Search 494
8.1.1.1. Area Chart 495
8.1.1.2. Column Chart 497
8.1.1.3. Donut Chart 499
8.1.1.4. Funnel Chart 501
8.1.1.5. Gauge Chart 503
8.1.1.6. Horizontal Bar Chart 504
8.1.1.7. Line Chart 507
8.1.1.8. Map Chart 509
8.1.1.9. Scatter Chart 513
8.1.1.10. Single Value Chart 515
8.1.2. Results Tables 517
8.2. Dashboards 522
8.2.1. Create a Dashboard 524
8.2.2. Edit a Dashboard 528
8.2.3. Add Interactions to Your Cribl Search Dashboard 539
8.2.4. Add Inputs to Your Cribl Search Dashboard 551
8.2.5. Add Cribl Search Visualizations With Cribl Copilot 560

8.2.6. Manage and Share Dashboards 566
8.2.7. Migrate Grafana Dashboards 567
8.3. Third-Party Visualization Tools 575
8.3.1. Visualize Cribl Search Results in Grafana 575
9. Send Alerts With Cribl Search 580
9.1. Scheduled Searches 581
9.2. Notifications 585
9.2.1. Email Notifications 590
9.2.2. AWS SNS Notifications 596
9.2.3. PagerDuty Notifications 601
9.2.4. Slack Notifications 604
9.2.5. Webhook Notifications 607
9.2.6. Notifications via Cribl Stream 614
10. Manage Cribl Search and Cribl.Cloud 619
10.1. Cribl.Cloud Access and Usage 621
10.1.1. Manage Cribl.Cloud Organizations 622
10.2. Workspaces 625
10.2.1. Configure Workspaces 630
10.3. Usage Settings 634
10.3.1. Usage Groups 636
10.3.2. Limits 639
10.4. Manage Access to Cribl Search Resources 641
10.5. Cribl Search Engines 645
10.6. Configuration Files 651
11. Optimize Cribl Search 652
11.1. Optimize Searches 653
11.2. Optimize Paths 659
11.3. Productivity Tips 665
11.4. Useful Queries (Analytic Cookbook) 669
11.5. Dynamic Search Concurrency 679
12. Troubleshooting Cribl Search 681
12.1. KQL Extensions 682
12.2. Lakehouse Search Differences 683
12.3. Diagnose Searches and Track Cribl Search Usage 686
12.4. Share Diagnostics 693
12.5. Common Issues and Resolutions 694
13. Knowledge Libraries in Cribl Search 700
13.1. Lookups 701

13.2. Parsers 705
13.3. Regexes 708
13.4. Grok Patterns 710
13.5. Macros 711
13.6. Cribl Search Packs 717
14. Language Reference 733
14.1. Language Reference Index 736
14.2. Operators in Cribl Search 750
14.2.1. Aggregation Operators 756
14.2.1.1. count 757
14.2.1.2. eventstats 759
14.2.1.3. summarize 762
14.2.1.4. timestats 767
14.2.2. Data Operators 771
14.2.2.1. centralize 772
14.2.2.2. export 774
14.2.2.3. extend 784
14.2.2.4. externaldata 786
14.2.2.5. extract 789
14.2.2.6. foldkeys 794
14.2.2.7. ip-lookup 800
14.2.2.8. join 803
14.2.2.9. lookup 808
14.2.2.10. mv-expand 811
14.2.2.11. mv-pull 814
14.2.2.12. pivot 817
14.2.2.13. send 821
14.2.2.14. top-hitters 825
14.2.2.15. union 827
14.2.3. Display Operators 829
14.2.3.1. limit 830
14.2.3.2. order 832
14.2.3.3. print 834
14.2.3.4. project 836
14.2.3.5. project-away 839
14.2.3.6. project-rename 841
14.2.3.7. range 843
14.2.3.8. render 845

14.2.3.9. sort 847
14.2.3.10. take 849
14.2.3.11. top 851
14.2.4. Filter Operators 853
14.2.4.1. between 854
14.2.4.2. dedup 857
14.2.4.3. distinct 859
14.2.4.4. search 861
14.2.4.5. suppress 865
14.2.4.6. where 867
14.2.5. Logical Operators 875
14.2.6. Numerical Operators 876
14.2.7. Search Operators 877
14.2.7.1. cribl 878
14.2.7.2. find 886
14.2.8. String Operators 891
14.2.8.1. == 894
14.2.8.2. != 896
14.2.8.3. =~ 898
14.2.8.4. !~ 900
14.2.8.5. contains 902
14.2.8.6. !contains 904
14.2.8.7. contains_cs 906
14.2.8.8. !contains_cs 908
14.2.8.9. endswith 910
14.2.8.10. !endswith 912
14.2.8.11. endswith_cs 914
14.2.8.12. !endswith_cs 916
14.2.8.13. has 918
14.2.8.14. !has 920
14.2.8.15. has_cs 922
14.2.8.16. !has_cs 924
14.2.8.17. has_all 926
14.2.8.18. !has_all 927
14.2.8.19. has_any 928
14.2.8.20. !has_any 929
14.2.8.21. hasprefix 930
14.2.8.22. !hasprefix 932

14.2.8.23. hasprefix_cs 934
14.2.8.24. !hasprefix_cs 936
14.2.8.25. hassuffix 938
14.2.8.26. !hassuffix 940
14.2.8.27. hassuffix_cs 942
14.2.8.28. !hassuffix_cs 944
14.2.8.29. in 946
14.2.8.30. !in 948
14.2.8.31. in~ 950
14.2.8.32. !in~ 952
14.2.8.33. matches regex 954
14.2.8.34. startswith 956
14.2.8.35. !startswith 958
14.2.8.36. startswith_cs 960
14.2.8.37. !startswith_cs 962
14.3. Commands 964
14.3.1. .cancel 969
14.3.2. .show 972
14.3.3. .clear 973
14.3.4. .generate 974
14.3.5. objects 975
14.3.6. options 978
14.3.7. stats 982
14.3.8. queries 984
14.4. Statements 986
14.4.1. let 987
14.4.2. set 991
14.5. Functions 1005
14.5.1. Context Functions 1018
14.5.1.1. createdTime 1020
14.5.1.2. displayUsername 1022
14.5.1.3. earliestTime 1023
14.5.1.4. jobID 1024
14.5.1.5. latestTime 1025
14.5.1.6. query 1026
14.5.1.7. user 1027
14.5.2. Cribl Functions 1028
14.5.2.1. findearliest 1030

14.5.2.2. findearliestif 1031
14.5.2.3. findfirst 1032
14.5.2.4. findfirstif 1034
14.5.2.5. findlast 1035
14.5.2.6. findlastif 1037
14.5.2.7. findlatest 1038
14.5.2.8. findlatestif 1039
14.5.2.9. list 1040
14.5.2.10. median 1041
14.5.2.11. medianif 1042
14.5.2.12. persecond 1043
14.5.2.13. persecondif 1044
14.5.2.14. rate 1045
14.5.2.15. rateif 1046
14.5.2.16. sumsq 1047
14.5.2.17. sumsqif 1048
14.5.2.18. values 1049
14.5.3. Scalar Functions 1051
14.5.3.1. Binary Functions 1061
14.5.3.1.1. binary_and 1062
14.5.3.1.2. binary_not 1063
14.5.3.1.3. binary_or 1064
14.5.3.1.4. binary_shift_left 1065
14.5.3.1.5. binary_shift_right 1066
14.5.3.1.6. binary_xor 1067
14.5.3.1.7. from_binary_string 1068
14.5.3.1.8. to_binary_string 1069
14.5.3.2. Conditional Functions 1070
14.5.3.2.1. case 1071
14.5.3.2.2. coalesce 1073
14.5.3.2.3. iff 1074
14.5.3.2.4. iif 1075
14.5.3.2.5. max_of 1076
14.5.3.2.6. min_of 1077
14.5.3.3. Conversion Functions 1078
14.5.3.3.1. bin 1079
14.5.3.3.2. bin_auto 1081
14.5.3.3.3. floor 1083

14.5.3.3.4. gettype 1085
14.5.3.3.5. tobool 1087
14.5.3.3.6. todecimal 1089
14.5.3.3.7. todouble 1090
14.5.3.3.8. toint 1091
14.5.3.3.9. tolong 1092
14.5.3.3.10. toreal 1093
14.5.3.3.11. tostring 1094
14.5.3.4. DateTime Functions 1095
14.5.3.4.1. ago 1098
14.5.3.4.2. datetime_add 1100
14.5.3.4.3. datetime_diff 1102
14.5.3.4.4. datetime_part 1104
14.5.3.4.5. dayofmonth 1107
14.5.3.4.6. dayofweek 1108
14.5.3.4.7. dayofyear 1109
14.5.3.4.8. endofday 1110
14.5.3.4.9. endofmonth 1111
14.5.3.4.10. endofweek 1112
14.5.3.4.11. endofyear 1113
14.5.3.4.12. format_datetime 1114
14.5.3.4.13. format_timespan 1118
14.5.3.4.14. getmonth 1122
14.5.3.4.15. getyear 1123
14.5.3.4.16. hourofday 1124
14.5.3.4.17. make_datetime 1125
14.5.3.4.18. make_timespan 1126
14.5.3.4.19. monthofyear 1128
14.5.3.4.20. now 1129
14.5.3.4.21. startofday 1131
14.5.3.4.22. startofmonth 1132
14.5.3.4.23. startofweek 1133
14.5.3.4.24. startofyear 1134
14.5.3.4.25. strftime 1135
14.5.3.4.26. strptime 1137
14.5.3.4.27. todatetime 1139
14.5.3.4.28. totimespan 1140
14.5.3.4.29. unixtime_microseconds_todatetime 1141

14.5.3.4.30. unixtime_milliseconds_todatetime 1142
14.5.3.4.31. unixtime_nanoseconds_todatetime 1143
14.5.3.4.32. unixtime_seconds_todatetime 1144
14.5.3.4.33. week_of_year 1145
14.5.3.5. Dynamic Functions 1146
14.5.3.5.1. bag_has_key 1147
14.5.3.5.2. bag_keys 1148
14.5.3.5.3. bag_merge 1149
14.5.3.5.4. bag_pack 1151
14.5.3.5.5. bag_pack_columns 1153
14.5.3.5.6. bag_remove_keys 1155
14.5.3.5.7. bag_set_key 1157
14.5.3.5.8. bag_zip 1160
14.5.3.5.9. make_bag 1162
14.5.3.5.10. make_bag_if 1165
14.5.3.5.11. zip 1168
14.5.3.6. Cryptographic Functions 1170
14.5.3.6.1. encrypt 1171
14.5.3.6.2. decrypt 1173
14.5.3.7. Hash Functions 1175
14.5.3.7.1. hash 1176
14.5.3.7.2. hash_combine 1178
14.5.3.7.3. hash_many 1179
14.5.3.7.4. hash_md5 1180
14.5.3.7.5. hash_sha1 1182
14.5.3.7.6. hash_sha256 1184
14.5.3.7.7. hash_xxhash64 1186
14.5.3.8. INET Functions 1187
14.5.3.8.1. ipv4_compare 1188
14.5.3.8.2. ipv4_is_in_range 1190
14.5.3.8.3. ipv4_is_in_any_range 1192
14.5.3.8.4. ipv4_is_match 1194
14.5.3.8.5. ipv4_is_private 1196
14.5.3.8.6. ipv4_netmask_suffix 1198
14.5.3.8.7. ipv6_compare 1200
14.5.3.8.8. ipv6_is_match 1202
14.5.3.8.9. format_bytes 1204
14.5.3.8.10. format_ipv4 1206

14.5.3.8.11. format_ipv4_mask 1207
14.5.3.9. Mathematical Functions 1208
14.5.3.9.1. abs 1210
14.5.3.9.2. acos 1211
14.5.3.9.3. asin 1212
14.5.3.9.4. atan 1213
14.5.3.9.5. atan2 1214
14.5.3.9.6. beta_cdf 1215
14.5.3.9.7. beta_inv 1217
14.5.3.9.8. beta_pdf 1219
14.5.3.9.9. ceil 1221
14.5.3.9.10. ceiling 1222
14.5.3.9.11. cos 1223
14.5.3.9.12. cot 1224
14.5.3.9.13. degrees 1225
14.5.3.9.14. exp 1226
14.5.3.9.15. exp2 1227
14.5.3.9.16. exp10 1228
14.5.3.9.17. gamma 1229
14.5.3.9.18. isfinite 1230
14.5.3.9.19. isinf 1231
14.5.3.9.20. isnan 1233
14.5.3.9.21. log 1234
14.5.3.9.22. log2 1235
14.5.3.9.23. log10 1236
14.5.3.9.24. loggamma 1237
14.5.3.9.25. not 1238
14.5.3.9.26. pi 1240
14.5.3.9.27. pow 1241
14.5.3.9.28. radians 1242
14.5.3.9.29. rand 1243
14.5.3.9.30. range 1244
14.5.3.9.31. round 1246
14.5.3.9.32. sign 1248
14.5.3.9.33. sin 1249
14.5.3.9.34. sqrt 1250
14.5.3.9.35. tan 1251
14.5.3.10. String Functions 1252

14.5.3.10.1. base64_decode_toarray 1255
14.5.3.10.2. base64_decode_tostring 1256
14.5.3.10.3. base64_encode_fromarray 1257
14.5.3.10.4. base64_encode_tostring 1259
14.5.3.10.5. countof 1260
14.5.3.10.6. extract 1263
14.5.3.10.7. extract_all 1265
14.5.3.10.8. extract_json 1268
14.5.3.10.9. has_any_index 1270
14.5.3.10.10. indexof 1272
14.5.3.10.11. isempty 1275
14.5.3.10.12. isnotempty 1277
14.5.3.10.13. isnotnull 1279
14.5.3.10.14. isnull 1280
14.5.3.10.15. match_regex 1281
14.5.3.10.16. parse_csv 1283
14.5.3.10.17. parse_ipv4 1285
14.5.3.10.18. parse_ipv4_mask 1287
14.5.3.10.19. parse_ipv6 1289
14.5.3.10.20. parse_ipv6_mask 1291
14.5.3.10.21. parse_json 1293
14.5.3.10.22. parse_url 1295
14.5.3.10.23. parse_urlquery 1297
14.5.3.10.24. parse_version 1299
14.5.3.10.25. replace_regex 1300
14.5.3.10.26. reverse 1302
14.5.3.10.27. split 1303
14.5.3.10.28. strcat 1305
14.5.3.10.29. strcat_delim 1307
14.5.3.10.30. strcmp 1308
14.5.3.10.31. strlen 1310
14.5.3.10.32. strrep 1311
14.5.3.10.33. substring 1313
14.5.3.10.34. tolower 1315
14.5.3.10.35. toupper 1316
14.5.3.10.36. translate 1317
14.5.3.10.37. trim 1319
14.5.3.10.38. trim_end 1321

14.5.3.10.39. trim_start 1322
14.5.3.10.40. url_decode 1323
14.5.3.10.41. url_encode 1324
14.5.4. Statistical Functions 1325
14.5.4.1. avg 1327
14.5.4.2. avgif 1329
14.5.4.3. count 1331
14.5.4.4. countif 1332
14.5.4.5. dcount 1333
14.5.4.6. dcountif 1336
14.5.4.7. max 1339
14.5.4.8. maxif 1340
14.5.4.9. min 1341
14.5.4.10. minif 1342
14.5.4.11. percentile 1344
14.5.4.12. stdev 1346
14.5.4.13. stdevif 1348
14.5.4.14. stdevp 1349
14.5.4.15. sum 1351
14.5.4.16. sumif 1352
14.5.4.17. take_any 1353
14.5.4.18. take_anyif 1355
14.5.4.19. variance 1357
14.5.4.20. varianceif 1359
14.5.4.21. variancep 1360
14.5.5. Window Functions 1362
14.5.5.1. next 1363
14.5.5.2. prev 1365
14.5.5.3. row_cumsum 1367
14.5.5.4. row_number 1369
14.5.5.5. row_rank_dense 1370
14.5.5.6. row_rank_min 1372
14.5.5.7. row_window_session 1374
14.6. Virtual Tables 1376
14.6.1. $vt_datasets 1377
14.6.2. $vt_dataset_providers 1379
14.6.3. $vt_dummy 1381
14.6.4. $vt_jobs 1383

14.6.5. $vt_list 1385
14.6.6. $vt_lookups 1387
14.6.7. $vt_results 1389
14.7. Types 1393
14.7.1. bool 1395
14.7.2. datetime 1399
14.7.3. decimal 1400
14.7.4. double 1401
14.7.5. dynamic 1402
14.7.6. int 1406
14.7.7. long 1407
14.7.8. null 1408
14.7.9. real 1412
14.7.10. string 1413
14.7.11. timespan 1415
14.8. Regex Matching 1417

1. About Cribl Search

Cribl Search is a unified log search and investigation platform that answers data questions with AI-assisted insights.

One Place to Search All Your Data

Combine fast ingest-based search with search-in-place
Ingest data directly into Cribl Search for high-speed access, while running federated queries on unindexed data stored elsewhere.

Understand your data before searching it
Explore your data and see available fields before writing a query.

Run AI-native investigations
Investigate incidents with AI guidance and capture your findings in one workspace.

Collaborate in Notebooks
Combine queries, visualizations, and Markdown notes in shareable Notebooks.

Visualize results
Build charts and Dashboards from your searches, track key metrics, and share live views with others.

Get alerted
Schedule searches, watch for spikes or outliers, and send alerts to your existing tools.

Scale with Packs
Install or build custom Packs of Dashboards, saved searches, Macros, and lookups.

Many Engines, One Interface

Lakehouse engines host and accelerate your data. You can:

- Onboard data directly from existing pipelines, APIs, webhooks, agents.
- Shape, filter, and enrich events on ingest.
- Organize your data into Search Datasets and fine-tune their retention.

The federated engine connects to external data without indexing, so you can:

- Query data where it lives: object stores, analytics services, APIs, and more.
- Search across multiple systems at once without copying data around.
- Run queries natively on AWS and Azure.

A unified interface lets you:

- Run lakehouse queries and federated searches side by side without switching tools.
- Use the same query language and natural-language prompts for both types of searches.
- Investigate incidents across both backends with AI guidance and capture the full story in a single Notebook.

Read the Docs

Start your Cribl Search journey with the following resources.

Overview

- Concepts: Get a glossary-level overview of Cribl Search's core building blocks.
- Quick Start: Create a Cribl.Cloud Organization to run your first search.
- Cribl Search Tour: Find your way around the Cribl Search UI.

Setup

- Get Data In: Ingest data into a lakehouse engine.
- Connect to External Data: Set up federated search for data stored elsewhere.
- Manage: Control engines, access, and system limits.

Search & Analysis

- Search: Learn how to build efficient queries.
- Investigate: Answer data questions with Notebooks and AI-driven workflows.
- Visualize: Turn search results into charts and Dashboards.
- Alert: Schedule searches and send notifications.

Reference

- Language Reference: Learn Kusto Query Language that powers your queries.
- API Code Examples: Run searches programmatically.
- API Reference: Full API reference for Cribl Search.

1.1. Cribl Search Concepts

Get familiar with Cribl Search terminology.

Search

A query that filters, aggregates, or transforms your data to answer a question, trigger an alert, or populate a dashboard.

In Cribl Search, you can query data ingested directly into a lakehouse engine for best performance, or run federated search-in-place queries on data stored elsewhere with no onboarding or indexing required.

Engine

A storage and compute resource that powers Cribl Search queries.

Lakehouse engines search data stored in Cribl Search. They keep your data hot for up to 10 years, with no storage tiering to manage. You can add multiple lakehouse engines and size each one for your ingest rate.

Federated engine runs search-in-place of data stored elsewhere. Each Workspace has one federated engine.

Datatype

A set of rules that lets Cribl Search recognize data of a certain type, break it into discrete events, timestamp them, and parse them into meaningful fields for more efficient searching.

Datatypes v1 work with federated searches.

Datatypes v2 support all search types and are the most efficient.

Read about Datatypes

Dataset

A named container that groups related events so you can scope searches and control retention.

Cribl Search Datasets group events stored in a lakehouse engine, based on **Dataset rules**.

Federated Datasets reference data stored externally, using **Dataset Providers** to access it.

Kusto Query Language (KQL)

Query language used to run searches in Cribl Search.

See Language Reference for full syntax reference.

1.2. Quick Start

Create a Cribl.Cloud Organization to run your first search.

Sign Up for Cribl.Cloud

Your first step is to create your Cribl.Cloud Organization.

1. Start at: https://cribl.cloud/signup/.
2. Select the **New User? Free signup** option, and register with your work email address.
3. Use the verification code from Cribl's email to confirm your registration.
4. On the **Create Organization** page, optionally enter an **Organization Name** (a friendly alias for the randomly generated ID that Cribl will assign to your Organization).
5. Select an AWS or Azure Region to host your Cribl.Cloud Leader. See the list of supported regions.


   

   The Organization region defines where the Leader Node resides.

   Once you select a region when registering your Organization, you cannot change it. You can, however, create Cribl-managed Stream Worker Groups in different AWS and Azure regions.


   In Cribl Search, the Organization region is the physical location where searches are executed. In Cribl Lake, the region defines the location where data is stored.
6. Select **Create Organization**.
7. On the resulting page labeled **We're spinning up your Organization...**, complete the quick survey to let us know how you plan to use Cribl products.
8. Select **Create Organization**.
9. On the resulting page labeled **We're spinning up your Organization...**, complete the quick survey to let us know how you plan to use Cribl products.

   The goals that you select here, and the Sources and Destinations that you choose on the next page, will display personalized guidance as soon as you open your Organization.
10. Select **Complete** to access your new Organization.
11. Select the **Search** tile's **Explore** button to open Cribl Search.



Cribl.Cloud landing page

12. The first time you sign in, you'll see a tile with a goat who can walk you through setting up Cribl Search. If you skip the walkthrough now, you can start it at any later time by opening the Support/Copilot drawer's **Get Help** tab, where you'll find the goat.




Searching

In this guide, you'll use a built-in sample Dataset named `cribl_search_sample`.


Runnable Kusto code examples include a **Run in Cribl Search** link in the top-right corner of the code block. Select it to open the query in your Cribl Search environment with the query loaded and ready to execute. You can also use the **Copy** button to copy a query and paste it into your own search.

1. From the Cribl Search sidebar, select **Data** to open the default **Datasets** tab. Find the `cribl_search_sample` Dataset within the **Datasets** table.
2. Select the **Search** button on the right side of the `cribl_search_sample` row.



Datasets

3. The **Logs** page opens and runs a basic search on the Dataset.




Limit Dataset results

We've referenced the Dataset with the field `dataset` and its `ID`, in this case, `cribl_search_sample`. The pipe | character indicates a new process for the query to run. Here, it's added a `limit` operator so the search only returns up to 1,000 events from the Dataset.

4. Next, let's run an aggregating search - counting the number of events per `source` (a built-in field that contains the name of the data object that included the event).


```
dataset="cribl_search_sample"
| limit 1000
| summarize count() by source
```

Copy | Run in Cribl Search


1 dataset="cribl_search_sample"
2 | limit 1000
3 | summarize count() by source
Events
Fields
Chart
Objects discovered: 150, scanned: 40, skipped: 0
21 results (2.89s)
Details
Actions
count_
119
100
80
60

1.3. Cribl Search UI Tour

Find your way around the Cribl Search UI.



Cribl Search Logs page

Sidebar (1-12) Query Box (13-17) Datasets and Searches (18-20)

Area	Description	More Info
1	**Recents** show your latest work.	Recents
2	**Logs** is where you run log searches.	Search Your Data
3	**Metrics** is where you explore, filter, and visualize metrics.	Metrics
4	**Monitors** watch metric queries and raise alerts.	Monitors
5	**History** keeps previous searches so you can reuse them or check cached results.	View Search History
6	**Saved Searches** let you run queries on schedule and set up Notifications.	Save Searches
7	**Dashboards** visualize search results in a variety of ways.	Dashboards
8	**Notebooks** let you combine queries, visualizations, and notes on one tab.	Notebooks

Area	Description	More Info
9	**Data** is where Search Admins and Editors manage Engines, Sources, Datasets, Dataset Providers, and Datatypes.	Get Data Into Cribl Search Connect to External Data
10	**Knowledge** contains your lookups, Parsers, regexes, Grok patterns, and Macros.	Knowledge Libraries
11	**Packs** let Search Admins and Editors import, export, and share knowledge objects.	Packs
12	**Settings** is where Search Admins set Notification targets, Usage Groups, and limits.	Usage Settings

2. Get Data Into Cribl Search

Ingest data into Cribl Search lakehouse engines for schema-aware searches and precisely scoped AI investigations.

Highlights

- Send directly into Cribl Search, auto-parsing events as they arrive.
- First, add a lakehouse engine and Search Datasets within it. Then, connect your Sources.
- Parse with Auto-Datatyping or your own Datatype rules. Set Dataset rules to route the parsed events into the Datasets.

Lakehouse Engines Make Search Faster


Next to running federated queries on external storage, Cribl Search can also store your data in lakehouse engines.

Lakehouse engines keep your data hot for up to 10 years, with no storage tiering to manage. This allows for:

- **High-speed search** for day-to-day investigations and incident response.
- **Deeper AI-powered analysis**, with structured data that makes exploration faster and more precise.
- **Tight cost control** through fixed-size engines and per-Dataset retention.

You don't have to use Cribl Stream, Edge, or Lake. You can ingest directly into Cribl Search.

To get started, add your first lakehouse engine. This enables the **Get Data In** tab in the Cribl Search **Data** section:



Get Data In tab in Cribl Search


Get Data In Permissions

Working with the **Get Data In** steps - **Sources**, **Datatyping**, and **Datasets** - needs the **Editor** or **Admin** Permission on Cribl Search. Adding a lakehouse engine needs the **Admin** Permission. See Cribl Search Permissions.

Data Onboarding Overview

To ingest data into Cribl Search:

1. Add a lakehouse engine.
2. Create your Search Datasets.
3. Connect your Sources.
4. Set up Datatyping.
5. Set Dataset rules.
6. Start sending data.



Ingesting data into Cribl Search

1. Add a Lakehouse Engine

Create a lakehouse engine first. It provides the storage and compute layer for ingested data.

Choose an engine size based on your expected daily ingest. Adjust over time as needed.

See Lakehouse Engines in Cribl Search to add an engine, choose a size, and estimate costs.

2. Create Your Search Datasets

Prepare Search Datasets that you'll later target with Dataset rules. This is where you set retention, from 1 day to 10 years, per Search Dataset.

See Create Search Datasets for planning guidance and step-by-step setup.

3. Connect Sources

With your lakehouse engine and Search Datasets ready, set up Sources in Cribl Search.

See Cribl Search Sources for end-to-end walkthroughs for each Source type.

4. Shape and Filter with Datatype Rules

Datatype rules control how incoming events are parsed and labeled.

Start with Auto-Datatyping. If needed, add new rules for uncategorized events, or create your own custom Datatypes.

See Shape Data with Datatype Rules.

5. Organize and Control Retention with Dataset Rules

Dataset rules route parsed events into your Search Datasets, so each event lands where its retention, investigation window, and access make sense.

See Organize Data with Dataset Rules.

6. Start Sending Data and Verify

Start sending events from your upstream sender. Confirm that data arrives, parses, and routes as expected using Live Data.

See individual Cribl Search Sources tutorials to learn how to set up your client.

2.1. Lakehouse Engines In Cribl Search

Add a lakehouse engine so you can ingest data directly into Cribl Search.

Highlights

- Lakehouse engines store and accelerate your data within Cribl Search.
- Storage auto-scales with your data volume and retention settings.
- Choose an engine size that covers your raw, uncompressed daily ingest. Resize or add more engines as needed.

Lakehouse Engines Store and Accelerate Data

When you send data into Cribl Search with Sources, it's parsed by Datatypes and stored in Search Datasets on a lakehouse engine.

A lakehouse engine is a storage-plus-compute unit that ingests, stores, and accelerates your data inside Cribl Search. It can keep your data hot for up to 10 years, with no storage tiering to manage.

Each lakehouse engine:

- Accepts data from one or more Sources.
- Uses Datatypes to break events into fields.
- Stores data in Search Datasets until their retention expires.
- Powers fast, schema-aware searches and AI workflows over that stored data.

Lakehouse Engine Sizes

To choose the right lakehouse engine size, think about the amount of raw, uncompressed data you expect per day, then include headroom for spikes and growth.

If your ingest rate changes, or you experience ingest or search latency, you can resize your lakehouse engine. If the available sizes are not enough, you can add more lakehouse engines to distribute the workload.

Lakehouse Engine Sizes Available

The ingest rate limit applies only to raw incoming data, not to fields you add or transform during processing.

Lakehouse Engine Size	Maximum Ingest per Day
Nano	75 GB
Micro	150 GB
X-Small	300 GB
Small	600 GB
Medium	1,200 GB
Large	2,400 GB
X-Large	4,800 GB
2X-Large	9,600 GB
3X-Large Contact Support	14 TB
4X-Large Contact Support	19 TB
5X-Large Contact Support	24 TB
6X-Large Contact Support	28 TB

Lakehouse Engine Compression Ratio

Cribl Search compresses ingested data at rest. The exact compression ratio depends on many factors, including the shape and content of your events, but it typically falls between 10:1 and 12:1.

Lakehouse Engine Billing

Because engine size acts as a hard limit on ingest, your costs are bounded, with no surprises from traffic spikes. You can scale your lakehouse engine up or down at any time to match your actual data needs.

With each lakehouse engine, you're charged for two things:

Component	Billing Basis	How It's Measured
Engine size	Maximum data ingest per day.	Measured at ingest, before compression, separately from any upstream Stream or Edge processing.

Component	Billing Basis	How It's Measured
Storage	Amount of data retained over time. This auto-scales with your data volume and retention periods.	Measured after compression. Estimated compression ratio is 10:1 to 12:1.

To estimate and optimize storage, set individual retention periods of your Search Datasets. See Plan Your Search Datasets for details.

To see how engine size and storage translate to costs, see Cribl Search Pricing.

See also: How Lakehouse and Federated Engines Are Billed.

Ingest Is Measured at the Engine

A lakehouse engine counts every byte it receives, regardless of any processing that happened upstream. The engine has no visibility into what your data looked like before it arrived.

This matters most when you process data in Cribl Stream or Cribl Edge before sending it to a lakehouse engine. Common processing patterns can inflate the byte count that the engine sees:

- Parsing raw events into structured formats like JSON or CSV.
- Enriching events with extra fields or lookup values.
- Keeping a copy of `_raw` alongside the parsed event.

For example, if Stream receives 1 GB of raw data and reshapes it into a more verbose format, the lakehouse engine can end up ingesting 2 GB or 3 GB. Stream's upstream ingest number and the engine's ingest number reflect different things, so they don't have to match.

If you don't need Stream or Edge processing before storage, **you can send data straight to a lakehouse engine**. Cribl Search has native Sources such as Syslog, Splunk HEC, OpenTelemetry, and Raw HTTP that keep the engine's ingest count aligned with the raw data volume you expect. Search also parses incoming events through Auto-Datatyping and Custom Datatypes v2, so in many cases you're better off skipping Stream or Edge pre-processing altogether.

Lakehouse Engine Retention

You don't set retention for a lakehouse engine as a whole, but for each of its Search Datasets individually. Each Search Dataset can keep data for 1 day to 10 years, and its storage scales accordingly. After the retention period ends, Cribl Search deletes the data.


For details, see Create Search Datasets and Organize Data with Dataset Rules.

Add a New Lakehouse Engine

Search Admins and above can add lakehouse engines from the Cribl Search **Engines** tab.

Until your Workspace has a lakehouse engine, **Get Data In** prompts you to add one, or to ask an administrator if you don't have the **Admin** Permission on Cribl Search.

1. On the Cribl.Cloud top bar, select **Products** > **Search** > **Data**.
2. Select the **Engines** tab, then **Add Engine**.



Adding a lakehouse engine in Cribl Search

3. Give your lakehouse engine an **ID** (for example, `palo_alto_logs`) unique across your Workspace. You won't be able to change it later.

   The `main` ID is reserved.
4. Set the **Lakehouse Engine Size**. You can resize it later if needed.
5. Confirm with **Save**.

   Cribl Search starts provisioning the lakehouse engine, adding a default Cribl HTTP Source with the ID `in_cribl_http`.

Once the lakehouse engine status becomes **Ready**, you can:

- Send sample data to test hypothetical ingest.
- Set up your Search Datasets.
- Connect your Sources.

Send Sample Data to a Lakehouse Engine

You can send sample data to the default `in_cribl_http` Source to test hypothetical ingest before you start setting up actual Sources.

1. On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Get Data In**.
2. Under the default Cribl HTTP Source (`in_cribl_http`), select **Send Sample Data**.
3. Select the **Sample Type** (for example, **Palo Alto Traffic**). You can edit the sample payload as you like.
4. Select **Send Sample Data**.
5. Go to the **Logs** page and run a search to see how the sample data was ingested.

   If you don't have any Search Datasets yet, you can run a query like:

```
dataset="main" | limit 10
```

Copy

To verify real data ingest, use Live Data. For complete verification, query the target Search Dataset directly.

Check Lakehouse Engine Status

You can check the status of a lakehouse engine in the Cribl Search **Engines** tab.

1. From the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Engines**.
2. Check the **Status** column.

Status	Meaning
Provisioning	Setting up the engine.
Delayed	Setup is taking longer than expected.
Failed	Engine hit an error and can't recover.
Ready	Engine is fully operational.
Blocked	Engine is down and trying to recover.
Resizing	Engine size is being changed.
Terminated	Engine is being deleted.

Resize a Lakehouse Engine

Search Admins and above can resize lakehouse engines from the Cribl Search **Engines** tab.

1. On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Engines**.
2. Select the lakehouse engine you want to resize.
3. Set the new **lakehouse engine Size**. See Lakehouse Engine Sizes.
4. Confirm with **Save**.

Wait until the lakehouse engine status changes from **Resizing** to **Ready** again.

Delete a Lakehouse Engine

Search Admins and above can delete lakehouse engines from the Cribl Search **Engines** tab. This is irreversible.

When you delete a lakehouse engine, here's what happens to its Search Datasets:

- All Search Datasets on the engine are removed, along with the data they contain.
- If the engine hosts the `main` Dataset, `main` moves to another lakehouse engine that you pick, but **wipes all its data**. You keep `main`'s ID, retention, and schema, but start ingesting data from scratch.

To delete a lakehouse engine:

1. On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Engines**.
2. Select the lakehouse engine you want to delete.
3. Select **Delete Engine**.
4. If the engine hosts the `main` Dataset, select another lakehouse engine in **Move Dataset to**, then select **Next**. If you don't have another lakehouse engine, add one first.
5. Type `DELETE` to confirm, then select **Delete Engine** again.

Next Steps

Now that your lakehouse engine is ready, create Search Datasets to organize your data and set retention.

Cost to Resources

2.2. Create Search Datasets In Cribl Search

Add Search Datasets within your lakehouse engine, so you can group ingested events and control retention.

Highlights

- Search Datasets group events ingested into Cribl Search, while federated Datasets point to external storage.
- You control Search Dataset assignment with Dataset rules.
- Each Search Dataset has its own retention period of 1 day to 10 years.


Datasets: Search vs. Federated

A Dataset in Cribl Search is a named container that groups related events.

Search Datasets organize events within Cribl-hosted lakehouse engines, following Dataset rules. They can hold together data from multiple Sources and of different Datatypes. They're optimized for fast, schema-aware search and AI workflows.

Federated Datasets reference your own storage, such as S3 or Azure Blob. Queries use your federated engine capacity to run searches "in place", with no ingestion or indexing needed. For more on these, see Connect Cribl Search to External Data.

	Search Datasets	Federated Datasets
Best for	Fast search and AI workflows	Search-in-place without indexing
Hosted with	Cribl Search	Your external storage
Powered by	Lakehouse engines	Federated engine



Datasets: Search vs. federated

Plan Your Search Datasets

Each Search Dataset auto-scales with:

- Amount of ingested data you route to the Dataset using Dataset rules.
- Retention period you set for the Dataset (1 day to 10 years, default: 1 year).

Adjust retention periods as your needs change. When retention ends, data is dropped.

Plan your Search Datasets ahead to estimate future storage costs. Exact strategy depends on your use case, but here's general guidance.

Group events by domain

Route firewall logs to one Dataset, auth logs to another, and so on. This lets you set different retention periods per category, and scope searches precisely.

Set retention to match your investigation window

This way, you can keep the right events close, and store long-term audit or archive data in Cribl Lake or other object storage for federated search.

Treat `main` as a fallback

The catch-all `main` Dataset prevents data from being silently lost. Treat it as a fallback mechanism, not target storage.

Estimate storage

Storage in a lakehouse engine is the amount of data retained in all of its Search Datasets over time, measured after compression. Estimated compression ratio is between 10:1 and 12:1.

The formula below calculates estimated storage for a single Search Dataset, assuming a compression ratio of 10:1. To see how storage translates to cost, see Cribl Search Pricing.

```
(Daily volume of data routed to the Dataset / 10) × Days of retention = Estimated stc
```

Copy

Set Up Your Search Datasets

To organize ingested data into Search Datasets:

1. Add Datasets: Create your Search Datasets and set their retention periods, along with performance-enhancing accelerated fields.
2. Add Dataset rules: Define how to route events into your Search Datasets.
3. Verify Dataset assignment: Check if your events are routed and retained as expected.


Add Search Datasets

Create Search Datasets that you'll later target with Dataset rules.

1. On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datasets** > **Add Dataset**.
2. Under **New Dataset**, configure the following:

Setting	Description	Example
ID	Dataset ID, unique across your Cribl.Cloud Workspace. Use letters (`A-Z`, `a-z`), numbers (`0-9`), hyphens, and underscores. Max 512 characters.	`my_dataset`
Description	Describe your Dataset so others know what it's for.	`Contains security logs`
Tags	When you have lots of Datasets, tags will help you organize them.	`security`, `logs`

3. Select the Dataset type: **Search Dataset**.



Add a new Search Dataset

If you're not seeing the **Search Dataset** option, wait till your first lakehouse engine is in **Ready** status.

4. Under **Search Dataset**, configure the following:


Setting	Description	Example
Retention period	Choose how long to keep the data, from 1 day to 10 years. (See Plan Your Search Datasets.)	`1 year` (default)
Engine	Select a lakehouse engine that will store the Dataset.	`palo_alto_logs`
Earliest expected timestamp	Relative time expression for the earliest accepted event timestamp. Leave it empty for no lower bound. Events with timestamps before this boundary have their `_time` reset to `now()` and the original value preserved in `_original_time`. See Configure Expected Time Range.	Empty (default)
Latest expected timestamp	Relative time expression for the latest accepted event timestamp, up to a maximum of `7d`. Events with timestamps	`1d` (default)

Setting	Description	Example
	after this boundary have their `_time` reset to `now()` and the original value preserved in `_original_time`. See Configure Expected Time Range.	

5. To improve search performance and speed up search results, you can add accelerated fields to your Search Dataset.

   Select **Performance** > **Add Field**, and enter the fields you search often.

   We recommend no more than 15 fields. Accelerated fields come with additional ingest and index costs, so use them intentionally.



Add accelerated fields on a Search Dataset

6. To generate an AI-powered reference file for your Search Dataset by analyzing its contents, select **Dataset Intelligence** > **Enable Dataset Intelligence**. For details, see Dataset Intelligence.
7. Confirm with **Save**.

Now you'll be able to target the new Dataset with Dataset rules.

Configure Expected Time Range

Each Search Dataset applies an expected time window to event timestamps at ingest. When the `_time` field of an incoming event falls outside the configured window, Cribl Search resets `_time` to `now()` and preserves the original value in `_original_time`. This prevents ingest failures from widely distributed event timestamps.

The expected time range settings appear on the **Datasets** tab when you add or edit a Search Dataset. They apply to every Search Dataset, including the `main` Dataset, and changes take effect immediately.

New Search Datasets start with **Earliest expected timestamp** empty and **Latest expected timestamp** set to `1d`. There is no limit on how far back the earliest boundary can reach, but Cribl Search caps the latest boundary at `7d` - future timestamps spread across many days create excess partitions in your lakehouse engine, which can fail ingest.

Relative Time Syntax

The **Earliest expected timestamp** and **Latest expected timestamp** fields accept a signed relative time expression. Supported time units are:

- `d`: Days. For example, `-30d` is 30 days before now, and `1d` is one day after now.
- `weeks`: Weeks. For example, `-420weeks` is 420 weeks before now.
- `mon`: Months. For example, `-1mon` is one month before now.
- `y`: Years. For example, `-1y` is one year before now.

Use a negative value to set a boundary in the past, and a positive value to set a boundary in the future.

Earliest expected timestamp is optional. Leave it empty, and Cribl Search accepts event timestamps of any age. **Latest expected timestamp** is required, and can't resolve to more than seven days in the future, so `7d` is the highest value you can set.

Out-of-Range Timestamp Handling

When an event arrives with a `_time` value outside the configured window:

- `_time` is reset to `now()` at the time of ingest.
- The original timestamp is preserved in a new field called `_original_time`.

The event is still written to the Dataset. Only the timestamp is corrected.

When **Earliest expected timestamp** is empty, only the latest boundary triggers this correction.

Validation

Cribl Search validates the expected time range when you save a Dataset.

State	Message	What to Do
Error	Latest cannot exceed the maximum allowed value of 7d.	The latest boundary resolves to more than seven days in the future. Set it to `7d` or less, for example `1d`.
Error	Earliest must resolve to a time before latest.	The earliest boundary resolves to a time equal to or later than the latest boundary. Correct the values

State	Message	What to Do
		before saving. Cribl Search runs this check only when you set an earliest boundary.
Warning	The configured time range spans {N} days (the recommended maximum is 40 days) and may cause errors on ingest.	The configured window exceeds 40 days and might cause ingest failures. Narrow the range if possible. Cribl Search shows this warning only when you set both boundaries.

The same limits apply when you create or update a Search Dataset outside the UI. A latest boundary above `7d` fails with `expectedRelativeTimeRange is invalid: latest ('14d') exceeds the maximum allowed value of 7d`, and a value that isn't a valid relative time expression fails with `expectedRelativeTimeRange contains an invalid time expression`.

Existing Datasets

Existing Search Datasets, including `main`, keep the expected time range you saved them with. Cribl Search doesn't apply the current defaults to them. Two cases need your attention:

- A Dataset with a latest boundary greater than `7d` keeps clamping at that boundary until you edit the Dataset. The next time you save it, lower the boundary to `7d` or less, otherwise validation fails.
- A Dataset created before the expected time range settings existed has no stored boundaries, so Cribl Search applies no lower bound and clamps at `1d`.

Review your Dataset configurations if you rely on events with future-dated timestamps. Set an earliest boundary only when you want Cribl Search to correct the timestamps of very old events.

The `main` Dataset

When you add your first lakehouse engine, Cribl Search creates a catch-all `main` Dataset for unrouted events:

Events Sent to `main`	Value Set for `_dataset_reason` Field
Events that match no Dataset rule.	`no_rules_matched`
Events that match a rule pointing to a deleted or invalid Dataset (**Orphaned** data).	`invalid_dataset_matched (<datasetId>)`
Events that arrive with a `dataset` field already set, pointing to an invalid Dataset.	`invalid_dataset_provided`

If your events land in `main` unexpectedly, fix your Dataset rules to send them to the correct Search Dataset instead.

You can change the retention period of your `main` Dataset, but you can't delete it. If you delete a lakehouse engine hosting `main`, you'll need to pick another lakehouse engine to take over.

The `metrics` Dataset

> **Preview Feature**
>
> Cribl is still developing this Preview feature. We don't recommend using it in a production environment, because the feature might not be fully tested or optimized for performance, and related documentation could be incomplete.
>
> Please continue to submit feedback through normal Cribl support channels, but assistance might be limited while the feature remains in Preview.

Alongside `main`, Cribl Search auto-provisions a metrics Dataset for each lakehouse engine. Every Source that ingests metrics writes into one of these Datasets, whichever one your Metric Rules select.

- The first engine's Dataset is named `metrics`. Each additional engine gets a Dataset named `metrics_<engine_id>`.
- The Dataset is built-in, so you can't delete or rename it.
- Its provider and type are `cribl_search` and `metrics`.
- The default retention is 365 days. You can change the retention in the Dataset configuration.

To review or configure the Dataset, on the Cribl.Cloud top bar select **Products** > **Search** > **Data** > **Datasets**, then select the metrics Dataset.

Send Results to a Search Dataset

Use the `export` operator with the `search` keyword to send search results into an existing Search Dataset.

This is useful when you want to materialize the output of a federated search or enrichment pipeline only once, and then run fast, repeated searches against the cached results instead of re-scanning the original Datasets.

```
dataset="cribl_search_sample"
| export to search mySearchDataset
```

Copy

The target must be a Search Dataset, not a federated Dataset, and its lakehouse engine must be in **Ready** status. Only Admin and Editor Search Members can run the `export` operator.

For full syntax, arguments, and limitations, see the `export` operator reference.

Clear a Search Dataset

You can wipe data stored in a Cribl-hosted Search Dataset while preserving your Dataset rules and retention settings. This requires Maintainer access on the Dataset, and can't be undone.

1. On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datasets**.
2. Select the Search Dataset you want to clear.
3. Select **Clear Dataset**.
4. Type `CLEAR`, and confirm with **Clear Dataset**.

2.3. Dataset Intelligence

Dataset Intelligence generates an AI-powered reference file for a Dataset by analyzing its contents, field structure, and event patterns. Once generated, the file is used automatically by Cribl Search investigations to improve Dataset selection and query accuracy during the data source identification phase.

Before You Begin

- AI must be configured correctly in your organization.
- You must have read access to the Dataset. Dataset Intelligence is only available for Datasets you can access.



If your Organization uses a Custom AI Provider (BYOM), Dataset Intelligence routes reference file generation through your configured provider.

Enable Dataset Intelligence

You can enable Dataset Intelligence from three places. All three produce the same result.

From the Dataset modal:

1. Open the Dataset you want to analyze.
2. Select the **Dataset Intelligence** tab.
3. Select **Enable Dataset Intelligence**.

From the Datasets list:

1. On the **Logs** page or the **Datasets** page, select the actions menu (three dots) next to a Dataset.
2. Select **Enable Dataset Intelligence**.

When favoriting a Dataset:

1. Select the star icon to favorite a Dataset.
2. In the prompt that appears, select **Enable Dataset Intelligence**.

After enabling, a notification confirms that Dataset Intelligence is running. Select **Dataset Details** in the notification to open the Dataset modal and monitor progress.



For Datasets you can edit, select **Save** after clicking **Enable Dataset Intelligence** to commit the change.

> The generation starts after you save.

Monitor Generation

After enabling, Cribl Search runs the Dataset Intelligence agent asynchronously against the Dataset. This typically takes 2-3 minutes.

The **Dataset Intelligence** tab shows a spinner with the message "Generating Dataset Intelligence" while the agent runs. The tab refreshes automatically every 5 seconds until generation completes or fails (up to a maximum of 5 minutes).

When complete, the tab displays the generated reference file in a read-only Markdown editor.

What the Reference File Contains

The generated file is a structured markdown document with the following sections:

- **Overview**: A narrative description of the Dataset's contents, data types, and any heterogeneous structure worth noting.
- **Record families**: One entry per distinct log or event type, each with a ready-made KQL filter scoped to that Source and the fields found in sampled events.
- **KQL field rules**: Dataset-specific field access rules, such as fields that require bracket-quoting, fields that are numeric rather than string, and nested object access patterns.
- **Semantic field mappings**: How fields map to common concepts such as user, action, status, and timestamp across the different record families.

This file is used automatically by investigation agents via the `get_dataset_context` tool. You do not need to reference it manually.

Disable Dataset Intelligence

To remove the reference file from a Dataset:

1. Open the Dataset modal.
2. Select the **Dataset Intelligence** tab.
3. Select **Disable Dataset Intelligence**.

For editable Datasets, select **Save** to apply the change. For read-only or default Datasets, the file is removed immediately.

Disabling Dataset Intelligence does not affect the Dataset itself or any investigations already in progress.

Related

- Run Investigations (Preview)
- Create Search Datasets

2.4. Shape Data With Datatype Rules

Parse and structure data being ingested into Cribl Search, so you can search it fast from the start.


Highlights

- Try Auto-Datatyping first, then handle uncategorized events with your own Datatype rules.
- Point your rules at stock v2 Datatypes, or define custom Datatypes.
- For detailed info on how Datatyping works (with or without lakehouse engines), see Datatypes in Cribl Search.

Datatyping in Lakehouse Engines


When your data flows from Sources into a lakehouse engine, it's parsed into structured events through a process called **Datatyping**. Here's how you can use it to shape your data:

1. **Use Auto-Datatyping**: Let Cribl Search assign Datatypes automatically.
2. **Check for uncategorized data**: See if any events were missed.
3. **Define your own Datatype rules**: To handle the uncategorized data, map specific patterns to the existing stock Datatypes.
4. **Add custom Datatypes**: To parse data not covered by the stock Datatypes, edit or add entirely new Datatypes.



Datatyping flow in Cribl Search lakehouse engines

To manage Datatyping in lakehouse engines: from the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Get Data In** > **2. Datatyping (auto)**.



Datatyping in lakehouse engines

1. Parse Automatically (Auto-Datatyping)

By default, Cribl Search automatically analyzes incoming events and assigns a matching Datatype. This requires no configuration on your part, and covers many common log types and data formats.

For most types of data, Auto-Datatyping just works.

2. Check for Uncategorized Data

Data that doesn't match any Datatypes displays as **Uncategorized**.

1. On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Get Data In** > **Datatyping**.
2. Under **Uncategorized Data**, select:
    - **View Live Data** to see a sample of uncategorized data as it arrives. See Live Data for details.
    - **View Last 24h** to run a search for uncategorized data from the past 24 hours.

3. Add Datatype Rules

To handle data uncategorized by Auto-Datatyping, define your own rules that map specific data patterns to stock v2 Datatypes or custom v2 Datatypes.

1. On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Get Data In** > **Datatyping**.
2. Select **Add Datatype Rule**. Name and describe your rule.
3. In **Kusto expression to match**, enter a KQL expression that matches a subset of the uncategorized data.

For details, see Datatype Rule Expressions.

4. From **Datatype**, select the Datatype to assign. You can choose from stock v2 Datatypes and your custom v2 Datatypes.
5. Make sure that **Enabled** in the top right corner is checked, and confirm with **Add**.

If you add more rules, drag them to change the order. Rules run top-down, and the first match wins. Put more specific rules above broader ones.

Datatype Rule Expressions

Point your Datatype KQL expressions at the fields that are guaranteed to exist before Datatype assignment:

Field	Description
`_raw`	Raw event text before Datatyping.
`__inputId`	Source identifier in `type:id` format. Supported types: `cribl_http`, `datadog_agent`, `elastic`, `http_raw`, `open_telemetry`, `prometheus_rw`, `splunk`, `splunk_hec`, `syslog`, `tcp`, `tcpjson`, `wef`, `wiz_webhook`. Example: `syslog:my_source_id`.

You can copy `__inputId` or other fields from the arriving events. To see them, select **Live Data** on the **Datatyping** page.

You can:

- Create KQL expressions that evaluate to `true`/`false` for matching events.
- Set case-insensitive conditions using `=` and wildcards (`*`).
- Pipe into `| where …`, `| find …`, or `| search …` for richer logic.

But:

- You can't use expressions that aggregate or reshape data (such as `stats` or `project`).
- You can't use `let` or `set` statements.

See the examples below for typical use cases. For full reference on the Cribl Search implementation of KQL, see Language Reference.

Text in _raw | One Source | Text + Source | Source Family | Chained Filters

```
_raw = "*failed login*"
```

Copy

Matches events that contain `failed login` (case-insensitive) anywhere in their raw text:

```
# Event 1
Mar 19 12:01:44 auth0 sshd[2041]: failed login for user admin from 10.0.0.5

# Event 2
2026-03-19T08:15:00Z WARN Failed Login attempt on account jdoe
```

Copy

Combine these patterns to catch multiple log formats with a single rule:

HTTP 5xx Errors | Memory Exhaustion

```
_raw = "*HTTP*" | search (" 500 " or " 502 " or " 503 " or " 504 ") and not "/heal
```

Copy

Matches HTTP 5xx server errors across Apache, Nginx, and AWS Application Load Balancer access logs with a single rule. The `and not "/healthcheck"` clause filters out healthcheck endpoints that legitimately produce 5xx noise:

```
# Event 1 (Apache)
10.0.0.42 - alice [15/Apr/2026:09:14:23 +0000] "GET /api/users HTTP/1.1" 502 1247

# Event 2 (Nginx)
198.51.100.5 - - [15/Apr/2026:09:14:25 +0000] "POST /checkout HTTP/2.0" 503 891 "-

# Event 3 (AWS ALB)
h2 2026-04-15T09:14:27.341Z app/prod-alb/abc123 10.0.1.55:48292 - 0.001 0.142 0.00
```

Copy

---

4. Add Custom Datatypes

To handle uncategorized data that's not covered by the stock v2 Datatypes:

1. Add a custom v2 Datatype.
2. Create a Datatype rule that points at your custom Datatype.

Fix Timezone Offsets

Cribl Search parses each event and interprets its timestamp. If the event includes timezone information, Cribl Search uses it. Otherwise, it assumes UTC.

You can deal with timezone offsets at different stages:

- **Before ingestion**: Set the `_time` override field before the event reaches Cribl Search. When Search finds a `_time` field on an incoming event, it uses that value and skips its own timestamp parsing.
- **At Datatyping**: Add a custom v2 Datatype in Cribl Search to fix the offset through your own timestamp extraction settings.
- **At Dataset assignment**: Use the **Modify fields** setting in your Dataset rules. This lets you adjust timestamps per Dataset while preserving the upstream Auto-Datatyping flow. For details, see Modify Fields in Dataset Rules.

Override Cribl Search Processing

To bypass Cribl Search timestamping, Datatyping, or Dataset rules, add **override fields** to your events before they reach Cribl Search. You can add these in Cribl Stream, or in any upstream sender.

Field	What Cribl Search Does
`_time`	Skips timestamp parsing and uses this value (in UTC) as the event time.
`datatype`	Skips Datatype rules and applies the specified stock or custom v2 Datatype. If the Datatype doesn't exist, falls back to Auto-Datatyping.
`isParsed` (use with `datatype`)	Uses the fields already on the event instead of reparsing `_raw`. Always pair with `datatype`. Without it, events fall back to Auto-Datatyping. Use when data is fully shaped upstream.
`dataset`	Skips Dataset rules and routes directly to the specified Dataset. If the Dataset doesn't exist, routes to `main` with `_dataset_reason = "does not exist"`.

For pre-parsed events from Cribl Stream or Cribl Edge, set both `datatype` and `isParsed`. If you also route by Dataset upstream, set `dataset`, too. See Ingest Cribl Stream/Edge Data into Cribl Search.

Next Steps

Now that you've shaped your data, organize it into Datasets.

2.5. Organize Data With Dataset Rules


Once you've created your Search Datasets, set Dataset rules to control which events land in which Dataset.

Highlights

- Each Dataset rule routes matching events to a specified Search Dataset.
- Each Search Dataset has its own retention period of 1 day to 10 years.
- Verify Dataset assignment to make sure events land where you expect.


Dataset Rules Overview

Each Dataset rule captures events that match a KQL expression, and then sends those events to the specified Search Dataset.



Dataset rules overview

To manage your Dataset rules: from the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Get Data In** > **3. Dataset Rules**.



Dataset rules in lakehouse engines

Add Dataset Rules

To add a new Dataset rule:

1. On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Get Data In** > **3. Dataset Rules**.
2. Select **Add Dataset Rule**. Name and describe your rule.
3. In **Kusto expression to match**, enter a KQL expression that matches events you want to route.

   See Dataset Rule Expressions for syntax and examples.
4. In **Send data to**, choose your target Search Dataset. This is where events matching the KQL expression will land.

   You can also select **Drop** to instead discard the events.
5. In **Modify fields**, you can perform Dataset-specific enrichment or normalization. See Modify Fields in Search Datasets.
6. Make sure that **Enabled** in the top right corner is checked, and confirm with **Add**.

If you add more rules, drag them to change the order. Rules run top-down, and the first match wins. Put more specific rules above broader ones.

Events that don't match any rule, or match a rule pointing to a deleted Dataset, fall back to the `main` Dataset.

Dataset Rule Expressions

Point your Dataset KQL expressions at these fields:

Field	Description
`datatype`	Datatype assigned through Datatyping.
`__inputId`	Source identifier in `type:id` format. Supported types: `cribl_http`, `datadog_agent`, `elastic`, `http_raw`, `open_telemetry`, `prometheus_rw`, `splunk`, `splunk_hec`, `syslog`, `tcp`, `tcpjson`, `wef`, `wiz_webhook`. Example: `syslog:my_source_id`.



You can copy `__inputId` or other fields from the arriving events. To see them, select **Live Data** to sample incoming events.

You can also filter by any other field in your parsed data.

Same as with Datatype rule expressions, you can:

- Create KQL expressions that evaluate to `true`/`false` for matching events.
- Set case-insensitive conditions using `=` and wildcards (`*`).
- Pipe into `| where …`, `| find …`, or `| search …` for richer logic.

But:

- You can't use expressions that aggregate or reshape data (such as `stats` or `project`).
- You can't use `let` or `set` statements.

See the examples below. For full reference on the Cribl Search implementation of KQL, see Language Reference.

Datatype | **Datatype + Source** | **Datatype + Field** | **Source** | **Drop Events**

Matches all events of Datatype `apache_httpd_accesslog_common`:

```
datatype = "apache_httpd_accesslog_common"
```

Copy

Verify Dataset Assignment

Check on your Search Datasets to make sure your events are routed and retained as expected.

1. Go to **Logs**: On the Cribl.Cloud top bar, select **Products** > **Search**.
2. Under **Available Datasets**, select a Search Dataset you want to inspect.

   Search Datasets are marked with the lakehouse icon .
3. In the resulting details panel, look at the **Fields** section.

   If the **Fields** section is empty, select **Retry** to load the metadata.

   If there's no **Fields** section at all, you're looking at a federated Dataset. Select a Search Dataset instead.
4. Verify that the Dataset contains the fields you'd expect from your Datatyping configuration and Dataset rules.
   For more information, see Explore Fields in Search Datasets.

For more ways to explore your Datasets, see Inspect Your Datasets.

Modify Fields in Dataset Rules

You can enrich or normalize events on their way into a specific Search Dataset, without affecting your upstream Datatyping rules. Use this to normalize timestamps, convert units, or reshape values, while preserving the Auto-Datatyping flow.

1. On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Get Data In** > **3. Dataset Rules**.
2. Select **Add Dataset Rule** (or edit an existing one). For details, see Add Dataset Rules.
3. Select **Modify fields**.
4. In the text box, write a KQL `extend` expression to add or overwrite fields on matched events.

See the examples below. For full reference on the Cribl Search implementation of KQL, see Language Reference.

Normalize Timestamps | Convert Units | Map Values

Offset `_time` based on the `host` field so that events from different regions align to the same timezone:

```
_time = case(host startswith "eastcoast", _time + 3h, host startswith "westcoast",
```

Copy

Override Dataset Rules

To bypass Dataset rules, add a `dataset` field to your events before they reach Cribl Search. You can add this and other override fields in Cribl Stream, or in any upstream sender.

Field	What Cribl Search Does
`dataset`	Skips Dataset rules and routes directly to the specified Dataset. If the Dataset doesn't exist, routes to `main` with `_dataset_reason = "does not exist"`.

Route Metrics with Metric Rules



Preview Feature

Cribl is still developing this Preview feature. We don't recommend using it in a production environment, because the feature might not be fully tested or optimized for performance, and related documentation could be incomplete.

Please continue to submit feedback through normal Cribl support channels, but assistance might be limited while the feature remains in Preview.

Metric Rules route incoming metrics to a metrics Dataset, the way Dataset rules route events to a Search Dataset. They have their own tab: on the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Dataset Rules**, then select the **Metric Rules** tab.

By default, a single **Metrics catch-all** rule (`*`) sends all metrics to the primary `metrics` Dataset. To send a Source to a different engine's Dataset, add a rule that matches that Source and routes it to the target Dataset:

- Metric Rules match on the internal `__inputId` field, which has the form `<sourceType>:<sourceId>` - for example, `prometheus_rw:in_prometheus_rw` for a Prometheus Remote Write Source, `open_telemetry:otel_prod` for an OpenTelemetry Source that stores metrics, or `cribl_http:in_cribl_http` for a Cribl HTTP Source that receives native metrics from Cribl Stream or Cribl Edge.
- Rules match top-down and the first match wins, so place more specific rules above the catch-all.



Metric Rules apply to data as it arrives and aren't retroactive. Set up your engine, Source, and rule before you start sending data. Metrics that arrive before a matching rule exists fall through to the catch-all and stay in the primary `metrics` Dataset.

2.6. View Live Data In Cribl Search

Get a real-time sample of events flowing into your lakehouse engine to verify that they parse and route as expected.

Highlights

- Capture a live sample of events at any ingestion stage: at the Source, after Datatyping, or after Dataset routing.
- Filter by Source, Datatype, Dataset, or event type to focus on specific data.
- Identify uncategorized events missing a Datatype, and orphaned events with no valid Dataset.

Verify Events Flowing Into Your Lakehouse Engine

When data flows from a Source into a lakehouse engine, Live Data shows you a real-time sample of what's actually arriving.


You can inspect events at different stages of the ingestion pipeline, filter by specific objects or event types, and quickly spot ingest and parsing issues before they reach your Datasets.

Keep in mind that Live Data is a preview for troubleshooting and debugging, and may not show every event in the monitored period. For the ultimate source of truth, query the Dataset directly.

To quickly test ingest before you set up Sources, send sample data.

See Live Data

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Live Data**. Cribl Search captures a sample of events and displays them in the event viewer on the right.



Capturing a sample of incoming events in Cribl Search

To narrow down the sample to the events you care about:

1. In **Live Data**, set the Capture Filters.
2. Select **Capture** to start sampling incoming events.

   Cribl Search stops capturing automatically when it reaches the **Maximum events to capture** limit or the **Capture time** expires. Select **Stop Capture** to end the capture early.
3. Review the captured events in the event viewer on the right.

   Select **Capture** again to refresh the results with the latest events.

Live Data Capture Filters

The following **Capture Filters** let you narrow down the sample to a specific set of events:

Objects | Capture Level | Size and Duration | Types

Filter events by Source, Datatypes, or Datasets.

Filter	Description
Source	Show only events from a specific Cribl Search Source.

Filter	Description
Datatypes	Show only events of specific Datatypes.
Datasets	Show only events routed to specific Datasets.

Find Events With No Datatype (Uncategorized)

Events that don't match any Datatype rule and aren't recognized by Auto-Datatyping appear as **Uncategorized**. Filter for them in the Live Data sample to find gaps in your Datatyping configuration.

1. On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Live Data**.
2. In **Capture Filters**, expand **Types** and select **Uncategorized**.
3. Set other filters to focus on the events you want to see.
4. Select **Capture**.
5. Review the captured events. Examine the raw event structure to determine which Datatype rules to add or adjust.

Find Events With No Dataset (Orphaned)

Events that match a Dataset rule pointing to a deleted or invalid Dataset appear as **Orphaned**. Filter for them in the Live Data sample to identify which Dataset rules need fixing.

1. On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Live Data**.
2. In **Capture Filters**, expand **Types** and select **Orphaned**.
3. Set other filters to focus on the events you want to see.
4. Select **Capture**.
5. Review the captured events. Check which Source or Datatype they come from, then update your Dataset rules to route those events to a valid Dataset.

Next Steps

2.7. Cribl Search Sources

Set up your Source with step-by-step instructions.

Cribl HTTP

Collect events sent from other Cribl components, from Cribl on-prem or Cribl.Cloud tenants.

Datadog Agent

Collect metrics, traces, and logs sent by the Datadog Agent using the Datadog API protocol.

Elasticsearch API

Collect data sent using the Elasticsearch bulk API, including from Beats and the Elastic Agent.

OpenTelemetry

Collect metrics, traces, and logs from any OTEL-compliant agent.

Prometheus Remote Write

Collect metrics sent using the Prometheus Remote Write API protocol.

Raw HTTP

Collect raw HTTP requests without any parsing or formatting, useful for custom protocols or debugging.

Splunk HEC

Collect data sent using the HTTP(S) protocols, including from the Splunk Universal Forwarder.

Splunk TCP

Collect data sent by Splunk Forwarders, including the Splunk Universal Forwarder.

Syslog

Collect data from syslog agents in the syslog format via TCP or UDP.

TCP

Collect data sent over TCP connections in any format.

TCP JSON

Collect JSON-formatted events sent over TCP connections, with automatic JSON parsing.

Windows Event Forwarder

Collect data from Windows Event Forwarder (WEF) servers over TCP.

Wiz Webhook

Collect security events and alerts sent by Wiz via webhook notifications.

2.7.1. Ingest Cribl Stream/Edge Data Into Cribl Search

Collect data from your on-prem or Cribl.Cloud tenants to store it in Cribl Search for fast analysis.

Before You Begin

You'll need:

- Search Editor Permission, or higher. Learn who can do what at Cribl Search Permissions.
- Cribl Stream or Cribl Edge (on-prem or Cribl.Cloud).
- Cribl.Cloud Enterprise on both sides (Cribl Stream/Edge and Cribl Search). For details, see Pricing.



If you don't need Cribl Stream or Edge processing, **you can send data directly to a lakehouse engine**, using native Cribl Search Sources such as Syslog, Splunk HEC, OpenTelemetry, or Raw HTTP. Search also parses incoming events through Auto-Datatyping and Custom Datatypes v2, so in many cases you're better off skipping Stream or Edge pre-processing altogether. For why this matters, see Ingest Is Measured at the Engine.

Looking for the Cribl HTTP Source in **Cribl Stream** instead?

1. Add a Lakehouse Engine


See Lakehouse Engines in Cribl Search.

2. Set Up Your Search Datasets

Create the Search Datasets you'll route events into, and set their retention. See Create Search Datasets.

3. Add a Cribl HTTP Source in Cribl Search

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Get Data In** > **Add Source** > **Cribl HTTP**.



Adding Sources in Cribl Search

Describe Your Source

Under **General**, configure:

Setting	Description	Example
ID	Source ID, unique across your Cribl.Cloud Workspace. Use letters, numbers, underscores, hyphens.	`cribl_stream_prod`
Description	Describe your Source so others know what it's for.	`Ingests data from Cribl Stream`
Address	Hostname (FQDN) that Cribl Stream/Edge connects to (**Cribl endpoint**).	`search.main.foo-bar-abc123.cribl.cloud`
Port	Network port to listen on. Keep the default unless it conflicts with another service.	`10200` (default)

Setting	Description	Example
Store this source data as	Select **Logs** (the default), **Metrics**, or **Both Logs and Metrics**. To ingest native metrics from the Cribl Search Destination, select **Metrics** or **Both Logs and Metrics**.	`Both Logs and Metrics`

Set up Authentication (Optional)

For cross-environment or cross-Workspace paths (for example, on-prem Cribl Stream to Cribl Search), you'll need to set up authentication tokens.

Under **Authentication**, select **Add Token**. Add as many tokens as you need.

Setting	Description	Example
Token secret (text secret)	Reference to a stored secret containing the token. Select a secret or **Create** a new one. (See Create and Manage Secrets in Cribl Stream).	`sec_cribl_stream_token`
Description	Describe which clients or environments use the token.	`Prod Cribl Stream`

Set Up Encryption

TLS encryption protects your data in transit. New Sources have TLS enabled by default, with TLS 1.2 as the minimum version.



TLS settings must match on both sides. Make sure TLS is also enabled on your Cribl Search Destination in Cribl Stream or Cribl Edge.

Under **Encrypt**, you can review or adjust the **Minimum TLS version** you want to accept:

TLS Version	When to Use
1.3	Provides the strongest security. Use when your clients support it.
1.2	The default. Use for broad client compatibility.
Older than 1.2	Avoid if possible. These versions are no longer considered secure.

Select **Save** to create the Source.

4. Assign Datatypes in Cribl Stream

When data comes from Cribl Stream or Cribl Edge, you can skip Datatyping in Cribl Search, and **assign Datatypes upstream**. Set the `datatype` override field to a stock or custom v2 Datatype.

If events are already fully parsed upstream (fields are on the event and you don't want Search to parse `_raw` again), set the `isParsed` override field. Remember to set `datatype` too, otherwise Auto-Datatyping kicks in.

To set both fields automatically, enable automatic parsing in a supported Source, Route, or Parser Function upstream from your Cribl Search Destination.

You can also set these fields manually with an Eval function in the same Pipeline.

If you'd rather configure Datatyping in Cribl Search instead, see Shape Your Data with Datatype Rules.

5. Route Events to Search Datasets

After you create your Search Datasets, assign each event to a Dataset upstream by setting the `dataset` override field in Cribl Stream or Cribl Edge. Search uses that value directly and skips Dataset rules.

1. In Cribl Search, add your Search Datasets and set their retention periods.
2. In Cribl Stream or Cribl Edge, set the `dataset` field on each event to the ID of the target Search Dataset. Use an Eval function in the Pipeline that feeds your Cribl Search Destination.

Events with no `dataset` field, or with a `dataset` field pointing to a Dataset that doesn't exist, fall back to the `main` Dataset.

If you'd rather route events with Dataset rules in Cribl Search, see Organize Your Data with Dataset Rules.

Route Metrics with Metric Rules

If this Source stores metrics, Metric Rules decide which metrics Dataset receives them. By default, a single catch-all rule sends all metrics to the primary `metrics` Dataset. A rule for this Source matches `cribl_http:<your-source-id>` - for example, `cribl_http:in_cribl_http` for the built-in Source.

Metric Rules apply to data as it arrives and aren't retroactive, so add your rule before you start sending data. For details, see Route Metrics with Metric Rules.

6. Add a Cribl Search Destination in Cribl Stream or Cribl Edge

For Cribl Stream, see Cribl Search Destination in the Stream docs.

For Cribl Edge, see Cribl Search Destination in the Edge docs.

7. Start Sending Data and Verify

Start sending events from Cribl Stream or Cribl Edge, and verify that they're successfully flowing into Cribl Search.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Live Data**.

Here, check for your Cribl HTTP Source. For details, see Live Data. To verify metrics, on the Cribl.Cloud top bar select **Products** > **Search** > **Metrics**. For details, see Metrics Explorer.

2.7.2. Ingest Datadog Agent Data Into Cribl Search

Collect metrics, traces, and logs via the Datadog API to store them in Cribl Search for fast analysis.

Before You Begin

You'll need:

- Cribl.Cloud Enterprise. For details, see Pricing.
- Search Editor Permission, or higher. Learn who can do what at Cribl Search Permissions.
- Datadog Agent that can send data to Cribl Search over HTTP(S).

You don't need Cribl Stream, Edge, or Lake. (Looking for the Datadog Agent Source in **Cribl Stream** instead?)

1. Add a Lakehouse Engine


See Lakehouse Engines in Cribl Search.

2. Set Up Your Search Datasets

Create the Search Datasets you'll route events into, and set their retention. See Create Search Datasets.

3. Add a Datadog Agent Source in Cribl Search

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Add Source** > **Datadog Agent**.



Adding Sources in Cribl Search

Under **General**, configure:

Setting	Description	Example
ID	Source ID, unique across your Cribl.Cloud Workspace. Use letters, numbers, underscores, hyphens.	`datadog_agent_prod`
Description	Describe your Source so others know what it's for.	`Ingests Datadog Agent data`
Address	Hostname (FQDN) that your Datadog Agent connects to. You'll need this to set up your Datadog Agent.	`search.main.foo-bar-abc123.cribl.cloud`
Port	Network port to listen on. Keep the default unless it conflicts with another service.	`20000` (default)

Set Up Encryption

TLS encryption protects your data in transit between the Datadog Agent and your Cribl Search Source. New Sources have TLS enabled by default, with TLS 1.2 as the minimum version.

Under **Encrypt**, you can review or adjust the **Minimum TLS version** you want to accept:

TLS Version	When to Use
1.3	Provides the strongest security. Use when your clients support it.
1.2	The default. Use for broad client compatibility.
Older than 1.2	Avoid if possible. These versions are no longer considered secure.

Select **Save** to create the Source.

4. Set Up Datatyping

Configure Datatype rules to parse, filter, and normalize your data into structured fields. We call this process Datatyping.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datatyping (auto)**. Here, you can:

- Use Auto-Datatyping to parse your data automatically.
- Check for uncategorized data that didn't match any Datatype rules.
- Handle the uncategorized data by adding custom Datatype rules.

See also:

- Datatypes in Cribl Search
- v2 Datatypes in Cribl Search
- List of Stock v2 Datatypes
- Add a Custom v2 Datatype

5. Set Up Dataset Rules

Configure Dataset rules to route the parsed events into your Search Datasets.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datasets: Organize Your Data**, and see Organize Data with Dataset Rules for details.

6. Set Up Your Datadog Agent

Configure the Datadog Agent to send data to Cribl Search.

You'll need these details from your Source configuration:

Name	Example
Address	`search.main.foo-bar-abc123.cribl.cloud`
Port	`20000` (default)

To find these for an existing Source: On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Sources**, and select your Source.

Example (Datadog Agent > Cribl Search)

Replace the example address (`search.main.foo-bar-abc123.cribl.cloud`) and port (if you changed the default `20000`) with your Source values.

datadog.yaml | Environment variables

```
dd_url: 'https://search.main.foo-bar-abc123.cribl.cloud:20000'
apm_config:
  apm_dd_url: 'https://search.main.foo-bar-abc123.cribl.cloud:20000'
logs_config:
  logs_dd_url: 'https://search.main.foo-bar-abc123.cribl.cloud:20000'
```

Copy

7. Start Sending Data and Verify

2.7.3. Ingest Elasticsearch Data Into Cribl Search

Collect data via the Bulk API from Beats or Elastic Agents to store it in Cribl Search for fast analysis.

Before You Begin

You'll need:

- Cribl.Cloud Enterprise. For details, see Pricing.
- Search Editor Permission, or higher. Learn who can do what at Cribl Search Permissions.
- A Beats, Elastic Agent, or other Elasticsearch bulk API sender that can reach Cribl Search over HTTP(S).

You don't need Cribl Stream, Edge, or Lake. (Looking for the Elasticsearch API Source in **Cribl Stream** instead?)



To query your Elasticsearch or OpenSearch index without moving data into Cribl Search, see Connect Cribl Search to Elasticsearch or Connect Cribl Search to OpenSearch.

1. Add a Lakehouse Engine


See Lakehouse Engines in Cribl Search.

2. Set Up Your Search Datasets

Create the Search Datasets you'll route events into, and set their retention. See Create Search Datasets.

3. Add an Elasticsearch API Source in Cribl Search

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Add Source** > **Elasticsearch API**.



Adding Sources in Cribl Search

Describe Your Source and Set the API Endpoint

Under **General**, configure:

Setting	Description	Example
ID	Source ID, unique across your Cribl.Cloud Workspace. Use letters, numbers, underscores, hyphens.	`elastic_api_prod`
Description	Describe your Source so others know what it's for.	`Ingests API from prod Beats`
Address	Hostname (FQDN) that your upstream sender connects to. You'll need this to set up your upstream sender.	`search.main.foo-bar-abc123.cribl.cloud`
Port	Network port to listen on. Keep the default unless it conflicts with another service.	`9200` (default)

Setting	Description	Example

Elasticsearch API endpoint	Base path on which to listen for Elasticsearch API requests. Defaults to `/`.
	
	Cribl Search automatically handles these sub-paths:
	`_bulk`
	`<indexName>/_bulk`
		`/myPath`
		
		Handles:
		`/myPath/_bulk`
		`/myPath/<indexName>/_bulk`

Set up Authentication

Use authentication to make sure only authorized senders can push data to your Cribl Search Source.

Under **Authentication**, select the **Authentication type** you want to use:

None | Basic | Basic (Credentials Secret) | Auth Tokens

Create a username and password. This is what your upstream sender will need to provide when sending data to your Source endpoint.

Setting	Example
Username	`elastic_user`
Password	`********`

Set Up Encryption

TLS encryption protects your data in transit between upstream senders and your Cribl Search Source. New Sources have TLS enabled by default, with TLS 1.2 as the minimum version.

Under **Encrypt**, you can review or adjust the **Minimum TLS version** you want to accept:

TLS Version	When to Use
1.3	Provides the strongest security. Use when your clients support it.
1.2	The default. Use for broad client compatibility.
Older than 1.2	Avoid if possible. These versions are no longer considered secure.

Select **Save** to create the Source.

4. Set Up Datatyping

Configure Datatype rules to parse, filter, and normalize your data into structured fields. We call this process Datatyping.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datatyping (auto)**. Here, you can:

- Use Auto-Datatyping to parse your data automatically.
- Check for uncategorized data that didn't match any Datatype rules.
- Handle the uncategorized data by adding custom Datatype rules.

See also:

- Datatypes in Cribl Search
- v2 Datatypes in Cribl Search
- List of Stock v2 Datatypes
- Add a Custom v2 Datatype

5. Set Up Dataset Rules

Configure Dataset rules to route the parsed events into your Search Datasets.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datasets: Organize Your Data**, and see Organize Data with Dataset Rules for details.

6. Set Up Your Elasticsearch Sender

Configure your upstream Beats, Elastic Agent, or other Elasticsearch bulk API sender to send data to Cribl Search.

You'll need these details from your Source configuration:

Name	Example
Address	`search.main.foo-bar-abc123.cribl.cloud`
Port	`9200` (default)

Username / **Password**
 	
Or, **Token**
	`elastic_user` / `********`
	
	`420`

Example: Beats > Cribl Search

Edit the Beats YAML configuration file, using the following example. For details, see Elastic docs.

Basic | Auth Tokens

Replace the example address (`search.main.foo-bar-abc123.cribl.cloud`), username, password, and port (if you changed the default `9200`) with your Source values.

```
output.elasticsearch:
  hosts: ['https://search.main.foo-bar-abc123.cribl.cloud:9200']
  username: 'your_username'
  password: '********'
```

Copy

7. Start Sending Data and Verify

Start sending events from your upstream Elasticsearch sender, and verify that they're successfully flowing into Cribl Search.

2.7.4. Ingest OpenTelemetry Data Into Cribl Search

Collect metrics, traces, and logs from OTLP-compliant agents to store them in Cribl Search for fast analysis.

Before You Begin

You'll need:

- Cribl.Cloud Enterprise. For details, see Pricing.
- Search Editor Permission, or higher. Learn who can do what at Cribl Search Permissions.
- An OpenTelemetry agent or collector that can reach Cribl Search over OTLP/gRPC or OTLP/HTTP.

You don't need Cribl Stream, Edge, or Lake. (Looking for the OpenTelemetry (OTel) Source in **Cribl Stream** instead?)

1. Add a Lakehouse Engine

See Lakehouse Engines in Cribl Search.


2. Set Up Your Search Datasets

Create the Search Datasets you'll route events into, and set their retention. See Create Search Datasets.

If this Source will store metrics, you don't need to create a Dataset for them. Cribl Search auto-provisions a metrics Dataset for each lakehouse engine. See The Metrics Dataset.

3. Add an OpenTelemetry Source in Cribl Search

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Add Source** > **OpenTelemetry**.



Adding Sources in Cribl Search

Describe Your Source and Set the Protocol

Under **General**, configure:

Setting	Description	Example
ID	Source ID, unique across your Cribl.Cloud Workspace. Use letters, numbers, underscores, hyphens.	`otel_prod`
Description	Describe your Source so others know what it's for.	`Ingests OTLP from prod collectors`
Address	Hostname (FQDN) that your upstream sender connects to. You'll need this to set up your upstream sender.	`search.main.foo-bar-abc123.cribl.cloud`
Port	Network port to listen on. The drop-down labels the two OTLP defaults as **gRPC Default (4317)** and **HTTP Default (4318)**. Keep the default unless it conflicts with another service.	`4317` (gRPC default), `4318` (HTTP default)

Setting	Description	Example
OTLP version	Version of the OTLP Protobuf spec to use. Choose the version that matches your upstream sender.	`1.3.1` (default)
Protocol	The transport protocol to accept: **gRPC** (default) or **HTTP**. Choose the protocol that matches your upstream sender.	gRPC (default)

Port follows **Protocol**. Switching to **HTTP** moves the port to `4318`, and switching back to **gRPC** moves it to `4317`. If another Source already uses the target port, the port stays where it is and the drop-down marks the target as already in use, so check the port before you save.

Choose Logs, Metrics, or Both

The Source also offers **Store this source data as**, which controls which OTLP signals the Source stores, and where it stores them. This setting appears only when metrics are enabled for your Organization.

Option	OTLP metrics	OTLP logs and spans
Logs (default)	Dropped.	Stored as events in your Search Datasets.
Metrics	Stored in the metrics Dataset of your lakehouse engine.	Dropped.
Both Logs and Metrics	Stored in the metrics Dataset of your lakehouse engine.	Stored as events in your Search Datasets.

Keep these behaviors in mind:

- **Both Logs and Metrics** stores each metric once, in the metrics Dataset. Cribl Search never keeps a second, event-shaped copy of a metric in a Search Dataset.
- **Metrics** stores metrics only. If you want to keep the logs and spans that the same Source receives, select **Both Logs and Metrics**.
- A Source that you created before this setting existed behaves as **Logs**, so the metrics it receives are dropped rather than stored as events.
- Cribl Search extracts the individual data points from your OTLP metric payloads for you. You don't need to configure an extraction setting.

Metrics is a Preview feature, and your metrics share the compute and storage of your lakehouse engine. To review the impact on your engine, see Explore Metrics in Cribl Search.

To learn which OTLP metric types Cribl Search stores, and how it renames them, see Supported OTLP Metrics.

Set up Authentication

Use authentication to make sure only authorized senders can push data to your Cribl Search Source.

Under **Authentication**, select the **Authentication type** you want to use:

None | Basic | Basic (Credentials Secret) | Auth Tokens | Auth Token (Text Secret)

Create a username and password. This is what your upstream sender will need to provide when sending data to your Source endpoint.

Setting	Example
Username	`otel_user`
Password	`********`

Set Up Encryption

TLS encryption protects your data in transit between upstream senders and your Cribl Search Source. New Sources have TLS enabled by default, with TLS 1.2 as the minimum version.

Under **Encrypt**, you can review or adjust the **Minimum TLS version** you want to accept:

TLS Version	When to Use
1.3	Provides the strongest security. Use when your clients support it.
1.2	The default. Use for broad client compatibility.
Older than 1.2	Avoid if possible. These versions are no longer considered secure.

Select **Save** to create the Source.

4. Set Up Datatyping

Datatyping applies to the logs and spans that take the event path. If this Source stores metrics only, you can skip this step, because metrics route to a metrics Dataset through Metric Rules instead.

Configure Datatype rules to parse, filter, and normalize your data into structured fields. We call this process Datatyping.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datatyping (auto)**. Here, you can:

- Use Auto-Datatyping to parse your data automatically.
- Check for uncategorized data that didn't match any Datatype rules.
- Handle the uncategorized data by adding custom Datatype rules.

See also:

- Datatypes in Cribl Search
- v2 Datatypes in Cribl Search
- List of Stock v2 Datatypes
- Add a Custom v2 Datatype

5. Set Up Dataset Rules

Configure Dataset rules to route the parsed events into your Search Datasets.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datasets: Organize Your Data**, and see Organize Data with Dataset Rules for details.

Route Metrics with Metric Rules

If this Source stores metrics, Metric Rules decide which metrics Dataset receives them. By default, a single catch-all rule sends all metrics to the primary `metrics` Dataset. A rule for this Source matches `open_telemetry:<your-source-id>` - for example, `open_telemetry:otel_prod`.

Metric Rules apply to data as it arrives and aren't retroactive, so add your rule before you start sending data. For details, see Route Metrics with Metric Rules.

6. Set Up Your OpenTelemetry Sender

Configure your OpenTelemetry collector to export to the Source endpoint.

You'll need these details from your Source configuration:

Name	Example
Address	`search.main.foo-bar-abc123.cribl.cloud`
Port	`4317` (gRPC default), `4318` (HTTP default)

Name	Example
Username / **Password**	`otel_user` / `********`
Or, **Token**	`420`

Examples: OpenTelemetry > Cribl Search

Edit the OpenTelemetry agent or collector's YAML configuration file, using the following example. For details, see OpenTelemetry docs.

Replace the example address (`search.main.foo-bar-abc123.cribl.cloud`), token, and port (if you changed the defaults `4317` for gRPC or `4318` for HTTP) with your Source values.

gRPC HTTPS

```
exporters:
  otlp:
    endpoint: "search.main.foo-bar-abc123.cribl.cloud:4317"
    headers:
      authorization: "Bearer 420"
```

Copy

7. Start Sending Data and Verify

Start sending events from your upstream OpenTelemetry sender, and verify that they're successfully flowing into Cribl Search.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Live Data**.

Here, check for your OpenTelemetry Source. For details, see Live Data.

Live Data shows the logs and spans that take the event path. To confirm that your metrics arrived, open the Metrics Explorer instead: on the Cribl.Cloud top bar, select **Products** > **Search** > **Metrics**, then select the metrics Dataset that your Metric Rules target. For details, see Explore Metrics in Cribl Search.

Supported OTLP Metrics

This section applies when the Source stores metrics. See Choose Logs, Metrics, or Both.

Metric Types

Cribl Search maps each supported OTLP metric type to a Prometheus metric type that you can query with PromQL:

OTLP metric type	Stored as
Gauge	Gauge
Sum, monotonic	Counter
Sum, non-monotonic	Gauge
Histogram with explicit buckets	Histogram

Cribl Search doesn't store Summary metrics or exponential histograms. It also drops individual data points that carry an unusable name, value, or timestamp, along with histograms that arrive without a sum. Your sender receives no error when Cribl Search drops a data point, so if a metric you expect is missing from the Metrics Explorer, check its type first.

Cribl Search also drops a data point whose timestamp falls outside the metrics Dataset's expected time range. By default, a metrics Dataset accepts timestamps up to 10 minutes in the future and has no lower bound, so a sender whose clock runs fast loses data even though the data points themselves are valid. To change the window, open the metrics Dataset and edit **Earliest expected timestamp** and **Latest expected timestamp**.

Metric and Label Names

To keep names valid in PromQL, Cribl Search translates OTLP metric and label names into Prometheus-compatible names. The name you query can therefore differ from the name your collector sends:

- Cribl Search appends the unit as a suffix when the name doesn't already include it. A metric measured in `s` gains `_seconds`, and a metric measured in `By` gains `_bytes`. A compound unit such as `m/s` becomes `_meters_per_second`. For example, `http.server.duration` measured in `ms` becomes `http_server_duration_milliseconds`.
- A counter gains a `_total` suffix at the end of the name, such as `http_server_requests_total`. If the name already contains `total`, Cribl Search moves it to the end instead of adding a second one, so `my.total.requests` becomes `my_requests_total`.
- A gauge measured in unit `1` gains a `_ratio` suffix, such as `system_cpu_utilization_ratio`. A non-monotonic sum stored as a gauge doesn't gain this suffix.
- In a metric name, any character other than a letter, a number, or a colon becomes an underscore, and a run of them collapses into a single underscore. A name that starts with a digit gains a leading underscore.

- Label names follow the stricter label rules of Prometheus, so a colon becomes an underscore there too, and a label name that would start with a digit gains a prefix. The OTLP attribute `service.name` becomes the label `service_name`.
- When two OTLP attribute keys translate to the same label name, Cribl Search joins their values with the `;` character rather than dropping either value.
- When your sender includes an instrumentation scope, Cribl Search adds the `_otel`

2.7.5. Ingest Prometheus Metrics Into Cribl Search

Preview Feature

Cribl is still developing this Preview feature. We don't recommend using it in a production environment, because the feature might not be fully tested or optimized for performance, and related documentation could be incomplete.

Please continue to submit feedback through normal Cribl support channels, but assistance might be limited while the feature remains in Preview.

Collect metrics via the Prometheus Remote Write API to store them in Cribl Search for fast analysis.

Before You Begin

You'll need:

- Cribl.Cloud Enterprise. For details, see Pricing.
- Search Editor Permission, or higher. Learn who can do what at Cribl Search Permissions.
- A Prometheus client that can reach Cribl Search over HTTP(S).

You can send metrics to this Source from a Prometheus client or from the Prometheus Destination in Cribl Stream or Cribl Edge.

To send OTLP metrics instead, use the OpenTelemetry Source. See Ingest OpenTelemetry Data into Cribl Search.

You don't need Cribl Stream, Edge, or Lake. (Looking for the Prometheus Remote Write Source in **Cribl Stream** instead?)

To query your Prometheus instance without moving data into Cribl Search, see Connect Cribl Search to Prometheus.

1. Add a Lakehouse Engine

Metrics are stored on a lakehouse engine. See Lakehouse Engines in Cribl Search.

Metrics is a Preview feature. Adding metrics to a production lakehouse engine can affect its performance. Until the impact is better understood, use one of these approaches:

- On a production engine, keep the metrics volume small.

- Give metrics a dedicated engine, so their load doesn't compete with production search. Route your metrics Source to that engine with Metric Rules.

2. Review the Metrics Dataset


You don't need to create a Dataset for your metrics. When you create an engine, Cribl Search auto-provisions a metrics Dataset for it, named `metrics` for the first engine and `metrics_<engine_id>` for each additional one.

To review its naming, retention, and configuration, see The Metrics Dataset.

3. Add a Prometheus Remote Write Source in Cribl Search

Your metrics engine ships with a built-in Prometheus Remote Write Source (`in_prometheus_rw`) that listens on port `10092`. You can point your Prometheus client at this Source directly, or add another Prometheus Remote Write Source - for example, to send a second data stream to a different engine.

To add a Source, on the Cribl.Cloud top bar select **Products** > **Search** > **Data** > **Add Source** > **Prometheus Remote Write**.



Adding Sources in Cribl Search

Describe Your Source and Set the Endpoint

Under **General**, configure:

Setting	Description	Example
ID	Source ID, unique across your Cribl.Cloud Workspace. Use letters, numbers, underscores, hyphens.	`prometheus_rw_prod`
Description	Describe your Source so others know what it's for.	`Ingests Prometheus Remote Write metrics`
Address	Hostname (FQDN) that your upstream sender connects to. You'll need this to set up your upstream sender.	`search.main.foo-bar-abc123.cribl.cloud`
Port	Network port to listen on. The built-in metrics Source uses `10092`. Change the default only if it conflicts with another service.	`10092`
Remote Write API endpoint	Base path on which to listen for Prometheus Remote Write API requests.	`/api/v1/write` (default)

Set up Authentication

Use authentication to make sure only authorized senders can push data to your Cribl Search Source.

Under **Authentication**, select the **Authentication type** you want to use:

None | Basic | Basic (Credentials Secret) | Auth Tokens | Auth Token (Text Secret)

Create a username and password. This is what your upstream sender will need to provide when sending data to your Source endpoint.

Setting	Example
Username	`prometheus_rw_user`
Password	`********`

Set Up Encryption

TLS encryption protects your data in transit between your upstream Prometheus client and the Cribl Search Source. The built-in metrics Source and any new Source you add have TLS enabled by default, with TLS 1.2 as the minimum version. Your Prometheus client must connect over `https`.

Under **Encrypt**, you can review or adjust the **Minimum TLS version** you want to accept:

TLS Version	When to Use
1.3	Provides the strongest security. Use when your clients support it.
1.2	The default. Use for broad client compatibility.
Older than 1.2	Avoid if possible. These versions are no longer considered secure.

Select **Save** to create the Source.

4. Set Up Datatyping

Datatyping applies to log data. If you're only ingesting metrics, you can skip this step - metrics route to a metrics Dataset through Metric Rules instead. Configure Datatype rules to parse, filter, and normalize your data into structured fields. We call this process Datatyping.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datatyping (auto)**. Here, you can:

- Use Auto-Datatyping to parse your data automatically.
- Check for uncategorized data that didn't match any Datatype rules.
- Handle the uncategorized data by adding custom Datatype rules.

See also:

- Datatypes in Cribl Search
- v2 Datatypes in Cribl Search
- List of Stock v2 Datatypes
- Add a Custom v2 Datatype

5. Route Metrics with Metric Rules

Metric Rules decide which metrics Dataset receives the metrics from this Source. By default, a single **Metrics catch-all** rule (`*`) sends all metrics to the primary `metrics` Dataset. A rule for this Source matches `prometheus_rw:<your-source-id>` - for example, `prometheus_rw:in_prometheus_rw`.

Metric Rules apply to data as it arrives and aren't retroactive, so add your rule before you start sending data. For details, see Route Metrics with Metric Rules.

6. Set Up Your Prometheus Client

Configure your upstream Prometheus client, or the Prometheus Destination in Stream or Edge, to send data to your Cribl Search Source.

You'll need these details from your Source configuration:

Setting	Example
Address	`search.main.foo-bar-abc123.cribl.cloud`
Port	`10092`
Remote Write API endpoint	`/api/v1/write` (default)

Example: Prometheus Remote Write > Cribl Search

Add a `remote_write` block to your `prometheus.yml` file, using the following example.

Basic | Auth Token

Replace the example address (`search.main.foo-bar-abc123.cribl.cloud`), username, password, endpoint, and port (if you chose a different port) with your Source values.

```
remote_write:
  - url: "https://search.main.foo-bar-abc123.cribl.cloud:10092/api/v1/write"
    basic_auth:
      username: "your_username"
      password: "********"
```

Copy

Send Metrics from Cribl Stream or Edge

Use the Prometheus Destination to send metric events from Stream or Edge to this Source:

1. In a Pipeline, produce metric events that contain a nonempty `__criblMetrics` array. For example, use the Publish Metrics Function.
2. Add a Prometheus Destination in Stream or Edge.
3. For **Remote Write URL**, enter the complete URL for your Search Source. Combine the **Address**, **Port**, and **Remote Write API endpoint** values. For example:

```
https://search.main.foo-bar-abc123.cribl.cloud:10092/api/v1/write
```

Copy

4. Configure the Destination authentication to match the Search Source authentication.
5. Select **Save**, then **Commit & Deploy**.

The Prometheus Destination sends events that contain `__criblMetrics` and drops other events.

7. Start Sending Data and Verify

Start sending events from your upstream Prometheus client, and verify that they're successfully flowing into Cribl Search.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Live Data**.

Here, check for your Prometheus Remote Write Source. For details, see Live Data.

Read Metrics from External Tools

Each metrics Dataset exposes a Prometheus-compatible query endpoint that Prometheus-compatible tools such as Grafana can read from. The endpoint has this form:

```
https://<cribl-host>/api/v1/products/lakehouse_engine_metrics/engines/<engine>/datase
```

Copy

Find this endpoint, labeled **Prometheus compatible endpoint**, in the metrics Dataset configuration. Control access to it with the Dataset's Query API Access authentication, which can be **None** or **Basic** (username and password).

Cribl strongly recommends setting **Query API Access** to **Basic** and configuring a username and password to lock down this endpoint. If you leave it set to **None**, the endpoint is completely open -

> anyone who can reach it can read your metrics, even if you never connect Grafana or another tool. Always set up Basic authentication to prevent unauthorized access.

Next Steps

Now that your metrics are in Cribl Search, you can start using them. For example:

- Explore your metrics
- Set up Monitors
- Search your data
- Start a Notebook
- Run an investigation

2.7.6. Ingest Raw HTTP Data Into Cribl Search

Collect HTTP data in any format to store it in Cribl Search for fast analysis.

Before You Begin

You'll need:

- Cribl.Cloud Enterprise. For details, see Pricing.
- Search Editor Permission, or higher. Learn who can do what at Cribl Search Permissions.

You don't need Cribl Stream, Edge, or Lake. (Looking for the Raw HTTP/S Source in **Cribl Stream** instead?)

1. Add a Lakehouse Engine


See Lakehouse Engines in Cribl Search.

2. Set Up Your Search Datasets

Create the Search Datasets you'll route events into, and set their retention. See Create Search Datasets.

3. Add a Raw HTTP Source in Cribl Search

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Add Source** > **Raw HTTP**.



Adding Sources in Cribl Search

Describe Your Source

Under **General**, configure:

Setting	Description	Example
ID	Source ID, unique across your Cribl.Cloud Workspace. Use letters, numbers, underscores, hyphens.	`raw_http_prod`
Description	Describe your Source so others know what it's for.	`Ingests raw HTTP requests`
Address	Hostname (FQDN) that your HTTP client connects to. You'll need this to set up your HTTP client.	`search.main.foo-bar-abc123.cribl.cloud`
Port	Network port to listen on. Keep the default unless it conflicts with another service.	`20000`

Set up Authentication

Use authentication to make sure only authorized HTTP clients can send data to your Cribl Search Source.

Under **Authentication**, select **Add Token**. Add as many tokens as you need.

Setting	Description	Example
Token	Authentication string you'll need to set up your HTTP client. Enter a token text, or select **Generate** for a random one.	`420`
Description	Describe which clients or environments use the token.	`Prod HTTP`
Fields	Extra fields to add to each event referencing this token. Use this to stamp events with metadata that you can later search by. In **Value**, enclose JavaScript expressions in backticks `` ` ` ``.	**Field name**: `fullSource` **Value**: `` `${host}:${source}` ``

Set Up Encryption

TLS encryption protects your data in transit between upstream HTTP clients and your Cribl Search Source. New Sources have TLS enabled by default, with TLS 1.2 as the minimum version.

Under **Encrypt**, you can review or adjust the **Minimum TLS version** you want to accept:

TLS Version	When to Use
1.3	Provides the strongest security. Use when your clients support it.
1.2	The default. Use for broad client compatibility.
Older than 1.2	Avoid if possible. These versions are no longer considered secure.

Select **Save** to create the Source.

4. Set Up Datatyping

Configure Datatype rules to parse, filter, and normalize your data into structured fields. We call this process Datatyping.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datatyping (auto)**. Here, you can:

- Use Auto-Datatyping to parse your data automatically.
- Check for uncategorized data that didn't match any Datatype rules.

- Handle the uncategorized data by adding custom Datatype rules.

See also:

- Datatypes in Cribl Search
- v2 Datatypes in Cribl Search
- List of Stock v2 Datatypes
- Add a Custom v2 Datatype

5. Set Up Dataset Rules

Configure Dataset rules to route the parsed events into your Search Datasets.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datasets: Organize Your Data**, and see Organize Data with Dataset Rules for details.

6. Set Up Your HTTP Client

Configure your upstream HTTP client to send data to your Cribl Search Source.

You'll need these details from your Source configuration:

Name	Example
Address	`search.main.foo-bar-abc123.cribl.cloud`
Port	`20000`
Auth Token	`420`

To find these for an existing Source: On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Sources**, and select your Source.

Example Request (Raw HTTP > Cribl Search)

Replace the example address (`search.main.foo-bar-abc123.cribl.cloud`) and port (if you changed the default `20000`) with your Source values.

Single Event | Multiple Events

```
curl -k "https://search.main.foo-bar-abc123.cribl.cloud:20000" \
-H "Authorization: your_token" \
-d '{"_raw":"this is a sample event"}'
```

2.7.7. Ingest Splunk HEC Events Into Cribl Search

Collect data sent via HTTP(S) protocols to store it in Cribl Search for fast analysis.

Before You Begin

You'll need:

- Cribl.Cloud Enterprise. For details, see Pricing.
- Search Editor Permission, or higher. Learn who can do what at Cribl Search Permissions.
- A Splunk HEC sender that can reach Cribl Search over HTTP(S): universal forwarder, heavy forwarder, or any other HEC client.

You don't need Cribl Stream, Edge, or Lake. (Looking for the Splunk HEC Source in **Cribl Stream** instead?)

1. Add a Lakehouse Engine


See Lakehouse Engines in Cribl Search.

2. Set Up Your Search Datasets

Create the Search Datasets you'll route events into, and set their retention. See Create Search Datasets.

3. Add a Splunk HEC Source in Cribl Search

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Add Source** > **Splunk HEC**.



Adding Sources in Cribl Search

Describe Your Source and Set the HEC Endpoint

Under **General**, configure:

Setting	Description	Example
ID	Source ID, unique across your Cribl.Cloud Workspace. Use letters, numbers, underscores, hyphens.	`splunk_hec_prod`
Description	Describe your Source so others know what it's for.	`Ingests HEC from prod Splunk`
Address	Hostname (FQDN) that your HEC client connects to. You'll need this to set up your HEC client.	`search.main.foo-bar-abc123.cribl.cloud`
Port	Network port to listen on. Keep the default unless it conflicts with another service.	`8088` (default)

Setting	Description	Example

Splunk HEC endpoint	Base path on which to listen for Splunk HEC API requests.
	
	Cribl Search automatically handles these sub-paths:
	`/event`
	`/raw`
	`/s2s`
	`/health`
		`/services/collector` (default)
		
		Handles:
		`/services/collector/event`
		`/services/collector/raw`
		`/services/collector/s2s`
		`/services/collector/health`

Set up Authentication

Use authentication to make sure only authorized HEC clients can send data to your Cribl Search Source.

Under **Authentication**, select **Add Token**. Add as many tokens as you need. Check **Enable token** for the tokens you want active.

For each token, set **Authentication method** to:

- **Manual** for quick setup or testing.
- **Secret** to securely manage credentials in production environments. (See Create and Manage Secrets in Cribl Stream.)

Manual Secret

Setting	Description	Example
Token	Authentication string you'll need to set up your HEC client. Enter a token text, or select **Generate** for a random one.	`420`
Description	Describe which clients or environments use the token.	`Prod UF`
Allowed indexes	Splunk indexes allowed for this token. Events with non-matching `index` values won't be ingested. Use this to scope tokens to specific indexes. For example, give the web team a token restricted to `web_*` and the security team a token restricted to `security_*` to keep each team's data separate.	`dev_*`

Setting	Description	Example
	Use wildcards to match multiple indexes. Leave blank to allow all.	
Fields	Extra fields to add to each event referencing this token. Use this to stamp events with metadata that you can later search by. In **Value**, enclose JavaScript expressions in backticks `` ` ` ``.	**Field name**: `fullSource` **Value**: `` `${host}:${source}` ``

Set Up Encryption

TLS encryption protects your data in transit between upstream Splunk HEC senders and your Cribl Search Source. New Sources have TLS enabled by default, with TLS 1.2 as the minimum version.

Under **Encrypt**, you can review or adjust the **Minimum TLS version** you want to accept:

TLS Version	When to Use
1.3	Provides the strongest security. Use when your clients support it.
1.2	The default. Use for broad client compatibility.
Older than 1.2	Avoid if possible. These versions are no longer considered secure.

Select **Save** to create the Source.

4. Set Up Datatyping

Configure Datatype rules to parse, filter, and normalize your data into structured fields. We call this process Datatyping.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datatyping (auto)**. Here, you can:

- Use Auto-Datatyping to parse your data automatically.
- Check for uncategorized data that didn't match any Datatype rules.
- Handle the uncategorized data by adding custom Datatype rules.

See also:

- Datatypes in Cribl Search

- v2 Datatypes in Cribl Search
- List of Stock v2 Datatypes
- Add a Custom v2 Datatype

5. Set Up Dataset Rules

Configure Dataset rules to route the parsed events into your Search Datasets.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datasets: Organize Your Data**, and see Organize Data with Dataset Rules for details.

6. Set Up Your HEC Client

Configure your upstream Splunk HEC client to send data to Cribl Search.

You'll need these details from your Source configuration:

Name	Example
Address	`search.main.foo-bar-abc123.cribl.cloud`
Port	`8088` (default)
Splunk HEC endpoint	`/services/collector`
Token / Auth Token	`420`

To find these for an existing Source: On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Sources**, and select your Source.

Example Request (Splunk HEC > Cribl Search)

Replace the example address (`search.main.foo-bar-abc123.cribl.cloud`) and port (if you changed the default `8088`) with your Source values.

JSON Event | Health Check

```
curl -k "https://search.main.foo-bar-abc123.cribl.cloud:8088/services/collector" \
-H "Authorization: your_token" \
-d '{"event": "Goats are better than ponies."}{"event": "Goats are better climbers
```

2.7.8. Ingest Splunk Forwarder Data Into Cribl Search

Collect S2S traffic from Splunk universal or heavy forwarders to store it in Cribl Search for fast analysis.

Before You Begin

You'll need:

- Cribl.Cloud Enterprise. For details, see Pricing.
- Search Editor Permission, or higher. Learn who can do what at Cribl Search Permissions.
- A Splunk sender that can reach Cribl Search over TCP (for example, a Splunk universal forwarder).

You don't need Cribl Stream, Edge, or Lake. (Looking for the Splunk TCP Source in **Cribl Stream** instead?)

1. Add a Lakehouse Engine


See Lakehouse Engines in Cribl Search.

2. Set Up Your Search Datasets

Create the Search Datasets you'll route events into, and set their retention. See Create Search Datasets.

3. Add a Splunk TCP Source in Cribl Search

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Add Source** > **Splunk TCP**.



Adding Sources in Cribl Search

Describe Your Source

Under **General**, configure:

Setting	Description	Example
ID	Source ID, unique across your Cribl.Cloud Workspace. Use letters, numbers, underscores, hyphens.	`splunk_tcp_prod`
Description	Describe your Source so others know what it's for.	`Ingests TCP from prod Splunk`
Address	Hostname (FQDN) that your Splunk forwarder connects to. You'll need this to set up your Splunk forwarder.	`search.main.foo-bar-abc123.cribl.cloud`
Port	Network port to listen on. Keep the default unless it conflicts with another service.	`9997` (default)

Set Up Authentication

Use authentication to make sure only authorized Splunk forwarders can send data to your Cribl Search Source.

Under **Authentication**, select **Add Token**. Add as many tokens as you need.

Setting	Description	Example
Token	Authentication string you'll need to set up your Splunk forwarder. Enter a token text, or select **Generate** for a random one.	`420`
Description	Describe which clients or environments use the token.	`Prod UF`

Set Up Encryption

TLS encryption protects your data in transit between upstream Splunk forwarders and your Cribl Search Source. New Sources have TLS enabled by default, with TLS 1.2 as the minimum version.

Under **Encrypt**, you can review or adjust the **Minimum TLS version** you want to accept:

TLS Version	When to Use
1.3	Provides the strongest security. Use when your clients support it.
1.2	The default. Use for broad client compatibility.
Older than 1.2	Avoid if possible. These versions are no longer considered secure.

Select **Save** to create the Source.

4. Set Up Datatyping

Configure Datatype rules to parse, filter, and normalize your data into structured fields. We call this process Datatyping.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datatyping (auto)**. Here, you can:

- Use Auto-Datatyping to parse your data automatically.
- Check for uncategorized data that didn't match any Datatype rules.
- Handle the uncategorized data by adding custom Datatype rules.

See also:

- Datatypes in Cribl Search

- v2 Datatypes in Cribl Search
- List of Stock v2 Datatypes
- Add a Custom v2 Datatype

5. Set Up Dataset Rules

Configure Dataset rules to route the parsed events into your Search Datasets.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datasets: Organize Your Data**, and see Organize Data with Dataset Rules for details.

6. Set Up Your Splunk Forwarder

Configure your upstream Splunk forwarder to send data to Cribl Search.

You'll need these details from your Source configuration:

Name	Example
Address	`search.main.foo-bar-abc123.cribl.cloud`
Port	`9997` (default)
Token	`420`

To find these for an existing Source: On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Sources**, and select your Source.

Example: Splunk TCP > Cribl Search

Use this sample outputs.conf stanza, replacing the example address (`search.main.foo-bar-abc123.cribl.cloud`), token, and port (if you changed the default `9997`) with your Source values.

```
[tcpout]
disabled = false
defaultGroup = cribl

[tcpout:cribl]
server = search.main.foo-bar-abc123.cribl.cloud:9997
```

2.7.9. Ingest Syslog Messages Into Cribl Search

Collect data from syslog agents via TCP or UDP to store it in Cribl Search for fast analysis.

Before You Begin

You'll need:

- Cribl.Cloud Enterprise. For details, see Pricing.
- Search Editor Permission, or higher. Learn who can do what at Cribl Search Permissions.
- A syslog sender that can reach Cribl Search over TCP or UDP: rsyslog, syslog-ng, or any other syslog client.

You don't need Cribl Stream, Edge, or Lake. (Looking for the Syslog Source in **Cribl Stream** instead?)

1. Add a Lakehouse Engine


See Lakehouse Engines in Cribl Search.

2. Set Up Your Search Datasets

Create the Search Datasets you'll route events into, and set their retention. See Create Search Datasets.

3. Add a Syslog Source in Cribl Search

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Add Source** > **Syslog**.



Adding Sources in Cribl Search

Describe Your Source

Under **General**, configure:

Setting	Description	Example
ID	Source ID, unique across your Cribl.Cloud Workspace. Use letters, numbers, underscores, hyphens.	`syslog_prod`
Description	Describe your Source so others know what it's for.	`Ingests syslog from prod servers`

Set Ports

Under **General**, set the ports you want to listen on:

Setting	Description	Example
Address	Hostname (FQDN) that your syslog client connects to. You'll need this to set up your syslog client.	`search.main.foo-bar-abc123.cribl.cloud`

Setting	Description	Example
TCP Port	Network port to listen on for TCP traffic. Set this if you want to receive data over TCP.	`9514` (default)
UDP Port	Network port to listen on for UDP traffic. Set this if you want to receive data over UDP.	`9514` (default)

Set Up Encryption

TLS encryption protects your data in transit between upstream syslog senders and your Cribl Search Source. New Sources have TLS enabled by default, with TLS 1.2 as the minimum version.

TLS is supported for TCP connections only. UDP traffic is never encrypted.

Under **Encrypt**, you can review or adjust the **Minimum TLS version** you want to accept:

TLS Version	When to Use
1.3	Provides the strongest security. Use when your clients support it.
1.2	The default. Use for broad client compatibility.
Older than 1.2	Avoid if possible. These versions are no longer considered secure.

Select **Save** to create the Source.

4. Set Up Datatyping

Configure Datatype rules to parse, filter, and normalize your syslog messages into structured fields. We call this process Datatyping.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datatyping (auto)**. Here, you can:

- Use Auto-Datatyping to parse your data automatically.
- Check for uncategorized data that didn't match any Datatype rules.
- Handle the uncategorized data by adding custom Datatype rules.

See also:

- Datatypes in Cribl Search
- v2 Datatypes in Cribl Search
- List of Stock v2 Datatypes

- Add a Custom v2 Datatype

5. Set Up Dataset Rules

Configure Dataset rules to route the parsed events into your Search Datasets.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datasets: Organize Your Data**, and see Organize Data with Dataset Rules for details.

6. Set Up Your Syslog Client

Configure your upstream syslog client to send data to Cribl Search.

You'll need these details from your Source configuration:

Name	Example
Address	`search.main.foo-bar-abc123.cribl.cloud`
TCP Port	`9514` (default)
UDP Port	`9514` (default)

To find these for an existing Source: On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Sources**, and select your Source.

Example Message (Syslog > Cribl Search)

Replace the example address (`search.main.foo-bar-abc123.cribl.cloud`) and port (if you changed the default `9514`) with your Source values.

RFC 3164 (TCP) RFC 3164 (UDP)

```
echo '<34>Oct 11 22:14:15 mymachine su: su root failed for lonvick on /dev/pts/8'
```

Copy

7. Start Sending Data and Verify

2.7.10. Ingest JSON Events Via TCP Into Cribl Search

Collect JSON-formatted events via TCP, and automatically parse and store them in Cribl Search for fast analysis.

Before You Begin

You'll need:

- Cribl.Cloud Enterprise. For details, see Pricing.
- Search Editor Permission, or higher. Learn who can do what at Cribl Search Permissions.
- A TCP client that can send newline-delimited JSON to Cribl Search.

You don't need Cribl Stream, Edge, or Lake. (Looking for the TCP JSON Source in **Cribl Stream** instead?)

1. Add a Lakehouse Engine


See Lakehouse Engines in Cribl Search.

2. Set Up Your Search Datasets

Create the Search Datasets you'll route events into, and set their retention. See Create Search Datasets.

3. Add a TCP JSON Source in Cribl Search

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Add Source** > **TCP JSON**.



Adding Sources in Cribl Search

Describe Your Source

Under **General**, configure:

Setting	Description	Example
ID	Source ID, unique across your Cribl.Cloud Workspace. Use letters, numbers, underscores, hyphens.	`tcp_json_prod`
Description	Describe your Source so others know what it's for.	`Ingests TCP JSON from prod servers`
Address	Hostname (FQDN) that your TCP client connects to. You'll need this to set up your TCP client.	`search.main.foo-bar-abc123.cribl.cloud`
Port	Network port to listen on. Keep the default unless it conflicts with another service.	`10070` (default)

Set Up Authentication

Use authentication to make sure only authorized TCP clients can send data to your Cribl Search Source.

Under **Authentication**, set the **Authentication method** to:

- **Manual** for quick setup or testing.
- **Secret** to securely manage credentials in production environments. (See Create and Manage Secrets in Cribl Stream.)

Manual Secret

Setting	Description	Example
Auth token	Shared secret that your TCP client will need to provide in the `authToken` header field. Enter a token text, or select **Generate** for a random one. Leave blank to allow unauthorized access.	`420`

Set Up Encryption

TLS encryption protects your data in transit between upstream TCP clients and your Cribl Search Source. New Sources have TLS enabled by default, with TLS 1.2 as the minimum version.

Under **Encrypt**, you can review or adjust the **Minimum TLS version** you want to accept:

TLS Version	When to Use
1.3	Provides the strongest security. Use when your clients support it.
1.2	The default. Use for broad client compatibility.
Older than 1.2	Avoid if possible. These versions are no longer considered secure.

Select **Save** to create the Source.

4. Set Up Datatyping

Configure Datatype rules to parse, filter, and normalize your data into structured fields. We call this process Datatyping.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datatyping (auto)**. Here, you can:

- Use Auto-Datatyping to parse your data automatically.
- Check for uncategorized data that didn't match any Datatype rules.
- Handle the uncategorized data by adding custom Datatype rules.

See also:

- Datatypes in Cribl Search
- v2 Datatypes in Cribl Search
- List of Stock v2 Datatypes
- Add a Custom v2 Datatype

5. Set Up Dataset Rules

Configure Dataset rules to route the parsed events into your Search Datasets.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datasets: Organize Your Data**, and see Organize Data with Dataset Rules for details.

6. Set Up Your TCP Client

Configure your upstream TCP client to send newline-delimited JSON to your Cribl Search Source.

You'll need these details from your Source configuration:

Name	Example
Address	`search.main.foo-bar-abc123.cribl.cloud`
Port	`10070` (default)
Auth Token	`420`

To find these for an existing Source: On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Sources**, and select your Source.

Example (TCP JSON > Cribl Search)

Create a `test.json` file with the following content. Replace the example address (`search.main.foo-bar-abc123.cribl.cloud`), auth token, and port (if you changed the default `10070`) with your Source values.

```
echo '{"authToken":"420"}
{"_raw":"this is a sample event", "host":"myHost", "source":"mySource", "fieldA":"val
{"_raw":"this is another sample event", "host":"myOtherHost", "source":"myOtherSource

cat test.json | ncat --ssl --ssl-verify search.main.foo-bar-abc123.cribl.cloud 10070
```

Copy

2.7.11. Ingest Raw TCP Data Into Cribl Search

Collect data in any format via TCP to store it in Cribl Search for fast analysis.

Before You Begin

You'll need:

- Cribl.Cloud Enterprise. For details, see Pricing.
- Search Editor Permission, or higher. Learn who can do what at Cribl Search Permissions.
- A TCP client that can send data to Cribl Search in any format.

You don't need Cribl Stream, Edge, or Lake. (Looking for the TCP (Raw) Source in **Cribl Stream** instead?)

1. Add a Lakehouse Engine


See Lakehouse Engines in Cribl Search.

2. Set Up Your Search Datasets

Create the Search Datasets you'll route events into, and set their retention. See Create Search Datasets.

3. Add a TCP Source in Cribl Search

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Add Source** > **TCP**.



Adding Sources in Cribl Search

Describe Your Source

Under **General**, configure:

Setting	Description	Example
ID	Source ID, unique across your Cribl.Cloud Workspace. Use letters, numbers, underscores, hyphens.	`tcp_raw_prod`
Description	Describe your Source so others know what it's for.	`Ingests TCP raw from prod servers`
Address	Hostname (FQDN) that your TCP client connects to. You'll need this to set up your TCP client.	`search.main.foo-bar-abc123.cribl.cloud`
Port	Network port to listen on. Keep the default unless it conflicts with another service.	`10060` (default)

Set Up Authentication

Use authentication to make sure only authorized TCP clients can send data to your Cribl Search Source.

Under **Authentication**, select **Enable header**, and then set **Authentication method** to:

- **Manual** for quick setup or testing.
- **Secret** to securely manage credentials in production environments. (See Create and Manage Secrets in Cribl Stream.)

Manual | Secret

Setting	Description	Example
Auth token	Shared secret that your TCP client provides in the `authToken` header field. Enter a token text, or select **Generate** for a random one. Leave blank to allow unauthorized access.	`420`

Set Up Encryption

TLS encryption protects your data in transit between your upstream TCP client and your Cribl Search Source. New Sources have TLS enabled by default, with TLS 1.2 as the minimum version.

Under **Encrypt**, you can review or adjust the **Minimum TLS version** you want to accept:

TLS Version	When to Use
1.3	Provides the strongest security. Use when your clients support it.
1.2	The default. Use for broad client compatibility.
Older than 1.2	Avoid if possible. These versions are no longer considered secure.

Select **Save** to create the Source.

4. Set Up Datatyping

Configure Datatype rules to parse, filter, and normalize your data into structured fields. We call this process Datatyping.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datatyping (auto)**. Here, you can:

- Use Auto-Datatyping to parse your data automatically.
- Check for uncategorized data that didn't match any Datatype rules.
- Handle the uncategorized data by adding custom Datatype rules.

See also:

- Datatypes in Cribl Search
- v2 Datatypes in Cribl Search
- List of Stock v2 Datatypes
- Add a Custom v2 Datatype

5. Set Up Dataset Rules

Configure Dataset rules to route the parsed events into your Search Datasets.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datasets: Organize Your Data**, and see Organize Data with Dataset Rules for details.

6. Set Up Your TCP Client

Configure your upstream TCP client to send data to your Cribl Search Source.

You'll need these details from your Source configuration:

Name	Example
Address	`search.main.foo-bar-abc123.cribl.cloud`
Port	`10060` (default)
Auth Token	`420`

To find these for an existing Source: On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Sources**, and select your Source.

Example (TCP > Cribl Search)

Replace the example address (`search.main.foo-bar-abc123.cribl.cloud`), auth token, and port (if you changed the default `10060`) with your Source values.

```
echo '{"authToken":"420", "fields": {"region": "us-east-1"}}
this is event number 1
this is event number 2' > test.raw

cat test.raw | ncat --ssl --ssl-verify search.main.foo-bar-abc123.cribl.cloud 10060
```

Copy

2.7.12. Ingest Windows Events Into Cribl Search

Collect Windows Event Forwarder logs from WEF servers to store them in Cribl Search for fast analysis.

Before You Begin

On the Cribl Search side, you'll need:

- Cribl.Cloud Enterprise. For details, see Pricing.
- Search Editor Permission, or higher. Learn who can do what at Cribl Search Permissions.

On the WEF server side, you'll need:

- WEF that's set up and enabled.
- WEF client(s) that are pointed to WECs.
- Either client certificate or Kerberos authentication configured. For details, see these Cribl Stream docs:
  - Client Certificate Authentication for Windows Event Forwarder
  - Kerberos Authentication for Windows Event Forwarder

You don't need Cribl Stream, Edge, or Lake. (Looking for the Windows Event Forwarder Source in **Cribl Stream** instead?)

1. Add a Lakehouse Engine


See Lakehouse Engines in Cribl Search.

2. Set Up Your Search Datasets

Create the Search Datasets you'll route events into, and set their retention. See Create Search Datasets.

3. Add a Windows Event Forwarder Source in Cribl Search

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Add Source** > **Windows Event Forwarder**.



Adding Sources in Cribl Search

Describe Your Source

Under **General**, configure:

Setting	Description	Example
ID	Source ID, unique across your Cribl.Cloud Workspace. Use letters, numbers, underscores, hyphens.	`wef_prod`
Description	Describe your Source so others know what it's for.	`Ingests WEF from prod servers`
Address	Hostname (FQDN) that your WEF client connects to.	`search.main.foo-bar-abc123.cribl.cloud`
Port	Network port to listen on. Keep the default unless it conflicts with another service.	`5986` (default)

Set Up Authentication and Encryption

You can authenticate incoming connections to your Source using either client certificate or Kerberos authentication.

Client Certificate | Kerberos

First, set up a client certificate on the WEF server side. See Client Certificate Authentication for Windows Event Forwarder.

Then, under **Authentication**, select **Client certificate**, and configure:

Setting	Description	Example
Certificate	Certificate name. Select a certificate, or **Create** a new one. (See Cribl Stream docs.)	`search.cribl.cloud`
Private key path	Path to the PEM-formatted private key file on the server. Enter the file path. Supports `$ENV_VARS`.	`/etc/ssl/private/wef.key`
Passphrase	Passphrase for decrypting the private key, if encrypted. Enter the passphrase. Use a secure secret input.	`myPassphrase`
Certificate path	Path to the PEM-formatted server certificate file on the server. Enter the file path. Supports `$ENV_VARS`.	`/etc/ssl/certs/wef.crt`
CA certificate path	Path to the PEM-formatted CA certificate file on the server. Enter the file path. Supports `$ENV_VARS`. If multiple certificates are present in a `.pem` file, each must directly certify the one preceding it.	`/etc/ssl/certs/ca.crt`
Common name	Regex to validate the peer certificate's CN or SANs. Enter a regex pattern. If SANs are present, matching is against SANs and CN is ignored.	`^worker\.cribl\.local$`
Minimum TLS version / Maximum TLS version	Minimum and maximum TLS versions to accept. Recommended: Min `1.2`, Max `1.3`.	Min `1.2`, Max `1.3`

Setting	Description	Example
Verify certificate via OCSP	Enable OCSP revocation checking for client certificates.	Yes
Strict validation	Toggle that controls how OCSP errors are handled. Enable to fail on any OCSP error. Disable to fail only on revocation errors.	Enabled

---

4. Set Up Datatyping

Configure Datatype rules to parse, filter, and normalize your data into structured fields. We call this process Datatyping.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datatyping (auto)**. Here, you can:

- Use Auto-Datatyping to parse your data automatically.
- Check for uncategorized data that didn't match any Datatype rules.
- Handle the uncategorized data by adding custom Datatype rules.

See also:

- Datatypes in Cribl Search
- v2 Datatypes in Cribl Search
- List of Stock v2 Datatypes
- Add a Custom v2 Datatype

5. Set Up Dataset Rules

Configure Dataset rules to route the parsed events into your Search Datasets.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datasets: Organize Your Data**, and see Organize Data with Dataset Rules for details.

6. Set Up Your WEF Client

Configure your WEF client to forward events to your Cribl Search Source.

For details, see the Cribl Stream docs: Windows Event Forwarder Source in Cribl Stream.

7. Start Sending Data and Verify

Start sending events from your Windows Event Forwarder, and verify that they're successfully flowing into Cribl Search.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Live Data**.

Here, check for your Windows Event Forwarder Source. For details, see Live Data.

2.7.13. Ingest Wiz Security Events Into Cribl Search

Collect security events and alerts via Wiz webhook notifications to store them in Cribl Search for fast analysis.

Before You Begin

You'll need:

- Cribl.Cloud Enterprise. For details, see Pricing.
- Search Editor Permission, or higher. Learn who can do what at Cribl Search Permissions.
- Wiz webhook integration that can send data to Cribl Search over HTTP(S).

You don't need Cribl Stream, Edge, or Lake. (Looking for the Wiz Webhook Source in **Cribl Stream** instead?)

1. Add a Lakehouse Engine


See Lakehouse Engines in Cribl Search.

2. Set Up Your Search Datasets

Create the Search Datasets you'll route events into, and set their retention. See Create Search Datasets.

3. Add a Wiz Webhook Source in Cribl Search

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Add Source** > **Wiz Webhook**.



Adding Sources in Cribl Search

Under **General**, configure:

Setting	Description	Example
ID	Source ID, unique across your Cribl.Cloud Workspace. Use letters, numbers, underscores, hyphens.	`wiz_webhook_prod`
Description	Describe your Source so others know what it's for.	`Ingests Wiz webhook security events`
Address	Hostname (FQDN) that your Wiz webhook connects to. You'll need this to set up your webhook client.	`search.main.foo-bar-abc123.cribl.cloud`
Port	Network port to listen on. Keep the default unless it conflicts with another service.	`20000` (default)

Set Up Authentication

Use authentication to make sure only authorized clients can send data to your Cribl Search Source.

Under **Authentication**, select **Add Token**, and configure:

Setting	Description	Example
Token	Authentication string you'll need to set up your Wiz client. Enter a token text, or select **Generate** for a random one.	`420`
Description	Describe which clients or environments use the token.	`Prod UF`

Set Up Encryption

TLS encryption protects your data in transit between Wiz and your Cribl Search Source. New Sources have TLS enabled by default, with TLS 1.2 as the minimum version.

Under **Encrypt**, you can review or adjust the **Minimum TLS version** you want to accept:

TLS Version	When to Use
1.3	Provides the strongest security. Use when your clients support it.
1.2	The default. Use for broad client compatibility.
Older than 1.2	Avoid if possible. These versions are no longer considered secure.

Select **Save** to create the Source.

4. Set Up Datatyping

Configure Datatype rules to parse, filter, and normalize your data into structured fields. We call this process Datatyping.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datatyping (auto)**. Here, you can:

- Use Auto-Datatyping to parse your data automatically.
- Check for uncategorized data that didn't match any Datatype rules.
- Handle the uncategorized data by adding custom Datatype rules.

See also:

- Datatypes in Cribl Search
- v2 Datatypes in Cribl Search
- List of Stock v2 Datatypes

- Add a Custom v2 Datatype

5. Set Up Dataset Rules

Configure Dataset rules to route the parsed events into your Search Datasets.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datasets: Organize Your Data**, and see Organize Data with Dataset Rules for details.

6. Set Up Your Wiz Webhook

In Wiz, configure a webhook to send security events to Cribl Search.

You'll need these details from your Source configuration:

Name	Example
Address	`search.main.foo-bar-abc123.cribl.cloud`
Port	`20000` (default)
Token	`420`

To find these for an existing Source: On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Sources**, and select your Source.

Example Request (Wiz Webhook > Cribl Search)

Configure the webhook in Wiz to point to your Source endpoint, using the following example.

Replace the example address (`search.main.foo-bar-abc123.cribl.cloud`), token, and port (if you changed the default `20000`) with your Source values.

```
curl -k "https://search.main.foo-bar-abc123.cribl.cloud:20000" \
-H "Authorization: 420" \
-d '{"event":"Wiz security alert", "host":"wiz", "source":"wiz-webhook", "severity":'
```

Copy

7. Start Sending Data and Verify

3. Explore Metrics In Cribl Search

Preview Feature


Cribl is still developing this Preview feature. We don't recommend using it in a production environment, because the feature might not be fully tested or optimized for performance, and related documentation could be incomplete.

Please continue to submit feedback through normal Cribl support channels, but assistance might be limited while the feature remains in Preview.

Explore, filter, and visualize your metrics in Cribl Search, alongside your logs.

About Metrics

Cribl Search ingests metrics into a lakehouse engine - the same storage that accelerates your logs - and their simple, consistent shape lets Cribl Search query and visualize them quickly, even across very large volumes.



Metrics Explorer

Because metrics live alongside your logs, they make a fast starting point for investigation: chart a metric to spot an anomaly, such as a latency spike or a drop in throughput, then pivot into your logs, an Investigation, or a Notebook to find the cause.

The Metrics experience is made up of four parts:

- **Metrics ingest**: Sending metrics into Cribl Search, through the Prometheus Remote Write, OpenTelemetry, or Cribl HTTP Source. See Ingest Metrics into Cribl Search.
- **Metrics storage**: Where your metrics land. Cribl Search auto-provisions a metrics Dataset for each lakehouse engine, and Metric Rules decide which one receives the metrics from a given Source.
- **Metrics Explorer**: The visual explorer described on this page, where you query and visualize individual metrics.
- **Monitors**: Alerting on metric conditions such as thresholds, changes, and anomalies.

You can also add metrics to Dashboards and Notebooks.

Metric Types

Cribl Search recognizes the standard Prometheus metric types, and shows each metric's type in the Metrics Explorer:

- **Counter**: A cumulative value that only increases and resets to zero on restart, such as total requests served. Query counters with the `rate` transformation to see the per-second rate of change.
- **Gauge**: A value that can go up or down, such as memory usage or queue depth. Read a gauge directly, without `rate`.
- **Histogram**: Samples observations into buckets, along with a running sum and count. Use histograms to analyze distributions, such as request latency, with the PromQL functions `histogram_quantile`, `histogram_fraction`, `histogram_count`, and `histogram_sum` in Code mode.

If you send metrics through the OpenTelemetry Source, Cribl Search maps each OTLP metric type to one of these types, and translates OTLP metric and label names into Prometheus-compatible names. A metric can therefore appear in the Metrics Explorer under a different name than the one your collector sends. For details, see Supported OTLP Metrics.

Metrics Permissions

Access to metrics has two parts:

- Your Cribl Search Permission decides whether **Metrics** and **Monitors** appear at all. Members with the **User**, **Editor**, or **Admin** Permission can open both. Members with the **No Access** Permission on Cribl Search don't see either one.

- Your Dataset Permission on an individual metrics Dataset decides whether you can query it. **Read Only** is enough to query the Dataset and browse its metric catalog.

Reading metrics and changing them need different levels of Cribl Search Permission. Any Member who has a metrics Dataset shared with them can query it, browse its metric catalog, and view its alert activity. Editing metric metadata and creating, editing, and deleting Monitors also need the **Editor** or **Admin** Permission on Cribl Search, on top of access to every metrics Dataset involved.

Cribl Search auto-provisions a metrics Dataset for each lakehouse engine, so no Member owns one. Members with the **Admin** Permission on Cribl Search can access all of them. Members with the **User** or **Editor** Permission on Cribl Search only have access to the metrics Datasets that a Member with the **Maintainer** Permission shares with them.



If no metrics Dataset has been shared with you, Cribl Search can prompt you to create one, even though the lakehouse engine already created the Dataset that you can't yet access. See Cribl Search Asks You to Create a Metrics Dataset.

Ingest Metrics into Cribl Search

Before you can explore metrics, you need to get metrics into Cribl Search. Metrics are stored on a lakehouse engine, the same compute and storage that accelerates your logs.

1. Add a lakehouse engine to store and accelerate your metrics. See Lakehouse Engines in Cribl Search. You can change the default 365-day **Retention** period on the metrics Dataset in the Dataset configuration.
2. Add one of the Sources that support metrics, then point your upstream sender at it.
    - **Prometheus Remote Write**: Receives Prometheus metrics from a Prometheus client, or from the Prometheus Destination in Cribl Stream or Cribl Edge. See Ingest Prometheus Metrics into Cribl Search.
    - **OpenTelemetry**: Receives OTLP metrics, logs, and spans. Set **Store this source data as** to **Metrics** or **Both Logs and Metrics** to store the metrics it receives. See Ingest OpenTelemetry Data into Cribl Search.
    - **Cribl HTTP**: Receives native metric events from the Cribl Search Destination in Cribl Stream or Cribl Edge. Set **Store this source data as** to **Metrics** or **Both Logs and Metrics** on the Source, and **Send as** to **Metrics** or **Logs and Metrics** on the Destination. Produce the metric events upstream with a Pipeline - for example, with the Publish Metrics Function. See Ingest Cribl Stream/Edge Data into Cribl Search.
3. Route the metrics to the metrics Dataset you want them stored in. By default, a catch-all rule sends all metrics to the primary `metrics` Dataset. To target a different engine's Dataset, add a rule that matches the Source. See Route Metrics with Metric Rules.

Metrics is a Preview feature. Adding metrics to a production lakehouse engine can affect its performance. Until the impact is better understood, use one of these approaches:

- On a production engine, keep the metrics volume small.
- Give metrics a dedicated engine, so their load doesn't compete with production search. You can route a metrics Source to a dedicated engine with Metric Rules.

After your metrics are flowing, open the Metrics Explorer to explore them.

Open the Metrics Explorer

On the Cribl.Cloud top bar, select **Products** > **Search** > **Metrics**.

The Metrics view has two tabs:

- **Explore**: Build and visualize metric queries. This is the tab described on this page.
- **Summary**: A catalog and health view of every metric. See Explore the Metrics Catalog.

Build a Metrics Query

The Metrics Explorer lets you build a query visually, without writing a query language. After you choose a metric and a time range, Cribl Search returns a visualization of that data.

1. Select a **metrics Dataset** to query. Each lakehouse engine has its own metrics Dataset, so choose the one that holds the metrics you want. Your Metric Rules determine which Dataset that is. The list shows only the metrics Datasets you can access. See Metrics Permissions.
2. Select a **metric** from the catalog of metric names that Cribl Search maintains for all ingested data. You can pick any metric name with no perceptible latency. To find a metric in the catalog:
   - Use the **Filter metrics** box to narrow the list by name.
   - Use the type filter to show only **All**, **Counter**, **Gauge**, or **Histogram** metrics.
   - Sort the list by **Relevance**, **Value**, **Change**, **A → Z**, or **Z → A**.

   By default, the browser shows only metrics that currently have data.
3. Filter the metric's time series by one or more **dimensions** that apply to that metric. Dimensions are the key-value attributes attached to a metric, and are often called *labels* in other tools.
4. Choose a **transformation** to apply to the metric value before it is returned. Common transformations include:
   - `count`
   - `sum`
   - `avg`

    - `min`
    - `max`
    - `stddev`
    - `rate`

    This is a sample, not the full set - open the transformation dropdown to see every transformation available.

5. Adjust the time range with the timepicker, and optionally set the display timezone.

Split by Dimensions

To break a metric down into separate series, split it by one or more dimensions. Splitting by a dimension returns one series per value of that dimension, so you can compare those values.

Combine Metrics

Add more queries - labeled **A**, **B**, and so on - and combine them with an **expression** (a formula). For example, take the difference between two metrics, multiply one metric by another, or apply mathematical functions and constants.

Refine the Explorer View

The Explorer header has controls that apply to the whole page, not just a single query:

- **Scope**: Apply one or more dimension filters across every query on the page at once, instead of setting the same filter on each query. The button summarizes the active filters.
- **Pinned views**: Save the current Explorer setup and return to it later. The button shows how many views you have pinned.
- **Refresh**: Re-run all queries to pull the latest data.

View Results as a Chart or Table

Cribl Search returns your results either as a chart or as a table of numerical values. Switch between the two to suit your analysis.

When viewing a chart, choose the chart type - **Column**, **Line**, or **Area** - and adjust how the chart renders:


- **Logarithmic**: Plot the y-axis on a logarithmic scale, which helps when values span several orders of magnitude.
- **Fill gaps**: Connect the series across missing data points instead of showing breaks.

Edit the Query Expression

Select **Code** to switch from the visual builder to a query editor that shows the exact PromQL the builder generates. The visual builder and the Code editor stay in sync, so you can build a query visually and then read or refine the generated PromQL, or paste in raw PromQL from an external source.

Explore the Metrics Catalog

The **Summary** tab is a catalog and health view of every metric in the selected Dataset. Use it to see what metrics you have and to understand their **cardinality** - the number of unique time series a metric generates, which drives its storage footprint and query speed.



Metrics Summary

Select a metric, then its **Cardinality anatomy** tab, to see the series count broken down by label. Cribl Search classifies each label - for example, **ID-like**, **High-cardinality**, or **Constant** - and suggests whether to **drop**, **aggregate**, or **keep** it. Expand a label to see its top values.

A suggestion is a hint, not a rule. Keep a high-cardinality label when the per-value detail is worth it, or drop or aggregate it when you only chart the metric at a coarser grain.

The catalog supports two kinds of edit, and both need the **Editor** or **Admin** Permission on Cribl Search. Editing a metric's own metadata, such as its unit or description, also needs access to the metrics Dataset that the metric belongs to. Changing the cardinality band thresholds that classify every metric applies across your Organization, so it needs no Dataset Permission. See Metrics Permissions.

Share a Metrics Investigation

The Metrics Explorer URL captures your current query, selected metrics, filters, split-by dimensions, visualization settings, and time range. Copy the URL to bookmark, share, or reopen the same investigation without recreating the context by hand.

Take Action on a Query

On the Explore tab, the **(take action)** menu turns your current query into another Cribl Search object or exports it:

- **Add to Dashboard**: Add the query to a new or existing Dashboard as a metrics panel. See Add Metrics to Dashboards.
- **Add to Search notebook**: Add the query to a Notebook as a metrics cell. See Add a Metrics Cell.
- Start an **Investigation** from the query. See Investigations.
- Create a **Monitor** to alert on the query. See Monitors.
- Copy a shareable **URL**, or export the results to **CSV**.

Add to Dashboard and **Add to Search notebook** also need the **Maintainer** Permission on the target Dashboard or Notebook. Your access to metrics doesn't extend to the Dashboard or Notebook you add the query to. See Cribl Search Dashboards and Cribl Search Notebooks.

Query Metrics from Grafana

Each metrics Dataset exposes a Prometheus-compatible query endpoint. In Grafana, add this endpoint as a standard Prometheus data source to query your metrics. This is separate from the Cribl Search plugin for Grafana, which runs Cribl Search queries in Grafana - the metrics endpoint instead connects to Grafana as a native Prometheus data source. To import Grafana Dashboards into Cribl Search, see Migrate Grafana Dashboards.

To connect Grafana to a metrics Dataset:

1. In the metrics Dataset configuration, copy the **Prometheus compatible endpoint** URL. On the **Query API Access** tab, set the **Auth type** to **None** or **Basic**. For **Basic**, note the **Username** and **Password**.
2. In Grafana, select **Connections > Data sources > Add data source > Prometheus**.
3. In **Prometheus server URL**, paste the Prometheus compatible endpoint.
4. Match the Dataset's authentication: if the Dataset uses **Basic**, under **Authentication** select **Basic authentication** and enter the Username and Password from the **Query API Access** tab. If the Dataset's Auth type is **None**, leave authentication off.
5. Select **Save & test**.
6. Query your metrics with standard PromQL against the Dataset's metric names, for example `rate(http_requests_total[5m])`.

Member Permissions don't govern the Prometheus compatible endpoint. Access to it comes from the Dataset's **Query API Access** configuration, so removing a Member's Permission on the metrics Dataset doesn't close the endpoint for them. To restrict the endpoint, change its **Auth type** or rotate the **Basic** credentials.

Next Steps

- Ingest Prometheus Metrics into Cribl Search.
- Ingest OpenTelemetry Data into Cribl Search.
- Ingest Cribl Stream/Edge Data into Cribl Search.
- Add Metrics to Dashboards for a unified view of logs and metrics.
- Migrate Grafana Dashboards into Cribl Search.
- Create Monitors to get alerted when a metric crosses a threshold or behaves anomalously

3.1. Create Monitors In Cribl Search

Preview Feature

Cribl is still developing this Preview feature. We don't recommend using it in a production environment, because the feature might not be fully tested or optimized for performance, and related documentation could be incomplete.

Please continue to submit feedback through normal Cribl support channels, but assistance might be limited while the feature remains in Preview.

Get notified when a metric moves outside its expected range, using Monitors.

About Monitors

A Monitor watches a metric query and raises an **alert** when the metric meets a condition you define, such as crossing a threshold or behaving anomalously.

- A **Monitor** is what keeps watch - a metric query, its detection method, thresholds, and firing conditions.
- An **alert** is the recorded moment a Monitor's condition was met.
- A **Notification** delivers that alert to where your team works, such as email, Slack, or a webhook.

Monitors are part of the Metrics experience. To explore and visualize metrics before you alert on them, see Explore Metrics in Cribl Search.

During Preview, some routing and suppression controls are not yet wired up - the sections below call out what is coming soon.

Monitor Permissions

Viewing a Monitor needs read access to every metrics Dataset that the Monitor evaluates. Creating, editing, and deleting Monitors needs that same read access, plus the **Editor** or **Admin** Permission on Cribl Search.

Members with the **Admin** Permission on Cribl Search can manage Monitors on any metrics Dataset. Members with the **Editor** Permission can manage Monitors only on the metrics Datasets that a **Maintainer** has shared with them. Members with the **User** Permission can view those Monitors and their alerts, but can't change them. For details, see Metrics Permissions.

Open Monitors

On the Cribl.Cloud top bar, select **Products** > **Search** > **Monitors**.

The list shows only the Monitors whose queries all read metrics Datasets you can access. A Monitor on a Dataset you can't access is hidden rather than shown as locked, so two Members can see different Monitors in the same Organization.

From the Monitors list, you can:

- Search and filter your Monitors.
- Enable or disable a Monitor with its row toggle.
- Select Monitors for bulk actions.
- Select **Add Monitor** to create one, or select an existing Monitor to edit it.

Build a Monitor

The **Monitor** page has a live preview chart at the top. Expand the sections below the chart to configure your Monitor settings.

- Turn **Simulate on past data** on to preview how the Monitor would have behaved against recent data.
- Use the **Enabled** toggle in the header to turn the Monitor on or off, then select **Save**.

Configure the Monitor in these sections:

1. Detection Method: choose how the Monitor fires.
2. General: name the Monitor and set its priority and team.
3. Query: choose the metric and shape the query.
4. Thresholds: map values to severities.
5. Metadata: attach key-value labels to alerts.
6. Firing Conditions: control how long a condition must hold.
7. Notifications: decide how alerts are delivered.

When you edit an existing Monitor, the page splits into a **Configure** tab and an **Activity** tab. See View Alert Activity.

Detection Method

The **Detection Method** determines how the Monitor decides to fire an alert. Select one:

Method	Fires when
Threshold	Metrics cross defined thresholds.

Method	Fires when
Change	The difference between a value N minutes ago and now.
Anomaly	A metric behaves anomalously based on historical data.
Forecast	A metric is projected to cross a threshold.

General

- **Name**: a unique name for the Monitor. Required.
- **Description**: a short note on what the Monitor checks and why it matters.
- **Priority**: the urgency of the Monitor: **P1 (Critical)**, **P2 (High)**, **P3 (Medium)**, **P4 (Low)**, **P5 (Info)**, or **Not defined**.
- **Team**: the team that owns the Monitor.

Query

The **Query** section defines what the Monitor evaluates. You can build the query visually or write PromQL directly.

Visual builder:

- **Metric**: the base metric to evaluate.
- **Label filters**: narrow the series with key-value matchers. Operators are `=`, `!=`, `=~` (regex), and `!~` (regex not).
- **Aggregation**: how samples roll up over the window: `count`, `avg`, `sum`, `min`, or `max`.
- **Group by**: one or more labels to evaluate as separate series.
- **Evaluation window**: the rolling lookback, such as `5m` or `1h`.

PromQL:

- Enter PromQL directly in the query editor.
- Use `$variable` in the query to add **template parameters**. Cribl Search shows a **Resolved Query** preview with the parameter values filled in.

You can add more than one query, labeled **A** through **D**, and give the Monitor a **Units** value (such as seconds, bytes, or count) so charts and thresholds read correctly.

When a Monitor has more than one query, or when a query reads a different metrics Dataset than the Monitor's default, you need read access to every metrics Dataset the Monitor evaluates. Cribl Search rejects a Monitor that reads a metrics Dataset you can't access, and doesn't save it. See Monitor Permissions.

Thresholds

Thresholds map evaluated values to severities in a **Default Rule**. For each row, configure:

- **Severity**: **Critical**, **Warning**, or **Info**.
- **Operator**: **greater than**, **greater than or equal**, **less than**, **less than or equal**, **equal to**, or **not equal to**.
- **Threshold**: the numeric value to compare against.
- **Times Triggered**: the number of consecutive evaluations the condition must hold before the alert fires. The minimum is 1.

Select **Add severity** to add a row (up to six). Turn on **Show on Chart** to draw the threshold on the preview chart.

Use **Included Tags** and **Excluded Tags** to scope the rule to specific series.

Metadata

Add arbitrary key-value pairs, such as `env=prod` or `team=platform`. These become labels on every alert the Monitor generates, so Notification policies and templates can use them for routing and formatting.

Firing Conditions

Firing Conditions control how long a condition must hold before an alert opens or clears. This is how Monitors avoid alert flapping when a metric hovers around a threshold.

- **Fire delay**: how long the condition must stay true before the alert fires.
- **Clear delay**: how long the condition must stay healthy before the alert clears.

Both accept **Immediate**, **1 minute**, **5 minutes**, **10 minutes**, **15 minutes**, **30 minutes**, or **1 hour**. Set the Clear delay together with **Times Triggered** to smooth out noisy metrics.

Notifications

Choose how alerts are delivered:

- **Route via Notification Policies**: route alerts by matching their labels against shared policies. Policies are evaluated top-down, and each matching policy processes the alert until a **final** policy ends routing.
- **Select Specific Notification Target**: send directly to a chosen target, bypassing policies.

To create and manage the Targets, Templates, and Policies that these options use, see Manage Monitor Notifications.

Mute a Monitor

Muting suppresses a Monitor's Notifications during a planned window, such as scheduled maintenance, without disabling the Monitor or losing alert history.



During Preview, **Add Muting Rule** is coming soon on Cribl Search Monitors. The button appears on the Monitor page but is not yet active. For Insights Alerts, see Muting Rules.

View Alert Activity

When you edit a Monitor, the **Activity** tab shows its history, so you can review when it fired and how it changed over time. The Alerts area also has an **Activity** tab across all Monitors.

Alert activity follows the same access rules as the Monitors list, so you see activity only for the Monitors you can access. History isn't available for a deleted Monitor, because Cribl Search no longer has a configuration to check your access against.

Next Steps

- Explore Metrics in Cribl Search
- Add Metrics to Dashboards
- Ingest Prometheus Metrics into Cribl Search

3.2. Manage Monitor Notifications

Preview Feature

Cribl is still developing this Preview feature. We don't recommend using it in a production environment, because the feature might not be fully tested or optimized for performance, and related documentation could be incomplete.

Please continue to submit feedback through normal Cribl support channels, but assistance might be limited while the feature remains in Preview.

Manage the Targets, Templates, and Policies that deliver Monitor alerts, from one place.

About Monitor Notifications

When a Monitor triggers an alert, a **Notification** delivers that alert to where your team works, such as email, Slack, or a webhook. The **Notifications** area centralizes the three building blocks that shape and route those Notifications:

- A **Target** is a delivery method, such as a Slack channel, a webhook endpoint, or an email recipient.
- A **Template** defines the content of a Notification, using a Handlebars template.
- A **Policy** routes an alert to one or more template-and-target pairs, based on conditions that match the alert's labels.

A Monitor can route its alerts either through Policies or directly to a specific Target. See Notifications on the Monitor page.

Cribl Search has two notification experiences. This page covers Notifications for Monitors. To alert on scheduled searches instead, see Notifications. The two experiences share the same Notification Targets, so a Target you create here is also available to scheduled searches, and the reverse. Templates and Policies apply only to Monitors.

Open Monitor Notifications

On the Cribl.Cloud top bar, select **Products** > **Search** > **Monitors**, then select the **Notifications** tab. A left sidebar exposes three sub-tabs: **Targets**, **Templates**, and **Policies**.

Every Member with a Cribl Search Permission can view all three sub-tabs, but write access differs by sub-tab. Where you can view a sub-tab without writing to it, the **Add**, **Edit**, and **Delete** controls are disabled and the row action shows **View** instead of **Edit**. See Permissions.

Targets

A Target specifies how and where to deliver a Notification. The **Targets** tab lists every Target with these columns:

Column	Description
Target name	The Target ID, with a health indicator (**Green**, **Red**, or **Unknown**).
Type	The Target type.
Usage	How many Policies and Monitors reference this Target.
Last Updated	The time of the Target's most recent health check.
Actions	**Edit** (or **View**) and a **Delete** menu.

Target Types

You can create and edit these Target types:

- **Webhook**
- **Slack**
- **PagerDuty**
- **SNS**
- **Email (SMTP)**

Cribl Search also manages some Targets automatically. These appear in the list but you can't create or edit them: **Bulletin Message**, **Default**, **Router**, and **Notifications Log**. The built-in `system_notifications` and `system_email` Targets are view-only, so you can't edit or delete them.

Add a Target

1. On the **Targets** tab, select **Add Notification Target**.
2. Give the Target a unique **Target ID**.
3. Select the **Target type**, then configure the fields for that type.
4. Select **Create Target**.

To change a Target, select its name or the **Edit** action, adjust the fields, then select **Update Target**.

Delete a Target

Select the **Delete** action on a Target's row, or select multiple Targets and use the bulk **Delete** control. Cribl Search prevents deletion in these cases:

- The Target is a system-managed Target: **System targets can't be deleted**.
- The Target is referenced by a Policy or Monitor: **In use by a policy or monitor**.

Templates

A Template defines the content of a Notification. The **Templates** tab lists every Template with these columns: **Template name**, **Type**, **Usage**, **Last Updated**, **Created By**, and **Actions**.

Templates marked with a **Default** tag are supplied by Cribl Search. You can view and clone them, but you can't edit or delete them.

Template Fields

- **Template ID**: a unique identifier for the Template. Required. You can't change it after you create the Template.
- **Description**: an optional note about the Template.
- **Target type**: the Target type this Template formats content for, one of **Webhook**, **Slack**, **PagerDuty**, **SNS**, or **Email (SMTP)**. Required. You can't change it after you create the Template.
- **Content**: the Notification body, written as a Handlebars template and edited in an inline code editor. Required.

Cribl Search validates the **Content** field as Handlebars. If the field is empty, you see **Template content is required**. If the syntax is invalid, you see **Invalid Handlebars template syntax**.

Add a Template

1. On the **Templates** tab, select **Add Notification Template**.
2. Enter a **Template ID**, and optionally a **Description**.
3. Select the **Target type**.
4. Write the **Content** in the editor.
5. Select **Create Template**.

To reuse an existing Template as a starting point, select its **Clone** action. To review a Template without changing it, select **View**.

Delete a Template

Select the **Delete** action, or select multiple Templates and use the bulk **Delete** control. Cribl Search prevents deletion in these cases:

- The Template is a default Template: **Default templates can't be deleted**.
- The Template is referenced by a Policy or Monitor: **In use by a policy or monitor**.

Policies

A Policy routes an alert to one or more template-and-target pairs when the alert's labels match the Policy's conditions. The **Policies** tab lists every Policy in evaluation order, with these columns:

Column	Description
ID	The Policy ID, with a number that shows its position in the evaluation order.
Routing	Whether the Policy is **Final**. A final Policy ends routing for a matching alert.
Description	A summary in the form **If** `<conditions>` **then send to** `<target → template pairs>`.
Actions	**Edit** (or **View**) and a **Delete** menu.

Policies are evaluated top-down. To change the order, drag a Policy's handle to a new position.

Conditions

A Policy's conditions are grouped. Within a group, all conditions must match (**AND**). A Policy matches if any group matches (**OR**). A Policy with no conditions matches every alert, shown as **all**.

Build conditions with these controls:

- **Add Label**: add a condition to the current group.
- **Add Label Group**: add another **OR** group.

Each condition has a key, an operator, and a value. The operators are `=`, `!=`, `=~` (regex), and `!~` (regex not) - the same operators as a Monitor's Query label filters. Cribl Search suggests keys and values from your Monitors' labels, drawn from Monitor metadata, PromQL label filters, and threshold tags.

Template-and-Target Pairs

Each Policy sends matching alerts to one or more pairs, each of which combines a Template with a Target. The **Description** column shows each pair as `target → template`. A pair with a missing Target or Template appears in red.

Add a Policy

1. On the **Policies** tab, select **Add Notification Policy**.
2. Enter a unique **Policy ID**.
3. Define at least one condition group. Each condition requires a key.
4. Add at least one template-and-target pair. Each pair requires both a Target and a Template.
5. Optionally turn on **Final** to stop routing at this Policy for matching alerts.
6. Select **Save**.

Preview Policy Matches

To check which Policies a set of labels would match, turn on the **Preview** toggle. Cribl Search then shows:

- A label selector where you choose the labels to test.
- A **Generate Labels from Monitor** button that fills the selector with labels from one of your Monitors.
- A **Status** column that marks each matching Policy, and condition tags that turn green when they match.

Permissions

Every Member with a Cribl Search Permission can open all three sub-tabs and view the Targets, Templates, and Policies in them. Write access differs by sub-tab:

Sub-tab	Who can add, edit, and delete
Targets	Search **Admins** and Organization **Owners**. See who can add Targets.
Templates	Search **Admins**.
Policies	Search **Admins**. Reordering Policies also needs the **Admin** Permission.

Where you can't write, Cribl Search shows **View** in place of **Edit** and disables the **Add** and **Delete** controls. You can still open each resource and read its configuration.

Managing a Monitor is governed separately, by your Cribl Search Permission together with your access to the metrics Datasets that the Monitor evaluates, rather than by these Notification Permissions. See Monitor Permissions.

Credential Fields on Targets

If you can't create Notification targets, Cribl Search omits the connection and credential fields from a target before showing it to you. It leaves the fields out of the response altogether, rather than masking their values, so the form renders them as empty. The affected fields are the Target's URL, routing key, host, port, username, password, token, secret, login URL, and extra HTTP headers. The Target still appears in the list with its name, type, health, and usage. This applies wherever you read a Target, including from Monitors and the API.

If a Target's fields look blank when you open it, check whether you have the **Admin** Permission on Cribl Search before you assume the Target is misconfigured.

Next Steps

- Add Notifications to a Monitor
- Explore Metrics in Cribl Search

3.3. Add Metrics To Dashboards

Preview Feature

Cribl is still developing this Preview feature. We don't recommend using it in a production environment, because the feature might not be fully tested or optimized for performance, and related documentation could be incomplete.

Please continue to submit feedback through normal Cribl support channels, but assistance might be limited while the feature remains in Preview.

Add metrics panels to your Dashboards so you can correlate metrics and logs in a single view.

About Metrics Panels

A metrics panel is a Dashboard panel backed by a metrics query instead of a log search. You add, edit, hide, rearrange, and delete metrics panels the same way you manage other panels. You can mix metrics panels and log panels on the same Dashboard.

Metrics panels support the same visualization types as other panels, such as line, bar, area, and table, along with format options such as units, thresholds, and axis labels. They also follow the Dashboard time range, auto-refresh, and shared crosshairs.

Add a Metrics Panel

You can add a metrics panel in two ways:

- **From a Dashboard**: Create a new panel and choose a metrics query as its source.
- **From the Metrics Explorer**: Build a query in Metrics, then save it to a new or existing Dashboard. Your split-by dimensions are preserved as a trellis breakdown on the resulting panel.

Inside a Dashboard | From Metrics Explorer

1. Open an existing Dashboard or create a new one.
2. Select **Edit**, then **Add > Visualization**.
3. Choose a metrics query as the panel source, then build the query as you would in the Metrics Explorer.
4. Select **Search**, then configure the visualization.

For layout, Inputs, and other panel controls, see Edit a Dashboard.

Open a Panel in the Metrics Explorer

To investigate or refine a metrics panel further, select the panel's Actions ⋯button, then **Open in Metrics**. Cribl Search opens that panel's query in the Metrics Explorer, with its filters, split-by dimensions, visualization options, and time range already applied, so you can drill down without rebuilding the query by hand. This action is available for every metrics panel.

Next Steps

- Explore Metrics in Cribl Search.
- Add a Metrics Cell to a Notebook.
- Create a Dashboard.
- Edit a Dashboard.

4. Connect Cribl Search To External Data

Link Cribl Search to where your data lives, so you can run federated search-in-place queries without moving or indexing the data.

Apart from ingesting data into high-speed lakehouse engines, Cribl Search can also connect directly to a wide array of federated Dataset Providers. This lets you run federated searches without moving or indexing the data.

To start searching, set up a Dataset Provider and a Dataset. For that, you need to be a Cribl Search **Editor** or **Admin**.

Add a Dataset Provider

A Dataset Provider tells Cribl Search where to send federated queries and contains access credentials. To start adding a new one, go to **Data** > **Dataset Providers** > **Add Provider**.

For detailed instructions on how to set up each Dataset Provider type, follow the relevant link from the list of supported data sources.

Add a Dataset

A Dataset tells Cribl Search what data to search from the Dataset Provider. To start adding a new one, go to **Data** > **Datasets** > **Add Dataset**.

For detailed instructions on how to set up each Dataset type, follow the relevant link from the list of supported data sources.

List of Supported Federated-Search Providers

Federated search offers native support for the data sources listed below. Follow the links to learn how to set up each one:

- Amazon S3
- Amazon Security Lake
- AWS API
- Azure API
- Azure Blob Storage
- Azure Data Explorer
- ClickHouse
- Cribl Edge

- Cribl Lake / Lakehouses
- Cribl Stream's "Data Lake Amazon S3" Destination
- CrowdStrike NG-SIEM
- Elasticsearch
- Google Cloud Platform API
- Google Cloud Storage
- Google Workspace API
- Generic HTTP API
- Microsoft Graph API
- Okta API
- OpenSearch
- Prometheus
- Snowflake
- Tailscale API
- Zoom API

If there's no native support for your data source type, there still might be ways to connect to your data. You can set up a Generic HTTP API Dataset, use the `externaldata` operator, or reach out to Cribl Support for finding a solution.

Connect Cribl Search to Other Cribl Products

Cribl Search seamlessly integrates with Cribl Stream, Cribl Edge, and Cribl Lake (with or without Lakehouses), as they're all part of your Cribl.Cloud Organization. In most cases, you can start searching your data right away. For more information, see the pages listed below.

Cribl Edge:

- Connect to Cribl Edge
- Built-In Cribl Edge Datasets
- Searching Cribl Edge Data

Cribl Lake:

- Connect to Cribl Lake
- Searching Cribl Lake
- Search a Lakehouse

4.1. Connect Cribl Search To Cribl Lake

Configure Cribl Search to query your Cribl Lake or Lakehouse data.

Cribl Lake Datasets work as Cribl Search Datasets out-of-the-box, so you can instantly start searching them.

You can assign Lake Datasets to Lakehouses, for dramatically faster search responses and more-predictable billing.

Where you need direct ownership of your data, for compliance or other purposes, you can use Storage Locations to create Lake Datasets directly on Amazon S3 or Azure Blob Storage. You can choose the storage class or access tier that Cribl Lake uses when writing objects; S3 Datasets default to the Standard storage class, and Azure Datasets default to the Inferred access tier.

For more information on Lake and Lakehouses, see the Cribl Lake docs.

Federated Search: Dataset Types v1 and v2


Lake-backed Search uses **Dataset Type v1** or **v2** on a **Federated Dataset** tied to the Lake Dataset Provider (`cribl_lake` or equivalent). Dataset Type **v2** supports newline-delimited JSON, Parquet, and DDSS objects in Lake storage.

Use Dataset Type and Datatypes for Lake Datasets for configuration steps. For limits and migration, see federated search v2.

Add a Cribl Lake Dataset Provider

Cribl Search comes with a preconfigured Dataset Provider for Cribl Lake (called `cribl_lake`), so you don't need to add it explicitly.

You can see it by going to **Products** (on the top bar) > **Search** > **Data** > **Dataset Providers**.



Cribl Search Dataset Provider interface

Add a Cribl Lake Dataset

Create the Lake Dataset in the Cribl Lake UI first. See Create a New Lake Dataset.

In Cribl Search, add or select the matching **Federated Dataset** to set **Dataset Type** and, on **Type v2**, the Datatype for each data format. See Dataset Type and Datatypes for Lake Datasets.

Dataset Type and Datatypes for Lake Datasets

Add or Edit a Lake Dataset

1. Select **Products** > **Search** > **Data** > **Datasets**.
2. Select an existing Lake-backed Dataset, or select **Add Dataset** to create one.
3. Under Dataset kind, select **Federated Dataset** (for data hosted in Cribl Lake).
4. Set **Dataset Provider** to your Lake provider.

Set Dataset Type (v1 or v2)

Set **Type** to **v1** or **v2**.

To switch an existing Lake Dataset to **Dataset Type v2**, change **Type** to **v2** on that Dataset, set a Datatype for each data format, then select **Save**. Lake Datasets can't be cloned. See Switch a Federated Dataset from v1 to v2.

Configure Datatypes for v2 Datasets

Lake Datasets don't use the **Filters** table that Amazon S3 and Azure Blob Storage Datasets use. Cribl Search already knows how Cribl Lake lays out and names objects, so a Lake Dataset has no **Bucket path**, **Region**, **Partitioning scheme**, or **Filter** glob to set.

Instead, when you set **Type** to **v2**, Cribl Search shows a **Datatypes** table. Each row pairs:

- **Data Format**: Read-only. This is the storage format of the Lake Dataset: `JSON`, `Parquet`, or `Splunk DDSS`.
- **Datatype ID**: A drop-down that lists only the Datatypes that can parse that data format.

Cribl Search adds the first row for you, based on the Lake Dataset's own storage format:

- **JSON** Lake Dataset: Data Format `JSON`, defaulting to the `generic_ndjson` Datatype.
- **Parquet** Lake Dataset: Data Format `Parquet`, defaulting to the `cribl_lake_parquet` Datatype.
- **DDSS** Lake Dataset: Data Format `Splunk DDSS`, defaulting to the `splunk_journal` Datatype. See Dataset Type v2 and DDSS.

You can change **Datatype ID** on any row, including to a clone of the stock Datatype.

If a JSON or Parquet Lake Dataset holds both formats, select **Add Data Formats** and choose the other format. This adds a second row, which is the maximum. You can delete the added row, but not the row that matches the Lake Dataset's own storage format.

Select **Save**.

For Parquet-backed events, Cribl Search reads `_time` from the column named in the Datatype's timestamp extraction settings. The stock `cribl_lake_parquet` Datatype reads the `_time` column. Other Parquet columns become event fields of the same name, including `host` and `sourcetype`.

Columns whose names collide with a Cribl Search reserved field (`_raw`, `_time`, `source`, `dataset`, or `datatype`) appear with a `data_` prefix. For example, a Parquet column named `source` becomes `data_source`, because the event's own `source` field holds the path of the Lake object that contains the event.

Dataset Type v2 and DDSS

DDSS Lake Datasets support **Dataset Type v2**. Because Cribl Search discovers Splunk journal files structurally, the **Datatypes** table shows a single row with the **Data Format** `Splunk DDSS`:

1. Set **Type** to `v2`.
2. Set **Datatype ID** to the stock `Splunk Journal` Datatype, `splunk_journal`, or to a clone of that Datatype. The drop-down lists only Datatypes that use the Splunk Journal data format.

3. Select **Save**.

A DDSS Lake Dataset has no **Add Data Formats** button, so you can't add a second data format row. For the Lake Dataset itself, see Splunk Cloud Self Storage (DDSS) Direct Access.

Send Cribl Search Results to Cribl Lake

After you create a Dataset in Cribl Lake, you can send Cribl Search results to it, using the `export` operator. Here is a simple example:

```
// export Cribl Search results to an existing Lake Dataset
dataset="cribl_search_sample"
| export to myLakeDataset
```

Copy

(You can find more `export` examples here.)

Typically, you're exporting data in which Cribl Search has already parsed field names and values. This makes the data compatible with Lakehouses. However, if you happen to send **unparsed** data, you won't be able to search it at Lakehouse speed.

Search a Cribl Lake Dataset

You can query your Lake Datasets just like any other Search Datasets. See Searching Cribl Lake for some query examples.

Search a Lakehouse

Searching a Lake Dataset that's linked to a Lakehouse is significantly faster, as long as your query's time range falls within the configured Lakehouse retention period.

Queries that access older data (still stored in the Dataset, but aged out of the Lakehouse) will run at standard search speed.

To create a new Lakehouse, see the Cribl Lake docs: Add a New Lakehouse.

See how to:


- Find Out if a Dataset is Linked to a Lakehouse
- Verify Lakehouse Use

- Search Multiple Lakehouse Datasets
- Disable Lakehouse Use

See also: Cribl Search Differences with Lakehouse.

Find Out if a Dataset is Linked to a Lakehouse

To see if a Dataset you're about to search is linked to a Lakehouse or not, look for the icon. For example, look at the list of available datasets in your **Search Home**:



A Dataset linked to a Lakehouse

You can also go to **Products** (on the top bar) > **Search** > **Data** > **Datasets** and look at the **Lakehouse** column.

Verify Lakehouse Use

To find out whether a search successfully used a Lakehouse, take a look at the tracking bar.

If the search failed to use a Lakehouse, the bar presents information about potential reasons.

Search Multiple Lakehouse Datasets

You can run a single query against multiple Lakehouse-assigned Datasets. For the query to execute at Lakehouse speed, all Datasets in the query must be Lakehouse-assigned, and your query must also meet one of these conditions:

- Include only operators from the following group: `cribl`, `centralize`, `extend`, `extract`, `foldkeys`, `limit`, `mv-expand`, `pivot`, `project`, `project-away`, `project-rename`, `search`, and `where`.
- Or, if you use any other operators, insert the `centralize` or `limit` operator before them. (Result counts will be further constrained by usage group limits.)

If neither of the above conditions is met, or if your query includes non-Lakehouse Datasets, the query will run at standard speed.

Disable Lakehouse Use

You can use a `set` statement with the `lakehouse` option to control whether a query can use a Lakehouse or not.

For example, to test how a Dataset linked to a Lakehouse performs without it:

```
set lakehouse="off" dataset="lakehouse_dataset"
```

4.2. Connect Cribl Search To Amazon S3

Configure Cribl Search to query your Amazon S3 data.

Amazon Simple Storage Service (Amazon S3) is an object storage service that allows you to store and retrieve data from anywhere.


In this guide, you'll set up a Dataset Provider and a Dataset to search objects in your Amazon S3 bucket.

Data transfer costs and other charges may apply. For cost and compatibility details, see the Data Transfer Charges and Storage Class Compatibility sections below.

Add an Amazon S3 Dataset Provider

A Dataset Provider tells Cribl Search where to query and contains access credentials. Here, you will add an Amazon S3 Dataset Provider.

To add a new Dataset Provider, select **Data**, then **Dataset Providers**, then **Add Provider**.



S3 Dataset Provider configuration

Basic Configuration

Configure the **New Dataset Provider** modal as follows:

1. **ID** is a unique identifier for the Dataset Provider. This is how you'll reference it when assigning Datasets to it. Start the ID with a letter; the rest of the ID can use letters, numbers, (for example, `my_dataset_provider_1`)
2. **Description** is optional. Here, you can enter a summary that will clarify this Dataset Provider's purpose to other users.
3. Set the **Dataset Provider type** to `Amazon S3`.
4. **Authentication method** provides two options, **Assume Role** and **AWS keys**. For details on configuring each option, see Authentication Method below.

Advanced Settings

This section provides the following optional configurations:

- **Endpoint**: S3 service or compatible endpoint. If empty, defaults to AWS Region-specific endpoint.
- **Signature version**: Signature version to use for signing S3 requests. Defaults to `v4`.
- **Reuse connections**: Whether to reuse connections between requests. Toggling on (default) can improve performance.
- **Reject unauthorized certificates**: Whether to reject certificates that cannot be verified against a valid Certificate Authority (for example, self-signed certificates). Defaults to toggled on.
- **Apply ABAC source-ip tagging**: Displayed only if you've set the **Authentication method** to **AssumeRole**. For details, see ABAC Tagging below.

Wrapping Up

Select **Save** when your configuration is complete.

Authentication Method

Your choices here are **AssumeRole** or **AWS keys**. For rich details on both options, beyond the configuration basics in this section, see Grant Access to AWS.

AssumeRole Authentication

Selecting **AssumeRole** requires the IAM role's ARN (**AssumeRole ARN**), and also exposes the following options:

- The **External ID** on this Dataset Provider must match the external ID defined in the IAM Role Trust Policy.
- The **Duration (seconds)** defines how long the AssumeRole's session lasts. Minimum is `900` (15 minutes), default is `3600` (1 hour), and maximum is `43200` (12 hours).
- The ABAC tagging controls described in the next section.

To the right, select the **Trust Policy** and **Permission Policy** buttons to see the default policies that you can copy and expand, so you don't have to write them from scratch. For more information, see Example Trust Policy and Expand the Permission Policy.

AWS Keys Authentication

Selecting **AWS keys** requires the IAM user's **Access key** and **Secret key**.

To the right, select the **Permission Policy** button to see the default policy that you can copy and expand, so you don't have to write it from scratch. For more information, see Expand the Permission Policy.

ABAC Tagging

Select **Apply ABAC source-ip tagging** if you want to make your AssumeRole sessions more secure by enabling attribute-based access controls (ABAC). By enabling this option, you can hard-code Cribl's Virtual Private Cloud Endpoint (VPCE) into your IAM trust policy.


Selecting this option exposes **VPC Endpoint IDs** for all supported Regions. Use the adjacent **Copy** buttons to transfer all the VPCE IDs to your IAM permission policy, as shown in Expand the Permission Policy.

Completing both parts of this configuration will make your credentials harder to impersonate. Specifically, your AssumeRole sessions will include a `source-ip` tag, enabling you to enforce a condition that `aws:RequestTag/source-ip` equals `${aws:SourceIp}`. Also, you can enforce that `aws:SourceVpce` matches one of the allowed VPC Endpoint IDs.

Add an Amazon S3 Dataset

Now you'll add a Dataset that tells Cribl Search what data to search from the Dataset Provider.

To add a new Dataset, select **Data**, then **Datasets**, then **Add Dataset**.



Set the Dataset type to **Federated Dataset**, and configure the following settings.

Identify the Dataset

Use the first few fields to uniquely identify this Dataset and specify its type:

1. **ID** is an identifier unique for both Cribl Search and Cribl Lake. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_1`). You'll use this to specify the Dataset in a query's scope, telling Cribl Search to search the Dataset (for example, `dataset=my_dataset_1`).
2. **Description** is optional. Here, you can enter a summary that will clarify this Dataset's purpose to other users.
3. Set **Dataset Provider** to the **ID** of an Amazon S3 Dataset Provider.
4. Set **Type** to **v1** (standard, the default) or **v2**. v2 Datasets support faster search and require NDJSON, Delimited Text, Parquet, or Splunk Journal format. If you select v2, see v2 Dataset Configuration for the remaining steps.

v2 Dataset Configuration for S3



If you're switching from v1 to v2, first see federated search v2 to see what's currently supported.

For v2 Datasets, configure the following fields:

1. **Bucket path** is the path to the S3 bucket and objects you want to search. Supports templating (for example, `mybucket/${fieldA}/${fieldB}`). For details, see Amazon S3 Bucket Paths.
2. **Filters** narrow the search to specific objects and map them to a Datatype. Add one or more filter rows. Each row has:
   - **Filter**: A glob expression (for example, `**` for all objects, or `**/*.ndjson` for NDJSON files).
   - **Datatype ID**: The Datatype for matching files. Use **Cribl NDJSON** (`generic_ndjson`), a Delimited Text Datatype, a Parquet Datatype, or **Splunk Journal** (`splunk_journal`). For Splunk journal files, see Search Splunk Journal Files.
3. The **Partitioning scheme** defaults to `Defined in Path`. Select `Splunk DDSS` or `Splunk SmartStore` if Splunk wrote the bucket layout. See v2 Datasets and Splunk Partitioning.
4. Toggle off **Auto-detect region** if you want to use the **Region** drop-down to specify where the bucket is located.
5. Select **Save** when finished.

v2 Datasets and Splunk Partitioning

When you select `Splunk DDSS` or `Splunk SmartStore` on a v2 Dataset, Cribl Search replaces the **Filters** table with a single **Datatype** drop-down. That drop-down lists only Datatypes that use the Splunk Journal data format. Set **Bucket path** to your index's parent folder. Cribl Search then traverses the Splunk layout and discovers the journal files itself.

For the path formats and the differences from v1, see Amazon S3 Partitioning Schemes and Splunk DDSS and SmartStore Buckets.

Glob Patterns

The path filter supports using glob patterns when indicating the path. The following glob patterns are available.

Pattern	Matches
`*`	Matches one path segment (any sequence of characters except `/`).
`?`	Matches any single character except `/`.
`**`	Matches any sequence of characters except `{` and `}`, but including `/`. Can match multiple segments, but not brace syntax.
`{a,b,c}`	Matches one of the comma-separated alternatives provided in the braces. Alternatives must not contain `{`, `}`, `*`, or `,`.
`{M..N}`	Matches a numeric range of non-negative integers. Examples: `{0..9}`, `{10..99}`. Leading zeros are supported (for example: `{001..099}`).

Negations

You can negate brace content by using `!`, for example:

- `!{a,b,c}` — path must not match any of the alternatives.
- `!{0..9}` — path must not match the numeric range.
- `!{foo}` — path must not match the literal `foo`.
- `*!{...}` - path matches anything that does not match the provided suffix.

Escaping

`\` (backslash) is the escape character for glob patterns. `\!{` matches a literal `!{` in the path (for example, a directory named `!{temp}`).

Set Up Paths, Regions, Partitioning

For v1 Datasets, define at least one path, Region, and partitioning configuration:

1. **Skip event time filter** is optional. Toggle this on only if you're sure you want to set the time range of your searches by partition time-boundaries rather than events' timestamps
2. **Bucket path** is the path to the S3 objects you'd like to search. Start the path with the bucket name, and then add partitioning details. Tokens and key-value pairs are supported (see Amazon S3 Bucket Paths).
3. Toggle off **Auto-detect region** if you want to use the adjacent **Region** drop-down to specify where the S3 bucket is located. When toggled on, Cribl automatically detects the Region and locks the drop-down.
4. **Path filter** is a JavaScript filter expression that is evaluated against the S3 bucket path. Defaults to `true`, which matches all data, but you can customize this value.
5. The **Partitioning scheme** defaults to `Defined in Path`. For Splunk-specific alternatives (and corresponding options), see Amazon S3 Partitioning Scheme.

Multiple Path Configs

Select **Add bucket/path** to define as many other path configurations as you want for this Dataset. Each path can have its own filter, Region, and partitioning scheme.

As with parallel Datasets, each partitioning scheme applies per path. When searching a Dataset, Cribl Search will search all its configured paths. However: **a failed search on any of a Dataset's paths will fail the whole search.**

Set Up Datatypes and Storage Classes

On the **Processing** left tab, you specify **Datatypes** to break data down into discrete events and define fields so they're ready to search.

Use a v2 Datatype for Amazon S3 Datasets when your data is NDJSON, Delimited Text, Parquet, or Splunk Journal. For other formats, use v1 Datatypes. For details, see Datatypes.

On the **Storage classes** left tab, select the storage classes that you want this Dataset to search against. You can minimize retrieval costs by selecting only warmer classes. You must select at least one class. For details, see Storage Classes.

Save the Configuration

Bypass the **Usage** left tabs for now, and select **Save** when your configuration is complete.

Path/Partitioning Considerations

This section offers details and guidance on configuring search paths, filters, and partitioning schemes. For best practices covering path design across all object stores, see Optimize Paths.

Amazon S3 Bucket Paths

Each **Bucket path** specifies a separate bucket of data within the Dataset. It defines the scope of this data, to narrow down what data is in the Dataset. This field supports tokens and key-value pairs. For example:

- `my-bucket/${data}/` - where `data` becomes a field for all events of that Dataset.
- `my-bucket/${data}/${*}` - equivalent, the wildcarded path is skipped.
- `my-bucket/<key=value>/<someVarOfInterest>` - see Hive-Style Paths just below.
- `my-bucket/<path>/${_time:%Y}/${_time:%m}/${_time:%d}/${_time:%H}/` - time-based partitioning.

Hive-Style Paths

To search paths of the form `my-bucket/<key=value>/<someVarOfInterest>`, your expression should place the wildcard `{*}` in the ordinal position, to ignore the hive (K-V) segment:

```
my-bucket/${*}/${someVarOfInterest}
```

This will allow Cribl Search to find the wildcarded subdirectory automatically.

Basic Tokens

Basic tokens' syntax follows that of JS template literals: `${token_name}` - where `token_name` is the field (name) of interest.

For example, if the path was set to `/var/log/${hostname}/${dataSource}/`, you could use a filter such as `hostname=='myHost' && dataSource=='mydataSource'` to specify data only from the `/var/log/myHost/mydataSource/` subdirectory.

Time-Based Tokens

Paths with time notation can be referenced with tokens, having a direct effect on the earliest and latest boundaries. The supported time fields are:

- `_time` is the raw event's timestamp.
- `__earliest` is the search start time.
- `__latest` is the search end time.

Time-based tokens are processed as follows:

- For each path, times must be notated in descending order. So Year/Month/Day order is supported, but Day/Month/Year is not.
- Paths may contain more than one time component. For example, `/my/path/2020-04/20/`.
- In a given path, each time component can be used only once. So `/my/path/${_time:%Y}/${_time:%m}/${_time:%d}/...` is a valid expression format, but

`/my/path/${_time:%Y}/${_time:%m}/${host}/${_time:%Y}/...` (with a repeated `Y`) is not supported.

- For each path, all extracted dates/times are considered in UTC.



Cribl recommends that your path always include and tokenize the largest available time fields, proceeding down to the smallest desired time fields. Otherwise, your searches might yield unexpected results, because Cribl Search will default the omitted fields to their earliest allowed value.

The following `strptime` format components are allowed:

- `Y`, `y` for years
- `m`, `B`, `b`, `e` for months
- `d`, `j` for days
- `H`, `I` for hours
- `M` for minutes
- `S` for seconds
- `s` for Unix time (seconds since 1/1/1970)

Time-based token syntax follows that of a slightly modified JS template literal: `${_time:some_strptime_format_component}`. Examples:

Path	Matches
`/path/${_time:%Y}/${_time:%m}/${_time:%d}/...`	`/path/2020/04/20/...`
`/path/${_time:year=%Y}/${_time:month=%m}/${_time:day=%d}/...`	`/path/year=2020/month=`
`/path/${_time:%Y-%m-%d}/...`	`/path/2020-05-20/...`

Set Query Time Range by Partition

If your data is partitioned by time (so your paths probably use time-based tokens), you can tell Cribl Search to ignore events' timestamps, and instead set the time range using the partition time-boundaries.

For example, an event with the timestamp of `2025-07-01T23:59:00.000` might be stored in the July 2 partition. Queries for July 1 or July 2 might not find it: the first due to wrong partition, the second due to wrong `_time`. Using partition time for the query range avoids this issue.

To search by partition time range, toggle on **Skip event time filter** when setting up your paths. Then, any time range you set (in the Cribl Search UI or with `earliest/latest` in the query text) will use partition time instead of event time.

If you toggle on the **Skip event time filter** option, Cribl Search will ignore the `_time` field in your events. Do **not** enable this option if your paths don't use time-based tokens.

Amazon S3 Path Filter

Each **Path filter** is a JavaScript expression that Cribl Search evaluates against the corresponding **Bucket path**. The **Path filter** field's value defaults to `true`, which matches all data. However, you can customize this value almost arbitrarily.

For example, with this **Path filter**:
`source.endsWith('.log') || source.endsWith('.txt')`
...this configuration will search only files/objects with `.log` or `.txt` extensions.

At each **Path filter** field's right edge are a Copy button and an Expand button that opens a validation modal.

On a v1 Dataset that uses DDSS or SmartStore partitioning, you can provide the index name as the **Path filter**, for example:
`index=="index_y"`

v2 Datasets have no **Path filter** field. To narrow a v2 search to one index, filter on the `index` field in the query.

Amazon S3 Partitioning Schemes

Each **Partitioning scheme** drop-down offers alternative options for partitioning inbound data from Splunk. You can choose among `Defined in Path`, `Splunk DDSS`, and `Splunk SmartStore`.

Both v1 and v2 Datasets offer all three schemes. To see how the Splunk schemes change the configuration of a v2 Dataset, see v2 Datasets and Splunk Partitioning.

With any option, in the corresponding **Bucket path** field, provide the path where indexes are stored (that is, your index's parent folder).

For Splunk SmartStore, the full path takes the form:
`<parent_folder>/<indexName>/db/<2-letter-hash>/<2-letter-hash>/<bucket_id_number-origin_guid>/<"guidSplunk"-uploader_guid>/`

For Splunk DDSS, the full path takes the form:
`<parent_folder>/<indexName>`

With either of these options, if you organize your bucket using this default file path, Cribl Search will automatically discover its content.

Both layouts put the index above the time-based part of the path, so name the index in every search against these Datasets. A time range alone still leaves Cribl Search traversing every index in the bucket:

```
dataset="my_ddss_dataset" earliest=-7d latest=-1d
| where index=="my_index"
```

Copy

Use the `where` operator with case-sensitive `==`, and spell the index name exactly as it appears in the path. Only an exact match narrows the path.

Splunk SmartStore Time Range on S3

When you select the `Splunk SmartStore` partitioning scheme for all buckets and paths within a v1 Amazon S3 Dataset, the **Dataset Provider** tab adds an **Advanced** section.

Use this section's **Time range** controls to define a rolling, retrospective time window over which Cribl Search will scan your Dataset to optimize search performance against it. The time window is evaluated against event timestamps. Its value defaults to `30 Days` back, and you can set it to anywhere between `1 Day(s)` and `All Time`.

v2 Datasets don't offer this control. Instead, Cribl Search reads the receipt metadata of each SmartStore bucket and skips the buckets that fall outside the time range of your search.

Search Amazon S3

Now that you have a Dataset Provider and Dataset, you're ready to start searching Amazon S3.

Data Transfer Charges

Data transfer to Cribl Search is free if your S3 bucket is in the same AWS Region as your Cribl.Cloud Workspace.

Data transfer to Cribl Search is subject to AWS data transfer costs if your S3 bucket is not in the Regions supported by Cribl.Cloud. AWS also charges API costs in some circumstances. For details, see the Amazon S3 Pricing topic's **Data transfer** section. Cribl Search users are responsible for paying Amazon data transfer and API costs; these are not covered by Cribl.Cloud credits.

Cribl Search will try to minimize the amount of data transferred, to the extend possible, by using path filters, pruning, and other methods.

Other Charges

Other charges may apply. For example, **LIST** and **GET** requests to your S3 buckets will be charged per AWS S3. See the **Requests & data retrievals** section in Amazon S3 Pricing.

Storage Class Compatibility

Cribl Search supports searching Amazon S3 storage classes as listed below.

S3 Storage Class	Cribl Search Compatibility
S3 Standard	Will attempt to read
S3 Intelligent-Tiering	Will attempt to read objects that have **not** aged into one of the unsupported classes below
S3 Express One Zone	Will attempt to read
S3 Standard-IA (infrequent access)	Will attempt to read
S3 One Zone-IA (infrequent access)	Will attempt to read
S3 Glacier Instant Retrieval	Will attempt to read
S3 Glacier Flexible Retrieval	**Unsupported** - will skip
S3 Glacier Deep Archive	**Unsupported** - will skip

When encountering objects from an unsupported storage class, Cribl Search skips them. You'll see the number of such objects next to the total count of search results, under the **skipped** metric:



Search progress

To find out which objects were ignored, go to **Details** > **Logs**, and find the logs containing the word `skipped`.

Search Archived Amazon S3 Objects

To read an object from an unsupported storage class (such as S3 Glacier Deep Archive), first temporarily restore the object in Amazon S3, and then make sure your Cribl Search Dataset is configured to include restored objects.

1. In Amazon S3, restore the archived object. The time this takes depends on the object's size, storage class, and other factors.
2. Once the object is successfully restored, open Cribl Search, and go to **Data** > **Datasets**.
3. Open the Dataset that contains the object, and select the **Storage classes** left tab.
4. Make sure the **Restored from Archive** check box is selected.
5. Select **Save**.

Now, your next search on this Dataset will attempt to read the restored object.

4.3. Connect Cribl Search To Cribl Edge

Configure Cribl Search to query your Cribl Edge Nodes.

With Cribl Edge, you can collect logs, metrics, application data, etc., and send them to Cribl Stream or any other supported destination in real time.

If you already have Edge Nodes running you don't need to set up anything and can start searching. For example searches, see Searching Cribl Edge. To search data not specified in a built-in Dataset, you can add a custom Dataset pointing to anywhere in the filesystem that Edge can read.

In this guide, you'll add a Cribl Edge Node on an Amazon EC2 instance to search its internal logs and metrics. For an in-depth installation guide of Cribl Edge see the Cribl Edge Deployment Guide.

Cribl Edge Access from Cribl Search

Cribl Search users can search the Edge Nodes to which they have access via Cribl Edge Permissions or Roles. Cribl Search Admins and Editors can create Datasets pointing to any Node (for example, using wildcards in the path). However, at search execution time, Cribl Search queries - and returns results from - only the Nodes to which the querying user has access.

For details on how to manage access to Edge Nodes, see the Cribl Edge docs:

- Access Management
- Product-Level Permissions (Stream and Edge)
- Group- and Fleet-Level Permissions

Configure Cribl Edge

To add a new Edge Node, follow the instructions in Add and Update Edge Nodes to add or bootstrap a new Node.

Configure EC2 Instance

We'll launch an Ubuntu instance using the AWS Management Console. For an in-depth tutorial, see how to get started with Amazon EC2 Linux instances.

1. Open the Amazon EC2 console at https://console.aws.amazon.com/ec2/.
2. From the EC2 console dashboard, in the **Launch instance** box, select **Launch instance**. From the options that appear, select **Launch instance** again.
3. Under **Name and tags**, for **Name**, enter a descriptive name for your instance.

4. Under **Application and OS Images (Amazon Machine Image)**, select **Quick Start**, and then select **Ubuntu**. This is the operating system (OS) for your instance.
5. Under **Key pair (login)**, for **Key pair name**, select or create a key pair.
6. Keep the default selections for the other configuration settings for your instance.
7. Select **Launch instance**.
8. A confirmation page lets you know that your instance is launching. Select **View all instances** to close the confirmation page and return to the console.
9. On the **Instances** screen, you can view the status of the launch. It takes a short time for an instance to launch. When you launch an instance, its initial state is pending. After the instance starts, its state changes to running and it receives a public DNS name.
10. It can take a few minutes for the instance to be ready for you to connect to it. Check that your instance has passed its status checks; you can view this information in the **Status check** column.
11. Now you'll connect to the instance as the root user using the Amazon EC2 console. Open the Amazon EC2 console at https://console.aws.amazon.com/ec2/. See how to connect using EC2 Instance Connect for more details.
12. In the navigation pane, select **Instances**, then the instance, then **Connect**.
13. Select the **EC2 Instance Connect** tab and verify the user name, then select **Connect** to open a terminal window.
14. In the terminal, to gain root access, run the command `sudo su`.
15. In the terminal as root, paste the bootstrap script you copied from Cribl Edge in the above section.
16. This will install the Edge Node in your EC2 instance and you can navigate back to Cribl Edge's **Edge Nodes** tab to view the new Node.

Built-In Cribl Edge Datasets

Cribl Search comes with several Cribl Edge Datasets, detailed in Built-In Cribl Edge Datasets. Each Dataset tells Cribl Search what data to search.

You do not need to make any changes to these Datasets, and you can start searching them immediately. However, you can edit these built-in Datasets, or add new ones to specify other logs anywhere in the filesystem that Edge can read.

To access Cribl Edge Datasets, select **Data** from the sidebar, then look for them on the default **Datasets** tab. The following sections explain the configurations available on a Dataset.

Path

The **Path** specifies the data that the Dataset consists of. It defines the scope of data, to narrow down what data is in the Dataset. This is a JavaScript expression that supports environment variables, wildcards, and tokens. For

example,

- `$CRIBL_STATE_DIR/system_metrics`
- `/foo/B*/*/baz`
- `/foo/${country}/${state}/${city}/` - where `country`, `state`, and `city` now become fields for all events of that Dataset.

Basic Tokens

Basic tokens' syntax follows that of JS template literals: `${token_name}` - where `token_name` is the field (name) of interest.

For example, if the path was set to `/var/log/${hostname}/${dataSource}/`, you could use a filter such as `hostname=='myHost' && dataSource=='mydataSource'` to specify data only from the `/var/log/myHost/mydataSource/` subdirectory.

Time-Based Tokens

Paths with time notation can be referenced with tokens, having a direct effect on the earliest and latest boundaries. The supported time fields are:

- `_time` is the raw event's timestamp.
- `__earliest` is the search start time.
- `__latest` is the search end time.

Time-based tokens are processed as follows:

- For each path, times must be notated in descending order. So Year/Month/Day order is supported, but Day/Month/Year is not.
- Paths may contain more than one time component. For example, `/my/path/2020-04/20/`.
- In a given path, each time component can be used only once. So `/my/path/${_time:%Y}/${_time:%m}/${_time:%d}/...` is a valid expression format, but `/my/path/${_time:%Y}/${_time:%m}/${host}/${_time:%Y}/...` (with a repeated `Y`) is not supported.
- For each path, all extracted dates/times are considered in UTC.



Cribl recommends that your path always include and tokenize the largest available time fields, proceeding down to the smallest desired time fields. Otherwise, your searches might yield unexpected results, because Cribl Search will default the omitted fields to their earliest allowed value.

The following `strptime` format components are allowed:

- `Y`, `y` for years
- `m`, `B`, `b`, `e` for months
- `d`, `j` for days
- `H`, `I` for hours
- `M` for minutes
- `S` for seconds
- `s` for Unix time (seconds since 1/1/1970)

Time-based token syntax follows that of a slightly modified JS template literal: `${_time:some_strptime_format_component}`. Examples:

Path	Matches
`/path/${_time:%Y}/${_time:%m}/${_time:%d}/...`	`/path/2020/04/20/...`
`/path/${_time:year=%Y}/${_time:month=%m}/${_time:day=%d}/...`	`/path/year=2020/month=`
`/path/${_time:%Y-%m-%d}/...`	`/path/2020-05-20/...`

Path Filter

This is a JavaScript filter expression that is evaluated against the provided Dataset path. The **Path Filter** value defaults to `true`, which matches all data, but this value can be customized almost arbitrarily.

For example, if a Dataset has this **Path Filter**:

```
source.endsWith('.log') || source.endsWith('.txt')
```

...then only files/objects with `.log` or `.txt` extensions will be searched.

At the **Path Filter** field's right edge are a Copy button and an Expand button that opens a validation modal.

With DDSS or SmartStore partitioning, you can provide the index name as **Path Filter**, for example: `index=="index_y"`.

Partitioning Scheme

Advanced Settings > **Partitioning scheme** lets you select the scheme for partitioning data incoming from Splunk.

You can choose between `Splunk DDSS` and `Splunk SmartStore`.

In both cases, provide the path where indices are stored (parent folder of your index) as **Bucket path**.

For Splunk DDSS, the full path takes the form:

```
<parent_folder>/<indexName>/db/db_<latestTime>_<earliestTime>_<bucketId>/rawdata/jou
```

or

```
<parent_folder>/<indexName>/db_<latestTime>_<earliestTime>_<bucketId>/rawdata/journa
```

For SmartStore, it is:

```
<parent_folder>/<indexName>/db/<2-letter-hash>/<2-letter-
hash>/<bucket_id_number-origin_guid>/<"guidSplunk"-uploader_guid>/
```

In both cases, if your bucket is organized using this default file path, Cribl Search will automatically discover its content.

Both layouts put the index above the time-based part of the path, so name the index in every search against these Datasets. A time range alone still leaves Cribl Search traversing every index in the path:

```
dataset="my_ddss_dataset" earliest=-7d latest=-1d
| where index=="my_index"
```

Copy

Use the `where` operator with case-sensitive `==`, and spell the index name exactly as it appears in the path. Only an exact match narrows the path.

Processing

Processing is done with **Datatypes**, to break data into discrete events and define fields so they're ready to search. These consist of rules that are applied to the data searched in your Dataset. See Datatypes for details.

Search Cribl Edge

Now that you have an Edge Node on an Amazon EC2 instance, you're ready to start searching Cribl Edge.

4.4. Connect Cribl Search To AWS

Link Cribl Search to your AWS data.

Grant Access to AWS

Allow Cribl Search to access to your AWS data, by configuring an IAM role or user. See various trust policy examples. See: Grant Access to AWS.

Amazon Security Lake

Configure Cribl Search to query your Amazon Security Lake data. See: Amazon Security Lake.

AWS API

Configure Cribl Search to query an AWS API endpoint. See: AWS API.

Data Lake Amazon S3

Configure Cribl Search to query Cribl Stream's Data Lake Amazon S3 Destination. See: Data Lake Amazon S3.

4.4.1. Grant Access To AWS

Allow Cribl Search to access to your AWS data, by configuring an IAM role or user. See various trust policy examples.

Cribl Search uses Amazon Web Services (AWS) IAM to access and search your data in AWS. When creating an Amazon Dataset Provider in Cribl Search, you'll need to provide it with credentials.

Access to AWS services is managed through AWS Identity and Access Management (IAM). You can grant access either at the IAM role level, or at the IAM user level using an access and secret key pair. Cribl recommends role-based access, as described below.

IAM User

You can use an IAM user's access keys (access key IDs and secret access keys) to grant access to your data in AWS. If creating a new IAM user, give it **Programmatic access** so AWS assigns the user access keys.

IAM Role

Cribl recommends using IAM role-based access for increased security. An IAM role is similar to a user - it is an AWS identity with permission policies that determine what the identity can and cannot do in AWS. However, instead of passing IAM user credentials, here a user assumes a role and triggers AWS to dynamically generate temporary security credentials. With these temporary credentials, the user then accesses an AWS resource by its Amazon Resource Name (ARN).



For details about configuring the IAM role in the AWS console, see Create a role using custom trust policies. For details about using permissions policies to restrict an IAM role's capabilities on AWS, see Permissions boundaries for IAM entities.

The process for granting access is:

1. Set up a new AWS IAM role in your account.

   You need to either build the IAM role and policy using your own infrastructure-management solution (such as Terraform or CloudFormation), or else build it via the AWS console.

   You can create a new role with Cribl's trust policy instead of attaching it - see the next step.

2. Attach the trust policy, provided by Cribl, to the role in your account.

   Modify your IAM role to include Cribl Search's trust policy. You can do this with the AWS console, CLI, or API.

3. Add the appropriate permissions to your IAM role using an identity-based policy. For example, to allow access to an S3 bucket called `cribl-search-data`, you'd use the following sample **permission policy**:

```
{
"Version": "2012-10-17",
"Statement": [{
        "Effect": "Allow",
        "Action": "s3:GetObject",
        "Resource": "arn:aws:s3:::cribl-search-data/*"
   },
   {
        "Effect": "Allow",
        "Action": "s3:ListBucket",
        "Resource": "arn:aws:s3:::cribl-search-data"
   }
]
}
```

Copy

4. Specify the IAM role's ARN on an AWS Dataset Provider.

Trust Policy

Cribl Search builds a trust policy that creates a trust relationship between Cribl Search and a role in your AWS account. This policy controls and restricts access to only those resources to which you grant access. This trust relationship can be revoked at any time, without having to also revoke credentials (and thus, revoke access to the data).

The provided trust policy contains the AWS Role ARN and external ID of Cribl Search's IAM role that you'll need to trust. The policy allows Cribl Search to perform the `sts:AssumeRole` operation toward your external account.

The external ID is a custom string that you create to enhance authentication and authorization when accessing the S3 resource. The crucial requirement is to ensure that the strings match on both the Cribl Dataset Provider the and AWS trust policy.



The external ID must meet the length and character requirements that AWS specifies in IAM name requirements.

Example Trust Policy

Here is a basic trust policy - an anonymized version of the policy you can copy from your Dataset Provider modal's **Trust Policy** button (when setting up the Authentication Method). See also the variations below the example.



In these examples, `<TENANT_ID>` and `<EXTERNAL_ID>` are anonymized placeholders:

- `<TENANT_ID>` is the Cribl AWS account ID for your organization. When you copy the trust policy from the **Trust Policy** button in your Dataset Provider modal, this value is automatically populated, so you do not need to look it up separately.
- `<EXTERNAL_ID>` is not pre-populated. Replace it with the value you entered in the **External ID** field of your Dataset Provider configuration.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Principal": {
        "AWS": "arn:aws:iam::<TENANT_ID>:role/search-exec-main"
      },
      "Action": "sts:AssumeRole",
      "Condition": {
        "StringEquals": {
          "sts:ExternalId": "<EXTERNAL_ID>"
        }
      }
    },
    {
      "Effect": "Allow",
      "Principal": {
        "AWS": "arn:aws:iam::<TENANT_ID>:role/search-exec-main"
      },
      "Action": "sts:TagSession"
    },
    {
      "Effect": "Allow",
      "Principal": {
        "AWS": "arn:aws:iam::<TENANT_ID>:role/search-exec-main"
      },
      "Action": "sts:SetSourceIdentity"
    }
  ]
}
```

Copy

Trust Policy with Multiple Workspaces

If you have configured multiple Workspaces, the default trust policy grants access only to your `main` Workspace. For other Workspaces, replace `search-exec-main` with `search-exec-<WORKSPACE-ID>`, where `<WORKSPACE-ID>` is the Workspace internal ID, not its display name.

To find a Workspace ID, select the Workspace name in the top navigation bar. In the modal that opens, the **ID** column lists the internal ID for each Workspace.

AWS does not support glob-style wildcards in IAM role ARN patterns within `Principal` elements. For example, `arn:aws:iam::<TENANT_ID>:role/search-exec-*` is not valid syntax. Add a separate set of three `Principal` statements (covering `sts:AssumeRole`, `sts:TagSession`, and `sts:SetSourceIdentity`) for each Workspace you need to authorize, substituting the correct Workspace ID in each.

Alternatively, you can use the fully open wildcard below, which allows any AWS principal and requires no per-Workspace changes. Use this approach only when your permission policies already tightly restrict what actions the assumed role can perform:

```
{
  "Effect": "Allow",
  "Principal": {
    "AWS": "*"
  },
```

Copy

Trust Policy with ABAC Tagging

You can make your AssumeRole sessions more secure by adding Cribl's VPCE (Virtual Private Cloud Endpoint) ID to your trust policy. This enables attribute-based access control (ABAC).

For an overview of how ABAC works on AWS, with links to further resources, see Define permissions based on attributes with ABAC authorization.

To set up ABAC on a supported Dataset Provider: After you enable the **Apply ABAC source-ip tagging** option, copy the adjacent **VPCE ID** to use later in this section. For convenience, we'll start with the default trust policy shown above:

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Principal": {
        "AWS": "arn:aws:iam::<TENANT_ID>:role/search-exec-main"
      },
      "Action": "sts:AssumeRole",
      "Condition": {
        "StringEquals": {
          "sts:ExternalId": "<EXTERNAL_ID>"
        }
      }
    },
    {
      "Effect": "Allow",
      "Principal": {
        "AWS": "arn:aws:iam::<TENANT_ID>:role/search-exec-main"
      },
      "Action": "sts:TagSession"
    },
    {
      "Effect": "Allow",
      "Principal": {
        "AWS": "arn:aws:iam::<TENANT_ID>:role/search-exec-main"
      },
      "Action": "sts:SetSourceIdentity"
    }
  ]
}
```

Copy

Expand the Trust Policy

First, expand the `"Action": "sts:TagSession"` element by adding the sub-element shown below. Paste in the `"${aws:SourceIp}"` variable as-is. This enables passing Cribl Search's `source-ip` value, making your sessions more secure by enforcing a condition that the `source-ip` tag must match the IP address requesting to assume the role:

```
    "Action": "sts:TagSession",
    "Condition": {
        "StringEquals": {
            "aws:RequestTag/source-ip": "${aws:SourceIp}"
        }
    }
```

Copy

Expand the Permission Policy

For the remaining steps, we'll start with this anonymized default policy that you can copy from your Dataset Provider modal's **Permission Policy** button (when setting up the Authentication Method).

```
{
    "Version": "2012-10-17",
    "Statement": [
      {
        "Effect": "Allow",
        "Action": "s3:GetObject",
        "Resource": ["arn:aws:s3:::<MY_S3_BUCKET>/*"]
      },
      {
        "Effect": "Allow",
        "Action": "s3:ListBucket",
        "Resource": ["arn:aws:s3:::<MY_S3_BUCKET>"]
      }
    ]
  }
```

Copy

Expand the `s3:ListBucket` element by adding the sub-element shown below. Replace `vpce-<someVpceId>` with the VPCE IDs that you copied from your Dataset Provider's config modal. You can include multiple VPCE IDs in the array:

```
{
 "Effect": "Allow",
 "Action": "s3:ListBucket",
 "Resource": ["arn:aws:s3:::<MY_S3_BUCKET>"],
 "Condition": {
     "StringEquals": {
         "aws:SourceVpce": [
             "vpce-<someVcpeId-1>",
             "vpce-<someVcpeId-2>"
         ]
     }
 }
}
```

Copy

Finally, copy the whole expanded `s3:ListBucket` element that you just modified. In the duplicated element shown below, paste in the `"${aws:SourceIp}"` variable as-is.

4.4.2. Connect Cribl Search To Amazon Security Lake

Configure Cribl Search to query your Amazon Security Lake data.

Using Amazon Security Lake, you can automatically consolidate security data from across AWS environments, SaaS providers, on-prem systems, and cloud sources into a purpose-built data lake.


In this guide, you'll set up a Dataset Provider and a Dataset to search objects in your Amazon Security Lake.

Data transfer costs and other charges may apply. For details, see the Data Transfer Charges section below.

Add an Amazon Security Lake Dataset Provider

A Dataset Provider tells Cribl Search where to query and contains access credentials. Here, you will add an Amazon Security Lake Dataset Provider.

To add a new Dataset Provider, select **Data**, then **Dataset Providers**, then **Add Provider**.



Amazon Security Lake Dataset Provider selection

Basic Configuration

Configure the **New Dataset Provider** modal as follows:

1. **ID** is a unique identifier for the Dataset Provider. This is how you'll reference it when assigning Datasets to it. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_provider_1`).
2. **Description** is optional. Here, you can enter a summary that will clarify this Dataset Provider's purpose to other users.
3. Set the **Dataset Provider type** to `Amazon S3`.
4. **Authentication method** provides two options, **Assume Role** and **AWS keys**. For details on configuring each option, see Authentication Method below.

Advanced Settings

This section provides the following optional configurations:

- **Endpoint**: S3 service or compatible endpoint. If empty, defaults to AWS Region-specific endpoint.
- **Signature version**: Signature version to use for signing S3 requests. Defaults to `v4`.
- **Reuse connections**: Whether to reuse connections between requests. Toggling on (default) can improve performance.
- **Reject unauthorized certificates**: Whether to reject certificates that cannot be verified against a valid Certificate Authority (for example, self-signed certificates). Defaults to toggled on.
- **Apply ABAC source-ip tagging**: Displayed only if you've set the **Authentication method** to **AssumeRole**. For details, see ABAC Tagging below.

Wrapping Up

Select **Save** when your configuration is complete.

Authentication Method

Your choices here are **AssumeRole** or **AWS keys**. For rich details on both options, beyond the configuration basics in this section, see Grant Access to AWS.

AssumeRole Authentication

Selecting **AssumeRole** requires the IAM role's ARN (**AssumeRole ARN**), and also exposes the following options:

- The **External ID** on this Dataset Provider must match the external ID defined in the IAM Role Trust Policy.
- The **Duration (seconds)** defines how long the AssumeRole's session lasts. Minimum is `900` (15 minutes), default is `3600` (1 hour), and maximum is `43200` (12 hours).
- The ABAC tagging controls described in the next section.

To the right, select the **Trust Policy** and **Permission Policy** buttons to see the default policies that you can copy and expand, so you don't have to write them from scratch. For more information, see Example Trust Policy and Expand the Permission Policy.

AWS Keys Authentication

Selecting **AWS keys** requires the IAM user's **Access key** and **Secret key**.

To the right, select the **Permission Policy** button to see the default policy that you can copy and expand, so you don't have to write it from scratch. For more information, see Expand the Permission Policy.

ABAC Tagging

Select **Apply ABAC source-ip tagging** if you want to make your AssumeRole sessions more secure by enabling attribute-based access controls (ABAC). By enabling this option, you can hard-code Cribl's Virtual Private Cloud Endpoint (VPCE) into your IAM trust policy.


Selecting this option exposes **VPC Endpoint IDs**. Use the adjacent Copy button to transfer the VPCE ID to your IAM trust policy, as shown in Trust Policy with ABAC Tagging.

Completing both parts of this configuration will make your credentials harder to impersonate. Specifically, your AssumeRole sessions will include a `source-ip` tag, enabling you to enforce a condition that `aws:RequestTag/source-ip` equals `${aws:SourceIp}`.

Add an Amazon Security Lake Dataset

Now you'll add a Dataset that tells Cribl Search what data to search from the Dataset Provider.

To add a new Dataset, select **Data**, then **Datasets**, then **Add Dataset**.



Datasets selection

Set the Dataset type to **Federated Dataset**, and configure the **New Dataset** modal as follows.

Identify the Dataset

Use the first few fields to uniquely identify this Dataset and specify its type:

1. **ID** is an identifier unique for both Cribl Search and Cribl Lake. You'll use this to specify the Dataset in a query's scope, telling Cribl Search to search the Dataset. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_1`).
2. **Description** is optional.
3. Set **Dataset Provider** to the **ID** of an Amazon Security Lake Dataset Provider.

Set the Path and Filter

Define the Dataset's bucket path and filtering:

1. **Path** is the path within the S3 buckets you'd like to search. Tokens and key-value pairs are supported. The path is prefilled with a recommended path string, that you can use for guidance. For details, see Set Path for Amazon Security Lake.
2. **Path Filter** is a JavaScript filter expression that is evaluated against the S3 bucket path. It defaults to `true`, which matches all data, but you can customize this value.

Set Up Buckets and Regions

Under **Selected buckets**, define at least one S3 bucket/Region pair for this Dataset to search:

1. Select **Add bucket** to add the first pair. In the resulting table row:
2. **Bucket name** is the name of the S3 bucket.
3. **Region** is the AWS Region where the bucket is located.

Select **Add bucket** again for each additional bucket/Region pair you want to append to the table.

Set Up Datatypes

1. On the **Processing** left tab, you specify **Datatypes** to break data down into discrete events and define fields so they're ready to search. Use the drop-down to set the first rule to `OCSF Datatypes`. For details, see Datatypes.
2. Optionally, click **Add Datatype Ruleset** to define more rulesets - each of which contains rules applied to the data searched in your Dataset.
3. Create a rule on a Datatype that converts the time field from milliseconds to seconds (For example, `_time = time/1000`). For details, see the Assign `time` Field section below.

Save the Configuration

Bypass the **Usage** left tabs for now, and select **Save** when your configuration is complete.

Path/Filter Considerations

This section offers details and guidance on configuring the search path, filter, and time extraction.

Set Path for Amazon Security Lake

The **Path** specifies the data that the Dataset consists of. It defines the scope of data, to narrow down what data is in the Dataset. This is a JavaScript expression that supports tokens and key-value pairs. For example,

- `path/to/folder/${data}/` - where `data` becomes a field for all events of that Dataset.
- `path/to/folder/${data}/${*}` - where `data` and the wildcarded path becomes a field for all events of that Dataset.

Basic Tokens

Basic tokens' syntax follows that of JS template literals: `${token_name}` - where `token_name` is the field (name) of interest.

For example, if the path was set to `/var/log/${hostname}/${dataSource}/`, you could use a filter such as `hostname=='myHost' && dataSource=='mydataSource'` to specify data only from the `/var/log/myHost/mydataSource/` subdirectory.

Time-Based Tokens

Paths with time notation can be referenced with tokens, having a direct effect on the earliest and latest boundaries. The supported time fields are:

- `_time` is the raw event's timestamp.
- `__earliest` is the search start time.
- `__latest` is the search end time.

Time-based tokens are processed as follows:

- For each path, times must be notated in descending order. So Year/Month/Day order is supported, but Day/Month/Year is not.
- Paths may contain more than one time component. For example, `/my/path/2020-04/20/`.
- In a given path, each time component can be used only once. So `/my/path/${_time:%Y}/${_time:%m}/${_time:%d}/...` is a valid expression format, but

`/my/path/${_time:%Y}/${_time:%m}/${host}/${_time:%Y}/...` (with a repeated `Y`) is not supported.

- For each path, all extracted dates/times are considered in UTC.



Cribl recommends that your path always include and tokenize the largest available time fields, proceeding down to the smallest desired time fields. Otherwise, your searches might yield unexpected results, because Cribl Search will default the omitted fields to their earliest allowed value.

The following `strptime` format components are allowed:

- `Y`, `y` for years
- `m`, `B`, `b`, `e` for months
- `d`, `j` for days
- `H`, `I` for hours
- `M` for minutes
- `S` for seconds
- `s` for Unix time (seconds since 1/1/1970)

Time-based token syntax follows that of a slightly modified JS template literal: `${_time:some_strptime_format_component}`. Examples:

Path	Matches
`/path/${_time:%Y}/${_time:%m}/${_time:%d}/...`	`/path/2020/04/20/...`
`/path/${_time:year=%Y}/${_time:month=%m}/${_time:day=%d}/...`	`/path/year=2020/month=`
`/path/${_time:%Y-%m-%d}/...`	`/path/2020-05-20/...`

Set Path Filter for Amazon Security Lake

The **Path filter** is a JavaScript filter expression that Cribl Search evaluates against the corresponding **Container path**. The **Path filter** field's value defaults to `true`, which matches all data. However, you can customize this value almost arbitrarily.

For example, if a Dataset has this **Filter**:
`source.endsWith('.log') || source.endsWith('.txt')`
...then only files/objects with `.log` or `.txt` extensions will be searched.

At the **Path filter** field's right edge are a Copy button and an Expand button that opens a validation modal.

Assign `time` Field for Amazon Security Lake

Amazon Security Lake automatically partitions incoming data from natively supported AWS services into storage-efficient and query-efficient Parquet files. Additionally, it transforms data from native AWS services into the open-source OCSF format.

The time is assigned to the `time` field, which is Unix time expressed in milliseconds.

To use this field, you need to set its value to the Cribl Search `_time` field. Because Cribl Search uses seconds instead of milliseconds, you must also convert it by dividing by 1,000. For this to work, add this field to a Datatype:
`_time = time/1000.`

Search Amazon Security Lake

Now that you have a Dataset Provider and Dataset, you're ready to start searching.

Search results can start showing up within a second or two, but when the search completes depends on how much data there is in the account.

Data Transfer Charges

Data transfer to Cribl Search is free if your S3 bucket is in the same Region as your Cribl.Cloud Workspace.

Data transfer to Cribl Search is subject to AWS data transfer costs if your S3 bucket is not in the Regions supported by Cribl.Cloud. See the **Data transfer** section in Amazon S3 Pricing.

Cribl Search will try to minimize the amount of data transferred, to the extend possible, by using path filters, pruning, and other methods.

Other Charges

Other charges may apply. For example, **LIST** and **GET** requests to your S3 buckets will be charged per AWS S3. See the **Requests & data retrievals** section in Amazon S3 Pricing.

4.4.3. Connect Cribl Search To AWS API

Configure Cribl Search to query an AWS API endpoint.

Amazon Web Services (AWS) offers scalable and cost-effective cloud computing solutions.

In this guide, you'll set up a Dataset Provider and a Dataset to search the AWS API supporting the following endpoints:

Product	Endpoints
EC2	EC2 Instances, EC2 Volumes, EC2 Security Groups
Lambda	Lambda Functions
IAM	Users, Roles, Groups, Policies, MFA Devices
CloudFormation	StackSets, Stacks, Exports
DynamoDB	Backups
RDS	Clusters, Cluster Endpoints, Instances, Security Groups, Certificates
CloudTrail	Events
VPC	VPCs, Subnets, Network Interfaces
EFS	File Systems

Add an AWS API Dataset Provider

A Dataset Provider tells Cribl Search where to query and contains access credentials. Here, you will add an AWS API Dataset Provider.

To add a new Dataset Provider, select **Data**, then **Dataset Providers**, then **Add Provider**.

Set the following configurations in the **New Dataset Provider** modal:

1. **ID** is a unique identifier for the Dataset Provider. This is how you'll reference it when assigning Datasets to it. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_provider_1`).
2. **Description** is optional.
3. Set **Dataset Provider Type** to **AWS API**.

4. **Authentication method** provides two options, **Assume Role** and **AWS keys**. See how to grant access to AWS for details on each option.
5. Select **Add Configuration** to specify your AWS account. The configuration depends on the **Authentication method** selected and you can use only one method for all configurations. In the **Account Configurations** table:
    - **Assume Role** requires the IAM role's ARN (**AssumeRole ARN**) and has options to define an **External ID** and **Duration**.
        - The **External ID** on the Dataset Provider must match the external ID defined in the IAM Role Trust Policy.
        - **Duration** defines the Assumed Role's session length of time, in seconds. Minimum is `900` (15 minutes), default is `3600` (1 hour), and maximum is `43200` (12 hours).
    - **AWS keys** requires the IAM user's account **Name**, **Access key**, and **Secret key**.
6. Select **Save** when finished.

For details on obtaining your AWS credentials, see Grant Access to AWS.

Permission Requirements for AWS API

Accessing specific AWS endpoints requires the following permissions:

Endpoint	Permission

`ec2_instances`
`ec2_volumes`
`ec2_security_groups`
	`ec2:DescribeInstances`
	`ec2:DescribeVolumes`
	`ec2:DescribeSecurityGroups`
	
	or
	
	`ec2:Describe*`

`lambda_functions`	`lambda:ListFunctions`

`iam_users`
`iam_groups`
`iam_policies`
`iam_roles`
`iam_mfa_devices`
	`iam:ListPolicies`
	`iam:ListRoles`
	`iam:ListUsers`
	`iam:ListGroups`
	`iam:ListMFADevices`

`cloudformation_stacks`
`cloudformation_stacksets`
`cloudformation_exports`
	`cloudformation:ListExports`
	`cloudformation:ListStacks`
	`cloudformation:ListStackSets`

`dynamodb_backups`	`dynamodb:ListBackups`

Endpoint	Permission

`rds_clusters`
`rds_cluster_endpoints`
`rds_instances`
`rds_security_groups`
`rds_certificates`
	`rds:DescribeDBInstances`
	`rds:DescribeDBClusterEndpoints`
	`rds:DescribeDBSecurityGroups`
	`rds:DescribeCertificates`
	`rds:DescribeDBClusters`
	
	or
	
	`rds:Describe*`

`cloudtrail_events`	`cloudtrail:LookupEvents`

`vpc_vpcs`
`vpc_subnets`
`vpc_network_interfaces`
	`ec2:DescribeNetworkInterfaces`
	`ec2:DescribeVpcs`
	`ec2:DescribeSubnets`

`efs_file_systems`	`elasticfilesystem:DescribeFileSystems`

Add an AWS API Dataset

Now you'll add a Dataset that tells Cribl Search what data to search from the Dataset Provider.

To add a new Dataset, select **Data**, then **Datasets**, then **Add Dataset**.

Set the following configurations in the **New Dataset** modal:

1. Select the Dataset type: **Federated Dataset**.
2. **ID** is an identifier unique for both Cribl Search and Cribl Lake. You'll use this to specify the Dataset in a query's scope, telling Cribl Search to search the Dataset. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_1`).
3. **Description** is optional.
4. Set **Dataset Provider** to the **ID** of an AWS Dataset Provider.
5. Under **Enabled endpoint**, select **Add Endpoints** to select the endpoints for your Dataset. Select an endpoint from the drop-down menu. Your options are:
    - `ec2_instances`
    - `ec2_volumes`
    - `ec2_security_groups`
    - `lambda_functions`
    - `iam_users`
    - `iam_roles`

    - iam_groups
    - iam_policies
    - iam_mfa_devices
    - cloudformation_stacks
    - cloudformation_stacksets
    - cloudformation_exports
    - dynamodb_backups
    - rds_exports
    - rds_backups
    - rds_clusters
    - rds_cluster_endpoints
    - rds_instances
    - rds_security_groups
    - rds_certificates
    - cloudtrail_events
    - vpc_subnets
    - vpc_network_interfaces
    - efs_file_systems
6. Under **AWS Regions**, select **Add Regions** to specify the AWS Regions to query for the endpoint(s).
7. In **Processing**, you can apply rules for breaking data into discrete events. For more information, see Datatypes.
8. In **Snapshots**, you can set up API Snapshots.
9. Select **Save** when finished.

Search AWS API

Now that you have a Dataset Provider and Dataset, you're ready to start searching.

Search results can start showing up within a second or two, but when the search completes depends on how much data there is in the account.

4.4.4. Connect Cribl Search To Data Lake Amazon S3

Configure Cribl Search to query Cribl Stream's Data Lake Amazon S3 Destination.

Cribl Stream's Data Lake Amazon S3 Destination sends data to Amazon S3 with a partitioning scheme tailored for Cribl Search. This scheme optimizes how objects are searched relative to the search's time range.

In this guide, you'll set up a Dataset Provider and a Dataset to search objects that Cribl Stream has exported to your Amazon S3 bucket via a Data Lake Amazon S3 Destination.


Data transfer costs and other charges might apply. For details, see the Data Transfer Charges section below.

Add a Data Lake Amazon S3 Dataset Provider

A Dataset Provider tells Cribl Search where to query, and contains access credentials. Here, you will add an Amazon S3 Dataset Provider.

To add a new Dataset Provider, select **Data**, then **Dataset Providers**, then **Add Provider**.

From the resulting drop-down, select the Cribl Stream Worker Group and the Data Lake Amazon S3 Destination you want to search.




Creating a Data Lake Amazon S3 Dataset Provider

Basic Configuration

Configure the resulting **New Dataset Provider** modal as follows:

1. **ID** is a unique identifier for the Dataset Provider. This is how you'll reference it when assigning Datasets to it. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_provider_1`).
2. **Description** is optional. Here, you can enter a summary that will clarify this Dataset Provider's purpose to other users.
3. Set the **Dataset Provider type** to `Amazon S3`.

4. **Authentication method** is automatically populated with the credentials used by the Data Lake Amazon S3 Destination. You can use different credentials if desired - you have two options, **Assume Role** and **AWS keys**. For details on configuring each option, see Authentication Method below.



Configuring a Data Lake Amazon S3 Dataset Provider

Advanced Settings

This section provides the following optional configurations:

- **Endpoint**: S3 service or compatible endpoint. If empty, defaults to AWS Region-specific endpoint.
- **Signature version**: Signature version to use for signing S3 requests. Defaults to `v4`.
- **Reuse connections**: Whether to reuse connections between requests. Toggling on (default) can improve performance.
- **Reject unauthorized certificates**: Whether to reject certificates that cannot be verified against a valid Certificate Authority (for example, self-signed certificates). Defaults to toggled on.

Wrapping Up

Select **Save** when your configuration is complete.

Authentication Method

Your choices here are **AssumeRole** or **AWS keys**. For rich details on both options, beyond the configuration basics in this section, see Grant Access to AWS.

AssumeRole Authentication

Selecting **AssumeRole** requires the IAM role's ARN (**AssumeRole ARN**), and also exposes the following options:

- The **External ID** on this Dataset Provider must match the external ID defined in the IAM Role Trust Policy.
- The **Duration (seconds)** defines how long the AssumeRole's session lasts. Minimum is `900` (15 minutes), default is `3600` (1 hour), and maximum is `43200` (12 hours).
- The ABAC tagging controls described in the next section.

To the right, select the **Trust Policy** and **Permission Policy** buttons to see the default policies that you can copy and expand, so you don't have to write them from scratch. For more information, see Example Trust Policy and Expand the Permission Policy.

AWS Keys Authentication

Selecting **AWS keys** requires the IAM user's **Access key** and **Secret key**.

To the right, select the **Permission Policy** button to see the default policy that you can copy and expand, so you don't have to write it from scratch. For more information, see Expand the Permission Policy.

Permissions for Data Lake Amazon S3

The following permissions are needed to read from an Amazon S3 bucket:

- `s3:GetObject`
- `s3:ListBucket`


If you're using the same IAM policy for this Dataset as the Data Lake Amazon S3 Destination, you need to provide permissions to read and write:

- `s3:GetObject`
- `s3:ListBucket`
- `s3:GetBucketLocation`
- `s3:PutObject`

Add a Data Lake Amazon S3 Dataset

Now you'll add a Dataset that tells Cribl Search what data to search from the Dataset Provider.

To add a new Dataset, select **Data**, then **Datasets**, then **Add Dataset**.



Dataset configuration

Configure the **New Dataset** modal as follows.

Identify the Dataset

1. Select the Dataset type: **Federated Dataset**.
2. **ID** is an identifier unique both in Cribl Search and in your Amazon S3 data lake. You'll use this to specify the Dataset in a query's scope, telling Cribl Search to search the Dataset. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_1`).
3. **Description** is optional. Here, you can enter a summary that will clarify this Dataset's purpose to other users.
4. Set **Dataset Provider** to the Amazon S3 Dataset Provider (its **ID**) that you created in the above Add a Data Lake Amazon S3 Dataset Provider section.

Set Up Path and Region

Configure the path and Region as follows:

1. **Bucket path** is the path to the S3 objects you'd like to search. Through Cribl Stream's Data Lake Amazon S3 Destination, data is partitioned specifically for Cribl Search and sent to Amazon S3. A time-based search scheme optimizes how objects are searched.

   The **Bucket path** is automatically populated to use this scheme, starting with the bucket name followed by time tokens: `<my-bucket-name>/${*}-${_time:%Y}/${*}-${_time:%m}/${*}-${_time:%d}/${*}-${_time:%H}`.

   Tokens and key-value pairs are supported, see bucket path for details.

2. **Path filter** is a JavaScript filter expression that is evaluated against the S3 bucket path. Defaults to `true`, which matches all data, but you can customize this value.
3. Toggle off **Auto-detect region** if you want to use the adjacent **Region** drop-down to specify the AWS Region where the S3 bucket is located. When toggled on, Cribl automatically detects the Region and locks the drop-down.

   The Amazon S3 Dataset type supports multiple path/filter/region configurations per bucket. For details about this option, see Multiple Path Configs.

Set Up Datatypes and Storage Classes

On the **Processing** left tab, you specify **Datatypes** to break data down into discrete events and define fields so they're ready to search.

Use the drop-down to set the first rule to `AWS Datatypes`. Optionally, click **Add Datatype Ruleset** to select more rulesets - each of which contains rules applied to the data searched in your Dataset. For details, see Datatypes.

On the **Storage classes** left tab, select the storage classes that you want this Dataset to search against. You can minimize retrieval costs by selecting only warmer classes. You must select at least one class. For details, see Storage Classes.

Save the Configuration

Bypass the **Usage** left tabs for now, and select **Save** when your configuration is complete.

Path/Filter Considerations

This section offers details and guidance on configuring search paths and filters.

Bucket Path

The **Bucket path** specifies the data that the Dataset consists of. It defines the scope of data, to narrow down what data is in the Dataset. This is a JavaScript expression that supports tokens and key-value pairs. For example,

- `my-bucket/${data}/` - where `data` becomes a field for all events of that Dataset.
- `my-bucket/${data}/${*}` - where `data` and the wildcarded path becomes a field for all events of that Dataset.

To search partitioned data in S3, the bucket path includes the partition keys and their corresponding values using URL encoding, where `%3D` replaces `=`. For example, the bucket path for data in `env` and `service` partitions is `my-bucket/env%3D${env}/service%3D${service}/`.

Basic Tokens

Basic tokens' syntax follows that of JS template literals: `${token_name}` - where `token_name` is the field (name) of interest.

For example, if the path was set to `/var/log/${hostname}/${dataSource}/`, you could use a filter such as `hostname=='myHost' && dataSource=='mydataSource'` to specify data only from the `/var/log/myHost/mydataSource/` subdirectory.

Time-Based Tokens

Paths with time notation can be referenced with tokens, having a direct effect on the earliest and latest boundaries. The supported time fields are:

- `_time` is the raw event's timestamp.
- `__earliest` is the search start time.
- `__latest` is the search end time.

Time-based tokens are processed as follows:

- For each path, times must be notated in descending order. So Year/Month/Day order is supported, but Day/Month/Year is not.
- Paths may contain more than one time component. For example, `/my/path/2020-04/20/`.
- In a given path, each time component can be used only once. So `/my/path/${_time:%Y}/${_time:%m}/${_time:%d}/...` is a valid expression format, but `/my/path/${_time:%Y}/${_time:%m}/${host}/${_time:%Y}/...` (with a repeated `Y`) is not supported.
- For each path, all extracted dates/times are considered in UTC.



Cribl recommends that your path always include and tokenize the largest available time fields, proceeding down to the smallest desired time fields. Otherwise, your searches might yield unexpected results, because Cribl Search will default the omitted fields to their earliest allowed value.

The following `strptime` format components are allowed:

- `Y`, `y` for years
- `m`, `B`, `b`, `e` for months
- `d`, `j` for days
- `H`, `I` for hours
- `M` for minutes

- `S` for seconds
- `s` for Unix time (seconds since 1/1/1970)

Time-based token syntax follows that of a slightly modified JS template literal: `${_time: some_strptime_format_component}`. Examples:

Path	Matches
`/path/${_time:%Y}/${_time:%m}/${_time:%d}/...`	`/path/2020/04/20/...`
`/path/${_time:year=%Y}/${_time:month=%m}/${_time:day=%d}/...`	`/path/year=2020/month=`
`/path/${_time:%Y-%m-%d}/...`	`/path/2020-05-20/...`

Path Filter

This is a JavaScript filter expression that Cribl Search evaluates against the corresponding **Bucket path**. The **Path filter** field's value defaults to `true`, which matches all data. However, you can customize this value almost arbitrarily.

For example, with this **Path filter**:
`source.endsWith('.log') || source.endsWith('.txt')`
...this configuration will search only files/objects with `.log` or `.txt` extensions.

At the **Path filter** ffield's right edge are a Copy button and an Expand button that opens a validation modal.

Search Data Lake Amazon S3

Now that you have a Dataset Provider and Dataset, you're ready to start searching.

Data Transfer Charges

Data transfer to Cribl Search is free if your S3 bucket is in the same Region as your Cribl.Cloud Workspace.

Data transfer to Cribl Search is subject to AWS data transfer costs if your S3 bucket is not in the Regions supported by Cribl.Cloud. See the **Data transfer** section in Amazon S3 Pricing.

Cribl Search will try to minimize the amount of data transferred, to the extend possible, by using path filters, pruning, and other methods.

Other Charges

Other charges may apply. For example, **LIST** and **GET** requests to your S3 buckets will be charged per AWS S3. See the **Requests & data retrievals** section in Amazon S3 Pricing.

4.5. Connect Cribl Search To Azure

Link Cribl Search to your Microsoft Azure data.

Azure Blob Storage

Configure Cribl Search to query your Azure Blob Storage data using standard or Private Link connectivity. See: Azure Blob Storage.

Azure Data Explorer

Configure Cribl Search to query Azure Data Explorer. See: Azure Data Explorer.

Azure Log Analytics

Configure Cribl Search to query log data in Azure Log Analytics workspaces. See: Azure Log Analytics.

Azure API

Configure Cribl Search to query an Azure API endpoint. See: Azure API.

4.5.1. Connect Cribl Search To Azure Blob Storage

Configure Cribl Search to query your Azure Blob Storage data, including v2 Datasets and Private Link connectivity.

Azure Blob Storage enables users to store large amounts of unstructured data on the Microsoft data storage platform. Blobs are binary large objects, including images and multimedia.

In this guide, you'll set up a Dataset Provider and a Dataset to search objects in Azure Blob Storage. You can route all data traffic over Azure Private Link or the public internet.


> For private connectivity, Cribl recommends Azure Private Link rather than public-internet routing or static-IP allowlisting. For details, see Why Cribl Recommends Private Link Over Static IPs and Configure Private Link.

Data transfer costs and other charges might apply. For details, see Data Transfer Charges.

Add an Azure Blob Storage Dataset Provider

A Dataset Provider tells Cribl Search where to query and contains access credentials. Here, you will add an Azure Blob Dataset Provider.

To add a new Dataset Provider, select **Data**, then **Dataset Providers**, then **Add Provider**.



Azure Blob Storage Dataset Provider configuration

Configure the **New Dataset Provider** modal as follows:

1. **ID** is a unique identifier for the Dataset Provider. This is how you'll reference it when assigning Datasets to it. Start the ID with a letter. The rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_provider_1`).
2. **Description** is optional. Here, you can enter a summary that will clarify the purpose of this Dataset Provider to other users.
3. Set the **Dataset Provider Type** to `Azure Blob`.
4. **Authentication method** provides three options, **Connection String**, **Blob SAS URL**, and **Client Secret**. For details on each option, see the next section.
5. Optionally, configure Private Link connectivity in the **Networking** section. See Configure Private Link.
6. Select **Save** when finished.

Azure Blob Storage Authentication

Your Azure Blob Storage access policy should include the **Read** and **List** permissions.

In the Cribl Search **New Dataset Provider** modal, use the **Authentication method** buttons to select one of these options:

- Connection String
- Blob SAS URL
- Client Secret

Connection String

The **Connection String** gives admin-level access to Search. This includes the authorization information required to access data in your Azure Storage account at runtime using Shared Key authorization. See the Azure Blob Storage documentation for more details. To view and copy your storage account connection string from the Azure portal:

1. In the Azure portal, go to your storage account.
2. Under **Security + networking**, select **Access keys**. Your account access keys appear, as well as the complete connection string for each key.
3. Select **Show keys** to show your access keys and connection strings and to enable buttons to copy the values.
4. Copy the entire **Connection string** of the key you want to use.

In the Cribl Search **New Dataset Provider** modal, enter the following information under **Authentication method**.

1. **Location** is your Azure account region, for example, `East US`. This can be found on the Azure portal **Overview** page. See the Azure Blob Storage documentation for more details.
2. **Connection String** is where you paste the **Connection string** of the key you want to use.
3. Select **Save** when finished.

Blob SAS URL

Blob SAS URL provides a more-restrictive access token called a "Shared Access Signature", which allows the user to specify which resources to grant access to. For details see, Create SAS tokens for your storage containers. To create SAS tokens for your storage containers:

1. In the Azure portal, navigate to your container.
2. Right-click the container or file and select **Generate SAS** from the drop-down menu.
3. Specify the permission levels, allowed IP addresses, and allowed protocols.
4. Review and then select **Generate SAS token and URL**.
5. The **Blob SAS token** query string and **Blob SAS URL** are displayed in the lower area of the window.
6. Copy and paste the **Blob SAS token** and **URL** values in a secure location. They'll only be displayed once and cannot be retrieved once the window is closed.

In the Cribl Search **New Dataset Provider** modal, enter the following information under **Authentication method**.

1. **Location** is your Azure account region, for example, `East US`. This can be found on the Azure portal **Overview** page. See the Azure Blob Storage documentation for more details.
2. Select **Add configurations** to specify the container(s).
    - **Container Name** is the name of the Azure Blob Storage container.
    - **Blob SAS URL** is where you paste the container-specific Blob SAS URL.
3. Select **Save** when finished.

Client Secret

The **Client Secret** is a type of authentication available for a service principal of your Microsoft Entra (formerly Azure Active Directory) application. To use this authentication method, first do the following in your Azure account:

1. Create and register a service principal for your Microsoft Entra application. To find out how, see Register a Microsoft Entra app and create a service principal from Microsoft.
2. Grant the service principal access to your data. To find out how, see Authorize access to blobs using Microsoft Entra ID.

In the Cribl Search **New Dataset Provider** modal, enter the following information under **Authentication method**.

1. **Location** is your Azure account region, for example, `East US`.
2. **Storage account name** is the name of your Azure storage account.
3. **Tenant ID** is your Microsoft Entra tenant ID. To find it, see How to find your Microsoft Entra tenant ID.
4. **Client ID** is the client ID of the Azure service principal. To find it, see Sign in to the application.
5. **Client secret** is the secret to use when connecting to your Microsoft Entra application. To get it, see Create a new client secret.

Configure Private Link



When you configure Private Link, Cribl creates a Private Endpoint in a Cribl-managed Azure network dedicated to your Cribl.Cloud Organization. This endpoint:

- Is scoped to the single storage account you specify in **Resource ID**, rather than granting broad access to your network.
- Provides a private, point-to-point path between Cribl Search and that storage account, instead of routing over the public internet.
- Does not become active until you approve the pending connection request in your own Azure account. See Approve the Private Endpoint in Azure.

This is the recommended alternative to public-internet routing or static-IP allowlisting. Private Link requires a v2 Dataset.

Before you begin, make sure you have an Azure subscription with a storage account that contains your data, and permission to approve Private Endpoint connections on that storage account.

Required Azure permissions on the storage account:

- `Microsoft.Storage/storageAccounts/privateEndpointConnections/read`
- `Microsoft.Storage/storageAccounts/privateEndpointConnections/write`
- `Microsoft.Storage/storageAccounts/privateEndpointConnectionsApproval/action`

The first two permissions let you view pending connections. The third authorizes the approval itself. Without it, the Azure portal hides the **Approve** button, and the equivalent CLI call fails with `AuthorizationFailed`.

Alternatively, use one of these built-in Azure roles, each of which grants all three permissions:

- Owner
- Contributor

- Storage Account Contributor

Use the **Networking** section of the **New Dataset Provider** modal to configure Private Link connectivity:

1. **Resource ID** is the Azure Resource Manager resource ID for your storage account.
2. **Private link request ID** is a free-form string of your choice with a 50-character limit. It appears at the end of the Private Endpoint name for the pending connection in your Azure account. Choose a value that lets you identify this specific connection later when you go to approve it - for example, `cribl-search-prod`.

To find the Resource ID in your Azure account:

1. Navigate to your Azure Blob storage account.
2. On the **Overview** page, in the **Essentials** section, select **JSON View**.
3. The resource ID for the storage account appears at the top of the **Resource JSON** page.

For more details, see Get the resource ID for a storage account in the Azure documentation.

Private Link Security Model

Security reviews often ask what Cribl creates inside your network. Cribl creates nothing there, and the connection cannot reach beyond the storage account you approve:

- **Azure storage accounts do not belong to a virtual network:** A storage account exposes its blob service at a public endpoint, such as `https://mystorageaccount.blob.core.windows.net/mycontainer/myblob`, which resolves to a public address that no virtual network controls. A Private Endpoint cannot reach into a network that holds your storage account, because the storage account was never in one.
- **The Private Endpoint lives on the Cribl side:** Cribl creates it in a Cribl-managed virtual network, in an Azure subscription dedicated to your Cribl.Cloud Organization and not shared with other customers. The endpoint is a network interface holding a private `10.x` address, plus a record in a private DNS zone that Cribl links only to that virtual network. Cribl Search then resolves the storage account hostname to that private address rather than the public one.
- **The connection is point-to-point:** Cribl scopes the endpoint to the single storage account resource ID you supply, and to the blob service on that account alone. Private Link creates no virtual network peering, propagates no routes, and opens no path from Cribl into the rest of your environment.
- **The blast radius matches static IP allowlisting:** If a Cribl Search instance were compromised, an attacker could reach only the storage account you approved. That is the same exposure as a static IP and network ACL approach, without the public-internet path or the allowlist maintenance.
- **You control approval:** Cribl submits the connection as a manual, cross-subscription request. It stays **Pending** and carries no traffic until you approve it in your own Azure account, and rejecting or deleting it

stops the private path. See Approve the Private Endpoint in Azure.

Resource	Created by	Located in
Storage account	You	Your Azure subscription
Private Endpoint and its network interface	Cribl	A Cribl-managed virtual network, in the Azure subscription dedicated to your Organization
Private DNS record for the storage account	Cribl	A private DNS zone in the Cribl-managed subscription, linked only to that virtual network
Approval of the connection	You	Your Azure subscription

Azure treats this pattern as a cross-subscription Private Link connection. In the Microsoft cross-subscription approval guide, you own the storage account, and Cribl takes the consumer role. Do not follow the consumer steps in that guide. Instead, supply the Resource ID to Cribl Search, wait for provisioning, then approve the request in your Azure account.

Why Cribl Recommends Private Link Over Static IPs


When securing access to Azure Blob Storage, customers sometimes ask for a set of static IP addresses to allowlist. Cribl recommends Private Link instead: it scopes access to only the storage account you approve, keeps traffic off the public internet, and removes the need to maintain IP allowlists.

For a full comparison of Private Link and static IP allowlisting, see Private Link Compared to Static IP Allowlisting.

Add an Azure Blob Storage Dataset

Now you'll add a Dataset that tells Cribl Search what data to search from the Dataset Provider.

To add a new Dataset, select **Data**, then **Datasets**, then **Add Dataset**.



Datasets selection

Configure the **New Dataset** modal as follows.

Identify the Dataset

Use the first few fields to uniquely identify this Dataset and specify its type:

1. Select the Dataset type: **Federated Dataset**.
2. **ID** is an identifier unique for both Cribl Search and Cribl Lake. Start the ID with a letter. The rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_1`). You'll use this to specify the Dataset in the scope of a query, telling Cribl Search to search the Dataset (for example, `dataset=my_dataset_1`).
3. **Description** is optional. Here, you can enter a summary that will clarify the purpose of this Dataset to other users.
4. Set **Dataset Provider** to the **ID** of an Azure Blob Dataset Provider.
5. Set **Type** to **v1** (standard, the default) or **v2**. v2 Datasets support faster search and Private Link connectivity, and require NDJSON, Delimited Text, Parquet, or Splunk Journal format. If you select v2, see v2 Dataset Configuration for the remaining steps.

v2 Dataset Configuration for Azure Blob

If you're switching from v1 to v2, first see federated search v2 to see what's currently supported.

For v2 Datasets, configure the following fields:

1. **Container path** is the path to the Azure Blob Storage container that holds your data. Supports templating. See the Azure Blob Storage documentation for details.
2. **Filters** narrow the search to specific objects and map them to a Datatype. Add one or more filter rows. Each row has:
    - **Filter**: A glob expression (for example, `**` for all objects, or `**/*.ndjson` for NDJSON files).
    - **Datatype ID**: The Datatype for matching files. Use **Cribl NDJSON** (`generic_ndjson`), a Delimited Text Datatype, a Parquet Datatype, or **Splunk Journal** (`splunk_journal`). For Splunk journal files, see Search Splunk Journal Files.
3. The **Partitioning scheme** defaults to `Defined in Path`. Select `Splunk DDSS` or `Splunk SmartStore` if Splunk wrote the container layout. See v2 Datasets and Splunk Partitioning.
4. Select **Save** when finished.

v2 Datasets and Splunk Partitioning

When you select `Splunk DDSS` or `Splunk SmartStore` on a v2 Dataset, Cribl Search replaces the **Filters** table with a single **Datatype** drop-down. That drop-down lists only Datatypes that use the Splunk Journal data format. Set **Container path** to the parent folder of your indexes. Cribl Search then traverses the Splunk layout and discovers the journal files itself.

For the path formats and the differences from v1, see Azure Blob Storage Partitioning Scheme and Splunk DDSS and SmartStore Buckets.

Glob Patterns

The path filter supports using glob patterns when indicating the path. The following glob patterns are available.

Pattern	Matches
`*`	Matches one path segment (any sequence of characters except `/`).
`?`	Matches any single character except `/`.
`**`	Matches any sequence of characters except `{` and `}`, but including `/`. Can match multiple segments, but not brace syntax.
`{a,b,c}`	Matches one of the comma-separated alternatives provided in the braces. Alternatives must not contain `{`, `}`, `*`, or `,`.
`{M..N}`	Matches a numeric range of non-negative integers. Examples: `{0..9}`, `{10..99}`. Leading zeros are supported (for example: `{001..099}`).

Negations

You can negate brace content by using `!`, for example:

- `!{a,b,c}` — path must not match any of the alternatives.
- `!{0..9}` — path must not match the numeric range.
- `!{foo}` — path must not match the literal `foo`.
- `*!{...}` - path matches anything that does not match the provided suffix.

Escaping

`\` (backslash) is the escape character for glob patterns. `\!{` matches a literal `!{` in the path (for example, a directory named `!{temp}`).

Set Up Paths, Regions, Partitioning

For v1 Datasets, define at least one path, region, and partitioning configuration:

1. **Skip event time filter** is optional. Toggle this on only if you're sure you want to set the time range of your searches by partition time-boundaries rather than event timestamps
2. **Container path** is the Azure Blob Storage container with your data. Start the path with the container name, and then add partitioning details. Tokens and key-value pairs are supported (see Azure Blob Storage Container Paths).
3. **Path filter** is a JavaScript filter expression that is evaluated against the container. Defaults to `true`, which matches all data, but you can customize this value.
4. The **Partitioning scheme** defaults to `Defined in Path`. For Splunk-specific alternatives, see Azure Blob Storage Partitioning Scheme.

Multiple Path Configs

Select **Add container/path** to define as many other path configurations as you want for this Dataset. Each path can have its own filter and partitioning scheme.

As with parallel Datasets, each partitioning scheme applies per path. When searching a Dataset, Cribl Search will search all its configured paths. However: **a failed search on any path in a Dataset will fail the whole search.**

Set Up Datatypes and Storage Classes

On the **Processing** left tab, you specify **Datatypes** to break data down into discrete events and define fields so they're ready to search.

Use the drop-down to set the first rule to `AWS Datatypes`. Optionally, select **Add Datatype Ruleset** to choose more rulesets - each of which contains rules applied to the data searched in your Dataset. For details, see Datatypes.

On the **Storage classes** left tab, select the access tiers that you want this Dataset to search against. You can minimize retrieval costs by selecting only warmer tiers. You must select at least one tier. For details, see Storage Classes.

Use a v2 Datatype for Azure Blob Datasets when your data is NDJSON, Delimited Text, Parquet, or Splunk Journal. For other formats, use v1 Datatypes. For details, see Datatypes.

Save the Configuration

Bypass the **Usage** left tabs for now, and select **Save** when your configuration is complete.

Approve the Private Endpoint in Azure

After you save a Dataset Provider configured for Private Link, Cribl Search submits a Private Endpoint connection request to the Azure storage account identified by the Resource ID. You must approve this request before searches can run. This requirement occurs once per storage account.

To approve the connection:

1. In the Azure portal, navigate to the storage account you specified in the **Resource ID** of the Dataset Provider.
2. Under **Security + networking**, select **Networking**.
3. Select the **Private endpoint connections** tab.
4. Find the pending connection from Cribl. Its Private Endpoint name ends with the **Private link request ID** that you entered in Cribl Search, so use that name to tell multiple Cribl connections apart. Azure derives the connection name from the Private Endpoint name, but shortens it and appends a unique identifier, so it might not show your full request ID. Every Cribl request carries the same description, `Cribl Search Fleet private endpoint connection request`, which does not identify a specific connection.
5. Select the connection and choose **Approve**.
6. Confirm the approval when prompted.

The connection status changes from **Pending** to **Approved**. Allow a few moments for the change to propagate before running a search.

Path/Partitioning Considerations

Use the following details and guidance when configuring search paths, filters, and partitioning schemes. For best practices covering path design across all object stores, see Optimize Paths.

Azure Blob Storage Container Paths

Each **Container path** specifies a separate blob of data within the Dataset. It defines the scope of this data, to narrow down what data is in the Dataset. This field supports tokens and key-value pairs. For example:

- `mycontainer/data` - where `data` becomes a field for all events of that Dataset.
- `mycontainer/${data}/${*}` - equivalent, the wildcarded path is skipped.
- `mycontainer/<key=value>/<someVarOfInterest>` - see Hive-Style Paths.
- `mycontainer/<path>/${_time:%Y}/${_time:%m}/${_time:%d}/${_time:%H}/` - time-based partitioning.

Hive-Style Paths

To search paths of the form `my-bucket/<key=value>/<someVarOfInterest>`, your expression should place the wildcard `{*}` in the ordinal position, to ignore the hive (K-V) segment:

```
my-bucket/${*}/${someVarOfInterest}
```

This will allow Cribl Search to find the wildcarded subdirectory automatically.

Basic Tokens

Basic tokens' syntax follows that of JS template literals: `${token_name}` - where `token_name` is the field (name) of interest.

For example, if the path was set to `/var/log/${hostname}/${dataSource}/`, you could use a filter such as `hostname=='myHost' && dataSource=='mydataSource'` to specify data only from the `/var/log/myHost/mydataSource/` subdirectory.

Time-Based Tokens

Paths with time notation can be referenced with tokens, having a direct effect on the earliest and latest boundaries. The supported time fields are:

- `_time` is the raw event's timestamp.
- `__earliest` is the search start time.
- `__latest` is the search end time.

Time-based tokens are processed as follows:

- For each path, times must be notated in descending order. So Year/Month/Day order is supported, but Day/Month/Year is not.
- Paths may contain more than one time component. For example, `/my/path/2020-04/20/`.
- In a given path, each time component can be used only once. So `/my/path/${_time:%Y}/${_time:%m}/${_time:%d}/...` is a valid expression format, but

`/my/path/${_time:%Y}/${_time:%m}/${host}/${_time:%Y}/...` (with a repeated `Y`) is not supported.

- For each path, all extracted dates/times are considered in UTC.



Cribl recommends that your path always include and tokenize the largest available time fields, proceeding down to the smallest desired time fields. Otherwise, your searches might yield unexpected results, because Cribl Search will default the omitted fields to their earliest allowed value.

The following `strptime` format components are allowed:

- `Y`, `y` for years
- `m`, `B`, `b`, `e` for months
- `d`, `j` for days
- `H`, `I` for hours
- `M` for minutes
- `S` for seconds
- `s` for Unix time (seconds since 1/1/1970)

Time-based token syntax follows that of a slightly modified JS template literal: `${_time:some_strptime_format_component}`. Examples:

Path	Matches
`/path/${_time:%Y}/${_time:%m}/${_time:%d}/...`	`/path/2020/04/20/...`
`/path/${_time:year=%Y}/${_time:month=%m}/${_time:day=%d}/...`	`/path/year=2020/month=`
`/path/${_time:%Y-%m-%d}/...`	`/path/2020-05-20/...`

Set Query Time Range by Partition

If your data is partitioned by time (so your paths probably use time-based tokens), you can tell Cribl Search to ignore events' timestamps, and instead set the time range using the partition time-boundaries.

For example, an event with the timestamp of `2025-07-01T23:59:00.000` might be stored in the July 2 partition. Queries for July 1 or July 2 might not find it: the first due to wrong partition, the second due to wrong `_time`. Using partition time for the query range avoids this issue.

To search by partition time range, toggle on **Skip event time filter** when setting up your paths. Then, any time range you set (in the Cribl Search UI or with `earliest/latest` in the query text) will use partition time instead of event time.

If you toggle on the **Skip event time filter** option, Cribl Search will ignore the `_time` field in your events. Do **not** enable this option if your paths don't use time-based tokens.

Azure Blob Storage Path Filter

Each **Path filter** is a JavaScript expression that Cribl Search evaluates against the corresponding **Container path**. The value of the **Path filter** field defaults to `true`, which matches all data. However, you can customize this value almost arbitrarily.

For example, if a Dataset has this **Path filter**:
`source.endsWith('.log') || source.endsWith('.txt')`
...this configuration will search only files/objects with `.log` or `.txt` extensions.

At the right edge of the **Path filter** field are a Copy button and an Expand button that opens a validation modal.

On a v1 Dataset that uses DDSS or SmartStore partitioning, you can provide the index name as **Path filter**, for example: `index=="index_y"`.

v2 Datasets have no **Path filter** field. To narrow a v2 search to one index, filter on the `index` field in the query.

Azure Blob Storage Partitioning Scheme

Partitioning schemes apply to v1 and v2 Datasets. For how the Splunk schemes change the configuration of a v2 Dataset, see v2 Datasets and Splunk Partitioning.

Each **Partitioning scheme** drop-down offers alternative options for partitioning inbound data from Splunk. You can choose between `Splunk DDSS` and `Splunk SmartStore`.

With either option, in the corresponding **Container path** field, provide the path where indexes are stored (that is, the parent folder of your index).

For Splunk DDSS, the full path takes the form:
`<parent_folder>/<indexName>/db/db_<latestTime>_<earliestTime>_<bucketId>/rawdata/journal`
...or:
`<parent_folder>/<indexName>/db_<latestTime>_<earliestTime>_<bucketId>/rawdata/journal.gz`

For SmartStore, the full path takes the form:
`<parent_folder>/<indexName>/db/<2-letter-hash>/<2-letter-hash>/<bucket_id_number-origin_guid>/<"guidSplunk"-uploader_guid>/`

With either option, if you organize your container using this default file path, Cribl Search will automatically discover its content.

Both layouts put the index above the time-based part of the path, so name the index in every search against these Datasets. A time range alone still leaves Cribl Search traversing every index in the container:

```
dataset="my_ddss_dataset" earliest=-7d latest=-1d
| where index=="my_index"
```

Copy

Use the `where` operator with case-sensitive `==`, and spell the index name exactly as it appears in the path. Only an exact match narrows the path.

Search Azure Blob Storage

4.5.2. Connect Cribl Search To Azure Data Explorer

Configure Cribl Search to query Azure Data Explorer.

Cribl Search allows you to search database tables from Azure Data Explorer (ADX). ADX stores log data in databases, which in turn contain one or more of the tables defined in the Azure namespace.



Azure Data Explorer has a 500,000 result limit per search.

In this guide, you'll set up a Dataset Provider and a Dataset to search database tables in Azure Data Explorer.

Add an Azure Data Explorer Dataset Provider

A Dataset Provider tells Cribl Search where to query and contains access credentials. Here, you will add an Azure Data Explorer Dataset Provider.

To add a new Dataset Provider, select **Data**, then **Dataset Providers**, then **Add Provider**.

Set the following configurations in the **New Dataset Provider** modal:

1. **ID** is a unique identifier for the Dataset Provider. This is how you'll reference it when assigning Datasets to it. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_provider_1`).
2. **Description** is optional.
3. Set **Dataset Provider Type** to **Azure Data Explorer**.
4. The following inputs are retrieved from Azure Data Explorer after creating and registering a Microsoft Entra service principal and then authorizing it to access an Azure Data Explorer database. See Microsoft's guide - Create a Microsoft Entra application registration in Azure Data Explorer for details.
    - **Tenant ID** is the ID of the Directory (tenant) in Azure Data Explorer to retrieve information from.
    - **Client ID** is the ID of the Application (client) in Azure Data Explorer.
    - **Client secret** is the client secret that will be used as the secret in the connection to the application.
5. Select **Save** when finished.

Add an Azure Data Explorer Dataset

Now you'll add a Dataset that tells Cribl Search what data to search from the Dataset Provider.

To add a new Dataset, select **Data**, then **Datasets**, then **Add Dataset**.

Set the following configurations in the **New Dataset** modal:

1. Select the Dataset type: **Federated Dataset**.
2. **ID** is an identifier unique for both Cribl Search and Cribl Lake. You'll use this to specify the Dataset in a query's scope, telling Cribl Search to search the Dataset. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_1`).
3. **Description** is optional.
4. Set **Dataset Provider** to the **ID** of an Azure Data Explorer provider.
    - Enter the **Cluster** name and select its region from the **Location** drop-down.
    - **Database** is the database name.
    - **Table or query** supports the Kusto Query Language. You can specify the name of a table to query, like `logs`, or enter a Kusto query, such as `StormEvents | summarize PropertyDamage = sum(DamageProperty) by State | join kind=innerunique PopulationData on State`.
    - **Timestamp field** is the event field with a timestamp. You need to specify a timestamp field to query by date and time in Cribl Search.
    - **Timestamp field contents** is the data type of the timestamp field. Defaults to Kusto's datetime data type.
5. In **Processing**, you can apply rules for breaking data into discrete events. For more information, see Datatypes.
6. Select **Save** when finished.

Search Azure Data Explorer

Now that you have a Dataset Provider and Dataset, you're ready to start searching.

It can take a few minutes for a search to start returning results. Here's an example of an initial exploratory search:

```
dataset="adx" | limit 1000
```

Copy

4.5.3. Connect Cribl Search To Azure Log Analytics

Configure Cribl Search to query log data stored in Azure Log Analytics workspaces.

In this guide, you will set up a Dataset Provider and a Dataset to search log tables in an Azure Log Analytics workspace.

Before You Start

Azure prerequisites:

- Create an **App Registration** in Microsoft Entra ID. Assign the **Log Analytics Reader** role to this app registration on the target Log Analytics workspace. See Microsoft's guide to registering an application for details.
- Collect the following values from the app registration before configuring the provider:
  - **Tenant ID** (your Microsoft Entra tenant GUID)
  - **Client ID** (the application client ID)
  - **Client Secret** (the secret **value**, not the secret ID)
  - **Workspace ID** (the Log Analytics workspace GUID)

Network prerequisites:

- The Cribl Search **Leader node** must have outbound HTTPS access to `api.loganalytics.io` and `login.microsoftonline.com`.
- If your environment restricts outbound traffic, allowlist the Leader node egress IP in your firewall or network policy before saving the provider.

Add an Azure Log Analytics Dataset Provider

A Dataset Provider tells Cribl Search where to query and stores the access credentials for that connection.

To add a new Azure Log Analytics Dataset Provider, select **Data**, then **Dataset Providers**, then **Add Provider**.

Set the following configurations in the **New Dataset Provider** modal:

1. **ID** is a unique identifier for the Dataset Provider. This is how you will reference it when assigning Datasets to it. Start the ID with a letter. The rest of the ID can use letters, numbers, and underscores (for example, `my_log_analytics_provider`).
2. **Description** is optional.
3. Set **Dataset Provider Type** to **Azure Log Analytics**.

4. Enter the following values from your Microsoft Entra app registration:
    - **Tenant ID** is the GUID of your Microsoft Entra tenant.
    - **Client ID** is the GUID of the app registration.
    - **Client Secret** is the secret value for the app registration. Enter the **secret value**, not the secret ID. The secret is stored encrypted at rest.
    - **Workspace ID** is the GUID of the Log Analytics workspace this provider connects to.
5. Select **Save** when finished.

When you save the provider, Cribl Search runs an automatic connectivity check against the configured workspace. If the check fails, a message appears explaining the cause. See Connectivity Check Errors for guidance on each error type.

Connectivity Check Errors

The connectivity check runs a lightweight query (`print 1`) against the workspace with a 30-second timeout. Failures return one of the following messages:

Error message	Cause and resolution
Invalid client secret. Use the secret value (not the secret ID) and confirm the secret has not expired.	The secret value was incorrect or has expired. Re-enter the correct secret value from the app registration.
Invalid tenant ID. Verify the Microsoft Entra tenant ID is correct.	The tenant ID does not match a valid Microsoft Entra directory. Check the value and re-enter it.
Invalid client ID. Verify the application (client) ID is correct.	The app registration was not found in the specified tenant. Verify the client ID.
Invalid credentials. Verify your tenant ID, client ID, and client secret.	Authentication failed. Check all three credential fields for typos or expired values.
Application not provisioned. Ask your Microsoft Entra administrator to grant admin consent for the application in your tenant.	The app registration exists but admin consent has not been granted in this tenant. Contact your Microsoft Entra administrator.
Insufficient permissions. Verify the application has the Log Analytics Reader role and has been granted access to this workspace.	The app registration was authenticated successfully but lacks the Log Analytics Reader role on this workspace.
Workspace not found. Verify the workspace ID is correct and belongs to the configured tenant.	The workspace GUID does not match a workspace accessible in this tenant. Confirm the workspace ID.

Error message	Cause and resolution
Azure Log Analytics is temporarily unavailable. Try again in a few minutes.	Microsoft returned a 5xx error. Retry after a brief wait. If the problem persists, check the Azure status page.
Unable to reach Azure Log Analytics. Check your network connectivity and firewall settings.	The Leader node could not reach `api.loganalytics.io` or `login.microsoftonline.com`. Verify network access and egress allowlists.

Add an Azure Log Analytics Dataset

Now you will add a Dataset that tells Cribl Search which log table to query within the provider's workspace.

To add a new Dataset, select **Data**, then **Datasets**, then **Add Dataset**.

Set the following configurations in the **New Dataset** modal:

1. Select the Dataset type: **Federated Dataset**.
2. **ID** is an identifier unique for both Cribl Search and Cribl Lake. You will use this to specify the Dataset in a query's scope. Start the ID with a letter. The rest of the ID can use letters, numbers, and underscores (for example, `my_la_dataset`).
3. **Description** is optional.
4. Set **Dataset Provider** to the **ID** of an Azure Log Analytics provider, then configure the following fields:
    - **Table or query** (required) is the source of data for this Dataset. Enter a bare table name such as `SecurityEvent`, or a KQL expression such as `SecurityEvent | where EventID in (4624, 4625)`. The value must not contain control commands (`.drop`, `.clear`, `.delete`, `.alter`, `.create`, `.rename`). You can include operators like `extend`, `project`, `summarize`, and `sort` in this field. When you run a Cribl Search query against this Dataset, filter conditions (such as `where`) are sent to Azure for server-side execution when possible, while other operations run locally on the Cribl Search Leader.
    - **Timestamp field** (optional, defaults to `TimeGenerated`) is the field promoted to the canonical `_time` field in Cribl Search results.
    - **Timestamp field contents** (optional, defaults to `kusto_datetime`) is the data format of the timestamp field. Select from the following options:
        - `kusto_datetime`: Kusto datetime scalar type (default)
        - `epoch_sec`: Unix epoch seconds
        - `epoch_millis`: Unix epoch milliseconds
        - `iso_string`: ISO 8601 string

5. In **Processing**, you can apply rules for breaking data into discrete events. For more information, see Datatypes.
6. Select **Save** when finished.



The **Table or query** field currently requires a non-empty value. Support for blank-table Datasets (where the analyst provides the full table reference in the query) is planned for a future release.

Search Azure Log Analytics

Now that you have a Dataset Provider and Dataset, you are ready to start searching.

```
dataset="my_la_dataset" | limit 1000
```

Copy

It can take a few moments for a search to start returning results on the first run.

Search Row Limits

Cribl Search enforces a **50,000 row limit** per query. When the entire query can be executed on the Azure side, this limit is appended to the KQL as `| limit 50000`. If your query already contains a `| limit` clause, KQL applies whichever value is lower. When the query includes operations that run locally in Cribl Search (such as aggregations), the limit is enforced locally instead.

Microsoft enforces separate per-query limits: 500,000 rows, ~100 MB response size (~64 MB compressed), and a 10-minute query timeout. Cribl Search sends data queries with a 10-minute server-side timeout, which is the maximum Azure allows. If a response hits one of these limits, Cribl Search returns the rows that were received and records a warning in the Search logs. To reduce the likelihood of truncation, add filters to your query or Dataset scope, or reduce the time range of the search.

4.5.4. Connect Cribl Search To Azure API

Configure Cribl Search to query an Azure API endpoint.

Microsoft Azure is a public cloud computing platform that offers a range of services that include Infrastructure as a Service (IaaS), Platform as a Service (PaaS), and Software as a Service (SaaS).

In this guide, you'll set up a Dataset Provider and a Dataset to search the disks, networkSecurityGroups, virtualMachines, and webapps endpoints in the Azure API.

Azure API Authorization

Set up an Azure service account with a client secret credential for Search. For details, see Create a Microsoft Entra application and service principal that can access resources. You will need the account credentials to Create a Dataset Provider.

Also, you can assign the built-in role of Reader to the application so it has read access to all endpoints. To limit access to the current Cribl Search endpoints (listed below), create a custom role:

- Microsoft.Compute/disks
- Microsoft.Network/networkSecurityGroups
- Microsoft.Compute/virtualMachines
- Microsoft.Web/sites

You can modify permissions as the application adds more endpoints. For details, see Create an Azure custom role.

Add an Azure API Dataset Provider

A Dataset Provider tells Cribl Search where to query and contains access credentials. Here, you will add an Azure API Dataset Provider.

To add a new Dataset Provider, select **Data**, then **Dataset Providers**, then **Add Provider**.

Set the following configurations in the **New Dataset Provider** modal:

1. **ID** is a unique identifier for the Dataset Provider. This is how you'll reference it when assigning Datasets to it. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_provider_1`).
2. **Description** is optional.
3. Set **Dataset Provider Type** to **Azure API**.
4. Select **Add Configuration** to specify your Azure account(s).

- **Account Name** is the Azure account name.
- **Tenant ID** is the ID of the Microsoft Entra ID to retrieve information from.
- **Client ID** is the ID of the application that will connect to Microsoft Entra ID Active Directory. For details, see Register an application.
- **Client Secret** is the key that will be used as the secret in the connection to Microsoft Entra ID. For details, see Add a client secret.

5. Select **Save** when finished.

Add an Azure API Dataset

Now you'll add a Dataset that tells Cribl Search what data to search from the Dataset Provider.

To add a new Dataset, select **Data**, then **Datasets**, then **Add Dataset**.

Set the following configurations in the **New Dataset** modal:

1. Select the Dataset type: **Federated Dataset**.
2. **ID** is an identifier unique for both Cribl Search and Cribl Lake. You'll use this to specify the Dataset in a query's scope, telling Cribl Search to search the Dataset. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_1`).
3. **Description** is optional.
4. Set **Dataset Provider** to the **ID** of an Azure API Dataset Provider.
5. Select **Add endpoint** to select the endpoints for your Dataset.
6. **Enabled endpoints**: Select an endpoint from the drop-down menu. Your options are:
   - virtualMachines
   - disks
   - networkSecurityGroups
   - webapps
7. **Subscription IDs** is a list of the Subscription IDs within the tenant to query with this Dataset.
8. In **Processing**, you can apply rules for breaking data into discrete events. For more information, see Datatypes.
9. In **Snapshots**, you can set up API Snapshots.
10. Select **Save** when finished.

Search Azure API

Now that you have a Dataset Provider and Dataset, you're ready to start searching.

Search results can start showing up within a second or two, but when the search completes depends on how much data there is in the account.

4.6. Connect Cribl Search To Google

Link Cribl Search to your Google services.

Google Cloud Storage

Configure Cribl Search to query your Google Cloud Storage data. See: Google Cloud Storage.

Google Cloud Platform API

Configure Cribl Search to query a Google Cloud Platform API endpoint. See: Google Cloud Platform API.

Google Workspace API

Configure Cribl Search to query a Google Workspace API endpoint. See: Google Workspace API.

4.6.1. Connect Cribl Search To Google Cloud Storage

Configure Cribl Search to query your Google Cloud Storage data.

Google Cloud Storage is a managed service for storing unstructured data.

In this guide, you'll set up a Dataset Provider and a Dataset to search your Google Cloud Storage account.

Data transfer costs and other charges may apply. For details, see the Data Transfer Charges section below.

Add a Google Cloud Storage Dataset Provider

A Dataset Provider tells Cribl Search where to query and contains access credentials. Here, you will add a Google Cloud Storage Dataset Provider.

To add a new Dataset Provider, select **Data**, then **Dataset Providers**, then **Add Provider**.

Configure the **New Dataset Provider** modal as follows:

1. **ID** is a unique identifier for the Dataset Provider. This is how you'll reference it when assigning Datasets to it. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_provider_1`).
2. **Description** is optional.
3. Set **Dataset Provider Type** to **Google Cloud Storage**.
4. The **Service Account Credentials** are the contents of your Google Cloud service account (JSON keys). You can also drag and drop a file into the field, or upload a file by clicking the upload button.
   For more information on the permissions needed, see the Google Cloud Permissions section.
   For more information on obtaining your Google Cloud Storage credentials, see Google's Authenticate to Cloud Storage.
5. Specify an **Endpoint**. If empty, the endpoint will default to `https://storage.googleapis.com`. For a list of the endpoints, see the Google Cloud Storage API Reference doc.
6. Select **Save** when finished.

Google Cloud Permissions

To let Cribl Search access your Google Cloud data, your Google Cloud service account needs at the minimum all of the following roles:

- `Storage Legacy Bucket Reader`
- `Storage Legacy Object Reader`

Alternatively, you can define a custom role that has all of the following permissions:

- `storage.buckets.get`
- `storage.objects.list`

For more information, see Google's IAM roles for Cloud Storage.

Add a Google Cloud Storage Dataset

Now you'll add a Dataset that tells Cribl Search what data to search from the Dataset Provider.

To add a new Dataset, select **Data**, then **Datasets**, then **Add Dataset**.

Set the Dataset type to **Federated Dataset**, and configure the following settings.

Identify the Dataset

Use the first few fields to uniquely identify this Dataset and specify its type:

1. **ID** is an identifier unique for both Cribl Search and Cribl Lake. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_1`). You'll use this to specify the Dataset in a query's scope, telling Cribl Search to search the Dataset (for example, `dataset=my_dataset_1`).
2. **Description** is optional.
3. Set **Dataset Provider** to the **ID** of a Google Cloud Storage Dataset Provider.

Set Up Paths and Partitioning

Define at least one path, filter, and partitioning configuration:

1. **Skip event time filter** is optional. Toggle this on only if you're sure you want to set the time range of your searches by partition time-boundaries rather than events' timestamps
2. **Bucket Path** is the path to the Google Cloud Storage objects you'd like to search. Start the path with the bucket name, for example: `my-bucket/data/*`. Tokens and key-value pairs are supported. For details, see bucket path.
3. **Path Filter** is a JavaScript filter expression that is evaluated against the S3 bucket path. Defaults to `true`, which matches all data, but you can customize this value.
4. The **Partitioning scheme** defaults to `Defined in Path`. For Splunk-specific alternatives, see Partitioning Scheme.

Multiple Path Configs

Select **Add bucket/path** to define as many other path configurations as you want for this Dataset. Each path can have its own filter and partitioning scheme.

As with parallel Datasets, each partitioning scheme applies per path. When searching a Dataset, Cribl Search will search all its configured paths. However: **a failed search on any of a Dataset's paths will fail the whole search.**

Set Up Datatypes and Storage Classes

On the **Processing** left tab, you specify **Datatypes** to break data down into discrete events and define fields so they're ready to search.

Use the drop-down to set the first rule to `AWS Datatypes`. Optionally, click **Add Datatype Ruleset** to select more rulesets - each of which contains rules applied to the data searched in your Dataset. For details, see Datatypes.

On the **Storage classes** left tab, select the storage classes that you want this Dataset to search against. You can minimize retrieval costs by selecting only warmer classes. You must select at least one class. For details, see Storage Classes.

Save the Configuration

Bypass the **Usage** left tabs for now, and select **Save** when your configuration is complete.

Path/Partitioning Considerations

This section offers details and guidance on configuring search paths, filters, and partitioning schemes. For best practices covering path design across all object stores, see Optimize Paths.

Bucket Paths

The **Bucket Path** specifies the data that the Dataset consists of. It defines the scope of data, to narrow down what data is in the Dataset. This is a JavaScript expression that supports tokens and key-value pairs. For example,

- `my-bucket/${data}/` - where `data` becomes a field for all events of that Dataset.
- `my-bucket/${data}/${*}` - equivalent, the wildcarded path is skipped.
- `my-bucket/<key=value>/<someVarOfInterest>` - see Hive-Style Paths just below.

Hive-Style Paths

To search paths of the form `my-bucket/<key=value>/<someVarOfInterest>`, your expression should place the wildcard `{*}` in the ordinal position, to ignore the hive (K-V) segment:

```
my-bucket/${*}/${someVarOfInterest}
```

This will allow Cribl Search to find the wildcarded subdirectory automatically.

Basic Tokens

Basic tokens' syntax follows that of JS template literals: `${token_name}` - where `token_name` is the field (name) of interest.

For example, if the path was set to `/var/log/${hostname}/${dataSource}/`, you could use a filter such as `hostname=='myHost' && dataSource=='mydataSource'` to specify data only from the `/var/log/myHost/mydataSource/` subdirectory.

Time-Based Tokens

Paths with time notation can be referenced with tokens, having a direct effect on the earliest and latest boundaries. The supported time fields are:

- `_time` is the raw event's timestamp.
- `__earliest` is the search start time.
- `__latest` is the search end time.

Time-based tokens are processed as follows:

- For each path, times must be notated in descending order. So Year/Month/Day order is supported, but Day/Month/Year is not.
- Paths may contain more than one time component. For example, `/my/path/2020-04/20/`.
- In a given path, each time component can be used only once. So `/my/path/${_time:%Y}/${_time:%m}/${_time:%d}/...` is a valid expression format, but `/my/path/${_time:%Y}/${_time:%m}/${host}/${_time:%Y}/...` (with a repeated `Y`) is not supported.
- For each path, all extracted dates/times are considered in UTC.



Cribl recommends that your path always include and tokenize the largest available time fields, proceeding down to the smallest desired time fields. Otherwise, your searches might yield unexpected results, because Cribl Search will default the omitted fields to their earliest allowed value.

The following `strptime` format components are allowed:

- `Y`, `y` for years
- `m`, `B`, `b`, `e` for months
- `d`, `j` for days
- `H`, `I` for hours
- `M` for minutes

- `S` for seconds
- `s` for Unix time (seconds since 1/1/1970)

Time-based token syntax follows that of a slightly modified JS template literal: `${_time:some_strptime_format_component}`. Examples:

Path	Matches
`/path/${_time:%Y}/${_time:%m}/${_time:%d}/...`	`/path/2020/04/20/...`
`/path/${_time:year=%Y}/${_time:month=%m}/${_time:day=%d}/...`	`/path/year=2020/month=`
`/path/${_time:%Y-%m-%d}/...`	`/path/2020-05-20/...`

Set Query Time Range by Partition

If your data is partitioned by time (so your paths probably use time-based tokens), you can tell Cribl Search to ignore events' timestamps, and instead set the time range using the partition time-boundaries.

For example, an event with the timestamp of `2025-07-01T23:59:00.000` might be stored in the July 2 partition. Queries for July 1 or July 2 might not find it: the first due to wrong partition, the second due to wrong `_time`. Using partition time for the query range avoids this issue.

To search by partition time range, toggle on **Skip event time filter** when setting up your paths. Then, any time range you set (in the Cribl Search UI or with `earliest/latest` in the query text) will use partition time instead of event time.



If you toggle on the **Skip event time filter** option, Cribl Search will ignore the `_time` field in your events. Do **not** enable this option if your paths don't use time-based tokens.

Path Filter

Each **Path filter** is a JavaScript expression that Cribl Search evaluates against the corresponding **Bucket path**. The **Path filter** field's value defaults to `true`, which matches all data. However, you can customize this value almost arbitrarily.

For example, with this **Path filter**:
`source.endsWith('.log') || source.endsWith('.txt')`
...this configuration will search only files/objects with `.log` or `.txt` extensions.

At each **Path filter** field's right edge are a Copy button and an Expand button that opens a validation modal.

With DDSS or SmartStore partitioning, you can provide the index name as the **Path filter**, for example:
`index=="index_y"`

Partitioning Scheme

Each **Partitioning scheme** drop-down offers alternative options for partitioning inbound data from Splunk. You can choose between `Splunk DDSS` and `Splunk SmartStore`.

With either option, in the corresponding **Bucket path** field, provide the path where indexes are stored (that is, your index's parent folder).

For Splunk DDSS, the full path takes the form:
`<parent_folder>/<indexName>/db/db_<latestTime>_<earliestTime>_<bucketId>/rawdata/journal`
...or:
`<parent_folder>/<indexName>/db_<latestTime>_<earliestTime>_<bucketId>/rawdata/journal.gz`

For SmartStore, the full path takes the form:
`<parent_folder>/<indexName>/db/<2-letter-hash>/<2-letter-hash>/<bucket_id_number-origin_guid>/<"guidSplunk"-uploader_guid>/`

With either option, if you organize your bucket using this default file path, Cribl Search will automatically discover its content.

Both layouts put the index above the time-based part of the path, so name the index in every search against these Datasets. A time range alone still leaves Cribl Search traversing every index in the bucket:

```
dataset="my_ddss_dataset" earliest=-7d latest=-1d
| where index=="my_index"
```

Copy

Use the `where` operator with case-sensitive `==`, and spell the index name exactly as it appears in the path. Only an exact match narrows the path.

Search Google Cloud Storage

Now that you have a Dataset Provider and Dataset, you're ready to start searching.

Search results can start showing up within a second or two, but when the search completes depends on how much data there is in the account.

Data Transfer Charges

Cribl Search uses both Class A and Class B operations in Google Cloud Storage. To understand the fees associated with these operations, refer to the Google Cloud Storage's Operation charges.

Additionally, retrieval fees may apply depending on the storage class of the bucket. See the Retrieval Fees section for details.

Using Cribl Search to read data from US regions might also result in General network usage egress charges. These charges fall under the “Egress Worldwide Destinations (excluding Asia & Australia)” category. For detailed information, refer to the General network usage.

4.6.2. Connect Cribl Search To Google Cloud Platform API

Configure Cribl Search to query a Google Cloud Platform API endpoint.

Google Cloud Platform provides a suite of computing services including data management, web and video delivery, AI and machine learning tools.

In this guide, you'll set up a Dataset Provider and a Dataset to search the instances, disks, security policies, and locations endpoints in your Google Cloud Platform account.

Add a Google Cloud Platform API Dataset Provider

A Dataset Provider tells Cribl Search where to query and contains access credentials. Here, you will add a Google Cloud Platform API Dataset Provider.

To add a new Dataset Provider, select **Data**, then **Dataset Providers**, then **Add Provider**.

Set the following configurations in the **New Dataset Provider** modal:

1. **ID** is a unique identifier for the Dataset Provider. This is how you'll reference it when assigning Datasets to it. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_provider_1`).
2. **Description** is optional.
3. Set **Dataset Provider Type** to **Google Cloud Platform API**.
4. Select **Add Configuration** to specify your Google Cloud Platform account. In the **Account Configurations** table, enter:
    - **Name**: Google Cloud Platform account name.
    - **Service Account Credentials**: The contents of your Google Cloud service account (JSON keys) file. You can also drag and drop a file into the field, or upload a file by clicking the upload button.
5. Select **Save** when finished.

Add a Google Cloud Platform API Dataset

Now you'll add a Dataset that tells Cribl Search what data to search from the Dataset Provider.

To add a new Dataset, select **Data**, then **Datasets**, then **Add Dataset**.

Set the following configurations in the **New Dataset** modal:

1. Select the Dataset type: **Federated Dataset**.
2. **ID** is an identifier unique for both Cribl Search and Cribl Lake. You'll use this to specify the Dataset in a query's scope, telling Cribl Search to search the Dataset. Start the ID with a letter; the rest of the ID can

use letters, numbers, and underscores (for example, `my_dataset_1`).

3. **Description** is optional.
4. Set **Dataset Provider** to the **ID** of a Google Cloud Platform Dataset Provider.
5. Select **Add endpoint** to select the endpoints for your Dataset.
6. **Enabled endpoints**: Select an endpoint from the drop-down menu. For details on the endpoints, see the Compute Engine API reference docs. Your options are:
    - `v1.instances`
    - `v1.disks`
    - `v1.securityPolicies`
    - `v1.projects.locations.functions`
    - `v2.projects.locations.functions`

    1. **Region**: The region of your Google Cloud Platform account, provided for certain endpoints, indicates its location.
7. In **Processing**, you can apply rules for breaking data into discrete events. For more information, see Datatypes.
8. In **Snapshots**, you can set up API Snapshots.
9. Select **Save** when finished.

Search Google Cloud Platform

Now that you have a Dataset Provider and Dataset, you're ready to start searching.

Search results can start showing up within a second or two, but when the search completes depends on how much data there is in the account.

4.6.3. Connect Cribl Search To Google Workspace API

Configure Cribl Search to query a Google Workspace API endpoint.

A Google Workspace plan offers business-specific email as well as collaboration tools such as Gmail, Calendar, Meet, Chat, Drive, Docs, Sheets, Slides, Forms, and Sites.

In this guide, you'll set up a Dataset Provider and a Dataset to search the activities of the admin, devices, drives, logins, and tokens endpoints on your Google Workspace account.

Google Workspace API Authorization

To allow Cribl Search to read your data, do the following on the Google Workspace side:

1. Create or use an existing Google Workspace service account.
2. Configure the service account with domain-wide delegation for the following scope:

   ```
   https://www.googleapis.com/auth/admin.reports.audit.readonly
   ```

   Copy

   Read more on domain-wide delegation.
3. Obtain the service account credentials. You'll need the API keys in JSON format when creating the Google Workspace API Dataset Provider.
4. Create or use an existing Google Workspace user account. This can be a real user or just a service placeholder. You'll need the user account's email address when creating the Google Workspace API Dataset Provider.
5. Authorize the user account with the Super Admin role. Due to how the Google Workspace APIs work, the user account must have the full Super Admin permissions for the resources that you want to search.

Add a Google Workspace API Dataset Provider

A Dataset Provider tells Cribl Search where to query and contains access credentials. Here, you will add a Google Workspace API Dataset Provider.

To add a new Dataset Provider, select **Data**, then **Dataset Providers**, then **Add Provider**.

Set the following configurations in the **New Dataset Provider** modal:

1. **ID** is a unique identifier for the Dataset Provider. This is how you'll reference it when assigning Datasets to it. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_provider_1`).

2. **Description** is optional.
3. Set **Dataset Provider Type** to **Google Workspace API**.
4. Select **Add Configuration** to specify your Google Workspace account(s).
    - **Account Name** is the name of your Google Workspace account.
    - **Impersonated Account's Email Address** is the email address of the **user account** that's used for searching the APIs. For details, see Authorization.
    - **Service Account Credentials** is the JSON keys of your Google Workspace **service account**. For details, see Authorization.
5. Select **Save** when finished.

Add a Google Workspace API Dataset

Now you'll add a Dataset that tells Cribl Search what data to search from the Dataset Provider.

To add a new Dataset, select **Data**, then **Datasets**, then **Add Dataset**.

Set the following configurations in the **New Dataset** modal:

1. Select the Dataset type: **Federated Dataset**.
2. **ID** is an identifier unique for both Cribl Search and Cribl Lake. You'll use this to specify the Dataset in a query's scope, telling Cribl Search to search the Dataset. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_1`).
3. **Description** is optional.
4. Set **Dataset Provider** to the **ID** of a Google Workspace Dataset Provider.
5. Select **Add endpoint** to select the endpoints for your Dataset.
6. **Enabled endpoints**: Select an endpoint from the drop-down menu. For details on the endpoints, see the Reports API Overview reference docs. Your options are:
    - `admin`
    - `mobile`
    - `devices`
    - `drive`
    - `login`
    - `token`
7. In **Processing**, you can apply rules for breaking data into discrete events. For more information, see Datatypes.
8. In **Snapshots**, you can set up API Snapshots.

9. Select **Save** when finished.

Search Google Workspace API

Now that you have a Dataset Provider and Dataset, you're ready to start searching.

Search results can start showing up within a second or two, but when the search completes depends on how much data there is in the account.

4.7. Connect Cribl Search To ClickHouse

Configure Cribl Search to query ClickHouse Cloud or a self-managed ClickHouse server.

ClickHouse is a column-oriented SQL database management system for online analytical processing, available both as open-source software and a cloud offering.

To start searching your ClickHouse databases with Cribl Search, you need:

- A ClickHouse Dataset Provider, which contains access credentials, and specifies what ClickHouse server or Cloud service to query.
- A ClickHouse Dataset, which points Cribl Search at a specific table, view, or query in a ClickHouse database.

Each Dataset Provider can have multiple Datasets assigned to it.

Add a ClickHouse Dataset Provider

Before adding a ClickHouse Dataset Provider, do the following:

1. Make sure your ClickHouse server or Cloud service has the HTTP interface enabled. Ideally, use HTTPS over the default port 8443.
2. Check your ClickHouse URL, username, and password.

To add a ClickHouse Dataset Provider in Cribl Search:

1. Log in to Cribl Search as an Admin or Editor Search Member.
2. Select **Data**, then **Dataset Providers**, then **Add Provider**.
3. In **ID**, enter a unique identifier. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_clickhouse_database_1`).
   This is how you or other Search Members reference your Dataset Provider when adding Datasets to it.
4. In **Description**, you can briefly describe your Dataset Provider, so that other Search Members know its purpose.
5. Set **Dataset Provider Type** to **ClickHouse**.
6. Enter the following:
   - **Username**: Your ClickHouse username, for authentication.
   - **Password**: Your ClickHouse password, for authentication.
   - **Endpoint**: Your ClickHouse server or Cloud service URL.
7. Select **Save**.

Now, you're ready to add a ClickHouse Dataset.

Add a ClickHouse Dataset

With a ClickHouse Dataset Provider ready, you can start adding ClickHouse Datasets:

1. Log in to Cribl Search as an Admin or Editor Search Member.
2. Select **Data**, then **Datasets**, then **Add Dataset**.
3. Select the Dataset type: **Federated Dataset**.
4. In **ID**, enter a unique identifier. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `clickhouse_dataset_1`).
   You and other Search Members will reference this ID when searching your Dataset (`dataset="clickhouse_dataset_1"`).
5. In **Description**, you can briefly describe your Dataset, so that other Search Members know its purpose.
6. In **Select a Provider**, pick the ID of a ClickHouse Dataset Provider.
7. Enter the following:
   - **Database name**: Case-sensitive name of the ClickHouse database. If not set, defaults to the ClickHouse `default_database` setting.
   - **Table name, view, or query**: The name of the table or view, or a query. May be a simple name (`logs`) or an SQL query (`select * from logs`). Mind that for queries, and for tables without sorting keys, results will be limited to 100,000.
   - **Timestamp field**: Optional, case-sensitive name of the column that holds the timestamp of the event to query.
8. Select **Save**.

List the Contents of a ClickHouse Dataset

You can quickly list all tables and views accessible through a ClickHouse Dataset, using the `.show objects` command. For example:

```
.show objects(clickhouse_dataset_ID)
```

Copy

Search a ClickHouse Dataset

After adding a ClickHouse Dataset Provider and Dataset, you're ready to start searching.

Cribl Search submits the query to ClickHouse. Results will start showing up after the ClickHouse SQL query completes. How long it takes depends on how much data there is in your ClickHouse database. Searching columns that contain large strings may result in a slower search.

Supported ClickHouse Data Types

Cribl Search supports the following ClickHouse data types:

- Strings: `String`, `FixedString`
- Integer types: `UInt8`, `UInt16`, `UInt32`, `UInt64`, `UInt128`, `UInt256`, `Int8`, `Int16`, `Int32`, `Int64`, `Int128`, `Int256`
- Floating-point numbers: `Float32`, `Float64`, `Decimal`
- Boolean: `Bool`
- Dates: `Date`, `Date32`, `DateTime`, `DateTime64`
- `UUID`
- Low cardinality types: `Enum`, `LowCardinality`
- `SimpleAggregateFunction`
- `Nullable`
- IP addresses: `IPv4`, `IPv6`

The following ClickHouse data types are **not supported**:

- `JSON`
- `Array`
- `Map`
- `AggregateFunction`
- `Tuple`
- Nested data structures (`Nested`)
- Geo types: `Point`, `Ring`, `Polygon`, `MultiPolygon`
- Special data types (including `Expression`, `Set`, `Nothing` and `Interval`)

Known ClickHouse Limitations

Searching ClickHouse comes with the following limitations:

- **Limited unsorted data:** When your ClickHouse Dataset targets a query, or a table without sorting keys, the maximum number of results is 100,000.

- **ClickHouse Cloud startup lag:** If you're using ClickHouse Cloud, and the service is not awake, the first search might be slow as ClickHouse wakes the service. This can take 20-30 seconds or more.
- **Structured data type parsing:** ClickHouse will error out if a parameter's value for structured data types like Bool, IPv4, IPv6, or UUID cannot be parsed. For example, using a value like `1.0.0` for an IPv4 column will fail with an error of the form: `Code: 675. DB::Exception: Cannot parse IPv4: value 1.0.0 cannot be parsed as IPv4 for query parameter.`
- **Wildcard/regex matching on non-string columns:** The `startswith` operator, and others that use `ilike` in ClickHouse SQL, will fail with an error for non-string columns such as `UUID` or `Int32`. For example, attempting to match `*2345*` on a numeric column will trigger an error of the form: `DB::Exception: Illegal type Int32 of argument of function ilike`. As a workaround, you can force a cast to `toString()` for regex and wildcard matches on non-string columns, to ensure that they work correctly.
- **Operators with incorrect formats:** Operators like `!=`, `==`, `<`, `>`, `<=`, `>=` will fail if the data format is incorrect. For example, comparing `1.2.3` with an IPv4 column will trigger an error if `1.2.3` is not a valid IP. Although casting to `toString()` is a potential workaround, it's better to validate the format first, to benefit from ClickHouse's type advantages.

4.8. Connect Cribl Search To CrowdStrike NG-SIEM

Configure Cribl Search to run in-place queries against an NG-SIEM repository or view.

Before You Begin

In CrowdStrike, do the following:

1. Create an API client, and note its client ID and client secret.
2. Grant the API client permission to run queries against the repository or view you plan to search.
3. Note the name of the repository or view to search, and your CrowdStrike API base URL. The base URL is specific to your CrowdStrike cloud region. For the URL that matches your region, see CrowdStrike's API documentation.

In your network, make sure Cribl Search can reach your CrowdStrike API base URL over HTTPS. If your environment restricts outbound traffic, allowlist the Cribl Search egress IP before you save the Dataset Provider.

Add a CrowdStrike NG-SIEM Dataset Provider

A Dataset Provider tells Cribl Search where to query and stores the access credentials for that connection.

To add a new Dataset Provider, select **Data**, then **Dataset Providers**, then **Add Provider**.

Next, configure the resulting **New Dataset Provider** modal as follows:

1. In **ID**, enter a unique identifier for the Dataset Provider. This is how you'll reference it when assigning Datasets to it. Start the ID with a letter. The rest of the ID can use letters, numbers, and underscores (for example, `my_ngsiem_provider`).
2. Optionally, add **Description** to quickly describe the Dataset Provider.
3. Set **Dataset Provider Type** to **CrowdStrike NG-SIEM**, listed under **Log Analytics**.
4. Enter the following:

Field	Description
Base URL	Your CrowdStrike API base URL, for example `https://api.us-2.crowdstrike.com`. Must use HTTPS.
Repository	Name of the LogScale repository or view to search.
Client ID	The client ID of your CrowdStrike API client.

Field	Description
Client secret	The client secret of your CrowdStrike API client. Cribl Search stores it encrypted at rest.

5. Select **Save** when finished.

When you select **Save**, Cribl Search tests the connection by running a small query against the repository.

If the test fails, Cribl Search doesn't save the Dataset Provider. Instead, a message explains the cause and highlights the field to correct. See Connection Errors for the full list of messages.

Connection Errors

A failed connection test returns one of the following messages:

Error message	Cause and resolution
`Base URL must use HTTPS.`	The **Base URL** doesn't start with `https://`. Correct the scheme.
`Unable to reach the provided Base URL. Verify the URL is correct (e.g. https://api.us-2.crowdstrike.com).`	The host didn't respond as a CrowdStrike API endpoint. Confirm the base URL for your CrowdStrike cloud region.
`Invalid client ID. Verify the OAuth2 API client ID is correct.`	CrowdStrike didn't recognize the client ID. Check the value for typos.
`Invalid client secret. Verify the OAuth2 API client secret is correct and has not expired.`	The client secret was wrong or has expired. Generate a new secret in CrowdStrike and re-enter it.
`Insufficient permissions. Verify the API client has the LogScale Query permission for this repository.`	The API client authenticated but can't run queries against this repository. Grant it query permission in CrowdStrike.
`Repository not found. Verify the repository name is correct and accessible to this API client.`	The **Repository** value doesn't match a repository or view this API client can access. Repository names are case-sensitive.
`CrowdStrike NG-SIEM is temporarily unavailable. Try again in a few minutes.`	CrowdStrike returned a server error. Retry after a brief wait.
`Unable to reach CrowdStrike API. Check your network connectivity and firewall settings.`	Cribl Search couldn't reach the base URL. Verify network access and egress allowlists.

Add a CrowdStrike NG-SIEM Dataset

Now you'll add a Dataset that tells Cribl Search what to query within the Dataset Provider's repository.

To add a new Dataset, select **Data**, then **Datasets**, then **Add Dataset**.

Next, configure the resulting **New Dataset** modal as follows:

1. Select the Dataset type: **Federated Dataset**.
2. In **ID**, enter a unique identifier for the Dataset. You'll use this to specify the Dataset in a query's scope. Start the ID with a letter. The rest of the ID can use letters, numbers, and underscores (for example, `ngsiem_firewall`).
3. Optionally, add **Description** to quickly describe the Dataset.
4. Set **Dataset Provider** to the ID of a CrowdStrike NG-SIEM Dataset Provider.
5. In **Query**, enter the CrowdStrike Query Language (CQL) query that defines what this Dataset represents, for example `#repo=base_sensor` or `@sourcetype=paloalto-ngfw`. This field is required.
6. In **Processing**, you can apply rules for breaking data into discrete events. For more information, see Datatypes.
7. Select **Save** when finished.

Use the **Query** field to scope the Dataset, not to filter individual investigations. Analysts narrow results further in their own Cribl Search queries.

Search CrowdStrike NG-SIEM

Now that you have a Dataset Provider and Dataset, you're ready to start searching:

```
dataset="ngsiem_firewall" | limit 100
```

Copy

Cribl Search combines your query with the Dataset's **Query**, sends it to CrowdStrike, and waits for CrowdStrike to finish before returning results.

If you cancel a search, Cribl Search asks CrowdStrike to cancel the matching query job. This is a best-effort request: Cribl Search doesn't wait for confirmation, so the job may keep running in CrowdStrike.

Cribl Search maps each returned event as follows:

Cribl Search field	Source
`_time`	LogScale's `@timestamp` field. This mapping is fixed and not configurable.
`_raw`	LogScale's `@rawstring` field.

Cribl Search field	Source
All other fields	Carried through under their original LogScale names, including `@`-prefixed names.

LogScale field names such as `@sourcetype` contain special characters, so quote them with `['` and `']` when you reference them:

```
dataset="ngsiem_firewall"
| summarize count() by ['@sourcetype']
```

Copy

Result Limits and Warnings

By default, LogScale returns only about 200 events for a query that doesn't specify how many events it wants. To raise that ceiling, Cribl Search appends a limit to the CQL it sends, based on your `max_results_per_search` setting. LogScale caps this limit at 200,000 events, so values above that are reduced.

Cribl Search appends this limit only when all of the following are true:

- Your Cribl Search query has no explicit `limit`.
- The Dataset's **Query** contains no CQL aggregate function, such as `count()` or `groupBy()`.
- The Dataset's **Query** doesn't already limit how many events it returns.

When your Cribl Search query does include a `limit`, Cribl Search sends that value to CrowdStrike instead. An aggregation in your Cribl Search query doesn't change this, because the aggregation runs in Cribl Search and needs enough events to aggregate over.

When results hit a cap, Cribl Search returns the results collected so far and shows this warning:

```
Results were capped at N. Narrow the time range or add filters to see all matching da
```

Copy

To get complete results, reduce the search time range, add filters to your query, or raise `max_results_per_search`.

If part of the result set fails to arrive, you get the results collected so far, along with this warning:

```
Some results may be missing — a page fetch failed after retries.
```

Copy

Run the search again to get the full result set.

4.9. Connect Cribl Search To Elasticsearch

Configure Cribl Search to query an Elasticsearch index.

Elasticsearch is a proprietary search engine for data-intensive applications.

In this guide, you'll set up a Dataset Provider and a Dataset to search an Elasticsearch index.



To search your Elasticsearch data much faster, ingest it into Cribl Search. See Ingest Elasticsearch Data into Cribl Search.

Add an Elasticsearch Dataset Provider

A Dataset Provider tells Cribl Search where to query and contains access credentials. Here, you will add an Elasticsearch Dataset Provider.

To add a new Dataset Provider:

1. From the sidebar, select **Data**, then **Dataset Providers**.
2. Select the **Add Provider** button on the right.

Next, set the following configurations in the **New Dataset Provider** modal:

1. In **ID**, enter a unique identifier for the Dataset Provider. This is how you'll reference it when assigning Datasets to it. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_provider_1`).
2. Optionally, add **Description** to quickly describe the Dataset Provider.
3. Set **Dataset Provider Type** to **Elasticsearch**.
4. Enter the following:
    - **Username**: Your Elasticsearch account name.
    - **Password**: Your password for Elasticsearch.
    - **Endpoint**: URL for the Elasticsearch endpoint, for example: `https://es.mycompany.com`.
5. Select **Save** when finished.

Add an Elasticsearch Dataset

Now you'll add a Dataset that tells Cribl Search what data to search from the Dataset Provider.

To add a new Dataset, select **Data**, then **Datasets**, then **Add Dataset**.

Next, set the following configuration in the resulting **New Dataset** modal:

1. Select the Dataset type: **Federated Dataset**.
2. In **ID**, enter a unique identifier for the Dataset. You'll use this to specify the Dataset in a query's scope, telling Cribl Search to search the Dataset. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_1`).
3. Optionally, add **Description** to quickly describe the Dataset.
4. Set **Dataset Provider** to the **ID** of an Elasticsearch Dataset Provider.
5. In **Index**, point to the identifier of the Elasticsearch index you want to search. If you have rolling indices (indices with dynamic naming), use the name of the index and the wildcard character `*`. For example, if your indices are named `my-index-00001`, `my-index-00002`, and so on, use `my-index*` in this field.
6. Make sure **Timestamp field** contains the name of the field that contains event timestamps. In most cases, this will be `@timestamp` for time series data in Elasticsearch.
7. Select **Save** when finished.

Search Elasticsearch

Now that you have a Dataset Provider and Dataset, you're ready to start searching.

Search results can start showing up within a second or two, but when the search completes depends on how much data there is in the account.

Elasticsearch Results Limit

The number of Elasticsearch results is capped by the `max_result_window` setting of your Elasticsearch index. By default, it's 10,000.

If you need to raise this limit, make sure you research and test for potential side effects.

4.10. Connect Cribl Search To A Generic HTTP API

Configure Cribl Search to query any HTTP API.

This guide shows you how to set up a Dataset Provider and Datasets to query static or dynamic HTTP API endpoints.



You can also quickly fetch data from an HTTP(S) URL by using the `externaldata` operator.

Add a Generic HTTP API Dataset Provider

A Dataset Provider tells Cribl Search where to query, and contains access credentials.

To add a new HTTP API Dataset Provider:

1. In Cribl Search, select **Data**, then **Dataset Providers**, then **Add Provider**.
2. In **ID**, enter the ID for the new Dataset Provider. This is how you'll reference the provider when assigning your HTTP API Datasets to it. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_provider_1`).
3. In **Description**, you can add a few words to make your new Dataset Provider easy to recognize.
4. Set **Dataset Provider Type** to **Generic HTTP API**. You'll see two new sections: **Endpoints** and **Authentication**.
5. In **Endpoints**, specify the endpoints that your Datasets will be able to reference. You can use parameters in the form `${parameterName}` in the **URL**, **POST Body**, **Headers**, and **Data field** so each search can supply runtime values. For each endpoint, set the following:
    - **Name**: This is how you'll recognize the endpoint when setting up your HTTP API Datasets.
    - **Data field**: For JSON responses, Cribl Search extracts events from a top-level JSON **array**, or from a nested property that holds the array. Enter a **dotted path** to navigate into the response and locate the array — for example, `results` for a single-level wrapper like `{"results": [...]}`, or `data.issues.nodes` for a deeper structure such as a GraphQL response. Leave blank when the response body is already a top-level array or when the response is not JSON. If the path you enter is not found in the response, the search returns an error.
    - **URL**: The URL for the endpoint. This is where Cribl Search will query for data.
    - **Method**: The HTTP method to use when making API requests.
    - **POST Body**: JavaScript expression for the request body, used with the **POST with Body** method. Cribl Search evaluates this field as a JS expression when the search runs. You can use:
        - Plain JSON with `${parameterName}` placeholders. For example, `{"queryString":"${queryString}"}`.

- A backtick-wrapped template literal for conditional logic or computed values. For example, `` `{"query": "issues(first: 50, after: ${cursor || null})"}` ``



Variable substitution runs when you execute a search. Placeholders in the form `${parameterName}` are replaced with the values you supply from the search bar. Backtick template literals also allow JavaScript expressions such as conditionals (`${cursor || null}`), function calls (`${uuid()}`), and arithmetic.

- **Headers**: Any HTTP headers needed to authenticate or authorize requests. For example, you might need to add an `Authorization` header with a bearer token.



When using **POST with Body**, set the **Content-Type** header manually in **Headers** if the endpoint requires it — for example, `Content-Type: application/json`. Cribl Search does not add or validate this header automatically.

6. In **Authentication**, you can select and configure an optional authentication method to use when making API requests. The default option is **None**.
7. When done, select **Save**.

Now, you can add a Dataset that tells Cribl Search what data to search from your new Dataset Provider.

Add a Generic HTTP API Dataset

A Dataset tells Cribl Search what data to search from the Dataset Provider.

To add a new HTTP API Dataset:

1. In Cribl Search, select **Data**, then **Datasets**, then **Add Dataset**.
2. Select the Dataset type: **Federated Dataset**.
3. In **ID**, enter the ID for the new Dataset. This is how you'll reference the Dataset to search it. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_1`).
4. In **Description**, you can add a few words to make your new Dataset easy to recognize.
5. Set **Dataset Provider** to the **ID** of an HTTP API Dataset Provider.
6. Select the endpoints that you want to search with this Dataset.
   To configure more endpoints, go to the Dataset Provider.
7. In **Processing**, you can apply rules for breaking data into discrete events. For more information, see Datatypes.
8. In **Snapshots**, you can set up API Snapshots.
9. When done, select **Save**.

Authentication Methods for Generic HTTP API

You can combine authentication with custom endpoint **Headers** and parameters in the **URL**, **POST Body**, and **Data field**. Cribl Search supports the following authentication methods for Generic HTTP API Dataset Providers:

- **None**: No authentication. This is the default option.
- Basic
- OAuth
- Login

Basic Authentication

To configure HTTP Basic authentication for a Generic HTTP API Dataset Provider in Cribl Search:

1. Start adding a Generic HTTP API Dataset Provider, or editing an existing one.
2. In the **Authentication** section, set **Authentication method** to **Basic**.
3. Enter the HTTP Basic **Username** and **Password** to use when making API requests.
4. Select **Save**.

Login Authentication

Login is the best authentication method to use for all services that return a JSON web token (JWT) or other authentication token whose content type is `application/json` or `content/plain`.

To configure Login authentication for a Generic HTTP API Dataset Provider in Cribl Search:

1. Start adding a Generic HTTP API Dataset Provider, or editing an existing one.
2. In the **Authentication** section, set **Authentication method** to **Login**.
3. Configure the following:
    - **Login URL**: URL for the Login API call, which is normally a POST call.
    - **Login username**: Login username.
    - **Login password**: Login password.
    - **POST body**: Template for POST body to send with the login request. The `${username}` and `${password}` variables specify the corresponding credentials' locations in the message.
    - **Token attribute**: Path to the token attribute in the login response body. Supports nested attributes. If the response from the auth request provides the JWT as `plain/text`, leave this field blank.
    - **Authorization header**: Authorization header key to pass to each endpoint's API request. Defaults to the literal name `Authorization`.

- **Authorize expression**: JavaScript expression used to compute an Authorization header to pass to each endpoint's API request. Uses `${token}` to reference the token obtained from a Login or OAuth authorization request.
- **Authentication headers**: Optionally, select **Add Header** for each custom auth header you want to define.

  Enter each header's **Name** and **Value**. In **Value**, you can define parameters, in the form of `${parameterName}`.

OAuth Authentication

To configure OAuth 2.0 authentication for a Generic HTTP API Dataset Provider in Cribl Search:

1. Start adding a Generic HTTP API Dataset Provider.
2. When you get to the **Authentication** section, set **Authentication method** to **OAuth**.
3. Configure the following:
   - **Login URL**: Endpoint for the OAuth API call, which is normally a POST call.
   - **Client secret parameter**: The name of the parameter to send with the **Client secret value**.
   - **Client secret value**: The OAuth client secret to authorize for an access token.
   - **Extra authentication parameters**: Optionally, select **Add parameter** for each additional OAuth request parameter you want to send in the body of POST requests. Automatically sets the `Content-Type` header to `application/x-www-form-urlencoded`.

     Enter each parameter's **Name** and **Value**. In **Value**, you can define parameters, in the form of `${parameterName}`.
   - **Token attribute**: Path to the token attribute in the login response body. Supports nested attributes.
   - **Authorization header**: Authorization header key to pass to each endpoint's API request. Defaults to the literal name `Authorization`.
   - **Authorize expression**: JavaScript expression used to compute an Authorization header to pass to each endpoint's API request. Uses `${token}` to reference the token obtained from a Login or OAuth authorization request.
   - **Authentication headers**: Optionally, select **Add Header** for each custom auth header you want to define.

     Enter each header's **Name** and **Value**. In **Value**, you can define parameters, in the form of `${parameterName}`.

Search a Generic HTTP API Dataset

Now that you have a Dataset Provider and Dataset, you're ready to start searching.

Parameters you define in the **POST Body** (or elsewhere on the endpoint) use the same `parameterName=parameterValue` form in the search as URL and header parameters. Those values are substituted into the POST body **when the query runs**, not when you save the Dataset Provider.

Search results can start showing up within a second or two, but when the search completes depends on how much data there is in the account.

Dynamically Query HTTP Endpoints

You can dynamically query different HTTP API endpoints, without having to change the Dataset Provider configuration for each query.


To be able to do that, configure your Generic HTTP API Dataset Provider with parameters in the form of `${parameterName}` in the **URL**, **Headers**, **Data field**, or **POST Body**. Then you can provide values for those parameters as key-value pairs (`parameterName=parameterValue`) in your query.



`earliest` and `latest` are reserved time-picker keywords and cannot be used as substitution parameters — they update the search time range instead of flowing into the request template. To pass time boundaries to your API, use custom parameter names such as `${startTime}` and `${endTime}` and supply the values from the search bar. The **URL** field supports only plain `${variableName}` substitution, not JavaScript expressions.

For example:

1. Start creating a Generic HTTP API Dataset Provider.
2. In the **Available endpoints** section, let's define parameters in the **URL**, **Headers**, and **POST Body** as shown below:
    - In **URL**, enter: `https://${domain}/${path}`.
    - In **Headers**, set **Value** to: `${headerVal1} ${headerVal2}`.
    - In **Headers**, enter **Content-Type** and set the **Value** to JSON.
    - For **Method**, select **POST with Body**.
    - In **POST Body** enter: `{"queryString":"${queryString}"}` so `${queryString}` is filled from the search bar when you run the query.
    - To use conditional logic (for example, cursor-based pagination), wrap the body in backticks: `` `{"query": "issues(first: 50, after: ${cursor || null})"}` `` This passes `null` on the first request (before a pagination cursor exists) and the cursor token on subsequent requests.



Generic HTTP API: Configuring dynamic query parameters

3. Use the new Dataset Provider to add a Generic HTTP API Dataset. Let's call the Dataset `my_http_api`.

4. Now, when searching the `my_http_api` Dataset, you'll be able to write queries like this one:

```
dataset="my_http_api" domain='api.example.com' path='v2/events' headerVal1='Bear
```

Copy

4.11. Connect Cribl Search To Microsoft Graph API

Configure Cribl Search to query a Microsoft Graph API endpoint.

With Microsoft Graph, you can access data across all Microsoft 365 services.

In this guide, you'll set up a Dataset Provider and a Dataset to search your Microsoft Entra ID or Microsoft 365 account(s) supporting the following endpoints:

- agreementAcceptances
- agreements
- applicationTemplates
- applications
- authenticationMethodConfigurations
- certificateBasedAuthConfiguration
- chats
- connections
- contacts
- contracts
- dataPolicyOperations
- devices
- directoryObjects
- directoryRoleTemplates
- directoryRoles
- domainDnsRecords
- domains
- drives
- filterOperators
- functions
- groupLifecyclePolicies
- groupSettingTemplates
- groupSettings
- groups
- identityProviders

- invitations
- localizations
- oauth2PermissionGrants
- organization
- permissionGrants
- places
- schemaExtensions
- scopedRoleMemberships
- servicePrincipals
- shares
- sites
- subscribedSkus
- subscriptions
- teamsTemplates
- teams
- users

Add a Microsoft Graph API Dataset Provider

A Dataset Provider tells Cribl Search where to query and contains access credentials. Here, you will add a Microsoft Graph API Dataset Provider.

To add a new Dataset Provider, select **Data**, then **Dataset Providers**, then **Add Provider**.

Set the following configurations in the **New Dataset Provider** modal:

1. **ID** is a unique identifier for the Dataset Provider. This is how you'll reference it when assigning Datasets to it. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_provider_1`).
2. **Description** is optional.
3. Set **Dataset Provider Type** to **Microsoft Graph API**.
4. Select **Add Configuration** to specify your Microsoft Graph account(s).
    - **Account Name** is the Microsoft Graph account name.
    - **Tenant ID** is the ID of the Microsoft Entra ID or Microsoft 365 to retrieve information from.
    - **Client ID** is the ID of the application that will connect to Microsoft Entra ID or Microsoft 365 account.

- **Client Secret** is the key that will be used as the secret in the connection to Microsoft Entra ID or Microsoft 365 account.

5. Select **Save** when finished.

Add a Microsoft Graph API Dataset

Now you'll add a Dataset that tells Cribl Search what data to search from the Dataset Provider.

To add a new Dataset, select **Data**, then **Datasets**, then **Add Dataset**.

Set the following configurations in the **New Dataset** modal:

1. Select the Dataset type: **Federated Dataset**.
2. **ID** is an identifier unique for both Cribl Search and Cribl Lake. You'll use this to specify the Dataset in a query's scope, telling Cribl Search to search the Dataset. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_1`).
3. **Description** is optional.
4. Set **Dataset Provider** to the **ID** of a Microsoft Graph API Dataset Provider.
5. Select **Add endpoint** to select the endpoints for your Dataset.
6. **Enabled endpoints**: Select an endpoint from the drop-down menu. For details on the endpoints, see the Microsoft Graph Rest API reference docs. Your options are:
    - `invitations`
    - `users`
    - `applicationTemplates`
    - `authenticationMethodConfigurations`
    - `identityProviders`
    - `applications`
    - `certificateBasedAuthConfiguration`
    - `contacts`
    - `contracts`
    - `devices`
    - `directoryObjects`
    - `directoryRoles`
    - `directoryRoleTemplates`
    - `domainDnsRecords`
    - `domains`

    - groups
    - groupSettings
    - groupSettingTemplates
    - localizations
    - oauth2PermissionGrants
    - organization
    - permissionGrants
    - scopedRoleMemberships
    - servicePrincipals
    - subscribedSkus
    - places
    - drives
    - shares
    - sites
    - schemaExtensions
    - groupLifecyclePolicies
    - filterOperators
    - functions
    - agreementAcceptances
    - agreements
    - dataPolicyOperations
    - subscriptions
    - connections
    - chats
    - teams
    - teamsTemplates
7. In **Processing**, you can apply rules for breaking data into discrete events. For more information, see Datatypes.
8. In **Snapshots**, you can set up API Snapshots.
9. Select **Save** when finished.

Search Microsoft Graph API

Now that you have a Dataset Provider and Dataset, you're ready to start searching.

Search results can start showing up within a second or two, but when the search completes depends on how much data there is in the account.

4.12. Connect Cribl Search To Okta API

Configure Cribl Search to query an Okta API endpoint.

Okta is a cloud-based identity solution that links your apps, logins, and devices.

In this guide, you'll set up a Dataset Provider and a Dataset to search the users, apps, devices, groups, and logs endpoints in your Okta account.

Add an Okta API Dataset Provider

A Dataset Provider tells Cribl Search where to query and contains access credentials. Here, you will add an Okta API Dataset Provider.

To add a new Dataset Provider, select **Data**, then **Dataset Providers**, then **Add Provider**.

Set the following configurations in the **New Dataset Provider** modal:

1. **ID** is a unique identifier for the Dataset Provider. This is how you'll reference it when assigning Datasets to it. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_provider_1`).
2. **Description** is optional.
3. Set **Dataset Provider Type** to **Okta API**.
4. Select **Add Configuration** to specify your Okta account. In the **Account Configuration** table, enter:
    - **Account Name**: Okta account name.
    - **Domain Endpoint**: URL for the subdomain of your organization. For example, `subdomain.okta.com`. For details, see Find your Okta domain.
    - **API Token**: API token for authorizing requests. For details, see Create an API token.
5. Select **Save** when finished.

Add an Okta API Dataset

Now you'll add a Dataset that tells Cribl Search what data to search from the Dataset Provider.

To add a new Dataset, select **Data**, then **Datasets**, then **Add Dataset**.

Set the following configurations in the **New Dataset** modal:

1. Select the Dataset type: **Federated Dataset**.
2. **ID** is an identifier unique for both Cribl Search and Cribl Lake. You'll use this to specify the Dataset in a query's scope, telling Cribl Search to search the Dataset. Start the ID with a letter; the rest of the ID can

use letters, numbers, and underscores (for example, `my_dataset_1`).

3. **Description** is optional.
4. Set **Dataset Provider** to the **ID** of an Okta Dataset Provider.
5. Select **Add endpoint** to select the endpoints for your Dataset.
6. **Enabled endpoints**: Select an endpoint from the drop-down menu. Your options are:
    - users
    - apps
    - devices
    - groups
    - logs
7. In **Processing**, you can apply rules for breaking data into discrete events. For more information, see Datatypes.
8. In **Snapshots**, you can set up API Snapshots.
9. Select **Save** when finished.

Search Okta API

Now that you have a Dataset Provider and Dataset, you're ready to start searching.

Search results can start showing up within a second or two, but when the search completes depends on how much data there is in the account.

4.13. Connect Cribl Search To OpenSearch

Configure Cribl Search to query an OpenSearch index.

OpenSearch is an open-source search engine for data-intensive applications.

In this guide, you'll set up a Dataset Provider and a Dataset to search an OpenSearch index.



To search your OpenSearch data much faster, ingest it into Cribl Search. See Ingest Elasticsearch Data into Cribl Search.

Add an OpenSearch Dataset Provider

A Dataset Provider tells Cribl Search where to query and contains access credentials. Here, you will add an OpenSearch Dataset Provider.

To add a new Dataset Provider:

1. From the sidebar, select **Data**, then **Dataset Providers**.
2. Select the **Add Provider** button on the right.

Next, set the following configurations in the **New Dataset Provider** modal:

1. In **ID**, enter a unique identifier for the Dataset Provider. This is how you'll reference it when assigning Datasets to it. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_provider_1`).
2. Optionally, add **Description** to quickly describe the Dataset Provider.
3. Set **Dataset Provider Type** to **OpenSearch**.
4. Enter the following:
    - **Username**: Your OpenSearch account name.
    - **Password**: Your password for OpenSearch.
    - **Endpoint**: URL for the OpenSearch endpoint, for example: `https://opensearch.thecriblgoat.farm`.
5. Select **Save** when finished.

Add an OpenSearch Dataset

Now you'll add a Dataset that tells Cribl Search what data to search from the Dataset Provider.

To add a new Dataset, select **Data**, then **Datasets**, then **Add Dataset**.

Next, set the following configuration in the resulting **New Dataset** modal:

1. Select the Dataset type: **Federated Dataset**.
2. In **ID**, enter a unique identifier for the Dataset. You'll use this to specify the Dataset in a query's scope, telling Cribl Search to search the Dataset. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_1`).
3. Optionally, add **Description** to quickly describe the Dataset.
4. Set **Dataset Provider** to the **ID** of an OpenSearch Dataset Provider.
5. In **Index**, point to the identifier of the OpenSearch index you want to search. If you have rolling indices (indices with dynamic naming), use the name of the index and the wildcard character `*`. For example, if your indices are named `my-index-00001`, `my-index-00002`, and so on, use `my-index*` in this field.
6. Make sure **Timestamp field** contains the name of the field that contains event timestamps. In most cases, this will be `@timestamp` for time series data in OpenSearch.
7. Select **Save** when finished.

Search OpenSearch

Now that you have a Dataset Provider and Dataset, you're ready to start searching.

Search results can start showing up within a second or two, but when the search completes depends on how much data there is in the account.

OpenSearch Results Limit

The number of OpenSearch results is capped by the `max_result_window` setting of your OpenSearch index. By default, it's 10,000.

If you need to raise this limit, make sure you research and test for potential side effects.

4.14. Connect Cribl Search To Prometheus

Configure Cribl Search to query your Prometheus instance.

Prometheus is a an open-source toolkit that collects and stores metrics as time-series data.

In this guide, you'll set up a Dataset Provider and a Dataset to search data at rest in your Prometheus instance.



To search your Prometheus metrics much faster, ingest them into Cribl Search. See Ingest Prometheus Metrics into Cribl Search.

Add a Prometheus Dataset Provider

A Dataset Provider tells Cribl Search where to query and contains access credentials. Here, you will add a Prometheus Dataset Provider.

To add a new Dataset Provider, select **Data**, then **Dataset Providers**, then **Add Provider**.

Configure the resulting **New Dataset Provider** modal as follows:

1. In **ID**, enter a unique identifier for your new Dataset Provider. You'll reference this ID when adding Datasets. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_provider_1`).
2. In **Description**, you can add a few words to make your new Dataset Provider easy to recognize.
3. Set **Dataset Provider Type** to **Prometheus**.
4. In **Endpoint**, enter the full URL of your Prometheus API endpoint, for example: `https://prometheus.goats.biz`. If you're using Grafana, the URL may look like this: `https://prometheus-foo-42-prod-us-central-0.grafana.net/api/prom`.
5. In **Concurrency limit**, set the maximum number of concurrent API requests. The default is `3`. Higher values may improve performance but put more load on the target service (with the risk of being rate limited).
6. In **Authentication type**, select how Cribl Search should authenticate to your Prometheus instance.
   - **Basic**: Select this if your Prometheus instance uses basic authentication. You'll need to enter a username and password.
   - **Token**: Select this if you're using token-based authentication. You'll need to enter a bearer token that Cribl Search will include with the authorization header.
7. Select **Save** when finished.

Add a Prometheus Dataset

After creating a Prometheus Dataset Provider, you can add a Prometheus Dataset. Datasets tell Cribl Search what data to search from the Dataset Provider.

To add a new Dataset, select **Data**, then **Datasets**, then **Add Dataset**.

Set the Dataset type to **Federated Dataset**, and configure the following settings.

Basic Configuration

1. In **ID**, enter an identifier unique for both Cribl Search and Cribl Lake. You'll reference this ID from the query box, when searching your new Dataset. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_1`).
2. In **Description**, you can add a few words to make your new Dataset easy to recognize.
3. Set **Dataset Provider** to the ID of a Prometheus Dataset Provider.

Prometheus Options

This exposes the following Prometheus-specific options:

1. **Number of data points**: How many data points you want to get each time you search this Dataset. Set this to a value between `1` and `11000` (a limit imposed by Prometheus). The default is `250`.
2. **Step mode**: Defines how to use the set **Number of data points** when calculating the interval between data points. Select one of the following:
    - **Exact number of data points**: Adjust the interval between data points to match the exact **Number of data points** set above.
    - **Snap to nearest unit**: Target the **Number of data points** set above, but snap the calculated interval up or down to the nearest Prometheus time unit. For example, `1043ms` will snap to `1s`, and `43 days` will snap to `6w`.
3. **Metric name pattern**: Optionally, enter a regular expression to filter metric names. Cribl Search will include only those metrics whose names match this pattern. This filtering lets you control access to your metrics, as described below.
4. Select **Save** when finished.

Control Access to Your Prometheus Metrics

If you want a group of users to have access only to a subset of your Prometheus metrics, you can add separate Prometheus Datasets with different **Metric name pattern** configurations.

For example, you can add a single Dataset Provider, but two separate Datasets:

1. Add a Prometheus Dataset Provider. This means both of your Prometheus Datasets can use the same authentication settings.
2. Add a Prometheus Dataset (say, `prometheus_dataset_1`). In the **Metric name pattern** field, add a regular expression that filters the names of your metrics, for example: `^abc`. When searching this Dataset, Cribl Search will include only those metrics whose names start with `abc`.
3. Add another Prometheus Dataset (say, `prometheus_dataset_2`), with a different **Metric name pattern**, for example: `^xyz`.
4. Share `prometheus_dataset_1` with one group of users (or a Team), and `prometheus_dataset_2` with another. Use the **Read Only** permission.
5. Now, one group of users can search only the `abc` metrics, and another only the `xyz` metrics.

List the Contents of a Prometheus Dataset

You can quickly list all metrics accessible through a Prometheus Dataset, by using the `.show objects` command. For example:

```
.show objects(prometheus_dataset_ID)
```

Copy

This returns a list of metrics that your Prometheus Dataset consists of. Each metric comes with the following fields:

Field	Description
`_time`	The `.show objects` command's execution time. It's the same for every returned metric.
`success`	Shows whether the command was successful.
`dataset`	The ID of the examined Dataset.
`datasetType`	The type of the examined Dataset.
`name`	The name of the metric.

Additionally, if your Prometheus instance supports the `/api/v1/targets/metadata` API, you'll also get the following metadata fields:

Field	Description
`type`	The type of the metric. For example, `counter`.

Field	Description
`unit`	What units the metric value conveys (usually empty).
`help`	A description of the metric.

Now, you can use the fields above to filter for specific metrics. For example, to list only gauge metrics:

```
.show objects(prometheus_dataset_ID)
 | where type == "gauge"
```

Copy

Search a Prometheus Dataset

After creating a Prometheus Dataset Provider and Dataset, you're ready to start searching. See the examples just below.

Search for any metrics whose names, labels, or label values start with `node_`:

```
dataset="prometheus_dataset_ID" node_*
```

Copy

Search the metric named `node_cpu_seconds_total` for values higher than `42`:

```
dataset="prometheus_dataset_ID" node_cpu_seconds_total > 42
```

Copy

Filter by multiple fields, and project only the `_time` and `cpu` fields:

```
dataset="prometheus_dataset_ID" node_cpu_seconds_total > 42 mode=idle cpu=7
 | project _time, cpu
```

Copy

Alternatively, you can search by using the Prometheus `__name__` field:

```
dataset="prometheus_dataset_ID" __name__=node_*
```

Copy

You can also search by Prometheus labels alone. This allows you to search any metrics that have the given label values, for example:

```
dataset="prometheus_dataset_ID" mode=idle cpu=7
```

Copy

Prometheus Results

Search results can start showing up within a second or two, but when the search completes depends on how much data there is in your Prometheus instance.

Each data point returned may include the following fields:

Field	Description
Built-in fields	Cribl Search's meta fields, such as `_raw` or `_time`. They're not part of the metrics, but can be referenced in queries.
Metric + value	The name of the queried metric, along with its value.
`__name__`	Prometheus's field that contains the name of the queried metric.
`step`	The `step` value used for the Prometheus query request, which translates to the interval between data points returned.
Others	Any other labels that apply to this data point, which show up as event fields.

Additionally, if your Prometheus instance supports the `/api/v1/targets/metadata` API, you'll also get a `metadata` field, which contains the following:

Field	Description
`type`	The type of the metric. For example, `counter`.
`unit`	What units the metric value conveys (usually empty).
`help`	A description of the metric.

Prometheus: Number of Data Points Returned

When searching a Prometheus Dataset, you can decide **how many data points** you want to spread across the time range of your search.


For example, a search can produce 500 data points for a 1-hour time range, giving you 1 data point every 7.2 seconds.

To adjust this to your needs, you can:

- Set the default number of data points returned. Cribl Search will adjust the interval between data points to match this number.
- Optionally, set a specific interval between data points for a given search. Cribl Search will then adjust the number of data points returned to match the specified interval.

Prometheus: Set the Default Number of Data Points Returned

You can set the default number of data points when editing or creating your Prometheus Dataset. Enter the desired value into the **Number of data points** field.



Configuring the number of data points returned

With **Step mode**, you can tell Cribl Search how to use the set **Number of data points** when calculating the interval between data points.

To always get the same, exact number of data points, set **Step mode** to **Exact number of data points**. Then, if you set the **Number of data points** to `250`, a search will always give you 250 data points, spread across the

time range of your search. For example, searching a 60-day time range will give you exactly 250 data points, with the interval of 5.76 hours between them.

To round the interval to the nearest time unit, set **Step mode** to **Snap to nearest unit**. Then, if you set the **Number of data points** to `250`, and search a 60-day time range, Cribl Search will snap the 5.76-hour interval to 6 hours, and adjust the number of data points accordingly.

Prometheus: Set the Interval Between Data Points Returned (`step`)

Every Prometheus search can override the calculated interval between data points, by using an explicit `step` value. For example:

```
dataset="prometheus_dataset_ID" step="30s"
```

Copy

This will adjust the number of data points returned to match the specified interval.

The value of `step` must match the following pattern:

```
^\\d+(ms|s|m|h|d|w|y)$

// for example:
// 10s
```

4.15. Connect Cribl Search To Snowflake

Configure Cribl Search to query your Snowflake warehouse.

Snowflake is a cloud platform that offers data warehousing as a service.

In this guide, you'll set up a Dataset Provider and a Dataset to search a Snowflake warehouse.

Add a Snowflake Dataset Provider

A Dataset Provider tells Cribl Search where to query and contains access credentials. Here, you will add a Snowflake Dataset Provider.

To add a new Dataset Provider, select **Data**, then **Dataset Providers**, then **Add Provider**.

Next, configure the resulting **New Dataset Provider** modal as follows:

1. In **ID**, enter a unique identifier for the Dataset Provider. This is how you'll reference it when assigning Datasets to it. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_provider_1`).
2. Optionally, add **Description** to quickly describe the Dataset Provider.
3. Set **Dataset Provider Type** to **Snowflake**.
4. Enter the following:
    - **Account identifier**: Case-sensitive Snowflake account identifier, in the format `<org_name>-<account_name>`. For example: `myorg-account123`.
    - **Username**: Case-sensitive Snowflake username.
    - **Private key**: The contents of your Snowflake private key (PEM) file. To upload a file, select the upload button at this field's upper right.
    - **Private key passphrase**: An optional passphrase used to protect your Snowflake private key.
    - **Executors limit**: Maximum number of concurrent Cribl Search executors dispatched for processing Snowflake data partitions.
    - **Endpoint**: Optional URL to Snowflake REST API. If empty, defaults to `https://<org_name>-<account_name>.snowflakecomputing.com`.
5. Select **Save** when finished.

Add a Snowflake Dataset

Now you'll add a Dataset that tells Cribl Search what data to search from the Dataset Provider.

To add a new Dataset, select **Data**, then **Datasets**, then **Add Dataset**.

Next, configure the resulting **New Dataset** modal as follows:

1. Select the Dataset type: **Federated Dataset**.
2. In **ID**, enter a unique identifier for the Dataset. You'll use this to specify the Dataset in a query's scope, telling Cribl Search to search the Dataset. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_1`).
3. Optionally, add **Description** to quickly describe the Dataset.
4. Set **Dataset Provider** to the ID of a Snowflake Dataset Provider.
5. Enter the following:
    - **Warehouse**: Case-sensitive name of the Snowflake warehouse. If not set, defaults to the `DEFAULT_WAREHOUSE` property for the Snowflake user.
    - **Database name**: Case-sensitive name of the Snowflake database. If not set, defaults to the database value in the `DEFAULT_NAMESPACE` for the Snowflake user.
    - **Schema name**: Case-sensitive name of the Snowflake schema that contains the tables you plan to query. If not set, defaults to the schema value in the `DEFAULT_NAMESPACE` for the Snowflake user.
    - **Table or query**: The name of the table or view, or a query. May be a simple name (`logs`) or an SQL query (`select * from logs`).
    - **Timestamp field**: Optional, case-sensitive name of the column that holds the timestamp of the event to query.
    - **Role**: Optional Snowflake role to use when running the SQL query. We recommend using a read-only role.
6. Select **Save** when finished.

List the Contents of a Snowflake Dataset

You can quickly list all tables and views accessible through a Snowflake Dataset, by using the `.show objects` command. For example:

```
.show objects(snowflake_dataset_ID)
```

Copy

Search a Snowflake Dataset

Now that you have a Snowflake Dataset Provider and Dataset, you're ready to start searching.

Cribl Search submits the query to Snowflake. Results will start showing up after the Snowflake SQL query completes. How long it takes depends on how much data there is in your Snowflake warehouse. Searching

columns that contain large strings may result in a slower search.

Snowflake: Supported SQL Data Types

When querying Snowflake, Cribl Search supports the following SQL data types:

- `NUMBER`, `DECIMAL`, `DEC`, `NUMERIC`, `INT`, `INTEGER`, `BIGINT`, `SMALLINT`, `TINYINT`, `BYTEINT`, `FLOAT`, `FLOAT4`, `FLOAT8`, `DOUBLE`, `DOUBLE PRECISION`, `REAL`
- `VARCHAR`, `CHAR`, `CHARACTER`, `STRING`, `TEXT`
- `BOOLEAN`
- `DATE`, `DATETIME`, `TIME`, `TIMESTAMP`, `TIMESTAMP_LTZ`, `TIMESTAMP_NTZ`, `TIMESTAMP_TZ`
- `VARIANT`, `OBJECT`

4.16. Connect Cribl Search To Tailscale API

Configure Cribl Search to query a Tailscale API endpoint.

Tailscale VPN makes your devices and applications accessible from anywhere in the world, securely and easily.

In this guide, you'll set up a Dataset Provider and a Dataset to search the acls and devices endpoints in your Tailscale account.

Add a Tailscale API Dataset Provider

A Dataset Provider tells Cribl Search where to query and contains access credentials. Here, you will add a Tailscale API Dataset Provider.

To add a new Dataset Provider, select **Data**, then **Dataset Providers**, then **Add Provider**.

Set the following configurations in the **New Dataset Provider** modal:

1. **ID** is a unique identifier for the Dataset Provider. This is how you'll reference it when assigning Datasets to it. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_provider_1`).
2. **Description** is optional.
3. Set **Dataset Provider Type** to **Tailscale API**.
4. Select **Add Configuration** to specify your Tailscale account. In the **Account Configuration** table, enter:
    - **Account Name**: Tailscale account name.
    - **Client ID**: Tailscale Client ID.
    - **Client Secret**: Tailscale Client Secret.
5. Select **Save** when finished.

For details on obtaining your Tailscale credentials, see Authentication.

Add a Tailscale API Dataset

Now you'll add a Dataset that tells Cribl Search what data to search from the Dataset Provider.

To add a new Dataset, select **Data**, then **Datasets**, then **Add Dataset**.

Set the following configurations in the **New Dataset** modal:

1. Select the Dataset type: **Federated Dataset**.
2. **ID** is an identifier unique for both Cribl Search and Cribl Lake. You'll use this to specify the Dataset in a query's scope, telling Cribl Search to search the Dataset. Start the ID with a letter; the rest of the ID can

use letters, numbers, and underscores (for example, `my_dataset_1`).

3. **Description** is optional.
4. Set **Dataset Provider** to the **ID** of a Tailscale Dataset Provider.
5. Select **Add endpoint** to select the endpoints for your Dataset.
6. **Enabled endpoints**: Select an endpoint from the drop-down menu. Your options are:
    - acls
    - devices
7. In **Processing**, you can apply rules for breaking data into discrete events. For more information, see Datatypes.
8. In **Snapshots**, you can set up API Snapshots.
9. Select **Save** when finished.

Search Tailscale API

Now that you have a Dataset Provider and Dataset, you're ready to start searching.

Search results can start showing up within a second or two, but when the search completes depends on how much data there is in the account.

4.17. Connect Cribl Search To Zoom API

Configure Cribl Search to query a Zoom API endpoint.

Zoom enables users to communicate via video, audio, phone, and chat.

In this guide, you'll set up a Dataset Provider and a Dataset to search the user, group, and meeting endpoints in your Zoom account.

Add a Zoom API Dataset Provider

A Dataset Provider tells Cribl Search where to query and contains access credentials. Here, you will add a Zoom API Dataset Provider.

To add a new Dataset Provider, select **Data**, then **Dataset Providers**, then **Add Provider**.

Set the following configurations in the **New Dataset Provider** modal:

1. **ID** is a unique identifier for the Dataset Provider. This is how you'll reference it when assigning Datasets to it. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_provider_1`).
2. **Description** is optional.
3. Set **Dataset Provider Type** to **Zoom API**.
4. Select **Add Configuration** to specify your Zoom account. In the **Account Configuration** table, enter:
    - **Account Name**: Zoom account name.
    - **Account ID**: Unique ID associated with your Zoom account.
    - **Client ID**: Zoom Client ID.
    - **Client Secret**: Zoom Client Secret.
5. Select **Save** when finished.

For details on obtaining your Zoom credentials, see Server-to-Server OAUTH.

Add a Zoom API Dataset

Now you'll add a Dataset that tells Cribl Search what data to search from the Dataset Provider.

To add a new Dataset, select **Data**, then **Datasets**, then **Add Dataset**.

Set the following configurations in the **New Dataset** modal:

1. Select the Dataset type: **Federated Dataset**.

2. **ID** is an identifier unique for both Cribl Search and Cribl Lake. You'll use this to specify the Dataset in a query's scope, telling Cribl Search to search the Dataset. Start the ID with a letter; the rest of the ID can use letters, numbers, and underscores (for example, `my_dataset_1`).
3. **Description** is optional.
4. Set **Dataset Provider** to the **ID** of a Zoom Dataset Provider.
5. Select **Add endpoint** to select the endpoints for your Dataset.
6. **Enabled endpoints**: Select an endpoint from the drop-down menu. Your options are:
    - users
    - groups
    - meetings
    - pastMeetings
7. In **Processing**, you can apply rules for breaking data into discrete events. For more information, see Datatypes.
8. In **Snapshots**, you can set up API Snapshots.
9. Select **Save** when finished.

Search Zoom API

Now that you have a Dataset Provider and Dataset, you're ready to start searching.

Search results can start showing up within a second or two, but when the search completes depends on how much data there is in the account.

4.18. Configure Data Connection Options In Cribl Search

Process data into discrete events, control your object storage costs, and learn about how Cribl Search processes the most common data formats.

Datatypes

Make searching easier by processing data into discrete events and defining fields. See: Datatypes.

Storage Classes

Control your costs by selectively enabling which object storage classes (access tiers) you want each Dataset to search. See: Storage Classes.

Supported Data Formats

Learn about how Cribl Search processes the most common data formats. See: Supported Data Formats.

4.18.1. Datatypes In Cribl Search

Define how Cribl Search interprets raw data, so you can extract meaningful fields and search faster.

What's a Datatype?

A set of rules that defines how Cribl Search processes incoming data into structured events.

If you're ingesting data into a lakehouse engine, Auto-Datatyping can parse your data automatically.

Datatypes allow Cribl Search to:

- **Recognize** the type of the incoming data (for example, "AWS S3 server access logs"), and detect how it's formatted (for example, `JSON Array`).
- **Break events**: Split raw input into discrete events.
- **Parse fields**: Turn event text into fields you can query.
- **Extract time**: Pull event timestamps to add the `_time` field to each event.
- **Enrich data**: Compute additional fields for schema mapping or other enrichment.

Datatypes add the relevant `datatype` field to each event (for example, `datatype: "aws_s3_server_access_logs"`).

Example: AWS VPC Flow Log

Here's how the `aws_vpcflow` v1 Datatype processes an AWS VPC Flow Log event:

In Out


```
{
  "_raw": "2 123456789010 eni-0858304751c757b2e 31.200.171.164 22.109.125.129 5855
  "_time": 1262332801,
  "datatype": "aws_vpcflow",
  "srcaddr": "31.200.171.164",
  "dstaddr": "22.109.125.129",
  "srcport": "58551",
  "dstport": "456",
  "action": "ACCEPT"
}
```

Copy

v1 and v2 Datatypes

Cribl Search features two Datatype models: older **v1 Datatypes** are gradually being replaced with the more efficient **v2 Datatypes**.

Learn more about each type:

- v1 Datatypes in Cribl Search
- v2 Datatypes in Cribl Search

The two Datatype models compare as follows:

Aspect	v1 Datatypes	v2 Datatypes
Work with	Federated providers only	All Cribl Search Sources (high-speed lakehouse engines) Federated Dataset Type v2: Amazon S3, Azure Blob Storage, Cribl Lake. Applicable formats depend on the provider. See federated search v2.

Data formats supported	`CSV`
	`Extended Log File Format`
	`Common Log Format`
	`Key=Value Pairs`
	`JSON Object`
	`Delimited values`
	`Regular Expression`
	`Grok`
		`JSON Newline Delimited`
		`Delimited Text`
		`JSON Array`
		`Key-Value Pair`
		`Parquet`
		`Raw Text`
		`Splunk Journal`
		`XML`

Stock Datatypes available	List of Stock v1 Datatypes	List of Stock v2 Datatypes
Auto-Datatyping	No	Yes
Customizable	Yes	Yes

Stock and Custom Datatypes

Cribl Search ships with a wide range of stock Datatypes:

- List of Stock v1 Datatypes
- List of Stock v2 Datatypes

You can also:

- Create your own Datatypes.
- Export or import Datatypes through Packs.

4.18.1.1. V1 Datatypes In Cribl Search

Use v1 Datatypes where v2 Datatypes are not supported yet.

What's a v1 Datatype?

A set of rules that tells Cribl Search how to interpret data when running **federated searches**. (For general info on Datatypes, see Datatypes in Cribl Search.)

Starting with Cribl Search 4.17.0, v1 Datatypes are being gradually replaced with the more efficient v2 Datatypes. To find to what's already supported, see v1 and v2 Datatypes.

Stock v1 Datatypes

Cribl Search ships with a number of stock v1 Datatypes, marked in the UI as part of the **Cribl** library.

For the full list, see List of Stock v1 Datatypes.

Add a Custom v1 Datatype



You can also edit or clone an existing v1 Datatype so you don't have start from scratch.

To create a custom v1 Datatype:

1. On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datatypes**.
2. On the **Datatypes** page, select **Add Datatype**.
3. Set the **Type** to **v1**.
4. Enter the **ID**, **Description**, and **Tags**, and set the **Min raw length**.
5. Select **Add Rule**. See Add a v1 Datatype Rule.
6. After setting up your rules, select **Save**.

Now, you can apply your new v1 Datatype to your federated Datasets. For example, for configuring an Amazon S3 Dataset, see Connect Cribl Search to Amazon S3.

Add a v1 Datatype Rule

Each v1 Datatype rule includes the following settings:

- Filter Condition
- Event Breaker Settings

- Timestamp Settings
- Parser Settings
- Add Fields to Events

Filter Condition

A JavaScript expression applied to the beginning of the incoming file or object. If the expression returns `true`, the rule kicks in. If not, the next rule is evaluated.

Example expression:

```
__collectStats.url.includes('/security/alert_v2')
```

Copy

Event Breaker Settings

Event Breakers tell Cribl Search how to split incoming data into individual events. You can choose from several Event Breaker types.

Max Event Bytes sets the largest event that an Event Breaker produces. It applies to every Event Breaker type. You can set it from `1` up to about 128 MB (`134217728` bytes). The default is `51200` (50 KB).

If the accumulated event size reaches this limit before the break pattern matches, Cribl Search splits the data into events of up to this size. Each full-size fragment has `__isBroken` set to `true`. If a leftover fragment is smaller than the limit, Cribl Search emits it with `__isBroken` set to `false`.


Timestamp Settings

Cribl Search timestamps each event with the `_time` field.

First, it finds a **timestamp anchor** in the incoming event. Starting from that anchor, it then either:

- Scans up to a configured depth and **autodetects** a timestamp, or
- Uses a **manual `strptime` format**, or
- Falls back to the **current time**.

Place the anchor as close as possible to the timestamp to improve performance and accuracy, especially when events contain more than one time value.



Anchors preceding timestamps

Parser Settings

The Parser attached to a rule extracts fields from events so you can reference them in searches. Each parsed field is a key-value pair, with the field name as the key.

Parsers work like the Parser function in Cribl Stream pipelines.

You can either configure a new Parser or choose one from the library. To learn more about each parser type, see Parsers.

Setting	Description
Type	Select the format of your data: `CSV`, `Extended Log File Format`, `Common Log Format`, `Key=Value Pairs`, `JSON Object`, `Delimited values`, `Regular Expression`, or `Grok`.
Library	Select a Parser defined in the library. The library is located at **Knowledge** > **Parsers**.
Source field	Define the field the Parser will use to extract from. Defaults to `_raw`.
Destination field	Provide a name for the field to which the extracted data will be assigned.
List of fields	Fields to be extracted in the desired order. Leave blank to generate the fields automatically.
Fields to keep	Fields to keep. Supports wildcards `*`. Takes precedence over **Fields to remove**.
Fields to remove	Fields to remove. Supports wildcards `*`. You cannot remove fields that match **Fields to keep**.
Fields filter expression	Expression evaluated against `{index, name, value}` context. Return `truthy` to keep a field, or `falsy` to remove it.

Add Fields to Events

A v1 Datatype rule can add extra fields as key-value pairs.

In each field's **Value Expression**, you can use JavaScript to compute the value.

For v1 Datatypes, configure each rule to add a `datatype` field with a clear value. That way, you can always see which Datatype produced a given event.

v1 Datatype Event Breakers

When configuring the **Event Breaker Settings** of a v1 Datatype rule, you can choose from the following Event Breakers:

- Regex
- JSON New Line Delimited
- JSON Array
- File Header
- Timestamp
- CSV
- AWS CloudTrail
- AWS VPC Flow Log
- Azure VNet Flow Log

Regex Event Breaker

Use the **Regex** Event Breaker when you need full control over where events split. You define a pattern that marks the start of each event.

How it works: Cribl Search breaks at the start of each match. The matched content is consumed. Use a positive lookahead such as `(?=pattern)` if you want to keep the content. Do not use capturing groups, because they split the data further. Breaking also occurs when **Max Event Bytes** is reached.

Example

- **Event Breaker:** - `[\n\r]+`
- **Parser** - `AWS VPC Flow Logs` from the Library.
- **Add Field** - `"datatype": "aws_vpcflow"`

```
--input--
2 123456789012 eni-0b2fc5457066bc156 10.0.0.164 54.239.152.25 41050 443 6 8 1297 1679
2 123456789013 eni-0b2fc5457066bc157 10.0.0.164 54.239.152.25 41050 443 6 8 1297 1679

--- output event 1 ---
{
 "_raw": "2 123456789012 eni-0b2fc5457066bc156 10.0.0.164 54.239.152.25 41050 443 6 8
 "_time": 1679339697,
 "datatype": "aws_vpcflow",
 "version": "2",
 "account_id": "123456789012",
 "interface_id": "eni-0b2fc5457066bc156",
 "srcaddr": "10.0.0.164",
 "dstaddr": "54.239.152.25",
 "srcport": "41050",
 "dstport": "443",
 "protocol": "6",
 "packets": "8",
 "bytes": "1297",
 "start": "1679339697",
 "end": "1679340000",
 "action": "ACCEPT",
 "log_status": "OK",
 "dataset": "s3_vpcflowlogs",
}

--- output event 2 ---
{
 "_raw": "2 123456789013 eni-0b2fc5457066bc157 10.0.0.164 54.239.152.25 41050 443 6 8
 "_time": 1679339698,
 "datatype": "aws_vpcflow",
 "version": "2",
 "account_id": "123456789013",
 "interface_id": "eni-0b2fc5457066bc156",
 "srcaddr": "10.0.0.164",
 "dstaddr": "54.239.152.25",
 "srcport": "41050",
 "dstport": "443",
 "protocol": "6",
 "packets": "8",
 "bytes": "1297",
 "start": "1679339698",
```

```
 "end": "1679340000",
 "action": "REJECT",
 "log_status": "OK",
 "dataset": "s3_vpcflowlogs",
}
```

Copy

JSON New Line Delimited Event Breaker

Use the **JSON New Line Delimited** Event Breaker when each line is a complete JSON object. You get fast parsing and automatic field extraction without extra config.

Example

Sample Event - Newline Delimited JSON Breaker

```
--- input ---
{"time":"2020-05-25T18:00:54.201Z","cid":"w1","channel":"clustercomm","level":"info",
{"time":"2020-05-25T18:00:54.246Z","cid":"w0","channel":"clustercomm","level":"info",


--- output event 1 ---
{
  "_raw": "{\"time\":\"2020-05-25T18:00:54.201Z\",\"cid\":\"w1\",\"channel\":\"cluste
  "time": "2020-05-25T18:00:54.201Z",
  "cid": "w1",
  "channel": "clustercomm",
  "level": "info",
  "message": "metric sender",
  "total": 720,
  "dropped": 0,
  "_time": 1590429654.201,
}

--- output event 2 ---
{
  "_raw": "{\"time\":\"2020-05-25T18:00:54.246Z\",\"cid\":\"w0\",\"channel\":\"cluste
  "time": "2020-05-25T18:00:54.246Z",
  "cid": "w0",
  "channel": "clustercomm",
  "level": "info",
  "message": "metric sender",
  "total": 720,
  "dropped": 0,
  "_time": 1590429654.246,
}
```

Copy

JSON Array Event Breaker

Use the **JSON Array** Event Breaker when you have a JSON document with an array of records (for example, CloudTrail). You extract each record as a separate event.

Settings: Configure **Array Field** (for example, `Records`), **Timestamp Field** (for example, `eventTime`), and **JSON Extract Fields** (**Yes** to auto-extract fields). If **JSON Extract Fields** is **No**, set **Timestamp Format** to **Autotimestamp** or **Current Time**.

Example

Sample Event - JSON Document (Array)

```
--- input ---
{"Records":[{"eventVersion":"1.05","eventTime":"2020-04-08T01:35:55Z","eventSource":'
{"eventVersion":"1.05","eventTime":"2020-04-08T01:35:56Z","eventSource":"ec2.amazonav

--- output event 1 ---
{
  "_raw": "{\"eventVersion\":\"1.05\",\"eventTime\":\"2020-04-08T01:35:55Z\",\"eventS
  "_time": 1586309755,
  "cribl_breaker": "j-array"
}

--- output event 2 ---
{
  "_raw": "{\"eventVersion\":\"1.05\",\"eventTime\":\"2020-04-08T01:35:56Z\",\"eventS
  "_time": 1586309756,
  "cribl_breaker": "j-array"
}
```

Copy

File Header Event Breaker

Use the **File Header** Event Breaker when your file has a header that lists field names (for example, IIS or Bro logs). You get both event splitting and field extraction from the header.

Settings: Configure **Header Line** (for example, `^#`), **Field Delimiter** (for example, `\s+`), **Field Regex** (one capturing group for the field list), **Null Values**, and **Clean Fields** (to replace non-alphanumeric characters with underscores).

Example

Sample Event - File Header

```
--- input ---
#fields ts      uid     id.orig_h       id.orig_p       id.resp_h       id.resp_p
#event-breakers  time    string  addr    port    addr    port    enum
1331904608.080000       -     192.168.204.59  137     192.168.204.255 137     udp
1331904609.190000       -     192.168.202.83  48516   192.168.207.4   53      udp


--- output event 1 ---
{
  "_raw": "1331904608.080000       -     192.168.204.59  137     192.168.204.255 137
  "ts": "1331904608.080000",
  "id_orig_h": "192.168.204.59",
  "id_orig_p": "137",
  "id_resp_h": "192.168.204.255",
  "id_resp_p": "137",
  "proto": "udp",
  "_time": 1331904608.08
}

--- output event 2 ---
{
  "_raw": "1331904609.190000       -     192.168.202.83  48516   192.168.207.4   53
  "ts": "1331904609.190000",
  "id_orig_h": "192.168.202.83",
  "id_orig_p": "48516",
  "id_resp_h": "192.168.207.4",
  "id_resp_p": "53",
  "proto": "udp",
  "_time": 1331904609.19
}
```

Copy

Timestamp Event Breaker

Use the **Timestamp** Event Breaker when each line starts with a timestamp but the format varies. You get automatic detection without defining a fixed pattern.

Example

Sample Event - Timestamp Based Breaker

```
--- input ---
{"level":"debug","ts":"2021-02-02T10:38:46.365Z","caller":"sdk/sync.go:42","msg":"Har
{"level":"debug","ts":"2021-02-02T10:38:56.365Z","caller":"sdk/sync.go:42","msg":"Har


--- output event 1 ---
{
  "_raw": "{\"level\":\"debug\",\"ts\":\"2021-02-02T10:38:46.365Z\",\"caller\":\"sdk/
  "_time": 1612262326.365
}

--- output event 2 ---
{
  "_raw": "{\"level\":\"debug\",\"ts\":\"2021-02-02T10:38:56.365Z\",\"caller\":\"sdk/
  "_time": 1612262336.365
}
```

Copy

CSV Event Breaker

Use the **CSV** Event Breaker when your data has a header row and comma-separated values. You get automatic field extraction and correct handling of quoted values.

Settings: Configure **Delimiter** (default `,`), **Quote Char** (default `"`), and **Escape Char** (default `"`).

Example

Sample Event - CSV Breaker

```
--- input ---
time,host,source,model,serial,bytes_in,bytes_out,cpu
1611768713,"myHost1","anet","cisco","ASN4204269",11430,43322,0.78
1611768714,"myHost2","anet","cisco","ASN420423",345062,143433,0.28


--- output event 1 ---
{
  "_raw": "\"1611768713\",\"myHost1\",\"anet\",\"cisco\",\"ASN4204269\",\"11430\",\"4
  "time": "1611768713",
  "host": "myHost1",
  "source": "anet",
  "model": "cisco",
  "serial": "ASN4204269",
  "bytes_in": "11430",
  "bytes_out": "43322",
  "cpu": "0.78",
  "_time": 1611768713
}

--- output event 2 ---
{
  "_raw": "\"1611768714\",\"myHost2\",\"anet\",\"cisco\",\"ASN420423\",\"345062\",\"1
  "time": "1611768714",
  "host": "myHost2",
  "source": "anet",
  "model": "cisco",
  "serial": "ASN420423",
  "bytes_in": "345062",
  "bytes_out": "143433",
  "cpu": "0.28",
  "_time": 1611768714
}
```

Copy

With **Type: CSV** selected, an Event Breaker will properly add quotes around all values, regardless of their initial state.

AWS CloudTrail Event Breaker

Use **AWS CloudTrail** for CloudTrail logs. You get faster parsing than with the generic JSON Array breaker.

Sample Event - AWS CloudTrail Breaker

```
--- input ---
{"Records":[{"eventVersion":"1.0","userIdentity":{"type":"IAMUser","principalId":"EX_

--- output event 1 ---
{
  "_raw": "{\"eventVersion\":\"1.0\",\"userIdentity\":{\"type\":\"IAMUser\",\"princip
  "_time": 1711112256.322
}

--- output event 2 ---
{
  "_raw": "{\"eventVersion\":\"1.0\",\"userIdentity\":{\"type\":\"IAMUser\",\"princip
  "_time": 1711112355.478
}

--- output event 3 ---
{
  "_raw": "{\"eventVersion\":\"1.0\",\"userIdentity\":{\"type\":\"IAMUser\",\"princip
  "_time": 1711112355.478
}
```

Copy

AWS VPC Flow Log Event Breaker

Use **AWS VPC Flow Log** for AWS VPC Flow Log data. You get faster parsing than with Regex, and a Parser.

Format: Space-separated columns, header line at the top, one event per line. Use – for null values.

Sample Event - AWS VPC Flow Log Breaker

```
--- input ---
version account_id interface_id srcaddr dstaddr srcport dstport protocol packets byte
2 123456789014 eni-07e5d76940fbaa5c6 231.234.233.57 83.70.34.149 19856 15726 17 3048
2 123456789010 eni-0858304751c757b2e 31.200.171.164 22.109.125.129 58551 456 17 10824
2 123456789013 eni-07e5d76940fbaa5c6 78.128.152.196 67.42.235.136 25164 29139 17 5380

--- output event 1 ---
{
  "_raw": "2 123456789014 eni-07e5d76940fbaa5c6 231.234.233.57 83.70.34.149 19856 157
  "version": "2",
  "account_id": "123456789014",
  "interface_id": "eni-07e5d76940fbaa5c6",
  "srcaddr": "231.234.233.57",
  "dstaddr": "83.70.34.149",
  "srcport": "19856",
  "dstport": "15726",
  "protocol": "17",
  "packets": "3048",
  "bytes": "380",
  "start": "1262332800",
  "end": "1262332900",
  "action": "ACCEPT",
  "log_status": "NODATA",
  "_time": 1611768713
}

--- output event 2 ---
{
  "_raw": "2 123456789010 eni-0858304751c757b2e 31.200.171.164 22.109.125.129 58551 4
  "version": "2",
  "account_id": "123456789010",
  "interface_id": "eni-0858304751c757b2e",
  "srcaddr": "31.200.171.164",
  "dstaddr": "22.109.125.129",
  "srcport": "58551",
  "dstport": "456",
  "protocol": "17",
  "packets": "10824",
  "bytes": "352",
  "start": "1262332801",
  "end": "1262333301",
  "action": "ACCEPT",
```

```
  "log_status": "OK",
  "_time": 1611768714
}

--- output event 3 ---
{
  "_raw": "2 123456789013 eni-07e5d76940fbaa5c6 78.128.152.196 67.42.235.136 25164 29
  "version": "2",
  "account_id": "123456789013",
  "interface_id": "eni-07e5d76940fbaa5c6",
  "srcaddr": "78.128.152.196",
  "dstaddr": "67.42.235.136",
  "srcport": "25164",
  "dstport": "29139",
  "protocol": "17",
  "packets": "5380",
  "bytes": "160",
  "start": "1262332802",
  "end": "1262332902",
  "action": "REJECT",
  "log_status": "OK",
  "_time": 1611768715
}
```


Copy

With **Type: AWS VPC Flow Log** selected, an Event Breaker will properly add quotes around all values, regardless of their initial state.

Azure VNet Flow Log Event Breaker

Use **Azure VNet Flow Log** when you have Azure NSG flow logs or VNet flow logs. You get faster parsing than with the generic JSON Array breaker.

Format: JSON with a `records` array. Each record has nested `flowRecords.flows.flowGroups.flowTuples`. Each tuple is a comma-separated string (timestamp, IPs, ports, protocol, direction, and related fields). The breaker flattens parent fields (time, rule, resource IDs) into each event.

Sample Event - Azure VNet Flow Log Breaker

```
--- input ---
{"records":[{"time":"2022-09-14T09:00:52.5625085Z","flowLogVersion":4,"flowLogGUID":'

--- output event 1 ---
{
  "_raw": "1663146003599,10.0.0.6,192.0.2.180,23956,443,6,O,B,NX,15,2340,12,8760",
  "_time": 1663146003.599,
  "flowLogVersion": 4,
  "flowLogGUID": "66aa66aa-bb77-cc88-dd99-00ee00ee00ee",
  "category": "FlowLogFlowEvent",
  "flowLogResourceID": "/subscriptions/.../flowLogs/nsg-flowlog",
  "targetResourceID": "/subscriptions/.../virtualNetworks/prod-vnet",
  "operationName": "FlowLogFlowEvent",
  "aclID": "00aa00aa-bb11-cc22-dd33-44ee44ee44ee",
  "rule": "DefaultRule_AllowInternetOutBound",
  "srcIp": "10.0.0.6",
  "dstIp": "192.0.2.180",
  "srcPort": "23956",
  "dstPort": "443",
  "protocol": "6",
  "flowDirection": "O",
  "flowState": "B",
  "flowEncryption": "NX",
  "packetsSrcToDst": "15",
  "bytesSrcToDst": "2340",
  "packetsDstToSrc": "12",
  "bytesDstToSrc": "8760"
}
```

Copy

List of Stock v1 Datatypes

You can use these v1 Datatypes out of the box:

- Apache Datatypes
- AWS Datatypes
- Azure Datatypes
- Cisco Datatypes
- Cribl Search _raw Data

- Cribl Search
- CSV Datatypes
- Microsoft Graph API Datatypes
- Microsoft O365 Datatypes
- Microsoft Windows Datatypes
- OCSF Datatypes
- Palo Alto Datatypes
- Syslog Datatypes
- Zeek Datatypes

Apache Datatypes

Parses Apache web server logs.

This v1 Datatype consists of the following rules, evaluated top-down:

	Rule name	Value of the `datatype` field added to the event
1	Apache Common	apache_access
2	Apache Combined	apache_access_combined

See some examples:

Common Combined

```
--- input ---
127.0.0.1 - frank [10/Oct/2000:13:55:36 -0700] "GET /apache_pb.gif HTTP/1.0" 200 2

--- output ---
{
  "_raw": "127.0.0.1 - frank [10/Oct/2000:13:55:36 -0700] \"GET /apache_pb.gif HTT
  "_time": 971211336,
  "datatype": "apache_access",
  "clientip": "127.0.0.1",
  "ident": "-",
  "user": "frank",
  "timestamp": "10/Oct/2000:13:55:36 -0700",
  "request": "GET /apache_pb.gif HTTP/1.0",
  "status": "200",
  "bytes": "2326"
}
```

Copy

AWS Datatypes

Parses common AWS log formats, such as VPC Flow, CloudFront, WAF.

This v1 Datatype consists of the following rules, evaluated top-down:

	Rule name	Value of the `datatype` field added to the event
1	AWS CloudTrail	aws_cloudtrail
2	AWS VPC Flow	aws_vpcflow
3	AWS ALB	aws_alb_accesslogs
4	AWS ELB	aws_elb_accesslogs
5	AWS Cloudfront Web	aws_cloudfront_accesslogs
6	AWS WAF	aws_waf

See some examples:

CloudTrail VPC Flow ALB ELB CloudFront WAF

```
---input---
{
  "eventTime": "2014-03-06T21:22:54Z",
  "eventSource": "ec2.amazonaws.com",
  "eventName": "StartInstances",
  "userIdentity": {
    "accountId": "123456789012",
    "userName": "Hatter"
  }
}

---output---
{
  "_raw": "{\"eventTime\":\"2014-03-06T21:22:54Z\",\"eventSource\":\"ec2.amazonaws
  "_time": 1394140974,
  "datatype": "aws_cloudtrail",
  "eventTime": "2014-03-06T21:22:54Z",
  "eventSource": "ec2.amazonaws.com",
  "eventName": "StartInstances",
  "userIdentity": {
    "accountId": "123456789012",
    "userName": "Hatter"
  }
}
```

Copy

Azure Datatypes

Parses Azure-specific logs, such as Network Security Group flow logs.

This v1 Datatype consists of a single rule:

Rule name	Value of the `datatype` field added to the event
`Network Security Group`	`azure_networksecuritygroup`

Here's an example of how this v1 Datatype processes an NSG flow log event:

Input Output


```
{
  "records": [
    {
      "time": "2023-05-15T12:00:00.0000000Z",
      "systemId": "00000000-0000-0000-0000-000000000000",
      "category": "NetworkSecurityGroupFlowEvent",
      "resourceId": "/SUBSCRIPTIONS/12345678-1234-1234-1234-123456789012/RESOURCEG
      "operationName": "NetworkSecurityGroupFlowEvents",
      "properties": {
        "Version": 2,
        "flows": [
          {
            "rule": "UserRule_Allow-HTTPS-Inbound",
            "flows": [
              {
                "mac": "000D3A146A48",
                "flowTuples": ["10.0.0.4,10.0.0.5,4096,443,T,O,A,1623840360,162384
              }
            ]
          }
        ]
      }
    }
  ]
}
```


Copy

Cisco Datatypes

Parses Cisco device logs.

This v1 Datatype consists of the following rules, evaluated top-down:

	Rule name	Value of the `datatype` field added to the event
1	`Cisco ASA`	`cisco_asa`

	Rule name	Value of the `datatype` field added to the event
2	`Cisco FWSM`	`cisco_fwsm`
3	`Cisco Estreamer`	`cisco_estreamer_data`

See some examples:

Cisco ASA | Cisco FWSM | Cisco Estreamer

```
--- input ---
%ASA-1-104001: Switching to ACTIVE - Primary interface is up

--- output ---
{
  "_raw": "%ASA-1-104001: Switching to ACTIVE - Primary interface is up",
  "_time": 1685613600,
  "datatype": "cisco_asa",
  "device": "ASA-1",
  "event": "104001",
  "status": "Switching to ACTIVE",
  "interface": "Primary"
}
```

Copy

Cribl Search

Parses newline-delimited JSON (NDJSON) data.

This v1 Datatype consists of a single rule:

Rule name	Value of the `datatype` field added to the event
`ndjson`	`cribl_json`

Here's an example:

Input | Output

{"timestamp":"2024-06-11T10:23:45.432Z","level":"warn","message":"Failed login att

Copy

Cribl Search _raw Data

Parses NDJSON-formatted logs where the actual event payload is in the `_raw` field.

This v1 Datatype consists of a single rule:

Rule name	Value of the `datatype` field added to the event
`ndjson`	`cribl_json_raw`

Here's an example:

Input Output

{"_raw":"{\"timestamp\":\"2024-06-11T10:24:13.123Z\",\"level\":\"info\",\"action\"

Copy

CSV Datatypes

Parses CSV-formatted logs.

This v1 Datatype consists of a single rule:

Rule name	Value of the `datatype` field added to the event
`csv`	`csv`

Input Output

```
"id","timestamp","level","message"
1,"2023-08-01T12:00:00Z","INFO","Service started"
2,"2023-08-01T12:05:00Z","WARN","Connection slow"
3,"2023-08-01T12:10:00Z","ERROR","Service failed"
```

Copy

Microsoft Graph API Datatypes

Parses Microsoft Graph API logs.

This v1 Datatype consists of the following rules, evaluated top-down:

	Rule name	Value of the `datatype` field added to the event
1	Security Alerts	microsoft_graph_securityalert
2	Security Alerts - Legacy	microsoft_graph_securityalert_legacy
3	Service Health	microsoft_graph_servicehealth
4	Service Issues	microsoft_graph_serviceissues
5	Messages	microsoft_graph_messages
6	Users	microsoft_graph_users
7	Devices	microsoft_graph_devices
8	Groups	microsoft_graph_groups
9	Applications	microsoft_graph_applications

See some examples:

Security Alerts Users Applications

```
--- input ---
[
  {
    "id": "12345-67890",
    "title": "Suspicious Activity",
    "severity": "High",
    "status": "NewAlert",
    "lastModifiedDateTime": "2023-05-20T15:30:00Z",
    "description": "User reported suspicious login."
  }
]

--- output ---
{
  "_raw": "{\"id\":\"12345-67890\",\"title\":\"Suspicious Activity\",\"severity\":
  "_time": 1684596600,
  "datatype": "microsoft_graph_securityalert",
  "id": "12345-67890",
  "title": "Suspicious Activity",
  "severity": "High",
  "status": "NewAlert",
  "lastModifiedDateTime": "2023-05-20T15:30:00Z",
  "description": "User reported suspicious login."
}
```

Copy

Microsoft O365 Datatypes

Parses Microsoft 365 (formerly Office 365) logs.

This v1 Datatype consists of the following rules, evaluated top-down:

	Rule name	Value of the `datatype` field added to the event
1	`status`	`microsoft_office365_status`
2	`messages`	`microsoft_office365_messages`
3	`mgmt-activity`	`microsoft_office365_mgmt-activity`

	Rule name	Value of the `datatype` field added to the event
4	msg-trace	microsoft_office365_msg-trace

See some examples:

Status | Messages | Management Activity | Message Trace

```
---input---
{
  "value": [
    {
      "Id": "ServiceStatus",
      "Workload": "Exchange",
      "StatusDisplayName": "Service degradation",
      "Status": "ServiceDegradation",
      "StatusTime": "2023-05-15T12:00:00Z",
      "WorkloadDisplayName": "Exchange Online",
      "IncidentIds": ["EX123456"]
    }
  ]
}


---output---
{
  "_raw": "{\"Id\":\"ServiceStatus\",\"Workload\":\"Exchange\",\"StatusDisplayName
  "_time": 1684152000,
  "datatype": "microsoft_office365_status",
  "Id": "ServiceStatus",
  "Workload": "Exchange",
  "StatusDisplayName": "Service degradation",
  "Status": "ServiceDegradation",
  "StatusTime": "2023-05-15T12:00:00Z",
  "WorkloadDisplayName": "Exchange Online",
  "IncidentIds": [
    "EX123456"
  ]
}
```

Copy

Microsoft Windows Datatypes

Parses Windows Event Log formats (classic and XML).

This v1 Datatype consists of the following rules, evaluated top-down:

	Rule name	Value of the `datatype` field added to the event
1	`Windows Event Log Classic`	`windows_event_classic`
2	`Windows XML Events`	`windows_event_xml`

See some examples:

Windows Event Log Classic Windows XML Event

```
---input---
06/15/2023 07:20:51 PM
LogName: Security
Source: Microsoft-Windows-Security-Auditing
EventID: 4624
Level: Information
User: N/A
Computer: WIN-7PC
Description:
An account was successfully logged on.

---output---
{
  "_raw": "06/15/2023 07:20:51 PM LogName: Security Source: Microsoft-Windows-Secu
  "_time": 1718511651,
  "datatype": "windows_event_classic",
  "log_name": "Security",
  "source": "Microsoft-Windows-Security-Auditing",
  "event_id": "4624",
  "level": "Information",
  "user": "N/A",
  "computer": "WIN-7PC",
  "description": "An account was successfully logged on."
}
```

Copy

OCSF Datatypes

Parses logs in the Open Cybersecurity Schema Framework (OCSF) format.

This v1 Datatype consists of a single rule:

Rule name	Value of the `datatype` field added to the event
`ndjson`	Value of the source event `category_name` field. For example, for `"category_name": "Network Activity"`, Cribl Search sets the `datatype` field to `"Network Activity"`

Here's an example:

Input Output


```
{
  "category_uid": 1,
  "category_name": "Network Activity",
```

4.18.1.2. V2 Datatypes In Cribl Search

Simplify parsing and speed up searches with v2 Datatypes.

What's a v2 Datatype?

A set of rules that tells Cribl Search how to interpret data, allowing for automatic parsing and faster searches than the older v1 Datasets.

For a comparison of v1 and v2 Datatypes, see v1 and v2 Datatypes.

For general info on Datatypes, see Datatypes in Cribl Search.

v2 Datatypes and Lakehouse Engines

v2 Datatypes help ingest your data into high-speed lakehouse engines. In this scenario, you can assign v2 Datatypes in different ways:

- Automatically, through Auto-Datatyping.
- Manually, by adding custom Datatype rules that match the stock v2 Datatypes.
- Manually, by editing or creating custom v2 Datatypes.

v2 Datatypes and Federated Datasets

v2 Datatypes are gradually replacing v1 Datatypes for federated searches, to offer more automated parsing and better search performance.

Cribl Lake federated Datasets with v2 Dataset Type assign a Datatype to each data format the Lake Dataset stores (for example, `generic_ndjson` for JSON or `cribl_lake_parquet` for Parquet). A **DDSS** Lake Dataset uses a single row with a Splunk Journal Datatype, such as `splunk_journal`. See Dataset Type and Datatypes for Lake Datasets.

To see what's currently supported, see federated search v2.

Edit a Stock v2 Datatype

To edit a stock v2 Datatype, clone it first.

1. On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datatypes**.
2. On the **Datatypes** page, select the v2 Datatype you want to edit.
3. Select **Clone Datatype**.

Now, you're editing the clone.

4. Make your changes. To find out how, see individual sections in Add a Custom v2 Datatype.

Confirm with **Save**. Now, you can apply your custom v2 Datatype to your Datasets.

Add a Custom v2 Datatype

You can add custom v2 Datatypes to parse data that's not covered by the auto-applied stock v2 Datatypes.

On the Cribl.Cloud top bar, select **Products** > **Search** > **Data** > **Datatypes** > **Add Datatype**.

1. Describe

In the **New Datatype** modal:

- Set **Type** of your Datatype to **v2**.
- In **ID**, enter a unique identifier for your v2 Datatype (for example, `web_access_v2`). Avoid spaces and special characters.
- In **Description**, give an overview of your v2 Datatype, so you and others know what it's for.
- In **Tags**, add keywords that might help you find your v2 Datatype later (for example, `web logs`).

2. Set the Data Format

In **Data format**, specify how your incoming data is formatted:

- **JSON Newline Delimited**
- **Delimited Text**
- **JSON Array**
- **Key-Value Pair**
- **Parquet**
- **Raw Text**
- **Splunk Journal**
- **XML**

See the tabs below for examples and details.

JSON Newline Delimited | Delimited Text | JSON Array | Key-Value Pair

Choose this data format if your data arrives as newline-delimited JSON, for example:

```
{"time":"2020-05-25T18:00:54.201Z","cid":"w1","channel":"clustercomm","level":"inf
{"time":"2020-05-25T18:01:01.120Z","cid":"w1","channel":"clustercomm","level":"inf
```

Copy

Parquet | Raw Text | Splunk Journal | XML

Choose this data format if your incoming data is formatted as Parquet.

3. Set the Maximum Event Size

In **Max Bytes**, set the maximum size of a single event. You can set it from `1` up to about 128 MB (`134217728` bytes). The default is `65536` (64 KB).

If the accumulated event size reaches this limit before Cribl Search finds a break boundary, Cribl Search splits the data into events of up to this size. Each full-size fragment has `__isBroken` set to `true`. If a leftover fragment is smaller than the limit, Cribl Search emits it with `__isBroken` set to `false`.

4. Set Additional Extractions

Use **Additional Extractions** to run secondary parsers for extracting more fields or peeling layered payloads.

This feature is not supported for federated Datasets.

5. Set Timestamp Extraction

Configure how to find timestamps in your data.

Set the **Extraction type**:

- **Auto**: Tries to detect the timestamp automatically. Set **Scan depth** to how many characters to scan after the anchor. Larger values are slower but may find timestamps farther into the event.
- **Manual**: Provide the exact strptime format (for example, `%Y-%m-%dT%H:%M:%S.%LZ`). Use when you know the exact format of your timestamps, and it's consistent.

Then, configure these settings:

Setting	Description
Time field	Field from which to extract the timestamp (for example, `_raw`). Leave blank to scan the entire event.
Default timezone	Timezone to apply to extracted timestamps. Defaults to `UTC`. By default, Cribl Search applies this only when the extracted timestamp has no zone info. To force it to apply to every timestamp, enable **Override timezone**.
Override timezone	When enabled, the **Default timezone** overrides any zone info present in the extracted timestamp. Defaults to disabled, in which case the default timezone applies only when no zone info is present.
Earliest timestamp allowed	Oldest acceptable timestamp relative to now (for example, `-1y`). Timestamps older than this are clamped to this value. Use `0` to allow back to the Unix epoch (Jan 1, 1970).
Future timestamp allowed	Newest acceptable timestamp relative to now (for example, `+2d`). Timestamps further in the future are clamped to this value.
Timestamp anchor	Regex matching the text that immediately precedes the timestamp. Use `$` to skip extraction.

6. Normalize Field Names with Schema Maps

Normalize vendor-specific field names into one or more canonical schemas (ECS, OCSF, your own), while keeping the original fields for backward compatibility and troubleshooting.



This feature is not supported for federated Datasets.

Under **Schema Maps**, select **Add Row**, and configure:

Setting	Description
Field Name	Name for your new, normalized field.
Kusto Expression	KQL filter that evaluates to `true` for the fields whose names you want to normalize.

Example: ECS | Example: OCSF

This example normalizes source IP addresses (`src_ip` and `client_ip`) to the ECS field name (`source.ip`).

Field Name	Kusto Expression
source.ip	src_ip:* or client_ip:*

```
---in---
src_ip: "10.0.0.1"
client_ip: "10.0.0.2"

---out---
src_ip: "10.0.0.1"
client_ip: "10.0.0.2"
source.ip: "10.0.0.1"
source.ip: "10.0.0.2"
```

Copy

7. Add Computed Fields

Enrich incoming events with new computed fields.

This feature is not supported for federated Datasets.

Under **Add fields to events**, select **Add Row**, and configure:

Setting	Description
Field Name	Name for your new field.
Kusto Expression	KQL filter that computes the field's value.

Example: Risk Score Example: Port Groups

Let's say your source sends a text `severity` field and you want a single numeric `risk_score` on every event, for alerting.

Field Name	Kusto Expression
risk_score	case(severity == "critical", 100, severity == "high", 80, severity == "medium", 50, 20)

```
---in---
severity: "critical"

---out---
severity: "critical"
risk_score: 100
```

Copy

Next Steps

Confirm with **Save**. Now, you're ready to apply your custom v2 Datatype to your Datasets.

List of Stock v2 Datatypes

Cribl Search comes with a wide range of stock v2 Datatypes that automatically recognize and parse common log types. This list highlights some key supported types, but many others are available and applied automatically.

Log type	Datatype ID (`datatype` field added)	Source data format
Apache Combined logs	`apache_httpd_accesslog_combined`	`Raw Text`
Apache Common logs	`apache_httpd_accesslog_common`	`Raw Text`
AWS Application Load Balancer Log Fields	`aws_alb_accesslog`	`Delimited Text`
AWS CloudFront access logs	`aws_cloudfront_accesslog`	`Delimited Text`
AWS Config configuration item change notifications	`aws_config`	`JSON Newline Delimi`
AWS EC2 system logs (syslog with ISO 8601 prefix)	`aws_ec2`	`Raw Text`
AWS EKS Kubernetes control plane audit logs in JSON format	`aws_eks_audit`	`JSON Newline Delimi`
AWS Classic Elastic Load Balancing Log Fields	`aws_elb_accesslog`	`Delimited Text`

Log type	Datatype ID (`datatype` field added)	Source data format
AWS GuardDuty finding events in JSON format	`aws_guardduty`	`JSON Newline Delimi`
AWS Network Firewall logs (Suricata EVE JSON with AWS metadata)	`aws_network_firewall`	`JSON Newline Delimi`
AWS Network Load Balancer TLS access logs	`aws_nlb_accesslog`	`Delimited Text`
AWS RDS MySQL audit logs (MariaDB audit plugin format)	`aws_rds_audit_mysql`	`Delimited Text`
AWS RDS PostgreSQL pgAudit logs	`aws_rds_audit_postgresql`	`Raw Text`
AWS Route 53 public DNS query logs (space-delimited)	`aws_route53_public`	`Delimited Text`
AWS Route 53 Resolver query logs in JSON format	`aws_route53_resolver`	`JSON Newline Delimi`
AWS S3 server access logs	`aws_s3_access`	`Raw Text`
AWS Security Hub findings in ASFF format	`aws_security_hub`	`JSON Newline Delimi`
AWS VPC Flow Logs version 2	`aws_vpc_v2`	`Delimited Text`
AWS VPC Flow Logs version 5	`aws_vpc_v5`	`Delimited Text`
AWS WAF logs in JSON format	`aws_waf_log_json`	`JSON Newline Delimi`
Microsoft Azure Graph Security API alert events in JSON format	`azure_graph_alerts`	`JSON Newline Delimi`
Microsoft Azure Graph API device records in JSON format	`azure_graph_devices`	`JSON Newline Delimi`
Microsoft Azure Graph API directory audit logs in JSON format	`azure_graph_directory_audits`	`JSON Newline Delimi`
Microsoft Azure Graph API sign-in logs in JSON format	`azure_graph_signins`	`JSON Newline Delimi`
Microsoft Azure Graph API user authentication	`azure_graph_user_registration`	`JSON Newline Delimi`

Log type	Datatype ID (`datatype` field added)	Source data format
registration details in JSON format		
Microsoft Azure Graph API user profile records in JSON format	`azure_graph_users`	`JSON Newline Delimi`
Azure Network Security Group (NSG) Flow Logs	`azure_nsg_flowlog_json`	`JSON Newline Delimi`
Check Point firewall logs in native key:“value”; semicolon-delimited format	`checkpoint_firewall`	`Raw Text`
Check Point firewall logs wrapped in RFC5424 syslog format	`checkpoint_firewall_rfc_5424`	`Raw Text`
Cisco ASA syslog messages (ASA-* message IDs) with embedded event timestamp and various message formats	`cisco_asa_syslog`	`Raw Text`
Cisco eStreamer event logs (eNcore KVP format)	`cisco_estreamer`	`Key-Value Pair`
Cisco Firewall Services Module (FWSM) logs	`cisco_fwsm_syslog`	`Raw Text`
Cisco Firewall Services Module (FWSM) syslog events (connection build/teardown, translations, denies)	`cisco_fwsm_v2`	`Raw Text`
Cisco IPS 4200 IDS/IPS alert events in comma-delimited key=value format	`cisco_ips_alert`	`Key-Value Pair`
Cisco NetFlow v9 records exported with a syslog-like prefix and comma-separated key=“value” pairs	`cisco_netflow_v9`	`Raw Text`
Cloudflare Zero Trust Access authentication events from Logpush in JSON format	`cloudflare_access_request`	`JSON Newline Delimi`
Cloudflare account audit logs from Logpush in JSON format	`cloudflare_audit`	`JSON Newline Delimi`

Log type	Datatype ID (`datatype` field added)	Source data format
Cloudflare firewall and WAF security events from Logpush in JSON format	`cloudflare_firewall_event`	`JSON Newline Delimi`
Cloudflare Zero Trust Gateway HTTP and network session logs from Logpush in JSON format	`cloudflare_gateway`	`JSON Newline Delimi`
Cloudflare Zero Trust Gateway DNS query logs from Logpush in JSON format	`cloudflare_gateway_dns`	`JSON Newline Delimi`
Cloudflare CDN HTTP request logs from Logpush in JSON format	`cloudflare_http_request`	`JSON Newline Delimi`
Cloudflare Workers trace events from Logpush in JSON format	`cloudflare_workers_trace`	`JSON Newline Delimi`
Cloudflare Zero Trust network session telemetry from Logpush in JSON format	`cloudflare_zero_trust_network_session`	`JSON Newline Delimi`
AWS CloudTrail digest files for log validation	`cloudtrail_digest`	`JSON Newline Delimi`
AWS CloudTrail event logs in JSON format	`cloudtrail_event`	`JSON Newline Delimi`
Confluent Cloud Kafka audit log events following CloudEvents v1.0 spec in JSON format	`confluent_audit`	`JSON Newline Delimi`
Cribl internal process logs in JSON format	`cribl_internal_logs`	`JSON Newline Delimi`
Cribl Stream metrics data in JSON format	`cribl_metrics`	`JSON Newline Delimi`
Cribl Lake Dataset objects stored as Apache Parquet	`cribl_lake_parquet`	`Parquet`
Exabeam Common Information Model (CIM) normalized events in JSON format	`exabeam_cim`	`JSON Newline Delimi`

Log type	Datatype ID (`datatype` field added)	Source data format
CrowdStrike Falcon Event Streams API events in JSON format	`falcon_events`	`JSON Newline Delimi`
CrowdStrike Falcon Data Replicator (FDR) sensor telemetry events in JSON format	`falcon_fdr`	`JSON Newline Delimi`
CrowdStrike Falcon Data Replicator (FDR) host/asset info records in JSON format	`falcon_fdr_aidmaster`	`JSON Newline Delimi`
CrowdStrike Falcon Data Replicator (FDR) external API events in JSON format	`falcon_fdr_external_api`	`JSON Newline Delimi`
CrowdStrike Falcon REST API alert events in JSON format	`falcon_rest_alerts`	`JSON Newline Delimi`
CrowdStrike Falcon Hosts API device inventory events in JSON format	`falcon_rest_devices`	`JSON Newline Delimi`
CrowdStrike Falcon Spotlight API vulnerability assessment events in JSON format	`falcon_rest_vulnerabilities`	`JSON Newline Delimi`
Fortinet FortiGate firewall logs in key=value format (FortiOS traffic/utm/event).	`fortinet_fortigate_syslog`	`Key-Value Pair`
Fortinet FortiGate firewall logs wrapped in a syslog PRI header followed by FortiOS key=value pairs.	`fortinet_fortigate_syslog_wrapped`	`Raw Text`
GCP Cloud Audit Logs in JSON format	`gcp_audit_logs`	`JSON Newline Delimi`
GCP VPC Firewall Rules Logs in JSON format	`gcp_firewall`	`JSON Newline Delimi`
GCP VPC Flow Logs in JSON format	`gcp_vpc_flow`	`JSON Newline Delimi`
Generic CSV data	`generic_csv`	`Delimited Text`

Log type	Datatype ID (`datatype` field added)	Source data format
Generic space-delimited key=value pairs	`generic_kvp`	`Key-Value Pair`
Generic metrics data	`generic_metrics`	`Raw Text`
Generic NDJSON data	`generic_ndjson`	`JSON Newline Delimi`
Generic tab-separated values	`generic_tsv`	`Delimited Text`
Generic XML content	`generic_xml`	`XML`
GitLab audit events from audit_json.log file for DevOps activity in JSON format	`gitlab_audit_log`	`JSON Newline Delimi`
GitLab audit events via streaming (HTTP webhook) for DevOps activity in JSON format	`gitlab_audit_streaming`	`JSON Newline Delimi`
Gong Revenue Intelligence Platform audit logs (UserActivityLog and AccessLog) in JSON format	`gong_audit`	`JSON Newline Delimi`
Google Workspace Activity Reports in JSON format	`gws_activity_reports`	`JSON Newline Delimi`
Google Workspace Alert Center alerts in JSON format	`gws_alerts`	`JSON Newline Delimi`
IBM AIX audit log events (AIX audit subsystem)	`ibm_aix_audit`	`Raw Text`
IBM Db2 audit CONTEXT events recording SQL statements and database operations such as COMMIT, ROLLBACK, CONNECT, and EXECUTE.	`ibm_db2_audit_context`	`Delimited Text`
IBM Db2 audit OBJMAINT events recording object maintenance actions such as CREATE_OBJECT, DROP_OBJECT, and RENAME_OBJECT.	`ibm_db2_audit_objmaint`	`Delimited Text`

Log type	Datatype ID (`datatype` field added)	Source data format
IBM Db2 audit SECMAINT events recording security maintenance actions such as GRANT, REVOKE, and IMPLICIT_GRANT of privileges and authorities.	`ibm_db2_audit_secmaint`	`Delimited Text`
IBM Db2 audit SYSADMIN events recording system administration actions such as DB2SET, DB2AUDIT, START_DB2, STOP_DB2, and GET_SNAPSHOT.	`ibm_db2_audit_sysadmin`	`Delimited Text`
IBM Db2 audit VALIDATE events recording authentication and user validation activities such as AUTHENTICATION, CHECK_GROUP_MEMBERSHIP, and GET_USERID.	`ibm_db2_audit_validate`	`Delimited Text`
IBM i (OS/400) logs in syslog-like format with key/value pairs	`ibm_os400_syslog`	`Raw Text`
IBM z/OS (OS/390) RACF audit events in syslog format with key-value payload	`ibm_racf_syslog`	`Raw Text`
Imperva SecureSphere Database Activity Monitor logs in CEF format with syslog prefix	`imperva_dam`	`Raw Text`
Imperva Incapsula Cloud WAF logs in CEF format	`imperva_incapsula_waf`	`Raw Text`
Infoblox logs in CEF (Common Event Format) format	`infoblox_cef`	`Raw Text`
Infoblox logs in CEF format with RFC 5424 syslog header	`infoblox_cef_rfc5424`	`Raw Text`
Infoblox logs in LEEF (Log Event Extended Format) format	`infoblox_leef`	`Raw Text`

Log type	Datatype ID (`datatype` field added)	Source data format
Infoblox logs in LEEF format with RFC 5424 syslog header	`infoblox_leef_rfc5424`	`Raw Text`
Infoblox DNS/DHCP appliance logs in standard syslog format	`infoblox_syslog`	`Raw Text`
Infoblox DNS/DHCP appliance logs in BSD syslog format without PRI header	`infoblox_syslog_bsd_nopri`	`Raw Text`
Infoblox DNS/DHCP appliance logs with ISO 8601 timestamps	`infoblox_syslog_iso8601`	`Raw Text`
ISC BIND9 named DNS query logs	`isc_bind_query`	`Raw Text`
Linux auditd events (audit logs) including PATH, AVC, SERVICE_START, and CRED_ACQ records	`linux_auditd_log`	`Raw Text`
Microsoft DHCP Server events forwarded as MSWinEventLog syslog with tab-delimited payload	`microsoft_dhcp_syslog`	`Raw Text`
Microsoft Windows DNS Server Service events in key=value style Windows Event Log export format	`microsoft_dns_server_eventlog`	`Raw Text`
Microsoft IIS 7.5 W3C HTTP access logs (space-delimited fields)	`microsoft_iis_accesslog`	`Delimited Text`
Microsoft Windows Event Log (classic format)	`microsoft_windows_eventlog_classic`	`Raw Text`
Microsoft Windows Event Log (XML format)	`microsoft_windows_eventlog_xml`	`XML`
MySQL/MariaDB server audit log in CSV format (timestamp, server host, user, client host, connection id, query id, operation, database, object/query, return code)	`mysql_server_audit`	`Delimited Text`

Log type	Datatype ID (`datatype` field added)	Source data format
n8n workflow automation log streaming events in JSON format	`n8n_log_streaming`	`JSON Newline Delimi`
NetApp filer cfoa event logs (weekday/month/day/time/tz prefix with bracketed cfoa event and severity)	`netapp_filer_cfoa`	`Raw Text`
NetApp log messages with leading weekday timestamp and bracketed event key and severity	`netapp_filer_syslog`	`Raw Text`
Netskope alert events (DLP, malware, malicious site, policy) in JSON/NDJSON format	`netskope_alert_json`	`JSON Newline Delimi`
Netskope event logs (page, application, audit, infrastructure) in JSON/NDJSON format	`netskope_event_json`	`JSON Newline Delimi`
nginx access logs in combined (remote_addr - remote_user [time] “request” status bytes “referer” “user_agent”) format	`nginx_accesslog`	`Raw Text`
Open Cybersecurity Schema Framework (OCSF) events in JSON format	`ocsf`	`JSON Newline Delimi`
Okta System Log events in JSON format	`okta_system_log`	`JSON Newline Delimi`
OpenAI organization audit logs in JSON format	`openai_audit`	`JSON Newline Delimi`
OpenAI API completions usage data in JSON format	`openai_completions`	`JSON Newline Delimi`
OpenAI organization cost data in JSON format	`openai_costs`	`JSON Newline Delimi`
OpenAI organization project data in JSON format	`openai_projects`	`JSON Newline Delimi`

Log type	Datatype ID (`datatype` field added)	Source data format
OpenAI organization user data in JSON format	`openai_users`	`JSON Newline Delimi`
Palo Alto authentication logs in CSV format	`pan_authentication_csv`	`Delimited Text`
Palo Alto authentication logs in syslog format	`pan_authentication_syslog`	`Raw Text`
Palo Alto authentication logs in syslog format without PRI header	`pan_authentication_syslog_nopri`	`Raw Text`
Palo Alto config logs in CSV format	`pan_config_csv`	`Delimited Text`
Palo Alto config logs in syslog format	`pan_config_syslog`	`Raw Text`
Palo Alto config logs in syslog format without PRI header	`pan_config_syslog_nopri`	`Raw Text`
Palo Alto correlation logs in CSV format	`pan_correlation_csv`	`Delimited Text`
Palo Alto correlation logs in syslog format	`pan_correlation_syslog`	`Raw Text`
Palo Alto correlation logs in syslog format without PRI header	`pan_correlation_syslog_nopri`	`Raw Text`
Palo Alto GlobalProtect logs in CSV format	`pan_globalprotect_csv`	`Delimited Text`
Palo Alto GlobalProtect logs in syslog format	`pan_globalprotect_syslog`	`Raw Text`
Palo Alto GlobalProtect logs in syslog format without PRI header	`pan_globalprotect_syslog_nopri`	`Raw Text`
Palo Alto HIP match logs in CSV format	`pan_hipmatch_csv`	`Delimited Text`
Palo Alto HIP match logs in syslog format	`pan_hipmatch_syslog`	`Raw Text`

Log type	Datatype ID (`datatype` field added)	Source data format
Palo Alto HIP match logs in syslog format without PRI header	`pan_hipmatch_syslog_nopri`	`Raw Text`
Palo Alto IP tag logs in CSV format	`pan_iptag_csv`	`Delimited Text`
Palo Alto IP tag logs in syslog format	`pan_iptag_syslog`	`Raw Text`
Palo Alto IP tag logs in syslog format without PRI header	`pan_iptag_syslog_nopri`	`Raw Text`
Palo Alto system logs in CSV format	`pan_system_csv`	`Delimited Text`
Palo Alto system logs in syslog format	`pan_system_syslog`	`Raw Text`
Palo Alto system logs in syslog format without PRI header	`pan_system_syslog_nopri`	`Raw Text`
Palo Alto threat logs in CSV format	`pan_threat_csv`	`Delimited Text`
Palo Alto threat logs in syslog format	`pan_threat_syslog`	`Raw Text`
Palo Alto threat logs in syslog format without PRI header	`pan_threat_syslog_nopri`	`Raw Text`
Palo Alto traffic logs in CSV format	`pan_traffic_csv`	`Delimited Text`
Palo Alto traffic logs in syslog format	`pan_traffic_syslog`	`Raw Text`
Palo Alto traffic logs in syslog format without PRI header	`pan_traffic_syslog_nopri`	`Raw Text`
Palo Alto tunnel logs in CSV format	`pan_tunnel_csv`	`Delimited Text`
Palo Alto tunnel logs in syslog format	`pan_tunnel_syslog`	`Raw Text`
Palo Alto tunnel logs in syslog format without PRI header	`pan_tunnel_syslog_nopri`	`Raw Text`

Log type	Datatype ID (`datatype` field added)	Source data format
Proofpoint PPS native logs with full-month timestamps and space-delimited key=value fields	`proofpoint_pps_log`	`Raw Text`
Proofpoint PPS module/filter logs with ISO timestamps and process names	`proofpoint_pps_module`	`Raw Text`
Proofpoint PPS sendmail/MTA queue logs with comma-delimited fields	`proofpoint_pps_sendmail`	`Raw Text`
Proofpoint TAP click events in JSON format	`proofpoint_tap_clicks`	`JSON Newline Delimi`
Proofpoint TAP message events in JSON format	`proofpoint_tap_messages`	`JSON Newline Delimi`
Proofpoint TAP events in RFC5424 syslog format	`proofpoint_tap_rfc5424`	`Raw Text`
Salesforce Event Log File ApexCallout events in CSV format	`salesforce_eventlogfile_callout`	`Delimited Text`
Salesforce Event Log File ApexExecution events in CSV format	`salesforce_eventlogfile_execution`	`Delimited Text`
Salesforce Event Log File ApexRestApi events in CSV format	`salesforce_eventlogfile_restapi`	`Delimited Text`
Salesforce Login History records in JSON format	`salesforce_loginhistory`	`JSON Newline Delimi`
Salesforce Setup Audit Trail records in JSON format	`salesforce_setupaudittrail`	`JSON Newline Delimi`
SentinelOne Cloud Funnel v1 EDR telemetry events in JSON format	`sentinelone_cloudfunnel_v1`	`JSON Newline Delimi`
SentinelOne Cloud Funnel v2 EDR telemetry events in flat JSON format	`sentinelone_cloudfunnel_v2`	`JSON Newline Delimi`

Log type	Datatype ID (`datatype` field added)	Source data format
Slack Workspace Audit Logs from the Slack Audit Logs API in JSON format	`slack_audit`	`JSON Newline Delimi`
Splunk binary journal files	`splunk_journal`	`Splunk Journal`
Snort IDS/IPS alert logs in Snort fast alert format (non-syslog)	`snort_alert_full`	`Raw Text`
Snort IDS/IPS alert logs in syslog format	`snort_alert_syslog`	`Raw Text`
Squid proxy access.log events (default native format)	`squid_access`	`Raw Text`
IBM z/OS SMF records exported by Syncsort in JSON format (multiple SMF record types)	`syncsort_zos_smf`	`JSON Newline Delimi`
IBM z/OS SMF type 80 RACF security audit records exported by Syncsort in JSON format	`syncsort_zos_smf_racf`	`JSON Newline Delimi`
IBM z/OS SYSLOG records exported by Syncsort in JSON format	`syncsort_zos_syslog`	`JSON Newline Delimi`
Syslog RFC 3164 format	`syslog_rfc3164`	`Raw Text`
Syslog RFC 5424 format	`syslog_rfc5424`	`Raw Text`
HashiCorp Terraform Enterprise audit log events for infrastructure changes in JSON format	`terraform_enterprise_audit`	`JSON Newline Delimi`
Trellix EDR endpoint detection events in JSON format	`trellix_edr_event`	`JSON Newline Delimi`
Trellix ePO device inventory data in JSON format	`trellix_epo_device`	`JSON Newline Delimi`
Trellix ePO security events in JSON format	`trellix_epo_event`	`JSON Newline Delimi`

Log type	Datatype ID (`datatype` field added)	Source data format
Trellix ePO group hierarchy data in JSON format	`trellix_epo_group`	`JSON Newline Delimi`
Trellix ePO syslog events in XML format	`trellix_epo_syslog_xml`	`XML`
Ubiquiti UniFi access point logs (mcad, hostapd, wevent, kernel)	`unifi_other`	`Raw Text`
Ubiquiti UniFi station tracking daemon (stahtd) logs with STA_ASSOC_TRACKER events	`unifi_stahtd`	`Raw Text`
VMware NSX FABRIC logs in RFC5424 syslog format with NSX structured data	`vmware_nsx_fabric_rfc`	`Raw Text`
VMWare NSX Firewall logs in RFC5424 syslog format with NSX structured data and firewall packet message fields	`vmware_nsx_firewall_syslog`	`Raw Text`
VMware NSX ROUTING logs in RFC5424 syslog format with NSX structured data	`vmware_nsx_routing_rfc`	`Raw Text`
VMware NSX SYSTEM logs in RFC5424 syslog format with NSX structured data	`vmware_nsx_system_rfc`	`Raw Text`
WordPress activity logs from		

4.18.1.3. Federated Search V2

Use v2 Datatypes and Datasets to speed up your federated searches. See what's currently supported.

Highlights

- v2 Datatypes are gradually replacing v1 Datatypes.
- Federated Datasets currently support v2 Datatypes for NDJSON, Delimited Text (CSV), Parquet, and Splunk Journal formats on S3 and Azure Blob.
- v2 Datasets support the `Splunk DDSS` and `Splunk SmartStore` partitioning schemes.
- Certain limitations apply.

What Are v2 Datatypes?

Next-generation Datatypes in Cribl Search. They power high-speed lakehouse engines, and let you use the new, high-performance architecture for federated queries into object storage like Amazon S3 or Azure Blob.

Whereas v2 Datatypes work with lakehouse engines out of the box, support for federated Datasets is rolling out gradually, and requires some reconfiguration on your part.

For basic info on v2 Datatypes, see v2 Datatypes in Cribl Search.

For info on Datatypes in general, see Datatypes in Cribl Search.

No Action Required For Now

You don't have to migrate your existing federated Datasets at this point. However, we recommend using v2 Datatypes for new Datasets where supported.

Why Switch from v1 to v2

Use v2 Datatypes and Datasets to get:

- **Faster queries**: Filtering and parsing happen closer to the data, replacing the older rule-chain model.
- **Clearer mapping**: Each path and glob pattern maps directly to a Datatype, so you always know which parsing applies.
- **Future-proofed**: Switching now aligns you with where federated search is going, as well as with high-speed lakehouse engines.

What's Supported Today

You can use v2 Datasets with:

- **Cribl-hosted** Search Datasets: v2 Datatypes work with lakehouse engines by default.
- **Amazon S3** and **Azure Blob Storage** federated Datasets, when formatted as NDJSON, delimited text (CSV), Parquet, or Splunk Journal (see limitations).
- `Splunk DDSS` and `Splunk SmartStore` partitioning on **Amazon S3** and **Azure Blob Storage** federated Datasets.
- **Cribl Lake** Datasets: Newline-delimited JSON, Parquet, and DDSS objects in Lake storage, configured with Datatype rows on the Dataset (see Dataset Type and Datatypes for Lake Datasets).

For full details on what's supported, see Current Limitations.

Switch a Federated Dataset from v1 to v2

You can't change **Type** on a saved federated Dataset. To move from **v1** to **v2**, clone the Dataset and set **Type** on the clone before you save.

1. Check What's Supported

Start by reviewing the limitations to understand current support.

2. Clone and Reconfigure Your Dataset



You can't clone **Lake Datasets** (including BYOS). Instead, open the existing Dataset, set **Type** to **v2**, configure **Datatypes**, and select **Save**. The change isn't destructive and you can switch back to **v1**. See Dataset Type and Datatypes for Lake Datasets.

1. Clone your existing v1 Dataset.
2. Switch the cloned Dataset's **Type** from **v1** to **v2**.
3. Configure the bucket/container path(s) and other settings.

   For Amazon S3, see v2 Dataset Configuration for S3.

   For Azure Blob, see v2 Dataset Configuration for Azure Blob.
4. Confirm with **Save**.

3. Run a Search to Verify

Run a test search against your new v2 Dataset. If the results include the correct `datatype` field, the switch worked.

Dataset configuration may be cached briefly after saving, so if results look off at first, wait a moment and re-run.

Search Splunk Journal Files in v2 Federated Datasets

Cribl Search supports Splunk binary journal files named `journal.gz`, `journal.zst`, or `journal.lz4` in v2 federated Datasets on Amazon S3 and Azure Blob Storage.

How you configure the Dataset depends on the layout of the bucket or container.

Journal Files in Paths You Define

Use the `Defined in Path` partitioning scheme when you copied journal files into a path of your own design, for example when archiving them off an indexer. This works on both Amazon S3 and Azure Blob Storage.

1. Add a filter row with **Filter** set to `**/journal.{gz,zst,lz4}`.
2. Set **Datatype ID** to the stock `Splunk Journal` Datatype, `splunk_journal`, or to a clone of that Datatype.
3. Confirm with **Save**.

Splunk DDSS and SmartStore Buckets

Use the `Splunk DDSS` or `Splunk SmartStore` partitioning scheme when Splunk created the layout. This is the case when Splunk Cloud rolls data off to Self Storage, or when Splunk Enterprise indexers offload to SmartStore. On v2 Datasets, these schemes are available for **Amazon S3** and **Azure Blob Storage**.

1. Set **Bucket path** (or **Container path**) to the parent folder of your indexes.
2. Set **Partitioning scheme** to `Splunk DDSS` or `Splunk SmartStore`.
3. Set **Datatype** to the stock `Splunk Journal` Datatype, `splunk_journal`, or to a clone of that Datatype.
4. Confirm with **Save**.

Selecting either scheme replaces the **Filters** table with a single **Datatype** drop-down, which lists only Datatypes that use the Splunk Journal data format. You don't configure glob patterns, file extensions, or compression formats. Cribl Search walks the Splunk directory layout itself to find the journal files.

Cribl Search also limits what it reads. For DDSS, it skips bucket directories whose encoded time range falls outside the time range of your search. For SmartStore, it evaluates the receipt metadata of each bucket before opening journal content.

For the path formats that each scheme expects, see Amazon S3 Partitioning Schemes and Azure Blob Storage Partitioning Scheme.

Always Narrow a Search to One Index

Name the index in every DDSS or SmartStore search. The index directory sits above the time-encoded `db_` directories in the Splunk layout, so a time range alone still leaves Cribl Search traversing every index in the bucket or container.

v1 Datasets let you select an index with a **Path filter** such as `index=="index_y"`. v2 Datasets have no equivalent field, so filter on the `index` field in the query instead:

```
dataset="my_ddss_dataset" earliest=-7d latest=-1d
| where index=="index_y"
```

Copy

Use the `where` operator with case-sensitive `==`, and spell the index name exactly as it appears in the path. Only an exact match narrows the path.

Current Limitations of Federated Search v2

Support for v2 Datasets on Amazon S3, Azure Blob Storage, and Cribl Lake is expanding gradually. Read on to see the current status.

Supported Data Formats

You can currently use the following data formats with v2 federated Datasets:

- `JSON Newline Delimited`
- `Delimited Text`
- `Parquet`
- `Splunk Journal`

Other formats aren't supported yet.

Splunk DDSS and SmartStore Partitioning

v2 Datasets support `Splunk DDSS` and `Splunk SmartStore` partitioning on **Amazon S3** and **Azure Blob Storage**. See Splunk DDSS and SmartStore Buckets. Two v1 options have no v2 equivalent:

- The **Path filter** that selects an index, for example `index=="index_y"`. Filter on the `index` field in the query instead.
- The SmartStore **Time range** control on the **Dataset Provider** tab. See Splunk SmartStore Time Range on S3.

Cribl Lake Formats

Cribl Lake v2 Datasets don't use the **Filters** table, because Cribl Search already knows how Cribl Lake lays out its objects. Instead, a **Datatypes** table pairs a read-only **Data Format** with a **Datatype ID**, and you never enter a glob. A JSON or Parquet Lake Dataset starts with one row for its own storage format, and you can select **Add**

Data Formats to add a second row for the other format. A **DDSS** Lake Dataset gets a single `Splunk DDSS` row, so you choose a Datatype but not a second format. See Dataset Type and Datatypes for Lake Datasets.



If `_raw` contains valid JSON, Cribl Search can extract fields from that JSON. For guidance on when to store only `_raw` versus sending structured top-level fields, see Structure Events for Cribl Lake and Manage Lake Datasets.

Unavailable v2 Datatype Options for Federated Search

If you configure a v2 Datatype with the following options, you won't be able to apply that Datatype to federated Datasets:

- **Additional Extractions**
- **Schema Maps**
- **Add Fields to Events**

When you're creating a federated Dataset, the Cribl Search UI hides any v2 Datatypes that use these configurations.

One Bucket/Container Path per Dataset

Each v2 Dataset on **Amazon S3**, **Azure Blob Storage**, or **Cribl Lake** supports only one bucket/container path. Creating multiple paths via the API will cause search errors.

You can add multiple filters to that path to handle different file types (e.g., JSON and CSV). Filters are applied in order, so place specific patterns before general ones.

Glob Patterns Match the Full Object Path

Glob patterns match the entire path (e.g., `bucket/prefix/folder/file.csv`), not just the filename. Use recursive patterns like `**/*.csv` to include files in subfolders.

Cribl Search doesn't validate patterns on save, so test with a small data subset first.

CSV Headers Are Parsed as Events

There's no setting to mark a header row. If your CSV files have one, it will appear as the first data event instead of being used as column names.

4.18.2. Storage Classes

Control your costs by selectively enabling which object storage classes (access tiers) you want each Dataset to search.

For each Dataset that targets Amazon S3, Azure Blob Storage, or Google Cloud Storage, you can specify which storage classes the Dataset should search. (Azure refers to storage classes as access tiers.) This configuration option offers two advantages:

- You can control costs by skipping over "colder" classes that are expensive to read.
- You can avoid errors, because Cribl Search automatically skips over the classes that it cannot read on demand.

How Storage Classes (Access Tiers) Work


When you create a new Dataset on an object store Dataset Provider, the configuration modal's **Storage classes** tab will default to a single class that offers rapid retrieval at low cost. As shown below, you can enable other storage classes that you want the Dataset to search.

By design, this tab omits classes that Cribl Search cannot search on the corresponding Dataset Provider. Objects in these classes can't be read on demand, because they must first be rehydrated to a warmer class. (See also Handling Automatically Aged Objects below.)

At least one storage class must be selected, before you can save or resave the Dataset's configuration.


Default Storage Classes

On Amazon S3 Datasets, the default storage class is **S3 Standard**. The tab omits unsupported tiers.




S3 Dataset: default storage classes

On Azure Blob Storage Datasets, the default storage class is **Hot tier**. The tab omits the unsupported archive tier.



Azure Blob Storage Dataset: default storage classes

On Google Cloud Storage Datasets, the default storage class is **Standard**.



Google Cloud Storage Dataset: default storage classes

Storage Classes on Existing Datasets

On Datasets that were configured before Cribl Search added storage class selection, **all** supported storage classes are initially enabled. This is to avoid disruption to searches that you've scheduled, or that you explicitly rerun.

However, you can optimize your future costs by using the above options to deselect classes that have higher retrieval costs. As we'll see next, these classes typically store older data that you'll consider less relevant to your current searches.

Handling Automatically Aged Objects

On Amazon S3 Datasets, S3 Intelligent-Tiering is a storage **class** that you can enable, but objects will gradually age into archive **tiers** that effectively behave like Cribl Search's unsupported Glacier tiers. On Datasets where you've enabled **S3 Intelligent-Tiering**, Cribl Search will try to read these objects, will gracefully skip them when reading fails, and will log a warning.

Objects in non-searchable Glacier classes can also arrive through Lake BYOS Dataset configuration rather than through aging. If a BYOS Dataset is configured to write to Glacier Flexible Retrieval or Glacier Deep Archive, Cribl Search skips those objects in the same way. See Storage Class for BYOS Datasets.

On Azure Blob Storage, enabling automatic lifecycle management, with a permissive policy, can similarly cause your blobs to age onto the archive tier. Blobs on this tier cannot be retrieved unless you rehydrate them into a warmer tier. Here, Cribl Search will similarly skip reading these blobs, and will log warnings. You can avoid the issue (and retain the option to make your data searchable) by configuring a lifecycle management policy that excludes the archive tier.

Objects can also arrive on the archive tier through Lake BYOS Dataset configuration rather than through aging. If an Azure BYOS Dataset is configured to write to the Archive tier, Cribl Search skips those objects in the same way. See Storage Class for BYOS Datasets.

On Google Cloud Storage, enabling Autoclass behavior can similarly cause your blobs to age onto cooler tiers that you haven't enabled your Dataset to search. Google Cloud Storage throws no warnings or errors, and will retrieve these objects at fast STANDARD speed (but with added retrieval costs). Therefore, be aware that enabling Autoclass can increase your costs.

4.18.3. Supported Data Formats

Learn about how Cribl Search processes the most common data formats.

List of Supported Data Formats

You can search data in most of the commonly used formats, including text files, binary files, archives, compressed files, and more.

Data Format Example	File Extension Examples
Gzip	`.gz .gzip .tgz .tar.gz application/x-gzip`
systemd Journal	`.journal .journal~`
Splunk Journal	`journal.gz journal.zst journal.lz4`
LZ4	`.lz4`
Snappy	`.snappy`
Parquet	`.parquet .pqt .parq`
Splunk rawdata	
Tar	`.tar .tgz .tar.gz`
Text	`.log .csv .json .ndjson .txt`
ZIP	`.zip`
Zstd	`.zst`

Text Data Formats

Text files contain human-readable data. They're often used to store logs, but can also contain structured data, in formats such as JSON or CSV.

You can search text files in most of the commonly used formats, including `.log`, `.json`, `.ndjson`, `csv`, and more.

Binary Data Formats

Binary files are non-human-readable files that use formats optimized for storage and processing efficiency. They're often used to store structured data, such as Parquet files, or system and application events, such as journals.

When you search files in formats that Cribl Search can't recognize, they're processed as binary files.

`systemd` Journal Files

systemd journal files are binary files used for logging and storing system and application events.

You can search both `.journal` and temporary `.journal~` files, which are helpful when investigating unexpected process failures.

Splunk Journal

Cribl Search recognizes Splunk binary journal files named `journal.gz`, `journal.zst`, or `journal.lz4`. These files contain events and native Splunk metadata, including `_time`, `indexTime`, `host`, `source`, and `sourcetype`.

For v2 federated Datasets, map the `**/journal.{gz,zst,lz4}` glob to the stock **Splunk Journal** (`splunk_journal`) Datatype. You can instead select the `Splunk DDSS` or `Splunk SmartStore` partitioning scheme, which lets Cribl Search discover journal files without a glob. For configuration steps, see Search Splunk Journal Files.

Parquet

Parquet binary files are columnar storage format files that support nested data structures. This makes them an ideal choice for big data analytics.

You can search Parquet files with the `.parquet`, `.pqt`, and `.parq` extensions.

Using Parquet Time Fields

When processing Parquet files, by default, the Cribl Search `_time` field is assigned the value of now. You can instead use a time field of the event, by assigning its value to `_time`:

1. Create or open a v1 Datatype by navigating to **Data** > **Datatypes**.
2. Select **Add rule**.
3. At the bottom, in the **Add fields to events** section, select **Add field**.
4. Assign the **Name** as `_time` and its **Value expression** to the time field in the event. For example, `_time = time`.
5. Save the Datatype changes.
6. Navigate to the Dataset that specifies your Parquet data and open the **Processing** section.

7. Assign the Datatype to the Dataset and save your changes.

Now, when searching your Parquet Dataset, the time from the event will be used as the reference for the search's time range.

> **Example: Amazon Security Lake**
>
> Amazon Security Lake logs data into Parquet format following the schema defined by OCSF. The time is assigned to the field `time` and is Unix time expressed in milliseconds.
>
> To use this field, you need to set its value to the Cribl Search field `_time`. Since Cribl Search uses seconds instead of milliseconds, you also need to convert it by dividing by 1,000. In this case, the field you'd add to a Datatype would be: `_time = time/1000`.

Compression Data Formats

Compression formats are used to reduce the size of data to optimize storage space and speed up data transmission.

You can search files compressed with a wide range of algorithms, including LZ4, zstd, gzip, Snappy, and more.

LZ4

LZ4 is a popular compression format that offers multiple compression levels and a good balance between compression ratio and speed.

Zstd

Zstandard, also known as zstd, is an open-source compression format developed at Facebook. It's often used in scenarios where high compression speeds are critical.

Splunk Rawdata

Splunk's compressed rawdata files store event data ingested by indexers. They also contain related journal information.

Gzip

A popular compression format, gzip is often used to compress log files.

In Cribl Search, you can search both `.gz` and `.gzip` files.

Snappy

Snappy, previously known as Zippy, is an open-source compression format developed at Google, popular for its high compression speeds.

In Cribl Search, you can search `.snappy` files.

Archive Data Formats

Archive formats are used to package multiple files together into a single file.

You can search archives in most of the commonly used formats, including tar, ZIP, and more.

Tar

The tar (tape archive) file format is used by the UNIX-based utility tar to package files together into sets known as “tarballs”.

ZIP

ZIP is a popular archive format that supports lossless data compression. `.zip` files can contain compressed or non-compressed data, and can use different compression levels.

Searching Tarballs and ZIP Archives

When searching tarballs or ZIP archives, you can specify which of the archive’s files you want to search.

When processing files with `.tar`, `.tgz`, `.tar.gz`, or `.zip` extensions, Cribl Search processes all files inside the archive and adds a field named `cribl_archive_source` to each file’s events. The value of `cribl_archive_source` is the name of the file inside the archive.

For example, let’s say an archive named `archive.tgz` contains files `dir1/file1.log` and `dir2/file2.log`. An event from `dir1/file1.log` returned from a search would look like this:

```
{
...
source: archive.tgz
cribl_archive_source: dir1/file1.log
...
}
```

Copy

Now, to search a specific file inside the `archive.tgz` archive, you can refer to the `cribl_archive_source` field in your query. For example: `cribl_archive_source=dir1/file1.log`.

Internal Fields

Cribl Search maintains an internal `__raw` field that contains each original event's state after Event Breakers are applied, but before other Datatype rules. (Where an event contains no `_raw` field, Cribl Search constructs one by serializing all the event's top-level and nested fields.)

You can access this field to determine the size of the original event, including its metadata.

5. Explore Your Cribl Search Data

Inspect your Datasets and check your team's search history before writing new queries.

Inspect Your Datasets

Explore your Datasets to understand their contents, check field statistics, and find proven queries. This helps you pick the right starting point for an investigation and catch ingest issues early.

See Inspect Datasets for details.

View Your Search History

Review all searches that you or your organization have run. View cached results, rerun searches, and build new queries on top of previous result sets.

See View Search History for details.

5.1. Inspect Your Cribl Search Datasets

Understand your data before searching, so you can pick the right Datasets, know their fields, and build on previous analyses.

Highlights

- From the **Logs** page, select a Dataset to see its contents, statistics, history, and more.
- Use that info to pick a starting point for an investigation, reuse trusted queries, or spot ingest issues.
- Cribl-hosted Search Datasets give you richer insights into fields than federated Datasets.

Explore Your Datasets Before Running a Search

Reviewing your Datasets beforehand lets you:

- Decide what fields matter most for your investigation.
- Reuse searches, Dashboards, and Notebooks instead of starting from scratch.
- Catch ingest and parsing issues before they affect analysis.

If you're unsure where to start in an environment with a lot of data:

- Prefer Datasets with higher recent search activity.
- De-prioritize low- or no-usage Datasets unless you have a specific use case.
- Look up a Dataset's top users to find people that can share proven query patterns.

Visibility depends on your permissions, so you'll only see Datasets you're allowed to access.

To verify that events are arriving, parsing, and routing as expected in real time, see Live Data.

See Dataset Details and Statistics

Explore your Search Datasets and federated Datasets:

1. Go to **Logs**: On the Cribl.Cloud top bar, select **Products** > **Search**.
2. Under **Available Datasets**, select a Dataset.

What you see in the details panel depends on the Dataset type.

Search Datasets | Federated Datasets

For new Search Datasets, allow time for the statistics to populate, especially for multi-day windows.

Section	Description
Earliest event time **Latest event time**	Dataset's time range and freshness.
Total event count **Total Dataset size**	Dataset's data volume.
Volume of Events and Bytes	Lets you spot spikes, drops, or gaps before you write a query.
Usage	Recent search activity on the Dataset.
Top 10 Users	Users who ran the most searches on the Dataset.
Fields	See Explore Fields in Search Datasets.

Search History

Review recent queries for proven starting points. Reuse what works, then refine.

For more information and ideas, see View History and Reuse Search Results.

Saved Searches

Open saved searches to apply team standards or keep results more consistent across users.

Dashboards

View Dashboards that reference this Dataset before you write a custom query.

Notebooks

Open related Notebooks to see or continue earlier investigations.

Explore Fields in Search Datasets

Cribl-hosted Search Datasets offer deep insight into their data structure, so you can pick fields that work well in filters, group-by clauses, or aggregations.

1. Go to **Logs**: On the Cribl.Cloud top bar, select **Products** > **Search**.
2. Under **Available Datasets**, select a Search Dataset you want to inspect.

   Search Datasets are marked with the lakehouse icon .

3. In the resulting details panel, look at the **Fields** section.

   If the **Fields** section is empty, select **Retry** to load the metadata.

   If there's no **Fields** section at all, you're looking at a federated Dataset. Select a Search Dataset instead.

Each field has the following metrics, filtered for the selected time window:

Field Metric	Description
Field	Field name you use in queries.
Type	Data type, such as string, numeric, boolean, object, or array.
Uniques	How many distinct values the field has in the selected time window.
Presence	What percentage of all events contain this field in the selected time window.
Null or empty	How often values are null or empty in the selected time window.

Use those metrics to find:

- High-presence fields for filters and joins.
- Low-cardinality fields for group-by clauses.
- Weak fields with many null or empty values.

Select a field to drill down into details. For example, you can add the field to a query, or aggregate on it.

5.2. View Search History In Cribl Search

View, rerun, and reuse past searches, saving time and resources.

Highlights

- Open **History** from the Cribl Search left sidebar to see searches run in the past.
- View and query cached result sets instead of running the same search again.
- Search Admins control how long searches are kept.

History Lets You Analyze and Reuse Past Searches

Every query you run is recorded in **History**, along with its details and result set. Reusing those records helps you avoid duplicate searches across your team, saving time and credits. Use search history to:

- View a past search without rerunning it.
- Rerun a query with the same settings to check for changes or to add it to a Dashboard or Notebook.
- View the cached results of a past search, query that result set, or reuse it in a new query.

Search Admins control how long searches are kept.

Search Admins see the history of all searches in the Cribl.Cloud Organization. Search Users and Editors see only their own searches and searches shared with them.

View Search History

From the Cribl.Cloud top bar, select **Products** > **Search** > **History**.

On the **History** page:

- Select the column selector to show or hide columns.
- Select **...more** to see search details.
- Select **Actions** ⋯ to rerun a search, save it, search its results, or add it to a Dashboard or Notebook.
- Select the refresh icon to refresh the page.
- Filter for **Scheduled** searches at the top right. Scheduled searches show information about their latest executions. To see individual runs, select **items**.
- Select check boxes to mark searches for deletion.

For a quick look at recent searches without leaving the **Logs** page, select the **History** tab below the query box.

Rerun a Past Search

Run a new search using the same query text and settings as a search run in the past.

1. From the Cribl.Cloud top bar, select **Products** > **Search** > **History**.
2. In a search row, select **Actions** ⋯.
3. Select **Rerun**.

In certain cases, you may find it faster and cheaper to query the result set or simply view the cached results.

View Cached Search Results

Load the cached results of a past search. This doesn't consume any credits.

1. From the Cribl.Cloud top bar, select **Products** > **Search** > **History**.
2. Select a search row.

Cribl Search loads the search and its cached results, without rerunning the query.

Query the Result Set of a Past Search

Run a query on the results of a search run in the past. This doesn't rerun the original query itself, but runs an actual search on the result set, so can lead to minor credit consumption.

1. From the Cribl.Cloud top bar, select **Products** > **Search** > **History**.
2. In a search row, select **Actions** ⋯.
3. Select **Search the Results**.

A new tab opens and runs a search on the result set, using the `$vt_results` virtual table. You can now modify the query for further analysis.

Reuse the Results of a Past Search in a New Query

When writing a query, reference the result set of a past search, using the `$vt_results` virtual table. This lets you treat the results as a regular Dataset.

This doesn't rerun the original query itself, but runs an actual search on the result set, so can lead to minor credit consumption.

Get the ID of the search you're interested in (you'll find it in the search details), and use the `jobId` predicate:

```
dataset="$vt_results" jobId="1704236905683.wgocax"
```

Copy

You can also load the results of multiple searches at once, for example:

```
dataset="$vt_results"
 | where jobId > "1704236905600" and jobId < "1704236906000"
```

Copy

To reuse the results of a saved or scheduled search, add the search name by using the `jobName` predicate. This will load the results of the latest execution of the saved search. For example:

```
dataset="$vt_results" jobName="mySavedSearch"

// or, for example
dataset="$vt_results"
 | where jobName startswith "my"
```

Copy

To load a specific execution of a saved search, use the `execution` parameter, for example:

```
// load the last run of mySavedSearch (default)
dataset="$vt_results" jobName="mySavedSearch" execution = 0

// load the run before last
dataset="$vt_results" jobName="mySavedSearch" execution = -1
```

Copy

For more information and examples, see `$vt_results`.

Add a Past Search to a Dashboard or Notebook

Find a search run in the past and add it to a new or existing Dashboard or Notebook.

1. From the Cribl.Cloud top bar, select **Products** > **Search** > **History**.
2. In a search row, select **Actions** ⋯.
3. Select **Add to Dashboard** or **Add to Notebook**.

Manage Search History Retention

Search Admins set the retention limits for search history:

- How long to keep each search (**Search history TTL**).
- How many searches to keep in total (**Search history job limit**).

The job limit takes priority. Once it's reached, the oldest searches are deleted regardless of their TTL.

To set these limits:

1. From the Cribl.Cloud top bar, select **Products** > **Search** > **Settings** > **Limits**.
2. Set the **Search history TTL** and **Search history job limit**. For details, see List of Configurable System Limits.

To override both limits for a specific scheduled search, use the **Keep last executions** setting.

Notebooks have a hard-coded 30-day retention period. Exceeding the **Search history job limit** will cause other jobs to be removed before Notebook jobs, to respect this extension.

6. Search Your Data With Cribl Search

Learn how to build Cribl Search queries, with examples.

Build a Search

Learn about query syntax, operators, time ranges, sampling, and more. See: Build a Search.

Write Your First Query

Write simple queries in Kusto Query Language, using operators such as `limit`, `project`, `where`, `count`, `order`, and others. See: Write Your First Query.

Write Queries Using Copilot

Use the Cribl Copilot KQL assistant to generate Kusto Query Language expressions from natural language. See: Write Queries Using Copilot.

Common Query Examples

Examine, run, and adapt some typical search queries. See: Common Query Examples.

Use Search Results

Reuse and manage the results from search queries you've already run. See: View Search History.

Notebooks

Run an entire investigation in one tab, and share your work with others. See: Notebooks.

Example Searches by Provider

Learn how to search data coming from different Dataset Providers. See: Example Searches by Provider.

Search and Retrieve Results with the Cribl API

Use the Cribl API to execute searches and retrieve Cribl Search results. See: Search and Retrieve Results.

6.1. Integrated AI Experience (Preview) In Cribl Search

Preview Feature

Cribl is still developing this Preview feature. We don't recommend using it in a production environment, because the feature might not be fully tested or optimized for performance, and related documentation could be incomplete.

Please continue to submit feedback through normal Cribl support channels, but assistance might be limited while the feature remains in Preview.

Ask Cribl AI to explain your data, run searches, and build content, without leaving the page you're on.

About the Integrated AI Experience in Cribl Search

Cribl AI is integrated across Cribl Search as a sidebar that stays with you as you move between the **Logs** page, Dashboards, Notebooks, and saved searches.

The assistant keeps your conversation and knows which page you're viewing. This means you can ask follow-up questions about what's in front of you, instead of restating context each time.

What Cribl AI Can Do

Explain and analyze. Ask what a set of results, a Dashboard panel, or a Notebook contains. Cribl AI reads the page you're on, including the current Dashboard definition and its panels, and answers in plain language. It reads a live snapshot each time, so it reflects edits you just made.

Run searches. Describe what you want to find and Cribl AI writes and runs the KQL for you. It can run a query in the live Search view from anywhere in the product, so you don't have to navigate to the **Logs** page first.

Create and update content. Cribl AI can create, update, and delete Dashboards, Dashboard Collections, Notebooks, and saved searches. It can also build Dashboard chart panels, set up alerts on saved searches, and manage search jobs.

Adjust what you're viewing. While you're on a Dashboard, ask Cribl AI to change an input to filter or re-scope the Dashboard without leaving the page.

Share resources. Cribl AI can grant or revoke user and team access to Dashboards, Datasets, Dataset Providers, Macros, Notebooks, and Notebook Templates.

When Cribl AI creates or updates something that has its own page, it offers a **View it here** link. Selecting the link opens the resource and leaves the sidebar open, so your session continues.

Cribl AI works only with Cribl Search objects. It can't change Cribl Stream or Cribl Edge configuration, and it can't create or edit Packs.


Before You Start

- Use Cribl.Cloud. This Preview isn't available in on-prem deployments or in Cribl.Cloud Government.
- Confirm that an AI provider is configured for your Organization. See Cribl AI Availability.
- (Optional) Enable Dataset Intelligence on the Datasets you search most often. Cribl AI reads this analysis to write more accurate queries.

Cribl AI doesn't appear on the **Metrics** and **Monitors** pages, which are out of scope for this Preview. If you open the sidebar and then navigate to either page, the sidebar closes.

Run a Cribl AI Session

On the top bar, select the Cribl AI icon at the upper right. The sidebar opens on the right side of the page, alongside your content rather than on top of it.



Cribl AI icon on the top bar

Select the icon again, or select **Close AI sidebar**, to close it. Closing the sidebar doesn't end your session.

A session is one continuous conversation. Cribl AI keeps your session as you move between Search pages, so you can build a Dashboard on one page and keep asking about it on another.

A new session is titled **New Chat**. After your first prompt, Cribl AI replaces the title with a topic it derives from what you asked, which makes sessions easier to recognize later.

The sidebar header offers these actions:

- **New chat**: Start a fresh session. Your previous session remains available in your history.
- **View session history**: Open the sessions drawer, which lists every session you have access to.
- **Close AI sidebar**: Hide the sidebar without ending the session.

In the sessions drawer, Cribl AI sessions appear with a **Context** of **Cribl AI**, and the sidebar lists your latest ones under **Recent sessions**. Sessions from Cribl Search investigations appear separately with a **Context** of **Investigations**. The two surfaces are distinct, so starting a Cribl AI session doesn't affect your investigations or vice versa.

How Permissions Apply

Cribl AI acts as you, so it can only do what your Search Permission already allows.

Before it offers a change, Cribl AI checks your permissions and shows **Checking permissions...** briefly. If you don't have permission, the card tells you so and offers only **Dismiss**. Cribl AI never sends the request, and no **Run request** button appears.

Confirm Changes Before They Happen

Cribl AI never changes anything without asking. When it proposes a change, the sidebar shows a confirmation card describing the action in plain language.

To review the exact change first, expand **View request**. This shows the HTTP method and URL that Cribl AI will call, along with the request body when there is one.

Then choose one of the following:

- **Run request**: Apply the change.
- **Cancel**: Reject the change. Cribl AI continues the conversation without applying it.

Find Searches That Cribl AI Ran

Searches that Cribl AI runs on your behalf have a job type of `agentic`. Search History excludes them by default, because a single conversation can generate many searches and they would otherwise crowd out the searches you ran yourself.

To see them, select `agentic` in the **Type** column filter. Search History then refetches and includes them.

Other Cribl AI Features in Cribl Search

Cribl Search offers several AI features. Use this page for the integrated sidebar, and see the following for the others:

- Run Investigations: A guided experience for incident investigation, with investigation plans, hypotheses, and Notebook output.
- Write Queries Using Cribl Copilot: Natural-language to KQL translation in the query box, plus suggested follow-up queries.
- Add Visualizations Using Cribl Copilot: Dataset analysis that suggests Dashboard visualizations.

For what each feature sends to an AI provider, see Cribl AI and Your Data.

6.2. Build A Search


Learn about query syntax, operators, time ranges, sampling, and more.

A search needs a query and a time range. Queries specify the data to search and run functions and operators from our ergonomic and powerful search language.

Queries contain zero or more operators separated by a pipe `|`. Data flows, or is piped, from one operator to the next. Events are filtered or manipulated at each operation and then fed into the following operation.

You can think of the data flow as a funnel, where you start out with selected events. Each time the data passes through another operator, it is filtered, rearranged, or summarized. Because the piping of information from one operator to another is sequential, the query operator order is important and can affect both results and performance. At the end of the funnel, you're left with a refined output.

The following diagram shows how each operation in a query changes search results.



Data flow diagram

Query Syntax

`[Statements;] Scope [| Processing [| ... ]]`

- **Statements** - Optional statements that can set query options and assign names to expressions (which allows you to use `join` or `union` later in the query). Each statement needs to end with a semicolon (`;`).
- **Scope** - Define Datasets and use the `cribl` operator to specify the events to search. Wildcards `*` represent one or more characters. For example, `source=/*/foo.log "error"` returns lines from `/*/foo.log` containing the term `error`.
  - Dataset syntax: `dataset=DatasetID`. E.g, `dataset=myCDNLogs`.
    - Data from different Datasets can be easily combined in a search. For example, `dataset=myVPCFlowlogs or dataset=myCDNLogs`.
  - The `default` Dataset is searched when no Dataset is defined.
  - The `cribl` operator is implicit when an operator isn't specified. You can stop this behavior by enabling **Strict Kusto Mode** in the UI Options.
  - The `cribl`, `externaldata`, and `find` operators are used in the scope.
  - The `search` and `timestats` operators may be used in the scope.
- **Processing** - Optional operators that can be used together with context, cribl, statistical, and scalar functions. Use a pipe `|` between operators.

Every stage of a query can also include Macros (for example, `${MacroID}`).

Examples



Runnable Kusto code examples include a **Run in Cribl Search** link in the top-right corner of the code block. Select it to open the query in your Cribl Search environment with the query loaded and ready to execute. You can also use the **Copy** button to copy a query and paste it into your own search.

- Find events with `error` in the `cribl_internal_logs` Dataset:

```
dataset="cribl_internal_logs" "error"
```

Copy | Run in Cribl Search

- Find and return up to 1,000 logs:

```
dataset="cribl_search_sample"
| limit 1000
```

Copy Run in Cribl Search

- Aggregate events by the `method` field:

```
dataset="cribl_internal_logs"
| limit 1000
| summarize count() by method
```

Copy Run in Cribl Search

- Count the events in each minute, grouping by the `method` field, from the last 15 minutes:

```
dataset="cribl_internal_logs" earliest=-15m method=*
| limit 1000
| timestats span=1m count() by method
```

Copy Run in Cribl Search

- Merge the events of two different Datasets:

```
let query1 = dataset="dataset1" | where x < 10;

dataset="dataset2"
| join query1 on commonField
```

Copy

Syntax Highlighting

Within the query box, the following color coding distinguishes components of your query:

Component	Light Mode	Dark Mode
Literal	Magenta	Magenta
Field name	Pink	Pink
Search term	Orange	Orange
Operator	Blue	Blue
Function	Teal	Teal

Component	Light Mode	Dark Mode
Connecting keyword	Amber	Amber
Error	Red	Red
Comment	Green	Green

(Dark mode uses lighter shades to reduce contrast.)

Field Names

Each event field has a unique name that is used as its reference in a query. Each field contains a key-value pair, where the field name is the key. Field names follow these rules:

- They're case-sensitive.
- Support letters, digits, underscores `_`, spaces, dots `.`, and dashes `-`.
- Fields containing a special character (spaces, dots, or dashes) require quoting (see below).

Quoting Keywords

Field names that are identical to some query language keywords, or have special characters, require quoting when they're referenced directly by a query:

Query text	Description
`field`	Field names that don't include special characters or map to some language keyword don't require quoting.
`['field-name']`	Field names that include special characters must be quoted using `['` and `']` or using `["` and `"]`.
`["where"]`	Field names that are language keywords must be quoted using `['` and `']` or using `["` and `"]`.



You can normalize field names that contain separators, using the `foldkeys` operator.

For example, events from the `cribl_internal_logs` Dataset have a `time` field which is a reserved keyword requiring quoting. To reference the field in a query you'd specify it as:

```
['time']="2023-03-31T12:24:10.770Z"
```

Copy

Similarly, to exclude `null` fields from the search results, you must bracket and quote the `null` keyword. To see how this works, let's start with the following query. Here, the `method` field has a value of null. We'll want to remove that field:

```
// Count of method over time with a null field value.
dataset="cribl_internal_logs" earliest=-15m
 | limit 1000
 | timestats count() by method
```

Copy Run in Cribl Search

This first attempt will **not** work, because `null` is unquoted:

```
// This won't work because null is a keyword and must be quoted within brackets.
dataset="cribl_internal_logs" earliest=-15m
 | limit 1000
 | timestats count() by method
 | project-away null
```

Copy Run in Cribl Search

Here is the same query, with `null` properly bracketed and quoted. If you run it, watch the `null` field from the original query go away:

```
// This will work because null is properly quoted.
dataset="cribl_internal_logs" earliest=-15m
 | limit 1000
 | timestats count() by method
 | project-away ["null"]
```

Copy Run in Cribl Search

Generated Fields

Cribl Search generates fields from expressions and returns them in your search results. The expression is evaluated and all non-word characters are replaced with underscores `_`. For example, `count(myField)` returns as `count_myField`.

If there's only one field, a single underscore is appended to it. For example, `count` returns as `count_`.

Maximum Field Length

Generated fields can be a maximum of 20 characters long. Fields are truncated from the left of the expression after the function name to keep within the 20-character limit. For example, `countif(channel, elapsedMS > 0)` returns as `countif_elapsedms_0`.

If the left field does not start with an alphabetic character, the farthest right field is truncated.

Built-in Fields

Cribl Search uses several fields to assist in the handling of data. These "meta" fields are not part of an event, but they are accessible, and can be referenced in queries.


Field	Description
`_raw`	The raw event. Where an event contains no `_raw` field, Cribl Search constructs one by serializing all the event's top-level and nested fields.
`_time`	The raw event's timestamp. If Cribl Search detects no timestamp, it uses the last modified timestamp.
`cribl_fleet`	The name of the Edge Fleet that contained the event.
`dataset`	The Dataset that was queried to retrieve the event.
`datatype`	The Datatype processed against the event.
`host`	The hostname of the device that contained the event.
`source`	The name of the data object that contained the event.

If an event has a field with the same name as a Cribl Search built-in field (except `_time`), the event's field is prepended with `data_`. For example, `data_source`.

Autocomplete

As you type in the query box, a drop-down modal with suggestions is displayed to make query writing easier. Use the down and up keyboard keys to highlight a suggestion. Press Enter/Return or Tab to add the highlighted suggestion to your query, or select a suggestion.

Autocomplete adapts its suggestions as you type, referencing built-in fields, Dataset IDs, and the query language.




Autocomplete

The bottom section of the autocomplete modal provides a list of recent queries. When clicked, the query is added to the query box.

You can reuse query text across different searches, by using Macros.

Look Up the Query Language Docs

Operators and functions have a greater-than character > displayed on the right of the autocomplete suggestion when highlighted. When clicked, autocomplete expands to display its documentation for reference.




Viewing the docs inside Cribl Search

Preview

Preview provides a testing mode where operators can be applied to a previously run query, allowing you to quickly preview the changes without executing the search on the actual data source. You can preview operators as many times as you need, without incurring the time or cost of executing them on actual data providers until you're ready.


- Up to 100 results from the initial search are used in Preview.
- The `centralize` and `send` operators are not supported.

To open Preview, hover over an operator and select **Preview**. For non-aggregate queries, you can first select bars in the histogram to view results for only the selected times. Use shift+select to select multiple bars.



Preview button

Type the operators you'd like to test against the initial search results and press Enter/Return or select **Preview**.



Preview example

Notice the results table switches to **Out** instead of **In**, indicating the displayed results are what the operator would return.


- New data is highlighted in green.
- Modified data is highlighted in orange.
- Deleted data is highlighted in red.

Select **Apply** to have your test query added to your original query.

Time Range

Use the **timepicker** at the top right to limit your search to a specific time period. You can:

- Use Quick Actions for a relative offset or a named calendar period.
- Set a relative time range to search between a point in the past and now, or between two relative times.
- Set a date range to search between two dates.
- Search around a specific point in time.
- Change the time zone of the time range you've selected.



Timepicker

Quick Actions

When you select the timepicker, the **Quick Actions** panel opens with two columns:

- **Left column** - Calendar-boundary Quick Actions that snap to a named calendar period in the selected time zone:

    - **Today** - From the start of today to now.
    - **This week**, **This month**, **This year** - From the start of the current week, month, or year to now.
    - **Yesterday** - The full previous day.
    - **Previous week**, **Previous month**, **Previous year** - The full previous week, month, or year.
- **Right column** - Relative offset actions (for example, **10 seconds ago**, **1 hour ago**, **7 days ago**), with **All Time** at the bottom.

Selecting a Quick Action applies the range immediately and populates the **Earliest** and **Latest** fields on the **Relative** tab. Reopen the timepicker and select the **Relative** tab to inspect or fine-tune the values. For snap syntax, see SnapToTimeUnit Syntax.



Calendar-boundary snapping is time zone-aware. For example, **This week** snaps to the week boundary (Sunday) in the time zone selected under **Current Timezone** in the timepicker.

These Quick Actions are also available on Dashboard Time Range Inputs and under **Insights** > **Alerts**, on **Active Alerts** and on the Monitor preview chart. The Monitor preview chart does not include **All Time**.

If your query already contains an `earliest` or `latest` argument, the timepicker displays that range.



To copy a time range to another browser tab, hover over the timepicker and use the **Copy**/**Paste** buttons.

When setting the time range, mind that:

- Some operators, like `cribl` and `timestats`, support their own time arguments that can override the time range set in the UI. See Time Syntax for details.
- Subqueries can also use their own time arguments, but the main query time range still applies to the final results. See Subqueries and Time Ranges for details.
- Each Notebook search cell has its own timepicker.

Set a Relative Time Range

To find events between a point in the past and now, select the **Relative** tab in the timepicker and enter an **Earliest** time, with an optional **Latest** time.

To cover a completed calendar period such as **Yesterday** or **Previous month**, use Quick Actions instead of leaving **Latest** as `now`.

For scheduled searches, `now` is the **scheduled** time, not the actual execution time. For example, if you schedule a search for 1:00, but an unplanned outage causes the search to run at 1:05, the value of `now` will be 1:00, not

1:05.

Set a Date Range

To find events between a start and end date, select the **Date Range** tab in the timepicker.

Type the start and end timestamps directly into the **From** and **To** fields, or select the calendar button next to a field to pick dates from the calendar.

Search Around a Point in Time

To find events around a specific timestamp, select the **Around** tab in the timepicker. Pick a date and a duration around it.

This is useful for finding events that you know happened near a particular date, but not exactly when. For example, selecting `07-03-2023` at `10:00` with a span of `+/- 2 hours` returns events that happened from 8:00 AM to 12:00 PM.

Change the Time Zone of a Search

To set the time zone of your search, select it under **Current Timezone** in the timepicker.

The time zone selection applies to all visualizations (tables, charts, histograms), and is saved in your browser, across searches and Dashboards. Changing the time zone in either of these places updates the saved preference.

Saved searches and scheduled searches store their own time zone settings (independently of each other).

In Notebooks, each search cell has its own time zone, stored with the cell.

Sampling

Sampling uses a ratio to reduce the number of results returned from a search. For example, if a search returns 1,000 events, a 1:10 sampling ratio returns about 100 events.

Select **Sampling** to the left of the time range box to set a sampling ratio.

You can also set the sampling rate directly in a query using the `set sample_rate` option. This is useful for saved searches, scheduled searches, and shared queries, where the sampling rate travels with the query itself.

Comments

You can add comments to your query with double forward slashes `//` prepending the comment. Any characters on the same line after `//` are part of a comment. For example:

```
goats | summarize count() // count the goats
```

Copy


Autoformat Query Text

To make a complex query more organized and easier to read, you can autoformat its text.

When in the query box, press the `Ctrl` + | (Linux, Windows) or `Command` + | (MacOS) key combination.

UI Options

Select the gear button to the left of the query box to open the options menu.



Search options

- **Auto Height**: Enabled by default. Automatically adjusts the height of the query box based on the size of

6.3. Write Your First Query

Write simple queries in Kusto Query Language, using operators such as `limit`, `project`, `where`, `count`, `order`, and others.

Cribl Search is based on Kusto Query Language (KQL), which lets you delve into your data to discover patterns, identify anomalies and outliers, and create statistical models.



To generate queries from natural language, try the Cribl Copilot KQL assistant.

Example Scenario

Imagine you're a security operations analyst working for a company that relies heavily on cloud infrastructure. You want to analyze a Dataset containing virtual private cloud (VPC) flow logs for insight into network traffic patterns, potential security threats, and resource utilization in different regions.

What You'll Learn

You'll write simple queries in KQL to analyze a sample Dataset of VPC flow logs. You'll learn how to:

- Understand the structure of a Cribl Search query.
- Return a specific number of rows by using the `limit` operator.
- Extract information from the `_raw` field using the `extract` operator and Parser.
- Filter data by using the `where` operator.
- Calculate available events by using the `count` operator.

Your Learning Goals

By the end of this tutorial, you'll be able to write a query with the most commonly used operators in KQL to analyze VPC flow logs, understand network traffic patterns, and identify potential security threats within your cloud infrastructure.

The Structure of a Cribl Search Query

Organizations across various sectors process vast amounts of data and aim to extract valuable insight from it. In the VPC flow logs example, you have a Dataset with network traffic data from your organization's cloud infrastructure. This tutorial will guide you through the fundamental structure of the Kusto Query Language to analyze and interpret the Dataset.

What's a Cribl Search Query?


A Cribl Search query is a read-only request expressed in plain text that processes data and returns results in a tabular or graphical format. It consists of one or more query statements. The predominant type of query statement is a tabular expression statement.

What's a Tabular Statement?

In a tabular expression statement, both input and output consist of tables or tabular Datasets.

Tabular statements hold zero or more operators, each beginning with tabular input and yielding tabular output. Operators are connected by a pipe (|), allowing data to flow from one operator to the next for filtering or manipulation. This sequential piping of information makes the query's operator order crucial.

Think of it like a funnel, where you start with a full data table. The data is filtered, rearranged, or summarized as it passes through each operator. At the end of the funnel, you obtain a refined output.



Data filtered through a funnel


Here's an example query:

Runnable Kusto code examples include a **Run in Cribl Search** link in the top-right corner of the code block. Select it to open the query in your Cribl Search environment with the query loaded and ready to execute. You can also use the **Copy** button to copy a query and paste it into your own search.

```
dataset="cribl_internal_logs" method=*
| where response_time > 1 and method != 'PATCH'
| summarize cnt=count() by method
| where cnt > 42
```

Copy | Run in Cribl Search

This query contains a single tabular expression statement that references a Dataset called “cribl_internal_logs” and filters the data based on the method column. The data rows are filtered by the response_time column’s value and exclude rows with the method “PATCH”. The query then summarizes the count of rows for each method and filters the results to only display methods with a count greater than 42.



Results of a query with a tabular expression statement

Return a Specific Number of Rows by Using the `limit` Operator

You can use a Cribl Search query to explore Datasets and gain insights. In this scenario, you have an unfamiliar Dataset of VPC flow logs called “cribl_search_sample” that ships out of the box with Cribl Search. You want to explore what you can learn from this data.

In this task, you'll examine the structure of the data to understand the kinds of questions you can ask about these network flows.

Write Your First Query

This query returns a small subset of the data to help you familiarize yourself with the columns and types of data in the table.


The `limit` operator is perfect for this task, as it returns a specific number of arbitrary rows.

1. Copy this query to your clipboard:

   ```
   dataset="cribl_search_sample" | limit 100
   ```

   Copy | Run in Cribl Search

2. Paste the query into the search box.
   Tip: You can autoformat the query text.
3. Notice that the query begins with a reference to the data table, `cribl_search_sample`. This data is piped into the first and only operator, which then selects 100 arbitrary rows.
4. Run the query by selecting **Search** or pressing **Enter**.
5. Review the results. The sample Dataset includes various data columns such as `_raw`, `source`, `host`, `dataSource`, and `datatype`.



Results of a query using the `limit` operator

Extract Information from the `_raw` Field by Using the `extract` Operator and Parser

Notice in the previous example that the useful information in the `_raw` field is unparsed. To analyze the data effectively, you need to extract and parse the information into separate fields.

Write a Query to Parse the `_raw` Field


To parse the data, you can use the `extract` operator along with the appropriate Parser (in this case, **AWS VPC Flow Logs**).

1. Copy this query to your clipboard:

```
dataset="cribl_search_sample" | limit 1000 | extract parser='AWS VPC Flow Logs'
```

Copy | Run in Cribl Search

2. Paste the query into the search box and select **Search** or press **Enter**.
3. Check that your parsed results are similar to the following example. The actual data in the rows might differ because the rows are selected arbitrarily. The parsed results should now contain separate fields for each data point in the `_raw` field.



Results of a query using the extract operator

Now that the data is parsed and organized into separate fields, you can perform further analysis and create more advanced queries to gain insight into the VPC flow logs.

Filter Data by Using the `where` Operator

In the previous sections, you learned how to extract and parse information from the VPC flow logs Dataset. Now let's explore how to filter the data using the `where` operator to answer specific questions about the VPC flow logs.

Use the `where` Operator

All the operators you've used so far have returned selected columns. Now let's take a look at specific rows of the data.

The `where` operator filters results that satisfy a certain condition. In this first example, you'll compare an integer column to a minimum value by using the numerical operator greater-than (`>`). Specifically, you want to see only flows that have a certain number of packets. So you'll look at rows of data where the number of packets is greater than a given threshold.


Run the following query:

```
dataset="cribl_search_sample"
| extract parser='AWS VPC Flow Logs'
| where packets > 5
| project _time, srcaddr, dstaddr, packets
| take 10
```

Copy | Run in Cribl Search

The `extract parser` line is superfluous, because Cribl Search applies the parser automatically, but it's included for illustration.

Notice that all rows returned have packet values greater than 5.




Results of a query using the where operator to return values

Similarly, you can filter for flow events that have a start time that's more recent than a certain time. For example, run the following query, where `earliest=-30m` means last 30 minutes:

```
dataset="cribl_search_sample" earliest=-30m
| extract parser='AWS VPC Flow Logs'
| where packets > 5
| summarize count() by srcaddr, dstaddr
```

Copy Run in Cribl Search



Results of a query using the where operator to filter for start times


Filter by Using a String Value

Let's narrow down the flows to those that were accepted. Run the following query, which uses a second `where` operator with the string value "ACCEPT":

```
dataset="cribl_search_sample" bytes > 100 and action = "ACCEPT"
| limit 1000
```

Copy | Run in Cribl Search

Notice that all records returned from this query have the action "ACCEPT" and bytes greater than 100.



Results of a query using the where operator to filter for a string value


Filter by Using the `has` Operator

You can search for specific strings in the flow log data by using the `has` operator. The `has` operator is a case-insensitive search that matches a full term.

For example, let's filter the VPC flow logs by a specific interface ID:

```
dataset="cribl_search_sample"
| extract parser='AWS VPC Flow Logs'
| where packets > 5
| where interface_id has "eni-07e5d76940fbaa5c6"
```

Copy Run in Cribl Search



Results of a query using the has operator

Filter on Time Range Values


Let's look more closely at the flows within a specific time range. Because time ranges are bounded by two extremes, it's most efficient to limit your query to events within these two times.

To construct a date range, use `earliest` and `latest` at the top level, with the following syntax: `[+|-]#TimeUnit[@SnapToTimeUnit]`

Let's incorporate the time range into a kind of query you've already seen. Run the following query:

```
dataset="cribl_search_sample" earliest=-35m latest=-5m
| limit 1000
| extract parser='AWS VPC Flow Logs'
| where bytes > 100
```

Copy Run in Cribl Search



Results of a query filtering on a time range

In this query, you filter the events in the Dataset by a specific time range, from 35 minutes ago to 5 minutes ago, using the `earliest` and `latest` operators. You then extract and parse the data using the `AWS VPC Flow Logs` Parser. To focus on flows with more than 100 bytes and action "ACCEPT", use the `where` operator with the respective conditions.

Finally, you use the `timestats` operator to aggregate the data using a daily time span (`span=1d`) and group the results by `srcaddr`.

The query will return results that show the aggregated statistics of VPC flows with action "ACCEPT" and bytes greater than 100 for each `srcaddr`, separated by day, during the specified time period.

Calculate Available Events by Using the `count` Operator

Now that you've refined your query using helpful operators, such as the `limit` operator that returns a specified number of events, suppose you want to determine the total number of events available within a specific Dataset.

In this case, you can use the `count` operator. For example, say you want to count VPC flow events where bytes

6.4. Write Cribl Search Queries With Cribl Copilot

Use the Cribl Copilot KQL assistant to generate Kusto Query Language expressions from natural language.

The Cribl Copilot KQL assistant enables you to define search queries in natural language. The assistant translates these into Kusto Query Language (KQL). You can use all basic KQL features - including grouping, aggregating, filtering, and sorting - without having to write anything in KQL. You'll usually get results in around 5 to 30 seconds.

Additional options here are:


- Selecting from automatically suggested follow-up queries.
- Pasting KQL queries into the assistant to generate natural-language summaries of their logic.
- Pasting problematic KQL queries into the assistant, to debug syntax that's triggered errors.

  Cribl AI is available by default. To manage AI features and model providers for all Cribl products in your Organization, select **Settings** > **Global** > **AI Settings**. See Cribl AI Availability for details.

Select from Follow-Up Query Suggestions

On the **Logs** page, below the query box, a **Follow-up queries** group suggests queries that you might find useful. Suggestions draw on your most recently used query and Dataset, and on other recent search history.

To hide or show these suggestions, select the settings ⋯button beside the query box, then turn **Follow-up queries** off or on. This switch appears only when Cribl AI is available.




Cribl Copilot autocomplete options

You have multiple options to respond to these suggestions, covered in the following subsections.

Accept a Suggestion


You can select one of the three follow-up query tiles. As shown below, this will immediately execute the query, while placing it in the query box for you to refine, as desired.



Suggested query after selection

Request Explanations

You can toggle on **Explain queries** to expand all the suggested-query tiles. This will reveal details about each suggestion.



Explain queries selected

Roll Your Own

You can simply ignore the suggestions, and build your new follow-up queries in the query box. Or, use the upper query box to describe your desired search in plain (natural) language. As described in the next section, Cribl Copilot will generate a corresponding query in KQL.

Generate a Query Using Cribl Copilot

To generate a KQL query from natural language:

1. On the **Logs** page, beside the search query box, select **Build Query** . Once the query box already contains a query, this button collapses to the icon alone.
2. In the box that opens, describe what you want to find, using ordinary language.
3. Select **Generate KQL** to translate your description into KQL.
4. Edit the resulting query if you want to make it more precise, and then select **Search**.

   You can also use the Cribl Copilot chatbot to generate queries. Select the Cribl Copilot button at the bottom right of any page, and then from the left drop-down select **Generate KQL**.

   Unlike the KQL assistant, the chatbot has no access to Cribl Search, your query history, or your Datasets. So KQL generation here is limited. However, this might be a good option for organizations with strict privacy policies.

How to Use Prompts Successfully

To ensure the best results from your natural language query:

- **Be specific.** If you know the names of specific Datasets or fields, or have other constraints, include these in the prompt. Example: `Sort results by column <my_timestamp>`
- **Refine your queries.** If the generated query is not exactly what you were looking for, refine your request to improve the result.
- **Provide feedback.** Select the thumbs-up or thumbs-down button to share feedback on responses. This helps improve the accuracy and relevance of Cribl Copilot.

How the KQL Assistant Works

When you enter a natural language query using the Cribl Copilot KQL assistant, a large language model (LLM) uses information about KQL, your 10 last-used Datasets, and the query you've entered, and combines this information to generate a valid KQL query.

6.5. Common Query Examples

Learn common ways of searching data.

Runnable Kusto code examples include a **Run in Cribl Search** link in the top-right corner of the code block. Select it to open the query in your Cribl Search environment with the query loaded and ready to execute. You can also use the **Copy** button to copy a query and paste it into your own search.

Show n Rows

Let's see some data. What's in a random sample of five rows?

```
dataset="cribl_search_sample"
 | take 5
```

Copy | Run in Cribl Search

Select a Subset of Fields

Use `project` to pick out only the fields you want.

```
dataset="cribl_search_sample"
 | project method, source, status, url
```

Copy | Run in Cribl Search

Returns:

method	source	status	url
GET	file://opt/cribl/log/access.log	200	/api/v1/health
…	…	…	…

Filter by Expression

We'll use an expression to find specific field and value matches. Let's see only `GET` events in the `access.log`:

```
dataset="cribl_internal_logs" source="*/access.log" method="GET"
 | project method, source, status, url
```

Copy | Run in Cribl Search

Returns:

method	source	status	url
GET	file://opt/cribl/log/access.log	200	/api/v1/health
GET	file://opt/cribl/log/access.log	...	...

Compute Derived Fields

Create a new field by computing a value in every row:

```
dataset="cribl_search_sample"
 | limit 5
 | extend query=query()
```

Copy | Run in Cribl Search

This query uses the context function `query()`.

It's possible to reuse a column name and assign a calculation result to the same column.

Example:

```
 | extend x = x + 1, y = x
 | extend x = x + 1
```

Copy

Aggregate Groups of Rows

To count the number of events by `src` we'll use the count function.

```
dataset="cribl_search_sample"
 | limit 1000
 | summarize cnt=count() by srcaddr
```

Copy Run in Cribl Search

Returns:

src	cnt
10.255.0.248	2978
...	...

The `summarize` operator groups together rows that have the same values in the `by` clause, and then uses an aggregation function (for example, `count`) to combine each group in a single row. In this case, there's a row for each `src` and a field for the count of rows in that `src`.

You can use several aggregation functions in one `summarize` operator to produce several computed columns. For example, we could get the count of events per `src`, and the sum of unique types of events per `src`.

```
dataset="cribl_search_sample" dataSource="access*"
 | limit 1000
 | summarize eventCount=count(), useragentCount=dcount(useragent) by clientip
```

Copy Run in Cribl Search

Returns:

src	eventCount	message
10.255.0.248	5610	2
...	...	...

In the results of a `summarize` operator:

- Each field is named in the `by` clause.
- Each computed expression has a field.
- Each combination of `by` values has a row.

Search Cribl Lake

You can search Cribl Lake Datasets the same way you use regular Cribl Search Datasets:

```
dataset="my_lake_dataset"
```

Copy

See Searching Cribl Lake for more examples.

Search Arrays

In this example, `arr1` is an array of strings, and `arr2` is an array of numbers:

```
dataset="my_dataset"
arr1[0]='s1'
arr2[0]=1
| limit 1000
```

Copy

As shown here, you can reference specific elements in an array - using zero-based index notation - to retrieve only the data you specify. Your query must specify the field name or data point at each array index. (Cribl Search does not support querying on the index to discover array members.)

Where a Dataset Provider returns array columns as strings, Cribl Search parses these columns back to arrays.

Search Nested JSON Objects

In this example, `bar` is a field nested within three levels of JSON objects:

```
dataset="my_warehouse" json1.obj2.nestedObj2.nestedObj3='bar'
 | limit 1000
```

Copy

Subqueries

Subqueries allow you to generate different sets of results in a single search. This lets you perform dynamic lookups with no need to create static, stored lookup tables.

You can use subqueries to append one set of results to another, through the `union` operator. You can also use them to merge data coming from different Datasets and Dataset Providers, with the help of the `join` operator.

There are two types of subqueries:

- Inline subqueries
- `let` subqueries

Inline Subqueries

An inline subquery is nested inside another query, using round brackets `()`.

You may find inline subqueries easier to write than `let` subqueries, but:

- You can reference their results only as vectors, using `union` or `join`.
- If you opt to use the `cribl` operator, you must explicitly include it in the inline subquery.

```
// main query
dataset=$vt_dummy event<10
 | extend foo=42
 | union (
    // inline subquery
    cribl dataset=$vt_dummy event<10
     | extend bar=24
 )
```

Copy Run in Cribl Search

You could achieve the same result as above by using a `let` subquery:

```
let subquery = dataset=$vt_dummy event<10
 | extend bar=24;

dataset=$vt_dummy event<10
 | extend foo=42
 | union subquery
```

Copy Run in Cribl Search

The following example uses an inline subquery to join two different scopes of data:

```
dataset=$vt_dummy event<10
 | extend foo=42
 | join (
    // inline subquery
    cribl dataset=$vt_dummy event<10
     | extend bar=24
 ) on event;
```

Copy Run in Cribl Search

`let` Subqueries

You define `let` subqueries at the beginning of a query, using `let` statements. You can then reference them by name, like this:

```
// each let statement ends with a semicolon
let x = 1000;

dataset="cribl_search_sample"
 | limit x
```

Copy Run in Cribl Search

Depending on what a `let` subquery evaluates to, you can reference it as a vector or as a scalar.

Similarly to inline subqueries, you can use `let` subqueries with the `join` and `union` operators:

```
let subquery = dataset="$vt_dummy" event < 10
 | extend bar=24;

dataset="$vt_dummy" event < 10
 | extend foo=42
 | join subquery on event
```

Copy Run in Cribl Search

`let` subqueries can also reference one another, for example:

```
let subquery = dataset="$vt_dummy" event < 1
 | extend bar=24;

dataset="$vt_dummy" event < 10
 | extend foo=42, subqueryBar=subquery.bar
```

Copy | Run in Cribl Search

Reference a `let` Subquery as a Vector

When a `let` subquery evaluates to a vector, you can use its results to filter the results of your main query, with help of the `in`/`!in`/`in~`/`!in~` operators.

Mind that this functionality is not supported by the implicit `cribl` operator, so you need to use `search`, `find`, or `where`. For example:

```
// dummy list of blocklisted IPs
let pretendBlocklistedIps = dataset="cribl_search_sample" dataSource="vpcflowlogs"
 | limit 10
 | distinct srcaddr
 | project blocklistedIp=srcaddr;

dataset="cribl_search_sample" dataSource="vpcflowlogs"
 | where srcaddr in pretendBlocklistedIps.blocklistedIp;
```

Copy | Run in Cribl Search

If you already know the values you want to match, define them as a `dynamic(...)` array in a `let` variable and reference the variable directly in the `in` list. See Dynamic Values in `in` Operators for details.

```
let blocklistedIps = dynamic(["10.0.0.1", "10.0.0.2", "10.0.0.3"]);

dataset="cribl_search_sample" dataSource="vpcflowlogs"
 | where srcaddr in (blocklistedIps);
```

Copy

Reference a `let` Subquery as a Scalar

To reference a `let` subquery as a scalar, mind the following:

- The subquery needs to produce exactly one event.
- You must specify a field, using dot notation (`subquery1.text`). You can also reference a nested field (`subquery1.headers.test`).
- The field you specify must be a scalar value, not an object.
- You can't specify fields that don't exist.

See the following example, which calculates the 95th percentile of requests in the Cribl internal logs.

```
let num_percentile = 95;

let response_time_percentile = dataset="cribl_internal_logs" method status response_t
 | summarize total=count(), response_time=percentile(response_time, num_percentile);

let long_responses = dataset="cribl_internal_logs" method status response_time
 | where response_time > response_time_percentile.response_time
 | summarize count=count(), maxResponseTime=max(response_time);

print strcat('There are ', long_responses.count, ' requests in the ', num_percentile,
```

Copy Run in Cribl Search

Subqueries and Time Ranges

A subquery can have its own time range. However, the time range of the main query (either set in the query itself, or configured through the UI) still applies to the final results.

For example, the following search won't get you any `earlysample` results, because they're outside of the time range of the main query:

```
// subquery time range between 50 and 45 minutes ago
let earlysample = dataset="cribl_search_sample" earliest=-50m@m latest=-45m@m
 | extend stage="one"
 | limit 100;

// main query time range between 10 and 5 minutes ago
dataset="cribl_search_sample" earliest=-10m@m latest=-5m@m
 | extend stage="two"
 | limit 100
 | union earlysample
```

Copy Run in Cribl Search

To go around this, you can apply that second time range to another subquery, and then let the main query contain both time ranges:

```
let earlysample = dataset="cribl_search_sample" earliest=-50m@m latest=-45m@m
 | extend stage="one"
 | limit 100;
```

6.6. View Search Results In Cribl Search

Explore your search results across three tabs, each tailored to a different type of output.

Highlights

- Results appear on the **Events**, **Fields**, or **Chart** tab, selected automatically based on the query type.
- Use **Events** for raw results, **Fields** for field statistics, and **Chart** for visualizations.
- Override the automatic tab selection by appending `| render table` or `| render event` to your query.

Three Tabs for Different Result Types

Every search returns results on one of three tabs:

- **Events** shows raw log events, a histogram, and a field browser. Best for non-aggregated searches.
- **Fields** shows all returned fields with type, uniqueness, and presence statistics.
- **Chart** shows aggregated results as a visualization with a corresponding table. Best for queries that use `summarize`, `eventstats`, or `timestats`.

Cribl Search automatically selects the appropriate tab based on the query type. To override this, use the `render` operator.

Track Search Progress

Once a search starts running, you can see its progress next to the **Details** indicator.



Search progress

Select the double chevron « to expand the toolbar. Depending on the type and state of your search, you'll see the following details:

- Name of the search (if it's a saved search).
- **Latest run**: The timestamp of the most recent execution of that search.
  If you opened the search from **History**, this tells you how old the displayed results are.

- Total number of objects that Cribl Search has **Discovered**, successfully **Scanned**, or **Skipped** (for example, because they were in an unsupported Amazon S3 storage class).
- Number of **results** returned.
- Duration of the search.

Toolbar Warnings

Cribl Search displays a warning in the results toolbar when something has affected the completeness of your results. The following conditions produce a warning:


- **Usage Group Results limit reached**: The search returned more events than the **Results limit** configured on the applicable Usage Group. To reduce the number of results returned, see Optimize Searches. To raise the limit, ask your Cribl Search administrator to update the **Results limit** for your Usage Group.
- **Datatype compatibility**: Some nodes were unable to process datatypes.

Events Tab

The **Events** tab displays a table with the raw log events returned from the search, along with a histogram, and the field browser.




To display results in the **Events** tab regardless of the search's type, append your query with `| render event`.



Events tab

Select any of the rows to open the event details panel, which displays the fields of the selected event.



Event details panel

Now, you can navigate between events using your keyboard's **Up** and **Down** arrow keys.

In the panel, you can:

- Filter the fields displayed. Type into the search bar at the top right.
- View the fields in JSON format. Select **JSON** at the top.
- View the `_raw` field, which contains the original event data. Select **_raw** at the top.
- Look up events outside of the time frame of the current search. Use the **Lookaround** at the top.
- Copy the event's JSON to the system clipboard. Select the copy icon at the top.
- Pin the panel open. Select the pin at the top right.

You can also quickly incorporate any of the fields into your next search. Select a field to see these options:


- **Add field in search**: Include this field name and value in the current query. If your query already includes this field, you'll see the **Remove field from search** option.
- **Exclude field from search**: Exclude this field value in the query (for example, `action!="ACCEPT"`).
- **New search with field**: Open another Cribl Search window, and include this field name and value in the new query.
- **Copy value to clipboard**: Copy the value of this field to the system clipboard.

To close the panel, click anywhere outside of it, or select **X** at the top right.

Change the Event View Options

When viewing the **Events** tab, you can change how the results are displayed.

Select the gear button in the heading row (to the left of **Time**).




Event view options

Here, you can:

- Toggle **Event details panel** off to disable it. You'll now be able to view fields directly in the table, by selecting > at the left of an event row.
- Toggle **Display** to view the original **Event**s, or a **Table** with only the returned fields.
  (The **Table** option allows you to adjust the order of columns displayed. Select and drag a column to the desired location.)
- Toggle **Line numbers** on or off to display or hide line numbers.
- Toggle **Wrap cells** on to prevent values from overflowing.


Events Shortcuts

In Events view, you can hover over field names in the sidebar to display an **Add field to column** button. Select these buttons to quickly build a custom Table view, showing only the fields that interest you.



Add columns

In Table view, you can hover over field names in the sidebar or heading row to display a close box. Select the **x** to remove their columns from the table.




Remove columns

Columns that you hide using these shortcuts are not permanently hidden. They will reappear when you refresh the page or reload this search.

Histogram

You can select bars in the histogram to view results for only the selected times. Use shift+select to select multiple bars.



Histogram bar selection

Approximate Versus Precise Events Counts


In the **Events** field browser's left column, and on the Fields tab, both covered below: The displayed event counts are approximations, and are not expected to be exact. Top-*N* lists are generated using probabilistic analysis, and are similarly not exact. However, you can compute precise results for a given field using a query of this form:

```
dataset=<DatasetName> | summarize count() by <fieldName>
```

Copy

Field Browser

The field browser on the **Events** tab allows you to easily identify information about the fields returned from your search. Use the search bar to filter the returned fields. The browser gives you the data type, the unique count of values the field has, and the percentage of log events returned with the field.



Event field browser

The options in the **Quick Searches** panel automatically generate and run a new search:

Quick Search	Query Example
New search with field	`response_time="*"`
New search without field	`response_time!="*"`
Add field to search	`dataset="cribl_search_sample" response_time="*" | limit 1000`
Exclude field from search	`dataset="cribl_search_sample" response_time!="*" | limit 1000`
Top 10 values	`dataset="cribl_search_sample" | limit 1000 | top-hitters 10 of response_time`


Quick Search	Query Example
Distinct values over time	`dataset="cribl_search_sample" | limit 1000 | timestats dcount(response_time)`
Min over time	`dataset="cribl_search_sample" | limit 1000 | timestats min(response_time)`
Max over time	`dataset="cribl_search_sample" | limit 1000 | timestats max(response_time)`
Avg over time	`dataset="cribl_search_sample" | limit 1000 | timestats avg(response_time)`
Stdev over time	`dataset="cribl_search_sample" | limit 1000 | timestats stdev(response_time)`

See the Fields tab for a table of all of the returned fields.

Lookaround

Lookaround allows you to filter search results by adding or subtracting seconds, minutes, hours, or days, enabling quick exploration of surrounding events.

Select an event's `Time` field or expand a row and select **+/- Lookaround** to view the modal.



Lookaround UI

Export Results as NDJSON


To download your results as NDJSON, or to send or export them to Cribl Lake, Cribl Stream, or another destination, see Export Search Results.

Fields Tab

The **Fields** tab displays all of the returned fields on a table by the following dimensions:

- **Type**: Data type.

- **Uniques**: Number of unique values.
- **Nulls**: Number of `null` values.
- **Top Value Distribution**: How often values occur using the standard cumulative beta distribution function.
- **Presence**: Percentage of results that contain the field.



Fields tab

The table supports sorting and filtering, and allows you to adjust the order of columns.

- Select a column heading to change its sorting order.
- Hover over a column heading and select the funnel icon to define a filter.
- Select the triangle to the left of a **Field name** to expand and collapse the list of returned values.




See the note above about Approximate Versus Precise Events Counts.

Chart Tab

When you run the `summarize`, `eventstats`, or `timestats` operator along with an aggregation function, the **Chart** tab automatically displays your results in a Chart, along with a corresponding results table. You can select from various Chart types and color palettes, manipulate how your results are plotted, and customize the results table display.



To display results in the **Chart** tab regardless of the search's type, append your query with `| render table`.



Aggregate results area on a Bar Chart

For detailed information about manipulating data and visualizations in aggregate search results, see Charts.

Display Multiple Series

Use multiple values in a `summarize by` clause to create a separate row for each combination of values:

```
dataset="cribl_search_sample" dataSource="access_combined"
 | limit 1000
 | summarize count() by host, clientip
```

Copy | Run in Cribl Search

Display a Time Series

The `timestats` operator aggregates events by time periods or bins, which is excellent for displaying a time series. Here we slice the results into one-minute sections, or bins:

```
dataset="cribl_search_sample"
 | limit 1000
 | timestats span=1m
```

Copy Run in Cribl Search

Display Results as Events or Tables

Use the `render` operator to display results as a list of events or a table.

To display results as a list of events under the **Events** tab:

```
dataset=$vt_dummy event<100
 | extend parity=iif(event%2==0, 'even', 'odd')
 | project event, parity
 | render table
```

Copy Run in Cribl Search

To display results as a table under the **Chart** tab:

```
dataset=$vt_dummy event<100
 | extend parity=iif(event%2==0, 'even', 'odd')
```

6.7. Export Cribl Search Results

Get the results of a query out of Cribl Search, so you can reuse them elsewhere.

Highlights

- Download results as CSV or NDJSON.
- Use the `export` operator to write results to Cribl Lake, a Search Dataset, a metrics Dataset, or a lookup.
- Use the `send` operator to forward results to Cribl Stream or any endpoint that accepts NDJSON over HTTP.

Cribl Search Export Methods

Pick a method based on where the results need to go and how much data you're moving.

Method	Best for	Destination
Download results	Quick, ad-hoc pulls from the UI	Your local machine
Export to a Search Dataset	Keeping results in an accelerated lakehouse engine	A Search Dataset
Export to metrics	Precomputing log aggregates as metrics for faster reads	An auto-provisioned metrics Dataset (`metrics` or `metrics_<engine_id>`)
Export to a lookup	Reusing results as a lookup table in later searches	A lookup
Export to Cribl Lake	Long-term, searchable storage in open formats	A Lake Dataset
Send to Cribl Stream	Routing results to any destination Cribl Stream can reach	A Worker Group, then onward
Send to a custom URL	Posting NDJSON results directly to an HTTP endpoint	Any compatible endpoint

These methods cover everyday exports of reasonable data volumes. For a large-scale data migration, contact your Cribl account team.

Download Search Results

You can download the results of any search as a CSV or NDJSON file.

1. Run a search.
2. At the bottom right of the query box, select **Actions**.
3. Select **Export**, then either **Export Results as CSV** or **Export Results as NDJSON**.

Notebooks let you download the result sets of individual cells. See Export Notebook Search Results.

Export to Search Datasets

Use the `export` operator with the `search` keyword to write results to an existing Search Dataset hosted on a Cribl-managed lakehouse engine. Remember that you need to create the Search Dataset first.

```
dataset="cribl_search_sample"
| export to search mySearchDataset
```

Copy

For the full syntax and requirements, see Export to a Cribl Search Dataset.

Export to Metrics

Preview Feature

Cribl is still developing this Preview feature. We don't recommend using it in a production environment, because the feature might not be fully tested or optimized for performance, and related documentation could be incomplete.

Please continue to submit feedback through normal Cribl support channels, but assistance might be limited while the feature remains in Preview.

Use the `export` operator with the `metrics` keyword to store aggregated search results as metrics. This is how you turn summarized logs into metrics in Cribl Search, so later queries and dashboards can read metrics instead of re-scanning raw events.

```
dataset="my_logs"
| where status >= 500
| summarize value=count() by _time=bin(_time, 1m), service, status
| extend name="http_errors_total", type="counter"
| export to metrics
    timeField=_time
    nameField=name
    valueField=value
    typeField=type
    labelFields=[service, status]
```

Copy

Keep the following in mind:

- Summarize first, then export. This is a Search query path (ad hoc or scheduled), not a continuous stream transform.
- Defaults write to the `metrics` Dataset and look for fields named `name`, `value`, and `type`. To target another lakehouse engine, export to that engine's auto-provisioned Dataset (`metrics_<engine_id>`).
- Set counters and gauges with `typeField`. Use `type=histogram` on `export` for histograms.
- If you aggregate with `bin`, assign the result back to `_time` (for example `_time=bin(_time, 1m)`) so the column name stays `_time`. If you omit `timeField`, export uses `_time` when present, otherwise it generates a timestamp with `now()`. If you set `timeField` and that timestamp is missing or invalid, export drops the data. Supported timestamp inputs include epoch seconds through nanoseconds, ISO-style and Search-style datetime strings, JavaScript `Date` values, and structured timestamp objects.
- Leave `tee` at the default (`false`) and check the export statistics: events sent should be greater than zero, and events dropped should be zero. That means the events were shaped correctly.
- Export to metrics requires metrics export permission, or Maintainer access on the target metrics Dataset.

For full syntax, metric types, and more examples, see Export to a metrics Dataset.

Export to a Lookup

Use the `export` operator with the `lookup` keyword to save results as a lookup table, so you can reuse them to enrich later searches.

```
dataset="cribl_search_sample"
| export to lookup myLookup
```

Copy

Keep the following in mind:

- Only Search **Admins** and **Editors** can run the `export` operator.
- `export` writes at most 10,000 rows to a lookup. It drops any events beyond that, and raising `maxEvents` doesn't lift the cap.
- The default `create` mode fails if the lookup already exists. Use `overwrite` or `append` mode to update one.
- You can't create or update Pack lookups with `export`.

For the full syntax, modes, and arguments, see Export to a lookup.

Export to Cribl Lake

Use the `export` operator to write search results to an existing Cribl Lake Dataset for long-term, searchable storage in an open format.

```
dataset="cribl_search_sample"
| export to lake myDataset
```

Copy

Keep the following in mind:

- Only Search **Admins** and **Editors** can run the `export` operator.
- You need to create the Lake Dataset before you export to it.
- The Dataset's format (JSON, Parquet, or DDSS) is set on the Dataset, not by your search.
- Exports to Lake include the `_raw` field. To drop it, append `project-away _raw`.
- Cribl Lake handles `_time` automatically. If an event has no `_time`, Lake sets it at write time.

For the full syntax, arguments, and more examples, see the `export` operator reference.

Send to Cribl Stream

Use the `send` operator to forward search results to Cribl Stream, where you can transform, route, and relay them to any destination Stream supports.

```
dataset="cribl_search_sample"
| send
```

Copy

By default, `send` forwards results to the Cribl HTTP Source on the `default` Worker Group in the same Workspace, with no extra ingest charges. Search **Editors** and **Admins** can also send to a named Worker Group.

For the full syntax, permissions, and more examples, see the `send` operator reference.

Send to a Custom URL

Search **Admins** (or higher) can use the `send` operator with a URL argument to send results directly to any endpoint that accepts a POST request with NDJSON content.

```
dataset="cribl_search_sample"
| send "https://example.com/events"
```

Copy

Keep the following in mind:

- The `send` operator sets the `Content-Type: application/x-ndjson` header.
- You can't use a custom URL together with the `group` argument. Ingest charges might apply when you send outside the Cribl HTTP scenario described in Send to Cribl Stream.
- Ingest charges might apply when you send outside the Cribl HTTP scenario described in Send to Cribl Stream.

6.8. Save Searches In Cribl Search

Keep queries you want to reuse, schedule, or share so you don't have to rebuild them from scratch.

Highlights

- To save your current search, select **Actions** > **Save Search**.
- Schedule a saved search to send Notifications on its results.
- Share saved searches through Packs.

Save Searches to Reuse, Schedule, and Share

Save a search to preserve its query text, sampling ratio, time range, and time zone.

Saving searches lets you quickly rerun frequently used queries, schedule a search to run at regular intervals, and send Notifications on results. You can also share proven searches with your team through Packs.

Save a Search

1. Run a search, or open a past search from **History**.
2. At the bottom right of the query box, select **Actions** > **Save Search**.
3. Name and describe your search. You can also adjust the query text, sampling ratio, time range, and time zone.
4. To share the search results with others, set the **Results Access** to **All Members**.
5. To run the search at regular intervals, select **Schedule**. See Scheduled Searches for details.
6. To get alerted on the scheduled search results, select **Notifications**. See Notifications for details.
7. Select **Save**.

Your search now appears in **Saved Searches**.

View Saved Searches

From the Cribl.Cloud top bar, select **Products** > **Search** > **Saved Searches**.

On the **Saved Searches** page:

- Select the column selector to show or hide columns.
- Select **Actions** ··· to clone a search, add it to a Dashboard or Notebook, or move it to a Pack.

- Filter for **Scheduled** searches at the top right.
- Select **Add Search** to save a new search.
- Select check boxes to mark searches for deletion.

Changing Saved Search Ownership

If the creator of a saved search is no longer an active Cribl Search Member, Search Admins with access to the search can continue to run it ad hoc. (They will now appear as the user requesting the search.) However, they will be unable to schedule the search. The Admin will need to copy the search's details, and to then re-create, save, and schedule the search under their ownership.

6.9. Example Searches By Provider

See specific examples of searching data from different Dataset Providers.

Examples by Provider

For examples of searching data from a specific Dataset Provider, see:

- Searching Cribl Edge
- Searching Cribl Lake
- Searching Amazon S3
- Searching AWS API
- Searching Okta API
- Searching Zoom API

For more Dataset Providers, see the List of Supported Data Sources.

Search Multiple Providers

You can query data from multiple Dataset Providers at once. For an example, see: Searching Multiple Providers.

6.9.1. Searching Cribl Lake

Learn how to search your Cribl Lake data.

This page provides example searches that you can run with Cribl Lake and Lakehouses.

Setting Up

To begin integrating Cribl Search with these data lakes, first see Connect to Cribl Lake.

Certain operators, functions, and data types behave differently when you search Cribl Lake Datasets with (versus without) Lakehouse caching. To avoid unexpected search results, see Lakehouse Search Differences.

Examples


Use these examples as starting points for your own searches.

Basic Search

This search specifies a Dataset (`test_dataset`) and limits the number of results.

```
dataset="test_dataset"
| limit 100
```

Copy




Sample Cribl Lake Search

Lake Partition

This search uses a Lake partition named `sourcetype` that is configured for the `partitioned` Dataset to speed up retrieval:

```
dataset="partitioned" host="cribl-stream"
```

Copy



Sample Cribl Lake Search: Using partitions

Exported Data

The `export` operator lets you export search results to a Cribl Lake Dataset. You can later search this Dataset to extract relevant data from it.

An efficient way to search exported data is to provide the search job ID to the `where` operator:

```
dataset="exported_data"
| where source contains "1713177481843.9AOqxI"
```

Copy

You can find the search job ID in search details after running it, or in History, in the **Search ID** column.

You can also label exported events using the `extend` operator and then include the added fields in your search. For example, during export you can include the user that performed the search:

```
dataset="cribl_search_sample"
| extend user = user()
| export to lake exported_data
```

Copy | Run in Cribl Search

You can then search for data by this user:

```
dataset="exported_data"
| where user == "John Doe"
```

Copy

6.9.2. Searching Cribl Edge

Learn how to search your Cribl Edge data.

Cribl Search comes with several Cribl Edge Datasets allowing you to quickly search Cribl Edge's internal logs and metrics that provide comprehensive information about an instance's status/health, inputs, outputs, Pipelines, Routes, Functions, and traffic. You can edit these built-in Datasets or create new ones to specify other logs anywhere in the filesystem that Edge can read.

Don't have a Cribl Edge Node? See the setup guide for Cribl Edge.

This document provides examples of searching Edge logs and metrics. To start, go to the **Logs** page, where log searches are run.



Searches over Cribl Edge execute in real time, at rest, directly on Edge Nodes. Broad or expensive queries can impact CPU and I/O on your nodes, especially over large time ranges. To minimize impact, see Best Practices for Searching Cribl Edge.

Best Practices for Searching Cribl Edge

- **Scope by Fleet**: Use the built-in `cribl_fleet` field to target a specific Fleet (for example, `cribl_fleet=MyFleet`). If you omit this filter, your query will run across all Edge Nodes in the system, which includes all configured Fleets.
- **Keep timeframes tight**: Start with the narrowest time range that can answer your question, then expand only as needed.
- **Avoid excessive wildcards**: Prefer specific field filters and paths over broad wildcard matches, especially in early query stages.
- **Validate your scope first**: Use **Explore** > **Files** in Fleet to confirm you are targeting the right locations before running large searches. For details, see Explore Cribl Edge.

Examples

Load Average

Imagine you are conducting an investigation and you need to determine which Edge Nodes have a higher-than-usual load average.

Let's go to the Dataset called `cribl_edge_metrics` and tell the search to return all the events that have the `node_load` term in them. And then let's ask it to build a time series of the load average of one minute (the default span) and split it by host:

```
dataset="cribl_edge_metrics" node_load*
| limit 1000
| timestats load1=max(node_load1) by host
```


Copy | Run in Cribl Search



Load average by host

We haven't collected this data in advance, we haven't moved it or pre-processed or ETL it in any way. The search is executed in real-time, at rest, directly on the edge.

Let's change the charting option to **Area** to improve visibility:



Area Chart of the load average by host


Cribl Search comes with rich charting options out of the box, allowing you to adjust Charts as needed.

System Logs

Now, let's check the `/var/log` directories containing the system logs of all Edge Nodes in the Fleet. We will query the built-in `cribl_edge_system_logs` Dataset and tell the search to get all the files that match `*auth.log` and have the terms `sshd` and `users`. We also set a limit of 1,000 results to return:

```
dataset="cribl_edge_system_logs" source=*auth.log sshd user
| limit 1000
```

Copy | Run in Cribl Search



System logs search

Cribl Search understands that these events are coming from Cribl Edge, and we can select the link and teleport directly to that Edge Node and see that file.



Open in Cribl Edge

Search Just a Single Fleet

You can easily filter Cribl Edge search results to a specific Fleet, using the built-in field `cribl_fleet`.

For example, the following query searches the `cribl_edge_system_logs` Dataset for events that:

- Match `*auth.log`.
- Contain the terms `sshd` and `users`.
- Come from a Fleet called `VermontGoatFarm`.

```
dataset="cribl_edge_system_logs" source=*auth.log sshd user cribl_fleet=VermontGoatFa
| limit 1000
```

Copy Run in Cribl Search

6.9.3. Built-In Cribl Edge Datasets

Learn about built-in Cribl Edge Datasets available in Cribl Search.

Cribl Search ships with built-in Cribl Edge Datasets so you can quickly search internal logs and metrics for your Edge Nodes. Using these Datasets, you can find comprehensive information about an instance's status/health, inputs, outputs, Pipelines, Routes, Functions, and traffic. You can edit these built-in Datasets, or create new ones to specify other logs anywhere in the filesystem that Edge can read.

Cribl Edge comes out-of-the-box with these Datasets:

- `cribl_edge_logs`
- `cribl_edge_state`
- `cribl_edge_metrics`
- `cribl_edge_system_logs`
- `cribl_edge_spool`

Details of Built-In Cribl Edge Datasets

Below are the type of data each Dataset returns, along with some event samples:

Dataset Name	Type of Data	Event Sample

`cribl_edge_logs`	Cribl Edge provides API server logs, Edge Node process(es), and Fleet logs. For details, see Types of Logs and Internal Logs.	{
		"dataset": "cribl_edge_logs",
		"source": "file:///opt/cribl/log/cribl.log",
		"host": "1e7a817de3be",
		"_raw": "{\"time\":\"2023-04-19T10:19:15.559Z\"
		"time": "2023-04-19T10:19:15.559Z",
		"cid": "api",
		"channel": "MetricsStore",
		"level": "info",
		"message": "active metrics",
		"numMetrics": 37,
		"_time": 1681899555.559,
		"datatype": "cribl_json",
		"cribl_taskId": "1681903132338.sOY7mn",
		"cribl_guid": "a315e568-cecb-45de-a53e-2075dbb
		"cribl_fleet": "default_fleet"
		}

`cribl_edge_state`	System state provides a snapshot of the host system's current state, including details on host info, groups, and users. For details, see System State.	{
		"dataset": "cribl_edge_state",
		"source": "file:///opt/cribl/state/system_state
		"host": "1e7a817de3be",
		"state_source": "userGroup",
		"_raw": "{\"_time\":1681902601.362,\"host\":\"1
		"_time": 1681902601.362,
		"name": "root",
		"groupId": 0,
		"users": ["root"],
		"datatype": "cribl_json",
		"cribl_taskId": "1681902737896.8EOlpP",
		"cribl_guid": "a315e568-cecb-45de-a53e-2075dbb
		"cribl_fleet": "default_fleet"
		}

Dataset Name	Type of Data	Event Sample

cribl_edge_metrics	Cribl Edge collects metrics from the host on which it is running, and can populate some standard metrics Dashboards right out of the box. For details, see Linux System Metrics Details.	{
		"dataset": "cribl_edge_metrics",
		"source": "file:///opt/cribl/state/system_metri
		"host": "1e7a817de3be",
		"metrics_source": "system",
		"_raw": "{\"_time\":1681902001.56,\"host\":\"1e
		"_time": 1681902001,
		"nodename": "1e7a817de3be",
		"release": "5.10.104-linuxkit",
		"sysname": "Linux",
		"version": "#1 SMP PREEMPT Thu Mar 17 17:05:54
		"node_uname_info": 1,
		"node_cpu_count": 5,
		"datatype": "cribl_json",
		"cribl_taskId": "1681902797516.BskPaQ",
		"cribl_guid": "a315e568-cecb-45de-a53e-2075dbb
		"cribl_fleet": "default_fleet"
		}

	Search through Linux host's	{ "dataset": "cribl_edge_system_logs", "source": "file:///var/log/bootstrap.log", "host": "1e7a817de3be", "_raw": "gpgv: Signature made Thu Apr 23 17:34 "_time": 1587663257,

6.9.4. Searching Amazon S3

Learn how to search your Amazon S3 data.

Cribl Search supports searching Amazon S3 buckets. You need a Dataset Provider and a Dataset, see the setup guide for Amazon S3 and Data Lake Amazon S3 for details.

This document provides examples of searching objects from Amazon S3. To start, go to the **Logs** page, where log searches are run.

Examples


The following examples reference a built-in Dataset with the **ID** `cribl_search_sample`.

Basic Search

This search specifies the Dataset and limits the number of results.

```
dataset="cribl_search_sample" source=*vpc*
| limit 100
```

Copy | Run in Cribl Search



Basic search


Built-in Parser

Cribl Search comes with parsing libraries so you don't have to write them manually. Use the `extract` operator to reference the built-in Parser for VPC Flow Logs.

```
dataset="cribl_search_sample" source=*vpc*
| limit 100
| extract parser='AWS VPC Flow Logs'
```

Copy | Run in Cribl Search

Note the additional fields shown in the field browser.



Parser search

If you want to see the built-in parser's effects, first run the `extract` command below. Then add the `extract` command:

```
dataset="$vt_dummy"
 | extend _raw = "2 602320997947 eni-5nxjlyb0xm0o96kgs 52.216.176.35 10.0.0.138 1311

// Run the above portion first to see the logs unparsed. Add the extract operator bel
 | extract parser='AWS VPC Flow Logs'
```


Copy | Run in Cribl Search

Aggregate

To aggregate, we'll use the `summarize` operator with the count function grouping by IP address pairs.

```
dataset="cribl_search_sample" source=*vpc*
| limit 1000
| extract parser='AWS VPC Flow Logs'
| summarize flowcount=count() by srcaddr, dstaddr
| sort by flowcount desc
```

Copy Run in Cribl Search



srcaddr	dstaddr	flowcount
217.12.208.8	10.0.0.138	517
10.0.0.138	52.216.176.35	28
52.216.176.35	10.0.0.138	28
10.0.0.164	10.0.0.89	21
54.239.152.25	10.0.0.164	21
10.0.0.89	10.0.0.164	21
162.142.125.94	10.0.0.164	21
159.203.36.225	10.0.0.138	20
10.0.0.89	10.0.0.236	20
209.141.51.176	10.0.0.138	19

Aggregating search

Aggregate over time


To aggregate over time, we'll use the `timestats` operator.

```
dataset="cribl_search_sample" source=*vpc*
| limit 1000
| extract parser='AWS VPC Flow Logs'
| timestats span=1h bytessum=sum(bytes)
| extend mb=bytessum/1024/1024
| project-away bytessum
```

Copy Run in Cribl Search

```
dataset="cribl_search_sample" source=*vpc*
| extract parser='AWS VPC Flow Logs'
| timestats span=1h bytessum=sum(bytes)
| extend mb=bytessum/1024/1024
| project-away bytessum
```

Events Fields Chart 25 results (24.37s) Status Save



_time	mb
2023-01-17 16:00:00	2777.6375551223755
2023-01-17 17:00:00	6037.800354003906
2023-01-17 18:00:00	6031.67071056366
2023-01-17 19:00:00	6042.601657867432
2023-01-17 20:00:00	6031.857895851135
2023-01-17 21:00:00	6038.328373908997
2023-01-17 22:00:00	6030.359065055847
2023-01-17 23:00:00	6047.208559036255
2023-01-18 00:00:00	6034.020042419434

6.9.5. Searching AWS API

Learn how to search your AWS data.

Cribl Search supports searching AWS API endpoints. You need a Dataset Provider and a Dataset, see the setup guide for AWS API for details.

This document provides examples of searching endpoints from the AWS API. To start, go to the **Logs** page, where log searches are run.

Account and Endpoint Identifiers

When you search the AWS API, events in the results will contain `accountName` and `endpointName` fields, which reflect the account and endpoint configured on the Dataset.

If your Dataset has multiple accounts and/or endpoints enabled, these fields distinguish each event's source. They also serve as potential filters that you can express in predicates, as you'll see in examples below.

Examples


The following examples reference a Dataset with the **ID** `aws_dataset1_a`.

EC2 Security Groups API Search

This search interrogates the `ec1_security_groups` endpoint for number of Security Groups that allow inbound to port `22` from `0.0.0.0/0`, grouped by `VPCID`?

```
dataset="aws_dataset1_a" endpointName="ec2_security_groups" IpPermissions[0].ToPort=2
| summarize Groups= count(GroupName), GroupsIds=count(GroupId) by VpcId
```

Copy




Sample AWS Search: EC2 Security Groups

EC2 Instances API Search

This search hits the `ec2_instances` API endpoints to find out top 5 most commonly used Amazon Machine Images (AMIs) and summarizes the results by `ImageId`.

```
dataset="aws_dataset1_a" endpointName="ec2_instances"
| summarize count () by ImageId
| where count >= 5
| order by count_desc
```

Copy



6.9.6. Searching Okta API

Learn how to search Okta API endpoints.

Cribl Search supports searching Okta API endpoints. You need a Dataset Provider and a Dataset, see the setup guide for Okta API for details.

This document provides examples of searching endpoints from the Okta API. To start, go to the **Logs** page, where log searches are run.

Examples


The following examples reference a Dataset with the **ID** `okta_dataset`.

Users API Search

This search interrogates the `users` endpoint for active and expired passwords.

```
dataset="okta_dataset" endpointName="users"
| summarize count () by status
```

Copy




Sample Okta Search: User status

Groups API Search

This search hits the `groups` API endpoints and summarizes the results by type.

```
dataset="okta_dataset" endpointName="groups"
| summarize count () by type
```

Copy



Sample Okta Search: Groups by Type

Cribl Search comes with rich charting options out of the box, allowing you to adjust Charts as needed.

6.9.7. Searching Zoom API

Learn how to search Zoom API endpoints.

Cribl Search supports searching Zoom API endpoints. You need a Dataset Provider and a Dataset, see the setup guide for Zoom API for details.

This document provides examples of searching endpoints from the Zoom API. To start, go to the **Logs** page, where log searches are run.

Examples


The following examples reference a Dataset with the **ID** `myzoom`.

User API Search

This search specifies the Dataset and aggregates the results by timezone.

```
dataset="myzoom" endpointName="users"
| summarize count () by timezone
```

Copy




Sample Zoom Search: Aggregate by Timezone

Meeting API Search

This search hits the `pastMeetings` API endpoints and summarizes the results by topic.

```
dataset="zoom_cribl1" endpointName="pastMeetings"
| summarize count () by topic
| order by count_desc
```

Copy



Sample Zoom Search: Past Meetings by Topic

Cribl Search comes with rich charting options out of the box, allowing you to adjust Charts as needed.

6.9.8. Searching Multiple Providers

Set up and search multiple Dataset Providers.

Cribl Search supports searching across multiple providers. In this example, we will illustrate how to configure and search logs across all three major object stores (Amazon S3, Azure Blob, and Google Cloud Storage).

Why would you want to search multiple providers, you might ask? Here are a few reasons:

- Investigate the same data across multiple providers more quickly (for example, by flowing logs across all three main providers).
- Ensure conformance across all object stores - Eventually you're going to have to search data across multiple object stores; to make sure they all follow the same standard, use Cribl Search to run conformance-based searches.
- Give users access to the data - Analytics systems can be expensive. What if those infrequent or ad hoc users could access your data through Cribl Search without incurring additional downstream licensing or cloud egress costs?
- Analyze historical data before replaying to your analysis system - We often need to review historical data for investigations, capacity exercises, or other reasons. Instead of replaying or rehydrating all the data for a given time, Cribl Search allows you to find the relevant data PRIOR to rehydrating.
- And more!

So now that you know searching across multiple providers can be useful, let's connect your object stores and start searching.

Connecting the Providers

This example searches Virtual Private Cloud (VPC) flow logs stored in Amazon S3, Azure Blob, and Google Cloud Storage.

Configuring and Routing VPC Flow Logs

VPC flow logs enable you to capture information about the IP traffic going to and from network interfaces in your VPC. For details on how you can configure the flow logs to be routed to each provider's storage object, see:

- Amazon S3: Publish flow logs to Amazon S3
- Azure Blob: Create a flow log and traffic analytics workspace
- Google Cloud Storage: Route logs with the Log Router

To process your VPC flow logs faster, use the **AWS VPC Flow Log** event breaker.

Configuring Cribl Search Data Providers

Once you have flow logs available in the respective object stores, you can set up data providers in Cribl Search to access the logs.

To give all three Datasets a uniform naming convention, append each Dataset **ID** with `_flowlogs`. This option allows us to use a wildcard in the query. For details, see the section below on Running a Search Across Multiple Dataset Providers.

Additionally, you can combine data from different Datasets in a single query by specifying each Dataset's ID. For example: `dataset=myAWSFlowlogs or dataset=myGCSFlowlogs or dataset=myAzureFlowlogs`. For details, see Syntax.

Amazon S3

Let's get started by setting up your Amazon S3 Dataset Provider and Dataset in Cribl Search.

Google Cloud Storage (GCS)

In Cribl Search, create a Google Cloud Storage Dataset Provider and Dataset.

Azure Blob

In Cribl Search, create an Azure Blob Dataset Provider and Dataset.


Running a Search Across Multiple Dataset Providers

We now have all three providers configured within Cribl Search. It's time to run some searches.

Since we appended the Dataset IDs with `_flowlogs`, this allows us to run the first search and combine data from all three Datasets:

```
dataset="*_flowlogs"
| limit 1000
```

Copy




Combined data across Datasets

We can see all three Datasets from GCS, Azure Blob, and Amazon S3 returning results here. With Cribl Search, you can easily gather all your flow logs from your multi-cloud environments for analysis.

Let's take that search and turn it into a Bar Chart with counts of each Dataset's flow log. Flow log volumes can be visualized for each provider to identify anomalies.

```
dataset="*_flowlogs"
| summarize flowcount=count() by Dataset
```

Copy




Flow logs count across Datasets

It's likely that the three providers will also share fields. They are, however, not normalized. For our Amazon S3 flow logs, we already have a `dstport`; however, Azure organizes flow logs into `tuples` from which we must extract the destination port.

As part of the next search, we try to accomplish just that, and then go one step further by using the coalesce function to create a normalized field, `Destination_Port`, across our Azure and Amazon S3 flows. It's also possible to create Datatypes with normalized fields for each Dataset. For details, see v1 Datatypes. Now that we've normalized fields, we can analyze data across all three providers agnostically.

```
dataset="*_flowlogs"
| limit 1000
| extract type=regex regex=@"\d+,([^,]*,){3}(?<dst_port>\d+)"
| extend Destination_Port= coalesce(dst_port, dstport)
```

Copy



Flow logs across all providers

Conclusion

Multi-cloud environments and object stores continue to grow in popularity, and Cribl Search allows you to bring

7. Investigate

You can explore events, identify patterns, and document results directly within Cribl Search.

Cribl Search investigations (Preview)

Cribl Search investigations (a Preview feature) is a guided workspace where you can explore incidents and telemetry data using natural-language prompts. It helps you move from vague questions or active incidents to structured findings, while tracking the steps, queries, and summaries generated during the session.

What you can do:

- **Start from scratch**: Begin with a specific incident or a described scenario and let Cribl Search identify relevant Datasets and generate initial queries.
- **Explore**: Ask questions in plain language. Cribl Search translates them to KQL, runs searches, and displays the query, results, and a short summary. For example: "Why are transactions slow?", "Show failed login attempts from unusual locations.", "What changed before this outage?"
- **Refine**: Respond to Cribl Search's suggested follow-up questions or ask your own to deepen the investigation. Cribl Search updates the underlying query while preserving context. In Deep Investigation Mode, you can select from a list of AI-generated hypotheses and have Cribl Search validate each one sequentially.
- **Enrich**: Pull in related information from external systems such as Jira, Bitbucket, or Slack (when configured). Use the Generic HTTP API to connect Cribl Search investigations to external context, or configure MCP Integrations to make external MCP server tools available to Cribl AI agents.
- **Capture**: From the investigation summary, select **Save to Notebook** to create a Notebook that preserves queries, results, and summaries as a shareable artifact. Your session is also saved automatically and accessible later from **Copilot Sessions** in the toolbar.

Investigations reduce the time and effort required to move from a question to actionable findings by:

- Generating KQL queries from natural-language prompts.
- Identifying relevant Datasets and key fields automatically.
- Running initial searches to establish context.
- Suggesting logical next steps based on results.
- Reducing repetitive tasks such as adjusting time ranges, switching Datasets, or rewriting similar queries.

By automating common investigative steps and maintaining context throughout the session, Cribl Search lets analysts focus on interpreting results rather than building and rebuilding queries.

Notebooks

A Notebook is a document-like workspace in Cribl Search where you and other data analysts can combine search queries, data visualizations, and Markdown notes into persistent, shareable investigations.

You can start an investigation from a Notebook, or convert a Cribl Search investigation into a Notebook to preserve findings, share results, and continue your analysis in a structured format.

What you can do:

- **Iterate**: Run and maintain multiple searches next to one another for faster, more efficient investigations.
- **Annotate**: Add context and clarity with Markdown notes for rich storytelling.
- **Collaborate**: Share your work through fine-grained edit or read-only access.
- **Control**: See who last edited your Notebook, and when.
- **Summarize**: Use Cribl Copilot to generate summaries of your findings and run queries from natural-language prompts.

For details on working in a Notebook, see Notebooks. For the **Templates** tab, reusable layouts, and sharing templates, see Notebook templates.

Deep Investigations

Deep Investigations (Preview) is an investigation mode that structures analysis around hypotheses. Cribl Search proposes potential root causes, you select which to pursue, and the AI validates each one sequentially using targeted queries and evidence gathering. Deep Investigation Mode is off by default. To use it, turn on the **Deep Investigation Mode** toggle in the Investigations toolbar before you start, or start an investigation from a Notebook.

What you can do:

- **Select hypotheses**: Review AI-generated hypotheses and choose which to investigate.
- **Track evidence**: Each hypothesis is validated with targeted queries and evidence is recorded automatically.
- **Map the investigation**: View the investigation as a graph showing goals, data sources, hypotheses, and the conclusion.
- **Disregard**: Dismiss a hypothesis at any time. It is marked terminal and noted in the summary.

For details, see Deep Investigations (Preview).

7.1. Run Investigations (Preview) With Cribl Search



Preview Feature

Cribl is still developing this Preview feature. We don't recommend using it in a production environment, because the feature might not be fully tested or optimized for performance, and related documentation could be incomplete.

Please continue to submit feedback through normal Cribl support channels, but assistance might be limited while the feature remains in Preview.

Investigate incidents with AI guidance and capture your findings in one workspace.

The Cribl Search investigations page provides a guided workspace for investigations or explorations in your data using natural language. Cribl Search helps you analyze telemetry data, identify patterns, and document findings without manually building every query.

From this page, you can start a new investigation, explore Datasets, or resume a prior session.

Before You Start:

- Ensure you have a paid, active Cribl Search subscription or billing plan.
- Enable investigations in **Global Settings > AI Settings**.
- (Optional) Configure MCP Integrations to give the investigation AI access to external tools such as FireHydrant, Jira, Slack, and Bitbucket. This improves investigation quality when working from incidents or tickets.
- Enable Dataset Intelligence on your frequently searched Datasets to improve investigation accuracy and query quality.


Customize Investigations

These settings are optional but recommended: configuring them before you start an investigation gives the AI the right model, access to external information, and any custom instructions your team needs.

Select a Model

If your Organization has configured a Bring Your Own Model (BYOM) provider in **AI Settings** with two or more models assigned to the reasoning model tier, a model selection control appears in the investigation chat input. Use it to choose which reasoning model Cribl Search uses for the session. The first model assigned to the reasoning tier becomes the default for all users.

The control doesn't appear if only one model is configured or if you are using the default Cribl-managed provider.



Model selection control in the investigation chat input

Enable Web Search

When web search is enabled, the investigation AI can search the web to supplement its analysis with up-to-date external information, for example, looking up CVE details, vendor release notes, or known issues related to a service.

To enable web search, go to **Global Settings** > **AI Settings** and turn on the web search option.

> Web search is not available in Cribl.Cloud Government. The control in **AI Settings** is disabled, and investigations run without web search rather than prompting you to enable it. See AI in Cribl.Cloud Government.

When the AI invokes a web search during an investigation, a **Searching the web...** indicator appears in the chat. Results are incorporated into the AI's response and cited inline. Each citation renders as a source tag next to the relevant statement:

- Results from `cribl.io` display the Cribl logo.
- Results from other domains display a globe icon and the domain name.

Hover over a source tag to see the full source URL. The AI always includes both an inline citation and a source reference for every web result it uses.

When the investigation summary is generated, a **Sources** section appears at the bottom of the summary listing every web source referenced in the findings or conclusion. Each entry shows a globe icon and a link with the source title you can select.

Edit agents.md

`agents.md` is a markdown guidance file that shapes how the Cribl Search investigation AI behaves. You can use it to set custom instructions, constraints, or tone for the AI during investigations, for example, requiring it to always cite data sources or focus on a specific set of Datasets.

An **agents.md** button appears in the investigation toolbar whenever an active investigation session is open. Select it to open the `agents.md` editor modal.

Permissions:

- **Admin users** (org owner, workspace owner, org admin, workspace admin, or product admin) can edit the content and save changes.
- **Non-admin users** can open the modal and view the current contents in read-only mode, but the **Save** button is hidden.

To edit `agents.md`:

1. Start or resume an investigation session.
2. In the investigation toolbar, select **agents.md**. The editor modal opens.
3. Update the markdown content with your instructions.
4. Select **Save**.

Changes take effect immediately for all new investigation interactions.

Choose How to Start

From the **Logs** page, select **Run Investigation**. The Cribl Search investigations page opens.

You can start by describing a scenario in the prompt box or by selecting a starting scenario card. Cribl Search will prompt you for more context.

From a Cribl Alert

Begin with a Cribl-native alert. Use this option when an alert has already fired in Cribl Search and you want the investigation to be grounded in that specific signal.

Select **Select from recent alerts**. Cribl Search shows a list of recent alerts from Cribl. Select one to anchor the investigation. The AI reads the alert's title and body to extract key entities - IP addresses, domains, hostnames, usernames, error codes, and similar fields - and uses them to select relevant Datasets and build initial queries automatically.

From an External Incident

Begin with an incident from an external incident management tool such as FireHydrant. Use this option when you have an active incident ticket and want Cribl Search to pull in its metadata alongside telemetry data.

Select **Select from recent incidents**. Cribl Search shows a list of recent incidents from your configured incident provider. Select one (for example, "Credit Card Processing Outage").

> Connecting MCP integrations gives Cribl Search access to external tools such as FireHydrant, Jira, and Slack. This significantly improves investigation quality, especially when starting from an incident, because the AI can pull in incident metadata, linked tickets, and channel context alongside your telemetry data.

Explore Your Data

Start an open-ended exploration of your Datasets. Use this option to look for anomalies, trends, or unexpected patterns. Cribl Search helps identify relevant fields and suggests follow-up queries. Ideal for exploratory analysis or hypothesis development.

Example: "Help me investigate errors in system X over the past 2 days and suggest likely root causes and fixes."

From a Notebook

Begin an investigation from an existing Notebook, using its searches and notes as a starting point. Use this option when a Notebook already holds relevant context and you want Cribl Search to dig deeper.

In the Notebook toolbar, select **New Investigation**. Cribl Search seeds the investigation from the Notebook, summarizes its contents, and confirms an investigation goal with you before it starts. For details, see Start an Investigation from a Notebook.

Resume a Prior Session

Cribl Search automatically saves your investigation sessions as you work. No manual action is required. Sessions are retained for a minimum of 30 days.

There are three ways to return to a previous session:

- **Investigations landing page - Resume tile:** When you first open the Investigations page, select the **Resume a Prior Investigation** tile. A drawer opens from the left side listing your saved sessions.
- **Investigations landing page - Recents list:** Scroll to the bottom of the Investigations landing page to see your most recent sessions. Select a session to open it, or select **View All** to open the full sessions drawer.
- **Investigations toolbar:** In the Investigations toolbar, select **Recent investigations** to open the sessions drawer at any time.

Once the drawer is open:

1. Browse or filter the list. The table shows each session's **Name**, **Context** (Investigations), **Last Updated** time, and **Owner**.
    - Use the filter input to search by ID, date updated, or owner.
    - Sessions from both standard and Deep Investigation modes appear together in a single unified list.
2. Select a session name to restore it. The session opens in chat-only mode with your prior messages visible, scrolled to the most recent message.



Sessions and Notebooks are separate artifacts. A session records the live investigation interaction. A Notebook is a structured document you can create from a session's findings by selecting **Save to Notebook** in the investigation summary.

Review the Investigation Plan

When you start an investigation with anything other than a straightforward request, Cribl Search proposes an investigation plan before it runs any queries. The plan gives you a chance to confirm the scope of the investigation before Cribl Search commits to it, and the Datasets and time range you confirm are used throughout the rest of the session.

The plan shows:

- The **Datasets** that Cribl Search considers relevant, along with a short explanation of why it selected each one.
- A suggested **time range**, shown in a time range picker, that Cribl Search thinks is appropriate for the investigation.

Adjust the Plan

Before you confirm, you can refine the proposed scope:

- **Datasets:** Add or remove Datasets so that Cribl Search searches only the data you care about. You control the final set of Datasets, rather than having Cribl Search select them automatically.
- **Time range:** Use the time range picker to widen or narrow the window that Cribl Search searches.

Confirm the Plan

Select **Confirm** to accept the plan. Cribl Search records the relevant Datasets and time range and uses them for the queries it builds during the investigation.

Cancel the Plan

Select **Cancel** to reject the plan. Cribl Search explains why the current plan might not be sufficient. If you provide feedback about what you want to investigate, Cribl Search proposes a new plan based on that feedback.

Refine and Extend the Investigation

Run the First Step

Choose a suggested step (for example, "Select from recent incidents" or "Review recent logs for service X"). Cribl Search:

- Generates the KQL query.
- Runs it against the selected Dataset(s).
- Shows query text, a result preview, and a short natural-language summary.

Pull in External Context

If your Organization has external providers configured in MCP Integrations (for example, FireHydrant, Jira, Bitbucket, Slack), you can ask Cribl Search to:

- "Search Jira for items linked to this incident."
- "Find the Bitbucket PR mentioned in Jira ticket AI-2676."
- "Summarize messages from the incident Slack channel around the outage time."

Cribl Search runs dataset-backed queries (for example, `dataset=jira_dataset ...`, Bitbucket audit logs) and summarizes what it finds.

Use the Generic HTTP API to connect Cribl Search investigations to external context. To make tools from external systems available to Cribl AI agents via the MCP protocol, see Connect Cribl AI to External MCP Servers.

Refine and Correlate

Ask questions such as: "Is there any relationship between the Next.js version in this PR and the error seen in the credit card processing logs?" Cribl Search correlates fields across Datasets and explains the link in plain language (for example, version mismatch causing the incident).

Deep Investigations

For more complex requests, such as root cause analysis, you can run a deep investigation that structures your analysis around hypotheses. Cribl Search proposes a list of potential root causes, you select the ones to

pursue, and the AI validates each one sequentially using targeted queries and evidence gathering.

Deep Investigation Mode is off by default. To use it, turn on the **Deep Investigation Mode** toggle in the Investigations toolbar before you start, or start an investigation from a Notebook. If Deep Mode returns an error, turn the toggle off and run your investigation again in standard investigation mode. Your preference persists across page reloads, and Cribl Search keeps the mode you set for the rest of the session.

For full details on the hypothesis workflow, the Investigation Graph, and hypothesis statuses, see Deep Investigations (Preview).

Save as Notebook

When you are satisfied with the findings:

1. In the investigation chat, choose **Save as Notebook** or type "Save a notebook with all findings and actions."
2. Cribl Search builds a Notebook containing:
    - An AI-generated summary of the investigation.
    - The queries it ran.
    - Key results and recommendations.

You can then share or extend this Notebook as a durable investigation artifact. For more details, see Notebooks.

Goat-to Resources

Cribl Search Demo: Security Investigation Video

7.2. Deep Investigations (Preview)

Preview Feature

Cribl is still developing this Preview feature. We don't recommend using it in a production environment, because the feature might not be fully tested or optimized for performance, and related documentation could be incomplete.

Please continue to submit feedback through normal Cribl support channels, but assistance might be limited while the feature remains in Preview.

Deep Investigation Mode is an investigation experience that structures your analysis around hypotheses. Instead of an open-ended conversation, Cribl Search proposes a set of hypotheses, you select the ones you want to pursue, and the AI validates each one sequentially - running queries, gathering evidence, and building toward a structured conclusion.

You decide when to run a deep investigation. To use Deep Investigation Mode, turn on the **Deep Investigation Mode** toggle in the Investigations toolbar, or start an investigation from a Notebook.

Before You Begin

- AI must be configured correctly in your organization.
- The **Search Investigations** setting must be active in **Global Settings > AI Settings**.
- A paid, active Cribl Search subscription or billing plan is required.

Turn On Deep Investigation Mode

There are two ways to run a deep investigation:

- **Turn on the toggle:** In the Investigations toolbar, turn on the **Deep Investigation Mode** toggle before you start. You must turn it on at the start - Cribl Search sets the mode when the investigation begins and keeps it for the rest of the session. Your toggle choice persists across page reloads.
- **Start from a Notebook:** A deep investigation also runs when you start one from a Notebook. For details, see Start an Investigation from a Notebook.

Deep Investigation Mode is a Preview feature that is still improving and can occasionally fail. If it returns an error, turn off the **Deep Investigation Mode** toggle and run your investigation again in standard investigation mode, so that Deep Mode issues don't block you from continuing.

How the Workflow Differs from Standard Investigations

Standard investigations use a free-form conversation model. Deep Investigations use a structured state machine that progresses through the following phases:

1. **Establish a goal**: Describe a scenario, select a recent incident, or browse external context. Cribl Search infers and records the investigation goal.
2. **Identify data sources**: Cribl Search selects up to five relevant Datasets and examines their schema and field statistics. If Dataset Intelligence is enabled on a Dataset, that context is used automatically.
3. **Select hypotheses**: Cribl Search proposes a list of hypotheses for you to review. Select the ones you want to investigate. You can also add your own.
4. **Validate hypotheses**: Cribl Search validates each selected hypothesis strictly one at a time, in the order selected. During this phase, the chat thread stays quiet while Cribl Search runs queries and updates progress in the background.
5. **Review the summary**: When all hypotheses have a terminal status, Cribl Search presents a structured investigation summary with findings, a conclusion, and terminal action buttons.

View the Investigation Graph

The Investigation Graph is a visual map of the investigation that updates as Cribl Search progresses.

To open it, select **Map** in the Investigations toolbar.

The graph displays the following nodes:

- **System Alert**: Shown when the investigation was started from an alert.
- **Investigation Goal**: The goal statement inferred from your input.
- **Context Discovery**: With a sub-node for each data source identified as relevant.
- **Hypotheses**: With a sub-node for each hypothesis selected.
- **Conclusion**: The overall outcome after all hypotheses reach a terminal status.

Select any hypothesis node to open the **Hypothesis Drawer**, which shows the hypothesis details, evidence gathered, and the **Disregard** option.

Hypothesis Statuses

Each hypothesis moves through a set of statuses during the investigation:

Status	Meaning
Enqueued	Selected and waiting to be investigated
Investigating	Currently being validated
Confirmed	Evidence strongly supports the hypothesis
Inconclusive	Evidence is partial or ambiguous
Unlikely	Evidence contradicts the hypothesis
Failed	Investigation could not gather sufficient evidence
Disregarded	Dismissed by you before or during investigation

All statuses except **Enqueued** and **Investigating** are terminal — the investigation does not revisit a hypothesis once it reaches a terminal status.

Disregard a Hypothesis

You can dismiss a hypothesis at any time during the investigation.

1. In the investigation toolbar, select **Map** to open the Investigation Graph.
2. Select the hypothesis node you want to dismiss.
3. In the Hypothesis Drawer, select **Disregard**.

A disregarded hypothesis is marked terminal immediately. Cribl Search will not run further queries for it. It is still noted in the investigation summary so your findings remain accurate.

Finish the Investigation

When every hypothesis has a terminal status, Cribl Search presents the investigation summary. From the summary, you can:

- **Save to Notebook**: Builds a Notebook containing the AI-generated summary, the queries run, key results, and recommendations. See Notebooks for details.
- **Dig deeper into findings**: Returns to the investigation to continue exploring.
- **End investigation**: Closes the investigation session.

Your session is saved automatically throughout. To return to this investigation later, select **Recent investigations** in the Investigations toolbar. See Saved Sessions for details.

Related

- Run Investigations (Preview)
- Notebooks

7.3. Cribl Search Notebooks

Run an entire investigation in one tab, and share your work with others.

Why Use Notebooks

A Notebook is a document-like page in Cribl Search where you and other data analysts can combine search queries, data visualizations, and Markdown notes into persistent, shareable investigations. Here's what you can do with Notebooks:


- **Iterate**: Run and maintain multiple searches next to one another, for faster, more-efficient investigations.
- **Annotate**: Add context and clarity with markdown notes for rich storytelling.
- **Collaborate**: Share your work through fine-grained edit or read-only access.
- **Control**: See who last edited your Notebook, and when.
- **Organize**: Track the status of each investigation and tag Notebooks by team, use case, or priority, so a long list stays navigable.
- **Summarize**: Use Cribl Copilot to generate summaries of your findings, and to run queries from natural-language prompts.
- **Standardize**: Use Notebook templates to capture repeatable investigations or operational runbooks your team can open with the same structure, queries, and notes.

Start working with Notebooks from anywhere in Cribl.Cloud: On the top bar, select **Products** > **Search** > **Notebooks**. On the **Notebooks** page, switch between the **Notebooks** and **Templates** tabs to work with saved investigations or templates.

What's in a Notebook

A Notebook consists of **Logs Search** cells, **Metrics Search** cells, and **note cells**. **Logs Search** cells run log queries. **Metrics Search** cells run metrics queries and appear when Metrics is enabled. See Add a Logs Cell and Add a Metrics Cell.

When a Notebook is shared, **Maintainers** can add and edit cells, drag cells up and down, and clone the Notebook. **Read Only** users can view the cells and their results. Read more about sharing Notebooks.


Search
Products
Apps
Non-Production Environment
Collapse
Notebooks
Notebooks / Notebook
Last modified by:
Last modified: Aug 11, 2026 15:37 | 2 viewers
Notebooks allow users to seamlessly add multiple live queries and annotations to a single document to share with teammates. This makes it an ideal artifact for data investigations, postmortems, and even how-to guides such as this.
Additionally, Notebook Templates allow teams to standardize the format and steps of these investigations to make tasks more efficient and consistent.
So let's use Notebooks to explore Cribl's default sample dataset, cribl_search_sample.
Logs Search 1
Last run: Aug 11, 2026 15:37
1 dataset="cribl_search_sample" | limit 1000
1000 results (13.18s)
Details
account_id 1
action 1
bytes 971
dataset 1
dataSource 1
datatype 1
dstaddr 16
dstport 20
end 716
interface_id 8
log_status 1
packets 60
protocol 1
source 50
srcaddr 19
2026-08-11 15:00:00
2026-08-11 15:05:00
2026-08-11 15:10:00
2026-08-11 15:15:00
2026-08-11 15:20:00
2026-08-11 15:25:00
2026-08-11 15:30:00
Time
Event
Metric Search
Dataset
metrics
Query A
Visual
Code
Clone
PROMQL: sum(ack_level_update)
Metric
ack_level_update
Function
Calculation
Query
sum
+ group by
Dimension filters
+ Add filter
+ Add query
241 results (0.24s)
Details
80000000
60000000
40000000
20000000
0
14:37:19
14:40
14:45
14:50
14:55
15:00
15:05
15:10
15:15
15:20
15:25
15:30
15:37:19
ack_le...pdate
_time
ack_level_update
2026-08-11 14:37:19.0
85743997
2026-08-11 14:37:34.0
85748566
2026-08-11 14:37:49.0
85748566
2026-08-11 14:38:04.0
85748566
2026-08-11 14:38:19.0
85748566
2026-08-11 14:38:34.0
85748566
2026-08-11 14:38:49.0
85748566
2026-08-11 14:39:04.0
85756771
Logs Search
Metrics Search
Add Note

A Notebook with two sample searches

Start a New Notebook

From Scratch | From Template | From Current Search | From Saved Search | From History

You can create an empty Notebook, and then add searches and notes as needed.

1. Go to the **Notebooks** page in Cribl Search: On the top bar, select **Products** > **Search** > **Notebooks**.
2. Select **Add Notebook**. Your new Notebook opens and gets autosaved.
3. Start running searches and adding notes.

Notebook Templates

For the **Templates** tab, **Add Template**, **Edit Template**, sharing, **Clone**, **Delete**, and creating templates from scratch, see Notebook templates.

When you work inside a Notebook, use the **From Template** tab under Start a New Notebook to start from a template, and **Save as Template** under Customize Notebook Display to capture the Notebook as a template.

Add a Logs Cell


Inside the Notebook | From Current Search | From Saved Search | From History

You can run multiple log searches directly from your Notebook. You need to be the Notebook's Maintainer for this.

1. Open an existing Notebook or create a new one.
2. At the bottom of the Notebook, select **Logs Search**. A cell with a query box opens.
3. Run your query, as you would anywhere else in Cribl Search. To learn how, see some quick examples, or this tutorial: Write Your First Query. If your Organization has Cribl AI configured correctly, you can also use your search cells to run natural-language queries.
4. To add another query, select **Logs Search** again. You can start another search while the first one is still running.

You can also add a **Logs Search** cell between existing cells: select **Add**, then select **Logs Search**.

Alternatively, you can create a new search cell by selecting a field within a field summary or event details panel, and then selecting **Add field to new cell** from the resulting context menu.



Creating a new cell from a returned field

Add a Metrics Cell (Preview)

Preview Feature

Cribl is still developing this Preview feature. We don't recommend using it in a production environment, because the feature might not be fully tested or optimized for performance, and related documentation could be incomplete.

Please continue to submit feedback through normal Cribl support channels, but assistance might be limited while the feature remains in Preview.

With the Metrics experience enabled, a Notebook can include a dedicated metrics cell alongside its log search cells and note cells. This lets you combine metrics analysis, log queries, and Markdown notes in one investigation.

You can add a metrics cell in two ways:

- **From a Notebook**: Select **Metrics Search** in the Notebook.
- **From the Metrics Explorer**: Build a query in Metrics, then add it to a new or existing Notebook.

Inside the Notebook | From Metrics Explorer

You need to be the Notebook Maintainer to add cells.

1. Open an existing Notebook or create a new one.
2. At the bottom of the Notebook, select **Metrics Search**. A metrics cell opens.
3. Build your metrics query in the cell, as you would in the Metrics Explorer.
4. In the cell header, select **Run** to execute the query and show its results.

You can also add a **Metrics Search** cell between existing cells: select **Add**, then select **Metrics Search**.

A metrics cell keeps its query visible after you run it, the same way a **Logs Search** query box does.

Each query appears as its own card (**Query A**, **Query B**, and so on), with **Visual** and **Code** (PromQL) views.

If you are the Notebook Maintainer, select the query to enter edit mode and refine it in the cell.

To open the query in the Metrics Explorer, select , then **Open in Metrics**.

To add a log search cell instead, select **Logs Search**. To add a note, select **Add Note**.

Add Notes to Your Notebook

You can add markdown-formatted notes to your Notebook using headings, lists, links, and more. See Markdown Guide for basic syntax.

You need to be the Notebook Maintainer for this.

1. Open an existing Notebook or create a new one.
2. At the bottom of the Notebook, select **Add Note**. A new note cell opens.
3. Write your notes using markdown. The Notebook gets autosaved.

Summarize Your Notebook with Cribl Copilot

If your Organization has Cribl AI configured correctly, you can generate an AI summary of your Notebook findings.

1. Open an existing Notebook or create a new one.
2. In the top-right corner, select **Summarize**.

A summary of your Notebook appears in a new note cell at the top of the Notebook. You can edit the summary as needed.

Start an Investigation from a Notebook

You can launch an investigation directly from a Notebook, using the Notebook's searches and notes as a starting point. This is useful when a Notebook already holds relevant context and you want Cribl Search to dig deeper.

1. Open the Notebook you want to investigate from.
2. In the Notebook toolbar, select **New Investigation**.


Cribl Search opens investigations, seeded from that Notebook. Cribl Search summarizes the contents of the Notebook and confirms an investigation goal with you before it starts investigating.

Customize Notebook Display

To make your Notebook easier to skim, you can manage how much detail the Notebook displays. In the top-left corner of each cell, a Collapse/Expand toggle enables you to reduce the cell's vertical depth to a summary view.

In the top-right corner of the Notebook itself, the Actions ⋯drop-down provides options to manage the appearance of the whole Notebook and to capture the layout as a template:

- Select **Collapse All Cells** or **Expand All Cells** to control the vertical spread of all cells at once.
- Select **Wide Layout** or **Default Layout** to control the horizontal width available for Notebook contents.
- Select **Save as Template** to create a new template from the current Notebook. See Save an existing Notebook as a template.



Summarize, Share, and Actions controls

Navigate with the Table of Contents


The **Table of Contents** panel shows an outline of the Notebook that Cribl Search builds from your note headings and search cells. Use it to jump between cells instead of scrolling a long investigation, and to give a colleague picking up your work a structure they can scan for context.

Open and Close the Panel

In the Notebook header, on the **Last modified** row, select **Table of Contents**. The outline opens in a panel to the left of the Notebook. To close it, select **Table of Contents** again, or select the close icon in the panel header.

The panel starts out closed. After that, Cribl Search remembers whether you left it open and applies that choice to every Notebook and Notebook template you open next. This preference lives in your browser, so it does not follow you to another browser or device.

Anyone who can open the Notebook can use the panel, including Read Only collaborators and anyone viewing a locked Notebook.



The Table of Contents panel, and the toggle that opens it

What Appears in the Outline

Cribl Search decides what to list based on the cell type:

- A **note cell** contributes an entry only when its first line is a Markdown heading, from `#` through `######`. The heading text becomes the label. A note whose first line is anything else does not appear in the outline at all, and neither does a heading further down inside a note. Put the heading at the top of the note cell whenever you want that note to anchor a section.
- A **Logs Search** cell always contributes an entry, labeled with the cell title. Untitled cells fall back to **Logs Search 1**, **Logs Search 2**, and so on.
- A **Metrics Search** cell behaves the same way, falling back to **Metrics Search 1**, **Metrics Search 2**, and so on.

Entries nest the way they would in a document outline:

- A heading nests under the closest preceding heading that is a level higher. An `##` heading nests under an earlier `#` heading, for example. A heading with no higher-level heading before it stays at the top level.
- A search cell nests under the closest preceding heading, at whatever level that heading is. Search cells that come before the first heading stay at the top level.

Where an entry has children, select the caret beside it to collapse or expand that branch. Labels longer than two lines are truncated.

Jump to a Cell and Reorder Cells

Select any entry to scroll its cell into view.

To reorder the Notebook, drag an entry to a new position in the outline. Note that this moves only the single cell that the entry represents. Cells nested under a heading do not travel with it, so moving a whole section means moving each of its cells in turn.

Dragging requires Maintainer access on a Notebook that is not locked. Otherwise the entries remain clickable, but you cannot drag them.

Export Notebook Search Results

You can export the results of a Notebook search as a CSV or NDJSON file.

1. Open an existing Notebook or create a new one.
2. In a search cell, select the Actions ⋯button.
3. From the drop-down, select **Export as**, and then either **Export Results as CSV** or **Export Results as NDJSON**.

Export a Notebook Chart

You can export a Chart contained in a Notebook search cell, as a JPG or PNG file.

1. Open an existing Notebook or create a new one.
2. In a search cell, select the Actions ⋯button.
3. From the drop-down, select **Export as**, and then either **Export Chart as JPG** or **Export Results as PNG**.

Export Your Notebook as a PDF

You can download your Notebook as a PDF file.

1. Open an existing Notebook or create a new one.
2. In the top-right corner, select the Actions ⋯button.
3. From the drop-down, select **Print to PDF**, and then save the file.

Organize Notebooks

Continuous investigative work builds up a long list of Notebooks. To keep that list navigable, give each Notebook a **Status** and a set of **Tags**. Status records where an investigation stands. Tags group Notebooks by team, use case, priority, or whatever else you track. You can also read and set both through the Cribl Search API.

You need to be a Maintainer on the Notebook to set a status or edit tags, and the Notebook must not be locked. Everyone who can open the Notebook sees both, and anyone can filter the **Notebooks** list by them.

Set the Status of a Notebook

A Notebook has one of three statuses:

Status	Meaning
None	The default for a new Notebook. The **Status** cell in the Notebooks list stays empty.
Active	The investigation is in progress.
Closed	The investigation is finished.

To set the status:

1. Open the Notebook.
2. In the Notebook header, select the status pill. On a Notebook that has no status yet, the pill reads **Add Status**.
3. Select **Active** or **Closed**. To return the Notebook to **None**, select **Clear status**.

Cribl Search saves the new status with the Notebook. When you clone a Notebook, the copy starts at **None** rather than inheriting the status from the original. Notebook templates do not have a status, so saving a Notebook as a template drops it.

Without **Maintainer** access, or on a locked Notebook, the pill still shows the status but you cannot change it.

Status also appears on the **Notebooks** tab in the details panel for a Dataset, so you can see which investigations involving that Dataset are still open.

Tag a Notebook

Tags are free-form labels. A Notebook can carry as many as you need, and the same tag can appear on any number of Notebooks and templates. Tags are case-sensitive, so `Triage` and `triage` are two different tags.

1. Open the Notebook.
2. Below the Notebook header, select the **Edit tags** icon. On a Notebook that has no tags yet, the tag area reads **Add tags**.

3. Enter one or more tags, separating them with commas. As you type, Cribl Search suggests tags already used on other Notebooks and templates, which helps you reuse a consistent vocabulary instead of inventing near-duplicates.
4. Select the check mark to save your changes, or the close icon to discard them. Pressing `Esc` also discards them.

Without **Maintainer** access, or on a locked Notebook, you see the tags but no editing controls. When a Notebook you cannot edit has no tags, the tag area is hidden entirely.

You can tag Notebook templates the same way.

Filter and Sort the Notebooks List

Go to the **Notebooks** page in Cribl Search: On the top bar, select **Products** > **Search** > **Notebooks**. For each Notebook, the **Notebooks** tab lists **Name**, **Status**, **Last Modified**, **Last Modified By**, **Created By**, and **Tags**, along with an **Actions** column.

To narrow the list:

- Select the **Status** control at the top of the list, then choose one or more statuses. Each option shows how many Notebooks currently carry it. A Notebook matches if it has any of the statuses you chose.
- Select the **Tags** control at the top of the list, then choose one or more tags. A Notebook matches only if it carries every tag you chose, so adding tags narrows the results rather than widening them. This control appears only when at least one Notebook in the list has a tag.
- Select a status pill or a tag directly in a row to replace the current filter with just that value. This is the quickest way to answer questions like "what else is tagged `pci-audit`?"

Each control lists your current selections next to its name. To drop a filter, select the X beside that control.

Sort the list by **Status** using the column header. **Tags** is not sortable, because a Notebook can carry several tags at once.

Share Your Notebook

As a **Maintainer**, you can allow others to view or edit your Notebooks at any time. For example, you might want to:

- Invite colleagues to join the investigation and contribute their expertise.
- Let others retrace your steps and pick up where you left off.
- Tell the full story behind your analysis, so stakeholders can understand how you reached your conclusions and review any assumptions you made.
- Grant limited access rights on your Notebooks to service accounts that connect to Cribl Search via API.


To share a Search Notebook with a Member, Team, or API Credential whose Search Permission is **Editor** or **User**:

1. Open an existing Notebook for which you are a Maintainer or create a new one.
2. In the top-right corner, select the Share button. Now, you can see who has access to the Notebook and at what level.
3. Under **Add Members, Teams, and API Credentials**:
    - From the left drop-down menu, select the Member, Team, or API Credential that you want to share the Notebook with.
    - From the right drop-down menu, select the Notebook Permission you want to grant: **Read Only** or **Maintainer**. For details, see Cribl Search Notebooks Permissions.
4. Select **Add Access**.
5. Select **Save**.

Admin Members, Teams, and API Credentials have the **Maintainer** Permission on all Notebooks by default.

To modify or remove access on a Search Notebook, find the Member, Team, or API Credential in the list on the **Sharing** pane. Select the desired Permission from the drop-down menu in the **Permission** column and save. Selecting **No Access** removes all access rights on the Notebook.

To copy a link to a specific cell, select the link icon in the cell's top-left corner.



Sharing a Notebook

Synchronize or Lock Edits

As a Notebook creator, or with a Maintainer or higher Permission: When you save changes to a Notebook, a

7.4. Notebook Templates

Notebook templates are reusable layouts for Search investigations. Each template stores the same kinds of **search cells** and **note cells** as a Notebook, including saved queries and chart settings, so teams can start from a known structure for incidents, audits, or onboarding. You can treat a template as an operational **runbook**: a fixed sequence of steps your Organization follows every time.

Templates are separate objects from Notebooks. Creating or editing a template does not write to a Notebook's activity history the way collaborative investigation work does, and template editing is focused on maintaining the template itself rather than preserving job-by-job search lineage like a live investigation.

Open the Templates List

1. Go to the **Notebooks** page in Cribl Search: On the top bar, select **Products** > **Search** > **Notebooks**.
2. Select the **Templates** tab.

For each template, the table lists **Name**, **Last Modified**, **Last Modified By**, **Created By**, and **Tags**, so you can see ownership and freshness at a glance.

From the list you can open a template, use it to create a Notebook, or use row actions where your permissions allow. At the top of the list, select **All**, **Custom**, or **Cribl** to switch between every template, the ones your Organization created, and the ready-made ones from Cribl.

To filter by tag, select the **Tags** control and choose one or more tags. A template matches only if it carries every tag you chose. You can also select a tag directly in a row to filter by just that tag. The **Tags** control appears only when at least one template has a tag. See Tag a Template.

Create a Template

Add a New Template From Scratch


1. On the **Templates** tab, select **Add Template**. Cribl Search creates a template and opens it in edit mode.
2. Add or adjust search cells and note cells the same way you do in a Notebook. You need **Maintainer**-level access on the template to edit it.
3. Select **Save** when you are finished. Select **Exit** to leave edit mode, or confirm discarding changes if you exit without saving.

Save an Existing Notebook as a Template

1. Open the Notebook you want to capture.

2. In the top-right corner, select the Actions ⋯drop-down, then select **Save as Template**.
3. Cribl Search creates a new template from the Notebook and opens it in template edit mode. The template name starts from the Notebook name, and you can rename it from the header.

You can also start from a ready-made Cribl template (for example, one that walks through sample data) by choosing it from the **Templates** tab or from the **Choose Template** flow when you create a Notebook from a template.



Save as Template

View or Edit a Template

On the **Templates** tab, select a template row to open it.

Templates open in **view** mode first. If you have **Maintainer** access, select **Edit Template** to change cells, queries, notes, and chart settings. While you edit, use **Save** to keep changes or **Exit** to leave edit mode. If you exit with unsaved edits, confirm whether to discard them.

Read Only access on a template lets you review the layout and results-style content and use **Use Template** or **Clone** from the list or template header, but not change the template or share it. **Maintainer** access is required for **Edit Template**, **Share Template**, and **Delete Template** actions where those controls appear.

For how object-level permissions map to **Read Only** and **Maintainer** in Search, see Cribl Search Notebooks Permissions. Template sharing uses the same permission model as Notebooks at the object level.

Outline a Template

Templates carry the same Table of Contents panel as Notebooks, built from the same note headings and search cell titles. In the template header, on the **Last modified** row, select **Table of Contents**. The panel works in view, preview, and edit mode.

Notebooks and templates share a single open or closed preference, so a panel you leave open in a template is still open the next time you open a Notebook.

Select an entry to scroll that cell into view, in any mode. Dragging entries to reorder cells works only while you have **Maintainer** access and the template is open in edit mode.

Tag a Template

Tag templates to group them by team, use case, or the kind of investigation they support, the same way you tag Notebooks. Templates and Notebooks draw from a shared pool of tags, so a tag you create in one place is suggested in the other.

You need **Maintainer** access, and the template has to be open in edit mode:

1. On the **Templates** tab, select a template to open it, then select **Edit Template**.
2. Below the template header, select the **Edit tags** icon. On a template that has no tags yet, the tag area reads **Add tags**.
3. Enter one or more tags, separating them with commas, then select the check mark to save. Select the close icon or press `Esc` to discard your changes.

In view mode, and for anyone with **Read Only** access, tags are visible but not editable. Templates do not have a status, because status applies only to Notebooks.

Share a Template

If you are a **Maintainer** on a template:

1. Open the template in view or edit mode.
2. Select **Share Template**.
3. Under **Add Members, Teams, and API Credentials**, choose who to add and assign **Read Only** or **Maintainer** for the template, then select **Add Access** and **Save**.

Grant **No Access** to remove someone from the template. Members without access cannot open the template from the list.

Clone or Delete a Template


- **Clone**: From the **Templates** tab, open the row actions for a template you can access and select **Clone**. Cribl Search creates a copy whose name includes **(Clone)** so you can adapt it without changing the original.
- **Delete**: From the **Templates** tab, select one or more templates you maintain, then select **Delete** and confirm. You need **Maintainer** access on each template you remove.

7.5. Investigative Searching

Optimize investigations with Cribl Search.

When performing investigations across multiple Datasets, an ideal workflow is:

- Search the smallest Dataset first, across all time, with a limit of 1,000 events.
- Alternatively, if your smallest Dataset has been searched before, search that Dataset first, for your time window of interest.



Ideal investigative workflow

S3: Discover Unknown Bucket Directory Structure

You can investigate this in the AWS Management Console. Or, in Cribl Search:

1. Create a Dataset whose path is just the S3 bucket name.
2. Run this query:

```
.show objects ("<dataset_name>") | where name contains "<xxx>"
```

Copy

Specify Time Formats in Paths

If directories are partitioned as year, month, day, hour, second, use:

```
${_time:%<parameter>}
```

Copy

For example:

```
. ${_time:%Y-%m-%d}
```

Copy

Or:

```
<mybucket>/${_time:%Y}/${_time:%m}/${_time:%d}/...
```

Copy

Or, if directories have `earliest` and `latest` in seconds, use those tokens:

```
<mybucket>/${__earliest/${__latest}/...
```

Copy

If the path has multiple time ranges:

- Use the most accurate field(s).
- Name the other field conspicuously (examples. `time_from_dir` or `other_time`).

Time Format Examples

If time in the directory format is:

```
<mybucket>/2024-128-19/xxx.gz
```

Copy

The path expression can be:

```
<mybucket>/prefix/${_time:%Y-%m-%d}
```

Copy

If time in directory format is:

```
<mybucket>t/2024/08/19/
```

Copy

The path expression can be:

```
<mybucket>/prefix/${_time:%Y}/${_time:%m}/${_time:%d}
```

Copy

For the following example:

```
aws/12-17-2024/db_0507829470_1165276110_8475_4288F9E6-9A3A-43B4-CCE9-4247DB82FCF9.csv
```

Copy

The path expression can be:

```
aws/${other_time}/db_${latest}_${earliest}_$(bucketid}_${suffix}.${extension}
```

Copy

Specific Versus Parameterized Dataset Paths

With specific file paths, you avoid `repository=*` problems:

```
<bucket>/sophos/${_time:%m}-${_time:%d}-${_time:%Y}/
<bucket>/okta/${_time:%m}-${_time:%d}-${_time:%Y}/
```

Copy

But to maximize search performance, parameterize your path structure, while specifying as many of the available parameterized fields as possible. Consider this structure:

```
<bucket>/${repository}/${_time:%m}-${_time:%d}-${_time:%Y}/
```

Copy

A simple query term like this would retrieve files from all repositories:

```
dataset=cribl_lake_logs
```

Copy

Whereas a specification like this - over the same timeframe - would filter for a much smaller subset of files. This would produce a faster and more efficient search:

```
dataset=cribl_lake_logs repository=okta
```

Copy

8. Visualize Cribl Search Results

Visualize your Cribl Search results with Charts, Tables, Dashboards, and other visualization tools.

Charts

When you run an aggregate search, your results display on a Chart. Learn how to use Charts in the following sections:

- Charts: Learn the basics, export a Chart as an image, save and reset Chart settings.
- Chart Types: See all available types of Charts, and learn how to customize each of them.
- Tables: Learn how to format the results table that displays below every Chart.

Dashboards

Cribl Search offers customizable Dashboards with a variety of visualization panels that you can tailor to your needs. Learn how to use Dashboards in the following sections:

- Dashboards: Get an overview and learn about built-in sample Dashboards.
- Create a Dashboard: Learn different ways of creating a Dashboard, and how to fill it with visualizations.
- Edit a Dashboard: Add, edit, hide, and arrange the visualization panels of your Dashboard.
- Apply a Parent Search: Aggregate results from multiple searches into a single visualization.
- Add Inputs: Link visualizations to specific data sources, using inputs.
- Add Interactions: Enable Dashboard viewers to drill down into specific values in a visualization panel.
- Add Markdown: Enrich your Dashboards with custom Markdown panels.
- Refresh Your Dashboards Automatically: Run a Dashboard on schedule, or configure its caching.
- Add Visualizations Using Cribl Copilot: Use the Cribl Copilot AI assistant to generate Dashboard visualizations.
- Manage and Share Dashboards: Collect, export, and share your Dashboards.

Third-Party Visualization Tools


You can easily visualize your Cribl Search results in Grafana, using the official Cribl Search plugin. See: Visualize Cribl Search Results in Grafana.

8.1. Charts

Visualize your search results, using Charts.

Cribl Search provides Charts to display aggregate search results. Cribl and statistical functions are used together with the `summarize`, `eventstats`, and `timestats` operators to aggregate your data.

When you run an aggregate search, your results display on a Chart. You can select from various Chart types and color palettes, and you can manipulate how your results are plotted.




Aggregate results on a Column Chart

See the following topics:

- Types of Charts in Cribl Search - Each page explains an available Chart type, the types of data it's best used for, and the settings available.
- Results Tables - covers the available options for the results table associated with a Chart, including sorting, filtering, and formatting tabular results.

See a Chart in Full Screen

To zoom your Chart up to a larger view, select the expand (Full screen) button at the Chart's top right.




Full screen

Export a Chart as an Image

To export your search results or Chart, open the **Actions** drop-down and select one of the following:

- **Export chart as PNG**.
- **Export chart as JPG**.
- **Export results as CSV**.
- **Export results as JSON**.



Export aggregate results


Save or Reset Chart Settings

The **Chart** tab provides a **Save chart settings** option (off by default). Enable this if you want to persist your Chart customizations when running later queries on the same page. If the Chart re-renders in unexpected ways (because some custiomizations conflict with new query terms), try turning this back off.

Selecting the **Reset** link will restore Chart defaults. This includes restoring the default Chart type (Column) and turning off the **Save chart settings** setting itself.



On Dashboards, visualizations do not provide this **Save** option. This is to maintain Dashboards' dynamic nature.



Save and Reset controls

8.1.1. Types Of Charts In Cribl Search

Learn what types of Charts Cribl Search offers.

List of Available Chart Types


Cribl Search provides the following types of Charts. To learn more about each of them, follow the relevant link.

- Area Chart
- Column Chart
- Donut Chart
- Funnel Chart
- Gauge Chart
- Horizontal Bar Chart
- Line Chart
- Map Chart
- Scatter Chart
- Single Value Chart

8.1.1.1. Area Chart

Visualize your search results, using an Area Chart.

An **Area** Chart is similar to a Line Chart, except the area representing values is filled in with the selected color. These are suited for data that accumulates, not so much for highly fluctuating data.



Area Chart

Chart Settings

Color palette: Select the color scheme you want to use in your Chart.

Data Settings

Trellis view: Enable to divide the Chart into subsets of data based on fields in your search. Select a field from the **Split view by** list (available only when your search query includes two or more fields.)

Interpolation: Select **Connect null values** to display null values. The default **Leave gaps** option hides null values.

Stack series: When enabled, data in the same category are stacked together. (This option is only configurable for Bar and Area Charts.)

Series table: You can edit the name of a series in the **Series name** column. The **Type** column allows you to set a different Chart type for each series. Use the **Color** column to set the desired color for the series.

X-Axis Settings

X-axis field: The data field to use for the X axis of the Chart. Defaults to a field chosen automatically based on the selected search.

Title: The label shown on the x-axis. Defaults to the field name that the axis references. Enter a custom name if needed.

Label orientation: The angle of rotation to display additional labels. Defaults to **0°**.

Position: Where to display the axis labels on the Chart.

Y-Axis Settings

Y-axis fields: The data fields to use for the Y axis of the chart. Defaults to fields chosen automatically based on the selected search.

Title: Defaults to the field name the axis references. Enter a custom name if needed.

Position: Where to display the axis labels on the chart. Defaults to **Left**.

Scale: Sets the distance between results. The default **Linear** scale uses an equal rate of change. A **Logarithmic** scale uses a percentage change.

Interval: The size of the axis measurement unit. For example, each interval on the y-axis can represent 2 or even 10 units, while each interval on the x-axis represents 1 unit.

Min: The minimum limit of units to display.

Max: The maximum limit of units to display. Defaults to `dataMax` where the maximum unit of data is used.

Show gridlines: Disable to hide the horizontal lines on the chart.

Legend Settings


Position: Where to display the legend relative to the chart.

Truncate: By default, Cribl Search truncates labels to fit your browser viewport, substituting a `...` for omitted characters. Toggle this off if you prefer to not alter labels.

8.1.1.2. Column Chart

Visualize your search results, using a Column Chart.

A **Column** Chart is best used to visualize categories of data. You could use a **Column** Chart to compare a distribution of values over time, to monitor the number of CPUs used by machine type, or to visualze the number of requests handled by a Pod.



Column Chart

Column is Cribl Search's default Chart type. (This type was labeled **Bar** in earlier Cribl Search versions.) To switch the vertical orientation, select the Horizontal Bar Chart type.

Chart Settings

Color palette: Select the color scheme you want to use in your Chart.

Data Settings

Trellis view: Enable to divide the Chart into subsets of data based on fields in your search. Select a field from the **Split view by** list (available only when your search query includes two or more fields.)

Interpolation: Select **Connect null values** to display null values. The default **Leave gaps** option hides null values.

Stack series: When enabled, data in the same category are stacked together. (This option is only configurable for Bar and Area Charts.)

Series table: You can edit the name of a series in the **Series name** column. The **Type** column allows you to set a different Chart type for each series. Use the **Color** column to set the desired color for the series.

X-Axis Settings

X-axis field: The data field to use for the X axis of the Chart. Defaults to a field chosen automatically based on the selected search.

Title: The label shown on the x-axis. Defaults to the field name that the axis references. Enter a custom name if needed.

Label orientation: The angle of rotation to display additional labels. Defaults to **0°**.

Position: Where to display the axis labels on the Chart.

Y-Axis Settings

Y-axis fields: The data fields to use for the Y axis of the chart. Defaults to fields chosen automatically based on the selected search.

Title: Defaults to the field name the axis references. Enter a custom name if needed.

Position: Where to display the axis labels on the chart. Defaults to **Left**.

Scale: Sets the distance between results. The default **Linear** scale uses an equal rate of change. A **Logarithmic** scale uses a percentage change.

Interval: The size of the axis measurement unit. For example, each interval on the y-axis can represent 2 or even 10 units, while each interval on the x-axis represents 1 unit.

Min: The minimum limit of units to display.

Max: The maximum limit of units to display. Defaults to `dataMax` where the maximum unit of data is used.

Show gridlines: Disable to hide the horizontal lines on the chart.

Legend Settings


Position: Where to display the legend relative to the chart.

Truncate: By default, Cribl Search truncates labels to fit your browser viewport, substituting a `...` for omitted characters. Toggle this off if you prefer to not alter labels.

8.1.1.3. Donut Chart

Visualize your search results, using a Donut Chart.

Donut Charts summarize how a total amount is divided into numerical proportions. Use a **Donut** Chart when you want to compare parts of a whole against the whole and its other parts, such as the distribution of operating system usage.



Donut Chart

Chart Settings

Color palette: Select the color scheme you want to use in your Chart.

Data Settings

Show only top N values: An optional numerical value that sets the Chart to display only the larger values of a Dataset, with smaller values filtered out. To display the smaller values grouped into a single category, enable **Summarize other values**.

Legend Settings


Position: Where to display the legend relative to the chart.

Truncate: By default, Cribl Search truncates labels to fit your browser viewport, substituting a `...` for omitted characters. Toggle this off if you prefer to not alter labels.

8.1.1.4. Funnel Chart

Visualize your search results, using a Funnel Chart.

A **Funnel** Chart helps visualize how data values move through a process in stages. **Funnel** Charts are useful for monitoring data that moves through a linear process in sequential, connected stages.



Funnel Chart

Chart Settings

Color palette: Select the color scheme you want to use in your Chart.

Data Settings

Show only top N values: An optional numerical value that sets the Chart to display only the larger values of a Dataset, with smaller values filtered out. To display the smaller values grouped into a single category, enable **Summarize other values**.

Legend Settings


Position: Where to display the legend relative to the chart.

Truncate: By default, Cribl Search truncates labels to fit your browser viewport, substituting a `...` for omitted characters. Toggle this off if you prefer to not alter labels.

8.1.1.5. Gauge Chart

Visualize your search results, using a Gauge Chart.

Gauge Charts (also known as dial or speedometer Charts) show progress toward a specific target or metric, displaying a specific value as a measure of progress toward that target.



Gauge Chart

Chart Settings

Apply threshold: Apply custom color threshold settings.

Enable **Apply threshold**, and then change or add custom colors and threshold values to change the display of the Chart.

Legend Settings


Position: Where to display the legend relative to the chart.

Truncate: By default, Cribl Search truncates labels to fit your browser viewport, substituting a `...` for omitted characters. Toggle this off if you prefer to not alter labels.

8.1.1.6. Horizontal Bar Chart

Visualize your search results, using a Horizontal Bar Chart.

A **Horizontal Bar** Chart is best used to render categorical results (such as “Top X Values”) or to render a large numbers of results.



Horizontal Bar Chart

If you prefer a bar Chart with vertical orientation, select the Column Chart type.

Chart Settings

Color palette: Select the color scheme you want to use in your Chart.

Save chart settings: Whether or not to persist Chart customizations when running new queries. For details, see Saving or Resetting Customizations.

Data Settings

Interpolation: Select **Connect null values** to display null values. The default **Leave gaps** option hides null values.

Stack series: When enabled, data in the same category are stacked together. (This option is only configurable for Bar and Area Charts.)

Series table: You can edit the name of a series in the **Series name** column. The **Type** column allows you to set a different Chart type for each series. Use the **Color** column to set the desired color for the series.

The **Trellis view** option is not displayed, and the **Stack series** option is not selectable, on this Chart type.

X-Axis Settings

X-axis field: The data field to use for the X axis of the Chart. Defaults to a field chosen automatically based on the selected search.

Title: The label shown on the x-axis. Defaults to the field name that the axis references. Enter a custom name if needed.

Label orientation: The angle of rotation to display additional labels. Defaults to **0°**.

Position: Where to display the axis labels on the Chart.

Y-Axis Settings

Y-axis fields: The data fields to use for the Y axis of the chart. Defaults to fields chosen automatically based on the selected search.

Title: Defaults to the field name the axis references. Enter a custom name if needed.

Position: Where to display the axis labels on the chart. Defaults to **Left**.

Scale: Sets the distance between results. The default **Linear** scale uses an equal rate of change. A **Logarithmic** scale uses a percentage change.

Interval: The size of the axis measurement unit. For example, each interval on the y-axis can represent 2 or even 10 units, while each interval on the x-axis represents 1 unit.

Min: The minimum limit of units to display.

Max: The maximum limit of units to display. Defaults to `dataMax` where the maximum unit of data is used.

Show gridlines: Disable to hide the horizontal lines on the chart.

Legend Settings


Position: Where to display the legend relative to the chart.

Truncate: By default, Cribl Search truncates labels to fit your browser viewport, substituting a `...` for omitted characters. Toggle this off if you prefer to not alter labels.

8.1.1.7. Line Chart

Visualize your search results, using a Line Chart.

A **Line** Chart is ideal for visualizing data over time, such as hardware usage and error events. These Charts work well with large and continuous sets of data.



Line Chart

Chart Settings

Color palette: Select the color scheme you want to use in your Chart.

Data Settings

Trellis view: Enable to divide the Chart into subsets of data based on fields in your search. Select a field from the **Split view by** list (available only when your search query includes two or more fields.)

Interpolation: Select **Connect null values** to display null values. The default **Leave gaps** option hides null values.

Stack series: When enabled, data in the same category are stacked together. (This option is only configurable for Bar and Area Charts.)

Series table: You can edit the name of a series in the **Series name** column. The **Type** column allows you to set a different Chart type for each series. Use the **Color** column to set the desired color for the series.

X-Axis Settings

X-axis field: The data field to use for the X axis of the Chart. Defaults to a field chosen automatically based on the selected search.

Title: The label shown on the x-axis. Defaults to the field name that the axis references. Enter a custom name if needed.

Label orientation: The angle of rotation to display additional labels. Defaults to **0°**.

Position: Where to display the axis labels on the Chart.

Y-Axis Settings

Y-axis fields: The data fields to use for the Y axis of the chart. Defaults to fields chosen automatically based on the selected search.

Title: Defaults to the field name the axis references. Enter a custom name if needed.

Position: Where to display the axis labels on the chart. Defaults to **Left**.

Scale: Sets the distance between results. The default **Linear** scale uses an equal rate of change. A **Logarithmic** scale uses a percentage change.

Interval: The size of the axis measurement unit. For example, each interval on the y-axis can represent 2 or even 10 units, while each interval on the x-axis represents 1 unit.

Min: The minimum limit of units to display.

Max: The maximum limit of units to display. Defaults to `dataMax` where the maximum unit of data is used.

Show gridlines: Disable to hide the horizontal lines on the chart.

Legend Settings

Position: Where to display the legend relative to the chart.


Truncate: By default, Cribl Search truncates labels to fit your browser viewport, substituting a `...` for omitted characters. Toggle this off if you prefer to not alter labels.

8.1.1.8. Map Chart

Visualize your search results, using a Map Chart.

Map Chart use geographical maps to display data points or categories associated with specific geographic locations.

To create Map Charts, your search needs to return supported geolocation data. You can use the `ip-lookup` operator, which references geolocation data from MaxMind's databases, or extract this information from your data. The Map Chart uses the first column (X-axis) to match the polygon name, and the second column (Y-axis) as the data.



Map Chart

Chart Settings


Color palette: Select the color scheme you want to use in your Chart.

Map Settings

First select either **World Map** or **USA Map**. Then choose whether you want to display the map as **Choropleth** or **Geo Map**.


A **choropleth** map displays divided geographical regions colored in relation to a data variable. This Chart uses the first column (X-axis) to match the polygon name, and the second column (Y-axis) as the data. A choropleth map is good for comparing high-level data at a glance.

To narrow the Chart's display of data in a choropleth map to show only a certain range of values, drag the **High/Low slider** handles from the top or bottom. To see individual data points highlighted on the map, hover your pointer over different parts of the **High/Low** slider.



Choropleth map example

A **geo** (geographic) map displays scaled data points based on a numeric value. You can customize the visualization by specifying the **Name**, **Latitude**, and **Longitude** fields, and you can select a specific scale or apply scale based on a data set in your query.



Geo map example

Sample Searches

The following example searches use the GeoLite2-City database in a lookup table called `geocity`. Note that to set them up, you'll need to first download a MaxMind `.mmdb` file and install it as a lookup table (follow the instructions in ip-lookup):


World Map

```
dataset=$vt_dummy event<100
| extend ip=strcat((10 + rand(205)),'.',rand(255),'.',rand(255),'.',rand(255))
| ip-lookup geocity on ip
| summarize count() by country
```

8.1.1.9. Scatter Chart

Visualize your search results, using a Scatter Chart.

Use a **Scatter** (or scatter plot) Chart to determine whether two numeric variables in a set of individual data points have a relationship or correlation. Dots or circles represent these data points.



Scatter Chart

Chart Settings

Color palette: Select the color scheme you want to use in your Chart.

Data Settings

Lines: Enable to connect all the data points with a line, similar to a **Line** Chart.

Name field: Adds labels to data points.

Data point scale: Sets the display size for data points. Select **Take from data field** to scale the data point size based on the selected field.

Scale field: The field to use for the data point scale, if **Take from data field** is selected.

X-Axis Settings

Title: The label shown on the x-axis. Defaults to the field name that the axis references. Enter a custom name if needed.

Label orientation: The angle of rotation to display additional labels. Defaults to **0°**.

Position: Where to display the axis labels on the Chart.

X-axis field: The field that will be used for the X-axis.

Y-Axis Settings

Title: Defaults to the field name the axis references. Enter a custom name if needed.

Position: Where to display the axis labels on the Chart. Defaults to **Left**.

Scale: Sets the distance between results. The default **Linear** scale uses an equal rate of change. A **Logarithmic** scale uses a percentage change.

Y-axis field: The field that will be used for the Y-axis.

Interval: The size of the axis measurement unit. For example, each interval on the y-axis can represent 2 or even 10 units, while each interval on the x-axis represents 1 unit.

Min: The minimum limit of units to display.

Max: The maximum limit of units to display. Defaults to `dataMax` where the maximum unit of data is used.

Show gridlines: Disable to hide the horizontal lines on the Chart.

Legend Settings

Position: Where to display the legend relative to the chart.

Truncate: By default, Cribl Search truncates labels to fit your browser viewport, substituting a `...` for omitted characters. Toggle this off if you prefer to not alter labels.

8.1.1.10. Single Value Chart

Visualize your search results, using a Single Value Chart.

A **Single Value** Chart allows you to display one search result. If there is more than one result, the first result is charted. These are helpful when you have an important value to track.



Single Value Chart

Chart Settings

Label: Defaults to the field name referenced on the Chart. Select the color block to the right of the **Label** field to choose a display color for the label and value.

Style: Select whether the color selected in the **Label** field appears as the background or foreground of the Chart.

Prefix: Add text before the single value.

Suffix: Append text after the single value.

Decimal places: Select the number of digits to the right of a decimal point.

Use 1000 separator (,): Display the single value with the , thousands separator. Enabled by default.

Apply threshold: Apply custom color threshold settings. Note that applying thresholds overwrites any color you may have selected in the **Label** field.

Enable **Apply threshold**, and then change or add custom colors and threshold values to change the display of the Chart.

8.1.2. Results Tables


Learn how to format tables that display search results.

Below every Chart is a results table that displays the Chart's data in numbers and/or text.

You can modify the table display, as well as some Chart visualization settings, in several ways. You'll find most of the available settings in each column's Settings drop-down:

1. On the **Chart** tab, scroll down to the table below the Chart.
2. Hover over the column header that contains the data you want to work with.
3. Select the Settings button ☰ to open the drop-down.
4. Select one of the three tabs on the drop-down:

- **General** ☰ - for plot settings, column sorting, stats info, and copying
- **Filter** - for filtering results based on search terms
- **Format** - for applying prefixes, suffixes, decimal places, and column colors



Settings drop-down/modal

You can use the grab handle at the top of the Settings drop-down to tear it off as a modal, and move it anywhere on the page. This way, it won't block the column you're modifying, and you can see your changes as you make them.


Changes made in the Settings drop-down apply only to the column selected when you opened the drop-down.

Adjust Plot Settings and Axis Colors

Adjust plot settings to change the display of column results in the associated Chart. You can choose which columns to display on the x-axis and y-axis, and you can change the color of column data in the Chart display.

You can open the plot menu in two ways:


- Select the plot icon y in a column header.
- On the **General** tab ☰ , select **Plot**.



Plot options on the General tab

View Stats

On the **General** tab ☰ , select **Stats** to see information about the fields returned from your search, including the data type and the count of unique field values.




Stats on the General tab

Sort Data

You can sort column results in ascending or descending order in two ways:


- Select the arrow buttons ⇕ that appear when you hover over a column header.
- On the **General** tab ☰ , select the arrow buttons next to **Sort**.



Sort arrows on the General tab

Filter Data

On the **Filter** tab ▼ , you can filter the results in a column by searching for a particular value.




Filter tab

Apply Column Formatting

The **Format** tab 🖌 provides the following options:

- Enter a **Prefix** or **Suffix** to be applied to every result in a column.

- **Format** can be a **Number**, **Currency**, or **Percentage**. You can specify the number of decimal places to show in a column. To display or hide the thousands separator, select or clear the **Use 1000 Separator (,)** check box.
    - **Currency** provides a drop-down with supported currencies.
- **Color** allows you to apply a value-based color palette to a column.



Format tab

When any field on this tab is modified, the Settings icon in the column header displays a blue dot to indicate that formatting is applied.

Display Multi-Value Columns

Some columns contain multi-value (array) fields. You can control how Cribl Search renders these columns, one column at a time, from the **Format** tab of the column **Settings** drop-down.

By default, Cribl Search displays each value in a multi-value field on its own line, which makes long lists easier to read than a single wrapped string. This works only for simple arrays, such as arrays of strings or numbers. Complex arrays, such as an array of objects or an array of arrays, are not formatted into individual values.

To change how an array column displays, open the column **Settings** drop-down, select the **Format** tab , then select an **Array** display option:


- **Split values** shows each value on its own line. You can hover over or select an individual value to open its field actions menu, and the actions apply to that value, not to the whole field.
- **Full list** shows all the values together as a single block of text.

These display options work together with word wrap. When you enable **Wrap cells**, long values wrap across multiple lines. When word wrap is disabled, values truncate to the column width.

These display options apply to Results Tables in Cribl Search and Notebooks. They are not available in Dashboards.

Show Line Numbers, Column Totals, and Row Totals

Select the gear button to the left of the results table to show or hide the display of line numbers, row totals, or column totals.



Toggles for line numbers, row totals, and column totals

8.2. Dashboards

Visualize your search results, using Dashboards.

Cribl Search offers customizable Dashboards with a variety of visualizations, in the form of panels, that you can tailor to fit your needs. Visualization panels are discrete units of displayed data that you can organize, interact with, and modify. A panel can be backed by a log search or, when Metrics (Preview) is enabled, by a metrics query.

You might add visualizations to a Dashboard to monitor server performance by time series and event timeline. Or, you might add visualizations to display customer behavior with donut charts and top-hitters lists.



Sample Dashboard

To start working with Dashboards, select **Dashboards** from the Cribl Search sidebar. To import Grafana Dashboards, select **Migrate**.

For details about who can access and modify this resource, see Search Member Permissions. With appropriate Permissions, you can export, share, and import Dashboards in Packs.

To zoom any Dashboard visualization panel up to a larger view, select the Actions ⋯ button at the panel's top right, then select **Full Screen**.

Cribl Search includes two Dashboards that you can use right away:

- **Search Monitoring** displays search status and CPU seconds over time, as well as details about completed searches and searches by user.
- **Sample Dashboard** provides examples of the types of data displays you can create with visualization panels.

These two Dashboards are standard for all users and cannot be edited. However, you can clone the Sample Dashboard and revise it for your own needs.



To quickly access your most recent Dashboards from any Cribl Suite product, select **Products** in the top bar, then hover over **Dashboards.**

8.2.1. Create A Dashboard

Learn how to create a Dashboard in Cribl Search.

You can create new Dashboards or add to existing Dashboards in several ways.

Create Dashboard From the Dashboards Tab

On the Dashboards page, you can create a new Dashboard and add visualization panels.

1. From the Cribl Search sidebar, select **Dashboards**.
2. Select **Add Dashboard**.
3. Give your new Dashboard a name and (optionally) a description.
4. Optionally, select or create a **Collection** to contain this Dashboard.
5. Optionally, configure a **Schedule** to automatically refresh your Dashboard at a set interval.
   For more details on Dashboard scheduling, see Refresh Your Dashboards Automatically.
6. When your basic configuration is complete, select **Save**.

The new Dashboard opens with a default **Time Range** Input already in place. Every visualization panel you add links to it automatically, so all panels share one time range. The Input doesn't count as Dashboard content, so the new Dashboard still presents the options for filling it.

Add Visualizations to a Dashboard

In the empty Dashboard that appears next, you'll see the following options:

- **Add Visualization Using Copilot**: This prompts you to specify a Dataset, and then prompts the Cribl Copilot AI to suggest visualizations for that Dataset. For details, see Add a Visualization when Creating a Dashboard.
- **Add Visualization**: This prompts you to specify a new or saved search, or a metrics query (Preview), and then define a corresponding chart type. For details, see New Search, Existing Search, and Add Metrics to Dashboards.
- **Add Group**: Create a collapsible section to organize related panels on the Dashboard. For details, see Create a Dashboard Group.
- **Add Input**: This prompts you to define a visualization panel constrained by a new or saved search, a range of values or numbers, a time range, or freeform text. For details, see Add Inputs to Your Cribl Search Dashboard.
- **Add Markdown**: This prompts you to define a visualization panel that offers users explanations or instructions on using your Dashboard. You can use markdown formatting to add arbitrary text, tables, and images. For details, see Add Markdown.

The last four options above are also available on the **Add** drop-down at the upper right. To get suggestions from Cribl Copilot after you've configured a Dashboard, see Add a Visualization when Editing a Dashboard.

Create Dashboard From the Products Sidebar

You can create a new Dashboard from the **Products** sidebar, too:

1. Select **Products** on the top bar.
2. In the **Products** sidebar, under **Search**, hover over **Dashboards** and select the **+** button.
3. In the **New Dashboard** modal, give your new Dashboard a name and (optionally) a description.
4. Optionally, select or create a **Collection** to contain this Dashboard.
5. Optionally, configure a **Schedule** to automatically refresh your Dashboard at a set interval. For more details on Dashboard scheduling, see Refresh Your Dashboards Automatically.
6. When your basic configuration is complete, select **Save**.



This flow does not add a default **Time Range** Input, unlike creating a Dashboard from the **Dashboards** page. To have all panels on the Dashboard share one time range, add a Time Range Input with the Input ID `time`.

Create Dashboard From Search Results

After performing a search, you can add it as a visualization panel to a new or existing Dashboard.

1. Select the **Actions** drop-down, and select **Add to Dashboard**.
2. Select whether you want to add the visualization to a new or existing Dashboard.
3. Select or name the Dashboard.
4. Enter the **Panel title**. This will be the name of the visualization panel in your Dashboard.
5. Select **Add & Go to Dashboard**.

The new panel links to the default **Time Range** Input on the Dashboard, rather than keeping the time range you ran the search with:

- On a **new** Dashboard, Cribl Search creates the Time Range Input using your search's time range, so the panel displays the same results at first.
- On an **existing** Dashboard, the panel adopts whatever time range the Time Range Input on that Dashboard is set to, and your search's own time range is disregarded.

To give the panel a time range independent of the Dashboard, unlink it.

Create Dashboard From the History or Saved Tab

Both in **History** and **Saved Searches**, you can turn any search in the list into a visualization panel, and add it to a new or existing Dashboard.

1. Select the Actions ⋯button to the right of a search and select **Add to Dashboard**.
2. Select whether you want to add the visualization to a new or existing Dashboard.
3. Select or name the Dashboard.
4. Enter the **Panel title**. This will be the name of the visualization panel in your Dashboard.
5. Select **Add & Go to Dashboard**.

The time range behavior is the same as when you add a search from search results. Adding a search to a Dashboard from a Notebook works the same way, too.



Wondering about the difference between saving a search and adding a search to a Dashboard? A saved search is a query that can be rerun to return new or updated data. You can add saved searches to Dashboards in the form of visualization panels. All saved searches are available to add to Dashboards, but adding a search to a Dashboard does not add it to the **Saved Searches** list.

Add a Panel From the Metrics Explorer (Preview)



Preview Feature

Cribl is still developing this Preview feature. We don't recommend using it in a production environment, because the feature might not be fully tested or optimized for performance, and related documentation could be incomplete.

Please continue to submit feedback through normal Cribl support channels, but assistance might be limited while the feature remains in Preview.

With the Metrics experience enabled, you can save a metrics query to a Dashboard as a visualization panel. Split-by dimensions are preserved as a trellis breakdown. See Add a Metrics Panel.

Create Dashboard From a Pack

You can import pre-built Dashboards from Packs, and you can also add Dashboards within a Pack.

A Dashboard you add within a Pack gets a default **Time Range** Input. An imported Dashboard keeps whatever Inputs its author defined.

8.2.2. Edit A Dashboard

Learn how to edit a Dashboard in Cribl Search.

Within a Dashboard, you can add and edit visualization panels. A panel can be backed by a log search or by a metrics query. You can also add Dashboard-level Inputs that apply to all visualizations on the Dashboard.



To edit the built-in Sample Dashboard, you need to clone it first. Go to **Dashboards** > **Sample Dashboard** > ⋯> **Clone**.

Add a Visualization

1. In an open Dashboard, select **Edit** at the top right, or press **E** on your keyboard.
2. From the **Add** drop-down, select **Visualization**.

If the Dashboard has a default **Time Range** Input, the new panel links to it automatically, and its date and time field reads **Linked to time**. The panel then follows the time range that viewers select for the Dashboard. To give the panel a time range of its own, unlink it.

Next, choose how to define your visualization: review Cribl Copilot AI suggestions, configure the visualization from a new or existing search, or choose a metrics query as the source.

To have Cribl Copilot suggest visualizations that display your data effectively:

1. At the top of the page, select the Cribl Copilot button .
2. The right drawer, now labeled **Copilot**, will prompt you to select or change the base Dataset for this visualization.
3. From the tiles that Cribl Copilot suggests, select **Add** to add the visualization you choose.

For details, see Add a Visualization when Editing a Dashboard.

New Search

If you want to base your visualization on a **New Search** (the default setting in the right drawer):

1. Either enter your query directly, or select a **Parent search ID** to pre-populate your query from a parent search (see Apply a Parent Search below).
2. Optionally, if you've started with a parent search, you can append terms to the query before proceeding.
3. Select **Search**.

To start over, select **Reset**. This clears the query and all chart settings.

Existing Search

If you prefer to base your visualization on an existing saved search (which can be a scheduled search):

1. In the right drawer, select **Saved**.
2. Select a **Saved search ID** to populate your query.
3. Optionally, append terms to the query before proceeding.
4. Set the **Run mode**:
    - **Run as new search** - Always rerun the query, even if the Dashboard has data caching enabled.
    - **Fetch results from last run** - Get results from the most recent run. (If the Dashboard has data caching enabled, Cribl Search will ignore this setting.) Cribl recommends selecting this option if you're basing this visualization on a scheduled search.
5. Select **Search**.

To start over, select **Reset**. This clears the query and all chart settings.

Metrics Query (Preview)



Preview Feature

Cribl is still developing this Preview feature. We don't recommend using it in a production environment, because the feature might not be fully tested or optimized for performance, and related documentation could be incomplete.

Please continue to submit feedback through normal Cribl support channels, but assistance might be limited while the feature remains in Preview.

To use a metrics query as the source of a visualization, instead of a log search, choose a metrics query and build it as you would in the Metrics Explorer. For the full add flow, including saving a query from the Explorer, see Add Metrics to Dashboards.

You edit, hide, rearrange, and refresh metrics panels the same way as other panels. Metrics panels also follow the Dashboard time range, auto-refresh, and shared crosshairs.

Edit a Visualization

To edit an existing visualization:

1. Open an existing Dashboard.
2. At the top right of the visualization panel you want to modify, select **Edit** . Depending on the layout, you might need to select the Actions ⋯ button first.

3. Edit the visualization just like you edit a Chart display. The options available depend on the Chart type used.

If you add a visualization by creating a new search, you'll see additional options to configure the type, format, and data display of the visualization.

If you create a visualization from a saved search, you can select **Edit** at the visualization panel's top right to revise the visualization.

Hide a Visualization

You can hide any visualization panel by editing it and selecting the **Hide this visualization** check box.

- In Dashboard edit mode, hidden panels are collapsed into a **Hidden Panels** section.
- To unhide a panel, edit the panel and clear the **Hide this visualization** check box.

Interact with Visualizations in a Dashboard

Within any visualization panel, you can hover over graphics or expand list events to see more details. Also, the Actions ⋯ buttons on the Dashboard, and on individual panels, offer further options.

Synchronize Crosshairs and Tooltips

When you hover over a time-series panel, Cribl Search marks that point in time with a crosshair and shows a tooltip with the values under your pointer. To extend the crosshair across the Dashboard, select the Dashboard's Actions ⋯ button, then use these toggles:

- **Synchronize Pointers**: Draws the crosshair at the same timestamp on every other time-series panel. Each panel continues to show only its own tooltip.
- **Synchronize Tooltips**: Draws the crosshair and shows each panel's own tooltip at that same timestamp, across all time-series panels. This includes pointer synchronization, so **Synchronize Pointers** stays selected and read-only while tooltip synchronization is on.

Synchronization covers the time-series panels linked to the same Time Range Input, including both log panels and metrics panels, so you can align a spike in one panel with what happened in the others at that moment. Cribl Search saves your choice with the Dashboard, so it persists across reloads and applies to everyone who opens the Dashboard. Both toggles are off until you turn them on.

Organize Dashboard Layout

Rearrange Visualization Panels

To arrange the visualizations in a Dashboard, select **Edit** at the top right, or press **E** on your keyboard. Use the drag handle at the top of any panel to drag it to a new position, and use the resize handle at the bottom right or left to resize it.

Create a Dashboard Group

You can organize related panels into **Groups**. Groups create labeled sections within a Dashboard and can be collapsed or expanded to simplify large Dashboards.

To create a group:

1. Open a Dashboard and select **Edit** .
2. Create the group:
    - If the Dashboard is empty, select **Add Group**.
    - If the Dashboard already has content, select **Add** > **Group**.
3. Enter a **Group title**, then select **Save**.

Add Panels to a Group

While in **Edit** mode, from the group header select **Add**, then choose one of the following:

- **Visualization**
- **Markdown**

Configure the panel and save it.

Move Panels Into or Between Groups

While in **Edit** mode, drag panels into the group container. You can also drag panels between groups or move them out of a group.

Manage Groups

From the group header, you can:

- **Rename** the group using the **More actions** menu and selecting **Edit**.
- **Reorder** groups using the **More actions** menu and selecting **Move Up** or **Move Down**.
- **Collapse or expand** the group to show or hide its panels.

Delete a Group

1. In the group header, open the **More actions** menu.
2. Select **Delete**.

Deleting a group also deletes the panels inside it. Move panels out of the group first if you want to keep them.


Refresh Visualizations

Refresh the data in a visualization by selecting the Refresh button at the top right of the panel.

To refresh all visualizations on the Dashboard automatically, see Refresh Your Dashboards Automatically.

Manage Visualizations

Select a visualization panel's own Actions ···button to expose the menu options shown below.



Visualization actions

The options here include:

- **Edit**: Opens the visualization panel for editing.
- **Clear Cache and Refresh**: A hard refresh of the visualization, to match current underlying data.
  To refresh all visualizations on the Dashboard automatically, see Refresh Your Dashboards Automatically.
- **Open Search Details**: Opens a read-only version of the Details modal, listing the search's query expression, execution times, and duration.
- **Open in Search**: Opens an editable version of the query expression.
- **Open in Metrics**: On a metrics panel, opens the panel's query in the Metrics Explorer, with filters, split-by dimensions, visualization options, and time range already applied.
- **Full Screen**: Zooms up an expanded display of the visualization, in a modal within your browser window.
- **Copy to Clipboard**: Copies the current visualization, as a static image, to the system clipboard.

- **Export Visualization as PNG/JPG**: Saves the current visualization as a static image in `.png` or `.jpg` format.

Apply a Parent Search

To reduce effort and significantly improve Dashboard loading time, you can reuse search results by saving them as **parent searches**. You can instantly add an existing search query to a visualization panel by designating another visualization in the same Dashboard as the parent search. This enables you to aggregate results from both searches into the same visualization.

1. Edit an existing Dashboard, and then select **Edit** at the top right of the visualization panel you want to modify.
2. Under **Parent search**, select the name of the visualization you want to use as the parent.
3. The parent search query becomes the new first line of your query in the **Search** box. Select **Search** to test your new aggregate query, and then select **Save** to save your Dashboard.

Hide a Parent Search

You can hide any visualization by editing it and selecting the **Hide this visualization** check box. This can be especially useful for visualizations you create for the sole purpose of acting as parent searches.

Parent Search Limitations

You can apply only one parent search per visualization panel.

When you apply a parent search, child searches wait until the parent search has completed. So you will not see "preview" results.

When you've applied a parent search to a visualization, and you open that visualization (using **Actions** > **Open in Search**), you won't be able to edit the child search's time parameters. This is because the child search is using the parent search's time span.

Like any other search, parent searches are bound by system limits and **system** Usage Group limits. Any aggregations in the child search will be based on the parent search's results, so if the parent search's results are capped, the child search's aggregations may be incomplete.

Add Inputs

To enable viewers to filter and control visualizations in your Dashboard, you can add Dashboard-level Inputs. For more information, see Add Inputs to Your Cribl Search Dashboard.


Add Interactions

To enable viewers to drill down into details when they select Dashboard data points, you can add Interactions to visualization panels. For more information, see Add Interactions to Your Cribl Search Dashboard.

Add Markdown

You can add a Markdown panel to your Dashboard to enrich it with any custom text. Use markdown to add explanations, captions, and additional information to your Dashboard. To add a Markdown panel:

1. In an open Dashboard, select **Edit** at the top right, or press **E** on your keyboard.
2. From the **Add** drop-down menu, select **Markdown**.
3. In the **Edit** pane, replace the sample text with any markdown content you want.
   The panel lets you use the features of Github-flavored markdown, including links, tables, codeblocks, and images (linking to external sources).
   You can also use tokens, defined in Inputs, surrounded by `$`. For example, if the Input ID is `firstname`, reference `$firstname$` in the markdown.
   As you edit, you will see a live preview of the rendered text.
4. Select **Save**.



Markdown panel with the pre-built markdown sample

The Markdown panel doesn't support raw HTML.

Rename a Dashboard

To change the name of an existing Dashboard:

1. From the Cribl Search sidebar, select **Dashboards**.
2. Select the row of the Dashboard that you want to rename.
3. At the top, next to the current Dashboard name, select **Settings**, and then select the **Edit** button.
4. Enter the new Dashboard name, and select **Save**.

Edit Dashboards as JSON

You can edit your Dashboards in a JSON editor built into Cribl Search, or import and export JSON files with complete configurations. This can significantly speed up setting up more complex Dashboards.

To edit an existing Dashboard as JSON:

1. From the Cribl Search sidebar, select **Dashboards**, and open a Dashboard.
2. At the top right, select the Actions ⋯button.
3. Select one of the following:
    - **Edit as JSON** to open the Dashboard configuration in the Cribl Search JSON editor.
    - **Copy Dashboard JSON** to copy the Dashboard JSON to clipboard.
    - **Export Dashboard JSON** to download a JSON file with the Dashboard configuration.
    - **Import Dashboard JSON** to upload a JSON file with a new configuration.

Refresh Your Dashboards Automatically

You can refresh a Dashboard automatically, either by running it on schedule, or by configuring its caching.


Configure Caching for a Dashboard

You can modify the time for which a Dashboard is cached (in other words, how often it is refreshed). This setting is configured within the **Schedule** section of the Dashboard Settings modal.

1. If you are creating a new Dashboard:
    - Start creating a Dashboard. The **New Dashboard** modal opens automatically.
2. If you are modifying an existing Dashboard:

- Open an existing Dashboard.
- Select the gear ( ) icon near the Dashboard name.
- In the dialog, select **Edit** to open the **Edit Dashboard** modal.

3. Under **Schedule**, select **Cache data**.
4. In **Cache data for**, set the time-to-live (TTL) for the Dashboard cache. This setting defines how often data in the Dashboard is refreshed.



Configuring caching for a new Dashboard

Run a Dashboard on Schedule

You can schedule the searches on **all** visualizations in a Dashboard to refresh on the default interval you define.

This can be advantageous on a Dashboard where you don't need to display up-to-the-minute data, but you prefer not to wait for the display to refresh. Schedule the underlying searches to refresh daily, hourly, or every few minutes. When the visualizations render, they'll fetch the results from the last scheduled run.


After scheduling the Dashboard as a whole, you retain the option to customize the schedules of the searches that underlie individual visualization panels and Inputs.

To run a Dashboard on a schedule:

1. If you are creating a new Dashboard:
   - Start creating a Dashboard. The **New Dashboard** modal opens automatically.
2. If you are modifying an existing Dashboard:
   - Open an existing Dashboard.
   - Select the gear ( ) icon near the Dashboard name.

- In the dialog, select **Edit** to open the **Edit Dashboard** modal.

3. Under **Schedule**, select **Run on schedule**.
4. Configure one of the two:
   - Define the timezone, the base interval (anything from `year` down to `minute`), and refresh time.
   - Or, define a **Cron** schedule string.
5. In **Keep last executions**, define how many past versions of the Dashboard data to keep.
   This is a rolling buffer
   - on each refresh of the Dashboard, Cribl Search will purge the oldest version beyond this count. Defaults to `2`.



Setting a schedule for a new Dashboard

Changing Scheduled Dashboard Ownership

If the creator of a scheduled Dashboard is no longer an active Cribl Search Member, active Members with access to the Dashboard will be unable to re-run the Dashboard. They will need to export the Dashboard configuration, then re-create the Dashboard by importing the config, and finally schedule the new Dashboard to run under their ownership.

Cloning a Scheduled Dashboard

When you clone a Dashboard that has **Run on schedule** enabled, the schedule is automatically disabled in the cloned copy.

The schedule configuration (timezone, interval, or Cron string) is preserved, but it must be manually re-enabled. This prevents unintended duplicate scheduled searches.

Re-Enable a Schedule on a Cloned Dashboard

1. Open the cloned Dashboard.
2. Select the gear ( ) next to the Dashboard title.
3. In the dialog, select **Edit** to open the **Edit Dashboard** modal.

8.2.3. Add Interactions To Your Cribl Search Dashboard

Enable Dashboard viewers to drill down into specific values in a visualization panel.

Why Use Dashboard Interactions

Interactions enable Dashboard viewers to take action directly from visualizations. By clicking on data points, users can trigger context-driven searches, follow external URLs, or open other Dashboards filtered by the value clicked.

This helps you design a seamless workflow that connects your Dashboard to other Cribl or third-party tools and resources, resulting in a smooth data experience for people consuming your Dashboards.

Dashboard Interaction Types

An Interaction controls what happens when you click on a specific data point on your Dashboard. Each Interaction can trigger one of the following actions:

- Run a new search, filling the query with the value clicked and other contextual information.
- Open an external link, enriching the URL with the value clicked or with metadata about the user's Cribl.Cloud Workspace.
- Open another Dashboard, populating one of its Inputs with the value clicked or other context.

Add a Dashboard Interaction



Map and Gauge visualizations do not support Interactions. The **Interactions** tab does not appear in the **Edit Visualization** drawer for these visualization types.

To an Existing Visualization | To a New Visualization | To a New Dashboard

1. Go to the **Dashboards** page in Cribl Search: On the top bar, select **Products** > **Search** > **Dashboards**.
2. Open a Dashboard.
3. Select **Edit** at the top right, or press **E** on your keyboard.
4. At the top right of the visualization panel you want to modify, select the **Edit** button. The **Edit Visualization** drawer opens.
5. At the bottom of the drawer, select **Interactions**.
6. Configure the Interaction you want. For more information, see Interaction Types.

7. At the top of the Dashboard, select **Save**.

Run a New Search From a Visualization

You can set up a visualization so that clicking on it runs a new search.

For this, add a **Run a New Search** Interaction:

1. Start adding or editing a Dashboard visualization panel.
2. At the bottom of the **Edit Visualization** drawer, select **Interactions**.
3. From the **Action** drop-down, select **Run a new search**.
4. Enter your search query. (See the examples below.)
5. At the top of the Dashboard, select **Save**.

Your search query can reference the following tokens:

- `$earliest$`
- `$environment.baseUrl$`
- `$environment.type$`
- `$environment.workspace$`
- `$field.name$`
- `$field.value$`
- `$latest$`
- `$rowData.<fieldname>$`
- `$value$`

Example 1 **Example 2**

If you configure a **Run a new search** Interaction with this query using the $value$ token...

```
dataset="users" email=$value$ | project id, email, last_login
```

Copy

...then clicking on `sam@example.com` triggers this query...

```
dataset="users" email="sam@example.com" | project id, email, last_login
```

Copy

...encoded in this URL:

```
https://<yourWorkspace>-<yourCloudInstance>.cribl.cloud/search/new?q=dataset%3D%22
```

Copy

For an Interaction to pass time parameters, it must either link to a Time Range Input directly, or have no time picker at all. If an Interaction links to a parent search that has a timepicker, it will fail.

Open a URL From a Visualization

You can set up a visualization so that clicking on it opens an external URL.

For this, add an **Open External Link** Interaction:

1. Start adding or editing a visualization on your Dashboard.
2. At the bottom of the **Edit Visualization** drawer, select **Interactions**.
3. From the **Action** drop-down, select **Open external link**.
4. Enter a URL. (See the example below.)
5. At the top of the Dashboard, select **Save**.

The URL can reference the following tokens:

- `$earliest$`
- `$environment.baseUrl$`
- `$environment.type$`
- `$environment.workspace$`
- `$field.name$`
- `$field.value$`
- `$latest$`
- `$rowData.<fieldname>$`
- `$value$`

Example

If you configure an **Open external link** Interaction with this URL...

```
https://www.virustotal.com/gui/domain/$value$
```

Copy

...then clicking on a data point with the value of `server1` opens this URL:

```
https://www.virustotal.com/gui/domain/server1
```

Copy

Include Your Organization and Workspace in a URL

To construct a URL that includes your Cribl.Cloud Organization and Workspace, use the `$environment.baseUrl$` token.

For example, if you configure an **Open external link** Interaction with this URL...

```
$environment.baseUrl$
```

Copy

...then clicking on the visualization in a Workspace named `main`, in an Organization called `amazing-heady-brcc3nr`, opens this URL:

```
https://main-amazing-heady-brcc3nr.cribl.cloud
```

Copy


Open Another Dashboard From a Visualization

You can set up a visualization so that clicking on it opens another Dashboard.

You can also pass the value clicked to one of the target Dashboard's Inputs, effectively filtering the new Dashboard by that value.

1. Start adding or editing a visualization on your Dashboard.
2. At the bottom of the **Edit Visualization** drawer, select **Interactions**.
3. From the **Action** drop-down, select **Add value to dashboard input**.

4. From the **Dashboard** drop-down, select the target Dashboard.
5. From the **Input** drop-down, select one of the target Dashboard's Inputs.
6. At the top of the Dashboard, select **Save**.



Interaction with an Input

Dashboard Interaction Tokens Reference

Tokens are placeholders that get replaced with actual values when an Interaction is triggered.

A token can be a **static** value, such as a specific string, or **dynamic**, such as the value of a field that was clicked.

You can use the following tokens in your Interactions:

Token	Type	Description
`$earliest$`	Static	The start timestamp of a time range to use.
`$environment.baseUrl$`	Static	The base URL of the user's Cribl.Cloud Organization.
`$environment.type$`	Static	The type of the user's Cribl.Cloud Workspace (`development`, `staging`, or `production`).
`$environment.workspace$`	Static	The name of the user's Cribl.Cloud Workspace.
`$field.name$`	Dynamic	The name of the field clicked.
`$field.value$`	Dynamic	The value of the field clicked.
`$latest$`	Static	The end timestamp of a time range to use.
`$rowData.<fieldname>$`	Dynamic	The value of the specified field in the clicked row.
`$value$`	Dynamic	The value of the data point clicked.

$earliest$

The start timestamp of a time range to use with the `timestats` operator.

Token Type	Interactions Types Supported
Static	Open an external link Run a new search

For example, if you configure a **Run a new search** Interaction with this query...

```
dataset="cribl_search_sample" | timestats count by host | where _time >= $earliest$
```

Copy

...and the current time range is `earliest=1729290112 latest=1729376512`, clicking the visualization triggers this query...

```
dataset="cribl_search_sample" | timestats count by host | where _time >= 1729290112
```

Copy

...encoded in this URL:

```
https://<yourWorkspace>-<yourCloudInstance>.cribl.cloud/search/new?q=dataset%3D%22cri
```

Copy

$environment.baseUrl$

The fully qualified base URL of the Cribl.Cloud Organization in which the user triggered the Interaction.

Token Type	Interactions Types Supported
Static	Open an external link Run a new search

The base URL includes:

- `https://` prefix
- Workspace name (`$environment.workspace$`)

- Organization ID (e.g., `amazing-heady-brcc3nr`)
- Environment type (`$environment.type$`)
- `cribl.cloud` suffix

For example, if you configure an **Open external link** Interaction with this URL...

```
$environment.baseUrl$/status
```

Copy

...for an Organization with the base URL `https://main-amazing-heady-brcc3nr.cribl.cloud`, the Interaction opens this URL:

```
https://main-amazing-heady-brcc3nr.cribl.cloud/status
```

Copy

`$environment.type$`

The type of the Cribl.Cloud Workspace in which the user triggered the Interaction. Possible values are: `development`, `staging`, or `production`.

Token Type	Interactions Types Supported
Static	Open an external link Run a new search

For example, if you configure an **Open external link** Interaction with this URL...

```
status.$environment.type$.example.com
```

Copy

...for a Workspace of type `production`, the Interaction opens this URL:

```
status.production.example.com
```

Copy

$environment.workspace$

The name of the Cribl.Cloud Workspace in which the user triggered the Interaction.

Token Type	Interactions Types Supported
Static	Open an external link Run a new search

For example, if you configure a **Open external link** Interaction with this URL...

```
dashboards.example.com/$environment.workspace$
```

Copy

...for a Workspace named `marketing`, the Interaction opens this URL:

```
dashboards.example.com/marketing
```

Copy

$field.name$

The name of the field clicked.

Token Type	Interactions Types Supported
Dynamic	Open an external link Run a new search

For example, if you configure a **Run a new search** Interaction with this query...

```
dataset="cribl_search_sample" | where $field.name$="foo"
```

Copy

...then clicking on a field named `host` triggers this query...

```
dataset="cribl_search_sample" | where host="foo"
```

Copy

...encoded in this URL:

```
https://<yourWorkspace>-<yourCloudInstance>.cribl.cloud/search/new?q=dataset%3D%22cri
```

Copy

$field.value$

The value of the field clicked.

Token Type	Interactions Types Supported
Dynamic	Open an external link Run a new search

For example, if you configure a **Run a new search** Interaction with this query...

```
dataset="cribl_search_sample" | where status=$field.value$
```

Copy

...then clicking on a field with the value `200` triggers this query...

```
dataset="cribl_search_sample" | where status="200"
```

Copy

...encoded in this URL:

```
https://<yourWorkspace>-<yourCloudInstance>.cribl.cloud/search/new?q=dataset%3D%22cri
```

Copy

$latest$

The end timestamp of a time range to use with the `timestats` operator.

Token Type	Interactions Types Supported
Static	Open an external link Run a new search

For example, if you configure a **Run a new search** Interaction with this query...

```
dataset="cribl_search_sample" | timestats count by host | where _time <= $latest$
```

Copy

...and the current time range is `earliest=1729290112 latest=1729376512`, clicking the visualization triggers this query...

```
dataset="cribl_search_sample" | timestats count by host | where _time <= 1729376512
```

Copy

...encoded in this URL:

```
https://<yourWorkspace>-<yourCloudInstance>.cribl.cloud/search/new?q=dataset%3D%22cri
```


Copy

`$rowData.<fieldname>$`

The value of a specific field in the clicked row (regardless of which row was actually clicked). Replace `<fieldname>` with a real field name.

Token Type	Interactions Types Supported
Dynamic	Open an external link Run a new search

Example



A visualization panel of the **Events** type

If you configure the visualization above with a **Run a new search** Interaction like this...

```
dataset="cribl_search_sample" | where method=$rowData.method$ & count=$rowData.count_
```

Copy

...then no matter whether the user selects `count\_: 66` or `method: GET`, the Interaction runs a query with both...

```
dataset="cribl_search_sample" | where method=GET & count=66
```

Copy

...encoded in this URL:

```
https://<yourWorkspace>-<yourCloudInstance>.cribl.cloud/search/new?q=dataset%3D%22cri
```

Copy

$value$

The value of the data point clicked.

Token Type	Interactions Types Supported
Dynamic	Open an external link Run a new search

For example, if you configure a **Run a new search** Interaction with this query...

```
dataset="cribl_search_sample" | where host=$value$
```

Copy

...then clicking on a data point with the value of `server1` triggers this query...

```
dataset="cribl_search_sample" | where host="server1"
```

Copy

...encoded in this URL:

```
https://<yourWorkspace>-<yourCloudInstance>.cribl.cloud/search/new?q=dataset%3D%22cri
```

Copy

8.2.4. Add Inputs To Your Cribl Search Dashboard

Enable Dashboard viewers to control visualizations through interactive widgets.

Why Use Dashboard Inputs

An Input is a small interactive area at the top of your Dashboard. When a user selects or enters values, the linked visualizations update to reflect the new criteria. This allows Dashboard viewers to quickly filter data, without needing to directly edit the underlying search queries.

Dashboard Input Types

Using different types of Inputs, you can enable Dashboard viewers to:

- Change the time range of visualizations, with a **Time Range** Input. New Dashboards include a default Time Range Input.
- Filter visualizations by freeform text, with a **Text** Input.
- Filter visualizations by numbers, with a **Number** Input.
- Filter visualizations by a preconfigured set of dynamic values, with a **Dropdown** Input.



Different types of Dashboard Inputs

Add a Dashboard Input

To add an Input to a new or existing Dashboard:

1. Go to the **Dashboards** page in Cribl Search: On the top bar, select **Products** > **Search** > **Dashboards**.
2. In an open Dashboard, select **Edit** at the top right, or press **E** on your keyboard.
3. At the top right, select **Add** > **Input**. Give the Input a title.
4. Set the Input ID. You'll reference this ID in the searches that you want the Input to control. Use alphanumeric characters, underscores, and hyphens only.
5. In the **Type** drop-down, select the Input type you want. See the details about each type:
    - Time Range
    - Text
    - Number
    - Dropdown
6. When done, select **Save** at the top of the Dashboard. (To skip this step, see Auto-Apply Input Changes.)

Now, link the Input to one or more visualizations in the Dashboard.


Link a Dashboard Input to a Visualization

After adding an Input to a Dashboard, you need to link it to one or more visualization panels. This way, when a user interacts with the Input, the linked visualizations update accordingly.

1. Add an Input to your Dashboard.
2. Add or edit a visualization panel that you want to control.
3. Depending on the Input type, follow the specific linking instructions:
    - Time Range
    - Text
    - Number
    - Dropdown

Enable Viewers to Change the Time Range of a Visualization

With a **Time Range Input**, you can enable viewers to control the time range of the visualization panels using a timepicker at the top of your Dashboard.



A Time Range Input

The Default Time Range Input

New Dashboards come with a Time Range Input already in place, so you don't have to add one and link each panel by hand. It's titled **Time Range**, its Input ID is `time`, and its default value is the last hour.

Every visualization panel you add afterward links to this Input automatically. As a result, all panels on the Dashboard share one time range, and viewers can change the time range for the whole Dashboard in one place.

Cribl Search adds the default Time Range Input when you:

- Create a Dashboard from the **Dashboards** page, including within a Pack.
- Add a search to a new Dashboard from search results, the **History** or **Saved Searches** tab, or a Notebook. In this case, the Input takes its default value from the time range of the search you added.

Auto-linking depends only on the Input ID. As long as a Dashboard has a Time Range Input whose ID is `time`, new panels link to it. So you can retitle, move, or recreate the default Input without losing auto-linking. You can also enable auto-linking on an older Dashboard, by adding a Time Range Input with the ID `time`.

Deleting the default Input is also allowed, but it affects your panels:

- Panels you add afterward are no longer linked. Each one gets its own time range, set to the last hour.
- Panels that were already linked keep pointing at the Input you deleted, and their date and time field reads **Invalid input link**. Give each one its own time range, or add a Time Range Input with the ID `time`

again to restore the link.

Cribl Search does not add the default Time Range Input when you create a Dashboard from the **Products** sidebar or through the API. Cloning a Dashboard, or importing a Dashboard configuration into an existing Dashboard, keeps the Inputs that are already defined. In all these cases, add a Time Range Input yourself if you want panels to share a time range.

Add a Time Range Input


To add a **Time Range Input** to a Dashboard that doesn't have one:

1. In an open Dashboard, select **Edit** at the top right, or press **E** on your keyboard.
2. At the top right, select **Add** > **Input**. Give the Input a title.
3. Set the Input ID. Use alphanumeric characters, underscores, and hyphens only.
   Use the ID `time` if you want new panels to link to this Input automatically.
4. In the **Type** drop-down, select **Time Range**.
5. Set the **Default value** in the timepicker. This is the time range applied when the Dashboard first loads. You can select a calendar period such as **Yesterday** or **Previous month**, or set a custom range. For the calendar presets, see Quick Actions.
6. When done, select **Save** at the top of the Dashboard. (To skip this step, see Auto-Apply Input Changes.)
   The new Input appears at the top of your Dashboard, where you can edit, clone, or delete it.

Link a Visualization to a Time Range Input

Panels that Cribl Search didn't link for you, and panels that you've unlinked, need to be linked manually:

1. Add or edit a visualization panel that you want to control.
2. Select the clock button in the date and time selector.
3. Select the **Link** tab.
4. In **Time range input**, select the Time Range Input to link to, and then select **Apply**.
   The visualization's date and time field now reads **Linked to** the Input ID.



Time range with linked Input

Now, when viewers select a time range in the Input, the linked visualizations update.

If the field reads **Invalid input link**, the panel points at an Input ID that no longer exists on the Dashboard. Either link the panel to an existing Input, or give the panel its own time range.

Unlink a Visualization from a Time Range Input

To give a panel a time range of its own, independent of the Time Range Input on the Dashboard:

1. Edit the visualization panel.
2. Select the clock button in the date and time selector.
3. On the **Relative**, **Date Range**, or **Around** tab, set the time range you want, and then apply it. Setting a time range directly replaces the link, and the panel keeps this time range no matter what viewers select in the Input.


Set the Time Range by Dragging Across a Chart

Viewers can narrow the shared time range straight from a chart, without opening the timepicker. On a chart panel whose horizontal axis is time, drag across the area you want to inspect. When you release, the Time Range Input updates to the range you selected, and every panel linked to that Input reruns.

This works only on panels that are linked to a Time Range Input. Panels with their own time range, and charts that don't plot time on the horizontal axis, ignore the drag.

Enable Viewers to Filter a Visualization by Text

Using a **Text Input**, you can enable Dashboard viewers to enter freeform text so that linked visualization panels display only data with that text value. Think of this as a free-text search box.



A Text Input

First, add a **Text Input**:

1. In an open Dashboard, select **Edit** at the top right, or press **E** on your keyboard.
2. At the top right, select **Add** > **Input**. Give the Input a title that gives the Dashboard viewer an idea of what they can type.
3. Set the Input ID. Use alphanumeric characters, underscores, and hyphens only.
4. In the **Type** drop-down, select **Text**.
5. Set the text field's **Default value**. This is the filter applied when the Dashboard first loads.
6. When done, select **Save** at the top of the Dashboard. (To skip this step, see Auto-Apply Input Changes.) The new Input appears at the top of your Dashboard, where you can edit, clone, or delete it.


Then, link your Text Input to one or more visualizations:

1. Add or edit a visualization panel that you want to filter.
2. In the visualization's search query, reference the **Input ID** of the Text Input you just created. Surround the ID by `$`. For example, if the Input ID is `firstname`, use `$firstname$`.

Now, when viewers type into the Input text field, the linked visualizations update.

Enable Viewers to Filter a Visualization by Numbers

Using a **Number Input**, you can enable Dashboard viewers to filter visualizations by a number they enter into a simple text area at the top of your Dashboard.



A Number Input

First, add a **Number Input**:

1. In an open Dashboard, select **Edit** at the top right, or press **E** on your keyboard.
2. At the top right, select **Add** > **Input**. Give the Input a title that gives the Dashboard viewer an idea of what they can type.
3. Set the Input ID. Use alphanumeric characters, underscores, and hyphens only.
4. In the **Type** drop-down, select **Number**.
5. Set the number field's **Default value**. This is the filter applied when the Dashboard first loads.
6. You can set the **Minimum value** and **Maximum value**, to restrict what viewers can enter.
7. When done, select **Save** at the top of the Dashboard. (To skip this step, see Auto-Apply Input Changes.) The new Input appears at the top of your Dashboard, where you can edit, clone, or delete it.

Then, link your Number Input to one or more visualizations:


1. Add or edit a visualization panel that you want to filter.
2. In the visualization's search query, reference the **Input ID** of the Number Input you just created. Surround the ID by `$`. For example, if the Input ID is `value`, use `$value$`.

Now, when viewers type into the Input number field, the linked visualizations update.

Enable Viewers to Filter a Visualization by Drop-Down Options

Using a **Dropdown Input**, you can enable Dashboard viewers to filter visualizations by selecting one or more values from a drop-down list at the top of your Dashboard.

The list of values can be static or dynamic. With a static list, you configure all the options available to the user. With a dynamic list, the results of a search provide the values for the drop-down.



A Dropdown Input

First, add a **Dropdown Input**:

1. In an open Dashboard, select **Edit** at the top right, or press **E** on your keyboard.
2. At the top right, select **Add** > **Input**.
3. Set the Input ID. Use alphanumeric characters, underscores, and hyphens only.
4. In the **Type** drop-down, select **Dropdown**.
5. Select how to populate the drop-down list: **New search**, **Saved search**, or **Manually add dropdown items**.
6. In the **Field name** (with the search options) or in the **Values** (with the manual option), enter a caption to help the viewer understand the item's purpose.
7. When done, select **Save** at the top of the Dashboard. (To skip this step, see Auto-Apply Input Changes.) The new Input appears at the top of your Dashboard, where you can edit, clone, or delete it.

8.2.5. Add Cribl Search Visualizations With Cribl Copilot

Use the Cribl Copilot AI assistant to generate Dashboard visualizations.


As an alternative to designing Dashboard visualizations from scratch, you can use the Cribl Copilot visualization assistant to analyze your Dataset and suggest effective display options. You can then adapt one of the initial suggestions, request different suggestions, or reject all suggestions and configure your own visualization.

> Cribl AI is available by default. To manage AI features and model providers for all Cribl products in your Organization, select **Settings** > **Global** > **AI Settings**. See Cribl AI Availability for details.

Add a Visualization from a Dataset


Cribl Copilot can suggest visualizations directly from the **Logs** page, using either of these entry points:

- Hover your pointer over any Dataset to expose a **Visualize** button, as shown below.
- In the Dataset list, open the actions ⋯menu and select **Visualize**. This menu also offers **Search Now**, **Settings**, and, where available, **Enable Dataset Intelligence**.



Cribl Copilot Visualize button


Select the button, and a **Visualize Dataset** drawer will open on the right. Here, Cribl Copilot will analyze the selected Dataset. After a few seconds, if the analysis is successful, the drawer will suggest three visualizations that might be useful in displaying the discovered data. Above the visualization panels, you will also see several buttons to generate alternative queries.



Suggested visualizations for your Dataset

You have the following options here:

- To accept one of the suggested visualizations, select its Actions ⋯ button (upper right), then select **Add to Dashboard**.
- To substitute a new query and generate a different set of visualizations, select one of the three buttons at the top right. As shown below, this will open a corresponding natural language prompt in a new query box. Refine the query as desired, then select the Send button - or press `Enter/return` - to see your new visualization options.
- Select **Write your own**. This will open a similar query box, where you can describe your own natural language query from scratch. As with the predefined query buttons, this will generate new suggested visualizations.




Adapt a new query to suggest new visualizations

Add a Visualization when Creating a Dashboard

When you add a new Dashboard, you can use Cribl Copilot to generate suggested visualizations.

1. From the Cribl Search sidebar, select **Dashboards**.
2. Select **Add Dashboard**.
3. Give your Dashboard a name, configure any additional settings you want, and then select **Save**.
4. Select **Add Visualization Using Copilot**.



Add Visualization Using Copilot button

5. Select the Dataset you want to use as your visualization's base.

   Soon, Cribl Copilot will display three recommended visualizations. (This could take up to several minutes with large Datasets.)

6. Select **Add** to add any suggested visualization to your new Dashboard, or select **Refresh** to generate three new visualizations.
7. You're now working in edit mode (described in the following section).

   To add more visualizations, select the Cribl Copilot button near the upper right.

Add a Visualization when Editing a Dashboard

When you're editing an existing Dashboard, you can use Cribl Copilot to generate suggested visualizations.


1. From the Cribl Search sidebar, select **Dashboards**.
2. Select the Dashboard you want to edit.
3. Select the Actions button at the upper right, and then select **Edit**.
4. Near the upper right, select the Cribl Copilot button .

   If the Dashboard is empty, you'll instead see the **Add Visualization Using Copilot** option, described in the preceding section.
5. From the list on the right, select the Dataset you want to use as your visualization's base.

   Soon, Cribl Copilot will display three recommended visualizations. (This could take up to several minutes with large Datasets.)
6. Select **Add** to add any visualization to your new Dashboard, or select **Refresh** to generate three new suggested visualizations.

You have two additional options when editing an existing Dashboard:

- To replace the Dataset used for your visualization, select **Change Dataset**.
- To refine your results, describe your preferences in everyday language in the text box at the top of the Copilot drawer.


Copilot
Generate only donut charts
cribl_internal_logs
Change Dataset
Suggested Visualizations
Request Count by Method
count_
PATCH
POST
null
null
GET
POST
PATCH

8.2.6. Manage And Share Dashboards

Collect, export, and share your Cribl Search Dashboards.

You can create custom Collections to group Dashboards together. You can export Dashboard visualization panels as image files. And you can share any Dashboard that you own.

Group Dashboards into Collections

You can create custom Collections in which to organize groups of Dashboards.

On the Dashboards page, select **Add Collection**, give your Collection a unique name, and then select **Add**. New Collections appear in the list on the left, in alphabetical order.

You can also create a Collection when creating a new Dashboard.

Add Dashboards to Collections by selecting a Collection name from the **Collection** drop-down in either the **Edit Dashboard** modal (when editing an existing Dashboard) or the **New Dashboard** modal (when adding a new Dashboard).

Move a Dashboard that you own by clicking the Dashboard's Actions ⋯button and selecting **Move**.

Rename or delete a Collection by clicking the button next to the Collection name.



Moving a Dashboard generally discards any sharing Permissions that were set on the original Dashboard. (However, moving a Dashboard **between** Collections does not change its access Permissions.) Share the Dashboard from its new location to add new Permissions.

Export a Visualization

To export a visualization panel as a `.jpg` or `.png` file, select the Actions ⋯button at the top right, and then choose the file type you want to export.

Share a Dashboard

You can share any Dashboard that you own by clicking the Dashboard's Actions ⋯button, and selecting **Share**.

8.2.7. Migrate Grafana Dashboards

Preview Feature

Cribl is still developing this Preview feature. We don't recommend using it in a production environment, because the feature might not be fully tested or optimized for performance, and related documentation could be incomplete.

Please continue to submit feedback through normal Cribl support channels, but assistance might be limited while the feature remains in Preview.

Assess and import supported Grafana Dashboards into Cribl Search, without rebuilding them by hand.

About Grafana Migration

A migration connects to Grafana, inventories your Grafana Dashboards, alert rules, and their dependencies, and classifies every selected resource before it creates anything in Cribl Search. You review the compatibility results, approve an import plan, and then import what is ready.

This workflow is separate from the two other ways Cribl Search works with Grafana:

- Query metrics from Grafana through the Prometheus-compatible endpoint on a metrics Dataset.
- Visualize Cribl Search Results in Grafana by running Cribl Search queries through the Cribl Search plugin.

What Migrates

A migration imports Grafana Dashboard definitions, not the metrics they chart. Those metrics must already be present in a metrics Dataset. See Before You Begin.

For each Prometheus-backed Dashboard you select, Cribl Search converts the supported Grafana layouts, rows, panels, variables, and code-mode PromQL into a Dashboard, in a Collection you choose.

Grafana resource	What Cribl Search does
Prometheus or Mimir Dashboards	Imports supported content as Dashboards.
Alert rules	Imports simple threshold rules as paused Monitors. Assesses the rest, so you know what to rebuild.
Loki, Tempo, SQL, InfluxQL, Elasticsearch, and other non-Prometheus Dashboards	Doesn't migrate.
Contact points, silences, and alert history	Doesn't migrate.

Anything Cribl Search can't reproduce, such as an unsupported panel type, a Grafana Macro, or an expression, is reported during review rather than dropped. Imported PromQL stays verbatim in Code mode, so a Dashboard that would silently lose behavior is never classified as Ready.



A migration is a one-time import, not a continuous sync. Start another migration to pick up later Grafana changes.

Before You Begin

Make sure that you have:

- A metrics Dataset that holds the metrics your Grafana Dashboards query. Only Prometheus-backed and Mimir-backed Dashboards migrate, and assessment classifies queries against this Dataset. If the metrics are not in Cribl Search yet, ingest them first. See Ingest Prometheus Metrics into Cribl Search.
- Permission to create and update Dashboards and Monitors in Cribl Search, and to create migration runs.
- A Grafana account that can read the folders, Dashboards, data sources, and alert rules you want to migrate.
- A Grafana service account token, stored as a Global Secret.

Reading a resource's raw Grafana export during review requires a separate Permission to read source snapshots. Users with read-only access can see migration runs and non-secret connection details, but can't create runs, change connections, or import.

For a live connection, Cribl Search must be able to reach your Grafana URL over HTTPS with a valid TLS certificate. Cribl Search doesn't tunnel into a private network, so if Grafana isn't reachable, upload a `.json` export instead. Requests to private, loopback, link-local, and cloud metadata addresses are rejected.

Start a Migration

1. From the Cribl Search sidebar, select **Dashboards** > **Migrate** > **New Migration**.
2. Under **Choose a source path**, select one of the following:
    - **Connect to Grafana** to discover content over a live connection. This is the default.
    - **Upload dashboard JSON** when Cribl Search can't reach Grafana.

A `.json` export doesn't carry every resource a Dashboard depends on, so an upload run can leave folders, data sources, or library panels unresolved. Assessment reports those unresolved dependencies.

Each migration is a run that you can leave and return to. To resume, select the run in the **Migrations** list, then select **Resume at** the current stage, for example **Resume at Connect**. Completed runs offer **Open**.

Connect to Grafana

1. Under **Grafana connection**, select an existing connection, or create one and enter your Grafana URL.
2. Under **Global Secret**, select the secret that holds your Grafana service account token.
3. Select **Test Connection**.
4. When the test reports **Connection test passed.**, review the detected **Grafana version** and capabilities, then select **Start Discovery**.

Cribl Search stores only a reference to the Global Secret. It never returns the token to the browser, includes it in reports, or prefills it in the form. A connection that already has a credential shows **Credential configured**, and users who can manage connections can select **Replace credential** to point it at a different secret.

You can't continue past a connection that hasn't been tested, or one whose test failed. A failed test names one of these causes:

Reported cause	What to do
The source is unreachable	Check the URL, DNS, TLS certificate, and network path.
Credentials were rejected	Confirm that the token is valid and hasn't expired, then replace the credential.
Permissions are missing	Grant the service account read access to the resources you want to migrate.
The version is unsupported	Upgrade Grafana, or use the upload path.
A required API is missing	Confirm that the Grafana instance exposes the Dashboard and folder APIs.
The request was blocked	The destination is disallowed by egress policy. Use a reachable public URL, or upload a `.json` export.
Connection testing is unavailable	Connection testing isn't enabled on the node serving the request. Contact Cribl Support.

Discover and Select Dashboards

Discovery inventories what your connection can read, and shows its progress by resource type. It resumes where it left off if you navigate away, and you can cancel it at any time.

If Grafana denies access to some resources, discovery shows a partial-permission warning rather than reporting a complete inventory. Grant the missing Grafana permissions and run discovery again if you expect those resources.

When discovery finishes, choose what to migrate:

1. Use **Search folders and dashboards** to filter the tree.
2. Under **Select Dashboards**, expand a folder in **Dashboards by folder** to see its Dashboards, each with a panel and data source count.
3. Select the Dashboards you want. Selecting a folder selects everything in it, and a partly selected folder shows an indeterminate check box.
4. Under **Select Alert Rules**, select the rules you want to assess.
5. Expand **Dependency summary for selection** to see what your selection references, including anything unresolved.
6. Select **Continue to Mapping**.

A resource you clear never appears in the assessment, the import plan, or the results.

Map Data Sources and Folders

Under **Map Data Sources & Folders**:

1. Map each supported Prometheus or Mimir data source to the metrics Dataset that holds its metrics.
2. Set the **Default Dataset**, which Cribl Search uses for queries whose data source is unmapped or absent.
3. Map each Grafana folder to an existing Collection, or type a name to create one.
4. Select **Run Assessment**.

Assessment can take a while, because it validates every selected Dashboard's queries against your metrics. While assessment is in progress, the page stays on screen and the button reads **Assessing…**, or **Retrying…** with an attempt count. Select **Cancel** to stop the pass and return to editable mapping. You can reload the page or come back later without losing progress.

If a pass fails, the page reports **Assessment failed** and keeps your mapping. The two common causes are missing Dataset-read Permission, and repeated internal failures. Fix the cause, then run the assessment again.

Review Compatibility

When assessment completes, Cribl Search opens **Review Compatibility** with a summary card for each status. Select a card to filter the table, and select **Inspect** on a row to open its details.

Every selected resource, and every nested panel, query, and variable, receives one of these statuses:

Status	Meaning
Ready	Cribl Search can import the resource with no known change in behavior.
Ready with changes	Cribl Search can import the resource, but something about it will change. The row states what.

Status	Meaning
Action required	You must resolve or explicitly skip the item before you can create an import plan.
Unsupported	Cribl Search can't import the resource. Import a placeholder, or skip it.
Error	Assessment couldn't classify or validate the resource.
Skipped	You excluded the resource, so it won't be imported.

Every result that isn't Ready includes a reason code, the effect, and a next action.

Inspect a Dashboard

The inspection drawer breaks a Dashboard down into **Panels**, **Variables**, and **Dependencies**, and shows each query's PromQL alongside its validation verdict. If you have Permission to read source snapshots, the inspection drawer includes the **Source JSON** tab.

Query validation distinguishes these outcomes, so an unavailable catalog never looks like a missing metric:

- The metric is absent from a complete catalog.
- The catalog couldn't be listed in full, so the result is inconclusive.
- The query ran, but returned no data in the validation window.
- The query can't run in Cribl Search.
- Validation timed out.
- Ingest renamed the metric, which is common for classic histogram metrics. Cribl Search validates the renamed form and reports the change.
- The query returns more series than a Dashboard panel displays.

Each verdict records the Cribl Search job ID, so you can correlate a result with Cribl Support.

To test against a different time range, select a **Validation window** and then **Re-run validation**. A panel with a no-data verdict also offers its own window and a validation rerun, so you can check one panel without reassessing the run.

Review Alert Rules

Use the **Dashboards** and **Alert rules** tabs to switch between resource types. The **Alert rules** table lists every selected rule with its folder, class, status, and reason.

Cribl Search imports the rules it can translate exactly, and assesses the rest:

Class	Status	What Cribl Search does
Simple threshold	Ready, or Ready with changes	Imports the rule as a paused Monitor.
Multi-query	Action required	Doesn't import the rule. Rebuild it as a Monitor by hand.
Classic conditions	Unsupported	Doesn't import the rule.
Other expression rules, and recording rules	Unsupported	Doesn't import the rule.

A simple threshold rule has one PromQL query, an optional `last` reducer, and one threshold condition. Any other shape would change what the alert fires on, so Cribl Search reports it instead of translating it.

Select **Inspect** on a rule to open its details. The drawer tags a rule that **Imports as paused Monitor**, and shows the query's validation verdict. **Extracted alert semantics** lists the comparator, the threshold, the **For duration**, the no-data behavior, and the execution-error behavior. The drawer also calls out the semantics that can't carry over, such as recovery behavior and contact point routing, and links the Dashboard that the rule came from.

Cribl Search creates migrated Monitors through the same Permission and validation checks as a Monitor you build by hand.

Create and Run the Import Plan

Resolve or explicitly skip every Action required item, then:

1. Select **Create import plan…**.
2. In **Confirm import plan**, review the plan revision, the Collection, Dashboard, and panel counts, and the warning that the import isn't atomic.
3. Select **Start Import**.

The import starts only from this confirmation. Opening **Import** directly reports that the import hasn't started.

Changing your selection or mapping produces a new plan revision.

Cribl Search writes Dashboards one at a time, so an import can partially succeed. Canceling stops further writes at the next safe point, and it doesn't undo Dashboards that were already created or updated. When the run finishes, Cribl Search opens **Results**.

Review the Results

Results reports the run as **Completed** or **Completed with warnings**, with a count for each outcome and a row per item that shows its source and its target ID:

Outcome	Meaning
Created	Cribl Search created a new Dashboard.
Updated	Cribl Search updated an existing Dashboard.
Up to date	Nothing changed, so Cribl Search wrote nothing.
Placeholder	Cribl Search imported a placeholder in place of unsupported content.
Skipped	You excluded the item.
Blocked	A conflict or a failed dependency prevented the write.
Failed	The write failed. The row states whether a retry is safe.

Imported Dashboards are available immediately in Cribl Search, in the Collections you mapped.

Alert rules appear in their own section, with the class and status from the assessment and the outcome of the write. A rule that produced a Monitor offers an **Open Monitor** link. A rule that Cribl Search didn't import states its reason instead, and never reports success.

Every migrated Monitor arrives paused, so it can't fire until you review it. To start alerting on one, open the Monitor and turn on **Enabled**. See Monitors.

You can export a redacted `.json` report of the run for support or automation. The report carries stable reason codes and no credentials.

Deleting a run removes the run record and its stored snapshots, but not the Dashboards it imported. Deleting a run that's still discovering or importing cancels it first, and you might need to delete it again after the run is canceled.

Rerun a Migration

Cribl Search matches previously imported Dashboards by their Grafana identity rather than their name, so renaming a Dashboard in either system doesn't create a duplicate. On a later run:

- A Dashboard that hasn't changed on either side is **Up to date**, and Cribl Search writes nothing.
- A Dashboard that changed in Grafana updates its existing target, as long as no one edited that target in Cribl Search.
- A Dashboard you edited in Cribl Search is reported as a conflict, with the reason `target-modified`.
- An unrelated Dashboard that already owns the target ID blocks the write.
- Cribl Search never deletes a target automatically, even when the Grafana Dashboard is gone.

To replace your edits in Cribl Search with the Grafana version, select **Overwrite `<target>` on import** during review. The row is tagged **Will overwrite**, and the import replaces the edited Dashboard. Leave the option clear to keep your Cribl Search edits.

Alert rules reconcile the same way. A rule that hasn't changed writes nothing, and a Monitor that someone edited in Cribl Search is reported as a conflict that you can keep or overwrite.

Enable Migration Mode

After an import, **Results** can offer **Migration mode** for each Dataset you mapped. When local storage doesn't cover a query, Cribl Search sends the whole query to a Prometheus Dataset Provider. It never merges local and remote results.

Migration mode is off by default. To turn it on for a Dataset:

1. In the **Migration mode** section, find the Dataset's row.
2. Under **Source provider for metrics**, select a Prometheus Dataset Provider. Until you do, the **Enable migration mode for metrics** toggle stays inactive.
3. Turn on **Enable migration mode for metrics**.

The change applies right away, with no separate save. The row's status becomes **Migration mode enabled**, and **Source provider for metrics** locks. Turn the toggle off to restore local-only queries and unlock the Dataset Provider.

If your Organization has no Prometheus Dataset Provider, the section reports **No Prometheus Dataset Providers available**. Create one, or ask an administrator for access to one, and then return here. If a change can't be saved, the row shows an error and the toggle returns to its previous state.

You can also configure migration mode later, on the metrics Dataset itself.

Next Steps


- Explore Metrics in Cribl Search to query the metrics behind your imported Dashboards.

8.3. Third-Party Visualization Tools

8.3.1. Visualize Cribl Search Results In Grafana

Visualize your search results in Grafana, using the official Cribl Search plugin.

In addition to the Charts and Dashboards included in Cribl Search, you might want to present your search results using Grafana's visualization tools. For that, use the official **Cribl Search plugin for Grafana**.



Cribl Search plugin for Grafana

Once the plugin is configured, you can:

- Run any Cribl Search query directly in Grafana.
- Feed your Grafana dashboards with up-to-date data, using scheduled searches.

This plugin is separate from Migrate Grafana Dashboards, which imports Grafana Dashboards into Cribl Search.

Connect Grafana to Cribl Search

To start using Cribl Search with Grafana, you need Organization administrator permissions in Grafana, and Owner or Admin permissions in Cribl.Cloud.

1. In Grafana, install the Cribl Search plugin.
2. In Cribl.Cloud, get a Cribl.Cloud credential.
3. In Grafana, add a Cribl Search data source.

Install the Cribl Search Plugin in Grafana

To install the Cribl Search plugin in Grafana:

1. Log in to Grafana as an Organization administrator.
2. Go to the Cribl Search plugin page, and select **Install**.

Create a Cribl.Cloud Credential for Grafana

To let Grafana pull data from Cribl Search, create an API Credential in Cribl.Cloud:


1. Log in to Cribl.Cloud, and select an Organization for which you're an Owner or Admin.
2. Go to **Account** > **Organization** > **API Management**.
3. Select **Add Credential**, and follow the steps to create an API Credential.
4. Once you created the credential, keep the following at hand:
    - Client ID.
    - Client Secret.
    - The URL of your Cribl.Cloud Organization (for example, `https://<workspaceName>-<organizationId>.cribl.cloud`).

Add a Cribl Search Data Source in Grafana

With the Cribl Search plugin installed, and your Cribl.Cloud credential ready, add a Cribl Search data source in Grafana:

1. Log in to Grafana as an Organization administrator.
2. In Grafana, follow Grafana's instructions for adding a new data source. Select the Cribl Search plugin as the data source type.
3. On the Cribl Search plugin page:
    - In **Cribl Organization URL**, enter the URL of your Cribl.Cloud Organization (for example, `https://<workspaceName>-<organizationId>.cribl.cloud`).
    - In **Cribl Client ID**, enter the Client ID of the Cribl.Cloud credential.
    - In **Cribl Client Secret**, enter the Client Secret of the Cribl.Cloud credential.

4. Select **Save & test**.



Cribl Search plugin configuration

Run a Cribl Search Query in Grafana

Once you set up the Cribl Search plugin, you can run any Cribl Search query right there in Grafana:

1. In Grafana, go to your Cribl Search data source.
2. In **Query Type**, select **adhoc**.
3. In **Query**, enter your Cribl Search query.

   Your query can include Grafana variables.
4. At the top right, adjust the time range.
5. Select **Run query**.

Schedule Searches to Load Grafana Dashboards Faster

To render your Grafana dashboards faster, keep them up to date by automatically pulling the latest results of scheduled searches from Cribl Search.

First, get the ID of the scheduled search that you want to visualize in Grafana:


1. From the Cribl Search sidebar, select **Saved Searches**.
2. Open an existing saved search, or select **Add Search** to save a new one.

3. Set up your scheduled search, by following this section: Schedule a Search.
4. At the top, copy the scheduled search **ID** (for example, `cribl_search_finished_1h`).

With the scheduled search ID ready, go to Grafana:

1. In Grafana, go to your Cribl Search data source.
2. In **Query Type**, select **saved**.
3. In **Saved Search**, enter the ID of your Cribl Search scheduled search.
4. Select **Run query**.

Now, Grafana will automatically fetch the latest results of your scheduled search. When you open Grafana, the dashboard dependent on your search will load immediately, since your Cribl Search results are already there.



Pulling scheduled search results in Grafana

Get Grafana Alerts Based on Cribl Search Results

You can create Grafana alert rules based on results produced by Cribl Search. For example, you can get Grafana alerts when the number of your Cribl Search results crosses a certain threshold, or when a result set contains a specific value.

1. Make sure your Grafana instance is connected to Cribl Search.

2. When configuring an alert rule in Grafana, select a Cribl Search data source, and add your ad-hoc or scheduled Cribl Search query.

For more information on setting up alerts, see Grafana's documentation.

9. Send Alerts With Cribl Search

Receive conditional Notifications about your results, using scheduled searches and Notification targets.

Scheduled Searches

Schedule a search to run at a specific frequency.

Notifications

Set up a Notification target to send alerts about your scheduled searches to:

- System Messages: Banner messages in the Cribl Search UI (the default target).
- Email messages.
- Amazon SNS topics.
- PagerDuty accounts.
- Slack channels.
- Webhook connections.

9.1. Scheduled Searches

Run a search at a scheduled frequency, and set up conditional Notifications.

Scheduled searches allow you to automate data analysis by monitoring systems, optimizing workflows, and sending Notifications based on the evaluation of search results against a specific condition. You can use scheduled searches to aggregate data, compare results, identify anomalies, and analyze long-term trends.

For example, instead of manually running a search to gather information about login types and failures from the previous month, you can schedule a search to automatically aggregate this data at midnight on the first day of each month.

Scheduled searches can also send Notifications, based on specific conditions. This helps you stay informed about important events with no manual effort. You can send Notifications to different targets, including:

- System Messages: Banner messages in the Cribl Search UI (the default target).
- Email messages.
- Amazon SNS topics.
- PagerDuty accounts.
- Slack channels.
- Webhook connections.

Schedule a Search

To schedule a search, save or edit an existing saved search, and then toggle **Schedule** on. The option to save a search is available in two places:

- At the bottom right of the query box, under the **Actions** menu.
- In **Saved Searches**, through the **Add Search** button.

Either way, the resulting modal provides these configuration options:

Name: Give the search a meaningful name that will help you identify it easily.

Description: A description is optional.

Results Access: Defaults to **Private** where only you can view the result set. Select **All Members** to share the results. When a result set is created its access level is defined. If you edit this setting, only subsequent results will have the new setting.

Query

Search string: This is the query; edit it if needed. For details, see Build a Search.

- **Sampling**: Sampling uses a ratio to reduce the number of results returned from a search. For example, if a search returns 1,000 events, a 1:10 sampling ratio returns 100 events. You can also set the sampling rate directly in the query using the `set sample_rate` option.
- **Time range**: Set the query time range, relative to the time the search is scheduled to run. See time range for details.

Schedule

Schedule: Enable **Run on schedule** to configure the run frequency. You can then set the frequency either by using the drop-downs, or by entering a custom cron expression. The cron expression defaults to `0 0 * * *`, running every day at 12:00 AM.

- **Timezone**: Select the time zone for the scheduled search to use. This is independent of the time zone of the underlying saved search.

Jitter

To avoid having many scheduled searches run at the same instant - for example, all at the top of the hour - Cribl Search can add a random delay, called jitter, to each run. This spreads scheduled search execution times to reduce load spikes.

Jitter percent: Sets the size of the random delay window as a percentage of the scheduling interval. For example, a search that runs every 10 minutes with a jitter of `50` runs at a random point between the scheduled time and 5 minutes after it. The valid range is `0` to `50`. Set it to `0` to disable jitter for this search. When you leave it unset, the search uses the global **Scheduled search jitter percent** limit, which defaults to `20`.

Keep these behaviors in mind:

- The jitter delay is calculated dynamically, so a new random value is used for each run.
- The search time range for relative modifiers is always calculated from the original scheduled time, not the jittered time. See Scheduled searches times are now relative to scheduled time.
- The maximum jitter for any run is 1 hour, even when the configured percentage of a long interval would be larger.
- Catch-up runs, where a search is behind schedule, are never jittered.
- Dashboards that run on a schedule never use jitter.

Notifications

For details about setting options on the **Notifications** tab, see Configure Notifications.

Advanced

Advanced provides a **Keep last executions** control. This determines the minimum number of result sets stored. Every hour, Cribl Search rotates result sets, preserving at least this number of past results. The minimum allowed is `1`, the default is `2`, and the maximum is `1000`. This setting overrides the **Search history maximum jobs** and **Search history TTL** limits.

Rules

- You can edit the schedule or query of a scheduled search and it will be used on subsequent runs.
- Daylight savings time is automatically incorporated based on the selected time zone.


Results

Result sets from scheduled searches can be utilized by:

- using the send operator to automatically send the results to Cribl Stream, for further routing and filtering.
- opening the search from the History tab for review.

History provides a filter on the top right of the table for **Scheduled** searches. The table provides details of each scheduled search, including its query, status, user, last run duration, and latest run time.

- Select a row to view the scheduled search's first result set.
- Select **N Items** to view all of the result sets. From the shown result sets:
  - Select a row to view the results.
  - Select the **Search ID** to view the search's details, helpful for troubleshooting.
- The **Actions** column has options to **Rerun** and **Save** the search.
- Delete one or many result sets by selecting check boxes on the left of a column and then clicking **Delete Selected Jobs** at the bottom left of the table.



Result Sets

Manage Scheduled Searches

You can view and manage your scheduled searches from **Saved Searches**. The saved searches table has a **Scheduled** filter and columns for **Schedule** and **Next Run**.

- Select a row to view, edit, or delete a saved search.
- The **Actions** column has options to **Rerun** and **Clone** the search.
- To stop a scheduled search, toggle its schedule off when editing it.

If you want to view the results of a previously run scheduled search, go to **History**. See the above Results section for details.

9.2. Notifications

Send Notifications about your scheduled searches.

Cribl Search can alert you when your scheduled searches generate results that match triggering conditions that you specify. You set up alerts in these basic stages:

1. Optionally, configure any custom Notification targets to which you want to send alerts. (Cribl Search comes preconfigured with at least one default `System Messages`. target, Some plans add a preconfigured `system_email`.)
2. Save and schedule each search from which you want to trigger alerts.
3. Configure one or more Notifications on each scheduled search.



You can't configure Notifications on a saved or scheduled search that resides within a Pack.



This page covers Notifications for scheduled searches. To alert on Monitors instead, see Manage Monitor Notifications.

Notification Targets

A Notification target specifies the delivery method for a Notification. Every Notification must have at least one target. Available target types are:

- System Messages: Banner messages in the Cribl Search UI (the default target).
- Email messages.
- Amazon SNS topics.
- PagerDuty accounts.
- Slack channels.
- Webhook connections.

By default, any Notification that you configure will have a `System Messages` target. Also, your Notification will include this target regardless of any other target that you add. When a Notification condition is triggered, Cribl Search will add an indicator on the top nav's **Messages** button. Here, select this button to view details in the **Messages** drawer.

Add a Notification Target

You must be a Search Admin or Owner to create targets.

To add a new Notification target:

1. In Cribl Search, go to **Settings** > **Search** > **Notification Targets**.
2. Select **Add Target** to open the **New Target** modal.
3. Give this target a unique **Target ID**.
4. Select the desired **Target type**.
5. Configure the target as appropriate for that type. See Notification Targets.

You can also use the Cribl API to create a Notification target.

When you create a Notification target in Cribl Search, Cribl Stream, or Cribl Edge, it will also be available to you in the other products. For example, if you create a Notification target in Cribl Search, you can also access that target in Cribl Stream and Cribl Edge. (Where you would, of course, configure very different Notification conditions.)

Manage Notification Targets

You manage existing targets on the same **Notification Targets** page where you create targets.

Select any existing Notification target to open a modal where you can manage the target, using buttons at the bottom of the configuration modal.

Select **Clone Target** to copy an existing Notification target. This refreshes the modal, enabling you to customize the new target.

Select **Delete Target** to delete an existing target.

To edit any target's definition in a JSON text editor, select **Manage as JSON** at the bottom of the **Notifications Targets** modal. You can directly edit multiple values, and you can use the **Import** and **Export** buttons to share existing target configurations as `.json` files.

Configure Notifications

To configure how, when, and where to send Notifications:

1. Schedule a search, or open an existing scheduled search.
2. In the search's configuration modal, open the **Notifications** left tab.
3. Toggle **Send notifications** on, and configure the options listed below.



The **Notifications** left tab unlocks only after you enable the **Schedule** tab's **Run on schedule** option.

To configure further Notifications on the same scheduled search, select **Add Notification**.

You can also use the Cribl API to create a Notification.

Notification Options

As you configure each Notification, the **Notifcations** tab offers the following options.

- **When**: Select the type of trigger condition, then define the corresponding trigger. (See Notification Triggers.)
- **Send Notification to**: Select an existing Notification target to deliver the Notification, or select **Create** to create a new target. (For target options, see Notification Targets.)

  All Notifications, regardless of their configured target, will also generate a message in the Cribl Search UI.


- **Include search results**: You must toggle this on if you want to insert the `{{resultSet}}` template variable into the **Message** field, in order to include or attach complete search results with Notifications. (See Message Options below for details and payload limits.) However, this is not required in order to include the contents of specified events and fields, in the format: `{{resultSet[0].<field-name>}}`. To see how each alert type implements this option, follow the links from Notification Targets.
- **Message**: Message payload template. For details, see Message Options below.

Message Options

The message sent with each Notification can contain a maximum of 1,000 characters, and a maximum of 100 events x 20 fields.

In the **Message** pane, you can customize each Notification's contents by inserting the template variables listed below. These are placeholders to populate your message with fields generated by the search. Insert a variable between pairs of double braces, in this format: `{{savedQueryId}}`.

Here's an example that inserts some literal text followed by a corresponding variable: `Date: {{timestamp}}`. This is the first string in the default template, shown below.



Message pane's Default template

The following template variables are available.

Variable	Description
`{{resultSet}}`	Array containing complete results of the search, up to the maximum message size.
`{{resultSet[<event-number>].<field-name>}}`	Contents of a specified event and field from the search results.
`{{savedQueryId}}`	ID of the saved search that triggered the Notification.
`{{searchId}}`	ID of the search job.
`{{searchResultsUrl}}`	URL corresponding to the search job results.
`{{notificationId}}`	ID of this Notification (autogenerated).
`{{timestamp}}`	Date this Notification was triggered.
`{{tenantId}}`	ID of the Cribl Organization.

If you choose to explicitly add the `{{resultSet}}` variable to the message body, this will have different effects with different targets:

- With a PagerDuty or Slack Notification, you can include `{{resultSet}}` to control where inline search results will be displayed within alerts.
- With an Email Notification, including `{{resultSet}}` will insert placeholder text indicating that the results will appear either "in the table below" (if you've selected **Send as**: **Inline table**) or "attached" (if you've selected **Send as**: **CSV** or **JSON**).
- With an Amazon SNS or Webhook Notification, including `{{resultSet}}` will send duplicate result sets - one each in the message and on the payload.



In order to insert the complete `{{resultSet}}` template variable, you must toggle on **Include search results**. This is not required in order to insert individual events/fields.

Notification Triggers

On the **Notifications** left tab, use the **When...** controls to define the trigger condition that will send the Notification. The drop-down here provides two options.

- **Where**: Select this to define a custom condition. See Notification Trigger Examples below.
- **Count of Results**: Exposes a drop-down where you can select a comparison operator, and a field where you can enter the corresponding threshold number.

How Notification Triggers Work

Cribl Search will send a Notification when at least one event satisfies the trigger condition. This can be useful if you want to define a search query that returns multiple results, but want alerts sent only when a specific condition among these results is met.

Notification Trigger Examples

For a query like this:

```
dataset="cribl_internal_logs" error
| summarize errorCount=count() by message
| top 10 by errorCount
```

Copy Run in Cribl Search

You could enter this **Where** condition to alert when `Request failed` is in the top 10 errors:

```
message == "Request failed"
```

Copy

For a query like this:

```
dataset="cribl_search_sample" log_status="OK"
| summarize count() by action
```

Copy Run in Cribl Search

You could enter this **Where** condition to alert upon connection errors:

```
action == "REJECT"
```

Copy

9.2.1. Email Notifications

Send email Notifications to alert on your scheduled searches.

If you're a Cribl Search Admin, email Notifications make it easy for you (or designated other people) to receive alerts about operational issues that merit your attention, such as a scheduled search's execution details.

An email Notification requires two things - a configured Notification and an email Notification target. Organizations on an Enterprise plan also have access to a preconfigured email Notification target.

Email Notifications do not provide an unsubscribe option. Recipients who do not want to receive particular email Notifications should contact their Cribl Search Admins.

Email Notifications are sent on a no-reply basis.

Email Notification Targets

You can send Notifications by email, using an SMTP server of your choice. Once you have configured the email Notification target, you can specify the recipients, and customize the subject line and message content. For details, see Configure Email Notifications.

To add an email Notification target in Cribl Search, do one of the following:

- Open a saved or scheduled search, then select **Notifications**. Toggle **Send notifications** on, if necessary, then configure the target.
- From the Cribl Search sidebar, select **Settings**, then **Search**, then **Notification Targets**, then **Add Target**.

If you have an Enterprise plan, you can use the preconfigured default Email Notification target.

General Settings

Target ID: Enter a unique name to identify this email Notification target.

Configuration

Address: Identify the SMTP server by its hostname or IP address.

Port: Set the SMTP port. Use port `587` for SMTP Secure (SMTPS). You can also use port `25`. Use `465` when SSL/TLS is enabled. You can also use port `2525` if your email service provider supports this port as a backup when other ports are blocked by a network provider or a firewall.

From: Identify the email address of the sender.

Encryption type: Specify the encryption type used to secure SMTP communication. Options include:

- **STARTTLS**: Select this option to start the connection as plaintext, then upgrade it to a TLS-encrypted one if the server supports it. If the server doesn't support it, the connection remains plaintext.

  STARTTLS upgrades the connection to be encrypted but does not authenticate the server. Take additional steps to prevent man-in-the-middle attacks.

- **Require STARTTLS**: Select this option to require TLS. If the server doesn't support a secure connection, the connection will be dropped.
- **TLS (SMTPS)**: Select this option to use an encrypted connection from the start without requiring a subsequent connection upgrade.
- **None**: Select this option to use a plaintext connection.

Minimum TLS version: Optionally, select the minimum TLS version to use when connecting.

Maximum TLS version: Optionally, select the maximum TLS version to use when connecting.

Validate server certs: Toggle on to reject certificates that are **not** authorized by a CA in the **CA certificate path** or by another trusted CA (such as the system's CA).

Authentication

Username: The authentication principal (if required).

Password: The authentication credential (if required).

Test Email Notification Targets

For arrival tests and log indicators, see Test the Email Notification Target.

Default Email Notification Target for Cribl.Cloud Enterprise Orgs

For Cribl.Cloud Enterprise orgs, a default email Notification target is available for Cribl Stream, Edge, Search, and Insights. You can use this target to route any email Notification to any valid email address.

This target appears in the **Notifications** > **Target** modal as `system_email`. You cannot modify or remove this target.

The `system_email` Notification target is managed by Cribl. It will be disabled in the unlikely event of abuse. If this target is disabled for a Workspace, a log entry will appear in the Notifications Service logs. Select **Monitoring** > **Logs** > **Notifications Service** to view this log.



The `system_email` email Notification target is available only for Organizations on an Enterprise plan. For details, see Pricing.

Send Domain for Cribl.Cloud Email Notifications

Every Cribl.Cloud Organization and Workspace has a unique address for its email Notification target. Messages sent using this target will have a sender's address in the form `do-not-reply@<workspaceName>-<organizationId>.criblcloud.email`. To ensure delivery, recipients should add the `criblcloud.email` domain to their email allowlists.

Configure Email Notifications

To create an email Notification:


1. Create a scheduled search.

   To schedule an existing search: Save it, then open its configuration modal from the **Saved Searches** tab.

   On that modal's **Schedule** left tab, enable **Run on schedule**.

2. On the **Notifications** left tab, enable **Send notifications** to unlock the options listed below.

Field	Description
When...	Use these controls to define the condition that will send the Notification (see Notification Triggers).
Send Notification to	Select an existing email Notification target from the drop-down. Or select **Create** to define a new target (see Email Notification Targets).



Email Notification with target selected

Once you've selected an email target, the following fields are available.

Field	Description
To	Email address(es) of one or more primary recipients.
Cc field	Toggle this on to expose a field where you can enter additional recipients' addresses.
Bcc field	Toggle this on to expose a field where you can enter blind-copy recipients' addresses.
Include search results	For details about this option, see Include Search Results With Email Notifications.
Subject	The subject line of the email Notification. You can use variables here.
Message	The body of the email Notification. You can use variables here.

Cribl Search does not limit the total number of recipients of an email Notification, but your email service might set a limit.

Email Notification Variables

Email variables are placeholders in the email template, which Cribl Search replaces with actual values when each email is sent. You can use these variables in the Notification's **Subject** or **Message** (body) field. Insert a variable between pairs of double braces, in this format: `{{timestamp}}`.

Variable	Description
`{{resultSet}}`	Array containing complete results of the search, up to the maximum message size.
`{{resultSet[<event-number>].<field-name>}}`	Contents of a specified event and field from the search results.
`{{savedQueryId}}`	ID of the saved search that triggered the Notification.
`{{searchId}}`	ID of the search job.
`{{searchResultsUrl}}`	URL corresponding to the search job results.

Variable	Description
`{{notificationId}}`	ID of this Notification (autogenerated).
`{{timestamp}}`	Date this Notification was triggered.
`{{tenantId}}`	ID of the Cribl Organization.

Include Search Results With Email Notifications

Your email Notifications can include a subset of the search results that you're alerting on. You can choose to include the results as a table within each message body, or as an attached CSV or JSON file.

To configure this:

1. Set up an email Notification target.
2. Open a scheduled search, and select **Notifications**.
3. Configure the Notifications, using the email Notification target you've created.
4. As you configure, toggle on the **Include search results** slider.
5. Select one of the following:
    - **Inline table**, to include the results within the email body. If you choose this option, see the considerations in the next section.
    - **CSV**, to include the results as a CSV attachment.
    - **JSON**, to include the results as a JSON attachment.

    If you select either attachment option, each attachment will automatically be assigned a unique file name, concatenating the following elements: the search ID, a timestamp in Unix time (representing when the search job was created), a random six-character string, and the appropriate file extension.

Inline Table Notifications

If you select the **Inline table** option, keep these details in mind:

The results table can accommodate up to 100 rows and 20 columns. If a table exceeds this size, Cribl Search will truncate it.

In the table, text will wrap. To make the results more legible, limit the number of fields sent (use the `project` operator) and the length of each field (use the `trim` function).



Security Risk

> Embedding unverified or unsanitized search results into an email can pose unintended security risks. Cribl recommends reviewing or sanitizing the results prior to including them.

Troubleshoot Email Notifications

For troubleshooting, see Common Issues and Resolutions.

9.2.2. AWS SNS Notifications

Send AWS SNS Notifications about your scheduled searches.

You can send Notifications to an Amazon Simple Notification Service (SNS) topic. This gives you access to a broad array of alert destinations, such as various AWS services, mobile push notifications, or text messages.

To add an Amazon SNS Notification target in Cribl Search, select **Settings** > **Search** > **Notification Targets** > **Add Target**.

General Settings

Target ID: Enter a unique ID used to identify the target. This will show in the **Target ID** column of the **Targets** tab. It can't be changed later, so make sure you like it.

Configuration

Destination type: Defaults to **Topic ARN**. For the **Phone number** option, see Text Message (SMS) Notifications.

Default Topic ARN: The Amazon Resource Name (ARN) of the Amazon SNS topic to which you want to send Notifications. Enter the ARN in the following format:

```
arn:aws:sns:region:account-id:MyTopic

// for example:
// arn:aws:sns:us-west-2:000000000000:my-topic
```

Copy

If you use a non-AWS URL, the format must be:

```
{url}/myQueueName

// for example:
// https://host:port/myQueueName
```

Copy

The default topic ARN must be a JavaScript expression (which can evaluate to a constant value), enclosed in quotes or backticks. Can be evaluated only at initialization time. For example, if you're referencing a global

variable: `` `https://host:port/myQueue-${C.vars.myVar}` ``. This value can be overridden by the Notification event `__topicArn` field.

Topic type: The type of the topic selected in AWS SNS. Can be **Standard** or **FIFO**.

Message group ID: The tag that specifies that a message belongs to a specific message group. Messages that belong to the same message group are processed in a first in, first out (FIFO) manner. Must be a JavaScript expression (which can evaluate to a constant value), enclosed in quotes or backticks. Can be evaluated only at initialization time. For example, referencing a global variable: `` `https://host:port/myQueue-${C.vars.myVar}` ``.

Region: The Region associated with the Amazon S3 bucket.

Phone number allowlist: A wildcard list of phone numbers that are allowed to receive SMS notifications. This is used when **Destination type** is set to **Phone number**.

Authentication

Auto: This default option uses the AWS instance's metadata service to automatically obtain short-lived credentials from the IAM role attached to an EC2 instance, local credentials, sidecar, or other source. The attached IAM role grants Cribl access to authorized AWS resources. Can also use the environment variables `AWS_ACCESS_KEY_ID` and `AWS_SECRET_ACCESS_KEY`. Works only when running on AWS.

Manual: If not running on AWS, you can select this option to enter a static set of user-associated IAM credentials (your access key and secret key) directly or by reference.

The **Manual** option exposes these additional fields:

- **Access key**: Enter your AWS access key. If not present, will fall back to the `env.AWS_ACCESS_KEY_ID` environment variable, or to the metadata endpoint for IAM role credentials.
- **Secret key**: Enter your AWS secret key. If not present, will fall back to the `env.AWS_SECRET_ACCESS_KEY` environment variable, or to the metadata endpoint for IAM credentials.

The values for **Access key** and **Secret key** can be a constant, or, a JavaScript expression enclosed in quotes or backticks. For environment variables, use a JavaScript expression, for example: `${C.env.MY_VAR}`.

Secret: If not running on AWS, you can select this option to supply a stored secret that references an AWS access key and secret key. The Secret option exposes this additional field:

- **Secret key pair**: Use the drop-down to select an API key/secret key pair that you've configured in Cribl Search's secrets manager. To store a new, reusable secret, select **Create**.

Assume Role

Enable for SNS: Toggle on to define an IAM Role to use, instead of automatically detecting one locally.

AssumeRole ARN: Enter the Amazon Resource Name (ARN) of the role to assume.

External ID: Enter the External ID to use when assuming role. This is required only when assuming a role that requires this ID to delegate third-party access. For details, see AWS documentation.

Duration (seconds): Duration of the Assumed Role's session, in seconds. Minimum is 900 (15 minutes). Maximum is 43200 (12 hours). Defaults to 3600 (1 hour).

Post-Processing

System fields: A list of fields to automatically add to events that use this output. By default, includes `cribl_pipe` (identifying the Search Pipeline that processed the event). Supports wildcards. Other options include:

- `cribl_host` - Search Node that processed the event.
- `cribl_input` - Search Source that processed the event.
- `cribl_output` - Search Destination that processed the event.
- `cribl_route` - Search Route (or QuickConnect) that processed the event.
- `cribl_wp` - Search Worker Process that processed the event.

Advanced Settings

Maximum number of retries: The maximum number of retries before the output returns an error. The retries use an exponential backoff policy.

Endpoint: The SNS service endpoint. If empty, defaults to AWS Region-specific endpoint. Otherwise, it must point to an SNS-compatible endpoint.

Signature version: Signature version to use for signing SNS requests. Defaults to `v4`.

Reuse connections: Whether to reuse connections between requests. Toggling on (default) can improve performance.

Reject unauthorized certificates: Toggle off to accept certificates that cannot be verified against a valid Certificate Authority (for example, self-signed certificates). Defaults to toggled off.

Send Text Message (SMS) Notifications

You can use an Amazon SNS Notification target to send text messages (SMS) to a list of phone numbers. To do this, you'll need to set up a allowlist of phone numbers that are permitted to receive Notifications.

1. Select **Settings** > **Search** > **Notification Targets** > **Add Target**.
2. Enter a unique **Target ID**.

3. Set the **Target type** to **AWS SNS**.
4. Set **Destination type** to **Phone number**.
5. Set **Region** to the Region of the Amazon S3 bucket.
6. In **Default Phone number**, enter a comma-separated list of phone numbers that are allowed to receive Notifications. This value can be overridden by the Notification event `__phoneNumber` field. You can use `*` as the wildcard character.
   For example: `+15555550123, +15555551***`.
7. If desired, use **Phone number allowlist** to specify a wildcard list of allowed phone numbers.
8. Configure the remaining sections of the target, as described in Post-Processing and Advanced Settings.
9. Select **Save**.

Now, when you set up Notifications, you can select the new Amazon SNS target and specify any phone number that matches the configured allowlist.

Include Search Results with AWS SNS Notifications

You can send AWS SNS Notifications that include a subset of search results in the Notification payload. Once you've configured your AWS SNS target, you specify this option separately on each Notification that uses the target.

To set this up:

1. Set up an AWS SNS Notification target, as outlined on this page.
2. Open a scheduled search, and select **Notifications**.
3. Configure the Notifications, using the AWS SNS Notification target you've created.
4. Within the configuration, enable **Include search results**.

Take the following into account:

- The results table can accommodate up to 100 rows and 20 columns. If it's larger, Cribl Search will truncate it.
- To make the results more legible, you can limit the number of fields sent (use the `project` operator) and the length of each field (use the `trim` function).



Security Risk

Embedding unverified or unsanitized search results into an AWS SNS Notification payload can pose unintended security risks. Cribl recommends reviewing result sets before including results with Notifications.

9.2.3. PagerDuty Notifications

Send PagerDuty Notifications about your scheduled searches.

You can send Notifications to PagerDuty, a real-time incident response platform, using Search's native integration with the PagerDuty API. Select **PagerDuty** in the **New Target** modal to expose the following additional options on the modal's (single) **General Settings** left tab:

General Settings

Target ID: Enter a unique ID used to identify the target. This will show in the **Target ID** column of the **Targets** tab. It can't be changed later, so make sure you like it.

Configuration

Routing key: Enter your 32-character Integration key on a PagerDuty service or global ruleset.

Group: Optionally, specify a PagerDuty default group to assign to Cribl Search Notifications.

Class: Optionally, specify a PagerDuty default class to assign to Cribl Search Notifications.

Component: Optionally, a PagerDuty default component value to assign to Cribl Search Notification. (This field is prefilled with `logstream`.)

Severity: Set the default message severity for events sent to PagerDuty. Defaults to `info`; you can instead select `error`, `warning`, or `critical`. (Will be overridden by the `__severity` value, if set.)

Retries

Honor Retry-After header: Whether to honor a `Retry-After` header, provided that the header specifies a delay no longer than 180 seconds. Search limits the delay to 180 seconds even if the `Retry-After` header specifies a longer delay. When enabled, any `Retry-After` header received takes precedence over all other options configured in the **Retries** section. When disabled, all `Retry-After` headers are ignored.

Settings for failed HTTP requests: When you want to automatically retry requests that receive particular HTTP response status codes, use these settings to list those response codes.

For any HTTP response status codes that are not explicitly configured for retries, Search applies the following rules:

Status Code	Action
Greater than or equal to `400` and less than or equal to `500`.	Drop the request.

Status Code	Action
Greater than `500`.	Retry the request.

Upon receiving a response code that's on the list, Search first waits for a set time interval called the **Pre-backoff interval** and then begins retrying the request. Time between retries increases based on an exponential backoff algorithm whose base is the **Backoff multiplier**, until the backoff multiplier reaches the **Backoff limit (ms)**. At that point, Search continues retrying the request without increasing the time between retries any further.

By default, this Destination has no response codes configured for automatic retries. For each response code you want to add to the list, select **Add Setting** and configure the following settings:

- **HTTP status code**: A response code that indicates a failed request, for example `429 (Too Many Requests)` or `503 (Service Unavailable)`.
- **Pre-backoff interval (ms)**: The amount of time to wait before beginning retries, in milliseconds. Defaults to `1000` (one second).
- **Backoff multiplier**: The base for the exponential backoff algorithm. A value of `2` (the default) means that Search will retry after 2 seconds, then 4 seconds, then 8 seconds, and so on.
- **Backoff limit (ms)**: The maximum backoff interval Search should apply for its final retry, in milliseconds. Default (and minimum) is `10,000` (10 seconds); maximum is `180,000` (180 seconds, or 3 minutes).

Retry timed-out HTTP requests: When you want to automatically retry requests that have timed out, toggle this control on to display the following settings for configuring retry behavior:

- **Pre-backoff interval (ms)**: The amount of time to wait before beginning retries, in milliseconds. Defaults to `1000` (one second).
- **Backoff multiplier**: The base for the exponential backoff algorithm. A value of `2` (the default) means that Search will retry after 2 seconds, then 4 seconds, then 8 seconds, and so on.
- **Backoff limit (ms)**: The maximum backoff interval Search should apply for its final retry, in milliseconds. Default (and minimum) is `10,000` (10 seconds); maximum is `180,000` (180 seconds, or 3 minutes).

After you've set and saved all of the above target configuration, you can set up Notifications that use the new PagerDuty target as their destination.

Include Search Results with PagerDuty Notifications

You can send PagerDuty Notifications that include a subset of search results in the Notification payload. Once you've configured your PagerDuty target, you specify this option separately on each Notification that uses the target.

To set this up:

1. Set up a PagerDuty Notification target, as outlined above.

2. Open a scheduled search, and select **Notifications**.
3. Configure the Notifications, using the PagerDuty Notification target you've created.
4. Within the configuration, enable **Include search results**.

Take the following into account:

- The results table can accommodate up to 100 rows and 20 columns. If it's larger, Cribl Search will truncate it.
- To make the results more legible, you can limit the number of fields sent (use the `project` operator) and the length of each field (use the `trim` function).

Security Risk

Embedding unverified or unsanitized search results into an AWS SNS Notification payload can pose unintended security risks. Cribl recommends reviewing result sets before including results with Notifications.

9.2.4. Slack Notifications

Send Slack Notifications about your scheduled searches.

You can send Notifications to a Slack channel, using Slack Incoming Webhooks.



You can also use a Webhook Destination to send specific event data to Slack for a team's attention. For more information, see our Slack/Webhook integration topic.

First, in your Slack workspace, use a Slack app to enable incoming webhooks.

Then, in the **New Target** modal, select **Slack** to expose the following additional options on the modal's (single) **General Settings** left tab:

General Settings

Target ID: Enter a unique ID used to identify the target. This will show in the **Target ID** column of the **Targets** tab. You can't change it later, so make sure you like it.

Configuration

Webhook URL: Add the full URL of your Slack Incoming Webhook. For example: `https://hooks.slack.com/services/T00000000/B00000000/XXXXXXXXXXXXXXXXXXXXXXXX`.

Retries

Honor Retry-After header: When toggled on and the `retry-after` header is present, Search honors any `retry-after` header that specifies a delay, up to a maximum of 20 seconds. Search always ignores `retry-after` headers that specify a delay longer than 20 seconds.

Search will log a warning message with the delay value retrieved from the `retry-after` header (converted to ms).

When toggled off (default), Search ignores all `retry-after` headers.

Settings for failed HTTP requests: Automatically retries after unsuccessful response status codes, such as `429` (Too Many Requests) or `503` (Service Unavailable). Selecting **Add Setting** reveals a table where you can add retry parameters for individual failed HTTP requests. These include:

- **HTTP status code**: The individual status code for which the retry parameters apply.
- **Pre-backoff interval (ms)**: How long, in milliseconds, Search should wait before initiating backoff. The maximum interval is 600,000 ms (10 minutes).

- **Backoff multiplier**: Base for exponential backoff. A value of `2` (default) means Search will retry after 2 seconds, then 4 seconds, then 8 seconds, and so forth.
- **Backoff limit (ms)**: The maximum backoff interval, in milliseconds, Search should apply. Default (and minimum) is 10,000 ms (10 seconds); maximum is 180,000 ms (180 seconds).

Retry timed-out HTTP requests: Toggle on if you want Search to automatically retries HTTP requests that have timed out. Defaults to off. Enabling this option exposes the following settings:

- **Pre-backoff interval (ms)**: How long, in milliseconds, Search should wait before initiating backoff. Maximum interval is `600,000 ms` (10 minutes).
- **Backoff multiplier**: Base for exponential backoff. A value of `2` (default) means Search will retry after 2 seconds, then 4 seconds, then 8 seconds, and so forth.
- **Backoff limit (ms)**: The maximum backoff interval, in milliseconds, Search should apply. Default (and minimum) is 10,000 ms (10 seconds); maximum is 180,000 ms (180 seconds).

After you've set and saved all of the above target configuration, you can set up Notifications that use the new Slack target as their destination.

Include Search Results with Slack Notifications

You can send Slack Notifications that include a subset of search results in the Notification payload. Once you've configured your Slack target, you specify this option separately on each Notification that uses the target.

To set this up:

1. Set up a Slack Notification target, as outlined above.
2. Open a scheduled search, and select **Notifications**.
3. Configure the Notifications, using the Slack Notification target you've created.
4. Within the configuration, enable **Include search results**.

Take the following into account:

- The results table can accommodate up to 100 rows and 20 columns. If it's larger, Cribl Search will truncate it.
- To make the results more legible, you can limit the number of fields sent (use the `project` operator) and the length of each field (use the `trim` function).

Security Risk

Embedding unverified or unsanitized search results into an AWS SNS Notification payload can pose unintended security risks. Cribl recommends reviewing result sets before including results with Notifications.

9.2.5. Webhook Notifications

Send webhook Notifications about your scheduled searches.

You can send Notifications to an arbitrary webhook. This topic outlines how to configure a Webhook target, and then how to send individual alerts to the corresponding endpoint

Target Configuration


In the **New Target** modal, select the **Webhook** radio button to expose multiple left tabs that provide the configuration options outlined below.

> For a streamlined, illustrated example of configuring a Webhook target, see Notifications via Cribl Stream.

General Settings

On this first left tab, fill in the following field.

Target ID: Enter a unique ID used to identify the target. This will show in the **Target ID** column of the **Targets** tab. You can't change it later, so choose an ID that will make this target's purpose clear to you and other users .



Configuration

This second left tab exposes the added options listed in this section.

URL: The endpoint that should receive Cribl Search Notification events.



To proxy outbound HTTP/S requests, see System Proxy Configuration.

Method: Select the appropriate HTTP verb for requests: `POST` (the default), `PUT`, or `PATCH`.

Format: Specifies how to format Notification events before sending them to the endpoint. Select one of the following:

- `NDJSON` (newline-delimited JSON, the default).
- `JSON Array`.
- `Custom`, which exposes these additional fields:
  - **Source expression**: JavaScript expression whose evaluation shapes the event that Search sends to the endpoint - for example: `notification=${_raw}`. For other fields you can use, see Expression Fields. If empty, Search will send the full Notification event as stringified JSON.
  - **Drop when null**: Toggle on if you want to drop events where the above **Source expression** evaluates to `null`.
  - **Event delimiter**: Delimiter string to insert between individual events. Defaults to newline character (`\n`).
  - **Content type**: Defaults to `application/x-ndjson`. You can substitute a different content type for requests sent to the endpoint. This entry will be overridden by any content types set in this modal's **Advanced Settings** tab > **Extra HTTP Headers** section.
  - **Batch expression**: Expression specifying how to format the payload for each batch. Defines a wrapper object in which to include the formatted events, such as a JSON document. This enables requests to APIs that require such objects. To reference the events to send, use the `${events}` variable. An example expression to send the batch inside a JSON object would be: `{"items" : [${events}] }`.

Expression Fields

When building the Source expression used with the `Custom` **Format**, you can use the following fields:


- `starttime`: Beginning of the time bucket where this condition was reported. All Notifications have this field.

- `endtime`: End of the time bucket where this condition was reported. All Notifications have this field.
- `_time`: Timestamp when this Notification was created. All Notifications have this.
- `cribl_host`: Hostname of the (physical or virtual) machine on which this Notification was created. All Destination and Source Notifications have this.
- `cribl_notification`: Configured name/ID of this Notification. All Destination and Source Notifications have this.
- `origin_metadata`: Object containing metadata about the Notification origin, with the following fields for all Destination Notifications:
  - `type`: "output".
  - `id`: ID of the affected Destination.
  - `subType`: Destination's type (where applicable).
- `origin_metadata`: Object containing metadata about the Notification origin, with the following fields for all Source Notifications:
  - `type`: "input".
  - `id`: ID of the affected Source.
  - `subType`: Source's type (where applicable).

Authentication

On this third left tab, select one of the following options for authentication:

- **None**: Don't use authentication.
- **Auth token**: Use HTTP token authentication. In the resulting **Token** field, enter the bearer token that must be included in the HTTP authorization header.
- **Basic**: In the resulting **Username** and **Password** fields, enter HTTP Basic authentication credentials.



Webhook Notification target - Authentication and lower tabs

Post-Processing Settings

System fields: In this section, you can specify a list of fields to automatically add to events relayed through this target. By default, includes `cribl_pipe` (identifying the Search Pipeline that processed the event). Supports wildcards. Other options include:

- `cribl_host` - Search Node that processed the event.
- `cribl_input` - Search Source that processed the event.
- `cribl_output` - Search Destination that processed the event.
- `cribl_route` - Search Route (or QuickConnect) that processed the event.
- `cribl_wp` - Search Worker Process that processed the event.

Retries

Honor Retry-After header: Whether to honor a `Retry-After` header, provided that the header specifies a delay no longer than 180 seconds. Search limits the delay to 180 seconds even if the `Retry-After` header specifies a longer delay. When enabled, any `Retry-After` header received takes precedence over all other options configured in the **Retries** section. When disabled, all `Retry-After` headers are ignored.

Settings for failed HTTP requests: When you want to automatically retry requests that receive particular HTTP response status codes, use these settings to list those response codes.

For any HTTP response status codes that are not explicitly configured for retries, Cribl Search applies the following rules:

Status Code	Action
Greater than or equal to `400` and less than or equal to `500`.	Drop the request.
Greater than `500`.	Retry the request.

Upon receiving a response code that's on the list, Search first waits for a set time interval called the **Pre-backoff interval** and then begins retrying the request. Time between retries increases based on an exponential backoff algorithm whose base is the **Backoff multiplier**, until the backoff multiplier reaches the **Backoff limit (ms)**. At that point, Search continues retrying the request without increasing the time between retries any further.

By default, this Destination has no response codes configured for automatic retries. For each response code you want to add to the list, select **Add Setting** and configure the following settings:

- **HTTP status code**: A response code that indicates a failed request, for example `429 (Too Many Requests)` or `503 (Service Unavailable)`.
- **Pre-backoff interval (ms)**: The amount of time to wait before beginning retries, in milliseconds. Defaults to `1000` (one second).
- **Backoff multiplier**: The base for the exponential backoff algorithm. A value of `2` (the default) means that Search will retry after 2 seconds, then 4 seconds, then 8 seconds, and so on.
- **Backoff limit (ms)**: The maximum backoff interval Search should apply for its final retry, in milliseconds. Default (and minimum) is `10,000` (10 seconds); maximum is `180,000` (180 seconds, or 3 minutes).

Retry timed-out HTTP requests: Toggle on to automatically retry requests that have timed out and configure the following settings for retry behavior:

- **Pre-backoff interval (ms)**: The amount of time to wait before beginning retries, in milliseconds. Defaults to `1000` (one second).
- **Backoff multiplier**: The base for the exponential backoff algorithm. A value of `2` (the default) means that Search will retry after 2 seconds, then 4 seconds, then 8 seconds, and so on.
- **Backoff limit (ms)**: The maximum backoff interval Search should apply for its final retry, in milliseconds. Default (and minimum) is `10,000` (10 seconds); maximum is `180,000` (180 seconds, or 3 minutes).

Advanced Settings

Validate server certs: Reject certificates not authorized by a CA in the **CA certificate path**, nor by another trusted CA (for example, the system's CA). Defaults to toggled on.

Round-robin DNS: Toggle on to use round-robin DNS lookup across multiple IPv6 addresses. When a DNS server returns multiple addresses, this will cause Search to cycle through them in the order returned.

Compress: Toggle on (default) to compress the payload body before sending.



If you accept this default, make sure that the endpoint receiving these Notifications supports compression.

Keep alive: By default, Search sends `Keep-Alive` headers to the remote server and preserves the connection from the client side up to a maximum of 120 seconds. Toggle **Keep alive** off if you want Search to close the connection immediately after sending a request.

Request timeout: Amount of time (in seconds) to wait for a request to complete before aborting it. Defaults to `30`.

Request concurrency: Maximum number of concurrent requests per Worker Process. When Search hits this limit, it begins throttling traffic to the downstream service. Defaults to `5`. Minimum: `1`. Maximum: `32`.

Body size limit (KB): Maximum size of the request body before compression. Defaults to `4096` KB, but you can set this limit to as high as 500 MB (512000 KB).

High values can cause high memory usage per Edge Node, especially if a dynamically constructed URL causes this target to send events to more than one URL. The actual request body size might exceed the specified value because the target adds bytes when it writes to the downstream receiver. Therefore, we recommend that you experiment with the **Body size limit** value until downstream receivers reliably accept all events.

Events-per-request limit: Maximum number of events to include in the request body. The `0` default allows unlimited events.

Flush period (sec): Maximum time between requests. Low values can cause the payload size to be smaller than its configured maximum. Defaults to `1`.

Extra HTTP headers: Name-value pairs to pass to all events as additional HTTP headers. Values will be sent encrypted. You can also add headers dynamically on a per-event basis in the `__headers` field; headers added by this method take precedence over headers defined in the **Extra HTTP headers** table.

Failed request logging mode: Use this drop-down to determine which data should be logged when a request fails. Select among `None` (the default), `Payload`, or `Payload + Headers`. With this last option, Search will redact all headers, except non-sensitive headers that you declare below in **Safe headers**.

Safe headers: Used to declare headers that are safe to log as plaintext. (Sensitive headers such as `authorization` will always be redacted, even if listed here.) Use a tab or hard return to separate header names.

Alerts Using the Target

After you've set and saved all of the above target configuration, you can set up Notifications that use the new Webhook target as their destination.

Include Search Results with Webhook Notifications

You can send Webhook Notifications that include a subset of search results in the Notification payload. Once you've configured your Webhook target, you specify this option separately on each Notification that uses the target.

To set this up:

1. Set up a Webhook Notification target, as outlined above.
2. Open a scheduled search, and select **Notifications**.
3. Configure the Notifications, using the Webhook Notification target you've created.
4. Within the configuration, enable **Include search results**.

Take the following into account:

9.2.6. Notifications Via Cribl Stream

Send Notifications about your scheduled searches through Cribl Stream to multiple downstream services.

This topic shows how to send Notifications to Cribl Stream Worker Groups, which can forward them to multiple downstream services, using workflows you've configured to also handle Notifications from Cribl Stream itself (and other Cribl products).

This technique is a convenient alternative to configuring multiple Webhook Notification targets in Cribl Search. Here, you configure a single Webhook target for the Worker Group, and let Cribl Stream multiplex the outbound Notifications from there.

We outline this technique in the following general steps:

- Identify Ingest Address for your Worker Group
- Add Webhook Notification Target in Cribl Search
- Schedule and Save Search and Notification
- Verify Inflow to Cribl Stream
- Configure Outflow from Cribl Stream

Identify Ingest Address

To find the ingest address of a Cribl-managed Worker Group, start in the Cribl.Cloud Organization that hosts your Cribl Search instance:

1. From the top bar, select **Products** > **Cribl**.
2. From the resulting sidebar, select **Data Sources**.
3. Use the **Group** drop-down to select the Cribl-managed Worker Group where you want to send the alerts.
4. Under **Sources Enabled by Default**, find the `http` entry.
5. Here, copy the **Ingest Address** (URL) of your Worker Group. This will point to port `10080`. The general format is:
   `https://<groupName>.<workspaceName>.<organizationId>.cribl.cloud:10080`


   An example with the most typical Group and Workspace names, and with a fictitious Organization name: `https://default.main.goat-farm.cribl.cloud:10080`



For a hybrid Group running on a host that you manage, the ingest address will typically be configured through your load balancer.

Add Webhook Notification Target


1. Navigate back to Cribl Search: Select **Products** > **Search**.
2. Select **Settings** > **Search** > **Notification Targets**.
3. Select the **Webhook** type.
4. Select **Add Target**.
5. Paste the **Ingest Address** URL that you copied from your Cribl.Cloud Organization, appending `/cribl/_bulk` as in this example:
   `https://default.main.<organizationId>.cribl.cloud:10080/cribl/_bulk`
6. Save the new target as `stream_webhook` or your desired name.



Configuring the Webhook Notification target


Schedule and Save Search and Notification

1. Create a search, customized according to your needs. The example shown here uses this query:
   `dataset="$vt_dummy" | extend alert="true"`
2. Select **Actions** > **Save** to open the configuration modal shown below.




Saving the search configuration

3. Schedule the search, according to your needs. This example sets a `* * * * *` cron schedule, to repeat the search every minute.



Scheduling the search

4. Add the Notification, pointing to the Webhook target you configured above.




Specifying the Notification

5. **Save** the search, with its configured schedule and Notification.

Verify Inflow to Cribl Stream

Next, make sure that Cribl Search is forwarding your Notifications to Cribl Stream:

1. In Cribl Stream, navigate to your targeted Worker Group.
2. Open the HTTP Source config modal: Select **Sources** > **HTTP**.
3. Select the **Live Data** tab, then its **Capture** button.
4. Set a long time window (several minutes), then select **Start**.
5. Wait. In about a minute, a properly configured alert will appear.


Sources › HTTP
http
Configure
Status
Charts
Live Data
Logs
Notifications
Filter Expression*
JS __inputId.startsWith('http:http:')
Fields
All
None
_raw
_time
cribl_host
cribl_notification
group
id
message
notificationId
now
orderedFieldNames
origin_metadata
origin_metadata.groupId
origin_metadata.id
origin_metadata.itemType
#
Event
1
56859-01-17 23:35:16.000 -06:00
_raw: Date: 2024-11-20T19:31:03.316Z
A notification was triggered for the scheduled search: webhook.1732131061078.mHKqHB,
Tenant ID: amazing-varahamihira
Search ID: webhook.
Notification: webhook_Notifi... Show more
_time: 1732131063316
cribl_host: ip-10-255-0-175
cribl_notification: webhook_Notification_1
group: default_search
id: SEARCH_NOTIFICATION_webhook_Notification_1_1732131063316
message: Date: 2024-11-20T19:31:03.316Z
A notification was triggered for the scheduled search: webhook.1732131061078.mHKqHB,
Tenant ID: amazing-varahamihira

10. Manage Cribl Search And Cribl.Cloud

Manage Cribl Search, your Cribl.Cloud Organization, and its Members, Permissions, usage, and billing.

Your Cribl Search instance is a part of a Cribl.Cloud Organization. This section covers how to manage the Organization itself, your Plan (credits and billing), and several aspects of access management and resource sharing.

Management Options by Permission

If you're an Organization Owner or Organization Admin, you can manage various aspects of your Cribl.Cloud Organization. You also automatically inherit all the Permissions of a Search Admin.

If you're a Search Admin, you can control most aspects of your Cribl Search environment.

For an overview of who can do what, see:

- Organization Member Permissions
- Search Member Permissions

Cribl.Cloud Organizations and Members

Learn how to manage your Cribl.Cloud Organization in the following sections:

- Manage Cribl.Cloud Organizations: Manage your Organization, configure network settings, and control user access.
- Manage Cribl.Cloud Members: Invite Cribl.Cloud Members, configuring their Permissions at the Organization or Cribl Search level.
- Cribl.Cloud Enterprise Plan: Explore the benefits of the Cribl.Cloud Enterprise Plan.
- FinOps Center: Check your plan and credits, track data usage, and download invoices.

Workspaces

Workspaces are isolated environments within your Cribl.Cloud Organization, each with its own Leader and access control. To make the most of them, see the following sections:

- Configure Workspaces: Add, edit, or delete your Cribl.Cloud Workspaces.
- Members and Teams: Fine-tune access control within your Workspaces, by configuring Members and Teams.

Usage Settings

Manage Notification targets, Usage Groups, and capacity limits, in the Cribl Search Settings.

Sharing

Share your Datasets, Dataset Providers, search results, and Dashboards with other Search Members.

10.1. Cribl.Cloud Access And Usage

Get an overview of the Cribl.Cloud environment that hosts Cribl Search and complementary Cribl products.

Cribl.Cloud provides a dedicated environment that hosts Cribl Search, Cribl Stream, Cribl Edge, and Cribl Lake, enabling you to start using Cribl products immediately. Cribl manages and scales infrastructure on your behalf.

Cribl.Cloud Resources

See these topics that cover creating and administering your Cribl.Cloud account, Organization, and authorization:

- Quick Setup: Register a Cribl.Cloud Organization to get started with Cribl Search.
- Manage Cribl.Cloud: Learn to switch between Cribl.Cloud Organizations and configure your Organization details.
- Manage Cribl.Cloud Members: Manage Cribl.Cloud access control - Members, invites, and Permissions.
- FinOps Center: Track your credit usage and billing across all Cribl products.

Cribl.Cloud Enterprise Plan

With a Cribl.Cloud Enterprise plan, you gain additional flexibility and options. These options include:

- Full role-based access control over Member Permissions and resources.
- Integrating external SSO authentication.
- Configuring and managing multiple Stream Worker Groups and Edge Fleets.
- Hybrid Stream Worker Groups.



For other Enterprise features, see Pricing.

10.1.1. Manage Cribl.Cloud Organizations

Manage your Cribl.Cloud Organization, configure network settings, and control user access.

Switch Organizations

When you own or are a Member of multiple Cribl.Cloud Organizations, you can switch between the Organizations:

1. In the top bar, hover over the name of your Organization.
2. In the drop-down, select the Organization you want to switch to.

Alternatively, in the drop-down you can select **Manage Organizations**. You will move to an Organization landing page, displayed to an Organization's Owners and Admins, where you can view details of all your Organizations, switch to any of them, add a new one or delete one, if you have proper permissions.

Configure Organization Details

To customize your Organization details, in the sidebar, select **Organization**.

You can modify the following information:

Field name	Description
Organization Name	A "friendly" name for your Organization. Upon signing in, Members will see this alias above the Organization ID on the Select Organization page.
Description	Add further details about your Organization.
Opt in to beta features	If displayed, this check box enables access to new options that Cribl has not yet made generally available. As with all beta features, expect some instability in exchange for advancing to the cutting edge of your Cribl.Cloud.

Select **Save** to immediately apply your changes.

You can check additional information about your Organization, including the AWS Cloud region in which it is located, the software version, and license, by selecting **Organization Details** at the bottom of the sidebar.

Manage Personal Settings

Use the **Account** menu at the top right of the Cribl.Cloud portal to configure your personal settings.

Select **My profile** to update your personal information. Here, you can also reset the configured biometric authentication. Do this, if you want to re-configure the authentication, or if you don't want to be prompted to

log in through fingerprint or face recognition.

Find Your Cribl.Cloud Organization Region

To locate your Organization region: In the Cribl.Cloud sidebar, select **Organization Details**.

Knowing your region helps you anticipate scheduled maintenance windows. The region may differ from your physical location.

Supported Cribl.Cloud Regions

Cribl.Cloud Government is supported exclusively on AWS US East/West Regions. Microsoft Azure is not supported.

AWS Region name	AWS Region	Azure Region Name	Azure Region
Asia Pacific (Tokyo)	`ap-northeast-1`	Japan East	`japaneast`
Asia Pacific (Singapore)	`ap-southeast-1`	Southeast Asia	`southeastasia`
Australia East	`ap-southeast-2`	Australia East	`australiaeast`
Canada Central	`ca-central-1`	Canada Central	`canadacentral`
Germany West Central	`eu-central-1`	Germany West Central	`germanywestcentral`
Europe (Zurich)	`eu-central-2`	Switzerland North	`switzerlandnorth`
Europe (Ireland)	`eu-west-1`	North Europe	`northeurope`
UK South	`eu-west-2`	UK South	`uksouth`
Europe (Paris)	`eu-west-3`	France Central	`francecentral`
South America (São Paulo)	`sa-east-1`	Brazil South	`brazilsouth`
US East (N. Virginia)	`us-east-1`	East US	`eastus`
US East (Ohio)	`us-east-2`	East US 2	`eastus2`
US West (Oregon)	`us-west-2`	West US 2	`westus2`

Get Support

In the top bar, select the **Support** icon to access a set of links with additional resources about Cribl Search, including:

- Sandboxes (free, interactive tutorials on fully hosted integrations)
- Cribl University
- Concept/demo videos

Refer to Cribl Status for information about Cribl.Cloud availability, including current and historical uptime data and incidents, split by component and AWS Region.

You can also subscribe there to incident notifications via email, text, Slack, or RSS.

10.2. Workspaces

Use Workspaces to create isolated environments within your Cribl.Cloud Organization.

Workspaces offer a multi-tenancy capability, enabling you to create multiple isolated instances in your Cribl.Cloud Organization. This lets you strengthen your security, and fulfill compliance and isolation requirements.

Each Workspace offers a dedicated virtual private cloud (VPC) that acts as a separate environment within your Organization. Workspaces do not share product configurations, resources, or data flows, and each has a separate Leader Node. They do share a layer of access control (Organization-level Permissions and SSO configuration), as well as API credentials, licenses, and billing.

A centralized interface allows you to manage all your Workspaces and control access for Members and Teams to individual Workspaces.

Multiple Workspaces require a Cribl.Cloud Enterprise plan.

An example use case scenario for creating multiple Workspaces is setting up separate environments for different business units in an enterprise. Data management, security, development, and any other units can have their own federated Workspaces, with completely separate Members and Permissions lists. This way, they can work in isolation without risk of interference and with increased focus.

Limitations

The number of included Workspaces depends on your Cribl.Cloud plan:

Plan	Included Workspaces	Additional Workspaces you can add
Standard	1 (the Main Workspace)	N/A
Enterprise	3	Up to 2, at 250 credits each per month

On an Enterprise plan, Organization Owners and Admins can add Workspaces beyond the included allowance. When you have used the 3 included Workspaces, you can add up to two more on the **Manage Workspaces** page for 250 credits each per month.

When you select **Add Workspace**, Cribl.Cloud opens **Accept additional cost?** Select **Accept** to continue, or **Cancel**. The confirmation states that each Workspace you add costs an additional 250 credits per month, reflected in your next billing cycle.

Charges for additional Workspaces appear on your invoice under **Infrastructure**. See Understand Your Monthly Invoice.

In Cribl.Cloud, one credit equals one US dollar. An additional Workspace therefore costs $250 per month, prorated daily. See How Is Cost Calculated?.

Switch Workspaces

When you have access to multiple Workspaces in your Cribl.Cloud Organization, you can switch between them from the top bar in any Cribl product:

1. On the top bar, select your current Workspace name.
2. In the drop-down, select the Workspace you want to switch to.

The drop-down lists **Manage Workspaces** first. Select it to open the Workspace management modal, where you can add, edit, or delete Workspaces.

Below **Manage Workspaces**, the drop-down lists your Workspaces with the current Workspace first, followed by other Workspaces in alphabetical order.

If your Organization has only one Workspace, selecting the Workspace name on the top bar opens the Workspace management modal directly.

Manage Workspaces

To list the Workspaces in the Organization, in the sidebar, select **Workspace** or **Organization** and then **Manage Workspaces**. The list includes the name, ID, description, Cribl Insights retention status, tags, Cribl version number, and current state for each Workspace in the Organization.

Select a Workspace name or the ellipsis (**. . .**) in the **Actions** column to edit the Workspace name, description, and tags or delete the Workspace.

Release Channels

In Cribl.Cloud, Enterprise customers can assign each Workspace to the Regular or Slow release channel.

The Regular release channel (default) follows the standard monthly release cadence. The Slow release channel also updates on a monthly basis but is one version behind the Regular release channel. Cribl sends monthly notifications describing the versions published to each release channel.

Release channels give you self-service control over the upgrade cadence for each Workspace and allow you to validate new Cribl versions in pre-production Workspaces before deploying them to production environments. Release channel selection does not affect your support or product lifecycle.

Release channels determine when Cribl publishes feature and maintenance releases to Workspaces:

- **Regular** release channel (default): Cribl publishes new feature and maintenance releases to the Regular release channel monthly.
- **Slow** release channel: Cribl publishes new feature and maintenance releases to the Slow release channel one month after the corresponding Regular release enters production.

If Cribl publishes a hotfix to the Regular release channel within the previous two weeks, Cribl delays the Slow release channel update until the following month.

Cribl does not update the Slow release channel in November or December.

Cribl might deliver critical security and other emergency updates outside the normal release channel schedule. In these cases, to protect customer environments, Cribl might update Workspaces assigned to the Slow release channel to the same version as Workspaces assigned to the Regular release channel.

Change the Release Channel for an Existing Workspace

To change the release channel for an existing Workspace:

1. On the top bar, select the current Workspace name, then select **Manage Workspaces**.
2. Next to the Workspace that you want to update, select **Settings** in the **Actions** column.
3. On the **Details** page, select the **Release Channels** tab.
4. Select **Regular** or **Slow**.
5. Select **Save**.

Cribl does not immediately change a Workspace's version when you change its release channel. The Workspace stays on its current version until the next scheduled upgrade cycle.

Cribl does not downgrade a Workspace when you change it to the Slow release channel. Cribl does not support rolling back Workspaces to earlier versions.

If your Workspace includes customer-managed Worker Nodes or Edge Nodes, do not upgrade them to a version newer than the Leader Node version. For version compatibility requirements, see Supported Version Differences Between Leader and Workers and Supported Version Differences Between Leader and Edge Nodes.

View Workspace Details

Workspaces provide a set of information that you can use when configuring data flow through their Edge Nodes.

View Access Details

To view detailed access information of your Workspace, in the sidebar, select **Workspace** and then **Access**.

This page presents a summary of information about your Cribl.Cloud Organization, as well as the **Cribl.Cloud URL** for the current Workspace.

Cribl.Cloud URL

Cribl.Cloud URL is a static address associated with the load balancer that is in front of the Leader. Hybrid Stream Workers will connect to this address on port 4200, while the Leader UI is served from this address on port 443.

You can use this URL for certain API calls and certain Collection operations coordinated by the Leader.

Static External IPs for the Leader

The **Leader NLB IPs** field in **Workspace** > **Access** lists the IPs for the Leader Network Load Balancers associated with the Workspace.

Typically, only 2 of the 3 addresses will be active (returned by DNS) at any time, while the inactive address is swapped in during infrastructure maintenance events.

You can add all those IPs to your firewall allowlist to ensure that the load balancers are accessible across your hybrid deployment.

Get ARN

To get the ARN (Amazon Resource Name) for your Workspace, in the sidebar, select **Workspace** and then **Trust**.

You can copy and paste the **Worker ARN**s listed in the **Trust** page to attach a Trust Relationship to an AWS account's IAM role. Use the **Group** drop-down to display the ARN for any Group of Cribl-managed Stream Worker Groups in Cribl.Cloud.

Attaching a Trust Relationship enables the `AssumeRole` action, providing cross-account access. For usage details, see the AWS Cross-Account Data Collection topic's **Account B Configuration** section.



This option applies only to your Cribl-managed Stream Workers in Cribl.Cloud. You cannot use this technique to enable access to customer-managed hybrid Workers.

Set Up ACL

To set up Access Control List (ACL) Rules, in the sidebar, select **Workspace** and then **Access Control List**.

ACL Rules (IPv4 CIDR ranges) let you restrict data sent to your data sources. The Rules you define here are global to all Cribl-managed Worker Groups in Cribl.Cloud in the current Workspace. You can set up a maximum of 9 ACL Rules.

The default `0.0.0.0/0` rule (modifiable) imposes no limits. End a rule with `/32` to specify a single IP address, or with `/24` to enable a whole CIDR block from `x.x.x.0` to `x.x.x.255`.

Select **Save** after adding, modifying, or removing rules. Each change takes up to 5 minutes to propagate. Cribl.Cloud will display a banner, notifying you that rules edits are temporarily disabled to prevent conflicts. A successful update proceeds silently - you will not see a confirmation message.



The **ACL** options apply only to Cribl-managed Stream Workers in Cribl.Cloud. You cannot use them to set access rules on customer-managed hybrid Workers.

10.2.1. Configure Workspaces


Add, edit, or delete your Cribl.Cloud Workspaces.

Add New Workspace

To create a new Workspace:

1. On the top bar, select the name of the current Workspace and then **Manage Workspaces**. This opens a modal with a list of all Workspaces to which you have access.
2. Select **Add Workspace**. Only Organization Owners and Organization Admins can add a Workspace.
    - If the Organization has used its included three Workspaces, Cribl.Cloud opens **Accept additional cost?** Select **Accept** to continue, or **Cancel**. See Workspace Limitations.
    - The confirmation states that you have reached your current Workspace limit, that each Workspace you add costs an additional 250 credits per month, and that the charge will appear in your next billing cycle.
3. Enter the following information:
    - **Workspace Name**: Human-readable name for the Workspace.
    - **Workspace ID**: Internal ID for the Workspace. This ID will be part of the Cribl.Cloud URL. **Cannot be changed** once the Workspace is created.
    - **Description**: Brief description for the Workspace (optional).
    - **Workspace region**: AWS Region where you want to deploy the Workspace. **Cannot be changed** once the Workspace is created.
    - **Tags**: Up to three tags that you can use to filter Workspaces (optional).

    If this Workspace is beyond the included allowance, the **Details** step shows that the Workspace will cost 250 credits per month, reflected in your next billing cycle.
4. Select **Next**.



Creating a new Workspace

5. Optionally enable Insights for the Workspace and choose a data retention tier, then select **Next**.
6. Select the release channel to use for the Workspace.
    - **Regular** (default): Get new feature and maintenance releases every month.
    - **Slow**: Get new feature and maintenance releases 1 month after the Regular release channel goes into production. If the Regular release channel has a hotfix in the previous 2 weeks, the Slow release channel is delayed until the following month. No releases in November or December. If needed, critical security upgrades may also ship on the Slow release channel.
7. Select **Save**.

The Workspace can take up to several minutes to spin up. While the process continues, you can navigate away and keep working with your Cribl.Cloud instance as usual.

Workspace Regions

When you add a new Workspace, you can select the AWS Region where you want to deploy it. The default Workspace `main` is always deployed in the same Region as the Organization, but you can deploy additional Workspaces in any of the following AWS Regions:

AWS Region Name	AWS Region Code
Asia Pacific (Singapore)	`ap-southeast-1`
Asia Pacific (Sydney)	`ap-southeast-2`
Asia Pacific (Tokyo)	`ap-northeast-1`
Canada (Central)	`ca-central-1`
Europe (Frankfurt)	`eu-central-1`
Europe (Ireland)	`eu-west-1`
Europe (London)	`eu-west-2`
Europe (Paris)	`eu-west-3`
Europe (Zurich)	`eu-central-2`
South America (São Paulo)	`sa-east-1`
US East (N. Virginia)	`us-east-1`
US East (Ohio)	`us-east-2`
US West (Oregon)	`us-west-2`

Edit or Delete a Workspace

To edit a Workspace:

1. On the top bar, select your current Workspace name. This opens a modal with a list of all Workspaces you have access to.
2. Next to the Workspace you want to edit, select **Settings** in the **Actions** column to open the **Details** page for the Workspace.
3. On the **Details** page, you can change the name of the Workspace, description, and tags. However, you can't change the Workspace ID after it has been created.
4. Select **Save**.

For all Workspaces except `main`, you can select **Delete Workspace** on the **Details** page to delete it. You will

10.3. Usage Settings

Manage Notification targets, Usage Groups, and capacity limits.

You can manage Cribl Search settings (as well as Cribl global settings) by selecting **Settings** from the sidebar. When you do so from within Cribl Search, the **Settings** > **Search** upper tab automatically gains focus.

You'll now see left tabs where you can configure the Cribl Search-specific settings listed below. (Adjacent tabs provide access to **Global** settings that govern your whole Organization, and to settings specific to other Cribl products.)

- Notification targets receive notifications from scheduled searches.
- Usage Groups define groups for controlling limits.
- Limits control searches and the UI.



Certain Cribl Search settings can be overridden by `set` statements in your queries.

Set the Limits of Search Results

By default, Cribl Search returns up to **50,000** results per search.

You can change this limit at three levels:

- Organization level (between 1 and 10 million).
- Usage Group level (between 1 and the Organization limit).
- Per-search level (between 1 and the Usage Group limit).

Certain Dataset Provider types also have their own results limits:

- Elasticsearch Results Limit
- OpenSearch Results Limit

Set the Results Limit for the Organization

A Search Admin can set the system-level limit that applies to all searches in the Organization, by changing the **Results limit** parameter of the **system** Usage Group:

1. Go to the **Usage Groups** page in Cribl Search: On the top bar, select **Products** > **Search** > **Settings** > **Usage Groups**.
2. Select the **system** Usage Group.
3. Change the **Results limit** to any value between `1` and `10000000`.

4. Save your changes.

Now, all searches in your Organization will be limited to the number of results you specified.

Set the Results Limit for a Usage Group

A Search Admin can set the results limit for a specific Usage Group. This limit will apply to all searches run by the group's members, and will be capped by the Organization limit.

1. Go to the **Usage Groups** page in Cribl Search: On the top bar, select **Products** > **Search** > **Settings** > **Usage Groups**.
2. Select the Usage Group you want to change.
3. Change the **Results limit** to any value between `1` and `10000000`.
4. Save your changes.

Set the Results Limit for a Search

Apart from using the `limit` operator, any user can set the results limit for a specific search by adding the `max_results_per_search` option in a `set` statement at the beginning of the query.

```
set max_results_per_search=1000;

dataset="cribl_search_sample"
```

Copy | Run in Cribl Search

For a regular user, this limit will be capped by their Usage Group limit, which in turn is capped by the Organization limit. For a Search Admin, the `max_results_per_search` value can override the Organization limit up to the maximum of 10 million.

10.3.1. Usage Groups

Control access to resources for specific Search Members, by creating Usage Groups.

Usage Groups enable you to assign limits to searches by specific users. By setting limits, you can prevent inefficient queries either by disallowing them, or by terminating their execution if they exceed a limit.



To set up general limits that apply to all searches in your Organization, see the limits topic.

Cribl Search provides two Usage Groups by default:

- **system** - Provides system-level limits that apply to all searches.
- **default** - Covers all ad hoc searches, unless covered by a different group.

Creating Usage Groups

To create a Usage Group, select **Settings** > **Search** > **Usage Groups**, then select **Add Usage Group**. This opens a **New Usage Group** modal.

On the modal's **Configuration** tab, give the group a name, and set up desired limits that members of this group will be bound by. Activate the group by making sure the **Enabled** toggle is selected before you save the configuration.

To assign users to a group, on the **Members** tab, select **Add Members** . All users who have the **User** or **Editor** Search Member Permissions are eligible to be group Members.

Usage Limits

You can configure the following usage limits for each group:

- **Earliest relative time range** - How far back in time the search can go. For example: `60m`, `30d`, `6mon`, `1y`. To specify time in seconds, enter a number with no time unit. This limit can be overridden by `max_earliest_relative`.
- **Time range limit** - Maximum time range for one search query, for example 3 days (`3d`). This limit can be overridden by `max_timerange_width`.



When managing each of the following three **concurrent** limits: Indicate a percentage (of CPU capacity on the Leader) by appending `%`. Reduce the default `100%` if you notice an impact on UI responsiveness, or on workloads like Stream Collector jobs. A Leader with only 1 CPU will treat all values as `100%`. You also have the option to allocate an absolute number of CPUs on the Leader, by omitting the `%`.

- **Concurrent ad hoc search limit** - Maximum volume of ad hoc searches that all Members of this Group can run simultaneously. Queries exceeding this limit will get queued. This limit can be overridden by `max_searches_per_user`, and by the **Overall concurrent search limit** value in this modal.
- **Concurrent scheduled search limit** - Maximum volume of scheduled searches that all Members of this Group can run simultaneously. Queries exceeding this limit will get queued. This limit can be overridden by `max_scheduled_searches_per_user`, and by the **Overall concurrent search limit** value in this modal.
- **Overall concurrent search limit** - Maximum number of simultaneous searches allowed across your Organization.
    - Percentage values for all **concurrrent** limits are calculated as: `Math.min(1, numCPU x maxConcurrentSearches/100)`.
    - Cribl Search will be entirely disabled if this number is set to `0`.
    - When dynamic search concurrency is on for the **system** Usage Group, this field is read-only and Cribl Search adjusts the cap automatically based on its current load.
- **Results limit** - Maximum number of events that can be returned per search.
    - Default is `50000`.
    - Minimum of `1`.
    - Maximum of `10000000`. When a search exceeds this limit, Cribl Search displays a warning in the results toolbar indicating that results may be incomplete. To reduce the number of results returned, see Optimize Searches. To raise the limit, override it with `max_results_per_search` or see Overriding Limits.
    - If set for the **system** Usage Group, the limit will apply to all searches in the Organization, including Packs and Dashboard parent searches.
- **Executors limit** - Maximum number of executors dispatched per search.
    - Default is `50`.
    - Minimum of `1`.
    - This limit can be overridden by `max_executors`.
- **Byte limit** - Maximum number of bytes that can be read per search. When the limit is exceeded, the search gets canceled. This limit can be overridden by `max_bytes_read_per_search`.
- **Running time limit** - Maximum time, in seconds, that a single search is allowed to run.
    - Default is `28800` seconds (8 hours).
    - This limit can be overridden by `max_running_time_per_search`.
- **Coordinator heap memory limit** - Memory allocation (in MB) for the search coordinator process.
    - Default is literally labeled `default`, which delegates to the Node.js default.

- Set a slightly higher value if you experience out-of-memory errors due to high Dataset cardinality or other conditions.
- Be aware that very high settings might compromise other applications.
- This limit applies only to new search coordinator processes. If a coordinator is reused, the new value takes effect only after that coordinator terminates and a new one starts.

Overriding Limits

Certain usage limits can be overridden by `set`-statement options, for example: `set max_searches_per_user=100000`.

Admins can also run a query as a specific Usage Group with: `set usage_group="secops"`.

The following `set` options correspond to the limits configured in the UI described above:

Limit	Setting
Earliest relative time range	`max_earliest_relative`
Time range limit	`max_timerange_width`
User concurrent ad hoc search limit	`max_searches_per_user`
User concurrent scheduled search limit	`max_scheduled_searches_per_user`
Results limit	`max_results_per_search`
Executors limit	`max_executors`
Byte limit	`max_bytes_read_per_search`
Running time limit	`max_running_time_per_search`

10.3.2. Limits

Configure limits that apply to all searches performed in your Cribl Search instance.

You can configure limits that control search history and the granularity of search summaries displayed in the UI.

Limits listed in this section apply to all searches performed in your Organization. (You can define specific limits per user by configuring Usage Groups.)

Certain limits can be overridden by `set` statements in your queries.



When dynamic search concurrency is on, Cribl Search adjusts the maximum number of concurrent searches automatically based on current load.

List of Configurable System Limits

The following limits are available at **Settings** > **Search** > **Limits**:

- **Enable dynamic concurrency**: When enabled, Cribl Search automatically adjusts the maximum number of concurrent searches based on CPU and memory pressure. This setting is on by default. For details, see Dynamic Search Concurrency.
- **Scheduled search jitter percent**: Percentage of the scheduling interval to use as a random jitter window for scheduled searches. This spreads scheduled search execution times to reduce load spikes. You can override this limit for a specific scheduled search, using the **Jitter percent** setting.
  - Default is `20`.
  - Minimum of `0`, which disables jitter.
  - Maximum of `50`.
- **Search history TTL**: Amount of time to keep search artifacts around before removing them.
  - Default is `7d` (7 days).
  - Minimum of `0`, which instructs Cribl Search to not retain search artifacts at all.
  - You can override this limit for a specific scheduled search, using the **Keep last executions** setting.
  - Notebooks have a hard-coded 30-day retention period to facilitate extended investigations. Exceeding the **Search history job limit** will cause other jobs to be removed before Notebook jobs, to respect this extension.
- **Search history job limit**: Maximum number of search jobs to retain before removing the oldest ones.
  - Default is `1000`.

    - Minimum of `0`.
    - You can override this limit for a specific scheduled search, using the **Keep last executions** setting.
- **Field summary nested depth limit**: Maximum depth supported when building field summaries on nested object values. For example, `x.y.z` corresponds to the default depth of `3`. Increase this default if you need to go deeper. For complex datasets with deeply nested structures, this limit prevents excessive resource consumption during field discovery.
    - Default is `3`.
    - Minimum of `1`.
- **Field summary breadth limit**: Maximum number of distinct fields to include (before truncation) when generating field summaries on objects. Reduce this limit to improve performance with complex Datasets.
    - Default is `200`.
    - Minimum of `0`.
- **Prevent revealing Dataset Provider secrets** (Admin only): When enabled, credentials used for configuring Dataset Providers (such as secret keys) are obfuscated.
    - Default is **Yes**.

List of Fixed System Limits

The following limits are not configurable:

- **Field size limit**: Maximum per-field payload size enforced on fields (like `_raw`). When results are rendered, Cribl Search will truncate or omit oversized payloads to maintain responsiveness. This limit applies to all searches.
    - Set to `2` MB per field, and not configurable.
- **Numeric precision limit** (Lakehouse only): Integer literals in queries are limited to the IEEE 754 safe integer range (±(2^53 − 1), or ±9,007,199,254,740,991). Integers outside this range, and values that overflow `Float64` to infinity (such as `1e309`), are automatically treated as strings in Lakehouse searches. To search on a large numeric value as a string, enclose it in quotes. For details and examples, see Numeric Precision Limits for Large Integers.

10.4. Manage Access To Cribl Search Resources

Grant fine-grained access rights on individual Datasets, Dataset Providers, Dashboards, Notebooks, and search results.

Cribl Search offers two layers of Permissions for Members, Teams, and API Credentials:

- Product-level Permissions: **User**, **Editor**, **Admin**, or **No Access**.
- Resource-level Permissions on Datasets and Dataset Providers, Dashboards, and Notebooks: **Maintainer** or **Read Only**.

You can grant resource-level Permissions on:

- Datasets (including Cribl-hosted Search Datasets, federated Datasets, and Cribl Lake Datasets)
- Dataset Providers
- Dashboards
- Search results
- Notebooks (see also Notebook templates)

Resource **Maintainers** can assign access to:

- Members of an Organization and Teams that group Members together.
- API Credentials for service accounts that connect to Cribl Search via API.

Share Datasets, Dataset Providers, Dashboards, and Notebooks

Members, Teams, and API Credentials with the Search **Editor** or **User** Permission do not, by default, have access to existing Datasets, Dataset Providers, Dashboards, or Notebooks. They receive the **Maintainer** Permission on resources that they create. Only Search **Editors** and Search **Admins** can create Datasets and Dataset Providers. Search **Users** can create Dashboards and Notebooks, but not Datasets or Dataset Providers. Search **Admin** Members, Teams, and API Credentials automatically inherit the **Maintainer** Permission on all resources at this level.

As a **Maintainer**, here is how to share a Dataset, Dataset Provider, Dashboard, or Notebook with a Member, Team, or API Credential whose Search Permission is **User** or **Editor**:

1. Select **Data** (for Datasets and Dataset Providers), **Dashboards**, or **Notebooks** from Cribl Search's sidebar.
    - For Datasets and Dataset Providers, select either the **Datasets** or **Dataset Providers** tab.
2. In the **Actions** column of the resource you want to share, select **Share**.

3. Under **Add Members, Teams, and API Credentials**:
    - From the left drop-down menu, select the Member, Team, or API Credential that you want to share the resource with.
    - From the right drop-down menu, select the Permission you want to grant: **Read Only** or **Maintainer**. For details, see Cribl Search Dataset Providers and Datasets, Cribl Search Dashboards, or Cribl Search Notebooks.
4. Select **Add Access**.
5. Select **Save**.

To modify or remove the resource-level Permission on a Dataset, Dataset Provider, Dashboard, or Notebook, find the Member, Team, or API Credential in the list on the **Sharing** pane. Select the desired Permission from the drop-down menu in the **Permission** column and save. Selecting **No Access** removes all access rights on the resource.

Revoke Dataset Access

If a **Maintainer** un-shares a Dataset from a Member or Team, or removes a Member from an authorized Team, the Member's past interaction with the Dataset determines their remaining access.


If a Member has performed a search against the Dataset, they retain access to its data and search results in the search history.

However, the Dataset itself is no longer visible to the Member, and the Member cannot re-run searches against that Dataset.

Share Search Results

You can set search results as either **Private** (the default) or **All Members**. **Private** results are visible only to you, and are hidden from other Members and Teams.

After running a search and viewing its results, you can open the **Actions** drop-down to change the search's **Results Access**.



Share Search Results


After that, other Members and Teams can see and reuse the search results in their own **History**.

You can also change the visibility of your searches with a `set` statement, using the `job_visibility` option.

The **Actions** menu provides more options on the **Fields** and **Charts** tab than are displayed in the above screenshot, which is from the **Events** tab.

Share Scheduled Search Results

Open a scheduled search's configuration modal to adjust its **Results Access** setting. Your saved setting applies to any subsequently created result sets from this search.



Managing access to a scheduled search

Share Search Results via URL

You can share displayed search results by copying the URL from your browser's address bar.

10.5. Cribl Search Engines

Understand engines that power Cribl Search and how to size them for your environment.


Cribl Search Engine Types

Cribl Search gives you two main compute surfaces:

- **Lakehouse**, where you ingest and store data in Cribl Search for the fastest, most guided experience.
- **Federated search**, where you query data in place in external systems like S3 or Lake/Lakehouse.

Engines are how you size those surfaces:

- **Lakehouse engines** control how much data you can ingest, store, and search in a given Workspace.
- The **federated engine** controls how much federated search capacity you provision at the Workspace level.



Lakehouse engines and the federated engine

Engines Are the Capacity Units Behind Search

Each engine setting defines how much capacity your Workspace can allocate to a specific search mode.

- **Lakehouse engines** provide both storage and compute for data you ingest into Cribl Search. You can provision multiple lakehouse engines per Workspace.
- The **federated engine** provides compute only, for search-in-place over data that stays in external systems. Each Workspace has a single, globally sized federated engine.

You manage the federated engine from the same place as lakehouse engines, in Cribl Search, select **Data** > **Engines**.

For information about billing, see How Lakehouse and Federated Engines Are Billed.

Lakehouse Engines

A **lakehouse engine** is a storage-plus-compute unit that backs **Get Your Data In** and **Search Datasets**. It keeps your data hot for up to 10 years, with no storage tiering to manage.

When you route data into Cribl Search with Sources, it's parsed by Datatypes and stored in Search Datasets on a lakehouse engine.

Each lakehouse engine:

- Accepts data from one or more Sources.
- Uses Datatypes to break events into fields.
- Stores data in Search Datasets until their retention expires.
- Powers fast, schema-aware searches and AI workflows over that stored data.

From a sizing perspective, you control two things:

- **Lakehouse engine size** (per engine): How much uncompressed data per day that engine is designed to ingest. Sizes range from **Nano** through **6X-Large**.
- **Retention period** (per Dataset): How long to keep the data on that engine.

For details on how lakehouse engines work, which sizes are available, and how to add or resize them, see:

- Get Your Data In: lakehouse engines in the ingest workflow.
- Lakehouse engines in Cribl Search: lakehouse engine sizes, billing, and step-by-step management.

Federated Engine

The federated engine is a Workspace-wide compute tier for federated search.

Federated search runs queries directly against external storage such as S3, Blob, or Lake/Lakehouse, without ingesting that data into lakehouse engines. Instead of creating multiple federated engines, each Workspace has a single federated engine with a configurable size.

The federated engine:

- Applies to all federated searches in the Workspace.
- Does not store data, it provides compute for search-in-place.
- Is independent of any lakehouse engine you configure.

Federated Engine Size Sets Workspace Federated Capacity

When you set the federated engine size, you define the capacity tier used for federated workloads in that Workspace. That choice:

- Acts as a capacity and entitlement signal for federated workloads.
- Is visible to Cribl billing, so your federated usage is interpreted in the context of the size you selected.

The federated engine size limits the number of concurrent federated searches allowed in your Cribl.Cloud Workspace. Searches that exceed the limit queue until capacity becomes available. You can also think of the federated size as:

- A way to align how heavily you expect to use federated search with how your account is configured and billed.
- A unit that's simple enough to choose in the UI, while exact thresholds and pricing remain governed by your contract and Cribl billing systems.

Changing the federated size:

- Does not resize any lakehouse engine.
- Does not change how much lakehouse data you can ingest or store.
- Only updates the Workspace-level federated capacity tier.

Billing Model Determines Available Federated Options

The federated selector behavior changes based on your current billing model.

Search Subscription

If you have an existing **Search Subscription** contract:

- Your Workspace appears with a federated size of **Search Subscription** when federated compute is enabled.
- The selector in **Search** > **Data** > **Engines** is disabled. You cannot change the size or switch to `Usage Based` from the UI while the subscription is active.
- You cannot switch to or from Search Subscription using the selector. This state is system-managed based on your contract.

In practice, Search Subscription reflects the federated capacity that your subscription already entitles you to. You continue to use federated search under that contract until it ends.

When the subscription expires, the UI will prompt you to choose:

- One of the **tiered federated sizes**, or

- **Usage Based (Pay-as-you-go)**, which remains available but is discouraged for long-running, high-volume federated workloads because costs can be harder to predict.

Tiered Federated Billing

If you are not on a legacy Search Subscription and your account uses tiered federated billing:

- The federated selector is fully enabled.
- You can move between fixed sizes within the constraints of your billing plan.

You choose a size based on how central federated is to your environment. Over time, you can revisit that choice as usage patterns become clearer.

Usage-Based Federated Billing

If you are billed on usage for federated search:

- The selector will show **Usage Based (Pay-as-you-go)** as the active choice initially.
- You can move from Usage Based into a tiered federated size when you are ready, and back again if your contract allows.

Federated Engine Sizes

The federated size selector is intentionally high-level: instead of asking you to reason about internal metrics, it asks you to decide how important federated search is to your day-to-day work and how predictable you want your costs to be.

Depending on your billing plan, you can choose from the following sizes:

- **Tiered Sizes:** Nano, Micro, X-Small, Small, Medium, Large, X-Large, 2X-Large, 3X-Large, 4X-Large, 5X-Large, and 6X-Large.
- **Usage Based (Pay-as-you-go):** Available for occasional or experimental use, though steady, production-grade usage is steered toward named tiers to prevent unpredictable costs during spikes.
- **Search Subscription:** A system-managed state for legacy contracts that entitles you to a fixed capacity.

In general:

- If federated search is central to how you operate (for example, teams run investigations, dashboards, or scheduled searches against S3 or Lake/Lakehouse every day or week), then a **tiered federated size** is the right starting point.
- If federated use is occasional or experimental, starting on **Usage Based (Pay-as-you-go)** can make sense while you learn how often it will be used, with a plan to move to a tier once usage stabilizes.

When to Change Federated Size

Federated sizing is not a one-time decision. You should revisit it when:

- Federated moves from being an occasional tool to a core part of investigations or reporting for multiple teams.
- Your Cribl billing/FinOps views show that federated usage has become a steady, high-volume component of your spend.
- You transition out of a Search Subscription state and want your federated capacity to match your current usage rather than the old contract.

How Lakehouse and Federated Engines Are Billed

The two engine types are billed differently because they do different jobs. Lakehouse engines store and search data inside Cribl Search. The federated engine runs searches over data that stays in external systems.

Aspect	Lakehouse Engine	Federated Engine
What you pay for	Engine size (a daily ingest limit). Storage retained on the engine.	One of: Engine size (a compute capacity tier). Usage-Based (Pay-as-you-go) credits. Legacy Search Subscription.
What we measure	Engine size: uncompressed ingest at the engine, separately from any upstream processing in Stream or Edge. Storage: retained, compressed data.	Compute consumed per search.
Are individual searches billed?	No.	Federated engine: no. Usage-Based: yes. Search Subscription: no.

You select one lakehouse engine size per engine, and one federated engine size per Workspace. For the available sizes and how to choose them, see Lakehouse Engine Sizes and Federated Engine Sizes.

For pricing details, see Cribl Search Pricing.

10.6. Configuration Files

Configuration files store the configuration changes locally on your system. They reflect the changes you make to configuration settings in the UI.

You can preview how settings are translated into configuration changes in the Git Changes modal whenever you commit your changes via the Version Control option.

Configuration file	Description
`breakers-search.yml`	Cribl Search Event Breaker settings.
`compute-fleets.yml`	Compute fleets for Cribl Search.
`dashboard-categories.yml`	Dashboard categories in Cribl Search.
`federated-search-engines.yml`	Federated engine configuration.
`local-search-dataset-rulesets.yml`	Dataset rules.
`local-search-datatype-rulesets.yml`	Datatype rules.
`macros.yml`	Macros in Cribl Search.
`saved-queries.yml`	Saved searches in Cribl Search.
`search.yml`	Cribl Search system configuration.
`search-limits.yml`	Limit configuration for Cribl Search.
`search-usage-groups.yml`	Cribl Search Usage Groups.

11. Optimize Cribl Search

Query, partitioning, and workflow strategies to maximize Cribl Search efficiency.

The following topics offer strategies and tips for optimizing your searches. They provide guidelines for designing efficient queries, partitioning paths effectively, and other practices to get the most out of Cribl Search.

- Optimize Searches
- Optimize Paths
- Investigative Searching
- Productivity Tips
- Useful Queries (Analytic Cookbook)
- Dynamic Search Concurrency

For a quick-reference summary of Cribl Search compatibility, sample operators and expressions for common queries, and optimization suggestions, download our Cribl Search Tip Sheet.

11.1. Optimize Searches

Get strategies and tips for optimizing your searches.

The practices on this page help you make searches more efficient and faster.

Constrain Initial Query with Limit, Count, or Time Window

Until you're certain how large your Dataset is, you should add a `limit`, `count()`, or time limit to your initial query.

Instead of this:

```
dataset="cribl_search_sample"
```

Copy

Do this:

```
dataset="cribl_search_sample" | limit 1000
```

Copy

Or this:

```
dataset="cribl_search_sample" dataSource="access_combined"
 | limit 1000
 | summarize count() by host, clientip
```

Copy

Or this, to constrain results to a 2-month window:

```
dataset="cribl_search_sample" earliest=-2mon
```

Copy

Unstructured Searches Are Fastest

Unstructured term searches will return faster than structured searches. Consider using a broad search (with a limit) in initial investigations.

Instead of this:

```
dataset="my_dataset" email="jim@company.com" | limit 1000
```

Copy

Do this:

```
dataset="my_dataset" "jim@company.com" | limit 1000
```

Copy

Place Filters Early in Queries

Try to push filtering expressions to the left-most side of your query wherever possible.

Instead of this:

```
dataset="<my-datasource>"
| where tenantId == "foo-bar-12345"
| where proc == "bash"
| where data_source == "stdout"
```

Copy

Do this:

```
dataset="<my-datasource>" tenantId="foo-bar-12345" proc="bash" data_source="stdout"
```

Copy

Place Intensive Operations Last

To minimize costs, try to move functions like `lookup` and `sort` to the right-most part of a query. First, filter or aggregate your Dataset to reduce the data volume sent to these functions.

Instead of this:

```
dataset="<my-datasource>" dataSource="VPC Flow Logs" | lookup service_names on dst_pc
```

Copy

Do this:

```
dataset="<my-datasource>" dataSource="VPC Flow Logs" | summarize count() by dst_port
```

Copy

Summarize to Search Faster

Any search that returns a large number of raw events back to the UI will be slower than a summary result set.

Instead of this:

```
dataset="my_data"
```

Copy

Do this:

```
dataset="my_data" | summarize count() by cid
```

Copy

Summarize Before Join

When using joins with aggregation operators, it's more efficient to summarize-then-join rather than join-then-summarize.

Instead of this:

```
let URLMethods=dataset="access_common_data";

dataset="my-datasource" | join URLMethods on URL | summarize count() by method
```

Copy

Do this:

```
let URLMethods=dataset="access_common_data" | summarize count() by URL, method;

dataset="my-datasource" | summarize count() by URL, method | join URLMethods on URL
```

Copy

Search Faster with Comma Syntax

Many operators can perform multiple functions simultaneously if you link your query together using commas instead of pipes.

Instead of this:

```
... | extend field1="foo" | extend field2="bar" | extend field3="pike"
```

Copy

Do this:

```
... | extend field1="foo", field2="bar", field3="pike"
```

Copy

Move Partition Tokens to Queries

Token-based partitions in your Dataset can drastically increase your search time if the directory paths are very broad. If you instead specify the tokens as part of your search, this will reduce the search span to only those sub-trees. Ideally, keep time to the left-most portion of your path, and keep tokens to the right wherever possible, as shown here.

If this is your Dataset definition:

```
data/${dataSource}/${_time:%Y}/${_time:%m}/${_time:%d}/${_time:%H}
```

Copy

Then instead of this:

```
dataset="myDataset" | summarize count() by destination | where dataSource="cisco"
```

Copy

Do this:

```
dataset="myDataset" dataSource="cisco" | summarize count() by destination
```

Copy

Send Exclusively to Cribl Stream to Speed Up Large Result Sets

When search results expand beyond several thousand events, sending the results to Cribl Stream via the `send` operator is faster than returning events to the Cribl Search UI.

Instead of this:

```
dataset="my_data" | send tee=true
```

Copy

Do this:

```
dataset="my_data" | send
```

Copy

Lakehouse: Use `where` for Case-Sensitive Searches

When performing a case-sensitive search against a Lakehouse, using the case-sensitive `where ==` syntax can provide faster performance than using the implicit `cribl` operator.

Instead of this (implicitly invoking `cribl`, which is case-insensitive):

```
dataset=my_dataset field1=foo field2=bar
```

Copy

Do this:

```
dataset=my_dataset | where field1=="foo" and field2=="bar"
```

Copy

With the `where` operator, you must place quotes around string literals that you use in comparisons, as shown just above. With the `cribl` operator, the quotes are optional.

Optimize Parquet with `project`

When searching Parquet files, use `project` in the second query clause, to narrow the subsequent expressions to only your fields of interest.

Instead of this:

```
dataset="a-parquet-datasource" | summarize sum(bytes) by customer, account
```

Copy

Do this:

```
dataset="a-parquet-datasource" | project bytes, customer, account | summarize sum(byt
```

Copy

11.2. Optimize Paths

Partition paths for efficient searchability.

Best Practices for Optimizing Paths in Object Stores

Use these guidelines when you define bucket paths and partitioning for Cribl Search Datasets on Amazon S3, Azure Blob Storage, and Google Cloud Storage to ensure efficient search performance and cost management.

Prioritize Time

Make time the left-most partition. Keep time tokens at the start of the bucket path. For example:

```
my-bucket/${_time:%Y}/${_time:%m}/${_time:%d}/${_time:%H}/....
```

Copy

By putting time first, you ensure the static search prefix is maximized, which lets Cribl Search quickly skip irrelevant data, resulting in faster search performance.

Set Time Granularity

Aim for a balance where each time partition directory contains a manageable number of objects (typically in the hundreds or low thousands). For high-volume Datasets, partition down to `hourly` or `per-minute` level to allow Cribl Search to skip entire folders for irrelevant hours.

Place Non-Time Attributes After Time

If you need to partition by attributes like `region`, `environment`, `account`, or `sourcetype`, add those segments under the time hierarchy. For example:

```
my-bucket/${_time:%Y}/${_time:%m}/${_time:%d}/${region}/${sourcetype}/....
```

Copy

Use search filters (such as, `where region == "us-east-1"`) instead of placing these attributes before time. This structure also simplifies applying different S3 retention policies for various data types.

Limit Wildcards

Use wildcards only when necessary (for example, to skip `key=value` segments). Place them only on the right side of the path and make sure they are applied to segments that do not impact search filtering. For example:

```
my-bucket/${_time:%Y}/${_time:%m}/${*}/${someVarOfInterest}
```

Copy

Static Values: Use Separate Datasets

If a path segment has a small, known list of values (for example, limited `dataImportance` or `environment` values), define multiple datasets or multiple bucket paths with static values rather than using a wildcard across that segment.

Use Sourcetype/Datatype as a Key Partition

When you control ingestion (for example, using Cribl Stream/Edge), consistently encode `sourcetype` or similar `datatype` signals in the path so related events land together and parsing is predictable.

Prefer Cribl Lake

Land data in Cribl Lake and search Lake Datasets instead of manually managing complex partitioning schemes in raw object stores. Cribl Lake automatically applies an optimized Dataset partitioning scheme that aids in `newest-first` discovery while maintaining intuitive time organization.

Common Pitfalls When Setting Up Paths

Avoid these common path design pitfalls when configuring your object store datasets.

Avoid Early Wildcards

Any wildcard near the left of the path forces Cribl Search to list and examine every key under that prefix before it can apply time filtering, dramatically increasing search time and cost.

Avoid patterns like:

```
my-bucket/${*}/${_time:%Y}/${_time:%m}/
```

or

```
my-bucket/data/${category:-*}/${_time:%Y}/.....
```

Avoid Large Directories

Avoid single directories containing tens or hundreds of thousands of objects. For high-volume data, partition down to at least the hourly level.

Avoid Over-Partitioning

Per-second or overly fine per-minute directories can cause excessive list operations and metadata overhead. If the majority of per-minute directories are empty or contain very few objects, coarsen your time partitioning (such as, from per-minute to hourly).

Avoid Placing Routing Fields Before Time

Placing routing fields (like `region` or `account`) before time prevents Search from leveraging time as the longest static prefix. This forces the object store to scan multiple, separate prefixes (one for every `region/account` queried) instead of using a single, efficient time-based lookup.

Avoid patterns like:

```
my-bucket/${region}/${account}/${_time:%Y}/${_time:%m}/...
```

Don’t Hide Key Attributes

If segments such as `dataImportance`, `environment`, or `sourcetype` are key to your search criteria, do not place them in segments you intend to wildcard. Placing them behind a wildcard (such as, `my-bucket/${*}/${_time:%Y}/...`) negates their value for path pruning and increases search time and cost.

Newest-First Ordering

The order in which Cribl Search traverses objects in public storage depends directly on the alphanumeric sorting (lexicographic order) of the object keys returned by the object store provider.

Default Behavior (Oldest-First)

- When you use a standard time hierarchy in your path (such as, `YYYY/MM/DD/...`), the object store API lists keys in ascending, oldest-first order.
- Although Cribl Search reads events within each file in reverse-chronological order, the overall traversal of objects is constrained by this oldest-first listing order.
- While this approach is efficient for smaller directory listings (hundreds of objects), for larger listings (thousands or more), Cribl Search must still respect this order to maintain predictable and efficient behavior.

Ordering in Cribl Lake

- Cribl Lake Datasets automatically apply an optimized “magic prefix” to the bucket path.

- This prefix encodes time in a way that forces the lexicographic listing order to correspond to reverse-chronological (newest-first) order.
- This optimization allows Cribl Search to discover and scan the newest objects first, significantly improving the speed of typical time-range queries.

Approximating Newest-First in Raw Object Stores

While Cribl Lake automatically handles optimal time partitioning for "newest-first" retrieval, you can achieve similar results when writing data directly to S3, Azure, or GCS using Cribl Stream or Cribl Edge.

Use `C.Time.s3TimePartition()`

Use the `C.Time.s3TimePartition()` function in Cribl Stream to generate your time prefix. This function encodes time in a special format that causes the resulting object keys to be ordered reverse-chronologically.

Incorporate this function into the bucket path expression within your Cribl Stream or Cribl Edge Destination:

```
my-bucket/${C.Time.s3TimePartition(_time, 'h')}/${sourcetype}/${host}/
```

Copy

The function takes a time field (`_time`) and a granularity specifier:

- `C.Time.s3TimePartition(_time, 'h')` yields an hourly prefix.
- `C.Time.s3TimePartition(_time, 'd')` yields a daily prefix.



This technique applies only to data written through Cribl Stream or Cribl Edge. Native producer formats (like CloudTrail or Splunk SmartStore) retain their own partitioning schemes. You must still configure Search Datasets with paths that align with your chosen prefix strategy.

Example: Manage Longest Static Prefix in S3

The Amazon S3 API uses your bucket path's longest static prefix for fetching data. So when using two partitions, they must be supplied in every search in order for your time fields to be considered in the prefilter fetch stage.

For example: If you specify `field1=foo` and `field2=bar`, at noon on November 1, 2024, the longest prefix for fetching data would be:

```
<mybucket>/inputID/foo/bar/2024/11/01/12/00/
```

Copy

This is exactly what you want, and very efficient for the files only in that S3 partition. But more efficiently, you'd want:

```
<mybucket>/2024/11/01/12/00/inputID/foo/bar
<mybucket>/2025/11/01/12/00/inputID/foo/bar
```

Copy

And ideally, you'd want them reverse-chronological, and lexicographically associated:

```
<mybucket>/baca-2025/ac-11/aa-01/ad-12/00/inputID/foo/bar
<mybucket>/bada-2024/ac-11/aa-01/ad-12/00/inputID/foo/bar
```

Copy

On the other hand, if you didn't specify `field2`, but used the same criteria, the longest prefix would then be:

```
<mybucket>/inputID/foo/
```

Copy

And here, Cribl Search would have to pull every file within that partition boundary across the S3 API.

Another approach is to reverse the order of your criteria, like this:

```
<mybucket>/inputId/year/month/day/hour/minute/FIELD_1/FIELD_2/
```

Copy

This eliminates the churn caused by omitting either of those criteria.

Note that you'd still get the correct data in your result set if you didn't specify `field2`, because Cribl Search will still filter each event. However, the pool of objects searched could potentially be much larger. This would increase your Search wall-clock time and your proportional retrieval cost.



In Cribl Stream, the Amazon Security Lake Destination automatically partitions buckets this way. It creates time partitions on top, and you can explicitly add further partitioning fields, which this Destination adds below the time boundaries.

11.3. Productivity Tips

Efficiently view your data and format search queries.

These tips help you make the most of Cribl Search.

Preview Search Modifications

Use the Operator Preview feature to test adding new operators to a previously run query, Preview works with a subset of your retrieved data, so you can quickly model the changes without incurring the time or cost of rerunning a search until you're ready.

1. Add an operator to your search (for example, `| extend` or `| extract`).
2. Hover over the operator keyword and select the **Preview** button.
3. Update your search in the resulting **Preview** modal, then select its own **Preview** button to preview the results on up to 100 rows of your data.
4. When you have validated your new query, select **Apply**. This sends the modified search back to your query box.

Quickly Format Queries

To make your search expression more readable in the query box, press the `Ctrl + |` (Linux, Windows) or `Command + |` (MacOS) key combination. This wraps the query at each pipe symbol.

Instead of this:

```
dataset="<my-datasource>" dataSource="VPC Flow Logs" | summarize count() by dst_port
```

Copy

See this:

```
dataset="<my-datasource>" dataSource="VPC Flow Logs"
| summarize count() by dst_port
| lookup service_names on dst_port
```

Copy

Simplify Queries with Reusable Macros

Cribl Search Macros enable you to store snippets of strings - and optionally, variables - that you can reuse in multiple queries.

Instead of this:

```
dataset="aws_ftc_audit_accesslogs"
| extend _raw=replace_regex(_raw, @'"', @'"')
| extract type=json
```

Copy

Insert this:

```
${ftc_audit_accesslogs}
```

Copy

Instead of this:

```
dataset="aws_ftc_audit_accesslogs" _raw!="\"_time\",source,host,sourcetype,\"_raw\",\
| extend _raw=replace_regex(_raw, @'"', @'"')
| extract type=json
```

Copy

Insert this:

```
${ftc_audit_accesslogs} ${exclude_header}
```

Copy

Manage Lookups

To list lookup files' names and contents, use this simple query:

```
dataset="cribl_lookups"
```

Copy

Filter Data with `.show`

To see file names in a Dataset:

```
.show objects("cribl_search_sample")
```

Copy | Run in Cribl Search

To see file names that do not end with `.gz`

```
.show objects("cribl_search_sample")
| where name !endswith('.gz')
```

Copy | Run in Cribl Search

Automatically Reuse Search Results

When writing a query, you can allow Cribl Search to automatically reuse the results of analogous searches that were run recently in your organization. This is especially useful for configuring Dashboards, or when you run the same query multiple times, potentially producing the same results.

Cribl Search treats two searches as analogous when they share the same:

- Search plan: both searches can be broken down into the same set of pipelines. For example, `sort by x desc | limit 10` has the same search plan as `top 10 by x`.
- Datasets: both searches touch (and have access to) the same Datasets.
- `set` statements that can affect results.
- Relative time range.
- Sample rate.

When a search reuses previous results, the **Details** tab describes such a search as an **alias job**, and provides the ID of the job that produced the original results. To hide potentially sensitive information, you can't access the logs, metrics, and diagnostics of the alias job or the original job.

To allow for automatic reuse, at the beginning of your query add a `set` statement with the `allow_previous_results` option set to a time interval.

For example, to allow Cribl Search to reuse results from the last 10 minutes, add the following statement:

```
set allow_previous_results="10min"

// here, add your query
```

Copy

11.4. Useful Queries (Analytic Cookbook)

Kusto Query Language (KQL) recipes to cook up productive searches.

This page presents KQL analytic search queries that are useful for various specific purposes. Entries describe how the queries work, and show sample results.

Search DDSS Bucket Time Ranges

You can use this query to return DDSS buckets' time ranges, formatted and sorted:

```
.show objects(<bucket name>)
| extend  path3=split(name,"/",2) | extend dbpath=split(path3,"_") | extend starttime
| extend starttime=format_datetime(starttime_epoch, 'yy-MM-dd hh:mm:ss tt'), endtime=
| project name, size, starttime, endtime
| sort by starttime asc
```


Copy

Z-Score-Based Anomaly Detection

This analytic takes a time series Dataset, applies a mean and standard deviation to it, then computes a high-and-low envelope based on `mean +/ n*stdev`, where N is called the "Z-score." This is what is commonly referred to as "N standard deviations above/below the average."

```
dataset="cribl_edge_metrics" cribl_fleet="default_fleet" host="ip-172-31-91-42.ec2.ir
| timestats span=10m cpu_max=max(node_cpu_percent_active_all), cpu_avg=avg(node_cpu_p
| extend z_score=4, delta=cpu_stdev*z_score // create a variable z-score, and a delta
| extend env_hi=cpu_avg+delta, env_lo=cpu_avg-delta // create an envelope above and b
| extend env_hi=min_of(env_hi,95), env_hi=max_of(env_hi,5) // fudge factor for the hi
| extend env_lo=max_of(env_lo,1)  // fudge factor for the low limit to be at least 1%
| extend anomaly_flag=iif(cpu_max>env_hi , 1,0), anomaly_chart = cpu_max * anomaly_fl
| project-away z_score, delta, cpu_stdev, cpu_avg // remove the intermediate computat
```

Copy



_time	cpu_max	env_hi	env_lo	anomaly_flag	anomaly_chart
2023-01-26 15:50:00	2.8	5	1	0	0
2023-01-26 16:00:00	4.8	5	1	0	0
2023-01-26 16:10:00	3.6	5	1	0	0
2023-01-26 16:20:00	2.5	5	1	0	0
2023-01-26 16:30:00	4.2	5	1	0	0
2023-01-26 16:40:00	2.8	5	1	0	0
2023-01-26 16:50:00	3.3	5	1	0	0
2023-01-26 17:00:00	0	5.018854132762661	1	1	6.2
2023-01-26 17:10:00	2.9	5	1	0	0
2023-01-26 17:20:00	2.9	5	1	0	0

Z-score results

Notes on Z-Score Detection

The various extend operators compute the z-score envelope (`env_hi` and `env_lo`) and then compute an `anomaly_flag` if the actual Dataset (here, `cpu_max`) is greater than the high envelope.

We use `anomaly_chart` to visually display the anomalies (points higher than `env_hi`) in a separate color, highlighting them. (This is a bit of a kludge, since we can't currently repaint individual data points in a series).

AWS Inventory by Datatype, Objects, Events, TotalBytes

This analytic looks in your S3-based Dataset and counts the number of objects (files, usually), the number of events in those files, and the number of bytes in those events. You can run this over a large sample of data - say, several days - to get a feel for how much data is in your S3 bucket.

The Unsampled Version

⚠ This version is expensive, in terms of time and CPU*seconds. Compare it to the sampled version below.

```
dataset="cribl_search_sample"
| extend eventBytes=strlen(_raw)
| summarize NumEvents=count(), NumObjects=dcount(source), totalBytes=sum(eventBytes)
```

Copy

#	datatype	NumEvents	NumObjects	totalBytes
1	vpcflowlogs	1724032	587	191470980
2	syslog	1723998	582	205655801
3	access_common	1724024	582	162145184
	0	5172054	1751	559271965

233.40s	11557.688	539.54MB	5175676	50
Time elapsed	CPU*s	Scanned	Events Returned	Executors

Unsampled results

Note: This search took almost 4 minutes of wall clock time and over 11,000 CPU*Seconds to run, equivalent to more than **three** Cribl credits.

The Sampled Version

The sampled version, run at 1:1000 sampling. (Use this one!) Byte and Event counts are corrected for the sampling error.

```
dataset="cribl_search_sample"
| extend eventBytes=strlen(_raw)
| summarize NumEvents=count(), NumObjects=dcount(source), totalBytes=sum(eventBytes)
| extend NumEvents=NumEvents*1000, totalBytes=totalBytes*1000
```

Copy

9.60s	221.507	556.42MB	8928	50
Time elapsed	CPU*s	Scanned	Events Returned	Executors

#	datatype	NumEvents	NumObjects	totalBytes
1	vpcflowlogs	1721000	547	191191000
2	syslog	1756000	544	209625000
3	access_common	1704000	541	159600000
	0	5181000	1632	560416000

Sampled results

Notes on AWS Optimization

This search took less than 10 seconds of wall clock time to run, and about 220 CPU*seconds, equivalent to only 0.06 Cribl credits.

When run over a large time range (say, 1 day), the sampled version is almost as accurate as the unsampled version (within two or three significant figures). It runs about 25x faster, and costs about 50x less in terms of CPU*seconds.

AWS Cost and Usage Report (CUR) - Parquet Analysis

This analytic is tricky only because the CUR is in Parquet format, and doesn't have `_time` in each event. Instead, there's a field called `identity_time_interval`, which inexplicably has **two** timestamps, with a slash separating them. By using a regex to extract them, we can then use one (here, the `intervalstarttime`) to cast back into `_time`, and then events will behave as desired.

```
dataset="billing"
| extract source=identity_time_interval type=regex regex=@"(?<intervalstarttime>.+)\/
| extend intervalstarttime=todatetime(intervalstarttime), intervalendtime=todatetime(
| extend _time=intervalstarttime
| timestats span=1h totalusage=sum(line_item_usage_amount) by product_group
```

Copy

This particular analytic simply summarizes `line_item_usage_amount` by `product_group`, but once the data has been properly formatted, any further analytics are fairly straightforward.

Internal Search Utilization

You can use this search to obtain a more granular view of your own Cribl Search usage.

```
dataset="cribl_internal_logs" message="search finished"
| summarize  sum(stats.cpuMetrics.totalCPUSeconds) by stats.user
```

Copy

Note that this example is split by `user`, but you can change it to `split by` anything, or eliminate the `split by` entirely.

Correct for dollars:

```
dataset="cribl_internal_logs" message="search finished"
| extend totalCost=stats.cpuMetrics.totalCPUSeconds/3600
| timestats span=1d  sum(totalCost) by stats.userDisplayName
```

Copy


JournalD Search via Edge

This search will connect to your Edge fleet and search JournalD files on all hosts in the fleet for Command Line arguments.

```
dataset="cribl_edge_journal" journald._CMDLINE=*
| limit 100
| project _time,host,journald._CMDLINE,journald._PID,journald._UID,journald._GIDf
```

Copy

This requires that you've created a Dataset called `cribl_edge_journal`, which is of type **Edge**, and filtered to look at journal files in `/var/log`. Here's an example of how to set up the Dataset:



Edge Dataset configuration

You can query specific Fleets by tailoring the **Fleets to query** field.

Splunk VPC Flow Logs Search via S3


This earches a set of Splunk rawdata (`journal.gz`) files in a bucket in S3, then extracts the results using an existing parser.

```
dataset="s3_splunk_rawdata" sourcetype=*vpc*
| limit 1000
| extract parser='AWS VPC Flow Logs'
```

Copy

This requires a Dataset pointing to a set of Splunk files. It will descend into subfolders - need not be flat.

All Splunk compression formats are supported, including `.zip`, `.gz`, and `.lzw`.



Splunk Dataset configuration

Search a Data Lake Populated from Cribl Stream

Any specific search will work on this Dataset.


```
dataset="data_lake" | limit 1000
```

Copy

Partitioning scheme needs to set to:

```
${}-${_time:%Y}/${}-${_time:%m}/${}-${_time:%d}/${}-${_time:%H}
```

Copy



Lake Dataset configuration

Send Cribl Search Results to Cribl Stream

Enables you to take arbitrary Cribl Search results and send them to Cribl Stream with the `send` operator.

```
dataset="s3_splunk_rawdata" sourcetype=*vpc*
| extract parser='AWS VPC Flow Logs'
| where srcaddr in~ ("34.215.24.225", "172.16.0.178") and dstaddr in~ ("172.16.0.178"
| send tee=false group=default
```

Copy

This is just an example of how to drill down into a Dataset (here, using the Splunk BOTS Dataset), and then send the results to Stream.

Internal-to-External Network Conversations

This analytic works with BOTS v3 Data:

```
dataset="bots_v3" sourcetype in ("stream:tcp", "stream:udp")
| limit 1000
| extract type=json
| where isnotnull(src_ip) and isnotnull(dest_ip)
| lookup matchMode='cidr' cidr_1918_blocks on src_ip=cidr_block
| extend src_network_type=network_type
| lookup matchMode='cidr' cidr_1918_blocks on dest_ip=cidr_block
| extend dest_network_type=network_type
| where src_network_type=="private" and dest_network_type=="public"
| summarize values(dest_port), session_count=count() by src_ip, dest_ip
```

Copy

This analytic works with VPC Flow Logs:

```
dataset="cribl_search_sample" dataSource=*vpc* | limit 1000
| where isnotnull(srcaddr) and isnotnull(dstaddr)
| lookup matchMode='cidr' cidr_1918_blocks on srcaddr=cidr_block
| extend src_network_type=network_type
| lookup matchMode='cidr' cidr_1918_blocks on dstaddr=cidr_block
| extend dest_network_type=network_type
| where src_network_type=="private" and dest_network_type=="public"
| summarize values(dstport), session_count=count() by srcaddr, dstaddr
```

Copy

Requires creating this lookup table:

```
cidr_block,network_type
10.0.0.0/8,private
127.0.0.0/8,loopback
172.16.0.0/12,private
192.168.0.0/16,private
0.0.0.0/0,public
```

Copy

Dataset Usage Stats

Analyze Cribl Search logs to understand the Datasets with the highest number of searches, number of users who have searched, when the last search was, and what the average search time is. Admins can use this analytic to help discover which Datasets would offer the highest return if optimized.

```
dataset="cribl_internal_logs" source=="file:///opt/cribl/log/searches.log" stats.stat
 | limit 1000
 | extract source=stats.query @'dataset=\"(?<datasetUsed>\S+)\"'
 | where datasetUsed
 | summarize searchCount = dcount(stats.id), lastSearch = max(_time), users = dcount(
 | extend lastSearch = strftime(lastSearch, '%Y-%m-%dT%H:%M:%S.%L%Z')
 | sort by searchCount desc
```

Copy

Events Fields Chart — Ran On: 2024-02-29 12:03:12 — 13 results — Details — Actions

datasetUsed	searchCount	lastSearch	users	averageSearchTimeSec
cribl_internal_logs	126	2024-02-29T19:59:55.535+0000	7	5.3
cribl_search_sample	62	2024-02-29T18:57:19.297+0000	5	13.97
nfilippi_training_dataset	8	2024-02-28T19:17:49.230+0000	1	5.11
cavuto_training_dataset	7	2024-02-28T18:02:07.006+0000	1	3.82
test_sample	5	2024-02-23T17:30:15.704+0000	1	5.34
aws_s3_flowlogs	5	2024-02-29T14:42:13.704+0000	4	8.42
tko_rest_api	4	2024-02-28T18:22:48.591+0000	1	1.67
cribl_edge_logs	3	2024-02-29T14:49:58.877+0000	2	0.56
$vt_results	1	2024-02-23T17:36:37.907+0000	1	0.53
google_gcs_flowlogs	1	2024-02-27T02:23:07.346+0000	1	9.98
*flowlogs	1	2024-02-27T02:25:35.290+0000	1	6.52
azure_blob_flowlogs	1	2024-02-27T19:18:02.589+0000	1	9.1
*_flowlogs	1	2024-02-27T20:22:08.373+0000	1	11.33

Dataset usage analysis

Timerange Distribution

What timerange do users most often use when running ad hoc (standard) searches?

```
dataset="searches" stats.status in ("completed","failed","canceled") stats.type="star
 | extract source=stats.searchTimeRange type=regex @'(?<timeRangeValue>\d*)'
 | extract source=stats.searchTimeRange type=regex @'\d*(?<timeRangeModifier>\D*)'
 | extend timeRangeMultiplier = case (timeRangeModifier == "ms", 0.000000277777778,
```

11.5. Dynamic Search Concurrency

Automatically scale the allowed number of concurrent searches to use available capacity without overloading Cribl Search.

Autoscale the Number of Concurrent Searches Allowed

Cribl Search runs each query against available compute capacity, which limits how many searches can run at the same time. Historically, the maximum number of concurrent searches was a static cap set by the Overall concurrent search limit on the **system** Usage Group. Admins typically set this cap conservatively to protect Cribl Search from worst-case workloads, which could leave compute capacity unused.

With **dynamic search concurrency**, Cribl Search continually measures its own CPU and memory load and adjusts the cap up or down to keep configurable headroom free. Throughput is higher when Cribl Search is idle, back-off is faster when it's under pressure, and you spend less time tuning by hand.

Dynamic search concurrency is on by default. You can turn it on or off at **Settings** > **Search** > **Limits**.



Usage Group concurrent limits still apply when dynamic search concurrency is on. Dynamic concurrency replaces only the **Overall concurrent search limit** on the **system** Usage Group, and that field becomes read-only.



Leave dynamic search concurrency on unless Cribl Support or your Cribl account team asks you to turn it off. The defaults work well for most workloads.

Turn Dynamic Search Concurrency On or Off

You need to be a Search Admin or higher.

1. In Cribl Search, go to **Settings** > **Limits**.
2. Select or clear **Enable dynamic concurrency**.
3. Select **Save**.

If **Enable dynamic concurrency** doesn't appear, dynamic search concurrency isn't available in your deployment. Contact Cribl Support or your Cribl account team if you need help tuning dynamic search concurrency for a specific workload.

See Also

- Limits describes general system limits that apply alongside dynamic search concurrency.
- Usage Groups lets you set per-group concurrent search limits and other usage limits.

12. Troubleshooting Cribl Search

Diagnose and solve Cribl Search issues.

Known Issues

Find out if a bug is already fixed, or discover temporary workarounds. See: Known Issues.

KQL Extensions

Identify where Cribl KQL operators, functions, or types differ from their Kusto counterparts. See: KQL Extensions.

Lakehouse Search Differences

Identify where operators, functions, or types differ when searching a Lakehouse versus other Cribl Lake Datasets. See: Lakehouse Search Differences.

Diagnose Search and Monitor Usage

Diagnose search issues and monitor organization-wide usage. See: Search Diagnostics.

Share Diagnostics

Share a diagnostic bundle with Cribl Support, to help us solve your issue. See: Share Diagnostics.

Common Issues and Resolutions

Diagnose and resolve common errors in working with Cribl Search. See: Common Issues and Resolutions.

12.1. KQL Extensions

Understand Cribl KQL extensions and variations from the Kusto language.

Cribl Search KQL is built on top of the Microsoft Kusto Query Language, with additional extensions and operators.

This page lists known areas where Cribl KQL operators, functions, and types differ from their similarly named Kusto counterparts.

These differences might require changes when you programmatically manage Cribl Search using API requests (or other automation) that was originally written around those Kusto counterparts.

- The `dayofweek` function returns an integer between `0` and `6`, representing the day of the week, beginning on Sunday. This differs from the standard Kusto `dayofweek` function, which returns a timespan.
- The `make_timespan` function converts the specified time period into a number of seconds. This output format differs from the standard Kusto `make_timespan` function, which returns a timespan.
- The `timespan` data type represents a time interval, in seconds. This representation differs from the standard Kusto `timespan` type, which represents a literal timespan.
- The `totimespan` function converts the input expression into a time interval, in seconds. This output format differs from the standard Kusto `totimespan` function, which returns a timespan.
- The `tostring` function, when applied to a `null` input value, returns `null`. This output format differs from the standard Kusto `tostring` function, which returns an empty string for `null` values.
- The `project` and `extend` operators return `null` for a field that an event doesn't contain. Standard Kusto rejects a query that references a column missing from the table, because it knows every column at query time. Cribl Search reads unstructured data, so it can't verify field names before it runs the query.

12.2. Lakehouse Search Differences

Identify Cribl Search behavior that differs when searching Lakehouses versus standard Cribl Lake Datasets.

When you run Cribl Search queries against a Lakehouse-assigned Dataset, some behavior and results differ from a corresponding search executed against a Cribl Lake Dataset without Lakehouse caching. This page identifies operators, functions, data types, and other details to keep in mind when searching Lakehouses.

You can disable using Lakehouse for a specific query by using the `set` statement with the `lakehouse` option set to `off`.

Unlimited Events with `sort`

The `sort` operator's `MaxNoOfOutputEvents` parameter defaults to unlimited with Lakehouse, rather than to `10000` events as in a regular search. However, you can set this limit parameter as desired.

Strict Boolean Comparisons

Boolean comparisons in Lakehouse searches are strongly typed. Assume a query condition like `field1==field2`, in which one field is a boolean, while the other is a boolean-compatible value (such as `"yes"`, `"y"`, `"t"`, `"true"`, or `"1"` for `true`; or `"no"`, `"f"`, `"false"`, or `"0"` for `false`).

In a mixed comparison - for example, where `field1`'s value is `true` and `field2`'s value is `"yes"` - note that `field1==field2` will not match. (When searching the same data without Lakehouse caching, looser typing allows these values to match.)

Statistical Aggregations with Booleans

A statistical aggregation that aggregates mathematically on a boolean value will return a `null` in Lakehouse searches. (Running the same aggregation without Lakehouse caching will return a numeric value - either `1` for `true` or `0` for `false`.)

This `null` return value applies to the following functions when their `Expression` argument takes a boolean value: `avg`, `percentile`, `stdev`, `stdevp`, `sum`, `variance`, and `variancep`. (A boolean value in these functions' `Predicate` argument does not cause a `null` return value.)

The `null` return value also occurs with a boolean value in the following functions' sole `Expression` argument: `avgif`, `stdevif`, `sumif`, and `varianceif`.

Extra `null` Column with `timestats`

Applying the `timestats` aggregation function to a search against a Lakehouse-assigned Dataset might return a `null` column when only empty values are found. Searches without Lakehouse caching do not return this column.

Higher `dedup` and `eventstats` Result Counts

Applying the `dedup` or `eventstats` operator to a search against a Lakehouse-assigned Dataset can return a higher result count, compared to searching the same data without Lakehouse caching. This is because `dedup` and `eventstats` in Lakehouse mode can process unlimited events, compared to the 50,000-event limit applied to `dedup` and `eventstats` in searches without caching.

Different `extract type=regex overwrite` Behavior

When using the `extract` operator with `type=regex` and the `overwrite` option for existing event fields, the behavior is different with and without Lakehouse caching. Without Lakehouse, if `overwrite` is set to `false`, the extraction will convert any existing field values to an array. However, Lakehouse searches will omit any existing field values, regardless of whether `overwrite` is set to `true` or `false`.

For example, if you extract `key src_ip` with value `10.2.3.3`, and the field already exists with value `10.1.2.2`, a non-Lakehouse search with `ow=false` will yield a field value of `["10.1.2.2", "10.2.3.3"]`. But a Lakehouse search will yield a field value of `10.2.3.3`.

To consistently preserve the field's original value, you can assign that value to a different variable earlier in the query.

Numeric Precision Limits for Large Integers

Numeric searches and computations in Lakehouse are limited to the IEEE 754 safe integer range (±(2^53 − 1), or ±9,007,199,254,740,991). Numeric literals outside this range — including large negative integers, decimals with a large integer part, out-of-range exponential notation, and values that overflow to infinity — are automatically treated as strings to prevent precision loss.

To filter on a large numeric value such as a record ID, enclose it in quotes:

```
dataset="my_dataset" | where id=="10001900000009910000"
```

Copy




This automatic conversion applies to Lakehouse searches only. Non-Lakehouse (federated) searches do not convert large numeric literals to strings automatically, and comparisons outside the safe integer range may return imprecise results.

12.3. Diagnose Searches And Track Cribl Search Usage

Diagnose search issues and monitor usage in your Cribl Search organization.

Details Modal

To troubleshoot issues, you can view the search's details, pipeline plan, logs, metrics, and more. At the bottom right of the query box, select **Details**.



Search details

The resulting **Details** modal (shown below) displays the following:


- **id**: Unique identifier of the search. You can use it to, for example, reuse search results. To quickly copy the ID, hover over the **Search Job** panel at the top, and select the **Copy to clipboard** icon.
- **status**: Search status - `new`, `running`, `completed`, `failed`, or `canceled`.
- **user**: User that ran the search.
- **query**: Search query string. If the query contains Macros, you can see what they resolved to, by selecting Expand Macros.
- **earliest**: Beginning of query time range, in a relative time format or milliseconds.
- **latest**: End of query time range, in a relative time format or milliseconds.
- **timeCreated**: Time when the search was created.
- **timeStarted**: Time when the search started running.
- **timeCompleted**: Time when the search was completed.
- **timeElapsed**: Total time the search ran.
- **timeInQueue**: How much time the search spent waiting in the queue.
- **sampleRate**: Ratio to reduce results, see sampling.
- **set options**: Any `set`-statement options affecting the search, like `maxResultsPerSearch` or `allow_previous_results`.

You can also select the following:

- **Search the Results**, to quickly query the result set of the search.
- **Rerun**, to run a new search that uses exactly the same query text and settings.
- **View Results**, to display the cached results of the search.

Diagnostics

The **Diagnostics** drop-down provides options to download a compressed folder with many backend logs, configuration files, and optionally, your search results.



Diagnostics drop-down

Select **Exclude Results** to remove the search results from the downloaded diagnostics folder.

If you're sending the diagnostics folder to someone, like Cribl Support, we recommend selecting this option to remove the results from the folder. This will keep the file size manageable.

For more about sending diagnostics to Cribl Support, see: Share Diagnostics.

Search Plan

The **Search plan** tab shows the backend processes your search ran. Your query was converted to a set of pipelines that work on the data. Pipelines are broken into the following categories:

- **Federated**: Pipelines executed by the remote end.
- **Coordinated**: Pipelines executed by the coordinator process.
- **Combined**: Combined **Federated** and **Coordinated** view.

Typically, the first function you'll see in the **Federated** pipeline is **Drop**. This is a filtering function, which drops data that does **not** match its **Filter** expression.

If your search consists of multiple stages, you can view the pipelines for each stage separately. To see a specific stage, select its ID on the left (for example, **root**).

Export a Search Plan

You can export the plan of a search as a JSON file:

1. Run a search.
2. Once the search starts running, select **Details**, then **Search Plan**.
3. If your search consists of multiple stages, select the ID of the stage whose plan you want to export (for example, **root**).
4. At the bottom left, select **View as JSON** to see the search plan in JSON format.
5. At the top right, select **Export**. The search plan is downloaded as a JSON file.

Logs of Your Search

Cribl Search creates log events of your search. You'll see informational and debugging level entries with details on every process run for your search.

Logs are separated into either **Coordinated** or **Executors** types:

- **Coordinated**: Organize query execution and do post-processing, for example, merging, sorting, aggregation, and persisting the search results.
- **Executors**: Scan data, for example, reading from S3, decompressing, filtering, and projection.

Enable Debug Logging for a Query

By default, Cribl Search logs informational-level events for your search. For a more detailed output for a specific query, add a `set` statement with `logger_level="debug"` at the beginning of the query:

```
set logger_level="debug";

dataset="cribl_search_sample" | limit 100
```

Copy

After the search runs, open **Details** > **Logs** to review the debug-level output. This covers most debugging needs without requiring any system-level configuration changes.


Find Logs

Select inside of the pane with the logs and then press Control+F (Windows) or Command+F (Mac) to open the **Find** bar.

You can search by plain text and have three advanced search options:

- Match Case
- Match Whole Word
- Regular Expression


By default, searches run against all logs. To search against only specific text, highlight the desired text and click the three horizontal lines icon.



Find in certain logs

Metrics of Your Search

Metrics from your search are provided to give you insight into the search's performance and the amount of data it touched.



Search metrics

The top area provides a high-level summary of the stats for the search:

- **Time elapsed**: How much time the search took.
- **CPU seconds**: Sum total of CPU seconds spent on the search.
- **Scanned**: Total volume of data ingested by executors and coordinators, calculated after decompression.
- **Events returned**: Number of events the search returned.
- **Executors**: Number of workers the search was split across.

Coordinators

The **Coordinators** table displays a summary of the work done by the coordinator locally. If no Datasets were processed by the coordinator, **Bytes In**, **Bytes Out**, and **Events Out** stats will be **N/A**.

Executors

The **Executors** table displays metrics of the work done by the federated executors, reported on a per-executor basis.

View Usage Statistics

As a Search Admin, you can query the `cribl_internal_logs` Dataset to monitor how your Workspace is using Cribl Search. Cribl Search writes product metrics to this Dataset every hour.

Runnable Kusto code examples include a **Run in Cribl Search** link in the top-right corner of the code block. Select it to open the query in your Cribl Search environment with the query loaded and ready to execute. You can also use the **Copy** button to copy a query and paste it into your own search.

View Dashboard Statistics

To check Dashboard statistics, search the `cribl_internal_logs` Dataset for the following fields:

Field	Description
`search.dashboards`	Total number of Dashboards in the Workspace.
`search.dashboards.creators`	Number of users who have created at least one Dashboard.

For example, to see the total number of Dashboards in your Workspace:

```
dataset="cribl_internal_logs" name="search.dashboards" earliest=-2h
| summarize arg_max(_time, value)
| project Dashboards = value
```

Copy | Run in Cribl Search

View Dataset and Provider Statistics

To check Dataset and Provider statistics, search the `cribl_internal_logs` Dataset for the following fields:

Field	Description
`search.datasets`	Total number of Datasets configured in the Workspace.
`search.providers`	Total number of Dataset Providers, with a breakdown by Provider type.

For example, to see the total number of Datasets in your Workspace:

```
dataset="cribl_internal_logs" name="search.datasets" earliest=-2h
| summarize arg_max(_time, value)
| project Datasets = value
```

Copy | Run in Cribl Search

View User Statistics

To check User statistics, search the `cribl_internal_logs` Dataset for the following field:

Field	Description
`search.users`	Number of users in the Workspace, with a breakdown by Role.

For example, to see the number of users in your Workspace:

```
dataset="cribl_internal_logs" name="search.users" earliest=-2h
| summarize arg_max(_time, value)
| project Users = value
```

Copy | Run in Cribl Search

View Saved Queries and Scheduled Searches

To check saved query and scheduled search statistics, search the `cribl_internal_logs` Dataset for the following fields:

12.4. Share Diagnostics

Share a diagnostic bundle with Cribl Support, to help us solve your issue.

A diagnostic bundle contains a snapshot of configuration files and logs at the time the bundle was created, and gives troubleshooters insights into how Cribl Search was configured and operating at that time.

Generate a Diag File

1. From the **Logs** page, load the problematic search into the query box.
2. Select **Details** to open this search in a **Details** modal.
3. From the **Diagnostics** drop-down, select either **Include Results** or **Exclude Results**. This will download the corresponding search details and logs as a .tgz file whose name is a generously long hash.



For details about whether to include or exclude results, see Diagnostics.

Submit Diags

You can submit diagnostics directly via the Support Portal after logging in. If access to this portal conflicts with your organization's policies, please work directly with your Support engineer to find a solution.

12.5. Common Issues And Resolutions

Diagnose and resolve common errors in working with Cribl Search.

This page lists errors and issues that you might commonly encounter when working with Cribl Search, and provides recommendations for diagnosing and resolving the problems.

General Troubleshooting Tree

If you are getting unexpected results from a search against an object store or data lake, start by following this general troubleshooting path:

1. Are you retrieving objects? (Check this using the `.show objects` command.)
2. If you've retrieved no objects, check bucket path(s), Search Permissions to access the Dataset and Dataset Provider, and access permissions on the object store.
3. If you are retrieving objects, search for raw events with no time filtering.
4. If you find no events, check the data format and permissions.
5. If you find events, check your original time filtering and time parsing - is time recognized accurately? Also check v1 Datatypes that contain Event Breakers.

Amazon Connectivity Issues

This section covers issues specific to Amazon Datasets.

S3 Returns No Elements

You might find no elements returned in response to your query.

Possible Cause

Check your Search Permission to access the Dataset and Dataset Provider. Also check Datatypes and Event Breakers.

Recommendations

Check contents (ListBuckets in S3) to see, and adjust, the Cribl user's or role's permissions on the bucket.

KMS Authorization Fails on S3

If you are using a custom KMS (key management system), you might find that Cribl Search cannot authorize on S3.

Possible Cause

Cribl Search cannot access your keys.

Recommendations

Include `AssumeRole` permissions in the KMS console and in the trust policy, to allow Cribl Search to access the keys.

KMS Decrypt Errors on S3

Retrieving results from objects in an S3 bucket fail, and internal logs show errors of the form: `User is not authorized to perform kms:Decrypt on resource.`

Possible Cause

Your IAM role is missing permissions required to access S3 objects that are encrypted with a KMS key.

Recommendations

Add this sub-element to the applicable IAM role:

```
"Action": [
    "kms:Decrypt",
    "kms:Describe*",
    "kms:Get*",
    "kms:List*",
    "kms:GenerateDataKey"
],
```

Copy

Existing AssumeRole Fails to Authorize on S3

You might find that your existing `AssumeRole` from Cribl Stream/Edge fails to authorize Cribl Search on S3.

Possible Cause

Cribl Search requires a different `Principal` element.

Recommendations

Add the required `Principal` to your trust policy. (Follow the link to see how to copy this `Principal` out of your Dataset Provider modal.)

Can’t Add Buckets to Amazon Security Lake Dataset

You might find that you cannot add new buckets to your Dataset.

Possible Cause

Insufficient permissions on Amazon Security Lake.

Recommendations

Check whether you have added the `securitylake:ListDataLakes` permission to your `AssumeRole`.

Performance Fixes

This section covers workarounds for slow, inefficient, or failing searches.

Scheduled Search Jobs Canceled Due to Queue Length Limit

You might find that some scheduled search jobs were canceled because the search queue reached its configured limit.

Possible Cause

By default, the search queue can hold five times the maximum number of concurrent searches. When the queue is full, Cribl Search rejects additional jobs.

Recommendations

To check the state of the queue, enter `.show queue stats` in the query box.

Contact Cribl Support or your Cribl account team to adjust the queue limit for your workload.

Feature Workarounds

This section covers substitutes for features that Cribl Search doesn't provide out-of-the-box.

Get the Length of an Array Field

Cribl Search currently has no native function to return the length of an array's field, without stringifying the value.

Recommendations

1. Strip everything from the array except for commas; apply the `strlen()` function; and then add 1 to the result.
2. Try a query of the form: `print <arrayName> = dynamic([1,2,3]) | extend len = <arrayName>.length`

Metrics and Monitors Issues

This section covers issues specific to Metrics and Monitors.

Cribl Search Asks You to Create a Metrics Dataset

You open **Metrics**, and Cribl Search shows **Create a Metrics Dataset** and invites you to add one, even though your Organization already ingests metrics.

Possible Cause

No metrics Dataset has been shared with you. Cribl Search lists only the metrics Datasets you can access, so an empty list looks the same as no Dataset existing at all. Adding a Dataset needs the **Editor** or **Admin** Permission, so the suggested action might also be unavailable to you.

Recommendations

Ask a Member with the **Maintainer** Permission on the metrics Dataset to share it with you, instead of adding a new Dataset. Cribl Search auto-provisions one metrics Dataset per lakehouse engine. See Metrics Permissions.

If you have the **Admin** Permission and still see this state, open the **Engines** tab to confirm that a lakehouse engine exists and its status is **Ready**.

The Metrics Explorer Is Empty with No Message

The Metrics Explorer opens but lists no metrics Datasets and gives no explanation.

Possible Cause

Cribl Search could not load the Dataset or lakehouse engine list. It suppresses its guidance message when that request fails, which leaves an empty Explorer.

Recommendations

Refresh the page. If the Explorer is still empty, check the status of your lakehouse engines, then contact Cribl Support.

A Monitor Is Missing from the Monitors List

A Monitor that a colleague can see doesn't appear in your Monitors list.

Possible Cause

The Monitors list shows only the Monitors whose queries all read metrics Datasets you can access. A Monitor on a Dataset you can't access is hidden rather than shown as locked.

Recommendations

Ask a Member with the **Maintainer** Permission to share every metrics Dataset the Monitor evaluates. A Monitor with more than one query can read more than one Dataset, and you need access to all of them. See Monitor Permissions.

Notification Target Fields Look Blank

You open a Notification target and its connection and credential fields are empty.

Possible Cause

Cribl Search omits those fields for Members who can't create Notification targets. It leaves them out of the response rather than masking their values, so the form renders them as empty even though the target is fully configured.

Recommendations

Check whether you have the **Admin** Permission on Cribl Search before treating the Target as misconfigured. See Credential Fields on Targets.

Email Notifications Issues

The section details the troubleshooting steps you can take if an email Notification fails to reach its intended recipient.

Test the Email Notification Target

To prevent email Notifications from failing in production, you can check the target's configuration as follows:

1. Open the target (in **Settings** > **Search** > **Notification Targets**).
2. Select **Test Target**.
3. Add one or more email addresses to the **Test Target** modal. (Include at least one address where you can check incoming messages.)
4. Select **Send Test Email**.
5. If the test succeeds, check the specified inbox(es) to verify that the test message actually arrived. If not, re-examine the target's configuration.



The preconfigured `system_email` target does not enable displaying this **Test Target** option or its parent modal.

Check Notification Logs

A failed email Notification leaves a log entry. You can search Cribl internal logs for SMTP errors using a query of this form:

```
dataset="cribl_internal_logs" level=error channel="output:*" ioName=smtp
```

Copy | Run in Cribl Search

Within any returned log events, unwrap the `reason` field to find details about the root cause of the outbound email failure.

13. Knowledge Libraries In Cribl Search

Use and customize Knowledge libraries to enrich your data, Macros to reuse query snippets across searches, and Packs to share pre-built Cribl Search configurations.

You can access and manage Cribl Search Knowledge libraries and Macros by selecting **Knowledge** from the sidebar. You'll now see upper tabs where you can configure the enrichment and automation resources listed below.

- Lookups are data tables that the `lookup` and `ip-lookup` operators use to enrich events with relevant geographic, identity, threat, or other details.
- Parsers in Cribl Search are definitions for Datatypes and for the `extract` operator.
- Regexes are definitions for Parsers.
- Grok patterns are definitions for Parsers.
- Macros are saved query snippets that you can reuse across different searches, providing consistency and a single point of maintenance.

Select **Packs** from the sidebar to import, modify, create, and export pre-built Cribl Search resources. Packs can include Dashboards, saved searches, Datatypes, Macros, and lookups - in any combination required to support a given data source or workflow.


13.1. Lookups

Enrich events with lookup tables.

Lookups are tables of data referenced by the `lookup` and `ip-lookup` operators to enrich events. For example, you can use lookups to map user IDs to additional attributes like names or addresses, and return this enriched data in the search results.

You can access the **Lookups** page, which provides a management interface for all lookups, by selecting **Knowledge** > **Lookups**.

This lookups table is searchable, and you can add Tags to each lookup as necessary. There's full support for `.csv` files. Compressed files are supported, but must be in gzip format (`.gz` extension).



Lookups page

For details about who can access and modify this resource, see Search Member Permissions. With appropriate Permissions, you can export, share, and import lookups in Packs.

Add a Lookup

As an alternative to using the **Lookups** page to add a lookup, you can use the `export` operator in a query to create or update a lookup. The `export` operator can write a maximum of 10,000 rows to the table.

1. On the top right, select **Add Lookup File**.
2. Select **Upload a New File** or **Create with Text Editor**.
3. Give your lookup a unique **Filename**. You'll use this to identify the lookup table in a lookup operation.
4. Optionally, enter a **Description**.
5. Optionally, enter any desired **Tags**.

6. If you selected **Create with Text Editor**, enter your lookup table in the text box. Use CSV (comma-separated values) format with the header values on the first row as the field names, and the field values in the subsequent rows.



Lookup field names must use letters, numbers, and underscores only.

7. Select **Save**.

You can't use the `export` operator to create Pack lookups.

Example Lookup Table

```
service_name,port_number,transport
tcpmux,1,tcp
tcpmux,1,udp
compressnet,2,tcp
compressnet,2,udp
compressnet,3,tcp
compressnet,3,udp
rje,5,tcp
rje,5,udp
echo,7,tcp
```

Copy


Modify a Lookup

To re-upload, expand, edit, or delete an existing lookup, select its row on the **Lookups** page.




If the lookup you want to delete belongs to a Pack, see Delete a Pack Resource.

In the resulting modal, you can edit files in **Table** or **Text** mode. However, **Text** mode is disabled for files larger than 1 MB. The maximum lookup size is 10,000 rows.



Editing in Table mode



Editing in Text mode

Editing Regex with Quotation Marks

> When a regex contains quotes, edit it in **Text** mode. Do not edit it in **Table** mode, which can cause the regex to behave in unexpected ways.

You can't use the `export` operator to modify Pack lookups.

Export a Lookup

To export a lookup file, including any modifications that you've made, you have two options:

- From a lookup's configuration modal, select the **Download File** button.
- From the **Lookups** page, Open the Actions ⋯menu on the lookup file's table row, then select **Download**.

List Available Lookups

You can list all your lookup files straight from the query box, using the `$vt_lookups` virtual table:

```
// lists all lookups available to the current user
dataset="$vt_lookups"
```

Copy | Run in Cribl Search

Search the Contents of Your Lookups

You can use the `$vt_lookups` virtual table to search the contents of your lookups.


For example, to get the contents of a lookup named `service_names_port_numbers.csv`:

13.2. Parsers

Define data to extract, using Parsers.

Parsers in Cribl Search are definitions for Datatypes and the `extract` operator.

To open the **Parsers** page, select **Knowledge** > **Parsers**. The Parsers page provides an interface for creating and editing Parsers. The table is searchable, and you can add Tags to each Parser as necessary.



Parsers page

For details about who can access and modify this resource, see Search Member Permissions.

Supported Parser Types

- **CSV**: Comma-separated values.
- **Extended Log File Format**: Extended Log File Format.
- **Common Log Format**: Common Log Format.
- **Key=Value Pairs**: A set of data that represents two associated groups through a key and a value.
- **JSON Object**: JavaScript Object Notation (JSON) is a standard text-based format for representing structured data based on JavaScript object syntax.

- **Delimited values**: A character identifies the beginning or the end of a character string.
- **Regular Expression**: A sequence of characters that specifies a match pattern in text.
- **Grok**: A string of special characters and regular expressions (pattern) that match data.

Creating a Parser

To create a Parser, follow these steps:

1. Go to **Knowledge** > **Parsers** and select **Add Parser**.
2. Enter a unique **ID**.
3. Optionally, enter a **Description**.
4. Optionally, enter any desired **Tags**.
5. Select a Parser **Type** (see the supported types above).
6. Enter the **List of fields** expected to be extracted, in order. Select this field's advanced mode icon (far right) if you'd like to open a modal where you can work with sample data and iterate on results.
7. Based on the **Type** selected, you'll also have additional configurations. See the below sections for details, either Key=Value Pairs, Delimited Values, Regular Expressions, or Grok.
8. Select **Save** when you're finished.

Key=Value Pairs

- **Clean fields**: Whether to clean field names by replacing non-alphanumeric characters `[a-zA-Z0-9]` with an underscore `_`.
- **Allowed key characters**: A list of characters that can appear in a key name, even though they're normally separator or control characters.
- **Allowed value characters**: A list of characters that can appear in a value name, even though they're normally separator or control characters.

Delimited Values

- **Delimiter**: Delimiter character to use to split values.
- **Quote character**: Character used to quote values. Required if values contain the delimiter character.
- **Escape character**: Character used to escape characters within a value.
- **Null value**: String value that should be treated as null or undefined.

Regular Expression

- **Regex**: Regex literal with named capturing groups, for example, `(?<foo>bar)`. Or with `_NAME_` and `_VALUE_` capturing groups, for example, `(?<_NAME_0>[^ =]+)=(?<_VALUE_0>[^,]+)`.

- **Additional regex**: Add another regular expression to match against other data.
- **Max exec**: The maximum number of times to apply the regex to the source field when the global flag is set, or when using named capturing groups.
- **Field name format expression**: JavaScript expression to format field names when `_NAME_n` and `_VALUE_n` capturing groups are used. The original field name is in the global variable `name`. For example, to append `XX` to all field names: `${name}_XX` (backticks are literal). If empty, names will be sanitized using this regex: `/^[_0-9]+|[^a-zA-Z0-9_]+/g`. You can access other field values via `__e.<fieldName>`.
- **Overwrite existing fields**: Overwrite existing event fields with extracted values. If set to **No**, existing fields will be converted to an array.

Grok

- **Pattern**: Grok pattern to extract fields. Syntax supported: `%{PATTERN_NAME:FIELD_NAME}`.
- **Additional Grok patterns**: Add another pattern to match other data.


13.3. Regexes

Use the built-in library of regular expressions, or define your own.

A regular expression (regex) is a sequence of characters that specifies a match pattern in text. Cribl Search uses regexes in definitions for Parsers.

Cribl Search ships with many commonly used regular expressions. The **Regexes** page provides an interface for creating and editing regular expressions. The table is searchable, and you can add Tags to each regex as necessary.

To open the **Regexes** page, select **Knowledge** > **Regexes**.



Regexes page

For details about who can access and modify this resource, see Search Member Permissions.

Add Custom Regex

1. On the top right, select **Add Regex**.
2. In the resulting modal, give your custom regex a unique **ID** and optionally, provide a **Description**.
3. Enter your **Regex pattern** and any **Sample data** the regex matches against.
4. Optionally, you can assign **Tags** for further organization or categorization in Cribl.
5. Select **Save**.

Exporting and Importing Regexes

You can export and import Custom (or Cribl) Regexes as JSON files. This facilitates sharing Regexes among Worker Groups or Cribl Stream and Cribl Edge deployments.

To export a Regex:

1. Select to open an existing Regex, or create a new Regex.
2. In the resulting modal, select **Manage as JSON** to open the JSON editor.
3. You can now modify the Regex directly in JSON, if you choose.
4. Select **Export**.

To import any Regex that has been exported as a valid JSON file:

1. Create a new Regex.
2. In the resulting modal, select **Manage as JSON** to open the JSON editor.
3. Select **Import**, and choose the file you want.
4. Select **OK** to get back to the **New regex** modal.
5. Select **Save**.



Every Regex must have a unique value in its top `id` key. Importing a JSON file with a duplicate `id` value will fail at the final **Save** step, with a message that the Regex already exists. You can remedy this by giving the file a unique `id` value.

Cribl Regexes Versus Custom Regexes

Regexes shipped by Cribl are listed under the **Cribl** tag, while user-built regexes are listed under **Custom**. Over time, Cribl will ship more patterns, so this distinction allows for both sets to grow independently. In the case of an ID/Name conflict, the Custom pattern takes priority.


13.4. Grok Patterns

Use the built-in library of Grok patterns, or define your own.

A Grok pattern is a string of special characters and regular expressions that match data. Cribl Search uses Grok patterns in definitions for Parsers.

Cribl Search ships with many commonly used Grok patterns. The **Grok Patterns** page provides an interface for creating and editing them.

To open the **Grok Patterns** page, select **Knowledge** > **Grok Patterns**.



Grok Patterns page

For details about who can access and modify this resource, see Search Member Permissions.

Add a Grok Pattern

1. On the top right, select **Add Grok Pattern File**.
2. Give your custom Grok pattern a unique **File name**.
3. Enter your Grok pattern in the **Content** pane.
4. Select **Save**.

13.5. Macros

Reuse query text across different searches, by using Macros.

Macros are reusable query snippets that you can reference by name when writing your query, using the `${...}` syntax. They can contain any valid Cribl Search query text, including functions, operators, or literals.

For example, you can create a Macro called `externalVpcReject` that consists of the following text:

```
(action=reject srcip!=10.* srcip!=172.16.*)
```

Copy

...and then use it anywhere in a query, like this:

```
${externalVpcReject}
```

Copy

...which is equivalent to writing:

```
(action=reject srcip!=10.* srcip!=172.16.*)
```

Copy

With Macros, you can construct queries faster and keep them consistent, especially if you frequently rerun the same complex query in various configurations.

You can share Macros with other Members of your Organization. To share Macros more broadly, you can export and import them in Packs.

Macro Parameters

Macro parameters are numbered placeholders (`$1`, `$2`, `$3`, ...) that you fill in with different values each time you inject the Macro into a query. They work similarly to Bash positional parameters.

For example, you can create a Macro called `filterByActionAndAnswer` that consists of the following text:

```
// define three parameters
action=$1 answer=$2 $3
```

Copy

...and then use it anywhere in a query, like this:

```
// pass the same number of arguments, in the same order
${filterByActionAndAnswer, 'reject', 42, ips="172.16.*"}
```

Copy

...which is equivalent to writing:

```
action='reject' answer=42 ips="172.16.*"
```

Copy

You can pass any type of value as an argument (including other Macros with parameters). If an expression contains commas (`,`), wrap it in quotes, for example: `${myMacro, "one, two, three", 42}`.

View Macros Available to You

Certain Macros may already be available to you, depending on your organization's configuration:

1. In Cribl Search, go to **Knowledge** > **Macros**.
2. Here, you can search and filter the available Macros:
    - To see only Macros built into Cribl Search by default, select the **Cribl** filter at the top right.
    - To see only Macros that you created or that were shared with you, select the **Custom** filter.
    - To search for a specific Macro, type its ID in the **Filter Macros** box.
3. To see a Macro's details, select its row.

Use a Macro in a Query

You can insert a Macro anywhere in any query. Type `$` followed by the Macro's ID in curly braces `{}`:

```
${macroId}
```

Copy

If the Macro is part of a Pack, you'll need to include the Pack's ID as well. See: Use a Pack Macro.

For example, to insert Macros named `myMacro1` and `myMacro2`:

```
dataset=myDataset ${myMacro1}
   | limit 1000 ${myMacro2}
```

Copy

When a Macro's definition includes a number of parameters, you need to pass the same number of arguments, in the same order. Pass your arguments after the Macro ID, separated by commas. For example:

```
dataset=myDataset ${myMacro1, argument1, argument2, argument3}
```

Copy

If you reference a Macro inside a string or another literal (like regex), it will behave as plain text. For example:

```
// here, "bar" won't be expanded
| where foo="${bar}"
```

Copy

Cribl Search's autocomplete will suggest available Macros as you type.

Expand Macros Used in a Query

After you run a query that contains Macros, you can expand the Macros to show the text that each Macro resolved to. This way, you can see the query exactly as it was executed, which is helpful for debugging your searches.

1. Run a search.
2. After the search starts running, select **Details** under the query box.
3. In the **Key** column, **query** row, select **Expand Macros**. The query expands to show the text that each Macro resolved to during the search execution.

Create a Macro

To create a new Macro:

1. In Cribl Search, select **Knowledge**, then **Macros**.
2. At the top right, select **Add Macro**. The **New Macro** modal appears.

- In **ID**, enter your Macro's ID. This is how you and others will reference the Macro in your queries. The ID must be unique among all Macros within your organization (even those unavailable to you). For details, see Naming Convention for Macros.
- In **Description**, enter a brief description of the Macro's purpose.
- In **Tags**, enter any tags that can help you and others find your Macro.
- In **Definition**, enter the query text that the Macro will expand to when referenced in a query.

3. In the bottom right, select **Save**.



You can also clone an existing Macro by selecting its row, and then **Clone Macro**.

Naming Convention for Macros

As Macros can be shared with multiple Members of your organization, and they all share a single namespace, every Macro ID must be unique across the entire Cribl.Cloud Search tenant.

To manage your namespace in a way that makes the most sense for your organization, we suggest following a consistent naming convention.

For example, you can use the following convention: `<teamName>_<DatasetName>_<functionName>`. This might create IDs like:

- `ops_flowlogs_uniqueAddresses`
- `IRT_emailAnomalies_lookupName`

Edit a Macro

To edit a Macro:

1. Make sure you have the **Maintainer** Permission for the Macro.
2. In Cribl Search, select **Knowledge**, then **Macros**.
3. Select the row of the Macro that you want to edit. The Macro's details appear.
4. Edit the Macro's **Description**, **Tags**, and **Definition**. For details, see the Create a Macro section.
5. In the bottom right, select **Save**.

Delete a Macro

To delete a Macro:

1. Make sure you have the **Maintainer** Permission for the Macro.
2. In Cribl Search, select **Knowledge**, then **Macros**.

3. Select the row of the Macro that you want to delete. The Macro's details appear.
4. In the bottom left, select **Delete Macro**.
5. Type **DELETE**, and then select **Delete Selected Macro**.



If the Macro you want to delete belongs to a Pack, see Delete a Pack Resource.

Sharing Macros with Other Members

You can share your Macros with other Members of your organization, to build a library of useful functions and transformations.

Macro Permissions

You can share Macros with individual users or entire Teams, granting one of the two access levels, **Read Only** or **Maintainer**:

Permission	Read Only	Maintainer
View the Macro		
Use the Macro in a query		
Edit the Macro		
Delete the Macro		

When you create a Macro, you automatically become its **Maintainer**.

See Who Can Access Your Macros

By default, Macros that you create are available only to you and the Search Admin.

To see who exactly has access to a Macro:

1. In Cribl Search, select **Knowledge**, then **Macros**.
2. In the row of the Macro that you want to share, select **Share**. The **Macro Members and Teams** modal appears.
3. Here, you can see who has Permission for the Macro.

Share a Macro

To share a Macro with another Member of your organization:

1. In Cribl Search, select **Knowledge**, then **Macros**.
2. In the row of the Macro that you want to share, select **Share**. The **Macro Members and Teams** modal appears.
3. Search for the Member or Team that you want to share the Macro with.
4. Select the Permission level that you want to grant to the Member or Team.
5. Select **Add Access**.

13.6. Cribl Search Packs

Import, export, and share pre-built Cribl Search resources.

Why Use Packs

A Pack is a collection of preconfigured Cribl Search assets, such as ready-to-use Dashboards, saved searches, or lookup files. Packs can help you and your team get started faster, quickly see what Cribl Search is capable of, and easily move complex configurations across different environments.

What's in a Pack

A Pack can contain any of the following resources:

- Dashboards
- Saved searches
- Datatypes, including v2 Datatypes
- Macros
- Lookups

A Pack can't reference other Packs, but it can reference other resources within the same Pack. It can also reference global, non-Pack resources. For details, see Pack Dependencies and Packs Limitations.

Who Can Use Packs

Packs are available to Cribl Search **Admins** and **Editors**. For reference, see Search Member Permissions.

Admins and Editors can:


- View Packs installed in the Organization.
- Use a Pack's resources, if the Pack is set to allow global access.
- Get new Packs from the Cribl Packs Dispensary, or import them from a file, URL, or Git repo.
- Modify existing Packs, including adding more resources, or modifying metadata.
- Create new Packs from scratch, using the Cribl Search UI.
- Share Packs, allowing access to Pack resources, or exporting a Pack to a file.

View Packs

To see Packs installed in your Organization, go to the **Packs** page in Cribl Search: On the top bar, select **Products** > **Search** > **Packs**.


The **ID** column shows each Pack's ID, by which you can reference the Pack's resources.

You can hover over an ID and select the copy icon to copy it to the system clipboard.



Packs page

Select a Pack to view the resources it contains. You can then switch among the upper tabs to view the Pack's **Dashboards**, **Saved Searches**, **Datatypes**, **Macros**, and **Lookups**.



Dashboards within a Pack

Use Packs

If a Pack is set to allow global access, you can use its resources similarly to any other resources in Cribl Search. For example, you can run saved searches included in the Pack, reference a Pack Macro in a query, or use a Pack lookup.

Use a Pack Macro

To use a Pack Macro from outside its Pack, make sure the Pack is set to allow global access. Then, reference the Pack's ID (`packId`) and the Macro's ID (`macroId`), in the following format:

```
${pack(packId).macroId}
```

Copy

For example, to use `myMacro` residing in a Pack called `cribl-sample-data`:

```
${pack(cribl-sample-data).myMacro}
```

Copy

Use a Pack Lookup

To use a Pack lookup from outside its Pack, make sure the Pack is set to allow global access. Then, reference the Pack's ID (`packId`) and the lookup's ID (`lookupId`), in the following format:

```
lookup pack(packId).lookupId
```

Copy

For example, to look for a common field in the event and in a `lookupTable` residing in `myPack`:

```
dataset=myDataset
 | lookup pack(myPack).lookupTable on commonField
```

Copy

You can't create or update Pack lookups with the `export` operator. For example, `| export to lookup pack(packId).lookupId` will **not** work.

Use a Pack Saved Search

To use a Pack saved search from outside its Pack, make sure the Pack is set to allow global access. Then, reference the Pack's ID (`packId`) and the saved search's ID (`savedSearchId`), in the following format:

```
packId.savedSearchId
```

Copy

Use a Pack Datatype

To use a Pack Datatype from outside its Pack, make sure the Pack is set to allow global access. Then, reference the Pack's ID (`packId`) and the Datatype's ID (`datatypeId`), in the following format:

```
packId.datatypeId
```

Copy



Pack v2 Datatypes used in federated Dataset path filters are resolved at search time regardless of whether the Pack allows global access. The Pack's global access setting only controls whether the Datatype appears in the global Datatypes listing.

Get Packs

As a Cribl Search Admin or Editor, you can install Packs in your Organization by importing them from the following sources:

- Packs Dispensary
- File
- URL
- Git repo

You can also create a new Pack from scratch, or modify an existing Pack.

Add a Pack from Dispensary

The Cribl Packs Dispensary is a Cribl-hosted resource for you to find and share Packs. Cribl, our partners, and community users develop Packs and submit them to the Dispensary for easy sharing. Cribl tests submissions before publication, to ensure each Pack's quality, security guardrails, and stability.

You can install Dispensary Packs as follows:

1. Go to the **Packs** page in Cribl Search: On the top bar, select **Products** > **Search** > **Packs**.
2. Select **Add Pack** > **Add from Dispensary**. The Packs Dispensary will open in a drawer.
3. Using the drawer controls, browse or search for the Pack(s) you want. (You can filter for only Packs **Built by Cribl**.)
4. Select any Pack tile to display its details page with its README. This will typically outline the Pack's purpose, compatibility, requirements, and installation.
5. To proceed, select **Add Pack** on this page.
6. That's it! You'll see a banner confirming that the Pack is now installed.

Import a Pack from File

To import a new Pack, or an updated version of an existing Pack, from your local filesystem:

1. Go to the **Packs** page in Cribl Search: On the top bar, select **Products** > **Search** > **Packs**.
2. Select **Add Pack** > **Import from File**.
3. Select the file to import.
4. Optionally, give the Pack an explicit, unique **New Pack ID**. (For details about this option, see Upgrade a Pack.)
5. Select **Import** to confirm the import.



When you import Packs that were exported in `merge` mode, make sure to re-enter any required secrets to restore full functionality. This is necessary because Cribl Search deletes all encrypted fields during the export process, to ensure security and prevent the accidental sharing of sensitive information.

Import a Pack from URL

To import a Pack from a known, public or internal, URL:

1. Go to the **Packs** page in Cribl Search: On the top bar, select **Products** > **Search** > **Packs**.
2. Select **Add Pack** > **Import from URL**.
3. Enter a valid URL for the Pack's source. (This field's input is validated for URL format, but not for accuracy.)
4. Optionally, give the Pack an explicit, unique **New Pack ID**. (See Upgrade a Pack.)
5. If the Pack matches an installed Pack's **Pack ID**, confirm that you want to **Overwrite** the existing Pack.
6. Select **Import** to confirm the import.

Import a Pack from Git

You can import a Pack from a known public or private Git repo.

1. Go to the **Packs** page in Cribl Search: On the top bar, select **Products** > **Search** > **Packs**.
2. Select **Add Pack** > **Import from Git**.
3. Enter the source repo's valid URL.

   This field's input is validated for URL format, but not for completeness or accuracy. When targeting a private repo, use the format: `https://<username>:<token/password>@<repo-address>`. Public repos need only `https://<repo-address>`.
4. Optionally, give the Pack an explicit, unique **New Pack ID**. (See Upgrade a Pack.)
5. If the Pack matches an installed Pack's **Pack ID**, confirm that you want to **Overwrite** the existing Pack.
6. Optionally, enter a **Branch or tag** to filter the import source using the repo's metadata. You can specify a branch (such as `main`) or a tag (such as a release number like `0.5.1`).
7. Select **Import** to confirm the import.

Pack Dispensary GitHub Repo

A particularly useful public repo is the Cribl Pack Dispensary on GitHub. This repo was established prior to the Cribl-hosted Cribl Packs Dispensary site, and it is a place to collaborate on developing Packs prior to submitting them to the newer site.

You can install Packs directly from this repo using the Import from Git option. However, if you prefer, you can click through to any Dispensary repo's release page, download the corresponding `.crbl` file, and then upload the file into Cribl Search.

Modify Packs

As a Cribl Search Admin or Editor, you can modify existing Packs:

- Add a resource to a Pack
- Modify a Pack's metadata
- Set a Pack's logo
- Upgrade a Pack
- Overwrite a Pack

Add a Resource to a Pack

You can fill a Pack with Dashboards, saved searches, Datatypes, Macros, and lookups.



When adding a Datatype to a Pack, the **Add Datatype** modal offers both v1 and v2 options, the same as in the global context. The Datatype is saved to the Pack and assigned a fully qualified ID in the format

```
packId.datatypeId.
```

For example, to add a Dashboard to a Pack:

1. Go to the **Packs** page in Cribl Search: On the top bar, select **Products** > **Search** > **Packs**.
2. Select the Pack you're interested in. Use the search box to filter the list.
3. From the **Dashboards** tab, select **Add Dashboard** to access the two options listed below:
    - **Add Existing**: Opens an **Add Existing Dashboards** modal, where you can select one or more Dashboards that are available to you, and add them to this Pack. (The list displayed in this modal will, by design, omit Dashboards already included in the Pack.)
    - **Add New**: Opens a **New Dashboard** modal, where you can configure a new Dashboard using the controls covered in Create a Dashboard.

For details on how to reference different types of Pack resources, see Pack Dependencies.

Delete a Pack Resource

To remove a Pack resource (Dashboard, saved search, Datatype, Macro, or lookup), you need to delete it from within its Pack.


For example, to delete a Pack Dashboard:

1. Go to the **Packs** page in Cribl Search: On the top bar, select **Products** > **Search** > **Packs**.
2. Select the Pack you're interested in. Use the search box to filter the list.
3. From the **Dashboards** tab, select the checkbox of the Dashboard to delete.
4. Select **Delete selected Dashboards**.

Modify a Pack's Metadata

You can modify a Pack's metadata, such as display name, version, description, and others.

1. Go to the **Packs** page in Cribl Search: On the top bar, select **Products** > **Search** > **Packs**.
2. Select the Pack you're interested in. Use the search box to filter the list.
3. Select the **Pack Settings** upper tab to expose two options on the left:
    - **README**: Here, you can edit extended information about the Pack, including its purpose, requirements (prerequisites), and usage instructions.
    - **Settings**: Here, you can update the Pack's **Display name**, **Version** number, short **Description**, **Author**, and arbitrary **Tags**. You can also control access to the Pack.
4. Save your changes.



Pack Settings

Set a Pack's Logo

We recommend adding a logo to each custom Pack, to visually distinguish the Pack UI from the surrounding Cribl Search UI (as well as from other Packs).

You can upload a `.png` or `.jpg`/`.jpeg` file, up to a maximum size of 2 MB and 350x350 px. Cribl recommends a transparent image, sized approximately 280x50 px.

To set a logo for an existing Pack:

1. Go to the **Packs** page in Cribl Search: On the top bar, select **Products** > **Search** > **Packs**.
2. Select the Pack you're interested in. Use the search box to filter the list.
3. Go to **Pack Settings** > **Display**.
4. Select **Choose File** to upload a new logo, and confirm.

Upgrade a Pack

To upgrade an existing Pack to a newer version:

1. Go to the **Packs** page in Cribl Search: On the top bar, select **Products** > **Search** > **Packs**.
2. Open the Actions ⋯ menu on a Pack's row, and then select **Upgrade**.

When upgrading a Pack, we recommend that you:

- Initially, import the updated Pack with a new ID, and with a new **Display name** that includes the version number. (For example, `Cribl Search Activity 0.5`.) This enables you to review and adjust new behavior against currently-deployed configurations.
- Do a side-by-side comparison of the previous and new versions of the Pack. Remember to review the new Pack's README.
- If the Pack includes any user-modified versions of default Cribl Search Knowledge resources (for example, lookups): Be sure to copy the modified files locally for safekeeping, before upgrading the Pack. After you install the upgrade, copy those files back to the upgraded Pack, overwriting the default versions in the Pack.
- Test, test, and test!
- If you're confident in the new version, you have the option to now overwrite the existing Pack, using the same ID.
- Commit and Deploy.

Overwrite a Pack

Each Pack that you install within a given Organization must have a unique ID. The ID is based on the internal configuration of the Pack - not on its Display name, nor on its parent file name. You cannot share an ID between two (or more) installed Packs.

If you import a Pack whose internal ID matches an installed Pack - whether an update, or just a duplicate - you'll be prompted to assign a unique **New Pack ID** to import it as a separate Pack.

Alternatively, you have the option to **Overwrite** the installed Pack, reusing the same ID.



With the **Overwrite** option, the imported Pack completely replaces your existing Pack. We recommend creating a local backup copy of the existing Pack first.

If you've modified an installed Pack, Cribl Search will block the overwrite of the Pack, to prevent deletion of your locally created resources.

Create Packs

As a Cribl Search Admin or Editor, you can create a new Pack from scratch, using the Cribl Search UI.

You can also create new Packs by importing, modifying, upgrading, or overwriting existing Packs.

When adding resources to a Pack, learn about how Pack dependencies work.

Create a Pack from UI

You can create a new Pack from scratch, using the Cribl Search UI.

1. Go to the **Packs** page in Cribl Search: On the top bar, select **Products** > **Search** > **Packs**.
2. Select **Add Pack** > **Create Pack**.
3. Enter the following details:
    - **Display name** is an arbitrary, human-readable name to identify this Pack.
    - **Pack ID** is required, and must be unique within your Cribl Search Organization.
    - **Version** is required, and identifies this Pack's own versioning.
    - **Description** and **Author** are optional identifiers.
    - **Tags** are optional, arbitrary labels that you can use to filter/search and organize Packs.
    - If you want to allow global access to this Pack, check **Allow global access**. This will make all of the Pack's resources visible and usable from anywhere in the current Workspace.
4. Select **Save**.
5. On the **Packs** page, select the new Pack's row to open the Pack.
6. Configure the resources you want to pack up, using the standard Cribl Search controls for Dashboards, saved searches, Datatypes, Macros, or lookups. As you save changes in the UI, they're saved to the Pack.

   If you want to reference resources that reside outside the Pack, learn about how Pack dependencies work.
7. Set the pack's logo, to visually distinguish the Pack UI from the surrounding Cribl Search UI (as well as from other Packs).

Share Packs

As a Cribl Search Admin or Editor, you can share Packs in the following ways:

- Allow access to all of a Pack's resources, making them usable from anywhere in the current Workspace.
- Move a Pack resource out of its Pack, to make the resource available globally.
- Move a resource into a Pack, to make the resource available only within that Pack.
- Move a Pack resource to another Pack.
- Clone a Pack resource, to play around with it without affecting the original.
- Export an entire Pack to a file, so that you can share it with other Organizations.



To move a sample resource shipped by Cribl, you need to clone it first.

Allow Global Access to a Pack

To make all of a Pack's resources visible and usable from anywhere in the current Workspace:

1. Go to the **Packs** page in Cribl Search: On the top bar, select **Products** > **Search** > **Packs**.
2. Select the Pack you're interested in. Use the search box to filter the list.
3. Go to **Pack Settings** > **Pack Info**.
4. Check **Allow global access**, and confirm with **Save**.

Move a Resource Out of a Pack

To make a resource (Dashboard, saved search, Datatype, Macro, or lookup) available outside its original Pack, you can move that resource to your Organization's global level.

For example, to move a Dashboard out of its Pack:

1. Go to the **Packs** page in Cribl Search: On the top bar, select **Products** > **Search** > **Packs**.
2. Select the Pack whose resource you want to move.
3. On the **Dashboards** tab, open a Dashboard's Actions ⋯menu.
4. Under **Move**, select **All Dashboards**.

Move a Resource Into a Pack

You can move a global resource (Dashboard, saved search, Datatype, Macro, or lookup) into a Pack. This makes the resource available only within that Pack, and removes it from the global context.

For example, to move a Dashboard into a Pack:

1. Go to the **Dasbboards** page in Cribl Search: On the top bar, select **Products** > **Search** > **Dashboards**.
2. Open the Actions ⋯menu of the custom Dashboard you want to move.
3. Under **Move**, hover over **Packs**, and select a Pack.



Moving a Dashboard into a Pack changes the Dashboard's **Created by** and **Last Modified by** indicators to match your identity. The move also discards any sharing Permissions that were set on the original Dashboard. Share the Dashboard from its new location to add new Permissions.

Move a Resource to Another Pack

You can move a resource (Dashboard, saved search, Datatype, Macro, or lookup) from one Pack to another.

For example, to move a Dashboard to another Pack:

1. Go to the **Packs** page in Cribl Search: On the top bar, select **Products** > **Search** > **Packs**.
2. Select the Pack whose resource you want to move.
3. On the **Dashboards** tab, open a Dashboard's Actions ⋯menu.

4. Under **Move**, hover over **Packs**, and select the Pack into which you want to move the resource.

Clone a Pack Resource

To play around with a Pack resource (Dashboard, saved search, Datatype, Macro, or lookup) without affecting the original, you can create a clone.

Cloned resources are saved to your current UI location. For example, if you clone a Dashboard while viewing its Pack, the clone is saved as part of the Pack. If you clone the same Dashboard while viewing the global **Dashboards** page, the clone is saved as a global resource.

For example, to clone a Dashboard into its Pack:

1. Go to the **Packs** page in Cribl Search: On the top bar, select **Products** > **Search** > **Packs**.
2. Select the Pack whose resource you want to clone.
3. On the **Dashboards** tab, open a Dashboard's Actions ⋯menu.
4. Select **Clone**. The copy is saved to the Pack, and its visibility outside the Pack depends on the global access setting.

To clone a Pack Dashboard into the global **Dashboards** page:

1. Go to the **Dasbboards** page in Cribl Search: On the top bar, select **Products** > **Search** > **Dashboards**.
2. Find the Pack Dashboard you want to clone. Look for the Pack's name in the **Pack** column.
3. Open the Dashboard's Actions ⋯menu.
4. Select **Clone**. The copy is saved to the global **Dashboards** page.

Export a Pack

To download an existing Pack as a single file, for sharing with other Organizations:

1. Go to the **Packs** page in Cribl Search: On the top bar, select **Products** > **Search** > **Packs**.
2. In the row of the Pack you're interested in, select the Actions ⋯menu, then **Export**.
3. In the resulting **Export Pack** modal, the filename defaults to the Pack's current ID, with the version number appended. You can modify this, as desired, before confirming the export.

If the Pack references any resources residing outside the Pack (for example, a global lookup file), you'll see a warning, saying `This Pack has external dependencies.`



When you export Packs in `merge` mode, make sure to re-enter any required secrets after importing the Pack, to restore full functionality. This is necessary because Cribl Search deletes all encrypted fields

during the export process, to ensure security and prevent the accidental sharing of sensitive information.

Pack Dependencies

When you're creating a new Pack, or adding resources to an existing Pack, you can reference resources residing outside that Pack ("global" resources). Or, the other way around: you might want to reference a Pack resource from outside the Pack. Keep in mind the following guidelines about such dependencies.

Pack resources:

- Can reference other resources within the same Pack.
- Can reference global, non-Pack resources.
- Can't reference other Packs.

Global resources, in turn, can reference a Pack's resources only when the Pack is set to allow global access.

Reference a Macro

To reference a **global** Macro from the **global** context (for example, simply using a Macro in a query), use the standard Macro syntax.

```
${macroId}
```

Copy

To reference a **Pack** Macro from the **global** context, make sure the Pack is set to allow global access. Then, specify the Pack's ID with `pack(packId)`, like this:

```
${pack(packId).macroId}
```

Copy

To reference a **global** Macro **from within a Pack**, specify the global Pack called `cribl`.

```
${pack(cribl).macroId}
```

Copy

To reference a **Pack** Macro **from within the same Pack**, you can use the standard Macro syntax:

```
${macroId}
```

Copy

A Pack can't reference a Macro residing in another Pack.

Reference a Lookup

To reference a **global** lookup from the **global** context (for example, simply using the `lookup` operator in a query), use the standard lookup syntax. For example:

```
dataset=myDataset
| lookup lookupId on commonField
```

Copy

To reference a **Pack** lookup from the **global** context, make sure the Pack is set to allow global access. Then, specify the Pack's ID with `pack(packId)`, like this:

```
dataset=myDataset
| lookup pack(packId).lookupId on commonField
```

Copy

To reference a **global** lookup **from within a Pack**, specify the global Pack called `cribl`.

```
dataset=myDataset
| lookup pack(cribl).lookupId on commonField
```

Copy

To reference a **Pack** lookup **from within the same Pack**, you can use the standard lookup syntax:

```
dataset=myDataset
| lookup lookupId on commonField
```

Copy

The following limitations apply:

- A Pack can't reference a lookup residing in another Pack.
- You can't create or update Pack lookups with the `export` operator.

Reference a Saved Search

To reference a **global** saved search from the **global** context (for example, when basing a Dashboard visualization on an existing saved search), use the saved search's ID:

```
savedSearchId
```

Copy

To reference a **Pack** saved search from the **global** context, make sure the Pack is set to allow global access. Then, specify the Pack's ID (`packId`) like this:

```
packId.savedSearchId
```

Copy

To reference a **global** saved search **from within a Pack**, specify the global Pack called `cribl` in the following format.

```
cribl.savedSearchId
```

Copy

To reference a **Pack** saved search **from within the same Pack**, you can use the standard syntax:

```
savedSearchId
```

Copy



A Pack can't reference a saved search residing in another Pack.

Reference a Datatype

To reference a **global** Datatype from the **global** context (for example, when adding a Dataset), you normally use the Datatype's ID:

```
datatypeId
```

Copy

To reference a **Pack** Datatype from the **global** context, make sure the Pack is set to allow global access. Then, specify the Pack's ID (`packId`) like this:

```
packId.datatypeId
```

Copy



You can't reference a Datatype **from within** a Pack.

Packs Limitations

Here's what you can't do with Packs:

- Packs can't reference other Packs.
- Packs can't override system limits or **system** Usage Group limits.

14. Language Reference

A comprehensive reference for the Cribl Search implementation of KQL.

Cribl Search is based on Kusto Query Language (KQL), which lets you delve into your data to discover patterns, identify anomalies and outliers, and create statistical models.

While the Cribl implementation of KQL mostly follows the original, there are certain KQL differences (for example, we provide the implicit `cribl` operator). To get the details right, follow the language usage guidelines presented in these sections:

- Operators
- Commands
- Statements
- Functions
- Virtual Tables

You can also browse and link to all KQL operators and functions in our Index of Operators and Functions.

Runnable Kusto code examples include a **Run in Cribl Search** link in the top-right corner of the code block. Select it to open the query in your Cribl Search environment with the query loaded and ready to execute. You can also use the **Copy** button to copy a query and paste it into your own search.

Operators

An operator in Cribl Search is a query component that processes data, performing actions such as filtering, counting, or transforming events. Operators can use functions, and are delimited by the pipe character `|`.

For example, the `limit` operator sets the maximum number of events returned from a search:

```
dataset="cribl_search_sample"
 | limit 100
```

Copy | Run in Cribl Search

To learn more, see: Operators.

Commands

A command in Cribl Search is an instruction used to manage searches directly from the query box.

Commands are designed primarily for Admins and Editors, who use them to manage search jobs or learn more about the Organization's Datasets.

Commands start with a period (`.`), and can be combined with literals and operators. For example, the `.show` command can list searches:

```
.show running queries
```

Copy | Run in Cribl Search

Statements

A statement in Cribl Search is a special keyword that sets advanced search options (`set`) or assigns names to expressions (`let`) (enabling you to join Datasets).

For example, this statement sets the maximum number of events returned by the current search:

```
set max_results_per_search=1000;
```

Copy | Run in Cribl Search

To learn more, see: Statements.

Functions

A function in Cribl Search is a unit of logic that processes data based on arguments passed to it.

Functions can be used with operators to perform calculations, transformations, or conversions.

For example, the `max` function returns the maximum value of a field:

```
dataset="cribl_search_sample"
 | summarize LatestEvent=max(start)
```

Copy | Run in Cribl Search

To learn more, see: Functions.

Virtual Tables

A virtual table in Cribl Search is a dynamically generated dataset that provides system information useful for troubleshooting, performance analysis, and testing.

For example, the `$vt_dummy` virtual table generates sample data:

```
dataset="$vt_dummy" event<10
```

Copy

To learn more, see: Virtual Tables.

14.1. Language Reference Index

An alphabetical index of all Cribl Search KQL elements.

This page provides a global, alphabetical index of all elements of the Cribl Search KQL language implementation: operators, functions, commands, statements, virtual tables, and supported types.

Mathematical symbols for equality and inequality operators precede letters. Each building block is linked to its reference page and category.

Operator, Function, Element	Category
== (equals, case-sensitive)	Operator
=~ (equals, case-insensitive)	Operator
!= (not equals, case-sensitive)	Operator
!~ (not equals, case-insensitive)	Operator
abs	Mathematical function
acos	Mathematical function
ago	DateTime function
asin	Mathematical function
atan	Mathematical function
atan2	Mathematical function
avg	Statistical function
avgif	Statistical function
bag_has_key	Dynamic function
bag_keys	Dynamic function
bag_merge	Dynamic function
bag_pack	Dynamic function
bag_pack_columns	Dynamic function
bag_remove_keys	Dynamic function

Operator, Function, Element	Category
bag_set_key	Dynamic function
bag_zip	Dynamic function
base64_decode_toarray	String function
base64_decode_tostring	String function
base64_encode_fromarray	String function
base64_encode_tostring	String function
beta_cdf	Mathematical function
beta_inv	Mathematical function
beta_pdf	Mathematical function
bin	Conversion function
bin_auto	Conversion function
binary_and	Binary function
binary_not	Binary function
binary_or	Binary function
binary_shift_left	Binary function
binary_shift_right	Binary function
binary_xor	Binary function
bool	Type
.cancel	Command
case	Conditional function
ceil	Mathematical function
ceiling	Mathematical function
.clear	Command
centralize	Operator

Operator, Function, Element	Category
coalesce	Conditional function
contains	Operator
contains_cs	Operator
!contains	Operator
!contains_cs	Operator
cos	Mathematical function
cot	Mathematical function
count	Operator
count	Statistical function
countif	Statistical function
countof	String function
cribl	Operator
datetime	Type
datetime_add	DateTime function
datetime_diff	DateTime function
datetime_part	DateTime function
dayofmonth	DateTime function
dayofweek	DateTime function
dayofyear	DateTime function
dcount	Statistical function
dcountif	Statistical function
decimal	Type
decrypt	Scalar function
dedup	Operator

Operator, Function, Element	Category
degrees	Mathematical function
distinct	Operator
double	Type
dynamic	Type
encrypt	Scalar function
endofday	DateTime function
endofmonth	DateTime function
endofweek	DateTime function
endofyear	DateTime function
endswith	Operator
!endswith	Operator
endswith_cs	Operator
!endswith_cs	Operator
eventstats	Operator
exp	Mathematical function
exp10	Mathematical function
exp2	Mathematical function
export	Operator
extend	Operator
externaldata	Operator
extract	String function
extract	Operator
extract_all	String function
extract_json	String function

Operator, Function, Element	Category
find	Operator
findearliest	Cribl function
findearliestif	Cribl function
findfirst	Cribl function
findfirstif	Cribl function
findlast	Cribl function
findlastif	Cribl function
findlatest	Cribl function
findlatestif	Cribl function
floor	Conversion function
foldkeys	Operator
format_bytes	INET function
format_datetime	DateTime function
format_ipv4	INET function
format_ipv4_mask	INET function
format_timespan	DateTime function
from_binary_string	Binary function
gamma	Mathematical function
.generate	Command
getmonth	DateTime function
gettype	Conversion function
getyear	DateTime function
has	Operator
!has	Operator

Operator, Function, Element	Category
has_all	Operator
!has_all	Operator
has_any	Operator
!has_any	Operator
has_any_index	String function
has_cs	Operator
!has_cs	Operator
!hasprefix	Operator
!hasprefix_cs	Operator
!hassuffix	Operator
!hassuffix_cs	Operator
hash	Hash function
hash_combine	Hash function
hash_many	Hash function
hash_md5	Hash function
hash_sha1	Hash function
hash_sha256	Hash function
hash_xxhash64	Hash function
hasprefix	Operator
hasprefix_cs	Operator
hassuffix	Operator
hassuffix_cs	Operator
hourofday	DateTime function
iff	Conditional function

Operator, Function, Element	Category
iif	Conditional function
in	Operator
indexof	String function
int	Type
in~	Operator
!in	Operator
!in~	Operator
ip-lookup	Operator
ipv4_compare	INET function
ipv4_is_in_any_range	INET function
ipv4_is_in_range	INET function
ipv4_is_match	INET function
ipv4_is_private	INET function
ipv4_netmask_suffix	INET function
ipv6_compare	INET function
ipv6_is_match	INET function
isempty	String function
isfinite	Mathematical function
isinf	Mathematical function
isnan	Mathematical function
isnotempty	String function
isnotnull	String function
isnull	String function
join	Operator

Operator, Function, Element	Category
let	Statement
limit	Operator
list	Cribl function
log	Mathematical function
log10	Mathematical function
log2	Mathematical function
loggamma	Mathematical function
long	Type
lookup	Operator
make_bag	Dynamic function
make_bag_if	Dynamic function
make_datetime	DateTime function
make_timespan	DateTime function
match_regex	String function
matches regex	Operator
max	Statistical function
max_of	Conditional function
maxif	Statistical function
median	Cribl function
medianif	Cribl function
min	Statistical function
min_of	Conditional function
minif	Statistical function
monthofyear	DateTime function

Operator, Function, Element	Category
mv-expand	Operator
mv-pull	Operator
next	Window function
not	Mathematical function
now	DateTime function
null	Type
objects	Command literal
options	Command literal
order	Operator
parse_csv	String function
parse_ipv4	String function
parse_ipv4_mask	String function
parse_ipv6	String function
parse_ipv6_mask	String function
parse_json	String function
parse_url	String function
parse_urlquery	String function
parse_version	String function
percentile	Statistical function
persecond	Cribl function
persecondif	Cribl function
pi	Mathematical function
pivot	Operator
pow	Mathematical function

Operator, Function, Element	Category
prev	Window function
print	Operator
project	Operator
project-away	Operator
project-rename	Operator
queries	Command literal
radians	Mathematical function
rand	Mathematical function
range	Operator
range	Mathematical function
rate	Cribl function
rateif	Cribl function
real	Type
render	Operator
replace_regex	String function
reverse	String function
round	Mathematical function
row_cumsum	Window function
row_number	Window function
row_rank_dense	Window function
row_rank_min	Window function
row_window_session	Window function
search	Operator
send	Operator

Operator, Function, Element	Category
set	Statement
.show	Command
sign	Mathematical function
sin	Mathematical function
sort	Operator
split	String function
sqrt	Mathematical function
startofday	DateTime function
startofmonth	DateTime function
startofweek	DateTime function
startofyear	DateTime function
startswith	Operator
!startswith	Operator
startswith_cs	Operator
!startswith_cs	Operator
stats	Command literal
stdev	Statistical function
stdevif	Statistical function
stdevp	Statistical function
strcat	String function
strcat_delim	String function
strcmp	String function
strftime	DateTime function
string	Type

Operator, Function, Element	Category
strlen	String function
strptime	DateTime function
strrep	String function
substring	String function
sum	Statistical function
sumif	Statistical function
summarize	Operator
sumsq	Cribl function
sumsqif	Cribl function
suppress	Operator
take	Operator
take_any	Statistical function
take_anyif	Statistical function
tan	Mathematical function
timespan	Type
timestats	Operator
to_binary_string	Binary function
tobool	Conversion function
todatetime	DateTime function
todecimal	Conversion function
todouble	Conversion function
toint	Conversion function
tolong	Conversion function
tolower	String function

Operator, Function, Element	Category
top	Operator
top-hitters	Operator
toreal	Conversion function
tostring	Conversion function
totimespan	DateTime function
toupper	String function
translate	String function
trim	String function
trim_end	String function
trim_start	String function
union	Operator
unixtime_microseconds_todatetime	DateTime function
unixtime_milliseconds_todatetime	DateTime function
unixtime_nanoseconds_todatetime	DateTime function
unixtime_seconds_todatetime	DateTime function
url_decode	String function
url_encode	String function
values	Cribl function

14.2. Operators In Cribl Search

A comprehensive list of all operators supported in Cribl Search, grouped by category.

An operator in Cribl Search is a query component that processes data, performing actions such as filtering, counting, or transforming events. Operators can use functions, and are delimited by the pipe character `|`.

For example, the `limit` operator sets the maximum number of events returned from a search:

```
dataset="cribl_search_sample"
 | limit 100
```

Copy | Run in Cribl Search

Aggregation Operators

Aggregation operators summarize data by grouping it based on specified fields and applying aggregation functions like `sum`, `avg`, or `max` to produce meaningful insights.

Name	Description
`count`	Returns the number of all input events.
`eventstats`	Aggregates events and adds the results as new fields to the source events.
`summarize`	Produces a table that aggregates the input data.
`timestats`	Aggregates events by time periods or bins..

Data Operators

Data operators transform, enrich, or manipulate events, enabling actions like renaming, joining, or exporting.

Name	Description
`centralize`	Forces subsequent operators to the coordinator.
`export`	Exports search results to a lookup or a Cribl Lake Dataset.
`extend`	Appends fields created by expressions.
`extract`	Extracts data from a field.

Name	Description
`foldkeys`	Folds hierarchical field names into a nested structure.
`ip-lookup`	Enriches events with IP address data.
`join`	Merges events from two different data scopes.
`lookup`	Enriches events with lookup files.
`mv-expand`	Expands an object into multiple events.
`mv-pull`	Pulls key-value pairs from array objects into events or objects/bags.
`project-rename`	Renames fields.
`union`	Appends one set of results to another.

Display Operators

Display operators control how data is presented in the output, allowing formatting, sorting, or visualizing results for better readability.

Name	Description
`limit` (`take`)	Limits the number of events.
`order` (`sort`)	Arranges events into order by one or more fields.
`print`	Outputs expression results.
`project`	Keeps only the fields specified, and can also rename fields and insert new computed fields.
`project-away`	Excludes specific fields from the results..
`range`	Generates a series of events.
`render`	Enforces a specific visualization of the search results.
`top`	Returns the first N events sorted by the specified fields.

Filter Operators

Filter operators exclude or include events based on specified conditions, allowing you to narrow down the Dataset to relevant records.

Name	Description
`dedup` (`suppress`)	Filters out duplicate events.
`distinct`	Finds unique field values.
`search`	Finds events that contain the specified text.
`where`	Filters events based on the specified predicate.

Logical Operators

Logical operators perform comparisons and evaluations.

Operator	Description
`AND`	Returns `true` if both operands are `true`, otherwise returns `false`.
`NOT` or `!`	Returns `true` if the operand is `false`, otherwise returns `false`.
`OR`	Returns `true` if at least one operand is `true`, otherwise returns `false`.

Numerical Operators

Numerical operators perform arithmetic operations on numerical values, enabling calculations like addition or subtraction.

Operator	Description
`==`	Equal
`!=`	Not Equal
`>`	Greater Than
`>=`	Greater Than or Equal To
`<`	Less Than
`<=`	Less Than or Equal To
`+`	Add

Operator	Description
-	Subtract
*	Multiply
/	Divide
%	Modulo

Search Operators

Search operators retrieve events based on defined criteria, enabling efficient data discovery.

Name	Description
`cribl`	Finds specific events. The fundamental Cribl Search operator, implicit in queries that do not specify an operator.
`find`	Finds specific events.

String Operators

String operators manipulate and transform text, enabling actions like concatenation, trimming, replacement, or extraction.

Operator	Description	Case-Sensitive	Example (yields `true`)
`==`	Equals	Yes	`"aBc" == "aBc"`
`!=`	Not equals	Yes	`"abc" != "ABC"`
`=~`	Equals	No	`"abc" =~ "ABC"`
`!~`	Not equals	No	`"aBc" !~ "xyz"`
`contains`	RHS occurs as a subsequence of LHS	No	`"FabriKam" contains "BRik"`
`!contains`	RHS doesn't occur in LHS	No	`"Fabrikam" !contains "xyz"`
`contains_cs`	RHS occurs as a subsequence of LHS	Yes	`"FabriKam" contains_cs "Kam"`
`!contains_cs`	RHS doesn't occur in LHS	Yes	`"Fabrikam" !contains_cs "Kam"`

Operator	Description	Case-Sensitive	Example (yields `true`)
`endswith`	RHS is a closing subsequence of LHS	No	`"Fabrikam" endswith "Kam"`
`!endswith`	RHS isn't a closing subsequence of LHS	No	`"Fabrikam" !endswith "brik"`
`endswith_cs`	RHS is a closing subsequence of LHS	Yes	`"Fabrikam" endswith_cs "kam"`
`!endswith_cs`	RHS isn't a closing subsequence of LHS	Yes	`"Fabrikam" !endswith_cs "brik"`
`has`	Right-hand-side (RHS) is a whole term in left-hand-side (LHS)	No	`"North America" has "america"`
`!has`	RHS isn't a full term in LHS	No	`"North America" !has "amer"`
`has_all`	Same as `has` but works on all of the events	No	`"North and South America" has_all("south", "north")`
`!has_all`	Not all of the RHS terms are present in LHS	No	`"North and South America" !has_all("south", "east")`
`has_any`	Same as `has` but works on any of the events	No	`"North America" has_any("south", "north")`
`!has_any`	None of the RHS terms are present in LHS	No	`"North and South America" !has_any("east", "west")`
`has_cs`	RHS is a whole term in LHS	Yes	`"North America" has_cs "America"`
`!has_cs`	RHS isn't a full term in LHS	Yes	`"North America" !has_cs "amer"`
`hasprefix`	RHS is a term prefix in LHS	No	`"North America" hasprefix "ame"`
`!hasprefix`	RHS isn't a term prefix in LHS	No	`"North America" !hasprefix "mer"`
`hasprefix_cs`	RHS is a term prefix in LHS	Yes	`"North America" hasprefix_cs "Ame"`

Operator	Description	Case-Sensitive	Example (yields `true`)
`!hasprefix_cs`	RHS isn't a term prefix in LHS	Yes	`"North America" !hasprefix_cs "CA"`
`hassuffix`	RHS is a term suffix in LHS	No	`"North America" hassuffix "ica"`
`!hassuffix`	RHS isn't a term suffix in LHS	No	`"North America" !hassuffix "americ"`
`hassuffix_cs`	RHS is a term suffix in LHS	Yes	`"North America" hassuffix_cs "ica"`
`!hassuffix_cs`	RHS isn't a term suffix in LHS	Yes	`"North America" !hassuffix_cs "icA"`
`in`	Equal to any of the events	Yes	`"abc" in ("123", "345", "abc")`
`!in`	Not equal to any of the events	Yes	`"bca" !in ("123", "345", "abc")`
`in~`	Equal to any of the events	No	`"Abc" in~ ("123", "345", "abc")`
`!in~`	Not equal to any of the events	No	`"bCa" !in~ ("123", "345", "ABC")`
`matches regex`	LHS contains a match for RHS	Yes	`"Fabrikam" matches regex "b.*k"`

14.2.1. Aggregation Operators

A list of aggregation operators supported by Cribl Search.

Aggregation operators summarize data by grouping it based on specified fields and applying aggregation functions like `sum`, `avg`, or `max` to produce meaningful insights.

On `summarize`, `eventstats`, and `timestats`, you can append `asc`, `desc`, `nulls first`, and `nulls last` to each field in the `by` clause to sort grouped results without a separate `order` step. See Group-by Sort Order.

Name	Description
`count`	Returns the number of all input events.
`eventstats`	Aggregates events and adds the results as new fields to the source events.
`summarize`	Produces a table that aggregates the input data.
`timestats`	Aggregates events by time periods or bins..



In Dashboards, aggregations in child searches are based on the parent search's results, so if the parent search's results are capped by a system limit (such as `max_results_per_search` / **Results limit**), the child search's aggregations may be incomplete.

14.2.1.1. Count

The `count` operator returns the number of all input events.



`count` is a short form of `summarize count=count()`.

Syntax

```
Scope | count
```

Copy

Arguments

- **Scope**: The events to search.

Results

Returns a single record and column of type long. The value is the number of records in the scope.



In Dashboards, aggregations in child searches are based on the parent search's results, so if the parent search's results are capped by a system limit (such as `max_results_per_search` / **Results limit**), the child search's aggregations may be incomplete.

Example

- Count events where `status=200` and `response_time>2`.

```
dataset=myDataset status=200 response_time>2
| count
```

Copy

- Count the number of events.

```
dataset=$vt_dummy event<10
| count
```

Copy Run in Cribl Search

- Show the number of search jobs by their status and the user that created it. `$vt_jobs` requires **Admin** Permissions.

```
dataset=$vt_jobs
| summarize jobs=count() by status, user
```

Copy Run in Cribl Search

14.2.1.2. EVENTSTATS

The `eventstats` operator aggregates events and adds the results as new fields to the source events.

`eventstats` is similar to `summarize`, but it enriches the input events instead of replacing them.

By default, `eventstats` can aggregate up to 50,000 events at a time. You can change this limit with the **MaxNoOfAggregatedEvents** parameter.

Syntax

```
Scope | eventstats [max_events=MaxNoOfAggregatedEvents] [[AggregatedField =]
AggregationFunction [, ...]] [by [GroupField =] GroupingExpression [ asc | desc ] [
nulls first | nulls last ] [, ...]]
```

Arguments

- **Scope**: The events to aggregate and enrich.
- **MaxNoOfAggregatedEvents**: The maximum number of events to aggregate. After reaching this limit, aggregation stops, and all of the input events are enriched with the same, most recent aggregation results. Default: `50000`.
- **AggregatedField**: Optional name for a field that contains an aggregation result. Defaults to a name derived from the corresponding **AggregationFunction**.
- **GroupField**: Optional name for a group field. Defaults to a name derived from the corresponding **GroupingExpression**.
- **AggregationFunction**: A Cribl or statistical function, with field names as arguments. You can add multiple functions, separated by a comma. Wildcards are not supported for field names in aggregation functions.
- **GroupingExpression**: The expression by which `eventstats` groups the input events before aggregating them. You can add multiple expressions, separated by a comma. After each expression, you can optionally add `asc` or `desc`, and `nulls first` or `nulls last` (see Group-by Sort Order).

Group-by Sort Order

In **`summarize`**, **`eventstats`**, and **`timestats`**, you can specify sort direction and null placement directly on each field in the `by` clause, instead of using a separate `order` or `sort` operator after the aggregation.

After each grouping expression, you can specify:

- `asc` or `desc`: Sort direction for that group-by field.
- `nulls first` or `nulls last`: Whether null values for that field sort before or after non-null values.

You can combine direction and null placement on each field independently. For example, instead of:

```
| summarize cnt=count() by tenantId, workspace
| order by tenantId asc, workspace asc
```

Copy

you can write:

```
| summarize cnt=count() by tenantId asc, workspace asc
```

Copy

The `asc`, `desc`, `nulls first`, and `nulls last` keywords use the same meaning as in the `order` operator (including sorting rules).

Results

First, the input events are arranged into groups where the corresponding **GroupingExpression**s evaluate to the same values.

Then, the specified **AggregationFunction**s process each group. The results are added to the input events as new fields.



In Dashboards, aggregations in child searches are based on the parent search's results, so if the parent search's results are capped by a system limit (such as `max_results_per_search` / **Results limit**), the child search's aggregations may be incomplete.

Examples

Calculate the average response time for all events, and add a new field that contains the result.

```
dataset="cribl_internal_logs"
| limit 100
| eventstats avgResponseTime = avg(response_time)
```

Copy Run in Cribl Search

Calculate the average response time separately for each distinct value of the `src` field. Name the result field `srcAvgResponseTime`.

```
dataset="cribl_internal_logs"
| limit 100
| eventstats srcAvgResponseTime = avg(response_time) by src
```

Copy Run in Cribl Search

Show only those events that have a response time greater than the average.

```
dataset="cribl_internal_logs"
| limit 100
| eventstats avgResponseTime = avg(response_time)
| where response_time > avgResponseTime
```

Copy Run in Cribl Search

Calculate the ratio of events for each HTTP method.

```
dataset="cribl_internal_logs" method
| limit 1000
| summarize cnt=count() by method
| eventstats total=sum(cnt)
| project method, ratio = (cnt * 100 / total)
```

Copy Run in Cribl Search

```
dataset=$vt_dummy event<1000
| extend randomNumber=rand(10)
| eventstats avg(randomNumber)
```

Copy Run in Cribl Search

14.2.1.3. SUMMARIZE

The `summarize` operator produces a table that aggregates the input data.

`summarize` is similar to eventstats, but it replaces the input events instead of enriching them.

Syntax

```
Scope | summarize [[AggregatedField =] AggregationFunction [, ...]] [by [GroupField =] GroupingExpression [ asc | desc ] [ nulls first | nulls last ] [, ...]]
```

Arguments

- **Scope**: The events to search.
- **AggregatedField**: Optional name for a field that contains an aggregation result. Defaults to a name derived from the corresponding **AggregationFunction**.
- **GroupField**: Optional name for a group field. Defaults to a name derived from the **GroupingExpression**.
- **AggregationFunction**: Cribl and statistical functions, with field names as arguments. Wildcards are not supported for field names in aggregation functions.
- **GroupingExpression**: An expression that can reference the input data. The output will have as many events as there are distinct values of all the grouping expressions. After each expression, you can optionally add `asc` or `desc`, and `nulls first` or `nulls last`, to control the order of output rows (see Group-by Sort Order).

When the input table is empty, the output depends on whether **GroupingExpression** is used:

- If **GroupingExpression** is not provided, the output will be a single (empty) event.
- If **GroupingExpression** is provided, the output will have no events.

Group-by Sort Order

In **`summarize`**, **`eventstats`**, and **`timestats`**, you can specify sort direction and null placement directly on each field in the `by` clause, instead of using a separate `order` or `sort` operator after the aggregation.

After each grouping expression, you can specify:

- `asc` or `desc`: Sort direction for that group-by field.
- `nulls first` or `nulls last`: Whether null values for that field sort before or after non-null values.

You can combine direction and null placement on each field independently. For example, instead of:

```
| summarize cnt=count() by tenantId, workspace
| order by tenantId asc, workspace asc
```

Copy

you can write:

```
| summarize cnt=count() by tenantId asc, workspace asc
```

Copy

The `asc`, `desc`, `nulls first`, and `nulls last` keywords use the same meaning as in the `order` operator (including sorting rules).

Results

The input events are arranged into groups having the same values of the `by` expressions. Then the specified aggregation functions are computed over each group, producing an event for each group. The result contains the `by` fields and also at least one field for each computed aggregate. (Some aggregation functions return multiple fields.)

The result has as many events as there are distinct combinations of `by` values (which may be zero). If there are no group keys provided, the result has a single record.



In Dashboards, aggregations in child searches are based on the parent search's results, so if the parent search's results are capped by a system limit (such as `max_results_per_search` / **Results limit**), the child search's aggregations may be incomplete.

Examples

Minimum and maximum timestamp

Finds the minimum and maximum timestamp of all events in the Dataset. There is no `by` clause, so there is just one event in the output:

```
dataset="cribl_search_sample"
| summarize Min = min(_time), Max = max(_time)
```

Copy Run in Cribl Search

Minimum and maximum across two fields

Finds the minimum `start` time and maximum `end` times across events in the Dataset. With no `by` clause, there is just one event in the output:

```
dataset="cribl_search_sample"
| summarize earliest = min(start), latest = max(end)
```

Copy | Run in Cribl Search

Distinct count

Create an event for each source address, showing a count of distinct ports. Because there are few values for `srcaddr`, no grouping function is needed in the `by` clause:

```
dataset="cribl_search_sample"
| summarize sources=dcount(srcport) by srcaddr
```

Copy | Run in Cribl Search

Create an event for each continent, showing a count of the cities in which activities occur. Because there are few values for `continent`, no grouping function is needed in the `by` clause:

```
dataset=myDataset
| summarize cities=dcount(city) by continent
```

Copy

Summarize a count of distinct destination ports, by both destination address and day start.

```
dataset="cribl_search_sample"
| summarize destinations=dcount(dstport) by dstaddr, startofday(start)
```

Copy | Run in Cribl Search

Count and total by category and month

Create a table with sell transactions and the total amount per fruit and sell month. The output fields show the count of transactions, transaction worth, fruit, and the `datetime` of the beginning of the month in which the transaction was recorded.

```
dataset=myDataset
| summarize NumTransactions=count(), Total=sum(UnitPrice * NumUnits) by Fruit, StartO
```

Copy

Count items in intervals

- Create a table that shows how many items have prices in each interval: [0,10.0], [10.0,20.0], and so on. This example has a field for the count and a field for the price range.

  ```
  dataset=myDataset
  | summarize count() by price_range=bin(price, 10.0)
  ```

  Copy

- Count events by 60-second intervals. formatting the results as human-readable times.

  ```
  dataset="cribl_search_sample"
  | summarize count() by minute=bin(start, 60), strftime(minute,"%X")
  ```

  Copy Run in Cribl Search

- Count by parity.

  ```
  dataset=$vt_dummy event<10
  | extend answer=42, parity=iif(event%2==0, 'even', 'odd')
  | summarize count() by parity
  ```

  Copy Run in Cribl Search

- Generate a table of users and the credits they have consumed. `$vt_jobs` requires **Admin** Permissions.

  ```
  dataset=$vt_jobs
  | summarize totalSeconds=sum(cpuMetrics.totalExecCPUSeconds) by user
  | extend CreditsUsed=totalSeconds/3600
  | project CreditsUsed, user
  | render table
  ```

  Copy Run in Cribl Search

14.2.1.4. TIMESTATS

The `timestats` operator aggregates events by time periods or bins.

Syntax

```
[... |] timestats [ span=Time[ SnapToTime ] | numBins=Bins ] [ timeSource=TimeSource ] [ timeLabel=TimeLabel ] [[ FieldName= ] Aggregation... ] [ by GroupExpression [ asc | desc ] [ nulls first | nulls last ] [, GroupExpression [ asc | desc ] [ nulls first | nulls last ] ]... ]
```

You can define either `span` or `numBins`, not both. If you define neither, this operator will automatically compute a suitable time span based on the search's time range.

Arguments

- **Time**: Time period. Supports these relative times - `s[econds]`, `m[inutes]`, `h[ours]`, `d[ays]`, `w[eeks]`, `mon[ths]`, and `y[ears]`. Values without units get interpreted as seconds. For example, `1` = `1s`.
- **SnapToTime**: Round down (backward) to the nearest instance of **Time**. Append the `@` modifier, followed by the same or more granular `Time`. For example,
  - `1d@d` snaps back to the beginning of today, 12:00 AM (midnight) in the selected timezone.
  - `1d@h` snaps to 4:00 PM the next day if it's currently 4:00 PM.
- **Bins**: Numeric literal, desired number of bins. Bins are split as close as possible based on the search's time range.
- **TimeSource**: String. Name of the time field to use for aggregation. Defaults to `_time`. The field needs to have time in seconds.
- **TimeLabel**: String. Name of the output time field. Defaults to the same field as **TimeSource**.
- **FieldName**: String. Name to give to the field with the results created by **Aggregation**.
- **Aggregation**: Cribl and statistical functions. Wildcards are not supported for field names in aggregation functions.
- **GroupExpression**: A scalar expression that can reference the input data. The output will have as many events as there are distinct values of all the group expressions. After each expression, you can optionally add `asc` or `desc`, and `nulls first` or `nulls last`, to control the order of output rows (see Group-by Sort Order).

Group-by Sort Order

In **`summarize`**, **`eventstats`**, and **`timestats`**, you can specify sort direction and null placement directly on each field in the `by` clause, instead of using a separate `order` or `sort` operator after the aggregation.

After each grouping expression, you can specify:

- `asc` or `desc`: Sort direction for that group-by field.
- `nulls first` or `nulls last`: Whether null values for that field sort before or after non-null values.

You can combine direction and null placement on each field independently. For example, instead of:

```
| summarize cnt=count() by tenantId, workspace
| order by tenantId asc, workspace asc
```

Copy

you can write:

```
| summarize cnt=count() by tenantId asc, workspace asc
```

Copy

The `asc`, `desc`, `nulls first`, and `nulls last` keywords use the same meaning as in the `order` operator (including sorting rules).

Results

`timestats` pivots its aggregations into columns. For how Cribl Search names those columns, see Column Names. For what a cell contains when it matches no events, see Cells Without Data.



In Dashboards, aggregations in child searches are based on the parent search's results, so if the parent search's results are capped by a system limit (such as `max_results_per_search` / **Results limit**), the child search's aggregations may be incomplete.

Examples

- Create two fields per host in the format `totalWaitTime: Host` and `avgResponseTime: Host`, where `Host` is a host value, showing the aggregates for the time-bins (rows) of one minute:

```
timestats span=1m totalWaitTime=sum(responseTime), avgResponseTime=avg(responseT
```

Copy

- Create roughly 42 time bins, labeled as `when`, and create one output field for each pair of `srcaddr` and `dstaddr` values, named in the form `SrcaddrValue, DstaddrValue`:

```
dataset="cribl_search_sample"
| timestats timeLabel="when" numBins=42 totalRequest=count() by srcaddr, dstaddr
```

Copy Run in Cribl Search

- Aggregate time durations by interface, bin every minute:

```
dataset="cribl_search_sample"
| timestats span=1m totalTime=sum(end-start) by interface
```

Copy Run in Cribl Search

- Count events over time, bin every minute:

```
dataset=$vt_dummy event<600
| extend _time=_time-rand(600)
| timestats span=1m count()
```

Copy Run in Cribl Search

- Count events over time, using the `timeSource` option:

```
dataset=$vt_dummy event<600
| extend rando=_time-rand(600)
| timestats span=1m timeSource=rando count()
```

Copy Run in Cribl Search

- Count events over time, split by the field `method`, bin every minute:

```
dataset=$vt_dummy event<600
| extend _time=_time-rand(600), method=iif(event%2>0, "GET", "POST")
| timestats span=1m count() by method
```

Copy Run in Cribl Search

14.2.2. Data Operators

A list of data operators supported by Cribl Search.

Data operators transform, enrich, or manipulate events, enabling actions like renaming, joining, or exporting.

Name	Description
`centralize`	Forces subsequent operators to the coordinator.
`export`	Exports search results to a lookup or a Cribl Lake Dataset.
`extend`	Appends fields created by expressions.
`extract`	Extracts data from a field.
`foldkeys`	Folds hierarchical field names into a nested structure.
`ip-lookup`	Enriches events with IP address data.
`join`	Merges events from two different data scopes.
`lookup`	Enriches events with lookup files.
`mv-expand`	Expands an object into multiple events.
`mv-pull`	Pulls key-value pairs from array objects into events or objects/bags.
`project-rename`	Renames fields.
`union`	Appends one set of results to another.

14.2.2.1. Centralize

The `centralize` operator enforces the execution of operators on the coordinator rather than on federated executors. This is useful where executors lack network visibility to the destination. You can centralize the results on a coordinator before sending them. This operator overrides the normal division of labor, in which:

- Executors process as close to your data as possible, on the remote end. They scan data - for example, reading from S3, decompressing, filtering, and projecting.
- Coordinators receive the partial results from the executors and perform post-aggregation and merging of the results.

Syntax

```
... | centralize
```

Copy

Examples

Centralize your data on a coordinator before sending it to a Cribl Stream Destination.

```
dataset=$vt_dummy event<100
| extend parity=iif(event%2==0, 'even', 'odd')
| centralize
| send
```

Copy Run in Cribl Search

```
dataset="cribl_search_sample"
| where dstport <= 1024 and action == REJECT
| centralize
| send
```

Copy Run in Cribl Search

```
dataset=myDataset method or status
| where status > 299
| centralize
| send
```

Copy

14.2.2.2. Export

The `export` operator does one of the following:

- Sends results generated by a search to an existing Cribl Lake Dataset. (You must create the Dataset first.)
- Sends results generated by a search to an existing Search Dataset. (You must create the Search Dataset first.)
- Writes aggregated search results to a metrics Dataset (logs to metrics).
- Creates or updates a lookup from search results.

Only Admin and Editor Search Members can run the `export` operator. See also specific limitations on exporting to Lake Datasets, to Search Datasets, to metrics Datasets, and to lookups.

Syntax

The `export` operator supports four destination keywords: `lake`, `search`, `metrics`, and `lookup`. Specify one keyword after `to` to pick the destination type.

If you don't specify a keyword, `export` tries to write to a Cribl Lake Dataset, not to a Search Dataset or a metrics Dataset. To export to a Search Dataset, a metrics Dataset, or a lookup, you must use the `search`, `metrics`, or `lookup` keyword explicitly.

Export to Cribl Lake:

```
Scope | export [ suppressPreviews=Previews ] to [ lake ] LakeDatasetName [ tee=Tee ]
```

Copy

Export to a Search Dataset:

```
Scope | export [ suppressPreviews=Previews ] to search SearchDatasetID [ tee=Tee ]
```

Copy

Export to a metrics Dataset:

```
Scope | export [ suppressPreviews=Previews ] to metrics [ MetricsDatasetID ]
                [ tee=Tee ]
                [ nameField=NameField ]
                [ valueField=ValueField ]
                [ typeField=TypeField ]
                [ timeField=TimeField ]
                [ type=histogram ]
                [ labelFields=LabelFields ]
```

Copy

Export to a lookup:

```
Scope | export [ mode=Mode ]
                [ description=Description ]
                [ suppressPreviews=Previews ]
                [ fieldMapping=PairsToMap ]
                [ compress=Compress ]
                to lookup LookupName
                [ tee=Tee ]
                [ maxEvents=MaxEvents ]
```

Copy

Arguments

Arguments are case-insensitive.

`lake`: Export to a Cribl Lake Dataset

- **Scope**: The events to search.
- **Previews**: Boolean. If `false` (default), Cribl Search displays intermediate statistics (previews) during the export operation. If `true` (so, `suppressPreviews=true`), you'll see only the final statistics, once the export operation completes.
- **LakeDatasetName**: The Cribl Lake Dataset to export results to. You must choose an already existing Dataset.
- **Tee**: Boolean. If set to `true`, the search results are shown as usual. If `false` (which is the default), instead of the results, Cribl Search displays statistics related to the export.

Dataset Limitations

Typically, you're exporting data in which Cribl Search has already parsed field names and values. This makes the data compatible with Lakehouses. However, if you happen to send **unparsed** data, you won't be able to search it at Lakehouse speed.

The `export` operator can't send data to a Cribl Lake Dataset that is populated via Splunk Cloud Direct Access.

`search`: Export to a Cribl Search Dataset

This option exports results to a Search Dataset hosted on a Cribl-managed lakehouse engine.

- **Scope**: The events to search.
- **Previews**: Boolean. If `false` (default), Cribl Search displays intermediate statistics (previews) during the export operation. If `true` (so, `suppressPreviews=true`), you'll see only the final statistics, once the export operation completes.
- **SearchDatasetID**: The ID of an existing Search Dataset to export results to. The Dataset must be hosted on a lakehouse engine that is in **Ready** status.
- **Tee**: Boolean. If set to `true`, the search results are shown as usual. If `false` (which is the default), instead of the results, Cribl Search displays statistics related to the export.

`metrics`: Export to a Metrics Dataset

Preview Feature

Cribl is still developing this Preview feature. We don't recommend using it in a production environment, because the feature might not be fully tested or optimized for performance, and related documentation could be incomplete.

Please continue to submit feedback through normal Cribl support channels, but assistance might be limited while the feature remains in Preview.

Use `export to metrics` to turn aggregated search results into stored metrics. Typically, you start by filtering logs, summarizing them with operators such as `summarize` and `bin`, shaping name/value/type fields, and then exporting. This is a Search query path (ad hoc or scheduled), not a continuous stream-based logs-to-metrics pipeline.

- **Scope**: The events to search. Each result that you export should already look like a metric sample (name, numeric value, optional type, optional labels, and optional timestamp).
- **Previews**: Boolean. If `false` (default), Cribl Search displays intermediate statistics (previews) during the export operation. If `true` (so, `suppressPreviews=true`), you'll see only the final statistics, once the

export operation completes.

- **MetricsDatasetID**: Optional ID of the metrics Dataset to write to. Defaults to `metrics`. Cribl Search auto-provisions a metrics Dataset for each lakehouse engine: the first engine's Dataset is named `metrics`, and each additional engine gets `metrics_<engine_id>`. See The Metrics Dataset.
- **Tee**: Boolean. If set to `true`, the search results are shown as usual. If `false` (which is the default), instead of the results, Cribl Search displays statistics related to the export (including events sent and events dropped). Use those stats to confirm the input shape: more than zero events sent and zero events dropped means the events were shaped correctly. Export is strict about the expected fields and values.
- **NameField**: Field that holds the metric name. Defaults to `name`. Empty or missing names are dropped.
- **ValueField**: Field that holds the numeric metric value. Defaults to `value`. Values must be finite numbers. Non-numeric or non-finite values are dropped.
- **TypeField**: Field that holds the scalar metric type for counter/gauge export. Defaults to `type`. Accepted values are `default`, `counter`, and `gauge` (case-insensitive). If the field is missing or empty, Cribl Search uses `default`. Other values are dropped. Ignored when `type=histogram`.
- **TimeField**: Field that holds the metric timestamp. Optional. If you set `timeField` and the operator can't find or coerce that timestamp, the event is dropped. If you omit `timeField`, Cribl Search looks for `_time` on each event. If `_time` is also missing, it generates a timestamp at insertion time with `now()` as a Unix epoch millisecond value. For scalar export, each row gets its own generated timestamp. For histogram export, observations in the same flush batch share one generated timestamp. Supported inputs include epoch seconds, milliseconds, microseconds, and nanoseconds, ISO-style and Search-style datetime strings, JavaScript `Date` values, and structured timestamp objects.
- **Type**: Literal export type. The only accepted value is `histogram`. Use `type=histogram` for histogram export. When `type=histogram` is set, histogram mode takes precedence over `typeField`. Literal `type=counter` and `type=gauge` are not supported - set those types with `typeField` instead.
- **LabelFields**: Metric labels (dimensions). Pass a list of fields (`labelFields=[host, service, status]`) or a single object field whose keys become label names (`labelFields=labels`). In object mode, the field must be a flat object with no nested objects - for example `{pod_name: "api-1", _123zone: "us-west-2"}`. Label values are stringified. Null values and nested object values are dropped. Nested paths and quoted field names are supported in list mode (for example `service.name`, `["weird field"]`). Wildcard field selectors are not supported. Label names are normalized for metric storage: characters outside `a-z`, `A-Z`, `0-9`, and `_` become `_`, and names that don't start with a letter or `_` get a leading `_`.

Metrics Limitations

- Export to metrics requires metrics export permission, or Maintainer access on the target metrics Dataset.

- Destination Datasets are the auto-provisioned metrics Datasets on a lakehouse engine (`metrics` or `metrics_<engine_id>`).
- For counters and gauges, set the type with `typeField`. Use the `type=` argument only for `histogram`.
- Invalid events are dropped during export. When `tee=false`, check export statistics for events sent and events dropped. Drop reasons can include `missing_name`, `invalid_value`, `invalid_type`, and `invalid_timestamp`.
- When you bin by time, assign the binned value back to `_time` (for example `_time=bin(_time, 1m)`). A bare `bin(_time, ...)` renames the column. If you set `timeField` and that timestamp is missing or invalid, export drops the data. If you omit `timeField`, export uses `_time` when present, otherwise it generates a timestamp with `now()`.
- Metrics field parameters (`nameField`, `valueField`, `typeField`, `timeField`, `type`, `labelFields`) apply only to `export to metrics`. They are rejected on `lake`, `search`, and `lookup` exports.

Metric Types for Export

- **Scalar (default path):** One ingest row per event. Use for counts and gauges. Set the type with `typeField` (`default`, `counter`, or `gauge`).
- **Histogram (`type=histogram`):** Each input event is one numeric sample. Cribl Search groups samples that share the same name, timestamp, and labels, then assembles a native histogram. Pass many sample rows (same name/labels/time, different values) rather than pre-built histogram buckets.

Logs to Metrics Pattern

1. Run a search against a log Dataset.
2. Filter and summarize (for example, errors per minute per service).
3. Shape fields so each result has a metric name, a numeric value, and optional type and labels.
4. Pipe to `| export to metrics` with field mappings. If you used time binning, assign it as `_time=bin(_time, ...)` so export can find `_time`. To use a different timestamp field, set `timeField` to that field.
5. Run the search and check the export statistics: events sent should be greater than zero, and events dropped should be zero.
6. Save and schedule the search if you want metrics to keep updating.

`lookup`: Export to a Lookup

- **Scope**: The events to search.

- **Mode**: Supports `create`, `overwrite`, and `append`. Defaults to `create`. If the lookup doesn't exist, it defaults to `create`, simplifying scheduled searches. When using `append` mode, you can include `description`, `fieldMapping`, and `compress` parameters, and if the lookup exists, they are ignored. This streamlines the process of appending data to a lookup as part of scheduled searches, as the table is generated during the first scheduled run and continues to append new content in subsequent runs.
- **Description**: String. The description to give the lookup.
- **Previews**: Boolean. If `false` (default), Cribl Search displays intermediate statistics (previews) during the export operation. If `true` (so, `suppressPreviews=true`), you'll see only the final statistics, once the export operation completes.
- **PairsToMap**: String. Comma-separated list of `sourceName:targetName` pairs to map event property names to CSV output names. Defaults to all of the last known list of projected fields.
- **Compress**: String. Defaults to `auto` where files larger than 16 KB are compressed. Set as `true` to compress no matter the size and `false` to not compress the file.
- **LookupName**: The lookup file name, without the file extension. For example: a file name of `users.csv` is entered as `users`.
- **Tee**: Boolean. Defaults to `false` where search results are not shown in Cribl Search. Instead, you get an event with the URL and the number of bytes and events sent or dropped. When `true` the search results are displayed and no stats are provided. For example: `tee=true`.
- **MaxEvents**: The maximum number of events that `export` will write to the table. Cribl Search will drop any events beyond this limit. Defaults to `10000` (10,000 rows). This is also the maximum number of events that this operator's `lookup` mode can handle, so entering a higher **MaxEvents** still effectively sets a limit of `10000`.

Lookup Limitations

You can't use the `create` mode on an existing lookup. This will trigger an error.

You can't use the `export` operator to create or update Pack lookups. For example, `| export to lookup pack(packId).lookupId` will **not** work.

`_raw` in Exports to Cribl Lake

Exports to Lake Datasets include the `_raw` field. If you want to remove this field, use the `project-away` operator.

`_time` in Exports to Cribl Lake

Cribl Lake handles the `_time` field automatically, so Datatype timestamp settings in Cribl Search don't apply.

If the source event has no `_time` field, Cribl Lake adds this field, setting its value to `now()` at write time.

Examples

Export search results to the `myDataset` Lake Dataset:

```
dataset="cribl_search_sample"
| export to lake myDataset

// you can also drop the `lake` keyword
dataset="cribl_search_sample"
| export to myDataset
```

Copy

Export search results to a Lake Dataset, and remove the `_raw` field:

```
dataset="cribl_search_sample"
| export to lake myDataset
| project-away _raw
```

Copy

Export search results to the `mySearchDataset` Search Dataset:

```
dataset="cribl_search_sample"
| export to search mySearchDataset
```

Copy

Count log levels and export them as metrics (uses default `name`, `value`, and destination Dataset `metrics`):

```
dataset="cribl_internal_logs" level!=null
| summarize value=count() by level
| project name="log_level_count", level, value
| export to metrics labelFields=[level]
```

Copy

Export HTTP 5xx errors per minute as a counter metric:

A bare `bin(_time, ...)` in `summarize` renames the `_time` column. Preserve the name with `_time=bin(_time, 1m)` so export can find `_time` (or set `timeField` to your timestamp field). Otherwise, if you set `timeField=_time` and the column is missing, export drops the events.

```
dataset="my_logs"
| where status >= 500
| summarize value=count() by _time=bin(_time, 1m), service, status
| extend name="http_errors_total", type="counter"
| export to metrics
    timeField=_time
    nameField=name
    valueField=value
    typeField=type
    labelFields=[service, status]
```

Copy

Export to a non-default metrics Dataset on another lakehouse engine:

```
dataset="my_logs"
| summarize value=count() by _time=bin(_time, 1m), service
| extend name="requests_total", type="counter"
| export to metrics metrics_my_engine
    timeField=_time
    labelFields=[service]
```

Copy

Export request duration samples as a histogram:

```
dataset="my_logs"
| where isnotnull(duration_ms)
| project _time, service, value=duration_ms
| extend name="http_request_duration_ms"
| export to metrics
    type=histogram
    timeField=_time
    nameField=name
    valueField=value
    labelFields=[service]
```

Copy

Create a lookup named `mylookup` with the `time` and `status` fields.

```
dataset="cribl_search_sample" status="*"
| limit 5
| export description="My lookup" fieldMapping="_time:time,status:status" to lookup my
```

Copy Run in Cribl Search

You can verify the contents of the lookup with this command - replacing `mylookup` with the name of your own lookup file:

```
dataset="$vt_lookups" lookupFile="mylookup"
```

Copy Run in Cribl Search

Export a lookup with two columns, `method` and `cnt`.

```
dataset=$vt_dummy event<600
| extend _time=_time-rand(600), method=iif(event%2>0, "GET", "POST")
| summarize cnt=count() by method
| export mode=append description="Table with http methods count" to lookup mymethods
```

Copy Run in Cribl Search

To verify that table was exported.

14.2.2.3. EXTEND

The `extend` operator calculates one or more expressions and assigns the results to fields.

Syntax

```
Scope | extend [FieldName | (FieldName[, ...]) =] Expression [, ...]
```

Copy

Arguments

- **Scope**: The events to search.
- **FieldName**: Optional. The name of the field to add or update. If omitted, the name will be generated.
    - If **Expression** returns more than one field, a list of field names can be specified in parentheses. In this case, **Expression**'s output fields will be given the specified names, dropping the rest of the output fields, if there are any.
    - If a list of the field names is not specified, all **Expression**'s output fields with generated names will be added to the output.
- **Expression**: A calculation over the fields of the input.

Results

Resulting fields are returned in one of the following ways:

- Field names noted by `extend` that already exist in the input are removed and appended as their new calculated values.
- Field names noted by `extend` that do not exist in the input are appended as their new calculated values.

If an **Expression** references a field that an event doesn't contain, `extend` returns `null` for that field. The field stays in the output, so every event has the same set of fields.

Examples

To calculate and add fields called `Duration` and `IsSevere`:

```
dataset=myDataset
| extend Duration = CreatedOn - CompletedOn
, IsSevere = Level == "Critical" or Level == "Error"
```

Copy

Monitoring Disk Operations by Ratio and Status

If you're using Cribl Edge, you can use `extend` to calculate the ratio of read and write operations on each Edge Node. Based on the ratio, you can use the iif function to give each Node a status, indicating any imbalances or I/O issues:

```
dataset="cribl_edge_metrics"
| extend Disk_Operation_Ratio = node_disk_reads_completed_all_total / node_disk_write
| extend operation_status = iif(Disk_Operation_Ratio > 2, 'High Read', iif(Disk_Opera
| summarize count() by operation_status
```

Copy Run in Cribl Search

Monitoring CPU Usage by Level

You can use `extend` to monitor CPU usage on each Edge Node. The following query breaks CPU usage into two categories: `High` for CPU usage greater than 70%, and `Low` for anything below that threshold. Then, the `timestats` operator allows you to observe how these categories change over time.

```
dataset=cribl_edge_metrics
| extend CPU_Usage_Per_Host = iif(node_cpu_percent_active_all > 70, 'High', 'Low'), H
| timestats by CPU_Usage_Per_Host
```

Copy Run in Cribl Search

```
dataset=$vt_dummy event<10
| extend answer=42, parity=iif(event%2==0, 'even', 'odd')
```

Copy Run in Cribl Search

14.2.2.4. EXTERNALDATA

The `externaldata` operator fetches external data from HTTP(S) URLs, including public APIs.



If you frequently use `externaldata` to search the same API endpoints, consider setting up a Generic HTTP API Dataset. See also the Usage Note below.

Syntax

```
externaldata [ ConnectionURL [, ...] ] [ with ( PropertyName = PropertyValue [, ...] ) ]
```

Copy



The outer brackets surrounding **ConnectionURL** are required and literal. They do not indicate an optional argument (as the inner brackets do).

Arguments

Name	Type	Required	Description
ConnectionURL	string	Yes	The HTTP(S) URL from which to fetch data.
PropertyName, **PropertyValue**	string	No	A list of optional properties that determine how to interpret the retrieved data.

Properties

Property	Type	Description
dataField	string	The name of the field (in the response JSON) to pull data from. Leave blank if the result is an array.
datatype	string	The data type to use to parse the data. If none is specified, tries to parse the data as a JSON array.
headers	string	A JSON object containing the headers to send with the request.
method	`GET` or `POST`	The HTTP method used when making the API request.

Usage Note

Unlike most other operators, `externaldata` includes - in the query - all that is needed to establish connectivity to remote data. This might include sensitive key information in cleartext.

The query is logged (like other queries), and the log events might include this sensitive information. The Dataset where it's logged is readable only by users with elevated privileges. However, to avoid any exposure of credentials in cleartext, consider configuring a generic HTTP API Dataset as an alternative to this operator.

Examples

Simple

```
externaldata
[
  "https://cat-fact.herokuapp.com/facts"
]
```

Copy

With a dataField

```
externaldata
[
  "https://vpic.nhtsa.dot.gov/api/vehicles/getallmanufacturers?format=json"
]
with(
  dataField="Results"
)
```

Copy

With a Datatype (ndjson file)

```
externaldata
[
  "https://gist.githubusercontent.com/rfmcnally/0a5a16e09374da7dd478ffbe6ba52503/raw/
]
with(
  datatype="Cribl Search"
)
```

Copy

Specifying HTTP headers

```
externaldata
[
  "https://vpic.nhtsa.dot.gov/api/vehicles/getallmanufacturers?format=json"
]
with(
  dataField="Results",
  headers='{"user-agent": "Foo", "otherHeader": "Bar"}'
)
```

Copy

Get weather data for New York City.

```
externaldata ["https://wttr.in/NewYork?format=j1"]
| mv-expand weather.0.hourly
```

14.2.2.5. Extract

The `extract` operator extracts information from a field (which defaults to `_raw`), using either a predefined Parser or various `Type` options (such as `delimited`, `regex`, `kvp`, `json`, `csv`, `elff`, or `clf`).



To extract a substring from a source string, using an RE2 regular expression, see the `extract` scalar string function.

Syntax

```
... | extract [ SourceOption ] [ type=Type | parser=Parser ]
```

- `[ type=delimited [ DelimOption ] FieldList ]`
- `[ [ type=regex ] [ RegexOption ] RegexLiteral [RegexLiteral[...]] ]`
- `[ type=keyvalue [ FieldList ]]`
- `[ type=json [ FieldList ]]`
- `[ type=csv FieldList ]`
- `[ type=elff FieldList ]`
- `[ type=clf [ FieldList ]]`

Rules

This operator automatically detects the `type` when you define **RegexLiteral** or **DelimOption**. For example, if you provide **RegexLiteral**, it's assigned as `type=regex`. Or, if you specify **DelimOption**, it's assigned as `type=delimited`.

You can define either **DelimOption** or **RegexOption**, not both.

You can have multiple **FieldList**s. These will be merged into one larger field list.

A **FieldList** is optional for the key value, JSON, and CLF types. If no **FieldList** is specified:

- Key value and JSON types extract all fields.
- CLF type extracts `clientip`, `ident`, `user`, `timestamp`, `request`, `status`, and `bytes`.

Arguments

Here are syntax details and options for each of this operator's arguments.

SourceOption

Syntax - `[ SourceIdent=FieldName ]`.

Defaults to `source=_raw`.

- **SourceIdent**: Define as `source`, `sourceField`, or `src`.
- **FieldName**: Name of the field to extract from. Case sensitive.

Type

Syntax - `[ Type=TypeName ]`. Example: `type=csv`

- **Type**: Define as either `type` or `format`.
- **TypeName**: See the following table.

TypeName	Define as
Delimiter	`delimited`, `del`, or `delim`
Regex	`regex`, `regexp`, or `re`
Key Value	`kvp`, `keyvalue`, or `kv`
JSON	`json` or `js`
CSV	`csv`
ELF	`elff` or `extended`
CLF	`clf` or `common` (case insensitive)

FieldList

Syntax - `"FieldName" [, "FieldNameList" ]`.

Case-sensitive. Example: `"field1,field2"`

Alternative syntax - `FieldIdent="FieldNameList"`.

Example: `fields=field1,field2`

- **FieldIdent**: Define as either `field` or `fields`.
- **FieldNameList**: Syntax - `FieldName [, FieldNameList ]`. Case sensitive.

Parser

Syntax - `parser="KnownParserName"`.

Use a predefined Parser. Case-sensitive.

RegexLiteral

Syntax - `@'NamedRegularExpression'`.

At least one named capture group is required. Example: `@'metric1=(?<metric1>\d+)'`

To extract key-value pairs and assign them to fields, use the capture group names `_NAME_0` and `_VALUE_0`. Example: `@'\"(?<_NAME_0>\w+)\s\/(?<_VALUE_0>.*)\"'`

Alternative syntax - `RegexIdent=@'NamedRegularExpression'`.

Example: `regex=@'metric1=(?<metric1>\d+)'`

- **RegexIdent**: Define as either `regex` or `regexp`.

DelimOption

Syntax - `[[ DelimCharOpt ] [ EscapeCharOpt ] [ QuoteCharOpt] [ NullValOpt ]]`

Argument	Define as	Syntax	Default Value	Example
DelimCharOpt	`delimchar`, `delimiter`, or `delim`	`DelimCharOpt=char`	`;`	`delimiter=:`
EscapeCharOpt	`escapechar`, `escape`, or `esc`	`EscapeCharOpt=char`	`\`	`esc=\`
QuoteCharOpt	`quotechar` or `quote`	`QuoteCharOpt=char`	`"`	`quotechar='`
NullValOpt	`nullvalue` or `undefined`			

RegexOption

Syntax - `[[ IterationOpt ] [ OverwriteOpt ]]`

Argument	Define as	Syntax	Default Value	Example
IterationOpt	`numiterations`, `iterations`, or `iter`	`IterationOpt=integer`	`100`	`iterations=11`
OverwriteOpt	`overwrite` or `ow`	`OverwriteOpt=boolean`	`false`	`ow=true`

Examples

This example extracts the domain name from an email address:

```
dataset=$vt_dummy event<10
| extend email="test@example.com"
| extract source=email @'@(?<domainName>.*$)'
```

Copy | Run in Cribl Search

This example extracts delimited field values:

```
dataset=$vt_dummy event<10
| extend myField="value1|value2|value3"
| extract source=myField type=delim delimChar="|" "field1,field2,field3"
```

Copy | Run in Cribl Search

This example extracts and names four fields from the CSV-formatted source field `foobar`:

```
dataset=$vt_dummy events < 10
| extend foobar="foo,bar,baz,quux"
| extract source=foobar type=csv "field1,field2,field3,field4"
```

Copy | Run in Cribl Search

This example extracts all key-value pairs from the default source field `_raw`:

```
dataset=myDataset
| extract type=keyvalue
```

Copy

This example extracts all key-value pairs from the named source field `payload`:

```
dataset=$vt_dummy events<10
| extend payload="time=now key=value message=\"many words here\""
| extract source=payload type=keyvalue
```

Copy | Run in Cribl Search

This examplee uses a Parser to extract all fields from `mySource`:

```
dataset=myDataset
| extract source="mySource" parser="Apache Common Log Format"
```

Copy

This example extracts delimited values (from `_raw`) using the `|` as the delimiter. The `type` specification could be omitted in this case, because the `type` is implicitly given by specifying the `delimChar` option:

```
dataset=myDataset
| extract type=delim delimChar="|" "field1,field2"
```

Copy

This example extracts the fields `metric1` and `foo` from `_raw` (default source) via named regular expressions. The `type` specification could be omitted in this case, because the `type` is implicitly given by specifying regular expressions.

```
dataset=myDataset
| extract type=regex @'metric1=(?<foo>\d+)'
```

Copy

14.2.2.6. FOLDKEYS

The `foldkeys` operator takes field names that contain a separator character, and folds them into a nested structure. This operator supports regex literals.

```
// fold all field names by `/`, and delete the original entries
Scope
 | foldkeys separator="/"
```

Copy

Purpose

Use `foldkeys` to normalize hierarchical field names. If you have data where a hierarchy of fields is encoded in the name (for example, `email.address` and `email.user`), `foldkeys` can transform the keys (not the values) into a nested structure.

Syntax

```
Scope
 | foldkeys [delete_original=true|false]
            [separator="<Separator>"]
            ["<SelectionRegex>"]
```

Copy

Parameters

Parameter	Required	Description
`Scope`		Events to search.
`delete_original`		`true` (default): output only the folded field names. `false`: output both the folded and original field names.
`separator`		Set a `Separator` character to use as the path separator, for example: `separator="/"`. The default is `.`.
`SelectionRegex`		Optional regular expression. If defined, only field names that match this expression are folded (along with the `SeparatorCharacter`).

To pass regex literals as **SelectRegex** parameters, see syntax details at Regex Examples, Regex Flags, and Disambiguate Regex Characters.

Returns

All the input events, but with hierarchical field names transformed into nested structures.

Examples

Fold All Field Names

Fold all field names, using the default `.` separator. Don't keep the original field names in the output.

```
dataset="$vt_dummy" event < 1
 | extend ["email.address"]="foo", ["email.user"]="bar"
 | foldkeys
```

Copy | Run in Cribl Search

Input (before `foldkeys`):

```
{
  "_time": 1723036428.379,
  "event": 0,
  "dataset": "$vt_dummy",
  "email.address": "foo",
  "email.user": "bar"
}
```

Copy

Output (after `foldkeys`):

```
{
  "_time": 1723036570.006,
  "event": 0,
  "dataset": "$vt_dummy",
  "email": {
    "address": "foo",
    "user": "bar"
  }
}
```


Copy

Fold Selected Field Names and Keep the Originals

Fold all field names that start with `eMail` (case-insensitive), using `/` as a separator. Keep the original field names in the output.

```
dataset="$vt_dummy" event < 3
 | extend ["email/name"]=strcat("foo", event +5), ["email/number"]=event * 3, ["rolf/
 | foldkeys delete_original=false separator="/" '/^eMail/i'
```

Copy Run in Cribl Search

Input (before `foldkeys`):

```
// event 0
{
  "_time": 1723036048.423,
  "event": 0,
  "dataset": "$vt_dummy",
  "email/name": "foo5",
  "email/number": 0,
  "rolf/sub/field": 10
}

// event 1
{
  "_time": 1723036048.423,
  "event": 1,
  "dataset": "$vt_dummy",
  "email/name": "foo6",
  "email/number": 3,
  "rolf/sub/field": 11
}

// event 2
{
  "_time": 1723036048.423,
  "event": 2,
  "dataset": "$vt_dummy",
  "email/name": "foo7",
  "email/number": 6,
  "rolf/sub/field": 12
}
```

Copy

Output (after `foldkeys`):

```
// event 0
{
  "_time": 1723036188.255,
  "event": 0,
  "dataset": "$vt_dummy",
  "email/name": "foo5",
  "email/number": 0,
  "rolf/sub/field": 10,
  "email": {
    "name": "foo5",
    "number": 0
  }
}

// event 1
```

14.2.2.7. IP-LOOKUP

The `ip-lookup` operator retrieves geolocation data of IP addresses using MaxMind's GeoIP2 and GeoLite2 or IPinfo's IP address databases to enrich events with details such as city, continent, country, latitude, longitude, postal code, region, and time zone based on the provided IP address field. You can customize which fields to return, add prefixes, and their language.



You can display `ip-lookup` results in a Map Chart.

Prerequisites

The `ip-lookup` operator needs a `.mmdb` database file. You need to download the file from MaxMind or IPinfo and then create a lookup table with it. This file contains the geolocation data needed for IP address enrichment.

- MaxMind's GeoIP2 City, GeoIP2 Country, and GeoLite2 are supported. The GeoIP2 databases are a more accurate version of the free GeoLite2 City database.
- To download the free GeoLite2 City database you need a free GeoLite2 account. For details, see MaxMind's Accessing GeoLite2 Free Geolocation Data documentation.
- IPinfo's IP Geolocation, IP to privacy detection, ASN, IP to Company, Abuse contact, and WHOIS databases are supported.
- IPinfo also provides the following free IP databases: IP to Country, IP to ASN, and IP to Country ASN.

Syntax

```
Scope | ip-lookup [ output=OutputField[, ...] ] [ prefix=Prefix ] [ lang=Lang ]
LookupTable [ on IPField ]
```

Arguments

- **Scope**: The events to search.
- **OutputField**: Field(s) to return from the lookup. By default, all available fields are returned.
  - `city` - for example, `Georgetown`
  - `continent` - for example, `North America`
  - `continent_code` - for example, `NA`
  - `country` - for example, `United States`
  - `country_code` - for example, `US`

    - `lat` - numeric latitude coordinate
    - `lon` - numeric longitude coordinate
    - `postal` - for example, `40324`
    - `region` - for example, `Kentucky`
    - `region_code` - for example, `KY`
    - `time_zone` - for example, `America/Los_Angeles`
- **Prefix**: A prefix to add to the output fields. For example, if the prefix is set to `ip_`, output fields will be named `ip_city ip_country`, etc.
- **Lang**: Specifies the language for data retrieval. Defaults to `en` for English. Supports Brazilian Portuguese (pt-BR), English (en), French (fr), German (de), Japanese (ja), Russian (ru), Simplified Chinese (zh-CN), and Spanish (es).
- **LookupTable**: The lookup filename that contains the database. Do not add the `.mmdb` file extension. For example, a filename of `GeoLite2-city.mmdb` is entered as `GeoLite2-city`.
- **IPField**: The field name with an IP address. Defaults to `ip`.

Examples

The runnable examples below require you to first acquire and upload a compatible `.mmdb` file, as outlined above in Prerequisites.

- Lookup geolocation data on the `dstaddr` field:

```
dataset="cribl_search_sample" dataSource=*vpc* | limit 1000  | ip-lookup geocity
```

Copy | Run in Cribl Search

- Lookup latitude and longitude data on the `dstaddr` field:

```
dataset="cribl_search_sample" dataSource=*vpc* | limit 1000  | ip-lookup output=
```

Copy | Run in Cribl Search

- Lookup geolocation data on the `ip` field:

```
dataset=myDataset
| ip-lookup 'GeoLite2-City'
```

Copy

- Lookup geolocation data on the `my_ip` field:

```
dataset=myDataset
| ip-lookup 'GeoLite2-City' on my_ip
```

Copy

- Lookup geolocation data on the `ip_address` field and return only the prefixed `ip_lat` and `ip_lon` fields:

```
dataset=myDataset
| ip-lookup output=lat,lon prefix=ip_ 'GeoLite2-City' on ip_address
```

Copy

- Lookup geolocation data on the `ip_address` field and return only the `city` and `region` fields in Spanish:

```
dataset=myDataset
| ip-lookup output=city,region lang=es 'GeoIP2-City' on ip_address
```

Copy

14.2.2.8. Join

The `join` operator merges events from two different data scopes.

You can merge data coming from different Datasets and Dataset Providers, and then process the output for further analysis.

Syntax

Using a `let` statement:

```
let RightScopeName = RightScope;

LeftScope
  | join [ JoinOptions ] RightScopeName on JoinConditions
```

Copy

Using an inline subquery:

```
LeftScope
  | join [ JoinOptions ] (
    RightScope
    )
    on JoinConditions
```

Copy

Arguments

- **RightScopeName**: The name for the **RightScope**. Spaces ( ) are not allowed.
- **RightScope**: The data on the right-hand side of the join operation. Needs to be assigned a name, using the let statement. Can be a single value, an expression, or an entire query, for example: `dataset="cribl_internal_logs" | limit 1000`.
- **LeftScope**: The data on the left-hand side of the join operation. Can be a single value, an expression, or an entire query.
- **JoinOptions**: The join operation's optional settings. Syntax: `option1=value1[, option2=value2, ...]`. The following options are available:

- `kind=String`: The type of join to perform. Can be `inner`, `innerunique`, `leftanti`, or `leftouter`. Default: `inner`.
- `overwrite=Bool`: Applies to fields with the same name on both **LeftScope** and **RightScope**. If set to `true`, this operator uses the values of the **RightScope** fields. If `false`, it uses the values of the **LeftScope** fields. Default: `false`.
- `caseInsensitive=Bool`: If `true`, the join operation is case-insensitive. Default: `false`.

- **JoinConditions**: The conditions on which the events are merged. Separate multiple conditions with a comma (`,`). Use the following syntax:
  - `FieldName`, if the fields you want to match have the same name in both Datasets.
  - `$left.LeftFieldName == $right.RightFieldName`, if you want to match fields that have different names.

Rules

The **RightScope** must:

- Either be assigned a name, using a let statement.
- Or be an inline subquery.

The join operation includes the first 50,000 events of the **RightScope**. The remaining events are ignored.

Types of Joins

By default, Cribl Search performs an **inner** join, which returns the following:

Scope	What's included in the output
LeftScope	Events that match the join conditions, including the matching keys
RightScope	Events that match the join conditions, including the matching keys

To perform an **innerunique** join, use the `kind=innerunique` setting, which returns the following:

Scope	What's included in the output
LeftScope	Unique events that match the join conditions, including the matching keys
RightScope	Unique events that match the join conditions, including the matching keys

To perform a **leftanti** join, use the `kind=leftanti` setting, which returns the following:

Scope	What's included in the output
LeftScope	Events that don't match the join conditions
RightScope	No events

To perform a **leftouter** join, use the `kind=leftouter` setting, which returns the following:

Scope	What's included in the output
LeftScope	All events
RightScope	Events that match the join conditions, including the matching keys

Examples

Using an inline subquery, join internal Cribl logs related to HTTP requests with a Dataset containing HTTP status codes.

```
// LeftScope
dataset="cribl_internal_logs" method status
 | where isnotnull(status)
 | join kind=leftouter (
    // RightScope (inline subquery)
    cribl dataset=$vt_dummy event < 4
     | extend x =
            case(event == 0, dynamic({"status": 200, "text": 'OK'}),
                 event == 1, dynamic({"status": 308, "text": 'Redirect'}),
                 event == 2, dynamic({"status": 404, "text": 'Not found'}),
                             dynamic({"status": 500, "text": 'Internal Error'}))
     | project statusNum=x.status, statusText=x.text
 ) on $left.status == $right.statusNum
```

Copy | Run in Cribl Search

Join two scopes of data, based on a single namesake field (`status`). Returns only those `LeftScope` events that have `status`. Those events are also enriched with the `status` fields from the `RightScope`.

```
// RightScope
let codeMap = dataset=$vt_dummy event < 4
 | extend x =
   case(event == 0, dynamic({"status": 200, "text": 'OK'}),
        event == 1, dynamic({"status": 308, "text": 'Redirect'}),
        event == 2, dynamic({"status": 404, "text": 'Not found'}),
                    dynamic({"status": 500, "text": 'Internal Error'}))
 | project status=x.status, statusText=x.text;

dataset="cribl_internal_logs" method status
 | where isnotnull(status) // LeftScope
 | join kind=leftouter codeMap on status
```

Copy Run in Cribl Search

Show blocklisted IPs in VPC flow logs and sensitive ports their network requests are accessing.

```
// first RightScope (dummy list of blocklisted IPs)
let pretendBlocklistedIps = dataset="cribl_search_sample" dataSource="vpcflowlogs"
 | limit 10
 | distinct srcaddr
 | project blocklistedIp=srcaddr;

// second RightScope
let servicePortsToWatch = dataset="cribl_lookups" lookup_table="service_names_port_nu
 | project port_number, service_name;

// LeftScope
dataset="cribl_search_sample" dataSource="vpcflowlogs"
 | limit 1000
 | join pretendBlocklistedIps on $left.srcaddr == $right.blocklistedIp
 | join servicePortsToWatch on $left.dstport == $right.port_number;
```

Copy Run in Cribl Search

Perform a join with the `overwrite` option set to `true`. Returns only those `LeftScope` events that have the `name` field, but the `RightScope` `name` values overwrite the `LeftScope` `name` values.

```
let RightScope = dataset=$vt_dummy event < 10
 | extend name=strcat('NameFromRightScope', event);

dataset=$vt_dummy event < 10
 | extend name=strcat('NameFromLeftScope', event) // LeftScope
 | join overwrite=true RightScope on event;
```

Copy Run in Cribl Search

Create a code map for different event statuses and then join it with another Dataset to produce a distinct list of methods along with their corresponding status codes and descriptive texts.

```
let codeMap = dataset=$vt_dummy event < 4
 | extend x =
   case(event == 0, dynamic({"status": 200, "text": 'OK'}),
        event == 1, dynamic({"status": 308, "text": 'Redirect'}),
        event == 2, dynamic({"status": 404, "text": 'Not found'}),
                    dynamic({"status": 500, "text": 'Internal Error'}))
 | project status=x.status, statusText=x.text;
```

14.2.2.9. Lookup

The `lookup` operator retrieves fields from a lookup through a first-match lookup process. It returns all rows of the table by default, incorporating any additional fields from the lookups wherever there is a match.



To enrich events with IP address data, use the `ip-lookup` operator.

Syntax

```
Scope | lookup [ output=OutputFields[, ...] [ defaultVal=Default ]]
               [ ignoreCase=Case ]
               [ matchMode=Mode [ matchType=Type ]]
               LookupTable on Conditions[, ...]
```

Copy

Arguments

The arguments are case-insensitive.

- **Scope**: The events to search.
- **OutputFields**: Field(s) to add from the lookup after matching. Defaults to **all** if not specified.
- **Default**: Assigns a default value to **OutputFields** when no value is present. Ignored if `output` is not defined.
- **Case**: Matching ignores case by default; set as `true`. Accepts boolean values - `yes`, `true`, `t`, `1` or `no`, `false`, `f`, `0`.
- **Mode**: Set to the matching logic of the lookup field(s). Supports `exact`, `cidr`, and `regex`. Defaults to `exact`. For example, if the lookup field contains a regular expression you'd use `regex`.
- **Type**: How to resolve multiple matches for `cidr` and `regex` modes. Defaults to `first`.
  - `first` returns the first matching entry.
  - `specific` scans all entries for the most specific match.
  - `all` returns all matches in the output, as arrays.
- **LookupTable**: The lookup filename, with or without the extension (you can enter `foo.csv` as `foo`). If the filename contains spaces, surround it with quotes (enter `foo bar.csv` as `"foo bar"`, `'foo bar'`, or `['foo bar']`).
- **Conditions**: Field(s) to look for in the lookup. There are three supported syntax variations:

- Looking in the lookup for the **exact** field name as it appears in events. Syntax: `CommonFieldName`.
- Single mapping between the event field and the lookup field name. Syntax: `EventFieldName = lookupFieldName`.
- A join condition that specifies how to combine the data from the two tables. Syntax: `$left.eventFieldName == $right.lookupFieldName` where the event is referenced as `$left` and the lookup as `$right`. You can have `$left` and `$right` on either side of the expression.

Examples

Look for a common field in the events and the `service_names_port_numbers.csv` lookup file.

```
dataset="cribl_search_sample"
 | limit 100
 | lookup service_names_port_numbers on commonField
```

Copy Run in Cribl Search

Map an event field (`dstport`) to a lookup field (`port_number`).

```
dataset="cribl_search_sample"
 | limit 100
 | lookup service_names_port_numbers on dstport=port_number
```

Copy Run in Cribl Search

Look for a common field, a mapped field, and use a join condition.

```
dataset="cribl_search_sample"
 | limit 100
 | lookup service_names_port_numbers on commonField, eventField1=lookupField1, $left.
```

Copy Run in Cribl Search

Look up an IP address range, using CIDR notation.

```
dataset="cribl_search_sample"
 | limit 100
 | lookup matchMode='cidr' matchType='all' service_names_port_numbers on $left.hostip
```

Copy Run in Cribl Search

Match using a regular expression.

```
dataset="cribl_search_sample"
 | limit 100
 | lookup matchMode='regex' matchType='all' service_names_port_numbers on eventfield=
```

Copy Run in Cribl Search

Create a lookup to use in the next example. This search won't display any results, but it creates a lookup file named `mymethods.csv`.

```
dataset=$vt_dummy event<600
 | extend _time=_time-rand(600), method=iif(event%2>0, "GET", "POST")
 | summarize cnt=count() by method
 | export description="Table with http methods count" to lookup mymethods
```

Copy Run in Cribl Search

Enrich events with a field `cnt` that comes from the `mymethods.csv` lookup file created in the example above.

```
dataset=$vt_dummy event<100
 | extend method=split("GET,POST", ",")
 | mv-expand method
 | lookup mymethods on method
```

Copy Run in Cribl Search

Use a lookup that's part of a Pack:

```
dataset=myDataset
 | lookup pack(myPack).LookupTable on commonField
```

Copy

14.2.2.10. Mv-Expand

Expand an array or object within an event into multiple events, where each of the generated events contains a single value of the original array or object. If you're curious, mv stands for multiple value.

Syntax

- `Scope | mv-expand [ bagexpansion=ExpansionMode ] [ with_itemindex=IndexFieldName ] FieldName [, FieldName... ] [ limit Rowlimit ]`
- `Scope | mv-expand [ bagexpansion=ExpansionMode ] [ Name=NewName ] ArrayExpression [, [ Name=NewName ] ArrayExpression... ] [ limit Rowlimit ]`

Arguments

Name	Type	Required	Description
ExpansionMode	string	No	`bag` (default) expands into single-entry property bags `array` expands into two-element `[key,value]` array structures, allowing uniform access to keys and values.
FieldName, **ArrayExpression**	string	Yes	A field reference, or a scalar expression with a value of type `dynamic` that holds an array or a property bag. The individual top-level elements of the array or property bag get expanded into multiple events. When **ArrayExpression** is used and **NewName** doesn't equal any input field name, the expanded value is extended into a new field in the output. Otherwise, the existing **FieldName** is replaced. Wildcards are not supported.
IndexFieldName	string	No	If `with_itemindex` is specified, the output includes another field named **IndexFieldName** that contains the index starting at 0 of the item in the original expanded collection.
NewName	string	No	A name for the new field.
RowLimit	int	No	The maximum number of rows generated from each original row. The default is `9007199254740991`.

Returns

For each event in the input, the operator returns zero, one, or many events in the output, as determined in the following way:

1. Input fields that aren't expanded appear in the output with their original value. If a single input event is expanded into multiple output events, the value is duplicated to all events.
2. For each **FieldName** or **ArrayExpression** that is expanded, the number of output events is determined for each value based on the **ExpansionMode**. For each input event, the maximum number of output events is calculated. All arrays or property bags are expanded in parallel. so that missing values (if any) are replaced by null values. Elements are expanded into rows in the order that they appear in the original array/bag.
3. If the dynamic value is null, then a single event is produced for that value (null). If the dynamic value is an empty array or property bag, no event is produced for that value. Otherwise, as many events are produced as there are elements in the dynamic value.



The expanded fields are of type `dynamic`.

Examples

Single field - expansion

```
dataset=myDataset
| mv-expand b
```

Copy

Single field - bag expansion to key-value pairs

A simple bag expansion to key-value pairs:

```
dataset=myDataset
| mv-expand bagexpansion=array b
| extend key = b[0], val=b[1]
```

Copy

Cartesian product of two fields

If you want to get a Cartesian product of expanding two fields, expand one after the other:

```
dataset=myDataset
| mv-expand b
| mv-expand c
```

Copy

Using with_itemindex

Expansion of an array with `with_itemindex`:

```
| extend x=dynamic([17, 3]), y=dynamic({'foo': 'bar', 'cribl': 'search'})
| mv-expand bagexpansion=array with_itemindex=i x, z=y limit 3
```

Copy

Filter a nested array

Expand a nested array and filter by its values:

```
dataset="myDataset"
| mv-expand events
| mv-expand events.parameters
| where events.parameters.name = 'suspicious' and events.parameters.boolValue == true
```

Copy

Create an event for each of the values of field `method`. You should see 200 events total.

```
dataset=$vt_dummy event<100
| extend method=split("GET,POST", ",")
| mv-expand method
```

Copy Run in Cribl Search

14.2.2.11. Mv-Pull

Pull key-value pairs from array objects into a top-level event, or into a dedicated object/bag. If you're curious, mv stands for multiple value.

Syntax

```
<scope> | mv-pull [key=<nameOfKeyFieldInData>]  [value=<nameOfValueFieldInData>] [del
```

Copy

Arguments

Name	Type	Required	Description
delete_original	boolean	No	If set to `true`, deletes the source array in the event after pulling up all key-value pairs. With the `false` default, the source array is unchanged.
nameOfKeyFieldInData	string	No	Name (or column path) of the key in each array element. Defaults to literal `Name`.
nameOfValueFieldInData	string	No	Name (or column path) of the value in each array element. Defaults to literal `Value`.
nameOrPathOfFieldToArray	string	Yes	Name (or column path) of the field that contains the array of objects from which to pull key-value pairs.
targetFieldName	string	No	Name or column path of an object/bag to contain the pulled fields. Specify this to group all pulled fields into one object. If omitted, the output will be separate fields at the event's root level.

Returns

If **targetFieldName** is specified, returns a corresponding object/bag containing all the extracted key-value pairs as fields. Otherwise, returns the extracted key-value pairs as separate top-level fields.

Examples

This example pulls a simple array's elements into a single event. Uncomment the indicated line to display the elements within that event:

```
print eventData=dynamic( { "eventArray": [ { "Name": "TotalBytes", "Value": 536 }, {
| mv-pull eventData.eventArray
//| project-away eventData // uncomment this line to see the results by themselves
| extend  _time=now()
| render event
```

Copy | Run in Cribl Search

A query with this argument would pull key-value pairs from an array named `eventData` into separate top-level fields in the target event:

```
... | mv-pull eventData | ...
```

Copy

The output might take the following form (with fictitious data):

```
{
  _time: 1724241414.121,
  dataset: "metrics-store",
  eventData: [
    { Name: "numBytesRead", Value: 1234 },
    { Name: "numBytesWrite", Value: 200 },
    { Name: "numRequests", Value: 42 },
  ],
  numBytesRead: 1234,
  numBytesWrite: 200,
  numRequests: 42,
}
```

Copy

Here is the same query with additional arguments, targeting an array whose key-value pairs have unusual naming:

```
... | mv-pull key="n" value="v" delete_original=true otherEventData as itsMyBag ...
```

Copy

The output would instead have this format:

```
{
  _time: 1724241414.121,
  dataset: "metrics-store",
  itsMyBag: { numBytesRead: 1234, numBytesWrite: 200, numRequests: 42 }
}
```

Copy

14.2.2.12. Pivot

The `pivot` operator turns each unique field **value** into a field **name** (rendered as a column header).

Syntax

```
Scope | pivot DataFields over ColumnFields [by LabelField]
```

Arguments

- **Scope**: The events to search.
- **DataFields**: One or more fields to populate the cells of the output table. Wildcards are not supported for field names.
- **ColumnFields**: One or more fields whose unique **values** become column headers (field **names**).
- **LabelField**: An additional field added to the left-most column of the output table, used to label the rows (events). If not specified, defaults to `_time`.

Nested and Bracketed Field Names

You can specify nested fields by using dot notation (`foo.bar`). Cribl Search flattens each nested path to a top-level field, replacing every period with an underscore, so `foo.bar` becomes `foo_bar` and `my.field` becomes `my_field`.

The flattened name is what appears in your results. If you pivot `by my.field`, the label column is named `my_field`. If you pivot more than one nested Data Field, the flattened name also becomes the column name prefix.

Cribl Search doesn't flatten bracketed field names, such as `["a.b"]`. Those keep their literal name. For the best performance on lakehouse engines and v2 Datasets, use `project-rename` to give those fields a flat name before you pivot.

Aggregation Behavior

Each cell of the output table holds a single value, so `pivot` behaves as an aggregation. Cribl recommends running `pivot` after a `summarize` operation, so that you control how Cribl Search collapses multiple values into one cell.

If you don't provide a matching `summarize`, Cribl Search automatically applies `take_any` to each **DataFields** entry before pivoting, grouped by the **LabelField** and all **ColumnFields**. This prevents duplicate rows for the same cell. The following two searches are equivalent:

```
pivot dataField over column by label
```

Copy

```
summarize dataField=take_any(dataField) by column, label
| pivot dataField over column by label
```

Copy

Because `take_any` returns an arbitrary value, results are non-deterministic when more than one event maps to the same cell. Write your own `summarize` when you need predictable cell values:

```
summarize total=sum(amount) by column, label
| pivot total over column by label
```

Copy

When you omit the **LabelField**, group by `_time` instead, because **LabelField** defaults to `_time`:

```
summarize total=sum(amount) by _time, column
| pivot total over column
```

Copy

When Cribl Search Skips the Automatic Aggregation

Cribl Search skips `take_any` only when a `summarize` immediately precedes the `pivot` and groups by exactly the **LabelField** and all **ColumnFields**. The order of the group-by fields doesn't matter. Cribl Search still applies `take_any` when:

- Another operator sits between the `summarize` and the `pivot`, such as `extend`.
- The `summarize` group-by omits a **ColumnFields** entry.
- The `summarize` group-by omits the **LabelField**.
- The `summarize` group-by includes fields beyond the **LabelField** and **ColumnFields**.

That last case still needs the automatic aggregation, because a broader group-by can produce more than one row per cell.

When you pre-aggregate nested fields, reference the flattened names in the `pivot`, because `summarize` flattens nested paths the same way:

```
summarize sum(foo.bar) by my.field, x.z
| pivot sum_foo_bar over x_z by my_field
```

Copy

Results

For each unique **value(s)** combination of the **ColumnFields**, `pivot` returns a column whose:

- Column header (field name) is taken from that **ColumnFields** value(s).
- Column cells (field values) are populated by the **DataFields**, calculated separately for each returned event.

Column Names

Cribl Search builds each column name from the **ColumnFields** values, and from the **DataFields** names when you pivot more than one Data Field:

Pivot	Column name	Example
One **DataFields** entry, one **ColumnFields** entry	The **ColumnFields** value	`Red`
One **DataFields** entry, several **ColumnFields** entries	The **ColumnFields** values, joined by a comma and a space	`Red, yes`
Several **DataFields** entries	The **DataFields** name, a colon and a space, then the **ColumnFields** values	`dataField1: Red, yes`

A `null` **ColumnFields** value appears in the column name as the literal string `null`.

Cells Without Data

When a combination of **LabelField** and **ColumnFields** values matches no events, the resulting cell depends on where the search runs:

- Searches over v1 Datasets populate the cell with `0`.
- Searches over v2 Datasets, and searches that run on a lakehouse engine, leave the cell blank.

Don't rely on `0` to mean "no data" if you might move a search between v1 and v2 Datasets.

Examples

Turn each unique value of the `colLabel` field (`Red`, `Blue`, and `Green`) into a column, and populate the columns' cells with random 1-100 numbers:

```
dataset=$vt_dummy event < 10
| extend dataField = floor(rand() * 100),
         colLabel = case(event % 3 == 0, 'Red', event % 3 == 1, 'Blue', 'Green')
| pivot dataField over colLabel by event
```

Copy | Run in Cribl Search

Perform a pivot on two fields, `colLabel1` and `colLabel2`. Because this search pivots two Data Fields, Cribl Search prefixes each column name with the Data Field name, producing columns such as `dataField1: Red, yes`:

```
dataset=$vt_dummy event < 10
| extend dataField1 = floor(rand() * 100),
         dataField2 = 200 - dataField1,
         colLabel1 = case(event % 3 == 0, 'Red', event % 3 == 1, 'Blue', 'Green'),
         colLabel2 = iif(event % 2 == 0, 'yes', 'no')
| pivot dataField1, dataField2 over colLabel1, colLabel2 by event
```

Copy | Run in Cribl Search

14.2.2.13. SEND

The `send` operator forwards search results to Cribl Stream, or to compatible endpoints.

Usage

By default, `send` forwards search results to a Cribl HTTP Source in a distributed Cribl Stream deployment. There, you can transform, route, and relay the results in multiple ways.

When you target a Cribl-managed Stream Worker Group within the same Workspace over Cribl HTTP, you incur no additional ingest charges. You consume credits only for the CPU time that `send` uses in Cribl Search.



The `send` operator can't target Cribl-managed Worker Groups in a Workspace that has enabled an Access Control List (ACL).

Permissions

Search **Editors** and Search **Admins** can send events to any Cribl-managed Stream Worker Group in the same Organization.

Search **Admins** can also send events to any endpoint that accepts a POST request and NDJSON content. (Ingest charges might apply outside the Cribl HTTP scenario outlined above.)

Here's a full breakdown of where different Search Member Types can send events:

Search Member Type	Default Stream Worker Group	Named Stream Worker Group	Custom URL
Search User			
Search Editor			
Search Admin			
Organization Admin			
Organization Owner			

Rules

- Aggregate results are sent once the search completes, so you won't see results until then.

- By default, events are sent to the Cribl HTTP Source in the same Cribl.Cloud Organization as your Cribl Search instance.
- Also use a Cribl HTTP Source to receive data on hybrid Worker Groups.
- Use the `centralize` operator when sending results from Edge Worker Nodes that lack access to the internet or to your Cribl.Cloud Organization.
- The `group` parameter is only for Cribl-managed Worker Groups in Cribl.Cloud, and cannot be used together with the `URL` argument.
- If any events are dropped, the search logs display an appropriate error message.
- The `send` operator sets the `Content-Type: application/x-ndjson` header on POST requests.

Syntax

```
... | send [ tee=TeeBoolean ] [ group=WorkerGroup | "URL" ]
```

Copy

Arguments

- **TeeBoolean**: Defaults to `false`, where search results are not shown in Cribl Search. Instead, you get an event with the URL, the status, and the number of bytes and events sent or dropped. When set to `true`, the search results are displayed, and no stats are provided. For example, `tee=true`.
- **WorkerGroup**: The Cribl Stream Worker Group to send data to. The default value is literally `default`. For example, `group=default`.
- **URL**: Your domain for inbound data, with the appropriate port. Defaults to your Cribl.Cloud ingest address and port `10200`, the default port for the Cribl HTTP Source. The general format is: `https://<groupName>.<workspaceName>.<organizationId>.cribl.cloud:10200`

  An example with the most typical Worker Group and Workspace names, and with a fictitious Organization name: `https://default.main.goat-farm.cribl.cloud:10200`

To check the ingest address for Cribl-managed Groups: From your Organization's top bar, select **Products** > **Cribl**. From the resulting sidebar, select **Data Sources**, then select the target **Group**. Under **Sources Enabled by Default**, find the `in_cribl_http` entry.

For a hybrid Group running on a host that you manage, the ingest address will typically be configured through your load balancer.

Examples

- Send events to the `default` Worker Group:

```
dataset=myDataset
| send
```

Copy

- Send up to 100 events and display the results:

```
dataset=myDataset
| limit 100
| send tee=true
```

Copy

- Send events to a Worker Group named Goat:

```
dataset=myDataset
| send group=goat
```

Copy

- Send events to a hybrid Worker Group:

```
dataset=myDataset
| send "https://in.your-tenant.com:10200"
```

Copy

- Send aggregate results by specifying the URL to your Cribl Stream internal Cribl HTTP Source:

```
dataset=myDataset
| summarize count() by action
| send "https://in.main-default-domain.cribl.cloud:10200"
```

Copy

- Send results to the Cribl.Cloud Stream default Worker Group:

```
dataset=$vt_dummy event<10
| extend _raw=iif(event%2>0, "This is a test event", "This is another event")
| send
```

Copy Run in Cribl Search

14.2.2.14. Top-Hitters

The `top-hitters` operator counts distinct value combinations and returns the most frequent combinations in descending order. It provides valuable insights into the most popular and impactful data combinations within your input Dataset.

This operator is conceptually equivalent to using the `summarize` operator with `count` and `top`:

```
Scope | summarize C=count() by ValueExpression | top NumberOfValues by C desc
```

Copy

Syntax

```
Scope | top-hitters NumberOfValues of ValueExpression [ by SummingExpression ]
```

Copy

Arguments

- **Scope**: The events to search.
- **NumberOfValues**: The number of distinct values of **ValueExpression**.
- **ValueExpression**: An expression or list of fields that operate over the **Scope** whose distinct values are returned. Supports single expressions like `x / 42` or `abs(status)` as well as more complex expressions such as `top-hitters 10 of method, status [by SummingExpression]`.
- **SummingExpression**: If specified, a numeric expression over the **Scope** whose sum per distinct value of **ValueExpression** establishes which values to emit. If not specified, the count of each distinct value of **ValueExpression** is used instead.

Examples

- Return the top 3 distinct `status` values.

```
dataset="cribl_search_sample" status="*"
| limit 1000
| top-hitters 3 of status
```

Copy Run in Cribl Search

- Sum `bytes` and returns the top 2 `host` values.

```
dataset="cribl_search_sample" status="*" host="*"
| limit 1000
| top-hitters 3 of host by bytes
```

Copy Run in Cribl Search

- Sum `bytes`, and return the top 10 distinct combinations of `clientip` and `useragent` values based on the `bytes` field.

```
dataset="cribl_search_sample" clientip="*" useragent="*"
| limit 1000
| top-hitters 5 of clientip, useragent by bytes
```

Copy Run in Cribl Search

14.2.2.15. Union

The `union` operator appends one set of results to another.

Results are automatically sorted by time in ascending order if a time field is present. Otherwise, the order will be random.

Syntax

Using a `let` statement:

```
let SubqueryName = Subquery;

MainQuery | union SubqueryName
```

Copy

Using an inline subquery:

```
MainQuery | union (
  Subquery
  )
```

Copy

Arguments

- **SubqueryName**: The name for the **Subquery** expression. Spaces ( ) are not allowed.
- **Subquery**: The data to append to the **MainQuery**.
- **MainQuery**: The data to which the results of **Subquery** are appended.

Rules

The union operation includes the first 50,000 events of **SubqueryName**. The remaining events are ignored.

Examples

Combine two sets of data.

```
let dataset1 = range x from 1 to 5 step 1 | extend dataField = x * 2;
range y from 6 to 10 step 1 | extend dataField = y * 3 | union dataset1;
```

Copy | Run in Cribl Search

Extend the results of three searches on the `$vt_dummy` Dataset, each filtered with `event < 10`, and combine them using the `union` operator.

```
let stage1 = search in($vt_dummy) event<10 | extend foo=42;
let stage2 = search in($vt_dummy) event<10 | extend bar=24;
search in($vt_dummy) event<10 | extend baz=84 | union stage1, stage2;
```

Copy | Run in Cribl Search

Append data, using an inline subquery.

```
// main query
print x = 1 | union (
  // inline subquery
  print y = 1 | extend y = 2
  )
```

Copy

14.2.3. Display Operators

A list of display operators supported by Cribl Search.

Display operators control how data is presented in the output, allowing formatting, sorting, or visualizing results for better readability.

Name	Description
`limit` (`take`)	Limits the number of events.
`order` (`sort`)	Arranges events into order by one or more fields.
`print`	Outputs expression results.
`project`	Keeps only the fields specified, and can also rename fields and insert new computed fields.
`project-away`	Excludes specific fields from the results..
`range`	Generates a series of events.
`render`	Enforces a specific visualization of the search results.
`top`	Returns the first N events sorted by the specified fields.

14.2.3.1. Limit

The `limit` operator returns up to the specified number of events (or fewer, if fewer events match the query). You can use this operator to size your result sets, and to control resource usage.

Alias: `take` (`limit` and `take` are synonyms).

Syntax

```
Scope | limit Integer
```

Copy

Arguments

- **Scope**: The events to search.
- **Integer**: A positive integer.

Usage

Bear in mind the following execution details:

- `limit` doesn't guarantee any consistency in its results when executing multiple times, even if the Dataset hasn't changed.
- In interactive searches (from the query box), query execution with `limit` displays previews of the results. These previews reflect only a sample of events, up to the `limit` threshold.
- Scheduled and programmatic searches omit these previews.
- In Lakehouse searches, `limit` constrains the number of output rows, but the query continues iterating over the whole population of events. Here, Cribl Search will true up aggregations as the query completes.
- Outside of Lakehouse searches, the `limit` operator's argument sets a hard threshold. Query execution will end when Cribl Search finds a matching number of events, or can be canceled during a preview. So aggregations will be accurate for the `limit` sample, but not necessarily for the overall population of events.

Example

```
dataset=myDataset
| limit 1000
```

Copy

Return only 42 events.

```
dataset=$vt_dummy event<100
| extend parity=iif(event%2==0, 'even', 'odd')
| limit 42
```

Copy Run in Cribl Search

14.2.3.2. Order

The `order` operator arranges events into order by one or more fields.

Alias: `sort` (`sort` and `order` are synonyms.)

For grouped results from `summarize`, `eventstats`, or `timestats`, you can often sort by adding direction and null placement on each `by` field instead of using `order` here. See Group-by Sort Order.

Syntax

```
Scope | order [ topN=MaxNoOfOutputEvents ] [ maxEvents=MaxNoOfInputEvents ] by Field [ asc | desc ] [ nulls first | nulls last ] [, ...]
```

Arguments

Name	Type	Required	Description
Scope	String	Yes	The events to search.
MaxNoOfOutputEvents	Int	No	Maximum number of events to produce. The output is limited to `10000` events, so entering a higher **MaxNoOfOutputEvents** value effectively sets a limit of `10000`.
MaxNoOfInputEvents	Int	No	Maximum number of events to handle and arrange. Usually, this value is already determined by the `limit` operator used earlier in the query, but you can also set it explicitly here.
Field	String	Yes	Field to sort by. The type of the field values must be numeric, date, time, or string.
`asc` or `desc`	String	No	`asc` sorts into ascending order, low to high. Default is `desc`, high to low. For more details, see Sorting Rules.
`nulls first` or `nulls last`	String	No	`nulls first` will place the null values at the beginning and `nulls last` will place the null values at the end. Default for `asc` is `nulls first`. Default for `desc` is `nulls last`.

Sorting Rules

- Numeric values appear before other data types. An exception to that may be `null`, whose behavior depends on the `nulls first/nulls last` setting above.

- Numeric strings are converted to numbers when sorted. For example, `"100"` and `"5"` are compared as `100` and `5`.
- By default: for ascending order, `null`s appear first, and for descending order, `null`s appear last. You can change this with the `nulls first/nulls last` setting above.

Example

All events with a specific `ClientRequestId`, ordered by their `Timestamp`.

```
dataset=myDataset
| where ClientRequestId == "5a848f70-9996-eb17-15ed-21b8eb94bf0e"
| order by Timestamp asc
```

Copy

Order results by the field `event` in descending order.

```
dataset=$vt_dummy event<100
| extend parity=iif(event%2==0, 'even', 'odd')
| order by event desc
```

Copy Run in Cribl Search

14.2.3.3. Print

The `print` operator evaluates one or more scalar expressions, and returns the results as a single row.

Use `print` to verify an expression before you include it in a larger query.



To produce sample events, use the `$vt_dummy` virtual table.

Syntax

```
print [FieldName =] Expression [, ...]
```

Arguments

- **FieldName**: The name to assign to the output field. If omitted, the name is generated from the corresponding **Expression**.
- **Expression**: The scalar expression to evaluate. A scalar expression is any combination of values and operators that evaluates to a single value. For example, `1 + 2` is a scalar expression that evaluates to `3`.

Results

Returns a single row with as many columns as there are **Expression** arguments.

Examples

- Check a calculation result.

```
// returns 6
print 1 + 2 + 3
```

Copy

- Check a string concatenation.

```
// returns "Hello, World!"
print strcat("Hello", ", ", "World!")
```

Copy

- Check multiple expressions, displaying the results as a single event.

```
// returns 200, "56", and 1692736230.271
print ["Check result"] = iif(false, 100 , 200), Check = substring("456", 2), ago
```

Copy

- Check an expression, displaying the results as multiple events.

```
// returns two events with "Word" and "Index" fields:
// Word: "foo", Index: 0
// Word: "bar", Index: 1
print Word=split("foo bar", " ")
| mv-expand with_itemindex=Index Word
```

Copy

- Print a single event with field `foo` set to 42.

```
print foo=42
```

Copy Run in Cribl Search

14.2.3.4. Project

The `project` operator keeps only the fields specified, and can also rename fields and insert new computed fields.

The order of the arguments determines the order of the fields in the result.

See also `extend` and `print`.



Unlike `project-rename`, `project` drops all fields that were not specified.

Syntax

- `Scope | project FieldName [= Expression] [, ...]`
- `Scope | project [FieldName | (FieldName[,]) =] Expression [, ...]`

Arguments

- **Scope**: The events to search.
- **FieldName**: Optional if there's an **Expression**. The name of the field to appear in the output. If omitted, the name will be generated.
    - If there is no **Expression**, then **FieldName** is mandatory and a field of that name must appear in the input.
    - If **Expression** returns more than one field, a list of field names can be specified in parentheses. In this case **Expression**'s output fields will be given the specified names, dropping all the rest of the output fields, if there are any. If a list of the field names is not specified, all **Expression**'s output fields with generated names will be added to the output.
- **Expression**: Optional if there's a **FieldName**. A scalar expression referencing the input fields.



You can return a new calculated field with the same name as an existing field in the input.

Results

Returns a table that has the fields named as arguments, and as many rows as the input table.

If an **Expression** references a field that an event doesn't contain, `project` returns `null` for that field. The field stays in the output, so every event has the same set of fields.

Examples

Show only two fields, `cost` and `price`.

```
dataset=myDataset
| project cost=price*quantity, price
```

Copy

The following example shows several kinds of manipulations that can be done using the `project` operator. The Dataset has three fields of type `int`: `A`, `B`, and `C`.

```
dataset=myDataset
| project
    X=C,                        // Rename field C to X
    A=2*B,                      // Calculate a new field A from the old B
    C=strcat("-",tostring(C)), // Calculate a new field C from the old C
    B=2*B                       // Calculate a new field B from the old B
```

Copy

You can also use `project` with nested data, using dot notation. In the following example, two new fields (`user` and `query`) are created based on an existing nested field (`stats`).

```
dataset="cribl_internal_logs" message="search finished"
| project _time, user=stats.userDisplayName, query=stats.query // show only the `_tim
```

Copy Run in Cribl Search

Show only `_time`, `event`, and `parity` fields.

```
dataset=$vt_dummy event<100
| extend parity=iif(event%2==0, 'even', 'odd')
| project _time, event, parity
```

Copy Run in Cribl Search

Show `_time`, `event`, and `parity` fields and evaluate two new fields, `foo` and `bar`.

```
dataset=$vt_dummy event<100
| extend parity=iif(event%2==0, 'even', 'odd')
| project _time, event, parity, foo=42, bar=foo*2
```

Copy Run in Cribl Search

14.2.3.5. Project-Away

The `project-away` operator excludes specific fields from the results.

Syntax

```
Scope | project-away ColumnNameOrPattern [, ...]
```

Copy

Arguments

- **Scope**: The events to search.
- **ColumnNameOrPattern**: The name of the field or field wildcard-pattern to be removed from the results.
  - Wildcards `*` represent zero or more characters in a field name. For example, `Sta*`.
  - Wildcards are not supported in the middle of a field name and consecutive wildcards are not allowed. For example, `St*us` and `S**s` are invalid.

Results

A table with fields that were not named as arguments. Contains the same number of rows from the data piped to the operation.

Example

```
dataset=myDataset
| project-away price, quantity, zz*
```

Copy

Exclude all fields that start with the letter "p".

```
dataset=$vt_dummy event<100
| extend parity=iif(event%2==0, 'even', 'odd')
| project-away p*
```

Copy Run in Cribl Search

14.2.3.6. Project-Rename

The `project-rename` operator renames fields.



Unlike `project`, `project-rename` keeps all fields that were not specified.

Syntax

```
Scope | project-rename NewFieldName = ExistingFieldName [, ...]
```

Copy

Arguments

- **Scope**: The events to search.
- **NewFieldName**: The new field name.
- **ExistingFieldName**: The name of the existing field to rename.

Results

A table that has the fields in the same order as in an existing table, with its fields renamed.

Example

```
dataset=myDataset
| project-rename new_b=b, new_a=a
```

Copy

Rename the field `parity` to `oddEven`.

```
dataset=$vt_dummy event<100
| extend parity=iif(event%2==0, 'even', 'odd')
| project-rename oddEven=parity
```

Copy Run in Cribl Search

14.2.3.7. RANGE

The `range` operator generates a series of events, each containing a generated numeric field and a `_time` field. You can use this operator as syntactic sugar on the `$vt_dummy` virtual table, to generate a defined range of events with equally spaced values.



This is a data-generating operator, not a data-consuming operator.

Syntax

```
range <FieldName> from <Start> to <Stop> [step <Step>]
```

Copy

Arguments

Name	Type	Required	Description
FieldName	String	Yes	The name of the single column in the output table.
Start	Int, Long, Real, Datetime, or Timespan	Yes	The smallest value to generate.
Stop	Int, Long, Real, Datetime, or Timespan	Yes	The highest value to generate; or, if **Step** would generate a value exceeding this parameter, a bound on the highest value.
Step	Int, Long, Real, Datetime, or Timespan	No	The difference between two consecutive values in the output.

Results

A series of events, each containing a field called `<FieldName>`, whose values are: `<Start>`, `<Start>` + `<Step>`, ... up to and including `<Stop>`.

Examples

Generate 10 equally spaced events, numbered `1` to `10`:

```
range theField from 1 to 10
```

Copy | Run in Cribl Search

Generate five equally spaced events, numbered 1 to 9:

```
range theField from 1 to 10 step 2
```

Copy | Run in Cribl Search

Generate a series of hourly events, starting three days back:

```
range theField from ago(3d) to ago(2d) step 1h | project strftime(theField,'%Y-%m-%dT
```

Copy | Run in Cribl Search

Generate a week's worth of daily events:

```
range _time from ago(7d) to now() step 1d
```

Copy

Generate 10 event values from 10 to 100, incremented by 10:

```
range myField from 10 to 100 step 10
```

Copy

14.2.3.8. Render

The `render` operator enforces a specific visualization of the search results. It's useful when you want to override the default rendering of a query.

The `render` operator supports the following modes:

- `event` - renders the results as a list of events, under the **Events** tab.
- `table` - renders the results as a table, under the **Chart** tab.

Syntax

```
Scope | render RenderMode
```

Copy

Arguments

- **Scope**: The events to search.
- **RenderMode**: The rendering mode to use. Can be `event` or `table`.

Examples

```
dataset=myDataset
| render table
```

Copy

Render a table of enumerated fields.

```
dataset=$vt_dummy event<100
| extend parity=iif(event%2==0, 'even', 'odd')
| project event, parity
| render table
```

Copy Run in Cribl Search

14.2.3.9. Sort

The `sort` operator arranges events into order by one or more fields.

Alias: `order` (`order` and `sort` are synonyms.)

For grouped results from `summarize`, `eventstats`, or `timestats`, you can often sort by adding direction and null placement on each `by` field instead of using `sort` here. See Group-by sort order.

Syntax

```
Scope | sort [ topN=MaxNoOfOutputEvents ] [ maxEvents=MaxNoOfInputEvents ] by Field [ asc | desc ] [ nulls first | nulls last ] [, ...]
```

Arguments

Name	Type	Required	Description
Scope	String	Yes	The events to search.
MaxNoOfOutputEvents	Int	No	Maximum number of events to produce. The output is limited to `10000` events, so entering a higher **MaxNoOfOutputEvents** value effectively sets a limit of `10000`.
MaxNoOfInputEvents	Int	No	Maximum number of events to handle and arrange. Usually, this value is already determined by the `limit` operator used earlier in the query, but you can also set it explicitly here.
Field	String	Yes	Field to sort by. The type of the field values must be numeric, date, time, or string.
`asc` or `desc`	String	No	`asc` sorts into ascending order, low to high. Default is `desc`, high to low. For more details, see Sorting Rules.
`nulls first` or `nulls last`	String	No	`nulls first` will place the null values at the beginning and `nulls last` will place the null values at the end. Default for `asc` is `nulls first`. Default for `desc` is `nulls last`.

Sorting Rules

- Numeric values appear before other data types. An exception to that may be `null`, whose behavior depends on the `nulls first/nulls last` setting above.

- Numeric strings are converted to numbers when sorted. For example, `"100"` and `"5"` are compared as `100` and `5`.
- By default: for ascending order, `null`s appear first, and for descending order, `null`s appear last. You can change this with the `nulls first/nulls last` setting above.

Example

All events with a specific `ClientRequestId`, sorted by their `Timestamp`.

```
dataset=myDataset
| where ClientRequestId == "5a848f70-9996-eb17-15ed-21b8eb94bf0e"
| sort by Timestamp asc
```

Copy

Sort results by the field `event` in descending order.

```
dataset=$vt_dummy event<100
| extend parity=iif(event%2==0, 'even', 'odd')
| order by event desc
```

Copy Run in Cribl Search

14.2.3.10. Take

The `take` operator returns up to the specified number of events.

Alias: `limit` (`limit` and `take` are synonyms.)



`take` doesn't guarantee any consistency in its results when executing multiple times, even if the data set hasn't changed.

Syntax

```
Scope | take Integer
```

Copy

Arguments

- **Scope**: The events to search.
- **Integer**: A positive integer.

Example

```
dataset=myDataset
| take 1000
```

Copy

Return only 42 events.

```
dataset=$vt_dummy event<100
| extend parity=iif(event%2==0, 'even', 'odd')
| take 42
```

Copy Run in Cribl Search

14.2.3.11. Top

The `top` operator returns the first N events sorted by the specified fields.



`top 5 by name` is equivalent to the expression `sort by name | take 5` both from semantic and performance perspectives.

When sorting different data types, numeric values always appear first.

Syntax

```
Scope | top NumberOfRows by Expression [ asc | desc ] [ nulls first | nulls last ]
```

Copy

Arguments

Name	Type	Required	Description
Scope	Tabular	Yes	The events to search.
NumberOfRows	Int	Yes	The number of rows to return.
Expression	String	Yes	Scalar expression by which to sort. The type of the values must be numeric, date, time or string.
`asc` or `desc`	String	No	Controls whether the selection is from the “bottom” or “top” of the range. Default desc. Numeric values always appear before other data types.
`nulls first` or `nulls last`	String	No	Controls whether null values appear at the “bottom” or “top” of the range. Default for `asc` is `nulls first`. Default for `desc` is `nulls last`.

Examples

Show the top 3 events with the most errors.

```
dataset=myDataset
| top 3 by errorCount
```

Copy

Return the top 42 results sorted by the `event` field in descending order.

```
dataset=$vt_dummy event<100
| extend parity=iif(event%2==0, 'even', 'odd')
| top 42 by event desc
```

Copy Run in Cribl Search

14.2.4. Filter Operators

A list of filter operators supported by Cribl Search.

Filter operators exclude or include events based on specified conditions, allowing you to narrow down the dataset to relevant records.

Name	Description
`dedup` (`suppress`)	Filters out duplicate events.
`distinct`	Finds unique field values.
`search`	Finds events that contain the specified text.
`where`	Filters events based on the specified predicate.

14.2.4.1. Between

The `between` operator returns events that fall within an inclusive range of `numeric`, `datetime`, or `timespan` values. Use `between` when you want a compact, readable alternative to chained comparison expressions such as:

`expr >= left AND expr <= right.`

You'll typically use `between` with the `where` operator.

Syntax

```
betweenExpression: (BANG?) BETWEEN OPEN_PAREN leftRange RANGE rightRange CLOSE_PAREN;

leftRange: numericLiteral | stringLiteral | datetimeExpression;

rightRange: numericLiteral | stringLiteral | datetimeExpression | timespanLiteral;
```

Copy

Arguments

- **Scope**: The set of events being filtered, usually produced by a Dataset selection such as `dataset="cribl_search_sample"` or another upstream operator.
- **Expr**: A scalar expression to evaluate for each event. Supported types: `numeric`, `decimal`, `double`, `int`, `long`, `real`, `datetime`, or `timespan`.
- **LeftRange**: A scalar expression of the same type as Expr, specifying the inclusive lower bound of the range.
- **RightRange**: A scalar expression specifying the inclusive upper bound of the range. Supported types: Same type as Expr (`numeric`, `datetime`, or `timespan`), or `timespan` only when Expr and LeftRange are both datetime values (for example, `StartTime between (datetime(2025-01-01) .. 3d)`).
- **Bang (!)**: When present (as !between), inverts the condition so that events are kept only when Expr is outside the [LeftRange .. RightRange] interval.

Behavior

- **Inclusive bounds**: `Expr between (LeftRange .. RightRange)` is equivalent to `Expr >= LeftRange and Expr <= RightRange`. Events where **Expr** equals either endpoint are included in the results.

- **Supported types**:
  - Numeric: `int`, `long`, `real/double/decimal`
  - Temporal: `datetime` versus `datetime` ranges, `datetime` versus `datetime, timespan` ranges (for example, "start at this date, for 3 days").
- **Logical negation**: To exclude a range, wrap `between` in a `!` expression:
  `| where (Expr. !between (LeftRange .. RightRange))`

Examples

Numeric Range Filter

Filter data where `field` falls between 10 and 50 (inclusive):

```
dataset="$vt_dummy" field< 100
| where event between (10 .. 50)
```

Copy

Equivalent explicit comparison:

```
dataset="$vt_dummy" field< 100
| where event >= 10 and event <= 50
```

Copy

Datetime Range Filter

Return internal logs with `_time` in a specific date range:

```
dataset="cribl_internal_logs"
| where _time between (
    datetime(2025-01-01T00:00:00Z)
    ..
    datetime(2025-01-02T00:00:00Z)
)
```

Copy

Datetime Plus Timespan

Filter events starting on or after a given date and within a 3-day window:

```
dataset="cribl_internal_logs"
| where _time between (
    datetime(2025-01-01T00:00:00Z)
    ..
    3d
)
```

Copy

In this pattern:

- `_time` is datetime.
- The left bound is datetime.
- The right bound is a timespan (3d), which is allowed when both `_time` and the left bound are datetime values.

14.2.4.2. Dedup

The `dedup` operator filters out duplicate events.

Alias: `suppress` (`dedup` and `suppress` are synonyms).

You need to specify the field that you want to inspect for duplicates (**FieldName**). When that field has the same value in multiple events, those events are considered duplicates.

You can also specify multiple fields. In that case, events are considered duplicates only if **all** of the specified fields are duplicated. For example, if you specify fields named `Phone` and `Email`, events are considered duplicates only if they have an identical `Phone` value **and** an identical `Email` value.

By default, the `dedup` operator outputs only the first duplicate it finds, and drops the rest. You can change this behavior by specifying the number of duplicates to keep (**NumberOfDuplicatesToKeep**).

When looking for duplicates, the `dedup` operator compares events timed within 30 seconds of each other. You can also specify a different time window (**TimeWindow**).

Syntax

```
Scope | dedup [time_window=TimeWindow] [num_duplicates=NumberOfDuplicatesToKeep] by FieldName [, ...]
```

Arguments

- **TimeWindow** (int): Sets a time interval, across event timestamps, over which this operator will apply the **NumberOfDuplicatesToKeep** limit on the specified **FieldName**(s). For event pairs outside this time interval, `dedup` will release the limit, allowing the next duplicate event to filter through to results. Default: `30` seconds.
- **NumberOfDuplicatesToKeep** (int or expression): The number of duplicate events to keep. Default: `1`.
- **FieldName**: The name of the field that you want to inspect for duplicates. Allowed formats: `fieldName` or `["field name"]`. Separate multiple fields with a comma: `fieldName1, ["field name 2"], ...`.

Results

Filters out events identified as duplicates.

Examples

Filter out events that contain duplicate instances of a random number:

```
dataset=$vt_dummy event<1000
| extend randomNumber=rand(10)
| dedup by randomNumber
```

Copy | Run in Cribl Search

Filter out events that have the same value in the `Name` field.

```
dataset=myDataset
| dedup by Name
```

Copy

Filter out events that have the same values in the corresponding `Name`, `Home address`, and `Work address` fields.

```
dataset=myDataset
| dedup by Name, ['Home address'], ["Work address"]
```

Copy

Filter out events that contain `Name` duplicates, and that were found within a minute of each other. If there are more than 5 such events, keep only the first 5.

```
dataset=myDataset
| dedup time_window=60 num_duplicates=5 by Name
```

Copy

14.2.4.3. Distinct

The `distinct` operator identifies unique values within each of the specified fields. It's used to retrieve distinct values for each field independently. `distinct` finds unique values within each provided field separately, helping you to analyze and explore data uniqueness within individual fields.

Syntax

```
Scope | distinct [ maxCombinations ] [ maxDepth ] FieldName [= Expression] [, ...]
```

Copy

Arguments

- **Scope**: The events to search.
- **maxCombinations**: The maximum number of distinct combinations. Defaults to `10000`. The maximum supported value is `50000`. Increasing the Usage Group **Results limit** above `50000` does not increase the `maxCombinations` limit.
- **maxDepth**: The maximum depth for searching unique combinations of field values. This controls how deep the search goes when identifying distinct combinations within nested or hierarchical data structures. Defaults to `15`.
- **FieldName**: One or more fields you want to find distinct values for. This operator allows you to identify unique values within the specified field(s) from your Dataset. A wildcard `*` indicates all available fields. You can also assign an expression inline using `FieldName = Expression` to compute a derived value and deduplicate on the result.

Examples

Find the distinct values for all fields in your Dataset.

```
dataset=myDataset
| distinct *
```

Copy

Find unique values within the `host` and `port` fields.

```
dataset=myDataset
| distinct host, port
```

Copy

Find distinct values for the `source` field, limiting the search to 100 combinations and a depth of 10.

```
dataset=myDataset
| distinct maxCombinations=100 maxDepth=10 source
```

Copy

Compute a derived value inline and deduplicate on the result.

```
dataset=myDataset level=error
| distinct x = strcat('ERROR: ', message)
```

Copy

```
dataset=$vt_dummy event<1000
| distinct randomNumber=rand(10)
```

Copy Run in Cribl Search

14.2.4.4. Search

The `search` operator finds events with specific text strings.



We recommend using the `cribl` operator, which has easier syntax and more capabilities.

Syntax

```
[Scope |] search [in (Dataset, ...)] [kind=CaseSensitivity] Predicate
```

Arguments

Scope: An optional expression that acts as a data source to be searched over. Cannot appear together with the optional phrase that includes **FieldName**.

CaseSensitivity: An optional flag that controls the behavior of all string scalar operators with respect to case sensitivity. Valid values are the two synonyms `default` and `case_insensitive` (which is the default for operators such as `has`, namely being case-insensitive) and `case_sensitive` (which forces all such operators into case-sensitive matching mode).

FieldName: An optional comma-separated list of "wildcarded" field names to take part in the search.

Predicate: An expression that defines what to search for and is evaluated for every record in the input. The expression must return a `bool` value. If the expression returns `true`, the record is outputted. The syntax for **Predicate** extends and modifies the normal syntax for expressions:

- **String matching extensions**: String literals that appear as terms in the **Predicate** indicate a term match between all fields and the literal using `has`, `hasprefix`, `hassuffix`, and the inverted `!` or case-sensitive `cs` versions of these operators. Asterisks are not supported within the literal, nor as wildcard characters.
- **Field restriction**: By default, string matching extensions attempt to match against all fields of the Dataset. It is possible to restrict this matching to a particular field by using the following syntax: `FieldName:StringLiteral`.
- **String equality**: Exact matches of a field against a string value (instead of a term-match) can be done using the syntax `FieldName==StringLiteral`.
- **Other expressions**: The syntax supports all expressions that return a `bool` value. For example, `"error" and x==123` means: search for records that have the term `error` in any of their fields, and have the value `123` in the `x` field."
- **Regex match**: Indicate regular expression matching using the syntax `FieldName matches regex RegularExpression`. For syntax details, see Regex Examples, Regex Flags, and Disambiguate Regex

Characters.

String Matching

#	Syntax	Meaning (equivalent `where`)
1	`search "err"`	`where * contains "err"`
2	`search in (T1,T2) "err"`	`union T1,T2 | where * contains “err”`
3	`search col:"err"`	`where col contains "err"`
4	`search col=="err"`	`where col=="err"`
10	`search col matches regex "..."`	`where col matches regex "..."`
11	search kind=case_sensitive	All string comparisons are case-sensitive
12	`search "abc" and ("def" or "hij")`	`where * contains "abc" and (* contains "def" or * contains "hij")`
13	`search "err" or (A>a and A<b)`	`where * contains "err" or (A>a and A<b)`

Examples

Simple term search over all Datasets and fields:

```
search "goats"
```

Copy

Looking only for records that match both terms:

```
search "goats" and ("Billy" or "Nanny")
```

Copy

Performing a case-sensitive match of all terms:

```
search kind=case_sensitive "BillB" and ("SteveB" or "SatyaN")
```

Copy

Restricting the match to certain fields:

```
search CEO:"goats" or CSA:"goats"
```

Copy

Specific time limit:

```
search "goats" and Timestamp >= datetime(1981-01-01)
```

Copy

Return results that match “test event”:

```
dataset=$vt_dummy event<10
| extend _raw=iif(event%2>0, "This is a test event", "This is another event")
| search _raw has "test event"
```

Copy Run in Cribl Search

In all the above examples, `search` behaves as a filtering operator. You can use `search` as a data-**producing** operator in simple expressions of the form `search in (<Dataset>)`:

```
search in (cribl_search_sample) "mozilla"
```

Copy Run in Cribl Search

However, in the next example, `search` again behaves as a filtering operator. It follows this behavior whenever a `search` expression is placed after a data-producing operator (such an explicit or implict `cribl`, or even another `search` operator in the pattern shown in the preceding example). This returns results where strings in the `useragent` field match “Mozilla”:

```
datatype="apache_access_combined"
| limit 10
| search useragent in ("Mozilla")
```

Copy Run in Cribl Search

14.2.4.5. Suppress

The `suppress` operator filters out duplicate events.

Alias: `dedup` (`dedup` and `suppress` are synonyms.)

You need to specify the field that you want to inspect for duplicates (**FieldName**). When that field has the same value in multiple events, those events are considered duplicates.

You can also specify multiple fields. In that case, events are considered duplicates only if **all** of the specified fields are duplicated. For example, if you specify fields named `Phone` and `Email`, events are considered duplicates only if they have an identical `Phone` value **and** an identical `Email` value.

By default, the `suppress` operator outputs only the first duplicate it finds, and drops the rest. You can change this behavior by specifying the number of duplicates to keep (**NumberOfDuplicatesToKeep**).

When looking for duplicates, the `suppress` operator compares events timed within 30 seconds of each other. You can also specify a different time window (**TimeWindow**).

Syntax

```
Scope | suppress [time_window=TimeWindow] [num_duplicates=NumberOfDuplicatesToKeep] by FieldName [, ...]
```

Arguments

- **TimeWindow** (int): Sets a time interval, across event timestamps, over which this operator will apply the **NumberOfDuplicatesToKeep** limit on the specified **FieldName**(s). For event pairs outside this time interval, `suppress` will release the limit, allowing the next duplicate event to filter through to results. Default: `30` seconds.
- **NumberOfDuplicatesToKeep** (int or expression): The number of duplicate events to keep. Default: `1`.
- **FieldName**: The name of the field that you want to inspect for duplicates. Allowed formats: `fieldName` or `["field name"]`. Separate multiple fields with a comma: `fieldName1, ["field name 2"], ...`.

Results

Filters out events identified as duplicates.

Examples

Filter out events that contain duplicate instances of a random number:

```
dataset=$vt_dummy event<1000
| extend randomNumber=rand(10)
| suppress by randomNumber
```

Copy | Run in Cribl Search

Filter out events that have the same value in the `Name` field.

```
dataset=myDataset
| suppress by Name
```

Copy

Filter out events that have the same values in the corresponding `Name`, `Home address`, and `Work address` fields.

```
dataset=myDataset
| suppress by Name, ['Home address'], ["Work address"]
```

Copy

Filter out events that contain `Name` duplicates, and that were found within a minute of each other. If there are more than 5 such events, keep only the first 5.

```
dataset=myDataset
| suppress time_window=60 num_duplicates=5 by Name
```

Copy

14.2.4.6. WHERE

The `where` operator filters events based on the specified predicate.

Syntax

```
Scope | where Predicate
```

Arguments

- **Scope**: The events to search.
- **Predicate**: An expression that returns a `bool` value for each event. This can match on strings, numeric values, or regular expressions.

Comparison and String Operators in `where`

You can construct a **Predicate** using the comparison and string operators shown below. Note the abbreviations used in these tables:

- Operators with a `_cs` suffix are case-sensitive.
- RHS = right-hand side of the predicate.
- LHS = left-hand side of the predicate.

Comparison Operators in `where`

To compare on wildcards (`*`), use the comparison operators of the `cribl` operator. The `where` operator supports wildcards only inside regex literals (`/^abc.*xyz$/`).

When comparing values of different types, Cribl Search performs automatic type conversion wherever possible, giving priority to number comparisons.

Some comparison examples:

- `"1.0" == 1` is `true`
- `"1.0" == "1"` is `true`
- `5 < 100` is `true`
- `"5" < "100"` is `true`
- `"abc" < "100"` is `false`
- `"abc" < 100` is `null`

Operator	Description	Example (Returns `true`)	Case-Sensitive	Accepts `null`	Supports Regex	Regex Example
`==`	Equals	`"aBc" == "aBc"`	Yes	Yes	Only in regex literals	`foo == /^abc.*xyz$/`
`!=`	Not equals	`"abc" != "ABC"`	Yes	Yes	Only in regex literals	`foo != /^abc.*xyz$/`
`=~`	Equals	`"abc" =~ "ABC"`	No	Yes	Only in regex literals	`foo =~ /^abc.*xyz$/`
`!~`	Not equals	`"aBc" !~ "xyz"`	No	Yes	Only in regex literals	`foo !~ /^abc.*xyz$/`
>	Greater than		-	No	-	-
<	Less than		-	No	-	-
>=	Greater than or equal to		-	No	-	-
<=	Less than or equal to		-	No	-	-
!	Unary inversion (NOT) Logical values only; string values are unsupported		-	No	-	-

String Operators in `where`

To search on wildcards (`*`), use the string operators of the `cribl` operator. The `where` operator supports wildcards only inside regex literals (`/^abc.*xyz$/`).

Operator	Description	Example (Returns `true`)	Case-Sensitive	Regex	Regex Example
`contains`	RHS occurs as a	`"FabriKam" contains "BRik"`	No	No	-

Operator	Description	Example (Returns `true`)	Case-Sensitive	Regex	Regex Example
	subsequence of LHS				
`!contains`	RHS doesn't occur in LHS	`"Fabrikam" !contains "xyz"`	No	No	-
`contains_cs`	RHS occurs as a subsequence of LHS	`"FabriKam" contains_cs "Kam"`	Yes	No	-
`!contains_cs`	RHS doesn't occur in LHS	`"Fabrikam" !contains_cs "Kam"`	Yes	No	-
`endswith`	RHS is a closing subsequence of LHS	`"Fabrikam" endswith "Kam"`	No	No	-
`!endswith`	RHS isn't a closing subsequence of LHS	`"Fabrikam" !endswith "brik"`	No	No	-
`endswith_cs`	RHS is a closing subsequence of LHS	`"Fabrikam" endswith_cs "kam"`	Yes	No	-
`!endswith_cs`	RHS isn't a closing subsequence of LHS	`"Fabrikam" !endswith_cs "brik"`	Yes	No	-
`has`	Right-hand-side (RHS) is a whole term in left-hand-side (LHS)	`"North America" has "america"`	No	No	-
`:`	Alias for `has`	`"North America" : "america"`	No	No	-
`!has`	RHS isn't a full term in LHS	`"North America" !has "amer"`	No	No	-

Operator	Description	Example (Returns `true`)	Case-Sensitive	Regex	Regex Example
`has_all`	Same as has but works on all of the events	`"North and South America" has_all("south", "north")`	No	No	-
`has_any`	Same as has but works on any of the events	`"North America" has_any("south", "north")`	No	No	-
`!has_all`	Same as has but works on all of the events	`"North and South America" has_all("south", "north")`	No	No	-
`!has_any`	Same as has but works on any of the events	`"North America" has_any("south", "north")`	No	No	-
`has_cs`	RHS is a whole term in LHS	`"North America" has_cs "America"`	Yes	No	-
`!has_cs`	RHS isn't a full term in LHS	`"North America" !has_cs "amer"`	Yes	No	-
`hasprefix`	RHS is a term prefix in LHS	`"North America" hasprefix "ame"`	No	No	-
`!hasprefix`	RHS isn't a term prefix in LHS	`"North America" !hasprefix "mer"`	No	No	-
`hasprefix_cs`	RHS is a term prefix in LHS	`"North America" hasprefix_cs "Ame"`	Yes	No	-
`!hasprefix_cs`	RHS isn't a term prefix in LHS	`"North America" !hasprefix_cs "CA"`	Yes	No	-
`hassuffix`	RHS is a term suffix in LHS	`"North America" hassuffix "ica"`	No	No	-
`!hassuffix`	RHS isn't a term suffix in	`"North America" !hassuffix`	No	No	-

Operator	Description	Example (Returns `true`)	Case-Sensitive	Regex	Regex Example
	LHS	`"americ"`			
`hassuffix_cs`	RHS is a term suffix in LHS	`"North America" hassuffix_cs "ica"`	Yes	No	-
`!hassuffix_cs`	RHS isn't a term suffix in LHS	`"North America" !hassuffix_cs "icA"`	Yes	No	-
`in`	Equal to any of the events	`"abc" in ("123", "345", "abc")`	Yes	Only in regex literals	`foo in ("ye*ah", /^no.+way/i, 'whee')`
`!in`	Not equal to any of the events	`"bca" !in ("123", "345", "abc")`	Yes	Only in regex literals	`foo !in ("ye*ah", /^no.+way/i, 'whee')`
`in~`	Equal to any of the events	`"Abc" in~ ("123", "345", "abc")`	No	Only in regex literals	`foo in~ ("ye*ah", /^no.+way/i, 'whee')`
`!in~`	Not equal to any of the events	`"bCa" !in~ ("123", "345", "ABC")`	No	Only in regex literals	`foo !in~ ("ye*ah", /^no.+way/i, 'whee')`
`matches regex`	LHS contains a match for RHS	`"Fabrikam" matches regex "b.*k"`	Yes	Only in regex literals	`foo matches regex /^some.+(body|thing)$/i`
`startswith`	RHS is an initial subsequence of LHS	`"Fabrikam" startswith "fab"`	No	No	-
`!startswith`	RHS isn't an initial subsequence of LHS	`"Fabrikam" !startswith "kam"`	No	No	-

Operator	Description	Example (Returns `true`)	Case-Sensitive	Regex	Regex Example
`startswith_cs`	RHS is an initial subsequence of LHS	`"Fabrikam" startswith_cs "Fab"`	Yes	No	-
`!startswith_cs`	RHS isn't an initial subsequence of LHS	`"Fabrikam" !startswith_cs "fab"`	Yes	No	-

Results

Returns events for which the **Predicate** evaluates to `true`.

Examples

Here are a few examples of how to use the `where` operator in queries.

Simple Comparisons First

This example retrieves events that are no older than 1 hour, come from a source called `MyCluster`, and have two fields containing the same value:

```
dataset=myDataset
| where Timestamp > ago(1h)
    and Source == "MyCluster"
    and ActivityId == SubActivityId
```

Copy

Columns Contain String

Retrieve all the events in which the word "Cribl" appears on word boundaries in `field`:

```
dataset=myDataset
| where field has "Cribl"
```

Copy

In `where` string comparisons, note that `:` is a substitute for the `has` operator. So in the above example, `where field:"Cribl"` is equivalent to `where field has "Cribl"`.

Match on AND Condition

Return results where the field `event` is greater than 20 and `parity` is odd.

```
dataset=$vt_dummy event<100
| extend parity=iif(event%2==0, 'even', 'odd')
| where event>20 and parity=='odd'
```

Copy Run in Cribl Search

Match on OR Condition

Return results that match either of two conditions:

```
dataset="cribl_internal_logs" | limit 50 | where method == "GET" or method == "POST"
```

Copy Run in Cribl Search

Match with Regex

The `where` operator supports regular expressions to match against strings or regex literals. You can see this in action in our Regex Examples.

Search on Non-String Values

When using `where` to search on non-`string` values (such as `int` numbers), omit the quotes (`""`, `''`). For example, instead of `dataset=$vt_dummy event<"10"`, do this:

```
dataset=$vt_dummy event<10
```

Copy Run in Cribl Search

An exception to this is searching for high-precision decimal numbers.

Filter by Field Existence (Truthy Check)

Use a bare field name as the sole predicate to keep only events where that field is present and has a non-null,

14.2.5. Logical Operators

A list of logical operators supported by Cribl Search.

Operator	Description
`AND`	Returns `true` if both operands are `true`, otherwise returns `false`.
`NOT` or `!`	Returns `true` if the operand is `false`, otherwise returns `false`.
`OR`	Returns `true` if at least one operand is `true`, otherwise returns `false`.

See also:

- `null` and Binary Operators
- `bool` and the Logical NOT Operator
- `null` and the Logical NOT Operator

14.2.6. Numerical Operators

A list of numerical operators supported by Cribl Search.

Numerical operators perform arithmetic operations on values of the following types:

- `double` (aliases: `real`, `decimal`)
- `int` (alias: `long`)

You can use the following numerical operators between pairs of the above value types:

Operator	Description
==	Equal
!=	Not Equal
>	Greater Than
>=	Greater Than or Equal To
<	Less Than
<=	Less Than or Equal To
+	Add
-	Subtract
*	Multiply
/	Divide
%	Modulo



Don't use the `+` operator to concatenate strings (with the `"string1" + "string2"` notation). Use the `strcat-delim` or `strcat` functions instead.

See also: `null` and Binary Operators.

14.2.7. Search Operators

A list of search operators supported by Cribl Search.

Search operators retrieve events based on defined criteria, enabling efficient data discovery.

Name	Description
`cribl`	Finds specific events. The fundamental Cribl Search operator, implicit in queries that do not specify an operator.
`find`	Finds specific events.

14.2.7.1. Cribl

The `cribl` operator finds specific events. It is the fundamental Cribl Search operator, and is implicit in queries that do not specify an operator.

Syntax

`[cribl] StringExpression ComparisonExpression [ BooleanOperator ] [ StringExpression | ComparisonExpression ]`

Either a **StringExpression** or a **ComparisonExpression** is required.

Rules

- `cribl` is implicit. You don't need to specify it in a query.
- But to use `cribl` in a subquery, you must specify it.
- `cribl`, like `find`, can be used to initiate a query expression.
- `cribl` doesn't support functions (or any kind of expressions). For this, you need to use the `where` operator.
- Wildcards `*` represent zero or more characters.
- An escaped `\*` represents a literal asterisk.
- `cribl` doesn't support including both a wildcard `*` and a literal `\*` in the same query. To perform this type of search, you need to use the `where` operator.
- `cribl` interprets both the `==` and `=` tokens as comparison (not assignment) operators.
- `cribl` implicitly matches against the `_raw` field if you specify no field; otherwise, it matches against an extracted field.

Arguments

The `cribl` operator accepts a flexible range of arguments.

StringExpression

Case-insensitive string of characters. For example, `"error"` or `error`. To see if you can omit the double quotes `""`, see Quotes in `cribl` Operator. Either a **StringExpression** or a **ComparisonExpression** is required.

BooleanOperator

`not`, `or`, `and`, in that order of precedence. This order differs from other operators. Use parentheses `()` to override this precedence.

Here, whitespace is equivalent to `and`. For example, `foo and bar` is the same as `foo bar`.

ComparisonExpression

Compare numbers, strings, and/or regular expressions; perform evaluations that evaluate to a boolean. Either a **ComparisonExpression** or a **StringExpression** is required.

Syntax: `Key ComparisonOperator Value` or `Key in (ListOfValues)` or `TimeExpression`

We break down these parameters below.

Key

This is a field name.

Comparison Operators in `cribl`

Formal comparison operators are `=`, `==`, `=~`, `!=`, `!==`, `>`, `>=`, `<`, `<=`, `=~`, and `!~`. (For comparisons against regex literals, we support only the `==`, `=~`, `!=`, and `!~` operators.) See also String Operators below.

Operator	Description	Case-Sensitive	Wildcards	Regex	Examples	Wildcard Example	Regex Example

Equal `=` or `==`	Returns `true` if the operands are equal.	No	Yes	Yes	`3 == var1`
					`"3" == var1`
					`3 == '3'`
						`foo == "abc*"`	`foo == /^abc.*xyz`

Not equal `!=`	Returns `true` if the operands are not equal.	No	Yes	Yes	`var1 != 4` `var2 != "3"`	`foo != "abc*"`	`foo != /^abc.*xyz`
Greater than `>`	Returns `true` if the left operand is greater than the right operand.	No	No	No	`var2 > var1` `"12" > 2`		
Less than `<`	Returns `true` if the left operand is less than the right operand.	No	No	No	`var1 < var2` `"2" < 12`		

Operator	Description	Case-Sensitive	Wildcards	Regex	Examples	Wildcard Example	Regex Example
Greater than or equal to `>=`	Returns `true` if the left operand is greater than or equal to the right operand.	No	No	No	`var2 >= var1` `var1 >= 3`		
Less than or equal to `<=`	Returns `true` if the left operand is less than or equal to the right operand.	No	No	No	`var1 <= var2` `var2 <= 5`		
`!`	Unary inversion (NOT) - logical values only; string values are unsupported	No	Yes	Yes			

String Operators in `cribl`

The **ComparisonOperator** parameter also supports the following string operators.

Operator	Description	Case-Sensitive	Wildcards	Regex	Example (yields `true`)	Regex Example
`in`	Equal to any of the events	Yes	No	Yes	`"abc" in ("123", "345", "abc")`	`foo in ("ye*ah", /^no.+way/i, 'whee')`
`!in`	Not equal to any of the events	Yes	No	Yes	`"bca" !in ("123", "345", "abc")`	`foo !in ("ye*ah", /^no.+way/i, 'whee')`
`in~`	Equal to any of the events	No	No	Yes	`"Abc" in~ ("123", "345", "abc")`	`foo in~ ("ye*ah", /^no.+way/i, 'whee')`

Operator	Description	Case-Sensitive	Wildcards	Regex	Example (yields `true`)	Regex Example
`!in~`	Not equal to any of the events	No	No	Yes	`"bCa" !in~ ("123", "345", "ABC")`	`foo !in~ ("ye*ah", /^no.+way/i, 'whee')`

Value

This is a **StringExpression**.

- **in**: `in` (or `!in`, or `in~`, or `!in~`) filters events with **ListOfValues**.

ListOfValues

This is a comma-separated list of one or more **StringExpression**s. For example: `(StringExpression, StringExpression, ...)`

TimeExpression

Relative or absolute time range. Syntax: `earliest=TimeString` and/or `latest=TimeString`. `earliest` is inclusive `>=`, while `latest` is exclusive `<`. The limit of `earliest` is 90 days (7776000 seconds) ago. See time syntax for details.

RegularExpression

Regex literal. Syntax: `/<regular expression>/<flags>`. For syntax details, see Regex Examples, Regex Flags, and Disambiguating Regex Characters.

ComparisonExpression Examples

- `foo=bar`, `foo23.4`, `bar42`, `foo!=bar*`
- `level in (INFO, DEBUG, ERROR)`
- `method in ("GET", "POST")`
- `earliest=-1h`, `latest=-42m`, `earliest=-42m@h latest=now`, `earliest=-2h@m latest=+2h@m`, `earliest=1700511360.123 latest=1700511420.123`
- `method == /ge*/i`
- `method =~ /ge*|p.*t/i`
- `method in ("GET", /^po.*/i)`

(In the final example above, note that your **ComparisonExpression** can mix string and regex target values.)

Quotes in `cribl` Operator

You **don't** need to enclose your StringExpression in double quotes `""`, as long as it's made of the following characters only:

- `a-z`
- `A-Z`
- `0-9`
- `$ _ * . -`

If your StringExpression contains any other character, you **do** need to enclose it in double quotes `""`, for example:

Characters	Need quotes `""`	Examples
`@ + - \ / ( ) [ ]`		`"john.doe@whatever.com"` `"/api/events"`
Space `( )`		`"test event"`
Keywords `dataset`, `earliest`, and `latest`		`"earliest=testEvent"`
`a-z A-Z 0-9`		`testEvent0` or `"testEvent0"`
`$ _ * . -`		`us-*` or `"us-*"`

Cribl Search keywords, such as operator or function names, don't need double quotes. The only the exceptions are `dataset`, `earliest`, and `latest`.

To escape double quotes, use the backslash `\`, for example: `"style=\"goatee\""`

Time Syntax

The `TimeString` used for `earliest` and `latest` can be one of the following:

- A relative timestamp, expressed in the human-readable format described below, with no quotes. For example, `earliest=-3h`.
- An absolute timestamp, expressed in Unix time, with no quotes. For example, `earliest=1729290112`.
- An ISO 8601-formatted timestamp string, in quotes. For example, `earliest="2024-12-01T00:00:00Z"`.

For relative timestamps, use the following syntax:

`[+|-]TimeNumberTimeUnit[@SnapToTimeUnit]`

Argument	Values Supported
`+` or `-`	Optional, defaults to `now`. Use `-` for times in the past, or `+` for times in the future.
`TimeNumber`	A positive integer.
`TimeUnit`	Unit of time. Supports `s[econds]`, `m[inutes]`, `h[ours]`, `d[ays]`, `w[eeks]`, `mon[ths]`, `q[uarters]`, `y[ears]`.
`@SnapToTimeUnit`	Optional. Append the `@` modifier, followed by any of the above `TimeUnits`, to round down to the nearest instance of that unit. (See the next section for details.)

For absolute timestamps, use the following syntax:

`TimeNumber`

Argument	Values Supported
`TimeNumber`	A Unix time value (number of seconds since 1 Jan 1970). Can be either an unquoted Unix time value (for example, `1700511360` or `1700511420.123` to express milliseconds), or a quoted ISO-8601 formatted string (for example, `"2024-12-01T00:00:00Z"`)

SnapToTimeUnit Syntax

The `@` snap modifier always rounds **down** (backwards) from any specified time. This is true even in relative time expressions with `+` (future) offsets.

Snap-to calculations respect the timezone selected in the timepicker. Calendar boundaries (day, week, month, quarter, year) are calculated based on the selected timezone.

For example:

- `@d` snaps back to the beginning of today, 12:00 AM (midnight) in the selected timezone.
- `-1d@d` snaps back to the beginning of yesterday. Pair `-1d@d` with `latest=@d` to cover all of yesterday.
- `+128m@h` looks forward 128 minutes, then snaps back to the nearest round hour. (If you specified this in the `Latest` field, and ran the Collector at 4:20 PM, collection would end at 6:00 PM. The expression would look forward to 6:28 PM, but snap back to 6:00 PM.)

Other options:

- `@w` or `@w7` to snap back to the beginning of the week - defined here as the preceding Sunday.
- To snap back to other days of a week, use `w1` (Monday) through `w6` (Saturday).
- `@mon` to snap back to the 1st of a month.

- `@q` to snap back to the beginning of the most recent quarter - Jan. 1, Apr. 1, Jul. 1, or Oct. 1.
- `@y` to snap back to Jan. 1.

Examples

Simple term search over all events in the `default` Dataset:

```
"goats"
```

Copy

Looking only for records that match both terms:

```
"goats" and ("climb" or "rock climb")
```

Copy

Looking in the `network` field for "sector7":

```
network in ("sector7")
```

Copy

Looking in the `region` field for values that start with `us-`:

```
region in (us-*)
```

Copy

Restricting the search to certain fields:

```
disk="f9" or process="index"
```

Copy

Specific time limit:

```
earliest=-2h@h latest=-1h@min
```

Copy

Searching Datasets that start with `foo` for specific terms and field values within a specified time range:

```
dataset=foo* (blocked or "access denied") method in (POST, GET) az !in (us-east*, us-
```

Copy

Return results that match “test event”.

```
dataset=$vt_dummy event<10
| extend _raw=iif(event%2>0, "This is a test event", "This is another event")
| cribl "test event"
```

Copy Run in Cribl Search

Return all events from a Dataset whose `_time` is between a specified range:

14.2.7.2. FIND

The `find` operator finds specific events.



We recommend using the `cribl` operator, which has easier syntax and more capabilities.

Either `cribl` or `find` can be used to initiate a query expression.

Syntax

- `find [withsource=FieldName] [in (Dataset [, Dataset, ...])] where Predicate [project-smart | project FieldName [:FieldType] [, FieldName[:FieldType], ...]`
- `find Predicate [project-smart | project FieldName[:FieldType] [, FieldName[:FieldType], ...]`

Arguments

- `withsource=`**FieldName**: Optional. By default, the output will include a field called `dataset` whose values indicate which Dataset has contributed to each result. If specified, **FieldName** will be used instead of `dataset`.
- **Predicate**: An expression over the fields of the Datasets that returns a `bool` value. For a summary of some filtering functions, see the `where` operator.
- **Dataset**: Optional. By default, find will look in all the Datasets for:
  - The name of a Dataset, such as `Events`.
  - A query expression, such as `(Events | where id==42)`.
- `project-smart | project`: If not specified, `project-smart` will be used by default. For more information, see output-schema below.

Output Schema

`dataset` field

The `find` operator output will always include a `dataset` field with the Dataset name. The field can be renamed using the `withsource` parameter.

Results fields

Datasets that don't contain any fields used by the predicate evaluation will be filtered out.

When using `project-smart`, the fields that will appear in the output will be:

- Fields that appear explicitly in the predicate.
- Fields that are common to all the filtered Datasets.

The rest of the fields will be packed into a property bag and will appear in an additional `pack_` field. A field that is referenced explicitly by the predicate and has multiple types will have a different field in the result schema for each such type. Each of the field names will be constructed from the original field name and type, separated by an underscore.

When using `project FieldName[:FieldType] [, FieldName[:FieldType], ...]:

The results will include the fields specified in the list. If a Dataset doesn't contain a certain field, the values in the corresponding rows will be null. When specifying a **FieldType** with a **FieldName**, this field will have the given type, and the values will be cast to that type if needed. The casting won't have an effect on the field type when evaluating the predicate.

`pack_` field

This field will contain a property bag with the data from all the fields that don't appear in the output schema. The Dataset name will serve as the property name and the field value will serve as the property value.

Examples

Term lookup across the `default` Dataset

The query finds all events from the `default` Dataset where any field includes the word `Goat`.

```
find "Goat"
```

Copy

Term lookup across the `default` Dataset matching a name pattern

The query finds all events from the `default` Dataset whose name starts with `G`, and in which any field includes the word `Cribl`.

```
find in ("cribl_search_sample") where _raw has "GET"
| limit 100
```

Copy

Examples of find output results

The following examples show how find can be used over two Datasets: EventsTable1 and EventsTable2. Assume we have the next content of these two Datasets:

EventsTable1

Session_Id	Level	EventText	Version
acbd207d-51aa-4df7-bfa7-be70eb68f04e	Information	Some Text1	v1.0.0
acbd207d-51aa-4df7-bfa7-be70eb68f04e	Error	Some Text2	v1.0.0
28b8e46e-3c31-43cf-83cb-48921c3986fc	Error	Some Text3	v1.0.1
8f057b11-3281-45c3-a856-05ebb18a3c59	Information	Some Text4	v1.1.0

EventsTable2

Session_Id	Level	EventText	EventName
f7d5f95f-f580-4ea6-830b-5776c8d64fdd	Information	Some Other Text1	Event1
acbd207d-51aa-4df7-bfa7-be70eb68f04e	Information	Some Other Text2	Event2
acbd207d-51aa-4df7-bfa7-be70eb68f04e	Error	Some Other Text3	Event3
15eaeab5-8576-4b58-8fc6-478f75d8fee4	Error	Some Other Text4	Event4

Search in common fields, project common and uncommon fields, and pack the rest

```
find in (EventsTable1, EventsTable2)
     where Session_Id == 'acbd207d-51aa-4df7-bfa7-be70eb68f04e' and Level == 'Error'
     project EventText, Version, EventName
```

Copy

dataset	EventText	Version	EventName	pack_
EventsTable1	Some Text2	v1.0.0		{“Session_Id”:“acbd207d-51aa-4df7-bfa7-be70eb68f04e”, “Level”:“Error”}

dataset	EventText	Version	EventName	pack_
EventsTable2	Some Other Text3		Event3	{“Session_Id”:“acbd207d-51aa-4df7-bfa7-be70eb68f04e”, “Level”:“Error”}

Search in common and uncommon fields

```
find Version == 'v1.0.0' or EventName == 'Event1' project Session_Id, EventText, Vers
```

Copy

dataset	Session_Id	EventText	Version	EventName
EventsTable1	acbd207d-51aa-4df7-bfa7-be70eb68f04e	Some Text1	v1.0.0	
EventsTable1	acbd207d-51aa-4df7-bfa7-be70eb68f04e	Some Text2	v1.0.0	
EventsTable2	f7d5f95f-f580-4ea6-830b-5776c8d64fdd	Some Other Text1		Event1

In practice, EventsTable1 rows will be filtered with Version == ‘v1.0.0’ predicate and EventsTable2 rows will be filtered with EventName == ‘Event1’ predicate.

Use abbreviated notation to search across the `default` Dataset

```
find Session_Id == 'acbd207d-51aa-4df7-bfa7-be70eb68f04e'
```

Copy

dataset	Session_Id	Level	EventText	pack_
EventsTable1	acbd207d-51aa-4df7-bfa7-be70eb68f04e	Information	Some Text1	{“Version”:“v1.0.0”}
EventsTable1	acbd207d-51aa-4df7-bfa7-be70eb68f04e	Error	Some Text2	{“Version”:“v1.0.0”}
EventsTable2	acbd207d-51aa-4df7-bfa7-be70eb68f04e	Information	Some Other Text2	{“EventName”:“Event2”}
EventsTable2	acbd207d-51aa-4df7-bfa7-be70eb68f04e	Error	Some Other Text3	{“EventName”:“Event3”}

Return the results from each row as a property bag

```
find Session_Id == 'acbd207d-51aa-4df7-bfa7-be70eb68f04e'
```

Copy

dataset	pack_
EventsTable1	{“Session_Id”:“acbd207d-51aa-4df7-bfa7-be70eb68f04e”, “Level”:“Information”, “EventText”:“Some Text1”, “Version”:“v1.0.0”}
EventsTable1	{“Session_Id”:“acbd207d-51aa-4df7-bfa7-be70eb68f04e”, “Level”:“Error”, “EventText”:“Some Text2”, “Version”:“v1.0.0”}
EventsTable2	{“Session_Id”:“acbd207d-51aa-4df7-bfa7-be70eb68f04e”, “Level”:“Information”, “EventText”:“Some Other Text2”, “EventName”:“Event2”}
EventsTable2	{“Session_Id”:“acbd207d-51aa-4df7-bfa7-be70eb68f04e”, “Level”:“Error”, “EventText”:“Some Other Text3”, “EventName”:“Event3”}

Return results that match “test event”.

```
dataset=$vt_dummy event<10
| extend _raw=iif(event%2>0, "This is a test event", "This is another event")
| find where * has "test event"
```

Copy Run in Cribl Search

14.2.8. String Operators

A list of string operators supported by Cribl Search.

String operators manipulate and transform text, enabling actions like concatenation, trimming, replacement, or extraction.

Note that these operators' support, and their case-sensitivity, vary depending on their parent search operators and filter operators. For exact details, see these pages:

- `cribl` operator.
- `where` operator.

We use the following abbreviations in the table below:

- Operators with a `_cs` suffix are case-sensitive.
- RHS = right-hand side of the expression.
- LHS = left-hand side of the expression.

Operator	Description	Case-Sensitive	Example (yields `true`)
`==`	Equals	Yes	`"aBc" == "aBc"`
`!=`	Not equals	Yes	`"abc" != "ABC"`
`=~`	Equals	No	`"abc" =~ "ABC"`
`!~`	Not equals	No	`"aBc" !~ "xyz"`
`contains`	RHS occurs as a subsequence of LHS	No	`"FabriKam" contains "BRik"`
`!contains`	RHS doesn't occur in LHS	No	`"Fabrikam" !contains "xyz"`
`contains_cs`	RHS occurs as a subsequence of LHS	Yes	`"FabriKam" contains_cs "Kam"`
`!contains_cs`	RHS doesn't occur in LHS	Yes	`"Fabrikam" !contains_cs "Kam"`
`endswith`	RHS is a closing subsequence of LHS	No	`"Fabrikam" endswith "Kam"`
`!endswith`	RHS isn't a closing subsequence of LHS	No	`"Fabrikam" !endswith "brik"`

Operator	Description	Case-Sensitive	Example (yields `true`)
`endswith_cs`	RHS is a closing subsequence of LHS	Yes	`"Fabrikam" endswith_cs "kam"`
`!endswith_cs`	RHS isn't a closing subsequence of LHS	Yes	`"Fabrikam" !endswith_cs "brik"`
`has`	Right-hand-side (RHS) is a whole term in left-hand-side (LHS)	No	`"North America" has "america"`
`!has`	RHS isn't a full term in LHS	No	`"North America" !has "amer"`
`has_all`	Same as `has` but works on all of the events	No	`"North and South America" has_all("south", "north")`
`!has_all`	Not all of the RHS terms are present in LHS	No	`"North and South America" !has_all("south", "east")`
`has_any`	Same as `has` but works on any of the events	No	`"North America" has_any("south", "north")`
`!has_any`	None of the RHS terms are present in LHS	No	`"North and South America" !has_any("east", "west")`
`has_cs`	RHS is a whole term in LHS	Yes	`"North America" has_cs "America"`
`!has_cs`	RHS isn't a full term in LHS	Yes	`"North America" !has_cs "amer"`
`hasprefix`	RHS is a term prefix in LHS	No	`"North America" hasprefix "ame"`
`!hasprefix`	RHS isn't a term prefix in LHS	No	`"North America" !hasprefix "mer"`
`hasprefix_cs`	RHS is a term prefix in LHS	Yes	`"North America" hasprefix_cs "Ame"`
`!hasprefix_cs`	RHS isn't a term prefix in LHS	Yes	`"North America" !hasprefix_cs "CA"`
`hassuffix`	RHS is a term suffix in LHS	No	`"North America" hassuffix "ica"`

Operator	Description	Case-Sensitive	Example (yields `true`)
`!hassuffix`	RHS isn't a term suffix in LHS	No	`"North America" !hassuffix "americ"`
`hassuffix_cs`	RHS is a term suffix in LHS	Yes	`"North America" hassuffix_cs "ica"`
`!hassuffix_cs`	RHS isn't a term suffix in LHS	Yes	`"North America" !hassuffix_cs "icA"`
`in`	Equal to any of the events	Yes	`"abc" in ("123", "345", "abc")`
`!in`	Not equal to any of the events	Yes	`"bca" !in ("123", "345", "abc")`
`in~`	Equal to any of the events	No	`"Abc" in~ ("123", "345", "abc")`
`!in~`	Not equal to any of the events	No	`"bCa" !in~ ("123", "345", "ABC")`
`matches regex`	LHS contains a match for RHS	Yes	`"Fabrikam" matches regex "b.*k"`
`startswith`	RHS is an initial subsequence of LHS	No	`"Fabrikam" startswith "fab"`
`!startswith`	RHS isn't an initial subsequence of LHS	No	`"Fabrikam" !startswith "kam"`
`startswith_cs`	RHS is an initial subsequence of LHS	Yes	`"Fabrikam" startswith_cs "Fab"`

14.2.8.1. ==

The `==` (equals) operator applies a case-sensitive string, or regex literal, filter and returns events that match.

The following table provides a comparison of the `equal` operators:

Operator	Description	Case-Sensitive	Example (yields `true`)
`==`	Equal	Yes	`"aBc" == "aBc"`
`!=`	Not equal	Yes	`"abc" != "ABC"`
`=~`	Equal	No	`"abc" =~ "ABC"`
`!~`	Not equal	No	`"aBc" !~ "xyz"`

When comparing values of different types, Cribl Search performs automatic type conversion wherever possible, giving priority to number comparisons.

For more details on comparison rules, see:

- Comparison operators of the `cribl` operator
- Comparison operators of the `where` operator

Syntax

```
Scope | where Field == (Expression, ... )
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **Expression**: An expression used to filter.

> To pass regex literals as **Expression** arguments, see syntax details at Regex Examples, Regex Flags, and Disambiguate Regex Characters.

Example

```
dataset=myDataset
| where state == "Kansas"
| count
```

Copy

14.2.8.2. !=

The `!=` (not equals) operator applies a case-sensitive string, or regex literal, filter, and excludes events that match.

The following table provides a comparison of the `equal` operators:

Operator	Description	Case-Sensitive	Example (yields `true`)
`==`	Equal	Yes	`"aBc" == "aBc"`
`!=`	Not equal	Yes	`"abc" != "ABC"`
`=~`	Equal	No	`"abc" =~ "ABC"`
`!~`	Not equal	No	`"aBc" !~ "xyz"`

When comparing values of different types, Cribl Search performs automatic type conversion wherever possible, giving priority to number comparisons.

For more details on comparison rules, see:

- Comparison operators of the `cribl` operator
- Comparison operators of the `where` operator

Syntax

```
Scope | where Field != (Expression, ... )
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **Expression**: An expression used to filter.

To pass regex literals as **Expression** arguments, see syntax details at Regex Examples, Regex Flags, and Disambiguate Regex Characters.

Example

```
dataset=myDataset
| where state != "Kansas"
| project EventId, State
```

Copy

14.2.8.3. =~

The `=~` (equals) operator applies a case-insensitive string filter and returns events that match.

The following table provides a comparison of the `equal` operators:

Operator	Description	Case-Sensitive	Example (yields `true`)
`==`	Equal	Yes	`"aBc" == "aBc"`
`!=`	Not equal	Yes	`"abc" != "ABC"`
`=~`	Equal	No	`"abc" =~ "ABC"`
`!~`	Not equal	No	`"aBc" !~ "xyz"`

When comparing values of different types, Cribl Search performs automatic type conversion wherever possible, giving priority to number comparisons.

For more details on comparison rules, see:

- Comparison operators of the `cribl` operator
- Comparison operators of the `where` operator

Syntax

```
Scope | where Field =~ (Expression, ... )
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **Expression**: An expression used to filter.

Example

```
dataset=myDataset
| where state =~ "Kansas"
| project EventId, State
```

Copy

14.2.8.4. !~

The `!~` (not equals) operator applies a case-insensitive string filter and excludes events that match.

The following table provides a comparison of the `equal` operators:

Operator	Description	Case-Sensitive	Example (yields `true`)
`==`	Equal	Yes	`"aBc" == "aBc"`
`!=`	Not equal	Yes	`"abc" != "ABC"`
`=~`	Equal	No	`"abc" =~ "ABC"`
`!~`	Not equal	No	`"aBc" !~ "xyz"`

When comparing values of different types, Cribl Search performs automatic type conversion wherever possible, giving priority to number comparisons.

For more details on comparison rules, see:

- Comparison operators of the `cribl` operator
- Comparison operators of the `where` operator

Syntax

```
Scope | where Field !~ (Expression, ... )
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **Expression**: An expression used to filter.

Example

```
dataset=myDataset
| summarize event_count=count() by State
| where (State !~ "texas") and (event_count > 3000)
| project State, event_count
```

Copy

14.2.8.5. Contains

The `contains` operator applies a case-insensitive string filter and returns events that match.

The following table compares the `contains` operators using these abbreviations:

- RHS = right-hand side of the expression
- LHS = left-hand side of the expression

Operator	Description	Case-Sensitive	Example (yields true)
`contains`	RHS occurs as a subsequence of LHS	No	`"FabriKam" contains "BRik"`
`!contains`	RHS doesn't occur in LHS	No	`"Fabrikam" !contains "xyz"`
`contains_cs`	RHS occurs as a subsequence of LHS	Yes	`"FabriKam" contains_cs "Kam"`
`!contains_cs`	RHS doesn't occur in LHS	Yes	`"Fabrikam" !contains_cs "Kam"`

Syntax

```
Scope | where Field contains String
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **String**: The string used to filter.

Example

```
dataset=myDataset
| summarize event_count=count() by State
| where State contains "enn"
```

Copy

14.2.8.6. !Contains

The `!contains` operator applies a case-insensitive string filter and excludes events that match.

The following table compares the `contains` operators using these abbreviations:

- RHS = right-hand side of the expression
- LHS = left-hand side of the expression

Operator	Description	Case-Sensitive	Example (yields true)
`contains`	RHS occurs as a subsequence of LHS	No	`"FabriKam" contains "BRik"`
`!contains`	RHS doesn't occur in LHS	No	`"Fabrikam" !contains "xyz"`
`contains_cs`	RHS occurs as a subsequence of LHS	Yes	`"FabriKam" contains_cs "Kam"`
`!contains_cs`	RHS doesn't occur in LHS	Yes	`"Fabrikam" !contains_cs "Kam"`

Syntax

```
Scope | where Field !contains String
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **String**: The string used to filter.

Example

```
dataset=myDataset
| summarize event_count=count() by State
| where State !contains "enn"
```

Copy

14.2.8.7. CONTAINS_CS

The `contains_cs` operator applies a case-sensitive string filter and returns events that match.

The following table compares the `contains` operators using these abbreviations:

- RHS = right-hand side of the expression
- LHS = left-hand side of the expression

Operator	Description	Case-Sensitive	Example (yields true)
`contains`	RHS occurs as a subsequence of LHS	No	`"FabriKam" contains "BRik"`
`!contains`	RHS doesn't occur in LHS	No	`"Fabrikam" !contains "xyz"`
`contains_cs`	RHS occurs as a subsequence of LHS	Yes	`"FabriKam" contains_cs "Kam"`
`!contains_cs`	RHS doesn't occur in LHS	Yes	`"Fabrikam" !contains_cs "Kam"`

Syntax

```
Scope | where Field contains_cs String
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **String**: The string used to filter.

Example

```
dataset=myDataset
| summarize event_count=count() by State
| where State contains_cs "AS"
```

Copy

14.2.8.8. !CONTAINS_CS

The `!contains_cs` operator applies a case-sensitive string filter and excludes events that match.

The following table compares the `contains` operators using these abbreviations:

- RHS = right-hand side of the expression
- LHS = left-hand side of the expression

Operator	Description	Case-Sensitive	Example (yields true)
`contains`	RHS occurs as a subsequence of LHS	No	`"FabriKam" contains "BRik"`
`!contains`	RHS doesn't occur in LHS	No	`"Fabrikam" !contains "xyz"`
`contains_cs`	RHS occurs as a subsequence of LHS	Yes	`"FabriKam" contains_cs "Kam"`
`!contains_cs`	RHS doesn't occur in LHS	Yes	`"Fabrikam" !contains_cs "Kam"`

Syntax

```
Scope | where Field !contains_cs String
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **String**: The string used to filter.

Example

```
dataset=myDataset
| summarize event_count=count() by State
| where State !contains_cs "AS"
```

Copy

14.2.8.9. ENDSWITH

The `endswith` operator applies a case-insensitive ending string filter and returns events that match.

The following table compares the `endswith` operators using these abbreviations:

- RHS = right-hand side of the expression
- LHS = left-hand side of the expression

Operator	Description	Case-Sensitive	Example (yields true)
`endswith`	RHS is a closing subsequence of LHS	No	`"Fabrikam" endswith "Kam"`
`!endswith`	RHS isn't a closing subsequence of LHS	No	`"Fabrikam" !endswith "brik"`
`endswith_cs`	RHS is a closing subsequence of LHS	Yes	`"Fabrikam" endswith_cs "kam"`
`!endswith_cs`	RHS isn't a closing subsequence of LHS	Yes	`"Fabrikam" !endswith_cs "brik"`

Syntax

```
Scope | where Field endswith String
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **String**: The string used to filter.

Example

```
dataset=myDataset
| summarize Events=count() by State
| where State endswith "sas"
```

Copy

14.2.8.10. !ENDSWITH

The `!endswith` operator applies a case-sensitive ending string filter and excludes events that match.

The following table compares the `endswith` operators using these abbreviations:

- RHS = right-hand side of the expression
- LHS = left-hand side of the expression

Operator	Description	Case-Sensitive	Example (yields true)
`endswith`	RHS is a closing subsequence of LHS	No	`"Fabrikam" endswith "Kam"`
`!endswith`	RHS isn't a closing subsequence of LHS	No	`"Fabrikam" !endswith "brik"`
`endswith_cs`	RHS is a closing subsequence of LHS	Yes	`"Fabrikam" endswith_cs "kam"`
`!endswith_cs`	RHS isn't a closing subsequence of LHS	Yes	`"Fabrikam" !endswith_cs "brik"`

Syntax

```
Scope | where Field !endswith String
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **String**: The string used to filter.

Example

```
dataset=myDataset
| summarize Events=count() by State
| where State !endswith "is"
```

Copy

14.2.8.11. ENDSWITH_CS

The `endswith_cs` operator applies a case-sensitive ending string filter and returns events that match.

The following table compares the `endswith` operators using these abbreviations:

- RHS = right-hand side of the expression
- LHS = left-hand side of the expression

Operator	Description	Case-Sensitive	Example (yields true)
`endswith`	RHS is a closing subsequence of LHS	No	`"Fabrikam" endswith "Kam"`
`!endswith`	RHS isn't a closing subsequence of LHS	No	`"Fabrikam" !endswith "brik"`
`endswith_cs`	RHS is a closing subsequence of LHS	Yes	`"Fabrikam" endswith_cs "kam"`
`!endswith_cs`	RHS isn't a closing subsequence of LHS	Yes	`"Fabrikam" !endswith_cs "brik"`

Syntax

```
Scope | where Field endswith_cs String
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **String**: The string used to filter.

Example

```
dataset=myDataset
| summarize Events=count() by State
| where State endswith_cs "NA"
```

Copy

14.2.8.12. !ENDSWITH_CS

The `!endswith_cs` operator applies a case-sensitive ending string filter and excludes events that match.

The following table compares the `endswith` operators using these abbreviations:

- RHS = right-hand side of the expression
- LHS = left-hand side of the expression

Operator	Description	Case-Sensitive	Example (yields true)
`endswith`	RHS is a closing subsequence of LHS	No	`"Fabrikam" endswith "Kam"`
`!endswith`	RHS isn't a closing subsequence of LHS	No	`"Fabrikam" !endswith "brik"`
`endswith_cs`	RHS is a closing subsequence of LHS	Yes	`"Fabrikam" endswith_cs "kam"`
`!endswith_cs`	RHS isn't a closing subsequence of LHS	Yes	`"Fabrikam" !endswith_cs "brik"`

Syntax

```
Scope | where Field !endswith_cs String
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **String**: The string used to filter.

Example

```
dataset=myDataset
| summarize Events=count() by State
| where State !endswith_cs "is"
```

Copy

14.2.8.13. Has

The `has` operator applies a case-insensitive string filter and returns events that match.

The following table compares the `has` operators using these abbreviations:

- RHS = right-hand side of the expression
- LHS = left-hand side of the expression

Operator	Description	Case-Sensitive	Example (yields true)
`has`	Right-hand-side (RHS) is a whole term in left-hand-side (LHS)	No	`"North America" has "america"`
`!has`	RHS isn't a full term in LHS	No	`"North America" !has "amer"`
`has_cs`	RHS is a whole term in LHS	Yes	`"North America" has_cs "America"`
`!has_cs`	RHS isn't a full term in LHS	Yes	`"North America" !has_cs "amer"`

Syntax

```
Scope | where Field has String
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **String**: The string used to filter.

Example

```
dataset=myDataset
| summarize event_count=count() by State
| where State has "New"
```

Copy

14.2.8.14. !Has

The `!has` operator applies a case-insensitive string filter and excludes events that match.

The following table compares the `has` operators using these abbreviations:

- RHS = right-hand side of the expression
- LHS = left-hand side of the expression

Operator	Description	Case-Sensitive	Example (yields true)
`has`	Right-hand-side (RHS) is a whole term in left-hand-side (LHS)	No	`"North America" has "america"`
`!has`	RHS isn't a full term in LHS	No	`"North America" !has "amer"`
`has_cs`	RHS is a whole term in LHS	Yes	`"North America" has_cs "America"`
`!has_cs`	RHS isn't a full term in LHS	Yes	`"North America" !has_cs "amer"`

Syntax

```
Scope | where Field !has String
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **String**: The string used to filter.

Example

```
dataset=myDataset
| summarize event_count=count() by State
| where State !has "New"
```

Copy

14.2.8.15. HAS_CS

The `has_cs` operator applies a case-sensitive string filter and returns events that match.

The following table compares the `has` operators using these abbreviations:

- RHS = right-hand side of the expression
- LHS = left-hand side of the expression

Operator	Description	Case-Sensitive	Example (yields true)
`has`	Right-hand-side (RHS) is a whole term in left-hand-side (LHS)	No	`"North America" has "america"`
`!has`	RHS isn't a full term in LHS	No	`"North America" !has "amer"`
`has_cs`	RHS is a whole term in LHS	Yes	`"North America" has_cs "America"`
`!has_cs`	RHS isn't a full term in LHS	Yes	`"North America" !has_cs "amer"`

Syntax

```
Scope | where Field has_cs String
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **String**: The string used to filter.

Example

```
dataset=myDataset
| summarize event_count=count() by State
| where State has_cs "FLORIDA"
```

Copy

14.2.8.16. !HAS_CS

The `!has_cs` operator applies a case-sensitive string filter and excludes events that match.

The following table compares the `has` operators using these abbreviations:

- RHS = right-hand side of the expression
- LHS = left-hand side of the expression

Operator	Description	Case-Sensitive	Example (yields true)
`has`	Right-hand-side (RHS) is a whole term in left-hand-side (LHS)	No	`"North America" has "america"`
`!has`	RHS isn't a full term in LHS	No	`"North America" !has "amer"`
`has_cs`	RHS is a whole term in LHS	Yes	`"North America" has_cs "America"`
`!has_cs`	RHS isn't a full term in LHS	Yes	`"North America" !has_cs "amer"`

Syntax

```
Scope | where Field !has_cs String
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **String**: The string used to filter.

Example

```
dataset=myDataset
| summarize event_count=count() by State
| where State !has_cs "New"
```

Copy

14.2.8.17. HAS_ALL

The `has_all` operator applies one or more case-insensitive string filters and returns events that match.

Syntax

```
Scope | where Field has_all (Expression, ... )
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **Expression**: An expression that specifies the values to search. An expression can be a type value or expression that produces a set of values.

Example

```
dataset=myDataset
| where EpisodeNarrative has_all ("cold", "strong", "afternoon", "hail")
| summarize Count=count() by EventType
```

Copy

14.2.8.18. !HAS_ALL

The `!has_all` operator applies one or more case-insensitive string filters and excludes events that do not match.

Syntax

```
Scope | where Field !has_all (Expression, ... )
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **Expression**: An expression that specifies the values to search. An expression can be a type value or expression that produces a set of values.

Example

```
dataset=myDataset
| where EpisodeNarrative !has_all ("cold", "strong", "afternoon", "hail")
| summarize Count=count() by EventType
```

Copy

14.2.8.19. HAS_ANY

The `has_any` operator applies any case-insensitive string filters and returns events that match.

Syntax

```
Scope | where Field has_any (Expression, ... )
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **Expression**: An expression that specifies the values to search. An expression can be a type value or expression that produces a set of values.

Examples

```
dataset=cribl_search_sample
| where action has_any ("ACCEPT", "REJECT")
| summarize count() by action
```

Copy Run in Cribl Search

```
dataset=myDataset
| where State has_any ("CAROLINA", "DAKOTA", "NEW")
| summarize count() by State
```

Copy

14.2.8.20. !HAS_ANY

The `!has_any` operator applies any case-insensitive string filters and excludes events that do not match.

Syntax

```
Scope | where Field !has_any (Expression, ... )
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **Expression**: An expression that specifies the values to search. An expression can be a type value or expression that produces a set of values.

Example

```
dataset=myDataset
| where State !has_any ("CAROLINA", "DAKOTA", "NEW")
| summarize count() by State
```

Copy

14.2.8.21. HASPREFIX

The `hasprefix` operator applies a case-insensitive starting string filter and returns events that match. Any of the words in the string can have the prefix.

The following table compares the `hasprefix` operators using these abbreviations:

- RHS = right-hand side of the expression
- LHS = left-hand side of the expression

Operator	Description	Case-Sensitive	Example (yields true)
`hasprefix`	RHS is a term prefix in LHS	No	`"North America" hasprefix "ame"`
`!hasprefix`	RHS isn't a term prefix in LHS	No	`"North America" !hasprefix "mer"`
`hasprefix_cs`	RHS is a term prefix in LHS	Yes	`"North America" hasprefix_cs "Ame"`
`!hasprefix_cs`	RHS isn't a term prefix in LHS	Yes	`"North America" !hasprefix_cs "CA"`

Syntax

```
Scope | where Field hasprefix Expression
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **Expression**: The expression for which to search.

Example

```
dataset=myDataset
| summarize Events=count() by State
| where State hasprefix "la"
```

Copy

14.2.8.22. !HASPREFIX

The `!hasprefix` operator applies a case-insensitive starting string filter and excludes events that match. Any of the words in the string can have the prefix.

The following table compares the `hasprefix` operators using these abbreviations:

- RHS = right-hand side of the expression
- LHS = left-hand side of the expression

Operator	Description	Case-Sensitive	Example (yields true)
`hasprefix`	RHS is a term prefix in LHS	No	`"North America" hasprefix "ame"`
`!hasprefix`	RHS isn't a term prefix in LHS	No	`"North America" !hasprefix "mer"`
`hasprefix_cs`	RHS is a term prefix in LHS	Yes	`"North America" hasprefix_cs "Ame"`
`!hasprefix_cs`	RHS isn't a term prefix in LHS	Yes	`"North America" !hasprefix_cs "CA"`

Syntax

```
Scope | where Field !hasprefix Expression
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **Expression**: The expression for which to search.

Example

```
dataset=myDataset
| summarize Events=count() by State
| where State !hasprefix "N"
```

Copy

14.2.8.23. HASPREFIX_CS

The `hasprefix_cs` operator applies a case-sensitive starting string filter and returns events that match. Any of the words in the string can have the prefix.

The following table compares the `hasprefix` operators using these abbreviations:

- RHS = right-hand side of the expression
- LHS = left-hand side of the expression

Operator	Description	Case-Sensitive	Example (yields true)
`hasprefix`	RHS is a term prefix in LHS	No	`"North America" hasprefix "ame"`
`!hasprefix`	RHS isn't a term prefix in LHS	No	`"North America" !hasprefix "mer"`
`hasprefix_cs`	RHS is a term prefix in LHS	Yes	`"North America" hasprefix_cs "Ame"`
`!hasprefix_cs`	RHS isn't a term prefix in LHS	Yes	`"North America" !hasprefix_cs "CA"`

Syntax

```
Scope | where Field hasprefix_cs Expression
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **Expression**: The expression for which to search.

Example

```
dataset=myDataset
| summarize Events=count() by State
| where State hasprefix_cs "P"
```

Copy

14.2.8.24. !HASPREFIX_CS

The `!hasprefix_cs` operator applies a case-sensitive starting string filter and excludes events that match. Any of the words in the string can have the prefix.

The following table compares the `hasprefix` operators using these abbreviations:

- RHS = right-hand side of the expression
- LHS = left-hand side of the expression

Operator	Description	Case-Sensitive	Example (yields true)
`hasprefix`	RHS is a term prefix in LHS	No	`"North America" hasprefix "ame"`
`!hasprefix`	RHS isn't a term prefix in LHS	No	`"North America" !hasprefix "mer"`
`hasprefix_cs`	RHS is a term prefix in LHS	Yes	`"North America" hasprefix_cs "Ame"`
`!hasprefix_cs`	RHS isn't a term prefix in LHS	Yes	`"North America" !hasprefix_cs "CA"`

Syntax

```
Scope | where Field !hasprefix_cs Expression
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **Expression**: The expression for which to search.

Example

```
dataset=myDataset
| summarize Events=count() by State
| where State !hasprefix_cs "P"
```

Copy

14.2.8.25. HASSUFFIX

The `hassuffix` operator applies a case-insensitive ending string filter and returns events that match. Any of the words in the string can have the suffix.

The following table compares the `hassuffix` operators using these abbreviations:

- RHS = right-hand side of the expression
- LHS = left-hand side of the expression

Operator	Description	Case-Sensitive	Example (yields true)
`hassuffix`	RHS is a term suffix in LHS	No	`"North America" hassuffix "ica"`
`!hassuffix`	RHS isn't a term suffix in LHS	No	`"North America" !hassuffix "americ"`
`hassuffix_cs`	RHS is a term suffix in LHS	Yes	`"North America" hassuffix_cs "ica"`
`!hassuffix_cs`	RHS isn't a term suffix in LHS	Yes	`"North America" !hassuffix_cs "icA"`

Syntax

```
Scope | where Field hassuffix Expression
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **Expression**: The scalar or literal expression to search.

Example

```
dataset=myDataset
| summarize event_count=count() by State
| where State hassuffix "o"
```

Copy

14.2.8.26. !HASSUFFIX

The `!hassuffix` operator applies a case-insensitive ending string filter and excludes events that match. Any of the words in the string can have the suffix.

The following table compares the `hassuffix` operators using these abbreviations:

- RHS = right-hand side of the expression
- LHS = left-hand side of the expression

Operator	Description	Case-Sensitive	Example (yields true)
`hassuffix`	RHS is a term suffix in LHS	No	`"North America" hassuffix "ica"`
`!hassuffix`	RHS isn't a term suffix in LHS	No	`"North America" !hassuffix "americ"`
`hassuffix_cs`	RHS is a term suffix in LHS	Yes	`"North America" hassuffix_cs "ica"`
`!hassuffix_cs`	RHS isn't a term suffix in LHS	Yes	`"North America" !hassuffix_cs "icA"`

Syntax

```
Scope | where Field !hassuffix Expression
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **Expression**: The scalar or literal expression to search.

Example

```
dataset=myDataset
| summarize event_count=count() by State
| where State !hassuffix "A"
```

Copy

14.2.8.27. HASSUFFIX_CS

The `hassuffix_cs` operator applies a case-sensitive ending string filter and returns events that match. Any of the words in the string can have the suffix.

The following table compares the `hassuffix` operators using these abbreviations:

- RHS = right-hand side of the expression
- LHS = left-hand side of the expression

Operator	Description	Case-Sensitive	Example (yields true)
`hassuffix`	RHS is a term suffix in LHS	No	`"North America" hassuffix "ica"`
`!hassuffix`	RHS isn't a term suffix in LHS	No	`"North America" !hassuffix "americ"`
`hassuffix_cs`	RHS is a term suffix in LHS	Yes	`"North America" hassuffix_cs "ica"`
`!hassuffix_cs`	RHS isn't a term suffix in LHS	Yes	`"North America" !hassuffix_cs "icA"`

Syntax

```
Scope | where Field hassuffix_cs Expression
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **Expression**: The scalar or literal expression to search.

Example

```
dataset=myDataset
| summarize event_count=count() by State
| where State hassuffix_cs "AS"
```

Copy

14.2.8.28. !HASSUFFIX_CS

The `!hassuffix_cs` operator applies a case-sensitive ending string filter and excludes events that match. Any of the words in the string can have the suffix.

The following table compares the `hassuffix` operators using these abbreviations:

- RHS = right-hand side of the expression
- LHS = left-hand side of the expression

Operator	Description	Case-Sensitive	Example (yields true)
`hassuffix`	RHS is a term suffix in LHS	No	`"North America" hassuffix "ica"`
`!hassuffix`	RHS isn't a term suffix in LHS	No	`"North America" !hassuffix "americ"`
`hassuffix_cs`	RHS is a term suffix in LHS	Yes	`"North America" hassuffix_cs "ica"`
`!hassuffix_cs`	RHS isn't a term suffix in LHS	Yes	`"North America" !hassuffix_cs "icA"`

Syntax

```
Scope | where Field !hassuffix_cs Expression
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **Expression**: The scalar or literal expression to search.

Example

```
dataset=myDataset
| summarize event_count=count() by State
| where State !hassuffix_cs "AS"
```

Copy

14.2.8.29. In

The `in` operator applies a case-sensitive string or regex literal filter.

The following table provides a comparison of the `in` operators:

Operator	Description	Case-Sensitive	Example (yields true)
`in`	Equal to one of the events	Yes	`"abc" in ("123", "345", "abc")`
`!in`	Not equal to any of the events	Yes	`"bca" !in ("123", "345", "abc")`
`in~`	Equal to any of the events	No	`"Abc" in~ ("123", "345", "abc")`
`!in~`	Not equal to any of the events	No	`"bCa" !in~ ("123", "345", "ABC")`

Syntax

```
Scope | where Field in (Expression, ... )
```

Or:

```
Scope in ListOfValues
```

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **Expression**: An expression that specifies the values to search. An expression can be a type value, an expression that produces a set of values, or a regex literal expression that returns a `bool` value.

  To pass regex literals as **Expression** arguments, see syntax details at Regex Examples, Regex Flags, and Disambiguate Regex Characters.

- **ListOfValues** Comma-separated list of one or more `StringExpressions`. For example, `(StringExpression, StringExpression, ...)`.

Example

The following query shows how to use `in` with a list of values.

```
dataset=myDataset
 | where State in ("FLORIDA", "GEORGIA", "NEW YORK")
 | count
```

Copy

Filter the `logs` Dataset for `host` fields that have a case-sensitive match in the `foo` query.

```
let foo =dataset="$vt_dummy" event < 3
 | extend x = case(
    event == 0, dynamic({"method": "GET"}),
    event == 1, dynamic({"method": "POST"}),
    dynamic({"method": "PATCH"})
    );

dataset="cribl_internal_logs"
| where  method in foo.x.method
```

Copy

You can also bind a `let` variable to a `dynamic(...)` array or scalar and reference it directly in the `in` list. See Dynamic Values in `in` Operators for details.

```
let allowedMethods = dynamic(["GET", "POST", "PUT"]);

dataset="cribl_search_sample"
 | where method in (allowedMethods)
```

Copy Run in Cribl Search

14.2.8.30. !In

The `!in` operator applies a case-sensitive string or regex literal filter, and excludes events that match the specified criteria.

The following table provides a comparison of the `in` operators:

Operator	Description	Case-Sensitive	Example (yields true)
`in`	Equal to one of the events	Yes	`"abc" in ("123", "345", "abc")`
`!in`	Not equal to any of the events	Yes	`"bca" !in ("123", "345", "abc")`
`in~`	Equal to any of the events	No	`"Abc" in~ ("123", "345", "abc")`
`!in~`	Not equal to any of the events	No	`"bCa" !in~ ("123", "345", "ABC")`

Syntax

```
Scope | where Field !in (Expression, ... )
```

Or:

```
Scope !in ListOfValues
```

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **Expression**: An expression that specifies the values to search. An expression can be a type value, an expression that produces a set of values, or a regex literal expression that returns a `bool` value.

  To pass regex literals as **Expression** arguments, see syntax details at Regex Examples, Regex Flags, and Disambiguate Regex Characters.

- **ListOfValues** Comma-separated list of one or more `StringExpressions`. For example, `(StringExpression, StringExpression, ...)`.

Example

The following query shows how to use `!in` with a list of values.

```
dataset=myDataset
  | where State !in ("FLORIDA", "GEORGIA", "NEW YORK")
  | count
```

Copy

Filter the `logs` Dataset for `host` fields that don't have a case-sensitive match in the `foo` query.

```
let foo = dataset=api
  | summarize count=count() by hostname

dataset=logs
  | where host !in foo.hostname
```

Copy

You can also bind a `let` variable to a `dynamic(...)` array or scalar and reference it directly in the `!in` list. See Dynamic Values in `in` Operators for details.

```
let errorStatuses = dynamic([404, 500]);

dataset="cribl_search_sample"
 | where status !in (errorStatuses)
```

Copy Run in Cribl Search

14.2.8.31. In~

The `in~` operator applies a case-insensitive string or regex literal filter.

The following table provides a comparison of the `in` operators:

Operator	Description	Case-Sensitive	Example (yields true)
`in`	Equal to one of the events	Yes	`"abc" in ("123", "345", "abc")`
`!in`	Not equal to any of the events	Yes	`"bca" !in ("123", "345", "abc")`
`in~`	Equal to any of the events	No	`"Abc" in~ ("123", "345", "abc")`
`!in~`	Not equal to any of the events	No	`"bCa" !in~ ("123", "345", "ABC")`

Syntax

```
Scope | where Field in~ (Expression, ... )
```

Or:

```
Scope in~ ListOfValues
```

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **Expression**: An expression that specifies the values to search. An expression can be a type value, an expression that produces a set of values, or a regex literal expression that returns a `bool` value.

  To pass regex literals as **Expression** arguments, see syntax details at Regex Examples, Regex Flags, and Disambiguate Regex Characters.

- **ListOfValues** Comma-separated list of one or more `StringExpressions`. For example, `(StringExpression, StringExpression, ...)`.

Example

The following query shows how to use `in~` with a list of values.

```
dataset=myDataset
  | where State in~ ("FLORIDA", "GEORGIA", "NEW YORK")
  | count
```

Copy

Filter the `logs` Dataset for `host` fields that have a case-insensitive match in the `foo` query.

```
let foo = dataset=api
  | summarize count=count() by hostname

dataset=logs
  | where host in~ foo.hostname
```

Copy

You can also bind a `let` variable to a `dynamic(...)` array or scalar and reference it directly in the `in~` list. See Dynamic Values in `in` Operators for details.

```
let allowedMethods = dynamic(["get", "post"]);

dataset="cribl_search_sample"
 | where method in~ (allowedMethods)
```

Copy Run in Cribl Search

14.2.8.32. !In~

The `!in~` operator applies a case-insensitive string or regex literal filter, and excludes events that match the specified criteria.

The following table provides a comparison of the `in` operators:

Operator	Description	Case-Sensitive	Example (yields true)
`in`	Equal to one of the events	Yes	`"abc" in ("123", "345", "abc")`
`!in`	Not equal to any of the events	Yes	`"bca" !in ("123", "345", "abc")`
`in~`	Equal to any of the events	No	`"Abc" in~ ("123", "345", "abc")`
`!in~`	Not equal to any of the events	No	`"bCa" !in~ ("123", "345", "ABC")`

Syntax

```
Scope | where Field !in~ (Expression, ... )
```

Or:

```
Scope !in~ ListOfValues
```

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **Expression**: An expression that specifies the values to search. An expression can be a type value, an expression that produces a set of values, or a regex literal expression that returns a `bool` value.

  To pass regex literals as **Expression** arguments, see syntax details at Regex Examples, Regex Flags, and Disambiguate Regex Characters.

- **ListOfValues** Comma-separated list of one or more `StringExpressions`. For example, `(StringExpression, StringExpression, ...)`.

Example

The following query shows how to use `!in~` with a list of values.

```
dataset=myDataset
  | where State !in~ ("FLORIDA", "GEORGIA", "NEW YORK")
  | count
```

Copy

Filter the `logs` Dataset for `host` fields that don't have a case-insensitive match in the `foo` query.

```
let foo = dataset=api
  | summarize count=count() by hostname

dataset=logs
  | where host !in~ foo.hostname
```

Copy

You can also bind a `let` variable to a `dynamic(...)` array or scalar and reference it directly in the `!in~` list. See Dynamic Values in `in` Operators for details.

```
let excludedMethods = dynamic(["delete", "options"]);

dataset="cribl_search_sample"
 | where method !in~ (excludedMethods)
```

Copy Run in Cribl Search

14.2.8.33. Matches Regex

The `matches regex` operator applies a case-sensitive regex, or a regex literal (with specified case-sensitivity), and returns events that match.

Syntax

```
Scope | where Field matches regex Expression
```

Copy

For detailed syntax, see Regex Flags and Disambiguate Regex Characters.

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **Expression**: The string or regex literal to search.

Examples

Match a string, with wildcard:

```
dataset=myDataset
| summarize event_count=count() by State
| where State matches regex "K.*S"
```

Copy

Match a regex literal (all `POST` requests, case-insensitive):

```
dataset="cribl_internal_logs" method=*
| limit 1000
| where method matches regex /^po.*/i
```

Copy Run in Cribl Search



For further examples using the `where` operator, see Regex Examples.

14.2.8.34. STARTSWITH

The `startswith` operator applies a case-insensitive string starting sequence filter and returns events that match.

The following table compares the startswith operators using these abbreviations:

- RHS = right-hand side of the expression
- LHS = left-hand side of the expression

Operator	Description	Case-Sensitive	Example (yields true)
`startswith`	RHS is an initial subsequence of LHS	No	`"Fabrikam" startswith "fab"`
`!startswith`	RHS isn't an initial subsequence of LHS	No	`"Fabrikam" !startswith "kam"`
`startswith_cs`	RHS is an initial subsequence of LHS	Yes	`"Fabrikam" startswith_cs "Fab"`
`!startswith_cs`	RHS isn't an initial subsequence of LHS	Yes	`"Fabrikam" !startswith_cs "fab"`

Syntax

```
Scope | where Field startswith String
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **String**: The string used to filter.

Example

```
dataset=myDataset
| summarize event_count=count() by State
| where State startswith "Lo"
```

Copy

14.2.8.35. !STARTSWITH

The `!startswith` operator applies a case-insensitive string starting sequence filter and excludes events that match.

The following table compares the startswith operators using these abbreviations:

- RHS = right-hand side of the expression
- LHS = left-hand side of the expression

Operator	Description	Case-Sensitive	Example (yields true)
`startswith`	RHS is an initial subsequence of LHS	No	`"Fabrikam" startswith "fab"`
`!startswith`	RHS isn't an initial subsequence of LHS	No	`"Fabrikam" !startswith "kam"`
`startswith_cs`	RHS is an initial subsequence of LHS	Yes	`"Fabrikam" startswith_cs "Fab"`
`!startswith_cs`	RHS isn't an initial subsequence of LHS	Yes	`"Fabrikam" !startswith_cs "fab"`

Syntax

```
Scope | where Field !startswith String
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **String**: The string used to filter.

Example

```
dataset=myDataset
| summarize event_count=count() by State
| where State !startswith "Lo"
```

Copy

14.2.8.36. STARTSWITH_CS

The `startswith_cs` operator applies a case-sensitive string starting sequence filter and returns events that match.

The following table compares the startswith operators using these abbreviations:

- RHS = right-hand side of the expression
- LHS = left-hand side of the expression

Operator	Description	Case-Sensitive	Example (yields true)
`startswith`	RHS is an initial subsequence of LHS	No	`"Fabrikam" startswith "fab"`
`!startswith`	RHS isn't an initial subsequence of LHS	No	`"Fabrikam" !startswith "kam"`
`startswith_cs`	RHS is an initial subsequence of LHS	Yes	`"Fabrikam" startswith_cs "Fab"`
`!startswith_cs`	RHS isn't an initial subsequence of LHS	Yes	`"Fabrikam" !startswith_cs "fab"`

Syntax

```
Scope | where Field startswith_cs String
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **String**: The string used to filter.

Example

```
dataset=myDataset
| summarize event_count=count() by State
| where State startswith_cs "Lo"
```

Copy

14.2.8.37. !STARTSWITH_CS

The `!startswith_cs` operator applies a case-sensitive string starting sequence filter and excludes events that match.

The following table compares the startswith operators using these abbreviations:

- RHS = right-hand side of the expression
- LHS = left-hand side of the expression

Operator	Description	Case-Sensitive	Example (yields true)
`startswith`	RHS is an initial subsequence of LHS	No	`"Fabrikam" startswith "fab"`
`!startswith`	RHS isn't an initial subsequence of LHS	No	`"Fabrikam" !startswith "kam"`
`startswith_cs`	RHS is an initial subsequence of LHS	Yes	`"Fabrikam" startswith_cs "Fab"`
`!startswith_cs`	RHS isn't an initial subsequence of LHS	Yes	`"Fabrikam" !startswith_cs "fab"`

Syntax

```
Scope | where Field !startswith_cs String
```

Copy

Arguments

- **Scope**: The input tabular result set to filter.
- **Field**: The field to filter.
- **String**: The string used to filter.

Example

```
dataset=myDataset
| summarize event_count=count() by State
| where State !startswith_cs "Lo"
```

Copy

14.3. Commands

Run commands, and `set`-statement options, from the query box to manage searches.

Cribl Search supports the following commands:

- `.cancel` - Stop queued, running, or all queued and running searches.
- `.clear` - Disable `set`-statement options.
- `.generate` - Produce statistics about the results of a search.
- `.show` - List objects in a Dataset, set-statement options or searches.

Commands can be combined with the following literals:

- `objects` - List the contents of a Dataset before you search it.
- `options` - View `set`-statement options configured for your account.
- `stats`
- `queries` - List queued, running, or all queued and running searches run by all users or specific users.



Runnable Kusto code examples include a **Run in Cribl Search** link in the top-right corner of the code block. Select it to open the query in your Cribl Search environment with the query loaded and ready to execute. You can also use the **Copy** button to copy a query and paste it into your own search.

Basic Command Usage

Unlike functions and operators, commands start with a period. For example:

```
.show objects
```

Copy

How commands work depends on your Search Member Permissions. For example, **User** Search Members can manage only their own searches, but **Admin** Search Members can manage the searches of all users in the organization.

You can combine commands with operators. For example, to show queued queries that were created more than 10 minutes ago:

```
.show queued queries
 | where timeCreated < ago(10min)
```

Copy | Run in Cribl Search

However, you can't use commands in subqueries. For example, this won't work:

```
// invalid example
let stage1 = .show objects(cribl_search_sample);
```

Copy

For more transparency, you can provide a reason why you're using a particular command. The reason will be added to the Cribl Search audit log. For example:

```
.cancel running queries with(reason = "Time is up.")
```

Copy | Run in Cribl Search

Manage Searches with Commands

You can manage your or your users' searches straight from the query box, using the following commands:

- `.show queries` - View searches based on their IDs, status, or the users running them.
- `.cancel` - Cancel queued or running searches.

View Searches

To display searches based on their IDs, status, or the users running them, use the `.show queries` command.

User and **Editor** Search Members can view only their own searches. **Admin** Search Members can view the searches of all users in the organization.

To view all queued or running searches:

```
.show queries
```

Copy | Run in Cribl Search

To view all queued searches:

```
.show queued queries
```

Copy | Run in Cribl Search

To view searches that are being run by specific users:

```
.show running queries by user "Jane*"
```

Copy | Run in Cribl Search

The results are not affected by the set time range.

Cancel Searches

To stop queued or running searches, use the `.cancel` command.

User and **Editor** Search Members can cancel only their own searches. **Admin** Search Members can cancel the searches of all users in the organization.

To cancel a specific search:

```
.cancel query "1693827597495.ji5y5g"
```

Copy

To cancel searches that are queued or being run by specific users:

```
.cancel queries by user("John Doe", "Jane*")
```

Copy | Run in Cribl Search

To cancel all currently running searches:

```
.cancel running queries
```

Copy | Run in Cribl Search

The results are not affected by the set time range.

Manage Set-Statement Options with Commands

You can manage your or your users' `set`-statement options straight from the query box, using the following commands:

- `.clear options` - Disable `set`-statement options.
- `.show options` - View `set`-statement options configured for your account.

View Set-Statement Options

To see `set`-statement options configured for your account, use the `.show options` command.

To view all options configured for you:

```
.show options
```

Copy | Run in Cribl Search

To view only those options that are **not** overridden by other settings:

```
.show active options
```

Copy | Run in Cribl Search

Disable Set-Statement Options

To disable `set`-statement options, use the `.clear options` command.

To disable all options configured for your own account:

```
.clear options
```

Copy

As an Admin Search Member, to disable all options for all users in the usage group:

```
.clear global options
```

Copy

14.3.1. .Cancel

The `.cancel` command stops queued, running, or all queued and running searches.

`.cancel` ignores the set time range.

```
// cancel all running searches
.cancel running queries with(reason = "Time is up.")
```

Copy | Run in Cribl Search

Purpose

Use `.cancel` to manage system resources and optimize performance by terminating queries that are no longer needed, taking too long, consuming too many resources, or made in error.

Permissions

Search Member Type	Permissions
Admin	Can cancel all searches in their Organization.
Editor or User	Can cancel only their own searches.

Syntax

```
.cancel query SearchId
              [with(reason = CancellationReason)]`
```

Copy

Or:

```
.cancel Status queries
               [by user (User[, ...])]
               [with(reason = CancellationReason)]
```

Copy

You can also combine this command with operators.

Parameters

Parameter	Type	Description
`SearchId`	`string`	The ID of the search to cancel.
`CancellationReason`	`string`	The reason for running the `.cancel` command, which is added to the Cribl Search audit log.
`Status`	`string`	The status of the queries to cancel: • `queued`: Cancel only queued searches. • `running`: Cancel only running searches. • `all` or `*`: Cancel both queued and running searches.
`User`	`string`	The name of the user whose searches you want to cancel.

Returns

Returns information about the canceled searches.

Examples

Cancel a specific search.

```
.cancel query "1693827597495.ji5y5g"
```

Copy

Cancel searches queued or being run by specific users.

```
.cancel queries by user("John Doe", "Jane*") with(reason = "I don't need these searcl
```

Copy

Cancel all searches started by users whose names start with `John` or `Jane`.

```
.cancel queries by user("John*", "Jane*") with(reason = "Cleaning up.")
```

Copy Run in Cribl Search

Cancel queued searches that were created more than 10 minutes ago.

```
.cancel queued queries
 | where timeCreated < ago(10min)
```

Copy Run in Cribl Search

14.3.2. .Show

The `.show` command can be used with:

- `objects` literal to list objects included in a Dataset, including files, tables, and endpoints, along with information about each object. The results are filtered by the set time range.
- `options` literal to list `set`-statement options configured for your account.
- `queries` literal to list queued, running, or all pending (queued and running) searches. You can limit the list to only searches run by a specific user.

```
// list all objects in the cribl_search_sample Dataset
.show objects(cribl_search_sample)
```

Copy Run in Cribl Search

14.3.3. .Clear

The `.clear` command is used with the `options` literal to disable `set`-statement options.

```
// disable all set-statement options configured for your account
.clear options
```

Copy Run in Cribl Search

14.3.4. .Generate

The `.generate` command is used with the `stats` literal to produce statistics about the results of a search.

```
// produce statistics for the search 1749594773597.yzoXZy, if available to the currer
.generate stats job("1749594773597.yzoXZy")
```

Copy

14.3.5. Objects

The `objects` literal is used with the `.show` command to list objects included in a Dataset, including files, tables, and endpoints, along with information about each object. The results are filtered by the set time range.



Cribl Edge Datasets are not supported.

Purpose

Use `.show objects` to get detailed information about the contents of a Dataset before you search it.

Permissions

Search Member Type	Permissions
Admin	Can see the objects of all Datasets in their organization.
Editor	Can see the objects of only those Datasets that they created themselves or that were shared with them.
User	Can see the objects of only those Datasets that were shared with them.

Syntax

```
.show objects(DatasetID[, ...])
            [with(reason = "InvestigationReason")]`
```

Copy

You can also combine this command with operators.

Parameters

Parameter	Type	Description
`DatasetID`	`string`	The ID of the Dataset whose objects you want to list. Separate multiple Dataset IDs with a comma `,`. Wildcards `*` are supported at the end or in the middle of an ID, as in `cribl_*_logs*`.

Parameter	Type	Description
`InvestigationReason`	`string`	The reason for running the `.show objects` command, which is added to the Cribl Search audit log.

Returns

The `.show objects` command returns a list of files, tables, endpoints, metrics, and any other units that the specified Dataset contains. Each object in the Dataset is represented by one row in the results table.

The details about each object vary according to which objects the Dataset contains. Depending on the Dataset, the results may include the following details:

Field	Description
`_time`	The `.show objects` command's execution time. It's the same for every returned object.
`success`	Shows whether the command was successful.
`dataset`	The ID of the examined Dataset.
`datasetType`	The type of the examined Dataset.
`name`	The name of the object.
`size`	The size of the object in bytes.
`lastModified`	The object's last modification time.

Examples

List all objects in the `cribl_internal_logs` and `cribl_search_sample` Datasets.

```
.show objects(cribl_internal_logs, cribl_search_sample)
```

Copy Run in Cribl Search

List the five largest objects in the `cribl_internal_logs` Dataset.

```
.show objects(cribl_internal_logs) | top 5 by size
```

Copy Run in Cribl Search

See how many objects larger than 50,000 bytes exist in all Datasets whose IDs start with `cribl_int`.

```
.show objects(cribl_int*)
    with(reason = "Investigating number of large objects")
    | where size > 50000 | count
```

Copy | Run in Cribl Search

14.3.6. Options

The `options` literal can be used with:

- `.clear` command to disable `set`-statement options.
- `.show` command to list `set`-statement options configured for your account.

Show Options

Use `.show options` to get a list of `set`-statement options that you, or an Admin Search Member, have configured for your account. This command lets you:

- See the values of the options.
- Find out which options are active and which are overridden by other settings.
- Identify which options were set by you and which were set the Search Admin.

Permissions

All Search Members can see all `set`-statement options that apply to their own account.

Syntax

```
.show [Scope] options
              [with(reason = "InvestigationReason")]`
```

Copy

Parameters

Parameter	Type	Description
`Scope`	`string`	Scope for listing the options: • `all` or `*`: List all options configured for your account. • `active`: List only those options that may affect your searches at the moment (that is, options that are not being overridden by other settings).
`InvestigationReason`	`string`	The reason for running the `.show options` command, which is added to the Cribl Search audit log.

Returns

Returns a list of `set`-statement options configured for your account. The results include the following details:

Field	Description
`_time`	Execution time of the `.show options` command.
`success`	`true` if the `.show options` command was successful.
`option`	The name of the `set`-statement option.
`value`	The value of the option.
`source`	The scope in which the option was set.
`active`	`true` if the option affects your searches. `false` if the option doesn't affect you at the moment because it's being overridden by another setting.

Examples

See all `set`-statement options that affect you at the moment.

```
.show active options
            with(reason = "Just checking options active for my account.")
```

Copy | Run in Cribl Search

Clear Options

Use `.clear options` to disable options that were configured by `set` statements.

To see which `set`-statement options affect your account at the moment before running `.clear options`, use the `.show options` command.

Permissions

Search Member Type	Permissions
Admin	Can disable any options configured for any scope.
Editor or User	Can disable only those options that they configured themselves.

Syntax

```
.clear [Scope] options
               [with(reason="DeactivationReason")]`
```

Copy

Parameters

Parameter	Type	Description
`Scope`	`string`	Scope of deactivation: • `user` (default): Deactivate all options that the current user set for their own account. • `global` (Admin only): Deactivate all options set for all users in the matching Usage Group. • `all` (Admin only): Deactivate according to both the `user` and `global` scopes.
`DeactivationReason`	`string`	A `string` that provides a reason for disabling the options, to add to the Cribl Search audit log.

Returns

Returns a single event that confirms the options are disabled.

Examples

Disable all `set`-statement options configured for your own account.

```
.clear user options
           with(reason = "Clearing all my options.")
```

Copy

Disable all `set`-statement options of all users in the Usage Group.

```
// Admin only
.clear global options
              with(reason = "Clearing all options for my users.")
```

Copy

Disable all `set`-statement options, both for your own account and for all users in the Usage Group.

```
// Admin only
.clear all options
          with(reason = "Clearing all options for me and my users.")
```

Copy

14.3.7. Stats

The `stats` literal is used with the `.generate` command to produce statistics about the results of a search.

Purpose

A standard Cribl Search query generates two types of statistics about its result set:

- **Timeline stats**: Distribution of data over time, such as the number of events per time bucket, or the earliest and latest timestamps in the result set. You can see these stats in the histogram of the search results.
- **Field stats**: Distribution of data across fields, such as the number of unique values in a field, or the minimum and maximum values of a field. You can see these stats in the field browser of the search results.

Certain types of searches (for example, Dashboard or scheduled searches) don't generate these statistics by default, to optimize performance.

The `.generate stats` command allows you to generate these statistics for any search, without having to rerun the search itself.

Permissions

Search Member Type	Permissions
Admin	Can generate stats for all searches in the Organization.
Editor or User	Can generate stats for public searches, or searches that they ran themselves.

Syntax

```
.generate [timeline|field|all] stats("SearchId") [force] [with(reason = "Investigatic
```

Copy

Parameters

Parameter	Required	Description
`timeline` or `field` or `all`	No	Type of statistics to generate. Use `timeline` for timeline stats, `field` for field stats, or `all` for both. If omitted, defaults to `all`.
`SearchId`	Yes	The ID of the search for which to generate statistics. Doesn't support wildcards.
`force`	No	Force the (re)generation of stats even if they were already generated.
`Investigation Reason`	No	The reason for running the command, added to the Cribl Search audit log.

Returns

Returns a message indicating whether the statistics were successfully generated or not.

If the search ID is invalid or the user doesn't have permission to access the search, returns an error message.

Examples

Generate timeline statistics for a search, overwriting any existing stats.

```
.generate timeline stats("1749594773597.yzoXZy") force with (reason="I have my reasor
```

Copy

14.3.8. Queries

The `queries` literal is used with the `.show` command to list queued, running, or all pending (queued and running) searches. You can limit the list to only searches run by a specific user.

Purpose

Use `.show queries` to monitor search status, track individual and overall search performance, and identify searches that are taking longer than expected. This command is especially useful in multi-user environments.

Permissions

Search Member Type	Permissions
Admin	Can see all searches in their Organization.
Editor or User	Can see only those searches that they ran themselves or that were shared with them.

Syntax

```
.show [Status] queries
              [by user User]
              [with(reason = "InvestigationReason")]`
```

Copy

You can also combine this command with operators.

Parameters

Parameter	Type	Description
`Status`	`string`	The status of the queries to list: • `queued`: Show only queued searches. • `running`: Show only running searches. • `all` or `*` (default): Show both queued and running searches.

Parameter	Type	Description
`User`	`string`	The names of the user whose queries you want to list.
`InvestigationReason`	`string`	The reason for running the `.show queries` command, which is added to the Cribl Search audit log.

Returns

Returns the details of the specified searches.

Examples

Each of these queries demonstrates runnable syntax, but this command will return results only if you have pending queries in a state matching the `Status` parameter.

Show all running searches:

```
.show running queries with(reason = "Checking what's taking so long.")
```

Copy | Run in Cribl Search

Show searches queued by specific users:

```
.show queued queries by user "John*" with(reason = "Just checking.")
```

Copy

Show searches being run by specific users:

```
.show running queries by user "John*" with(reason = "Thinking of resources.")
```

Copy

14.4. Statements

A list of special statements supported by Cribl Search.

A statement in Cribl Search is a special keyword that sets options (`set`) or assigns names to expressions (`let`).

Name	Description
`let`	Assigns a referenceable name to a value, expression, or an entire subquery.
`set`	Configures options that affect one or more searches.

14.4.1. Let

The `let` statement assigns a name to a value, expression, or an entire query.

You can then reference that name in the context of the same search. This allows you to write more complex queries that consist of several stages and can reuse their results.

`let` statements are often used together with the `join` and `union` operators.



You can also perform unions and joins by using inline subqueries.

Syntax

```
let Name = Expression;
```

Each `let` statement needs to end with a semicolon (`;`).

Arguments

- **Name**: String. The name to assign to the **Expression**. Spaces ( ), and the keyword `root` are not allowed.
- **Expression**: The value to assign to the **Name**. Can be a single value, an expression, or an entire query.

A `let` variable must resolve to a scalar (such as a number or string) to be referenced in most query positions. The exception is in `in`, `!in`, `in~`, and `!in~` lists, where a `let` variable bound to a `dynamic(...)` value is also allowed. For details, see Dynamic Values in `in` Operators.

Examples

Return no more than 1000 events.

```
let x = 1000;

dataset="cribl_search_sample"
 | limit x
```

Copy | Run in Cribl Search

Find all VPC flow logs in the `cribl_search_sample` Dataset that are DNS-related requests.

```
// returns 1 record (a scalar)
let dns = dataset="cribl_lookups" lookup_table="service_names_port_numbers" service_r

dataset="cribl_search_sample" dataSource='vpcflowlogs'
 | where dstport == dns.port_number
```

Copy Run in Cribl Search

Join internal Cribl logs related to HTTP requests with a Dataset containing HTTP status codes.

```
let codeMap = dataset=$vt_dummy event < 4
 | extend x =
   case(event == 0, dynamic({"status": 200, "text": 'OK'}),
        event == 1, dynamic({"status": 308, "text": 'Redirect'}),
        event == 2, dynamic({"status": 404, "text": 'Not found'}),
                    dynamic({"status": 500, "text": 'Internal Error'}))
 | project status=x.status, statusText=x.text;

dataset="cribl_internal_logs" method status
 | where isnotnull(status)
 | join kind=leftouter codeMap on status
```

Copy Run in Cribl Search

Calculate the 95th percentile of requests in the Cribl internal logs.

```
let num_percentile = 95;

let response_time_percentile = dataset="cribl_internal_logs" method status response_t
 | summarize total=count(), response_time=percentile(response_time, num_percentile);

let long_responses = dataset="cribl_internal_logs" method status response_time
 | where response_time > response_time_percentile.response_time
 | summarize count=count(), maxResponseTime=max(response_time);

print strcat('There are ', long_responses.count, ' requests in the ', num_percentile,
```

Copy Run in Cribl Search

Dynamic Values in `in` Operators

You can bind a `let` variable to a `dynamic(...)` array or scalar and reference it in the value list of `in`, `!in`, `in~`, or `!in~`. This lets you build reusable allow lists and block lists without retyping the values.

The variable must be a simple identifier (no field paths or function calls), and its value must be a `dynamic(...)` literal or another `let` variable that resolves to a scalar literal.

Filter on a list of values stored in a `let` variable:

```
let allowedMethods = dynamic(["GET", "POST", "PUT"]);

dataset="cribl_search_sample"
 | where method in (allowedMethods)
```

Copy Run in Cribl Search

Use a numeric array with `!in` to exclude specific status codes:

```
let errorStatuses = dynamic([404, 500]);

dataset="cribl_search_sample"
 | where status !in (errorStatuses)
```

Copy Run in Cribl Search

Mix a `let` variable with literal values in the same list:

```
let extraMethods = dynamic(["GET"]);

dataset="cribl_search_sample"
 | where method in (extraMethods, "POST", "PUT")
```

Copy Run in Cribl Search

Use case-insensitive matching with `in~`. The `let` value is lowercase, but `in~` still matches uppercase field values such as `GET` and `POST`:

```
let allowedMethods = dynamic(["get", "post"]);

dataset="cribl_search_sample"
 | where method in~ (allowedMethods)
```

Copy Run in Cribl Search

14.4.2. Set

The `set` statement configures options that affect one or more searches.

```
// return no more than 1000 results in this search
set max_results_per_search=1000;
```

Copy | Run in Cribl Search

Purpose

Use `set` statements to control search behavior. For example, you can configure how long the current search can run before getting canceled, or set the default maximum time range for each of your searches.



Use `set` statements carefully and always make sure you understand the option that you want to change. If in doubt, read the docs, or contact the Cribl Support team.

To see which `set`-statement options affect your account at the moment, use the `.show options` command.

To disable `set`-statement options, use the `.clear options` command.

Syntax

```
set [Scope:]OptionName=OptionValue [, ...];
```

Copy

Each `set` statement needs to end with a semicolon `;`.

Parameters

Parameter	Description
`Scope`	The scope to which the option will apply. Can be either `user:` or `global:` (only when set by Admin Search Members). When omitted, affects only the current search.
`OptionName`	The name of the option to set.
`OptionValue`	The value of the option to set.

Scope of Set Statements

You can apply `set` statements in the following scopes:

Scope	Example	Impact	Can be set by
Single search	`set max_results_per_search=1000;`	Applies only to the current search. Depending on the permissions, can override user settings and Usage Group settings.	All Search Members
`user:`	`set user:max_results_per_search=1000;`	Applies to every search by the current user. Depending on the permissions, can override Usage Group settings.	All Search Members
`global:`	`set global:max_results_per_search=1000;`	Applies to every search by every member of the Usage Group.	Admin Search Members

Depending on your permissions and the options specified, `set` statements can also override certain Cribl Search settings, limits, and Usage Group configurations.

A single `set` statement can apply multiple options to multiple scopes at once. For example:

```
set global:max_executors=10, user:max_bytes_read_per_search=536870912, max_resu
```

Copy

Returns

Search results are returned as usual, but with the specified settings applied.

The settings that were applied to a search are always logged in that search's details, under **set options**.

Examples

Set the maximum number of results to 100,000.

```
set max_results_per_search=100000;

dataset="cribl_internal_logs"
```

Copy | Run in Cribl Search

If an analogous search ran within the last 10 minutes, automatically reuse its results instead of running the same search again.

```
set allow_previous_results="10min";

dataset="cribl_internal_logs" method status
| summarize count() by method, status
```

Copy | Run in Cribl Search

Available Set-Statement Options

The `set` statement accepts the following options.

allow_incomplete_results

Enable querying uncompleted search jobs.

When you set this property to `true`, the `$vt_results` virtual table will enable querying the results of jobs that ended in `failed` or `canceled` status. (By default, `$vt_results` allows reading only successfully completed jobs.)

When you set this property to `true`, the output will contain a `jobStatus` property, in addition to the original data fields. Usage example:

```
set allow_incomplete_results=true;
dataset="$vt_results" jobId=<some-ID>
```

Copy

You can set this option to one of the following:

Setting	Behavior
`false` or `"no"` or `0` (default)	Disable querying `failed` or `canceled` search results.

Setting	Behavior
`true` or `"yes"` or `1`	Enable querying `failed` or `canceled` search results.

allow_previous_results

Automatically reuse the results of analogous searches that were run in the specified time range.

You can set this option to a time string such as `1h` (1 hour), `10min` (10 minutes), or `10` (10 seconds).

```
// allow this search to reuse analogous search results from the last 10 minutes
set allow_previous_results="10min";

// allow my every search to reuse analogous search results from the last 10 minutes
set user:allow_previous_results="10min";

// (admin only) allow every user to reuse analogous search results from the last 10 m
set global:allow_previous_results="10min";
```

Copy

disable_previews

Disable generating preview of search results.

Certain Cribl Search functions generate preliminary results that get replaced as the search scans more data. This way, you quickly can see initial search results. The `disable_previews` option suppresses generating those previews, which, in certain scenarios, may speed the overall search up and get you the final results faster.

You can set this option to one of the following:

Setting	Behavior
`false` or `"no"` or `0` (default)	If possible, generate the preview of the search results.
`true` or `"yes"` or `1`	Don't generate the preview of the search results.

For example:

```
// in this search, don't generate the preview of the results
set disable_previews=true;

// in all your searches, don't generate previews
set user:disable_previews=1;

// (admin only) disable previews for all searches run by any user
set global:disable_previews="yes";
```

Copy

job_visibility

Set the default visibility of the search and its results.

You can also change the visibility of a search in **Actions** > **Results Access**.

You can set this option to one of the following:

Setting	Who can see the search and its results
`private` (default)	Only you and the Search Admin. Same as **Private**.
`public`	Everyone in your Organization. Same as **All Members**.

For example:

```
// make this search visible only to you and the Search Admin
set job_visibility="private";

// make all your searches visible to everyone
set user:job_visibility="public";

// (admin only) make all users' searches visible to everyone
set global:job_visibility="public";
```

Copy

lakehouse

When querying a Cribl Lake Dataset linked to a Lakehouse, define whether the search should use the Lakehouse or not.

Setting	Behavior
on (default)	Use only Lakehouse-cached data.
off	Don't use Lakehouse data. Run the search at regular speed.

For example:

```
// query the Lake Dataset using Lakehouse caching
set lakehouse="on";

// query the Dataset without Lakehouse caching
set lakehouse="off";
```

Copy

max_bytes_read_per_search

Maximum number of bytes that can be read per search. When the limit is exceeded, the search gets canceled.

You can set this option to an int (as bytes), for example:

```
// allow this search to read up to 512MB of data
set max_bytes_read_per_search=536870912;

// allow my every search to read up to 512MB of data
set user:max_bytes_read_per_search=536870912;

// (admin only) allow every user to read up to 512MB of data per search
set global:max_bytes_read_per_search=536870912;
```

Copy

Depending on your permissions, this option can override the **Byte limit** of the matching Usage Group:

Search Member Type	Permissions
Admin	Can increase or decrease the **Byte limit** value.
Editor or User	Can only decrease the **Byte limit** value.

max_earliest_relative

How far back in time the search can go.

You can set this option to a negative time string, for example: `-1h` (1 hour), `-10min` (10 minutes), or `-10` (10 seconds).

```
// allow this search to scan data as old as 90 days
set max_earliest_relative=-90d;

// allow my every search to scan data as old as 90 days
set user:max_earliest_relative=-90d;

// (admin only) allow all users to scan data as old as 90 days
set global:max_earliest_relative=-90d;
```

Copy

Depending on your permissions, this option can override the **Earliest relative time range** of the matching Usage Group.

Search Member Type	Permissions
Admin	Can increase or decrease the value of the **Earliest relative time range**.
Editor or User	Can only decrease the value of the **Earliest relative time range**.

max_executors

Maximum number of executors that the search can use.



More executors don't necessarily cause better performance. Sometimes, more executors can lead to an overload of the coordinator, slowing search execution down.

You can set this option to an int or to the string `"auto"`.

With `max_executors="auto"`, the search starts with a few executors and then dynamically scales these up or down based on collected throughput metrics. In the **Details** of the search, you'll see an additional metric showing the **average** number of executors.

```
// allow this search to invoke up to 5 executors
set max_executors=5;
// automatically adjust the number of executors for this search
set max_executors="auto";

// allow my every search to invoke up to 5 executors
set user:max_executors=5;
// automatically adjust the number of executors for my every search
set user:max_executors="auto";

// (admin only) allow every user to invoke up to 5 executors per search
set global:max_executors=5;
// (admin only) automatically adjust the number of executors for all users
set global:max_executors="auto";
```

Copy

Depending on your permissions, this option can override the **Executors limit** of the matching Usage Group.

Search Member Type	Permissions
Admin	Can increase or decrease the value of the **Executors limit**.
Editor or User	Can only decrease the value of the **Executors limit**.

max_results_per_search

Maximum number of events returned by the search.

You can set this option to an int between `1` and `10000000`, for example:

```
// allow this search to store up to 100,000 result events
set max_results_per_search=100000;

// allow my every search to store up to 100,000 result events
set user:max_results_per_search=100000;

// (admin only) allow every user to store up to 100,000 result events per search
set global:max_results_per_search=100000;
```

Copy

Depending on your permissions, this option can override the **Results limit** of the matching Usage Group. For details, see: Set the Limits of Search Results.

Search Member Type	Permissions
Admin	Can increase or decrease the value of the **Results limit**.
Editor or User	Can only decrease the value of the **Results limit**.



If set for the **system** Usage Group, the limit will apply to all searches in the Organization, including Packs and Dashboard parent searches.

max_running_time_per_search

How long the search can run. When the limit is exceeded, the search gets canceled.

You can set this option to an int (as seconds), for example:

```
// allow this search to run for up to 1 hour
set max_running_time_per_search=3600;

// allow my every search to run for up to 1 hour
set user:max_running_time_per_search=3600;

// (admin only) allow every search by every user to run for up to 1 hour
set global:max_running_time_per_search=3600;
```

Copy

Depending on your permissions, this option can override the **Running time limit** of the matching Usage Group.

Search Member Type	Permissions
Admin	Can increase or decrease the value of the **Running time limit**.
Editor or User	Can only decrease the value of the **Running time limit**.

When a search does exceed the `max_running_time_per_search`, it can take up to an additional 10 seconds for the job to fully terminate. This ensures proper collection of internal logs and metrics during a graceful shutdown. {.box .info}

max_scheduled_searches_per_user

Maximum number of concurrent scheduled searches per user. If the user tries to execute more scheduled searches than specified by this limit, the searches get queued.

You can set this option to an int, for example:

```
// allow yourself to run up to 2 scheduled searches at once
set max_scheduled_searches_per_user=2;
// or:
set user:max_scheduled_searches_per_user=2;

// (admin only) allow every user to run up to 2 scheduled searches at once
set global:max_scheduled_searches_per_user=2;
```

Copy

Depending on your permissions, this option can override the **User concurrent scheduled search limit** of the matching Usage Group:

Search Member Type	Permissions
Admin	Can increase or decrease the value of the **User concurrent scheduled search limit**.
Editor or User	Can only decrease the value of the **User concurrent scheduled search limit**.

max_searches_per_user

Maximum number of concurrent ad-hoc searches per user. If the user tries to execute more queries than specified by this limit, the searches get queued.

You can set this option to an int, for example:

```
// allow yourself to run up to 3 searches at the same time
set max_searches_per_user=3;
// or:
set user:max_searches_per_user=3;

// (admin only) allow every user to run up to 3 searches at the same time
set global:max_searches_per_user=3;
```

Copy

Depending on your permissions, this option can override the **User concurrent ad hoc search limit** of the matching Usage Group:

Search Member Type	Permissions
Admin	Can increase or decrease the value of the **User concurrent ad hoc search limit**.
Editor or User	Can only decrease the value of the **User concurrent ad hoc search limit**.

max_timerange_width

Maximum time range (the value between `earliest` and `latest`) that a single search can cover.

You can set this option to a time string such as `1h` (1 hour), `10min` (10 minutes), or `10` (10 seconds).

```
// allow this search to scan up to 2 hours of data
set max_timerange_width=7200;

// allow my every search to scan up to 2 hours of data
set user:max_timerange_width=7200;

// (admin only) allow every user to scan up to 2 hours of data per search
set global:max_timerange_width=7200;
```

Copy

Depending on your permissions, this option can override the **Time range limit** of the matching Usage Group.

Search Member Type	Permissions
Admin	Can increase or decrease the value of the **Time range limit**.
Editor or User	Can only decrease the value of the **Time range limit**.

sample_rate

Set the fraction of events to sample from the search results.

When you set this option, Cribl Search evaluates only that fraction of events, reducing the amount of data scanned and the cost of the search. A value of `1` (or `"100%"`) means no sampling — all events are evaluated. A value of `0.1` (or `"10%"`, or `"1:10"`) means one in ten events is evaluated.

You can set this option in three formats:

Format	Example	Sampling rate
Decimal (0-1)	`sample_rate=0.5`	50%
Percent string	`sample_rate="50%"`	50%
Fraction string	`sample_rate="1:2"`	50%

When set, this option overrides the sampling ratio configured in the **Sampling** UI control.

```
// sample 10% of events in this search
set sample_rate=0.1;

// sample 10% of every search by the current user
set user:sample_rate=0.1;

// (admin only) sample 10% of every search by every user
set global:sample_rate=0.1;
```

Copy

Use `sample_rate` in saved searches, scheduled searches, and shared queries so that the sampling rate travels with the query itself, without requiring recipients to configure it manually.

token_search

Use the full-text search index to speed up searches that match complete alphanumeric tokens in `_raw`.

When the index is in use, Cribl Search resolves matching searches against an inverted index of `_raw` instead of scanning every event, which can dramatically speed up searches for alphanumeric tokens. The index is on by default.

You can set this option to one of the following:

Setting	Behavior
`true` or `"on"` (default)	Use the full-text search index when possible.
`false` or `"off"`	Cribl doesn't use the full-text search index and scans every event.

You use this option mainly to turn the index off.

```
// turn the full-text search index off for this search
set token_search="off";

// turn the full-text search index off for all your searches
set user:token_search="off";

// (admin only) turn the full-text search index off for all users' searches
set global:token_search=false;

// turn the full-text search index back on for this search
set token_search="on";
```

Copy

The following restrictions apply:

- This option works only with Datasets created in Cribl Search 4.17.1 or later. For Datasets created before 4.17.1, only data ingested after May 21, 2026 is indexed.
- The search term must be a complete alphanumeric string. Substrings and wildcards are not supported.
- Only the search terms in the initial filter use the index. Filters that appear after subsequent operations don't use the token search.



As of Cribl Search 4.19.0, the full-text search index is on by default. In earlier releases, it was off by default. To turn the index off, set the option to `"off"` or `false`.

14.5. Functions

A comprehensive list of all functions supported in Cribl Search, grouped by category.

Context Functions

Context functions return contextual information about your search.

Name	Description
`createdTime()`	Time when the search was created, in seconds.
`displayUsername()`	Friendly display name (typically first + last name) of the user who created the search.
`earliestTime()`	Beginning of the search's time range, in seconds.
`jobID()`	Unique search identifier.
`latestTime()`	End of the search's time range, in seconds.
`query()`	Query string.
`user()`	Username of the user who created the search.

Cribl Functions

Cribl functions can be used together with the `summarize`, `eventstats`, and `timestats` operators to aggregate your data. We refer to those additional functions as **Cribl** functions, since they're specific to Cribl Search.

Name	Description
`findearliest`	Returns the earliest value of an expression across the group.
`findearliestif`	Returns the earliest value of an expression across the group for which a predicate evalutes to `true`.
`findfirst`	Returns the first observed value of an expression across the group.
`findfirstif`	Returns the first observed value of an expression across the group for which a predicate evalutes to `true`.
`findlast`	Returns the last observed value of an expression across the group.

Name	Description
findlastif	Returns the last observed value of an expression across the group for which a predicate evalutes to true.
findlatest	Returns the latest value of an expression across the group.
findlatestif	Returns the latest value of an expression across the group for which a predicate evalutes to true.
list	Returns the list of values of an expression across the group
median	Returns the middle value of an expression across the group.
medianif	Returns the middle value of an expression across the group for which a predicate evalutes to true.
persecond	Returns the per-second rate of an expression across the group
persecondif	Returns the per-second rate of an expression across the group for which a predicate evalutes to true.
rate	Returns the rate observed value of an expression across the group.
rateif	Returns the rate observed value of an expression across the group for which a predicate evalutes to true.
sumsq	Returns the sum of squares of an expression across the group.
sumsqif	Returns the sum of squares of an expression across the group for which a predicate evalutes to true.
values	Returns all of the distinct values of an expression across the group.

Scalar Functions

Scalar functions perform calculations, transformations, or conversions.

Binary Functions

Name	Description
binary_and	Returns a result of the bitwise and operation between two values.
binary_not	Returns a bitwise negation of the input value.
binary_or	Returns a result of the bitwise or operation of the two values.

Name	Description
binary_shift_left	Returns binary shift left operation on a pair of numbers.
binary_shift_right	Returns binary shift right operation on a pair of numbers.
binary_xor	Returns the bitwise `xor` operation of the two values.
from_binary_string	Takes a binary string and returns a number.
to_binary_string	Takes a number and returns a binary string.

Conditional Functions

Name	Description
case	Evaluates a list of predicates and returns the first result expression whose predicate is satisfied.
coalesce	Evaluates a list of expressions and returns the first non-null (or non-empty for string) expression.
iif (iff)	Evaluates the first argument (the predicate), and returns the value of either the second or third arguments, depending on whether the predicate evaluated to `true` (second) or `false` (third).
max_of	Returns the maximum value of several evaluated numeric expressions.
min_of	Returns the minimum value of several evaluated numeric expressions.

Conversion Functions

Name	Description
bin	Rounds values down to an integer multiple of a given bin size.
bin_auto	Rounds values down to a fixed-size bin.
floor	Rounds values down to an integer multiple of a given floor size.
gettype	Returns the type of the input value.
tobool	Converts the input to a `bool` value.
todouble (toreal, todecimal)	Converts the input to a `double` (`real`, `decimal`) value.

Name	Description
`toint` (`tolong`)	Converts the input to an `int` (`long`) value.
`tostring`	Converts the input to a `string` value.

DateTime Functions

Name	Description
`ago`	Subtracts the given timespan from the current UTC clock time.
`datetime_add`	Calculates a new datetime from a specified datepart multiplied by a specified amount, added to a specified datetime.
`datetime_diff`	Calculates the number of the specified periods between two datetime values.
`datetime_part`	Extracts the requested date part as an integer value.
`dayofmonth`	Returns the integer number representing the day number of the given month.
`dayofweek`	Returns an integer between `0` and `6` representing the day of the week, beginning on Sunday.
`dayofyear`	Returns the integer number representing the day number of the given year.
`endofday`	Returns the end of the day containing the date, shifted by an offset, if provided.
`endofmonth`	Returns the end of the month containing the date, shifted by an offset, if provided.
`endofweek`	Returns the end of the week containing the date, shifted by an offset, if provided.
`endofyear`	Returns the end of the year containing the date, shifted by an offset, if provided.
`format_datetime`	Formats a datetime according to the provided format.
`format_timespan`	Formats a timespan according to the provided format.
`getmonth` (`monthofyear`)	Gets the month number (1-12) from a datetime.
`getyear` (`yearofyear`)	Returns the year part of a datetime.

Name	Description
hourofday	Returns the integer number representing the hour number of the given date.
make_datetime	Converts the specified date and time into a datetime value (Unix time in seconds).
make_timespan	Converts the specified time period into a datetime value (Unix time in seconds).
now	Returns the current UTC clock time as a datetime value (Unix time in seconds).
startofday	Returns the start of the day containing the date, shifted by an offset, if provided.
startofmonth	Returns the start of the month containing the date, shifted by an offset, if provided.
startofweek	Returns the start of the week containing the date, shifted by an offset, if provided.
startofyear	Returns the start of the year containing the date, shifted by an offset, if provided.
strftime (format_time)	Converts a datetime (date) object to a human-readable string.
strptime (parse_time)	Converts a string to a datetime.
todatetime	Converts the input into a datetime value (Unix time in seconds).
totimespan	Converts the input into a number of seconds.
unixtime_microseconds_todatetime	Converts the input into a datetime value (Unix time in seconds).
unixtime_milliseconds_todatetime	Converts the input into a datetime value (Unix time in seconds).
unixtime-nanoseconds_todatetime	Converts the input into a datetime value (Unix time in seconds).
unixtime_seconds_todatetime	Converts the input into a datetime value (Unix time in seconds).
week_of_year	Returns an integer representing the week number.

Dynamic Functions

Dynamic scalar functions allow you to manipulate objects by operating on `dynamic` values, including dynamic arrays and property bags.

Name	Description
`bag_has_key`	Checks whether a property bag contains a given key.
`bag_keys`	Lists all root keys of a property bag.
`bag_merge`	Merges multiple property bags, discarding duplicate keys.
`bag_pack`	Creates a property bag from an alternating list of keys and values.
`bag_pack_columns`	Creates a property bag from a list of columns.
`bag_remove_keys`	Removes key-value pairs from a property bag.
`bag_set_key`	Adds or overwrites a key-value pair in a property bag.
`bag_zip`	Creates a property bag from two dynamic arrays.
`make_bag`	Creates a property bag from multiple input bags.
`make_bag_if`	Creates a property bag from those input bags that meet the specified condition.
`zip`	Merges dynamic arrays, grouping elements by index.

The following string functions support `dynamic` types as well:

Function	Usage with dynamic data types
`extractjson(`path,object`)`	Uses path to navigate into object.
`parse_json(`source`)`	Turns a JSON string into a dynamic object.
`range(`from,to,step`)`	Generates an array of values.

Cryptographic Functions

Name	Description
`encrypt`	Encrypts data with a key managed by a Cribl Stream Worker Group.
`decrypt`	Decrypts data with a key managed by a Cribl Stream Worker Group.

Hash Functions

Name	Description
hash	Returns a hash value for the input value.
hash_combine	Combines hash values of two or more hashes.
hash_many	Returns a combined hash value of multiple values.
hash_md5	Returns an MD5 hash value for the input value.
hash_sha1	Returns a SHA1 hash value for the input value.
hash_sha256	Returns a SHA-256 hash value for the input value.
hash_xxhash64	Returns a 64-bit hash value for the input value.

INET Functions

Name	Description
ipv4_compare	Compares two IPv4 strings.
ipv4_is_in_range	Checks if IPv4 string address is in IPv4-prefix notation range.
ipv4_is_in_any_range	Checks whether IPv4 string address is in any of the specified IPv4 address ranges.
ipv4_is_match	Matches two IPv4 strings.
ipv4_is_private	Checks if IPv4 string address belongs to a set of private network IPs.
ipv4_netmask_suffix	Returns the value of the IPv4 netmask suffix from IPv4 string address.
ipv6_compare	Compares two IPv6 or IPv4 network address strings.
ipv6_is_match	Matches two IPv6 or IPv4 network address strings.
format_bytes	Converts the input into a string that represents data size.
format_ipv4	Parses input with a netmask and returns string representing IPv4 address.
format_ipv4_mask	Parses input with a netmask and returns string representing IPv4 address as CIDR notation.

Mathematical Functions

Name	Description
abs	Calculates the absolute value of the input.
acos	Calculates the angle whose cosine is the specified number.
asin	Calculates the angle whose sine is the specified number.
atan	Returns the angle whose tangent is the specified number.
atan2	Calculates the angle, in radians, between the positive x-axis and the ray from the origin to the point (y, x).
beta_cdf	Returns the standard cumulative beta distribution function.
beta_inv	Returns the inverse of the beta cumulative probability beta density function.
beta_pdf	Returns the probability density beta function.
ceil	Rounds up a numeric expression's value to the nearest integer.
ceiling	Rounds up a numeric expression's value to the nearest integer.
cos	Returns the cosine function.
cot	Calculates the trigonometric cotangent of the specified angle, in radians.
degrees	Converts angle value in radians into value in degrees.
exp	Calculates the base-e exponential function of x.
exp2	Calculates the base-2 exponential function of x.
exp10	Calculates the base-10 exponential function of x.
gamma	Computes gamma function.
isfinite	Returns whether input is a finite value.
isinf	Returns whether input is an infinite value.
isnan	Returns whether input is Not-a-Number (NaN) value.
log	Returns the natural logarithm function.
log2	Returns the (base-2) logarithm function.

Name	Description
log10	Returns the common (base-10) logarithm function.
loggamma	Computes log of absolute value of the loggamma function.
not	Reverses the value of its boolean argument.
pi	Returns the constant value of Pi.
pow	Returns a result of raising to power.
radians	Converts angle value in degrees into value in radians.
rand	Returns a random number.
range	Generates a dynamic array, holding a series of equally spaced values.
round	Returns the rounded source to the specified precision.
sign	Returns the sign of a numeric expression.
sin	Returns the sine of a numeric expression.
sqrt	Returns the square root function.
tan	Returns the tangent function.

String Functions

Name	Description
base64_decode_toarray	Decodes a base64 string to an array of long values.
base64_decode_tostring	Decodes a base64 string to a UTF-8 string.
base64_encode_fromarray	Encodes a base64 string from a bytes array.
base64_encode_tostring	Encodes a string as base64 string.
countof	Counts occurrences of a substring in a string.
extract	Gets a match for an RE2 regular expression from a source string.
extract_all	Gets all matches for an RE2 regular expression from a source string.
extract_json	Gets a specified element out of a JSON text using a path expression.

Name	Description
has_any_index	Gets a match for an RE2 regular expression from a source string.
indexof	Reports the zero-based index of the first occurrence of a specified string within the input string.
isempty	Returns `true` if the argument is an empty string or is null.
isnotempty (notempty)	Returns `true` if the argument isn't an empty string, and it isn't null.
isnotnull (notnull)	Returns `true` if the argument is not null.
isnull	Indicates whether the argument evaluates to a null value.
match_regex	Searches a text string for a specific pattern defined by a regular expression.
parse_csv	Splits a given string representing a single record of comma-separated values.
parse_ipv4	Converts IPv4 string to long (signed 64-bit) number representation in big-endian order.
parse_ipv4_mask	Converts the input string of IPv4 and netmask to a signed, 64-bit wide, long number representation in big-endian order.
parse_ipv6	Converts IPv6 or IPv4 string to a canonical IPv6 string representation.
parse_ipv6_mask	Converts IPv6/IPv4 string and netmask to a canonical IPv6 string representation.
parse_json (todynamic)	Interprets a string as a JSON value and returns the value as dynamic.
parse_url	Parses an absolute URL string and returns a dynamic object that contains URL parts.
parse_urlquery	Returns a dynamic object that contains the Query parameters.
parse_version	Converts the input string representation of version to a comparable decimal number.
replace_regex	Replaces all RE2 regular expression matches with another string.
reverse	Reverses the order of the input string.
split	Splits a given string according to a given delimiter.
strcat	Concatenates between 1 and 64 arguments.

Name	Description
strcat_delim	Concatenates between 2 and 64 arguments, with a delimiter.
strcmp	Compares two strings.
strlen	Returns the length, in characters, of the input string.
strrep	Repeats given string specified number of times.
substring	Extracts a substring from a source string starting from some index to the end of the string.
tolower	Converts a string to lower case.
toupper	Converts a string to upper case.
translate	Replaces a set of characters with another set of characters in a given string.
trim	Removes all leading and trailing matches of the specified string or regular expression.
trim_end	Removes trailing match of the specified regular expression.
trim_start	Removes leading match of the specified regular expression.
url_decode	Converts encoded URL into a to regular URL representation.
url_encode	Converts characters of the input URL into a format that can be transmitted over the Internet.

Statistical Functions

Name	Description
avg	Calculates the average across the group.
avgif	Calculates the average across the group where a predicate evaluates to `true`.
count	Counts events per summarization group.
countif	Counts events based on a predicate.
dcount	Calculates an estimate of the number of distinct values.

Name	Description
dcountif	Calculates an estimate of the number of distinct values for those rows where a predicate evaluates to `true`.
max	Finds the maximum value across the group.
maxif	Finds the maximum value for which a predicate evaluates to `true`.
min	Finds the minimum value across the group.
minif	Finds the minimum value which a predicate evaluates to `true`.
percentile	Returns an estimate for the specified nearest-rank percentile of the population defined.
stdev	Calculates the standard deviation of an expression across the group.
stdevif	Calculates the standard deviation of an expression which a predicate evaluates to `true`.
stdevp	Calculates the standard deviation of an expression across the group, considering the group as a population.
sum	Calculates the sum of an expression across the group.
sumif	Calculates the sum of an expression for which a predicate evaluates to `true`.
take_any	Returns an arbitrary non-`null` value of an expression from each group.
take_anyif	Returns an arbitrary non-`null` value of an expression from rows where a predicate evaluates to `true`.
variance	Calculates the variance of an expression.
varianceif	Calculates the variance of an expression for which a predicate evaluates to `true`.
variancep	Calculates the variance of an expression across the group, considering the group as a population.

Window Functions

14.5.1. Context Functions

Context functions return contextual information about your search.

Name	Description
`createdTime()`	Time when the search was created, in seconds.
`displayUsername()`	Friendly display name (typically first + last name) of the user who created the search.
`earliestTime()`	Beginning of the search's time range, in seconds.
`jobID()`	Unique search identifier.
`latestTime()`	End of the search's time range, in seconds.
`query()`	Query string.
`user()`	Username of the user who created the search.

Examples

Return multiple details about a search:

```
dataset="cribl_search_sample" action=="*"
| summarize eventsPerSecond = (count() / (latestTime() - earliestTime())) by action
| project action, eventsPerSecond, reportTime=createdTime(), reportId=jobID(), report
```

Copy | Run in Cribl Search

Reference the search's time range:

```
dataset=myDataset
| summarize eventsPerSecond = (count() / (latestTime() - earliestTime())) by host
```

Copy

Filter events by the current user:

```
dataset=myDataset
| where user == user()
```

Copy

Enrich results with search information:

```
dataset=myDataset
| summarize NumTransactions=count(), Total=sum(UnitPrice * NumUnits) by Fruit, StartC
| extend query=query(), searchid=jobID()
```

Copy

14.5.1.1. CreatedTime

The `createdTime` function returns the time when the current search was created, expressed as a Unix timestamp in seconds.

This is useful for annotating exported results with when the search was run, or for computing how much time has elapsed since the search started.

Syntax

```
createdTime()
```

Arguments

None.

Returns

A `long` containing the Unix timestamp, in seconds, of when the search was created.

Examples

Annotate exported results with the time the search was run:

```
dataset=myDataset
| extend search_created=createdTime()
| export to lake myAuditDataset
```

Copy

Build a full provenance record alongside the job ID and the user who ran the search:

```
dataset=myDataset
| extend search_id=jobID(), run_by=user(), created_at=createdTime()
| export to lake myAuditDataset
```

Copy

14.5.1.2. DisplayUsername

The `displayUsername` function returns the friendly display name (typically first and last name) of the user who created the current search.

To get the user's login username instead, use `user()`.

Syntax

```
displayUsername()
```

Arguments

None.

Returns

A `string` containing the display name of the user who created the search.

Examples

Tag exported results with the full name of the user who ran the search:

```
dataset=myDataset
| extend run_by=displayUsername()
| export to lake myAuditDataset
```

Copy

Build a full provenance record combining the display name, login username, and job ID:

```
dataset=myDataset
| extend search_id=jobID(), display_name=displayUsername(), login=user()
| export to lake myAuditDataset
```

Copy

14.5.1.3. EarliestTime

The `earliestTime` function returns the beginning of the current search's time range, expressed as a Unix timestamp in seconds.

To get the end of the search's time range, use `latestTime()`.

Syntax

```
earliestTime()
```

Arguments

None.

Returns

A `long` containing the Unix timestamp, in seconds, of the start of the search's time range.

Examples

Compute the rate of events per second across the search's time window:

```
dataset=myDataset
|| summarize eventsPerSecond = count() / (latestTime() - earliestTime()) by host
```

Copy

Annotate each result with the boundaries of the search's time range:

```
dataset=myDataset
|| extend window_start=earliestTime(), window_end=latestTime()
|| export to lake myAuditDataset
```

Copy

14.5.1.4. JobID

The `jobID` function returns the unique identifier assigned to the current search job.

You can use `jobID` to tag exported results, distinguish between concurrent or scheduled search runs, and correlate results written to different destinations.

Syntax

```
jobID()
```

Arguments

None.

Returns

A `string` containing the unique identifier of the current search job.

Examples

Tag each exported event with the ID of the search that produced it:

```
dataset=myDataset
| extend search_id=jobID()
| export to lake myEnrichedDataset
```

Copy

Combine `jobID` with other context functions to build a full audit trail on export:

```
dataset=myDataset
| extend search_id=jobID(), run_by=user(), search_query=query()
| export to lake myAuditDataset
```

Copy

14.5.1.5. LatestTime

The `latestTime` function returns the end of the current search's time range, expressed as a Unix timestamp in seconds.

To get the start of the search's time range, use `earliestTime()`.

Syntax

```
latestTime()
```

Arguments

None.

Returns

A `long` containing the Unix timestamp, in seconds, of the end of the search's time range.

Examples

Compute the rate of events per second across the search's time window:

```
dataset=myDataset
|| summarize eventsPerSecond = count() / (latestTime() - earliestTime()) by host
```

Copy

Annotate each result with the boundaries of the search's time range:

```
dataset=myDataset
|| extend window_start=earliestTime(), window_end=latestTime()
|| export to lake myAuditDataset
```

Copy

14.5.1.6. Query

The `query` function returns the full query string of the current search as a text value.

This is useful for audit logging, debugging, and annotating exported results so that the exact search that produced them can be traced later.

Syntax

`query()`

Arguments

None.

Returns

A `string` containing the full query string of the current search.

Examples

Append the originating query as a field on each exported event:

```
dataset=myDataset
| extend source_query=query()
| export to lake myAuditDataset
```

Copy

Build a full provenance record alongside the job ID and the user who ran the search:

```
dataset=myDataset
| extend search_id=jobID(), run_by=user(), source_query=query()
| export to lake myAuditDataset
```

Copy

14.5.1.7. User

The `user` function returns the login username of the user who created the current search.

To get the user's friendly display name (typically first and last name) instead, use `displayUsername()`.

Syntax

```
user()
```

Arguments

None.

Returns

A `string` containing the login username of the user who created the search.

Examples

Filter events to those belonging to the current user:

```
dataset=myDataset
| where owner == user()
```

Copy

Tag exported results with the name of the user who ran the search:

```
dataset=myDataset
| extend run_by=user(), search_id=jobID()
| export to lake myAuditDataset
```

Copy

14.5.2. Cribl Functions

Cribl Search supports additional functions that you can use together with the `summarize`, `eventstats`, and `timestats` operators to aggregate your data. We refer to those additional functions as **Cribl** functions, since they're specific to Cribl Search.

Cribl Search supports the following Cribl functions:

Name	Description
`findearliest`	Returns the earliest value of an expression across the group.
`findearliestif`	Returns the earliest value of an expression across the group for which a predicate evalutes to `true`.
`findfirst`	Returns the first observed value of an expression across the group.
`findfirstif`	Returns the first observed value of an expression across the group for which a predicate evalutes to `true`.
`findlast`	Returns the last observed value of an expression across the group.
`findlastif`	Returns the last observed value of an expression across the group for which a predicate evalutes to `true`.
`findlatest`	Returns the latest value of an expression across the group.
`findlatestif`	Returns the latest value of an expression across the group for which a predicate evalutes to `true`.
`list`	Returns the list of values of an expression across the group
`median`	Returns the middle value of an expression across the group.
`medianif`	Returns the middle value of an expression across the group for which a predicate evalutes to `true`.
`persecond`	Returns the per-second rate of an expression across the group
`persecondif`	Returns the per-second rate of an expression across the group for which a predicate evalutes to `true`.
`rate`	Returns the rate observed value of an expression across the group.
`rateif`	Returns the rate observed value of an expression across the group for which a predicate evalutes to `true`.
`sumsq`	Returns the sum of squares of an expression across the group.

Name	Description
`sumsqif`	Returns the sum of squares of an expression across the group for which a predicate evalutes to `true`.
`values`	Returns all of the distinct values of an expression across the group.

14.5.2.1. FINDEARLIEST

The `findearliest` aggregation function returns the earliest value (based on `_time`) of **Expression** across the group.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
findearliest( Expression )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.

Examples

Return the earliest event by `_time`:

```
dataset="cribl_search_sample"
| summarize findearliest(_time)
```

Copy Run in Cribl Search

Return the earliest event by a custom field's value:

```
dataset=myDataset
| summarize findearliest(receiptTime)
```

Copy

14.5.2.2. FINDEARLIESTIF

The `findearliestif` aggregation function returns the earliest value (based on `_time`) of **Expression** across the group for which **Predicate** evaluates to `true`.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
findearliestif( Expression, Predicate )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.
- **Predicate**: Expression that will be used to filter rows.

Examples

This example returns the 10 earliest events with an `ACCEPT` action:

```
dataset="cribl_search_sample" | limit 10
| eventstats startTime=findearliestif(_time, action=="ACCEPT")
| extend timeDelta=_time-startTime
```

Copy Run in Cribl Search

This example returns the earliest date for all products that have more than 4 letters.

```
dataset=myDataset
| summarize findearliestif(date, strlen(product) > 4)
```

Copy

14.5.2.3. FINDFIRST

The `findfirst` aggregation function returns the first observed non-`null` value of **Expression** across the group.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
findfirst( Expression )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.

Usage

To find an earliest event with respect to the `_time` field, instead use `findearliest`.

When events are sorted with `sort` or `order`, `findfirst` returns the first non-`null` value of **Expression** in that sort order.

When events are not sorted, `findfirst` behaves like `take_any` and returns an arbitrary non-`null` value. Use `take_any` when sort order does not matter.

Examples

Here is a basic example:

```
dataset=myDataset
| summarize findfirst(channel)
```

Copy

This example effectively finds `min(status)` and `max(status)`:

```
dataset="cribl_internal_logs" status=/[0-9]+/
| order by status asc
| summarize x = findfirst(status), y = findlast(status)
```

Copy Run in Cribl Search

14.5.2.4. FINDFIRSTIF

The `findfirstif` aggregation function returns the first observed non-`null` value of **Expression** across the group for which **Predicate** evaluates to `true`.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
findfirstif( Expression, Predicate )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.
- **Predicate**: Expression that will be used to filter rows.

Usage

To find an earliest event with respect to the `_time` field, instead use `findearliestif`.

When events are sorted with `sort` or `order`, `findfirstif` returns the first non-`null` value of **Expression** in that sort order for rows where **Predicate** evaluates to `true`.

When events are not sorted, `findfirstif` behaves like `take_anyif` and returns an arbitrary non-`null` value from matching rows. Use `take_anyif` when sort order does not matter.

Example

This example returns the birthday for all names that have more than 4 letters.

```
dataset=myDataset
| summarize findfirstif(day_of_birth, strlen(name) > 4)
```

Copy

14.5.2.5. FINDLAST

The `findlast` aggregation function returns the last observed non-`null` value of **Expression** across the group.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
findlast( Expression )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.

Usage

To find a latest event with respect to the `_time` field, instead use `findlatest`.

When events are sorted with `sort` or `order`, `findlast` returns the last non-`null` value of **Expression** in that sort order.

When events are not sorted, `findlast` returns an arbitrary non-`null` value. Use `take_any` when sort order does not matter.

Examples

Here is a basic example:

```
dataset=myDataset
| summarize findlast(channel)
```

Copy

This example effectively finds `min(status)` and `max(status)`:

```
dataset="cribl_internal_logs" status=/[0-9]+/
| order by status asc
| summarize x = findfirst(status), y = findlast(status)
```

14.5.2.6. FINDLASTIF

The `findlastif` aggregation function returns the last observed non-`null` value of **Expression** across the group for which **Predicate** evaluates to `true`.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
findlastif( Expression, Predicate )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.
- **Predicate**: Expression that will be used to filter rows.

Usage

To find a latest event with respect to the `_time` field, instead use `findlatestif`.

When events are sorted with `sort` or `order`, `findlastif` returns the last non-`null` value of **Expression** in that sort order for rows where **Predicate** evaluates to `true`.

When events are not sorted, `findlastif` returns an arbitrary non-`null` value from matching rows. Use `take_anyif` when sort order does not matter.

Example

This example returns the birthday for all names that have more than 4 letters.

```
dataset=myDataset
| summarize findlastif(day_of_birth, strlen(name) > 4)
```

Copy

14.5.2.7. FINDLATEST

The `findlatest` aggregation function returns the latest value (based on `_time`) of **Expression** across the group.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
findlatest( Expression )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.

Example

```
dataset=myDataset
| summarize findlatest(receiptTime)
```

Copy

14.5.2.8. FINDLATESTIF

The `findlatestif` aggregation function returns the latest value (based on `_time`) of **Expression** across the group for which **Predicate** evaluates to `true`.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
findlatestif( Expression, Predicate )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.
- **Predicate**: Expression that will be used to filter rows.

Example

This example returns the latest date for all products that have more than 4 letters.

```
dataset=myDataset
| summarize findlatestif(date, strlen(product) > 4)
```

Copy

14.5.2.9. List

The `list` aggregation function returns the list of values of **Expression** across the group.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
list( Expression [, Max ] )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.
- **Max**: An integer that limits the number of values returned. The default is `100`. If set to `0`, all values are returned.

Examples

This example lists methods (HTTP verbs) on API requests, up to a limit:

```
dataset="cribl_search_sample" dataSource=access*
| limit 1000
| summarize list(request_method)
```

Copy Run in Cribl Search

14.5.2.10. Median

The `median` aggregation function returns the middle value of **Expression** across the group.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
median( Expression )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.

Example

```
dataset=myDataset
| summarize median(age)
```

Copy

14.5.2.11. MEDIANIF

The `medianif` aggregation function returns the middle value of **Expression** across the group for which **Predicate** evaluates to `true`.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
medianif( Expression, Predicate )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.
- **Predicate**: Expression that will be used to filter rows.

Example

```
dataset=myDataset
| summarize medianif(data, host=="Cribl.local")
```

Copy

14.5.2.12. Persecond

The `persecond` aggregation function returns the per second rate (based on `_time`) of **Expression** across the group.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
persecond( Expression )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.

Example

```
dataset=myDataset
| summarize persecond(transactions)
```

Copy

14.5.2.13. PERSECONDIF

The `persecondif` aggregation function returns the per second rate (based on `_time`) of **Expression** across the group for which **Predicate** evaluates to `true`.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
persecondif( Expression, Predicate )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.
- **Predicate**: Expression that will be used to filter rows.

Example

```
dataset=myDataset
| summarize persecondif(transactions, location=="town")
```

Copy

14.5.2.14. Rate

The `rate` aggregation function returns the rate (based on `_time`) observed value of **Expression** across the group.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
rate( Expression, Time )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.
- **Time**: Unit of time, specified with a positive integer and time period. Supports weeks (`w`), days (`d`), hours (`h`), minutes (`m`), and seconds (`s`). For example, one day would be `1d`.

Example

```
dataset=myDataset
| summarize rate(goats, "5m")
```

Copy

14.5.2.15. RATEIF

The `rateif` aggregation function returns the rate (based on `_time`) observed value of **Expression** across the group for which **Predicate** evaluates to `true`.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
rateif( Expression, Time, Predicate )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.
- **Time**: Unit of time, specified with a positive integer and time period. Supports weeks (`w`), days (`d`), hours (`h`), minutes (`m`), and seconds (`s`). For example, one day would be `1d`.
- **Predicate**: Expression that will be used to filter rows.

Example

```
dataset=myDataset
| summarize rateif(goats, "5s", host=="Cribl.local")
```

Copy

14.5.2.16. SUMSQ

The `sumsq` aggregation function returns the sum of squares of **Expression** across the group.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
sumsq( Expression )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.

Example

```
dataset=myDataset
| summarize sumsq(goats)
```

Copy

14.5.2.17. SUMSQIF

The `sumsqif` aggregation function returns the sum of squares of **Expression** across the group for which **Predicate** evaluates to `true`.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
sumsqif( Expression, Predicate )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.
- **Predicate**: Expression that will be used to filter rows.

Example

```
dataset=myDataset
| summarize sumsqif(goats, host=="Cribl.local")
```

Copy

14.5.2.18. Values

The `values` aggregation function returns all of the distinct values of **Expression** across the group. This allows you to quickly identify and understand all the values a field has in your data.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
values( Expression [, Max [, ErrorRate] ] )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.
- **Max**: An integer that limits the number of values returned. The default is `0` where all distinct values are returned.
- **ErrorRate**: Controls how accurately the function counts distinct values. Range is `0-1`. The default value is `0.01`. Higher values allow higher error rates (fewer unique values recognized), with the offsetting benefit of less memory usage.

Results

The response field is an array of unique values (a "set"), up to either a specified limit or the default limit of `100`. There is no guarantee that this array's elements will be returned in any particular order.

Examples

This example lists unique methods (HTTP verbs) on API requests, up to the supplied limit:

```
dataset="cribl_search_sample" dataSource=access*
| limit 1000
| summarize values(request_method)
```

Copy Run in Cribl Search

14.5.3. Scalar Functions

A list of all scalar functions supported by Cribl Search, grouped by category.

Context Functions

Context functions return information about the current search, such as who ran it and what query was used. They are useful for enriching exported results with provenance metadata.

Name	Description
`createdTime()`	Time when the search was created, in seconds.
`displayUsername()`	Friendly display name (typically first + last name) of the user who created the search.
`earliestTime()`	Beginning of the search's time range, in seconds.
`jobID()`	Unique search identifier.
`latestTime()`	End of the search's time range, in seconds.
`query()`	Query string.
`user()`	Username of the user who created the search.

Binary Functions

Name	Description
`binary_and`	Returns a result of the bitwise `and` operation between two values.
`binary_not`	Returns a bitwise negation of the input value.
`binary_or`	Returns a result of the bitwise or operation of the two values.
`binary_shift_left`	Returns binary shift left operation on a pair of numbers.
`binary_shift_right`	Returns binary shift right operation on a pair of numbers.
`binary_xor`	Returns the bitwise `xor` operation of the two values.
`from_binary_string`	Takes a binary string and returns a number.

Name	Description
to_binary_string	Takes a number and returns a binary string.

Conditional Functions

Name	Description
case	Evaluates a list of predicates and returns the first result expression whose predicate is satisfied.
coalesce	Evaluates a list of expressions and returns the first non-null (or non-empty for string) expression.
iif (iff)	Evaluates the first argument (the predicate), and returns the value of either the second or third arguments, depending on whether the predicate evaluated to `true` (second) or `false` (third).
max_of	Returns the maximum value of several evaluated numeric expressions.
min_of	Returns the minimum value of several evaluated numeric expressions.

Conversion Functions

Name	Description
bin	Rounds values down to an integer multiple of a given bin size.
bin_auto	Rounds values down to a fixed-size bin.
floor	Rounds values down to an integer multiple of a given floor size.
gettype	Returns the type of the input value.
tobool	Converts the input to a `bool` value.
todouble (toreal, todecimal)	Converts the input to a `double` (`real`, `decimal`) value.
toint (tolong)	Converts the input to an `int` (`long`) value.
tostring	Converts the input to a `string` value.

DateTime Functions

Name	Description
ago	Subtracts the given timespan from the current UTC clock time.
datetime_add	Calculates a new datetime from a specified datepart multiplied by a specified amount, added to a specified datetime.
datetime_diff	Calculates the number of the specified periods between two datetime values.
datetime_part	Extracts the requested date part as an integer value.
dayofmonth	Returns the integer number representing the day number of the given month.
dayofweek	Returns an integer between `0` and `6` representing the day of the week, beginning on Sunday.
dayofyear	Returns the integer number representing the day number of the given year.
endofday	Returns the end of the day containing the date, shifted by an offset, if provided.
endofmonth	Returns the end of the month containing the date, shifted by an offset, if provided.
endofweek	Returns the end of the week containing the date, shifted by an offset, if provided.
endofyear	Returns the end of the year containing the date, shifted by an offset, if provided.
format_datetime	Formats a datetime according to the provided format.
format_timespan	Formats a timespan according to the provided format.
getmonth (monthofyear)	Gets the month number (1-12) from a datetime.
getyear (yearofyear)	Returns the year part of a datetime.
hourofday	Returns the integer number representing the hour number of the given date.
make_datetime	Converts the specified date and time into a datetime value (Unix time in seconds).
make_timespan	Converts the specified time period into a datetime value (Unix time in seconds).

Name	Description
now	Returns the current UTC clock time as a datetime value (Unix time in seconds).
startofday	Returns the start of the day containing the date, shifted by an offset, if provided.
startofmonth	Returns the start of the month containing the date, shifted by an offset, if provided.
startofweek	Returns the start of the week containing the date, shifted by an offset, if provided.
startofyear	Returns the start of the year containing the date, shifted by an offset, if provided.
strftime (format_time)	Converts a datetime (date) object to a human-readable string.
strptime (parse_time)	Converts a string to a datetime.
todatetime	Converts the input into a datetime value (Unix time in seconds).
totimespan	Converts the input into a number of seconds.
unixtime_microseconds_todatetime	Converts the input into a datetime value (Unix time in seconds).
unixtime_milliseconds_todatetime	Converts the input into a datetime value (Unix time in seconds).
unixtime-nanoseconds_todatetime	Converts the input into a datetime value (Unix time in seconds).
unixtime_seconds_todatetime	Converts the input into a datetime value (Unix time in seconds).
week_of_year	Returns an integer representing the week number.

Dynamic Functions

Dynamic scalar functions allow you to manipulate objects by operating on dynamic values, including dynamic arrays and property bags.

Name	Description
bag_has_key	Checks whether a property bag contains a given key.

Name	Description
`bag_keys`	Lists all root keys of a property bag.
`bag_merge`	Merges multiple property bags, discarding duplicate keys.
`bag_pack`	Creates a property bag from an alternating list of keys and values.
`bag_pack_columns`	Creates a property bag from a list of columns.
`bag_remove_keys`	Removes key-value pairs from a property bag.
`bag_set_key`	Adds or overwrites a key-value pair in a property bag.
`bag_zip`	Creates a property bag from two dynamic arrays.
`make_bag`	Creates a property bag from multiple input bags.
`make_bag_if`	Creates a property bag from those input bags that meet the specified condition.
`zip`	Merges dynamic arrays, grouping elements by index.

The following string functions support `dynamic` types as well:

Function	Usage with dynamic data types
`extractjson(`path,object`)`	Uses path to navigate into object.
`parse_json(`source`)`	Turns a JSON string into a dynamic object.
`range(`from,to,step`)`	Generates an array of values.

Cryptographic Functions

Name	Description
`encrypt`	Encrypts data with a key managed by a Cribl Stream Worker Group.
`decrypt`	Decrypts data with a key managed by a Cribl Stream Worker Group.

Hash Functions

Name	Description
hash	Returns a hash value for the input value.
hash_combine	Combines hash values of two or more hashes.
hash_many	Returns a combined hash value of multiple values.
hash_md5	Returns an MD5 hash value for the input value.
hash_sha1	Returns a SHA1 hash value for the input value.
hash_sha256	Returns a SHA-256 hash value for the input value.
hash_xxhash64	Returns a 64-bit hash value for the input value.

INET Functions

Name	Description
ipv4_compare	Compares two IPv4 strings.
ipv4_is_in_range	Checks if IPv4 string address is in IPv4-prefix notation range.
ipv4_is_in_any_range	Checks whether IPv4 string address is in any of the specified IPv4 address ranges.
ipv4_is_match	Matches two IPv4 strings.
ipv4_is_private	Checks if IPv4 string address belongs to a set of private network IPs.
ipv4_netmask_suffix	Returns the value of the IPv4 netmask suffix from IPv4 string address.
ipv6_compare	Compares two IPv6 or IPv4 network address strings.
ipv6_is_match	Matches two IPv6 or IPv4 network address strings.
format_bytes	Converts the input into a string that represents data size.
format_ipv4	Parses input with a netmask and returns string representing IPv4 address.
format_ipv4_mask	Parses input with a netmask and returns string representing IPv4 address as CIDR notation.

Mathematical Functions

Name	Description
abs	Calculates the absolute value of the input.
acos	Calculates the angle whose cosine is the specified number.
asin	Calculates the angle whose sine is the specified number.
atan	Returns the angle whose tangent is the specified number.
atan2	Calculates the angle, in radians, between the positive x-axis and the ray from the origin to the point (y, x).
beta_cdf	Returns the standard cumulative beta distribution function.
beta_inv	Returns the inverse of the beta cumulative probability beta density function.
beta_pdf	Returns the probability density beta function.
ceil	Rounds up a numeric expression's value to the nearest integer.
ceiling	Rounds up a numeric expression's value to the nearest integer.
cos	Returns the cosine function.
cot	Calculates the trigonometric cotangent of the specified angle, in radians.
degrees	Converts angle value in radians into value in degrees.
exp	Calculates the base-e exponential function of x.
exp2	Calculates the base-2 exponential function of x.
exp10	Calculates the base-10 exponential function of x.
gamma	Computes gamma function.
isfinite	Returns whether input is a finite value.
isinf	Returns whether input is an infinite value.
isnan	Returns whether input is Not-a-Number (NaN) value.
log	Returns the natural logarithm function.
log2	Returns the (base-2) logarithm function.
log10	Returns the common (base-10) logarithm function.

Name	Description
loggamma	Computes log of absolute value of the loggamma function.
not	Reverses the value of its boolean argument.
pi	Returns the constant value of Pi.
pow	Returns a result of raising to power.
radians	Converts angle value in degrees into value in radians.
rand	Returns a random number.
range	Generates a dynamic array, holding a series of equally spaced values.
round	Returns the rounded source to the specified precision.
sign	Returns the sign of a numeric expression.
sin	Returns the sine of a numeric expression.
sqrt	Returns the square root function.
tan	Returns the tangent function.

String Functions

Name	Description
base64_decode_toarray	Decodes a base64 string to an array of long values.
base64_decode_tostring	Decodes a base64 string to a UTF-8 string.
base64_encode_fromarray	Encodes a base64 string from a bytes array.
base64_encode_tostring	Encodes a string as base64 string.
countof	Counts occurrences of a substring in a string.
extract	Gets a match for an RE2 regular expression from a source string.
extract_all	Gets all matches for an RE2 regular expression from a source string.
extract_json	Gets a specified element out of a JSON text using a path expression.

Name	Description
has_any_index	Gets a match for an RE2 regular expression from a source string.
indexof	Reports the zero-based index of the first occurrence of a specified string within the input string.
isempty	Returns `true` if the argument is an empty string or is null.
isnotempty (notempty)	Returns `true` if the argument isn't an empty string, and it isn't null.
isnotnull (notnull)	Returns `true` if the argument is not null.
isnull	Indicates whether the argument evaluates to a null value.
match_regex	Searches a text string for a specific pattern defined by a regular expression.
parse_csv	Splits a given string representing a single record of comma-separated values.
parse_ipv4	Converts IPv4 string to long (signed 64-bit) number representation in big-endian order.
parse_ipv4_mask	Converts the input string of IPv4 and netmask to a signed, 64-bit wide, long number representation in big-endian order.
parse_ipv6	Converts IPv6 or IPv4 string to a canonical IPv6 string representation.
parse_ipv6_mask	Converts IPv6/IPv4 string and netmask to a canonical IPv6 string representation.
parse_json (todynamic)	Interprets a string as a JSON value and returns the value as dynamic.
parse_url	Parses an absolute URL string and returns a dynamic object that contains URL parts.
parse_urlquery	Returns a dynamic object that contains the Query parameters.
parse_version	Converts the input string representation of version to a comparable decimal number.
replace_regex	Replaces all RE2 regular expression matches with another string.
reverse	Reverses the order of the input string.
split	Splits a given string according to a given delimiter.
strcat	Concatenates between 1 and 64 arguments.

Name	Description
strcat_delim	Concatenates between 2 and 64 arguments, with a delimiter.
strcmp	Compares two strings.
strlen	Returns the length, in characters, of the input string.
strrep	Repeats given string specified number of times.
substring	Extracts a substring from a source string starting from some index to the end of the string.
tolower	Converts a string to lower case.

14.5.3.1. Binary Functions

A list of all binary functions supported by Cribl Search.

Name	Description
`binary_and`	Returns a result of the bitwise `and` operation between two values.
`binary_not`	Returns a bitwise negation of the input value.
`binary_or`	Returns a result of the bitwise or operation of the two values.
`binary_shift_left`	Returns binary shift left operation on a pair of numbers.
`binary_shift_right`	Returns binary shift right operation on a pair of numbers.
`binary_xor`	Returns the bitwise `xor` operation of the two values.
`from_binary_string`	Takes a binary string and returns a number.
`to_binary_string`	Takes a number and returns a binary string.

14.5.3.1.1. BINARY_AND

The `binary_and` function returns a result of the bitwise `and` operation between two values.

Syntax

```
binary_and( Number1, Number2 )
```

Copy

Arguments

- **NumberX**: A Long number. The Long data type represents a signed, 64-bit wide integer.

Example

```
dataset=myDataset
| where bit != binary_and(101,101)
```

Copy

14.5.3.1.2. BINARY_NOT

The `binary_not` function returns a bitwise negation of the input value.

Syntax

```
binary_not( Number )
```

Copy

Arguments

- **Number**: A number.

Example

```
dataset=myDataset
| where bit != binary_not(101)
```

Copy

14.5.3.1.3. BINARY_OR

The `binary_or` function returns a result of the bitwise `or` operation of the two values.

Syntax

```
binary_or( Number1, Number2 )
```

Copy

Arguments

- **NumberX**: A Long number. The Long data type represents a signed, 64-bit wide integer.

Example

```
dataset=myDataset
| where bit != binary_or(101,101)
```

Copy

14.5.3.1.4. BINARY_SHIFT_LEFT

The `binary_shift_left` function returns binary shift left operation on a pair of numbers.

Syntax

```
binary_shift_left( Number1, Number2 )
```

Copy

Arguments

- **NumberX**: An integer.

Example

```
dataset=myDataset
| where bit != binary_shift_left(101,101)
```

Copy

14.5.3.1.5. BINARY_SHIFT_RIGHT

The `binary_shift_right` function returns binary shift right operation on a pair of numbers.

Syntax

```
binary_shift_right( Number1, Number2 )
```

Copy

Arguments

- **NumberX**: A Long number. The Long data type represents a signed, 64-bit wide integer.

Example

```
dataset=myDataset
| where bit != binary_shift_right(101,101)
```

Copy

14.5.3.1.6. BINARY_XOR

The `binary_xor` function returns the bitwise `xor` operation of the two values.

Syntax

```
binary_xor( Number1, Number2 )
```

Copy

Arguments

- **NumberX**: A Long number. The Long data type represents a signed, 64-bit wide integer.

Example

```
dataset=myDataset
| where bit != binary_xor(101,101)
```

Copy

14.5.3.1.7. FROM_BINARY_STRING

The `from_binary_string` function takes a binary string and returns a number.

Syntax

```
from_binary_string( String )
```

Copy

Arguments

- **String**: A binary value.

Example

```
// returns 42
from_binary_string('101010')
```

Copy

14.5.3.1.8. TO_BINARY_STRING

The `to_binary_string` function takes a number and returns a binary string.

Syntax

```
to_binary_string( Number )
```

Copy

Arguments

- **Number**: An integer.

Example

```
// returns '101010'
to_binary_string(42)
```

Copy

14.5.3.2. Conditional Functions

A list of all conditional functions supported by Cribl Search.

Name	Description
`case`	Evaluates a list of predicates and returns the first result expression whose predicate is satisfied.
`coalesce`	Evaluates a list of expressions and returns the first non-null (or non-empty for string) expression.
`iif` (`iff`)	Evaluates the first argument (the predicate), and returns the value of either the second or third arguments, depending on whether the predicate evaluated to `true` (second) or `false` (third).
`max_of`	Returns the maximum value of several evaluated numeric expressions.
`min_of`	Returns the minimum value of several evaluated numeric expressions.

14.5.3.2.1. Case

The `case` function evaluates a list of predicates and returns the first result expression whose predicate is satisfied.

If neither of the predicates return `true`, the result of the last expression (the `else`) is returned. All odd arguments (count starts at 1) must be expressions that evaluate to a `boolean` value. All even arguments (the `thens`) and the last argument (the `else`) must be of the same type.

Syntax

```
case( Predicate_1, Then_1, Predicate_2, Then_2, Predicate_3, Then_3, Else )
```

Copy

Arguments

- **Predicate_i**: An expression that evaluates to a `boolean` value.
- **Then_i**: An expression that gets evaluated and its value is returned from the function if **Predicate_i** is the first predicate that evaluates to `true`.
- **Else**: An expression that gets evaluated and its value is returned from the function if neither of the **Predicate_i** evaluate to `true`.

Results

The value of the first **Then_i** whose **Predicate_i** evaluates to `true`, or the value of **Else** if neither of the predicates is satisfied.

Example

```
dataset=myDataset
| extend bucket = case(Size <= 3, "Small",
                       Size <= 10, "Medium",
                       "Large")
```

Copy

14.5.3.2.2. Coalesce

The `coalesce` function evaluates a list of expressions and returns the first non-null expression.

Syntax

```
coalesce( Expression_1, Expression_2, ... )
```

Copy

Arguments

Expression_i: A scalar expression, to be evaluated.

- All arguments must be of the same type.
- Maximum of 64 arguments is supported.

Results

The value of the first **Expression_1** whose value isn't null (or not-empty for string expressions).

Example

- `coalesce(tolong("not a number"), tolong("42"), 33)` returns as `42`

14.5.3.2.3. Iff

The `iff` function evaluates the first argument (the predicate), and returns the value of either the second or third arguments, depending on whether the predicate evaluated to `true` (second) or `false` (third).

The second and third arguments must be of the same type.

Alias: iif (`iff` and `iif` are synonyms.)

Syntax

```
iff( Predicate, IfTrue, IfFalse )
```

Arguments

- **Predicate**: An expression that evaluates to a `boolean` value.
- **IfTrue**: An expression that gets evaluated and its value returned from the function if **Predicate** evaluates to `true`.
- **IfFalse**: An expression that gets evaluated and its value returned from the function if **Predicate** evaluates to `false`.

Results

This function returns the value of **IfTrue** if predicate evaluates to `true`, or the value of **IfFalse** otherwise.

Example

- `| extend day = iff(floor(Timestamp, 1d)==floor(now(), 1d), "today", "anotherday")`

14.5.3.2.4. IIF

The `iif` function evaluates the first argument (the predicate), and returns the value of either the second or third arguments, depending on whether the predicate evaluated to `true` (second) or `false` (third).

The second and third arguments must be of the same type.

Alias: iff (`iif` and `iff` are synonyms.)

Syntax

```
iif( Predicate, IfTrue, IfFalse )
```

Arguments

- **Predicate**: An expression that evaluates to a `boolean` value.
- **IfTrue**: An expression that gets evaluated and its value returned from the function if **Predicate** evaluates to `true`.
- **IfFalse**: An expression that gets evaluated and its value returned from the function if **Predicate** evaluates to `false`.

Results

This function returns the value of **IfTrue** if predicate evaluates to `true`, or the value of **IfFalse** otherwise.

Example

- `| extend day = iif(floor(Timestamp, 1d)==floor(now(), 1d), "today", "anotherday")`

14.5.3.2.5. MAX_OF

The `max_of` function returns the maximum value of several evaluated numeric expressions.

Syntax

```
max_of( Expression_1, Expression_2, ... )
```

Copy

Arguments

Expression_i: A scalar expression, to be evaluated.

- All arguments must be of the same type.
- Maximum of 64 arguments is supported.
- Non-null values take precedence to null values.

Results

The maximum value of all argument expressions.

Example

- `max_of(10, 1, -3, 17)` returns as `17`

14.5.3.2.6. MIN_OF

The `min_of` function returns the minimum value of several evaluated numeric expressions.

Syntax

```
min_of( Expression_1, Expression_2, ... )
```

Copy

Arguments

Expression_i: A scalar expression, to be evaluated.

- All arguments must be of the same type.
- Maximum of 64 arguments is supported.
- Non-null values take precedence to null values.

Results

The minimum value of all argument expressions.

Example

- `min_of(10, 1, -3, 17)` returns as `-3`

14.5.3.3. Conversion Functions

A list of all conversion functions supported by Cribl Search.

Name	Description
`bin`	Rounds values down to an integer multiple of a given bin size.
`bin_auto`	Rounds values down to a fixed-size bin.
`floor`	Rounds values down to an integer multiple of a given floor size.
`gettype`	Returns the type of the input value.
`tobool`	Converts the input to a `bool` value.
`todouble` (`toreal`, `todecimal`)	Converts the input to a `double` (`real`, `decimal`) value.
`toint` (`tolong`)	Converts the input to an `int` (`long`) value.
`tostring`	Converts the input to a `string` value.

14.5.3.3.1. Bin

The `bin` function rounds values down to an integer multiple of a given bin size. If you have a scattered set of values, they'll be grouped into a smaller set of specific values.

Null values, a null bin size, or a negative bin size results in `null`.

You can use this function with the `summarize` and `eventstats` operators.

Syntax

```
bin( Value, RoundTo )
```

Copy

Arguments

- **Value**: A number, date, or timespan.
- **RoundTo**: The "bin size". A number or timespan that divides value.

Returns

The nearest multiple of **RoundTo** below value.

Examples

- `bin(4.5, 1)` results in `4.0`
- `bin(time(16d), 7d)` results in `14d`
- `bin(datetime(1970-05-11 13:45:07), 1d)` results in `datetime(1970-05-11)`

The following expression calculates a histogram of durations, with a bucket size of 1 second:

```
dataset=myDataset
| summarize Hits=count() by bin(Duration, 1s)
```

Copy

14.5.3.3.2. BIN_AUTO

The `bin_auto` function rounds values down to a fixed-size “bin”, with control over the bin size and starting point provided by an option property.

You can use this function with the `summarize` and `eventstats` operators.

Syntax

```
bin_auto( Expression )
```

Copy

with option:

```
set OptionName [ = OptionValue ] ; ... | ... bin_auto( Expression )
```

Copy

Arguments

- **Expression**: A scalar expression of a numeric type indicating the value to round.
- **OptionName**:
  - `query_bin_auto_size`: Time period. Supports these relative times - `s[econds]`, `m[inutes]`, `h[ours]`, and `d[ays]`.
  - `query_bin_auto_buckets`: Numeric literal, desired number of buckets to be created by `bin_auto`. Buckets are split as close as possible based on the search’s time range.

Rules

- The total number of buckets will vary based on the time range.
- Values without units get interpreted as seconds. (For example, `-1 = -1s`.)

Example

```
set query_bin_auto_size=1h;
dataset=myDataset
| summarize count() by bin_auto(timestamp)
```

Copy

14.5.3.3.3. Floor

The `floor` function rounds values down to an integer multiple of a given floor size. If you have a scattered set of values, they'll be grouped into a smaller set of specific values.

Null values, a null floor size, or a negative floor size results in `null`.

You can use this function with the `summarize` and `eventstats` operators.

Syntax

```
floor( Value [, RoundTo ] )
```

Copy

Arguments

- **Value**: A number, date, or timespan.
- **RoundTo**: The "floor size". A number or timespan that divides value. Defaults to `1`.

Returns

The nearest multiple of **RoundTo** below value.

Examples

- `floor(4.5, 1)` results in `4`
- `floor(3.14)` results in `3`.
- `floor(time(16d), 7d)` results in `14d`
- `floor(datetime(1970-05-11 13:45:07), 1d)` results in `datetime(1970-05-11)`

The following expression calculates a histogram of durations, with a bucket size of 1 second:

```
dataset=myDataset
| summarize Hits=count() by floor(Duration, 1s)
```

Copy

14.5.3.3.4. GETTYPE

The `gettype` function returns the type of the input value.

Syntax

```
gettype( Expression )
```

Arguments

- **Expression**: The value whose type you want to check.

Returns

Depending on the input, returns one of the following strings:

Input	Returned string	Input examples
A boolean	`bool`	`true`, `false`, `3 < 5`
A number	`int` for values in range `-2^31...2^31-1`.	`3`, `1000`
	`long` for values in range `-2^63...2^63-1` but greater than `int`.	`2 ** 40`
	`decimal` for values greater than `long`.	`2 ** 65`
	`real`	`3.15`, `3 / 5`
	`NaN`	`NaN`
A `bigint`	Same as a number: `int`, `long`, or `decimal`, based on the value range.	`BigInt(1234567890123456789)`
A string	`string`	`'Aloa'`
`[]`	`array`	`[17, 3]`
`{}`	`dictionary`	`{ foo: 'bar' }`
`null`	`null`	`null`
Undefined	`null`	Undefined field reference

Input	Returned string	Input examples
Anything else, like functions	unknown	`coalesce(33)`

Examples

Input	Output
`true`	`bool`
`false`	`bool`
`0`	`int`
`42`	`int`
`2 ** 40`	`long`
`BigInt(2 ** 60)`	`long`
`3.1415`	`real`
`2 ** 65`	`decimal`
`BigInt(2 ** 65)`	`decimal`
`[17, 3]`	`array`
`{ foo: "bar" }`	`dictionary`
`Number.NaN`	`NaN`
`null`	`null`
Undefined	`null`
`() => 42`	`unknown`

14.5.3.3.5. Tobool

The `tobool` function converts the input to a value of type `bool`.

Aliases: `bool`.

Syntax

```
tobool( Expression )
```

Arguments

- **Expression**: Expression to convert to a `bool` value.

Returns

If the type conversion is successful, returns a `bool` value.

If the type conversion fails, returns `null`.

Examples

Query	Result
`tobool("true")`	`true`
`tobool("TRUE")`	`true`
`tobool("yes")`	`true`
`tobool("false")`	`false`
`tobool("f")`	`false`
`tobool(1)`	`true`
`tobool("1")`	`true`
`tobool(123)`	`true`
`tobool(0)`	`false`
`tobool(0.0)`	`false`

Query	Result
`tobool("abc")`	`null`
`tobool(null)`	`null`

14.5.3.3.6. Todecimal

The `todecimal` function converts the input to a value of type `decimal` (`double`, `real`).

Aliases: `decimal`, `double`, `todouble`, `real`, `toreal`.

Syntax

```
todecimal( Expression )
```

Arguments

- **Expression**: Expression whose value will be converted to a value of type `decimal`.

Returns

If the type conversion is successful, the result is a value of type `decimal` (`double`, `real`).

If the type conversion fails, returns `null`.

Examples

- `todecimal("123.4")` returns `123.4`
- `todecimal("1e3")` returns `1000`
- `todecimal("hello")` returns `null`

14.5.3.3.7. todouble

The `todouble` function converts the input to a value of type `double` (`real`, `decimal`).

Aliases: `double`, `decimal`, `todecimal`, `real`, `toreal`.

Syntax

```
todouble( Expression )
```

Arguments

- **Expression**: Expression whose value will be converted to a value of type `double`.

Returns

If the type conversion is successful, the result is a value of type `double` (`real`, `decimal`).

If the type conversion fails, returns `null`.

Example

- `todouble("123.4")` returns `123.4`
- `todouble("1e3")` returns `1000`
- `todouble("hello")` returns `null`

14.5.3.3.8. TOINT

The `toint` function converts the input to a value of type `int` (`long`).

Aliases: `int`, `long`, `tolong`.

Syntax

```
toint( Expression )
```

Arguments

- **Expression**: Expression to convert to a value of type `int`.

Returns

If the type conversion is successful, returns an `int` value. Decimal places are truncated.

If the type conversion fails, returns `null`.

Examples

- `toint(123)` returns `123`
- `toint("123.456")` returns `123`
- `toint("abc")` returns `null`

14.5.3.3.9. TOLONG

The `tolong` function converts the input to a value of type `long` (`int`).

Aliases: `long`, `int`, `toint`.

Syntax

```
tolong( Expression )
```

Arguments

- **Expression**: Expression to convert to a value of type `long`.

Returns

If the type conversion is successful, returns a `long` number. Decimal places are truncated.

If the type conversion fails, returns `null`.

Example

- `tolong(123)` returns `123`
- `tolong("123.456")` returns `123`
- `tolong("abc")` returns `null`

14.5.3.3.10. TOREAL

The `toreal` function converts the input to a value of type `real` (`double`, `decimal`).

Aliases: `real`, `decimal`, `todecimal`, `double`, `todouble`.

Syntax

```
toreal( Expression )
```

Arguments

- **Expression**: Expression whose value will be converted to a value of type `real`.

Returns

If the type conversion is successful, returns a value of type `real` (`double`, `decimal`).

If the type conversion fails, returns `null`.

Example

- `toreal("123.4")` returns `123.4`
- `toreal("1e3")` returns `1000`
- `toreal("hello")` returns `null`

14.5.3.3.11. TOSTRING

The `tostring` function converts the input to a value of type `string`.

Syntax

```
tostring( Expression )
```

Arguments

- **Expression**: Expression to convert to a string.

Returns

If the **Expression** value is non-null, returns a string representation of **Expression**.

If the **Expression** value is `null`, returns `null` as well.



This is different from standard Kusto Query Language (KQL), in which `tostring` returns an empty string for `null` values.

Example

- `tostring(123)` returns `"123"`
- `tostring("hello")` returns `"hello"`
- `tostring(null)` returns `null`
- `tostring(dynamic({"a":1,"b":2}))` returns `'{"a":1,"b":2}'`
- `tostring(dynamic([1,2,3]))` returns `'[1,2,3]'`

14.5.3.4. DateTime Functions

A list of all DateTime functions supported by Cribl Search.

Name	Description
`ago`	Subtracts the given timespan from the current UTC clock time.
`datetime_add`	Calculates a new datetime from a specified datepart multiplied by a specified amount, added to a specified datetime.
`datetime_diff`	Calculates the number of the specified periods between two datetime values.
`datetime_part`	Extracts the requested date part as an integer value.
`dayofmonth`	Returns the integer number representing the day number of the given month.
`dayofweek`	Returns an integer between `0` and `6` representing the day of the week, beginning on Sunday.
`dayofyear`	Returns the integer number representing the day number of the given year.
`endofday`	Returns the end of the day containing the date, shifted by an offset, if provided.
`endofmonth`	Returns the end of the month containing the date, shifted by an offset, if provided.
`endofweek`	Returns the end of the week containing the date, shifted by an offset, if provided.
`endofyear`	Returns the end of the year containing the date, shifted by an offset, if provided.
`format_datetime`	Formats a datetime according to the provided format.
`format_timespan`	Formats a timespan according to the provided format.
`getmonth` (`monthofyear`)	Gets the month number (1-12) from a datetime.
`getyear` (`yearofyear`)	Returns the year part of a datetime.
`hourofday`	Returns the integer number representing the hour number of the given date.

Name	Description
make_datetime	Converts the specified date and time into a datetime value (Unix time in seconds).
make_timespan	Converts the specified time period into a datetime value (Unix time in seconds).
now	Returns the current UTC clock time as a datetime value (Unix time in seconds).
startofday	Returns the start of the day containing the date, shifted by an offset, if provided.
startofmonth	Returns the start of the month containing the date, shifted by an offset, if provided.
startofweek	Returns the start of the week containing the date, shifted by an offset, if provided.
startofyear	Returns the start of the year containing the date, shifted by an offset, if provided.
strftime (format_time)	Converts a datetime (date) object to a human-readable string.
strptime (parse_time)	Converts a string to a datetime.
todatetime	Converts the input into a datetime value (Unix time in seconds).
totimespan	Converts the input into a number of seconds.
unixtime_microseconds_todatetime	Converts the input into a datetime value (Unix time in seconds).
unixtime_milliseconds_todatetime	Converts the input into a datetime value (Unix time in seconds).
unixtime-nanoseconds_todatetime	Converts the input into a datetime value (Unix time in seconds).
unixtime_seconds_todatetime	Converts the input into a datetime value (Unix time in seconds).
week_of_year	Returns an integer representing the week number.

14.5.3.4.1. Ago

The `ago` function subtracts the given timespan from the current UTC clock time.

Like now, this function can be used multiple times in a statement and the UTC clock time being referenced will be the same for all instantiations.

Syntax

```
ago( Timespan )
```

Copy

Arguments

- **Timespan**: Interval to subtract from the current UTC clock time.

Returns

`now() - Timespan`

Examples

This example subtracts two days from the current time, using, strftime to format the result as a human-readable date:

```
print newDate = ago(2d)
| extend prettyDate = strftime( newDate, '%x' )
```

Copy Run in Cribl Search

This example returns all rows with a timestamp in the past hour:

```
dataset=myDataset
| where Timestamp > ago(1h)
```

Copy

14.5.3.4.2. DATETIME_ADD

The `datetime_add` function calculates a new datetime from a specified datepart multiplied by a specified amount, added to a specified datetime.

Syntax

```
datetime_add( Period, Amount, Datetime )
```

Copy

Arguments

- **Period**: Possible values are: `Year`, `Quarter`, `Month`, `Week`, `Day`, `Hour`, `Minute`, `Second`, `Millisecond`, `Microsecond`, `Nanosecond`.
- **Amount**: An integer.
- **Datetime**: A datetime.

Returns

A date after a certain time/date interval has been added, represented as `datetime` (Unix time).

Examples

This example adds two days to the specified date:

```
print newDate=datetime_add( 'day', 2, make_datetime( 2025,12,31 ) )
| extend prettyDate = strftime( newDate, '%x'  )
```

Copy Run in Cribl Search

The following examples illustrate calling this function with different values for the `Period` argument:

```
print year = datetime_add('year',1,make_datetime(2025,1,1))
```

Copy Run in Cribl Search

```
print month = datetime_add('month',1,make_datetime(2025,1,1))
```

Copy Run in Cribl Search

```
print quarter = datetime_add('quarter',1,make_datetime(2025,1,1))
```

Copy Run in Cribl Search

```
print week = datetime_add('week',1,make_datetime(2025,1,1))
```

Copy Run in Cribl Search

```
print day = datetime_add('day',1,make_datetime(2025,1,1))
```

Copy Run in Cribl Search

```
print hour = datetime_add('hour',1,make_datetime(2025,1,1))
```

Copy Run in Cribl Search

```
print minute = datetime_add('minute',1,make_datetime(2025,1,1))
```

Copy Run in Cribl Search

```
print second = datetime_add('second',1,make_datetime(2025,1,1))
```

Copy Run in Cribl Search

14.5.3.4.3. DATETIME_DIFF

The `datetime_diff` function calculates the number of the specified periods between two datetime values.

Syntax

```
datetime_diff( Period, Datetime1, Datetime2 )
```

Copy

Arguments

- **Period**: Possible values are: `Year`, `Quarter`, `Month`, `Week`, `Day`, `Hour`, `Minute`, `Second`, `Millisecond`, `Microsecond`, `Nanosecond`.
- **DatetimeX**: A datetime.

Returns

An integer, which represents amount of **Period**s in the result of subtraction `(Datetime1 - Datetime2)`.

Examples

The following examples illustrate calling this function with different values for the `Period` argument:

```
printyear = datetime_diff('year',datetime(2017-01-01),datetime(2000-12-31))
```

Copy Run in Cribl Search

```
printquarter = datetime_diff('quarter',datetime(2017-07-01),datetime(2017-03-30))
```

Copy Run in Cribl Search

```
printmonth = datetime_diff('month',datetime(2017-01-01),datetime(2015-12-30))
```

Copy Run in Cribl Search

```
printweek = datetime_diff('week',datetime(2017-10-29 00:00),datetime(2017-09-30 23:59
```

Copy Run in Cribl Search

```
printday = datetime_diff('day',datetime(2017-10-29 00:00),datetime(2017-09-30 23:59))
```

Copy Run in Cribl Search

```
printhour = datetime_diff('hour',datetime(2017-10-31 01:00),datetime(2017-10-30 23:59
```

Copy Run in Cribl Search

```
printminute = datetime_diff('minute',datetime(2017-10-30 23:05:01),datetime(2017-10-3
```

Copy Run in Cribl Search

```
printsecond = datetime_diff('second',datetime(2017-10-30 23:00:10.100),datetime(2017-
```

Copy Run in Cribl Search

```
printmillisecond = datetime_diff('millisecond',datetime(2017-10-30 23:00:00.200100),d
```

Copy Run in Cribl Search

```
printmicrosecond = datetime_diff('microsecond',datetime(2017-10-30 23:00:00.1009001),
```

Copy Run in Cribl Search

```
printnanosecond = datetime_diff('nanosecond',datetime(2017-10-30 23:00:00.0000000),da
```

Copy Run in Cribl Search

14.5.3.4.4. DATETIME_PART

The `datetime_part` function extracts the requested date part as an integer value.

Syntax

```
datetime_part( Part, Datetime )
```

Copy

Arguments

- **Part**: Possible values are: `Year`, `Quarter`, `Month`, `week_of_year`, `Day`, `DayOfYear`, `Hour`, `Minute`, `Second`, `Millisecond`, `Microsecond`, `Nanosecond`.
- **Datetime**: A datetime.

Returns

An integer representing the extracted part.



`week_of_year` returns an integer that represents the week number. The week number is calculated from the first week of a year, which is the one that includes the first Thursday.

Examples

The following examples illustrate calling this function with different values for the `Part` argument:

```
let dt = datetime(2017-10-30 01:02:03.7654321);
print year = datetime_part("year", dt)
```

Copy Run in Cribl Search

```
let dt = datetime(2017-10-30 01:02:03.7654321);
print quarter = datetime_part("quarter", dt)
```

Copy Run in Cribl Search

```
let dt = datetime(2017-10-30 01:02:03.7654321);
print month = datetime_part("month", dt)
```

Copy Run in Cribl Search

```
let dt = datetime(2017-10-30 01:02:03.7654321);
print weekOfYear = datetime_part("week_of_year", dt)
```

Copy Run in Cribl Search

```
let dt = datetime(2017-10-30 01:02:03.7654321);
print day = datetime_part("day", dt)
```

Copy Run in Cribl Search

```
let dt = datetime(2017-10-30 01:02:03.7654321);
print dayOfYear = datetime_part("dayOfYear", dt)
```

Copy Run in Cribl Search

```
let dt = datetime(2017-10-30 01:02:03.7654321);
print hour = datetime_part("hour", dt)
```

Copy Run in Cribl Search

```
let dt = datetime(2017-10-30 01:02:03.7654321);
print minute = datetime_part("minute", dt)
```

Copy Run in Cribl Search

```
let dt = datetime(2017-10-30 01:02:03.7654321);
print second = datetime_part("second", dt)
```

Copy Run in Cribl Search

```
let dt = datetime(2017-10-30 01:02:03.7654321);
print millisecond = datetime_part("millisecond", dt)
```

Copy Run in Cribl Search

```
let dt = datetime(2017-10-30 01:02:03.7654321);
print microsecond = datetime_part("microsecond", dt)
```

Copy Run in Cribl Search

```
let dt = datetime(2017-10-30 01:02:03.7654321);
print nanosecond = datetime_part("nanosecond", dt)
```

Copy Run in Cribl Search

14.5.3.4.5. DAYOFMONTH

The `dayofmonth` function returns the integer number representing the day number of the given month.

Syntax

```
dayofmonth( Date )
```

Copy

Arguments

- **Date**: A `datetime`.

Returns

The day number of the given month.

Example

This example returns `14`:

```
print dayofmonth(datetime(2015-12-14))
```

Copy Run in Cribl Search

14.5.3.4.6. DAYOFWEEK

The `dayofweek` function returns an integer between `0` and `6` representing the day of the week, beginning on Sunday.



This differs from the standard Kusto `dayofweek` function, which returns a timespan.

Syntax

```
dayofweek( Date )
```

Copy

Arguments

- **Date**: A `datetime`.

Returns

The `timespan` since midnight at the beginning of the preceding Sunday, rounded down to an integer number of days.

Example

This example returns `2 for Tuesday:

```
print dayofweek( datetime(2025-12-16) )
```

Copy Run in Cribl Search

14.5.3.4.7. DAYOFYEAR

The `dayofyear` function returns the integer number representing the day number of the given year.

Syntax

```
dayofyear( Date )
```

Copy

Arguments

- **Date**: A `datetime`.

Returns

The day number of the given year.

Example

This example returns `348`:

```
print dayofyear( datetime(2025-12-14) )
```

Copy Run in Cribl Search

14.5.3.4.8. ENDOFDAY

The `endofday` function returns the end of the day containing the date, shifted by an offset, if provided.

Syntax

```
endofday( Date [, Offset] )
```

Copy

Arguments

- **Date**: The input date.
- **Offset**: An optional number of offset days from the input date (integer, default - 0).

Returns

A `datetime` representing the end of the day for the given **Date** value, with the offset, if specified.

Example

This example returns `1,766,707,199.999`, representing `Thu Dec 25 2025 23:59:59 GMT+0000`:

```
project dayEnd = endofday( datetime(2025-12-24), 1 )
```

Copy | Run in Cribl Search

14.5.3.4.9. ENDOFMONTH

The `endofmonth` function returns the end of the month containing the date, shifted by an offset, if provided.

Syntax

```
endofmonth( Date [, Offset] )
```

Copy

Arguments

- **Date**: The input date.
- **Offset**: An optional number of offset months from the input date (integer, default - 0).

Returns

A `datetime` representing the end of the month for the given **Date** value, with the offset, if specified.

Example

This example returns `1,769,903,999.999`, representing `Sat Jan 31 2026 23:59:59 GMT+0000`:

```
print monthEnd = endofmonth( datetime(2025-12-21 10:10:17), 1 )
```

Copy Run in Cribl Search

14.5.3.4.10. ENDOFWEEK

The `endofweek` function returns the end of the week containing the date, shifted by an offset, if provided.

Last day of the week is considered to be a Saturday.

Syntax

```
endofweek( Date [, Offset] )
```

Copy

Arguments

- **Date**: The input date.
- **Offset**: An optional number of offset weeks from the input date (integer, default - 0).

Returns

A `datetime` representing the end of the week for the given **Date** value, with the offset, if specified.

Example

This example returns `1,767,484,799.999`, representing `Sat Jan 31 2026 23:59:59 GMT+0000`:

```
print weekEnd = endofweek( datetime(2025-12-21 10:10:17), 1)
```

Copy Run in Cribl Search

14.5.3.4.11. ENDOFYEAR

The `endofyear` function returns the end of the year containing the date, shifted by an offset, if provided.

Syntax

```
endofyear( Date [, Offset] )
```

Copy

Arguments

- **Date**: The input date.
- **Offset**: An optional number of offset years from the input date (integer, default - 0).

Returns

A `datetime` representing the end of the year for the given **Date** value, with the offset, if specified.

Example

This example returns `1,798,761,599.999`, representing `Wed Dec 31 2026 23:59:59 GMT+0000`:

```
print yearEnd = endofyear( datetime(2025-10-31 10:10:17), 1)
```

Copy Run in Cribl Search

14.5.3.4.12. FORMAT_DATETIME

The `format_datetime` function formats a `datetime` according to the provided format.

Syntax

```
format_datetime( Datetime, Format)
```

Copy

Arguments

- **Datetime**: A `datetime`.
- **Format**: Format specifier string, consisting of one or more format elements.

Returns

The string with the format result.

Supported Formats

Format specifier	Description	Examples
`d`	The day of the month, from 1 through 31.	2009-06-01T13:45:30 -> 1, 2009-06-15T13:45:30 -> 15
`dd`	The day of the month, from 01 through 31.	2009-06-01T13:45:30 -> 01, 2009-06-15T13:45:30 -> 15
`f`	The tenths of a second in a date and time value.	2009-06-15T13:45:30.6170000 -> 6, 2009-06-15T13:45:30.05 -> 0
`ff`	The hundredths of a second in a date and time value.	2009-06-15T13:45:30.6170000 -> 61, 2009-06-15T13:45:30.0050000 -> 00
`fff`	The milliseconds in a date and time value.	6/15/2009 13:45:30.617 -> 617, 6/15/2009 13:45:30.0005 -> 000
`ffff`	The ten thousandths of a second in a date and time value.	2009-06-15T13:45:30.6175000 -> 6175, 2009-06-15T13:45:30.0000500 -> 0000

Format specifier	Description	Examples
`fffff`	The hundred thousandths of a second in a date and time value.	2009-06-15T13:45:30.6175400 -> 61754, 2009-06-15T13:45:30.000005 -> 00000
`ffffff`	The millionths of a second in a date and time value.	2009-06-15T13:45:30.6175420 -> 617542, 2009-06-15T13:45:30.0000005 -> 000000
`fffffff`	The ten millionths of a second in a date and time value.	2009-06-15T13:45:30.6175425 -> 6175425, 2009-06-15T13:45:30.0001150 -> 0001150
`F`	If non-zero, the tenths of a second in a date and time value.	2009-06-15T13:45:30.6170000 -> 6, 2009-06-15T13:45:30.0500000 -> (no output)
`FF`	If non-zero, the hundredths of a second in a date and time value.	2009-06-15T13:45:30.6170000 -> 61, 2009-06-15T13:45:30.0050000 -> (no output)
`FFF`	If non-zero, the milliseconds in a date and time value.	2009-06-15T13:45:30.6170000 -> 617, 2009-06-15T13:45:30.0005000 -> (no output)
`FFFF`	If non-zero, the ten thousandths of a second in a date and time value.	2009-06-15T13:45:30.5275000 -> 5275, 2009-06-15T13:45:30.0000500 -> (no output)
`FFFFF`	If non-zero, the hundred thousandths of a second in a date and time value.	2009-06-15T13:45:30.6175400 -> 61754, 2009-06-15T13:45:30.0000050 -> (no output)
`FFFFFF`	If non-zero, the millionths of a second in a date and time value.	2009-06-15T13:45:30.6175420 -> 617542, 2009-06-15T13:45:30.0000005 -> (no output)
`FFFFFFF`	If non-zero, the ten millionths of a second in a date and time value.	2009-06-15T13:45:30.6175425 -> 6175425, 2009-06-15T13:45:30.0001150 -> 0001150
`h`	The hour, using a 12-hour clock from 1 to 12.	2009-06-15T01:45:30 -> 1, 2009-06-15T13:45:30 -> 1
`hh`	The hour, using a 12-hour clock from 01 to 12.	2009-06-15T01:45:30 -> 01, 2009-06-15T13:45:30 -> 01
`H`	The hour, using a 24-hour clock from 0 to 23.	2009-06-15T01:45:30 -> 1, 2009-06-15T13:45:30 -> 13
`HH`	The hour, using a 24-hour clock from 00 to 23.	2009-06-15T01:45:30 -> 01, 2009-06-15T13:45:30 -> 13
`m`	The minute, from 0 through 59.	2009-06-15T01:09:30 -> 9, 2009-06-15T13:29:30 -> 29

Format specifier	Description	Examples
`mm`	The minute, from 00 through 59.	2009-06-15T01:09:30 -> 09, 2009-06-15T01:45:30 -> 45
`M`	The month, from 1 through 12.	2009-06-15T13:45:30 -> 6
`MM`	The month, from 01 through 12.	2009-06-15T13:45:30 -> 06
`s`	The second, from 0 through 59.	2009-06-15T13:45:09 -> 9
`ss`	The second, from 00 through 59.	2009-06-15T13:45:09 -> 09
`y`	The year, from 0 to 99.	0001-01-01T00:00:00 -> 1, 0900-01-01T00:00:00 -> 0, 1900-01-01T00:00:00 -> 0, 2009-06-15T13:45:30 -> 9, 2019-06-15T13:45:30 -> 19
`yy`	The year, from 00 to 99.	0001-01-01T00:00:00 -> 01, 0900-01-01T00:00:00 -> 00, 1900-01-01T00:00:00 -> 00, 2019-06-15T13:45:30 -> 19
`yyyy`	The year as a four-digit number.	0001-01-01T00:00:00 -> 0001, 0900-01-01T00:00:00 -> 0900, 1900-01-01T00:00:00 -> 1900, 2009-06-15T13:45:30 -> 2009
`tt`	AM / PM `hours`	2009-06-15T13:45:09 -> PM

Supported Delimiters

Format specifier can include following delimiter characters:

Delimiter	Comment
	Space
`/`	
`-`	Dash
`:`	
`,`	
`.`	
`\_`	
`[`	

Delimiter	Comment
]	

Examples

This example returns `17-01-29 [09:00:05]`:

```
let dt = datetime(2017-01-29 09:00:05);
print v1=format_datetime(dt,'yy-MM-dd [HH:mm:ss]')
```

Copy Run in Cribl Search

This example returns `2017-1-29 [9:00:05]`:

```
let dt = datetime(2017-01-29 09:00:05);
print v2=format_datetime(dt, 'yyyy-M-dd [H:mm:ss]')
```

Copy Run in Cribl Search

This example returns `17-01-29 [09:00:05 AM]`:

14.5.3.4.13. FORMAT_TIMESPAN

The `format_timespan` function formats a timespan according to the provided format.

Syntax

```
format_timespan( Timespan, Format)
```

Copy

Arguments

- **Timespan**: A timespan.
- **Format**: Format specifier string, consisting of one or more format elements.

Returns

The string with the format result.

Supported Formats

Format specifier	Description	Examples
`d-dddddddd`	The number of whole days in the time interval. Padded with zeros if needed.	15.13:45:30: d -> 15, dd -> 15, ddd -> 015
`f`	The tenths of a second in the time interval.	15.13:45:30.6170000 -> 6, 15.13:45:30.05 -> 0
`ff`	The hundredths of a second in the time interval.	15.13:45:30.6170000 -> 61, 15.13:45:30.0050000 -> 00
`fff`	The milliseconds in the time interval.	6/15/2009 13:45:30.617 -> 617, 6/15/2009 13:45:30.0005 -> 000
`ffff`	The ten thousandths of a second in the time interval.	15.13:45:30.6175000 -> 6175, 15.13:45:30.0000500 -> 0000
`fffff`	The hundred thousandths of a second in the time interval.	15.13:45:30.6175400 -> 61754, 15.13:45:30.000005 -> 00000

Format specifier	Description	Examples
`ffffff`	The millionths of a second in the time interval.	15.13:45:30.6175420 -> 617542, 15.13:45:30.0000005 -> 000000
`fffffff`	The ten millionths of a second in the time interval.	15.13:45:30.6175425 -> 6175425, 15.13:45:30.0001150 -> 0001150
`F`	If non-zero, the tenths of a second in the time interval.	15.13:45:30.6170000 -> 6, 15.13:45:30.0500000 -> (no output)
`FF`	If non-zero, the hundredths of a second in the time interval.	15.13:45:30.6170000 -> 61, 15.13:45:30.0050000 -> (no output)
`FFF`	If non-zero, the milliseconds in the time interval.	15.13:45:30.6170000 -> 617, 15.13:45:30.0005000 -> (no output)
`FFFF`	If non-zero, the ten thousandths of a second in the time interval.	15.13:45:30.5275000 -> 5275, 15.13:45:30.0000500 -> (no output)
`FFFFF`	If non-zero, the hundred thousandths of a second in the time interval.	15.13:45:30.6175400 -> 61754, 15.13:45:30.0000050 -> (no output)
`FFFFFF`	If non-zero, the millionths of a second in the time interval.	15.13:45:30.6175420 -> 617542, 15.13:45:30.0000005 -> (no output)
`FFFFFFF`	If non-zero, the ten millionths of a second in the time interval.	15.13:45:30.6175425 -> 6175425, 15.13:45:30.0001150 -> 000115
`H`	The hour, using a 24-hour clock from 0 to 23.	15.01:45:30 -> 1, 15.13:45:30 -> 13
`HH`	The hour, using a 24-hour clock from 00 to 23.	15.01:45:30 -> 01, 15.13:45:30 -> 13
`m`	The number of whole minutes in the time interval that are not included as part of hours or days. Single-digit minutes do not have a leading zero.	15.01:09:30 -> 9, 15.13:29:30 -> 29
`mm`	The number of whole minutes in the time interval that are not included as part of hours or days. Single-digit minutes have a leading zero.	15.01:09:30 -> 09, 15.01:45:30 -> 45
`s`	The number of whole seconds in the time interval that are not included as part of hours, days, or minutes.	15.13:45:09 -> 9

Format specifier	Description	Examples
	Single-digit seconds do not have a leading zero.	
ss	The number of whole seconds in the time interval that are not included as part of hours, days, or minutes. Single-digit seconds have a leading zero.	15.13:45:09 -> 09

Supported Delimiters

Format specifier can include following delimiter characters:

Delimiter	Comment
	Space
/	
-	Dash
:	
,	
.	
_	
[	
]	

Examples

This example returns `29.09:00:05:12`:

```
let t = make_timespan(1,12,30,55.123);
print v1=format_timespan(t, 'dd.hh:mm:ss:FF')
```

Copy Run in Cribl Search

This example returns `001.12:30:55 [1230000]`:

14.5.3.4.14. GETMONTH

The `getmonth` function gets the month number (1-12) from a `datetime`.

Alias: `monthofyear`

Syntax

```
getmonth( Datetime )
```

Copy

Arguments

- **Datetime**: A `datetime`.

Example

This example returns `10`:

```
print month = getmonth( datetime(2025-10-14) )
```

Copy Run in Cribl Search

14.5.3.4.15. GETYEAR

The `getyear` function returns the year part of a `datetime`.

Alias: `yearofyear`

Syntax

```
getyear( Datetime )
```

Copy

Arguments

- **Datetime**: A `datetime`.

Example

This example returns `2025`:

```
print year = getyear( datetime(2025-07-14) )
```

Copy Run in Cribl Search

14.5.3.4.16. HOUROFDAY

The `hourofday` function returns the integer representing the hour number of the given date.

Syntax

```
hourofday( Datetime )
```

Copy

Arguments

- **Datetime**: A `datetime`.

Returns

The hour number of the day (0-23).

Example

This example returns `18`:

```
print hourofday( datetime(2025-11-30 18:54) )
```

Copy Run in Cribl Search

14.5.3.4.17. MAKE_DATETIME

The `make_datetime` function converts the specified date and time into a `datetime` value (Unix time in seconds).



To convert `datetime` (Unix time) into a `string`, or vice versa, use the `strftime` and `strptime` functions.

Syntax

```
make_datetime( Year, Month, Day [, Hour] [, Minute] [, Second])
```

Arguments

- **Year**: year (an integer value, from 0 to 9999)
- **Month**: month (an integer value, from 1 to 12)
- **Day**: day (an integer value, from 1 to 28-31)
- **Hour**: hour (an integer value, from 0 to 23)
- **Minute**: minute (an integer value, from 0 to 59)
- **Second**: second (a real value, from 0 to 59.9999999)

Returns

If creation is successful, result will be a `datetime` value; otherwise, the result will be `null`.

Example

This example returns `1506729600`:

```
print year_month_day = make_datetime(2017,10,0)
```

Copy Run in Cribl Search

14.5.3.4.18. MAKE_TIMESPAN

The `make_timespan` function converts the specified time period into a number of seconds.



This output format differs from the standard Kusto `make_timespan` function, which returns a timespan.

To convert `datetime` (Unix time) into a `string`, or vice versa, use the `strftime` and `strptime` functions.

Syntax

```
make_timespan( [ Day ,] Hour, Minute [, Second])
```

Arguments

- **Day**: day (an integer value, from 1 to 28-31)
- **Hour**: hour (an integer value, from 0 to 23)
- **Minute**: minute (an integer value, from 0 to 59)
- **Second**: second (a real value, from 0 to 59.9999999)

Returns

If creation is successful, the result will be the number of seconds in the interval. Otherwise, the result will be `null`.

Examples

This example returns `131455.123`:

```
print make_timespan(1,12,30,55.123)
```

Copy Run in Cribl Search

This example returns `3600`:

```
print make_timespan(1, 0)
```

Copy Run in Cribl Search

14.5.3.4.19. MONTHOFYEAR

The `monthofyear` function returns the integer number representing the month number of the given year.

Syntax

```
monthofyear( Datetime )
```

Copy

Arguments

- **Datetime**: A `datetime`.

Returns

The month number of the given year.

Example

This example returns `11`:

```
print monthofyear( datetime("2025-11-30") )
```

Copy Run in Cribl Search

14.5.3.4.20. Now

The `now` function returns the current UTC clock time as a datetime value (Unix time in seconds), optionally offset by a given timespan.

You can use `now` multiple times in a statement and the clock time being referenced will be the same for all instances.



To convert `datetime` (Unix time) into a `string`, or vice versa, use the `strftime` and `strptime` functions.

Syntax

```
now( [ Offset ] )
```

Arguments

- **Offset**: A timespan, added to the current UTC clock time. Default: 0.

Returns

The current UTC clock time as a `datetime`.

Examples

This returns the current time, in Unix time:

```
print now()
```

Copy Run in Cribl Search

This returns the current time two days earlier, in Unix time:

```
print now(-2d)
```

Copy Run in Cribl Search

14.5.3.4.21. STARTOFDAY

The `startofday` function returns the start of the day containing the date, shifted by an offset, if provided.

Syntax

```
startofday( Date, Offset )
```

Copy

Arguments

- **Date**: The input date.
- **Offset**: An optional number of offset days from the input date (integer, default - 0).

Returns

A `datetime` representing the start of the day for the given **Date** value, with the offset, if specified.

Example

This example returns `1641081600`:

```
print dayStart = startofday( datetime(2022-01-01 10:10:17), 1 )
```

Copy | Run in Cribl Search

14.5.3.4.22. STARTOFMONTH

The `startofmonth` function returns the start of the month containing the date, shifted by an offset, if provided.

Syntax

```
startofmonth( Date, Offset )
```

Copy

Arguments

- **Date**: The input date.
- **Offset**: An optional number of offset months from the input date (integer, default - 0).

Returns

A `datetime` representing the start of the month for the given **Date** value, with the offset, if specified.

Example

This example returns `1664582400`:

```
print monthStart = startofmonth( datetime(2022-09-01 10:10:17), 1 )
```

Copy Run in Cribl Search

14.5.3.4.23. STARTOFWEEK

The `startofweek` function returns the start of the week containing the date, shifted by an offset, if provided.

Start of the week is considered to be a Sunday.

Syntax

```
startofweek( Date, Offset )
```

Copy

Arguments

- **Date**: The input date.
- **Offset**: An optional number of offset weeks from the input date (integer, default - 0).

Returns

A `datetime` representing the start of the week for the given **Date** value, with the offset, if specified.

Example

This example returns `1,662,249,600`:

```
print weekStart = startofweek( datetime(2022-09-01 10:10:17), 1 )
```

Copy Run in Cribl Search

14.5.3.4.24. Startofyear

The `startofyear` function returns the start of the year containing the date, shifted by an offset, if provided.

Syntax

```
startofyear( Date, Offset )
```

Copy

Arguments

- **Date**: The input date.
- **Offset**: An optional number of offset years from the input date (integer, default - 0).

Returns

A `datetime` representing the start of the year for the given **Date** value, with the offset, if specified.

Example

This example returns `1,767,225,600`:

```
print yearStart = startofyear( datetime(2025-12-01 10:10:17), 1 )
```

Copy Run in Cribl Search

14.5.3.4.25. STRFTIME

The `strftime` function converts a `datetime` (date) object to a human-readable string.

Alias: `format_time`

Syntax

```
strftime( TimeSeconds, FormatString )
```

Copy

Arguments

- **TimeSeconds**: The time value in seconds to convert to a string.
- **FormatString**: The time pattern to convert the date into.

Time Pattern

The time pattern string supports the following directives:

- `%a` - abbreviated weekday name.
- `%A` - full weekday name.
- `%b` - abbreviated month name.
- `%B` - full month name.
- `%c` - the locale's date and time, such as `%x, %X`.
- `%d` - zero-padded day of the month as a decimal number [01,31].
- `%e` - space-padded day of the month as a decimal number [1,31]; equivalent to `%_d`.
- `%f` - microseconds as a decimal number [000000, 999999].
- `%H` - hour (24-hour clock) as a decimal number [00,23].
- `%I` - hour (12-hour clock) as a decimal number [01,12].
- `%j` - day of the year as a decimal number [001,366].
- `%m` - month as a decimal number [01,12].
- `%M` - minute as a decimal number [00,59].
- `%L` - milliseconds as a decimal number [000, 999].
- `%p` - either AM or PM.

- `%q` - quarter of the year as a decimal number [1,4].
- `%Q` - Unix time (milliseconds).
- `%s` - Unix time (seconds).
- `%S` - second as a decimal number [00,61].
- `%u` - Monday-based (ISO 8601) weekday as a decimal number [1,7].
- `%U` - Sunday-based week of the year as a decimal number [00,53].
- `%V` - ISO 8601 week of the year as a decimal number [01, 53].
- `%w` - Sunday-based weekday as a decimal number [0,6].
- `%W` - Monday-based week of the year as a decimal number [00,53].
- `%x` - the locale's date, such as `%-m/%-d/%Y`.
- `%X` - the locale's time, such as `%-I:%M:%S %p`.
- `%y` - year without century as a decimal number [00,99].
- `%Y` - year with century as a decimal number, such as `1999`.
- `%Z` - time zone offset, such as `-0700`, `-07:00`, `-07`, or `Z`.
- `%%` - a literal percent sign (`%`).

For more details, see format specifiers.

Example

This example returns `"2022-06-27T17:00:26.499+0000"`:

```
print strftime( 1656349226.499, '%Y-%m-%dT%H:%M:%S.%L%Z' )
```

Copy | Run in Cribl Search

14.5.3.4.26. STRPTIME

The `strptime` function converts a string to a `datetime`.

Alias: `parse_time`

Syntax

```
strptime( TimeString, FormatString )
```

Copy

Arguments

- **TimeString**: The string to parse to a `datetime`.
- **FormatString**: The time pattern that matches the string to parse.

Time Pattern

The time pattern string supports the following directives:

- `%a` - abbreviated weekday name.
- `%A` - full weekday name.
- `%b` - abbreviated month name.
- `%B` - full month name.
- `%c` - the locale's date and time, such as `%x, %X`.
- `%d` - zero-padded day of the month as a decimal number [01,31].
- `%e` - space-padded day of the month as a decimal number [1,31]; equivalent to `%_d`.
- `%f` - microseconds as a decimal number [000000, 999999].
- `%H` - hour (24-hour clock) as a decimal number [00,23].
- `%I` - hour (12-hour clock) as a decimal number [01,12].
- `%j` - day of the year as a decimal number [001,366].
- `%m` - month as a decimal number [01,12].
- `%M` - minute as a decimal number [00,59].
- `%L` - milliseconds as a decimal number [000, 999].
- `%p` - either AM or PM.

- `%q` - quarter of the year as a decimal number [1,4].
- `%Q` - Unix time (milliseconds).
- `%s` - Unix time (seconds).
- `%S` - second as a decimal number [00,61].
- `%u` - Monday-based (ISO 8601) weekday as a decimal number [1,7].
- `%U` - Sunday-based week of the year as a decimal number [00,53].
- `%V` - ISO 8601 week of the year as a decimal number [01, 53].
- `%w` - Sunday-based weekday as a decimal number [0,6].
- `%W` - Monday-based week of the year as a decimal number [00,53].
- `%x` - the locale's date, such as `%-m/%-d/%Y`.
- `%X` - the locale's time, such as `%-I:%M:%S %p`.
- `%y` - year without century as a decimal number [00,99].
- `%Y` - year with century as a decimal number, such as `1999`.
- `%Z` - time zone offset, such as `-0700`, `-07:00`, `-07`, or `Z`.
- `%%` - a literal percent sign (`%`).

For more details, see format specifiers.

Example

This example returns `1,647,518,400`:

```
print strptime( '2022-03-17T12:00:00.000Z', '%Y-%m-%dT%H:%M:%S.%L%Z' )
```

Copy | Run in Cribl Search

14.5.3.4.27. TODATETIME

The `todatetime` function converts the input into a `datetime` value (Unix time in seconds).



To convert `datetime` (Unix time) into a `string`, or vice versa, use the `strftime` and `strptime` functions.

Syntax

```
todatetime( Expression )
```

Arguments

- **Expression**: Expression that will be converted into `datetime`.

Returns

If the conversion is successful, the result will be a `datetime` value, otherwise, the result will be `null`.

Example

This example returns `1,485,216,000`:

```
print todatetime( "2015-25-24" )
```

Copy | Run in Cribl Search

14.5.3.4.28. TOTIMESPAN

The `totimespan` function converts the input expression into a time interval, in seconds.



This output format differs from the standard Kusto `totimespan` function, which returns a timespan.

To convert `datetime` (Unix time) into a `string`, or vice versa, use the `strftime` and `strptime` functions.

Syntax

```
totimespan( Expression )
```

Arguments

- **Expression**: Expression that will be converted to timespan.

Returns

If the conversion is successful, the result will be the number of seconds in the interval. Otherwise, the result will be `null`.

Example

This example returns `3660`:

```
print totimespan( "0.01:01:00" )
```

Copy | Run in Cribl Search

14.5.3.4.29. UNIXTIME_MICROSECONDS_TODATETIME

The `unixtime_microseconds_todatetime` function converts the input into a `datetime` value (Unix time in seconds).



To convert `datetime` (Unix time) into a `string`, or vice versa, use the `strftime` and `strptime` functions.

Syntax

```
unixtime_microseconds_todatetime( Microseconds )
```

Arguments

- **Microseconds**: Unix time in microseconds. Time that occurs before the Unix epoch (1970-01-01 00:00:00) has a negative value.

Returns

If the conversion is successful, the result will be a `datetime` value (Unix time in seconds). Otherwise, the result will be `null`.

Example

This example returns `1,546,300,800`:

```
print unixtime_microseconds_todatetime( 1546300800000000 )
```

Copy Run in Cribl Search

14.5.3.4.30. UNIXTIME_MILLISECONDS_TODATETIME

The `unixtime_milliseconds_todatetime` function converts the input into a `datetime` value (Unix time in seconds).



To convert `datetime` (Unix time) into a `string`, or vice versa, use the `strftime` and `strptime` functions.

Syntax

```
unixtime_milliseconds_todatetime( Milliseconds )
```

Arguments

- **Milliseconds**: Unix time in milliseconds. Time that occurs before the Unix epoch (1970-01-01 00:00:00) has a negative value.

Returns

If the conversion is successful, the result will be a `datetime` value (Unix time in seconds). Otherwise, the result will be `null`.

Example

This example returns `1,546,300,800`:

```
print unixtime_milliseconds_todatetime( 1546300800000 )
```

Copy Run in Cribl Search

14.5.3.4.31. UNIXTIME_NANOSECONDS_TODATETIME

The `unixtime_nanoseconds_todatetime` function converts the input into a `datetime` value (Unix time in seconds).



To convert `datetime` (Unix time) into a `string`, or vice versa, use the `strftime` and `strptime` functions.

Syntax

```
unixtime_nanoseconds_todatetime( Nanoseconds )
```

Arguments

- **Nanoseconds**: Unix time in nanoseconds. Time that occurs before the Unix epoch (1970-01-01 00:00:00) has a negative value.

Returns

If the conversion is successful, the result will be a `datetime` value (Unix time in seconds). Otherwise, the result will be `null`.

Example

This example returns `1,546,300,800`:

```
print unixtime_nanoseconds_todatetime( 1546300800000000000 )
```

Copy Run in Cribl Search

14.5.3.4.32. UNIXTIME_SECONDS_TODATETIME

The `unixtime_seconds_todatetime` function converts the input into a `datetime` value (Unix time in seconds).



To convert `datetime` (Unix time) into a `string`, or vice versa, use the `strftime` and `strptime` functions.

Syntax

```
unixtime_seconds_todatetime( Seconds )
```

Arguments

- **Seconds**: Unix time in seconds. Time that occurs before the Unix epoch (1970-01-01 00:00:00) has a negative value.

Returns

If the conversion is successful, the result will be a `datetime` value (Unix time in seconds). Otherwise, the result will be `null`.

Example

This example returns `1,546,300,800`:

```
print date_time = unixtime_seconds_todatetime( 1546300800 )
```

Copy | Run in Cribl Search

14.5.3.4.33. WEEK_OF_YEAR

The `week_of_year` function returns an integer representing the week number. The week number is calculated from the first week of a year, which is the one that includes the first Thursday, according to ISO 8601.

Syntax

```
week_of_year( Datetime )
```

Copy

Arguments

- **Datetime**: A `datetime`.

Returns

The week number of the given year.

Examples

This example returns `53`:

```
print week_of_year( datetime(2020-12-31) )
```

Copy Run in Cribl Search

This example returns `1`:

```
print week_of_year( datetime(1970-01-01) )
```

Copy Run in Cribl Search

14.5.3.5. Dynamic Functions

A list of all dynamic functions supported by Cribl Search.

Dynamic scalar functions allow you to manipulate objects by operating on `dynamic` values, including dynamic arrays and property bags.

Name	Description
`bag_has_key`	Checks whether a property bag contains a given key.
`bag_keys`	Lists all root keys of a property bag.
`bag_merge`	Merges multiple property bags, discarding duplicate keys.
`bag_pack`	Creates a property bag from an alternating list of keys and values.
`bag_pack_columns`	Creates a property bag from a list of columns.
`bag_remove_keys`	Removes key-value pairs from a property bag.
`bag_set_key`	Adds or overwrites a key-value pair in a property bag.
`bag_zip`	Creates a property bag from two dynamic arrays.
`make_bag`	Creates a property bag from multiple input bags.
`make_bag_if`	Creates a property bag from those input bags that meet the specified condition.
`zip`	Merges dynamic arrays, grouping elements by index.

The following string functions support `dynamic` types as well:

Function	Usage with dynamic data types
`extractjson(`path,object`)`	Uses path to navigate into object.
`parse_json(`source`)`	Turns a JSON string into a dynamic object.
`range(`from,to,step`)`	Generates an array of values.

14.5.3.5.1. BAG_HAS_KEY

The `bag_has_key` function checks whether a property bag contains a given key.

Syntax

```
bag_has_key( Bag, Key )
```

Copy

Parameters

Name	Type	Required	Description
Bag	dynamic	Yes	The property bag to check.
Key	string	Yes	The key for which to search.

Returns

Returns `true` or `false`, depending on whether the key exists in the bag.

Example

```
print bag = dynamic({ "foo": 42, "bar": true })
 | extend fooExists = bag_has_key(bag, "foo"),
          blubbExists = bag_has_key(bag, "blubb")

// fooExists: `true`
// blubbExists: `false`
```

Copy Run in Cribl Search

14.5.3.5.2. BAG_KEYS

The `bag_keys` function lists all root keys of a property bag.

Syntax

```
bag_keys( Bag )
```

Copy

Parameters

Name	Type	Required	Description
Bag	dynamic	Yes	The property bag whose root keys you want to list.

Returns

Returns an array of strings. The order of the keys is undetermined.

Example

```
print bag = dynamic({ "a": "b", "c": { "d": 123 }})
 | extend listOfKeys = bag_keys(bag)

// returns: ['a', 'c']
```

Copy Run in Cribl Search

14.5.3.5.3. BAG_MERGE

The `bag_merge` function merges two or more property bags, discarding duplicate keys.

Syntax

```
bag_merge( Bag1, Bag2[, ...] )
```

Copy

Parameters

Name	Type	Required	Description
Bag	dynamic	Yes	The property bags to merge.

Returns

Returns a single property bag containing the merged results of all input bags.

If the same key is present in multiple input bags, only the value associated with the key from the leftmost argument is kept.

The order of the key-value pairs returned is undetermined.

Example

```
print foo = dynamic({'A1':12, 'B1':2, 'C1':3}), bar = dynamic({'A2':81, 'B2':82, 'A1'
 | project result = bag_merge(foo, bar)
```

Copy Run in Cribl Search

Input (before `bag_merge`):

```
{
  "foo": {
    "A1": 12,
    "B1": 2,
    "C1": 3
  },
  "bar": {
    "A2": 81,
    "B2": 82,
    "A1": 1
  }
}
```

Copy

Output (after `bag_merge`):

```
{
  "result": {
    "A2": 81,
    "B2": 82,
    "A1": 12,
    "B1": 2,
    "C1": 3
  }
}
```

14.5.3.5.4. BAG_PACK

The `bag_pack` function creates a property bag from an alternating list of keys and values.

Syntax

```
bag_pack( Key1, Value1, Key2, Value2, ... )
```

Copy

Parameters

Name	Type	Required	Description
`Key`	`string`	Yes	The key.
`Value`	`dynamic`	Yes	The key's value.

You need to provide an even number of arguments (each `Key` needs a `Value`).

Returns

Returns a single property bag made from the input keys and values.

The order of the key-value pairs returned is undetermined.

Example

```
print bag = bag_pack("Level", "Information", "ProcessID", 1234, "Data", bag_pack("url
```

Copy Run in Cribl Search

Output:

```
{
  "bag": {
    "Level": "Information",
    "ProcessID": 1234,
    "Data": {
      "url": "www.cribl.io"
    }
  }
}
```

14.5.3.5.5. BAG_PACK_COLUMNS

The `bag_pack_columns` function creates a property bag from a list of fields (columns).

Syntax

```
bag_pack( FieldName[, ...] )
```

Copy

Parameters

Name	Type	Required	Description
`FieldName`	Any scalar data type	Yes	The name of a field to add to the output property bag.

Returns

Returns a property bag made from the specified fields. The source field names serve as property names (keys), and the field values as property values.

Example

```
dataset="$vt_dummy"
 | extend foo=1
 | extend bar=2
 | project Packed = bag_pack_columns(foo, bar)
```

Copy Run in Cribl Search

Output:

```
{
  "Packed": {
    "foo": 1,
    "bar": 2
  }
}
```

Copy

14.5.3.5.6. BAG_REMOVE_KEYS

The `bag_remove_keys` function removes key-value pairs from a property bag.

Syntax

```
bag_remove_keys( Bag, Keys )
```

Copy

Parameters

Name	Type	Required	Description
Bag	dynamic	Yes	The property bag from which to remove keys.
Keys	dynamic	Yes	A key, or a list of keys, to remove.

Returns

Returns the input property bag stripped of the specified keys and their values.

The order of the key-value pairs returned is undetermined.

Example

```
print bag = dynamic({ "foo": 42, "bar": true })
 | project result = bag_remove_keys(bag, "foo")
```

Copy Run in Cribl Search

Input (before `bag_remove_keys`):

```
{
  "bag": {
    "foo": 42,
    "bar": true
  }
}
```

Copy

Output (after `bag_remove_keys`):

```
{
  "result": {
    "bar": true
  }
}
```

Copy

14.5.3.5.7. BAG_SET_KEY

The `bag_set_key` function adds a key-value pair to a property bag, or, if the specified key already exists, overwrites the key's value.

Syntax

```
bag_set_key( Bag, Key, Value )
```

Copy

Parameters

Name	Type	Required	Description
`Bag`	`dynamic`	Yes	The property bag to modify.
`Key`	`string`	Yes	The key to set.
`Value`	`dynamic`	Yes	The value to set.

Returns

Returns the input property bag, adding the specified key-value pair if the `Key` doesn't exist, or overwriting the value if the `Key` is already there.

The order of the key-value pairs returned is undetermined.

If the `Bag` specified is not a valid property bag, `bag_set_key` returns `null`.

Examples

Add a Key-Value Pair to a Property Bag

```
print bag = dynamic({ "foo": 42, "bar": true })
 | project result = bag_set_key(bag, "new", 1)
```

Copy Run in Cribl Search

Input (before `bag_set_key`):

```
{
  "bag": {
    "foo": 42,
    "bar": true
  }
}
```

Copy

Output (after `bag_set_key`):

```
{
  "result": {
    "foo": 42,
    "bar": true,
    "new": 1
  }
}
```

Copy

Overwrite a Key-Value Pair in a Property Bag

```
print bag = dynamic({ "foo": 42, "bar": true })
 | project result = bag_set_key(bag, "foo", 100)
```

Copy Run in Cribl Search

Input (before `bag_set_key`):

```
{
  "bag": {
    "foo": 42,
    "bar": true
  }
}
```

Copy

Output (after `bag_set_key`):

```
{
  "result": {
    "foo": 100,
    "bar": true
  }
}
```

Copy

14.5.3.5.8. BAG_ZIP

The `bag_zip` function creates a property bag from two input dynamic arrays. The first array provides keys, the second array provides values.

Syntax

```
bag_zip( KeysArray, ValuesArray )
```

Copy

Parameters

Name	Type	Required	Description
`KeysArray`	Array of strings	Yes	Keys to set in the output property bag.
`ValuesArray`	`dynamic`	Yes	Values in the output property bag.

Returns

Returns a property bag where keys come from the first array, and values from the second array. The keys and values are matched in the order in which they are listed in the input (`key1: value1, key2: value2`).

- If there are more keys than values, missing values are filled with `null`.
- If there are more values than keys, values with no matching keys are ignored.
- Keys that aren't strings are ignored.

The order of the key-value pairs returned is undetermined.

Example

```
print foo = dynamic(['key1', 'key2']), bar = dynamic(['value1', 'value2'])
 | project bag_zip(foo, bar)
```

Copy Run in Cribl Search

Input (before `bag_zip`):

```
{
  "foo": [
    "key1",
    "key2"
  ],
  "bar": [
    "value1",
    "value2"
  ]
}
```

Copy

Output (after `bag_zip`):

```
{
  "bag_zip_foo_bar": {
    "key1": "value1",
    "key2": "value2"
  }
}
```

Copy

14.5.3.5.9. MAKE_BAG

The `make_bag` aggregation function creates a property bag from multiple input bags.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
make_bag( Expression, [ MaxOutputSize ] )
```

Copy

Parameters

Name	Type	Required	Description
`Expression`	`dynamic`	Yes	Expression used for the aggregation calculation.
`MaxOutputSize`	`int`	No	Maximum number of elements returned. Default: `1048576`. Max: `2^53`.

Returns

Returns a single property bag, made of those `Expression` values that are property bags (other values are ignored).

If a key appears in the input more than once, only its **first value** is kept.

The order of the key-value pairs returned is undetermined.

Example

```
range v from 1 to 3
 | extend foo = case(v == 1, dynamic({"a": 1, "foo": 42}), v == 2, dynamic({"b": 2, '
 | summarize mb=make_bag(foo)
```

Copy Run in Cribl Search

Input (before `make_bag`):

```
// event 1
{
  "_time": 1735830806.91,
  "v": 1,
  "foo": {
    "a": 1,
    "foo": 42
  }
}

// event 2
{
  "_time": 1735830806.91,
  "v": 2,
  "foo": {
    "b": 2,
    "foo": 17
  }
}

// event 3
{
  "_time": 1735830806.91,
  "v": 3,
  "foo": {
    "c": 3
  }
}
```

Copy

Output (after `make_bag`):

```
{
  "mb": {
    "a": 1,
    "foo": 42,
    "b": 2,
    "c": 3
  }
}
```

Copy

14.5.3.5.10. MAKE_BAG_IF

The `make_bag_if` aggregation function creates a property bag from those input bags that meet the specified condition.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
make_bag_if( Expression, Predicate, [ MaxOutputSize ] )
```

Copy

Parameters

Name	Type	Required	Description
`Expression`	`dynamic`	Yes	Expression used for the aggregation calculation.
`Predicate`	`bool`	Yes	Predicate that must evalute to `true` for an input bag to be included in the output.
`MaxOutputSize`	`int`	No	Maximum number of elements returned. Default: `1048576`. Max: `2^53`.

Returns

Returns a single property bag, made of those `Expression` values that are property bags (other values are ignored) and for whose the `Predicate` evaluates to `true`.

If a key appears in the input more than once, only its **first value** is kept.

The order of the key-value pairs returned is undetermined.

Example

```
range v from 1 to 3
 | extend foo = case(v == 1, dynamic({"a": 1, "foo": 42}), v == 2, dynamic({"b": 2, '
 | summarize mb=make_bag_if(foo,v > 1)
```

Copy Run in Cribl Search

Input (before `make_bag_if`):

```
// event 1
{
  "_time": 1735831049.413,
  "v": 1,
  "foo": {
    "a": 1,
    "foo": 42
  }
}

// event 2
{
  "_time": 1735831049.413,
  "v": 2,
  "foo": {
    "b": 2,
    "foo": 17
  }
}

// event 3
{
  "_time": 1735831049.413,
  "v": 3,
  "foo": {
    "c": 3
  }
}
```

Copy

Output (after `make_bag_if`):

```
{
  "mb": {
    "b": 2,
    "foo": 17,
    "c": 3
  }
```

14.5.3.5.11. Zip

The `zip` function merges two or more dynamic arrays, grouping elements of the same index.

Syntax

```
zip( Arrays )
```

Copy

Parameters

Name	Type	Required	Description
`Arrays`	`dynamic`	Yes	The dynamic array values to zip.

Returns

Returns an array whose elements are each an array holding the elements of the input arrays of the same index.

Example

```
print foo = zip(dynamic([1,3,5]), dynamic([2,4,6]))
```

Copy Run in Cribl Search

Output:

```
{
  "foo": [
    [
      1,
      2
    ],
    [
      3,
      4
    ],
    [
```

14.5.3.6. Cryptographic Functions

A list of all cryptographic functions supported by Cribl Search.

Name	Description
`encrypt`	Encrypts data with a key managed by a Cribl Stream Worker Group.
`decrypt`	Decrypts data with a key managed by a Cribl Stream Worker Group.

14.5.3.6.1. Encrypt

The `encrypt` function encrypts data with a key managed by a Cribl Stream Worker Group.

For more information on how to set up encryption keys, see the Cribl Stream docs:

- Encryption of Data in Motion
- Create and Manage Encryption Keys
- C.Crypto - Data Encryption and Decryption

Syntax

```
encrypt(value, workerGroup, keyId)
```

Parameters

Name	Type	Required	Description
`value`	`string`	Yes	A valid KQL expression. This is the data to encrypt.
`workerGroup`	`string`	Yes	The name of the Stream Worker Group that has the encryption key.
`keyId`	`string`	Yes	The ID of the encryption key.

Returns

Returns the input data, encrypted using the specified key from the specified Stream Worker Group, encoded as a Base64 string.

Permissions

You need access to the Stream Worker Group that contains the encryption key.

Example

Encrypt a specific field (`dstport`), and export it to a Cribl Lake Dataset.

```
dataset="cribl_search_sample"
 | limit 1000
 | extend dstport = encrypt(dstport, <workerGroup>, <keyId>)
 | export to lake myLakeDataset
```

Copy

14.5.3.6.2. Decrypt

The `decrypt` function decrypts data with a key managed by a Cribl Stream Worker Group.

For more information on how to set up encryption keys, see the Cribl Stream docs:

- Encryption of Data in Motion
- Create and Manage Encryption Keys
- C.Crypto - Data Encryption and Decryption

Search Admins, Organization Admins, and Organization Owners can view the results of all searches in the Organization, for as long as they're kept in the history. Mind that results from the `decrypt` function are stored as decrypted plaintext. To reduce the visibility, consider adjusting the **Search history TTL** limit.

Syntax

```
decrypt(value, workerGroup)
```

Parameters

Name	Type	Required	Description
`value`	`string`	Yes	A valid KQL expression, containing data encrypted with a key from the specified `workerGroup`.
`workerGroup`	`string`	Yes	The name of the Stream Worker Group that has the encryption key.

Returns

Returns the input data, decrypted using the key from the specified Stream Worker Group.

Permissions

You need access to the Stream Worker Group that contains the encryption key.

Examples

Get the results of a past search (with ID `1704236905683.wgocax`), and decrypt a specific field (`dstport`).

```
dataset="$vt_results" jobId='1704236905683.wgocax'
 | extend dstport = decrypt(dstport, <workerGroup>)
```

Copy

14.5.3.7. Hash Functions

A list of all hash functions supported by Cribl Search.

Name	Description
`hash`	Returns a hash value for the input value.
`hash_combine`	Combines hash values of two or more hashes.
`hash_many`	Returns a combined hash value of multiple values.
`hash_md5`	Returns an MD5 hash value for the input value.
`hash_sha1`	Returns a SHA1 hash value for the input value.
`hash_sha256`	Returns a SHA-256 hash value for the input value.
`hash_xxhash64`	Returns a 64-bit hash value for the input value.

14.5.3.7.1. Hash

The `hash` function returns a hash value for the input value.

Syntax

```
hash( Source, Mod )
```

Copy

Arguments

- **Source**: The value to be hashed.
- **Mod**: An optional modulo value to be applied to the hash result, so that the output value is between `0` and `Mod - 1`.

Returns

The hash value of **Source**. If **Mod** is specified, the function returns the hash value modulo the value of **Mod**.

Examples

- `hash("World")` returns as `1846988464401551951`
- `hash("World", 100)` returns as `51 (1846988464401551951 % 100)`
- `hash(datetime("2015-01-01"))` returns as `1380966698541616202`

Sampling

You can use the `hash` function for sampling data if the values in one of its columns are uniformly distributed. In the following example, StartTime values are uniformly distributed and the function is used to run a query on 10% of the data.

```
dataset=Dataset
| where hash(StartTime, 10) == 0
| summarize StormCount = count(), TypeOfStorms = dcount(EventType) by State
| top 5 by StormCount desc
```

Copy

14.5.3.7.2. HASH_COMBINE

The `hash_combine` function combines hash values of two or more hashes.

Syntax

```
hash_combine( Hash1 , Hash2 [, Hash3 ...] )
```

Copy

Arguments

- **Hash1**: Long value representing the first hash value.
- **Hash2**: Long value representing the second hash value.
- **Hash3**: Long value representing Nth hash value.

Returns

The combined hash value of the given scalars.

Example

```
dataset=myDataset
| extend h1 = hash(value1), h2=hash(value2)
| extend combined = hash_combine(h1, h2)
```

Copy

14.5.3.7.3. HASH_MANY

The `hash_many` function returns a combined hash value of multiple values.

Syntax

```
hash_many( Value1 , Value2 [, ValueN ...] )
```

Copy

Arguments

- **Value1**, **Value2**, **ValueN**: Input values that will be hashed together.

Returns

The `hash` function is applied to each of the specified scalars. The resulting hashes are combined into a single hash and returned.

Example

```
dataset=myDataset
| extend combined = hash_many(value1, value2)
```

Copy

14.5.3.7.4. HASH_MD5

The `hash_md5` function returns an MD5 hash value for the input value.

Syntax

```
hash_md5( Source )
```

Copy

Arguments

- **Source**: The value to be hashed.

Returns

The MD5 hash value of the given scalar, encoded as a hex string (a string of characters, each two of which represent a single Hex number between 0 and 255).

Examples

- `h1=hash_md5("World")`
- `h2=hash_md5(datetime(2020-01-01))`

Aggregate by hash

This example uses the `hash_md5` function to aggregate StormEvents based on the State's MD5 hash value.

```
dataset=StormEvents
| summarize StormCount = count() by State, StateHash=hash_md5(State)
| top 5 by StormCount
```

Copy

Returns the following:

State	StateHash	StormCount
TEXAS	3b00dbe6e07e7485a1c12d36c8e9910a	4701

State	StateHash	StormCount
KANSAS	e1338d0ac8be43846cf9ae967bd02e7f	3166
IOWA	6d4a7c02942f093576149db764d4e2d2	2337
ILLINOIS	8c00d9e0b3fcd55aed5657e42cc40cf1	2022
MISSOURI	2d82f0c963c0763012b2539d469e5008	2016

14.5.3.7.5. HASH_SHA1

The `hash_sha1` function returns a SHA1 hash value for the input value.

Syntax

```
hash_sha1( Source )
```

Copy

Arguments

- **Source**: The value to be hashed.

Returns

The SHA1 hash value of the given scalar, encoded as a hex string (a string of characters, each two of which represent a single Hex number between 0 and 255).

Examples

- `h1=hash_sha1("World")`
- `h2=hash_sha1(datetime(2020-01-01))`

Aggregate by hash

This example uses the `hash_sha1` function to aggregate StormEvents based on the State's SHA1 hash value.

```
dataset=StormEvents
| summarize StormCount = count() by State, StateHash=hash_sha1(State)
| top 5 by StormCount desc
```

Copy

Returns the following:

State	StateHash	StormCount
TEXAS	3128d805194d4e6141766cc846778eeacb12e3ea	4701

State	StateHash	StormCount
KANSAS	ea926e17098148921e472b1a760cd5a8117e84d6	3166
IOWA	cacf86ec119cfd5b574bde5b59604774de3273db	2337
ILLINOIS	03740763b16dae9d799097f51623fe635d8c4852	2022
MISSOURI	26d938907240121b54d9e039473dacc96e712f61	2016

14.5.3.7.6. HASH_SHA256

The `hash_sha256` function returns a SHA-256 hash value for the input value.

Syntax

```
hash_sha256( Source )
```

Copy

Arguments

- **Source**: The value to be hashed.

Returns

The SHA-256 hash value of the given scalar, encoded as a hex string (a string of characters, each two of which represent a single Hex number between 0 and 255).

Examples

- `h1=hash_sha256("World")`
- `h2=hash_sha256(datetime(2020-01-01))`

Aggregate by hash

This example uses the `hash_sha256` function to aggregate StormEvents based on the State's SHA-256 hash value.

```
dataset=StormEvents
| summarize StormCount = count() by State, StateHash=hash_sha256(State)
| top 5 by StormCount desc
```

Copy

Returns the following:

State	StateHash	StormCount
TEXAS	9087f20f23f91b5a77e8406846117049029e6798ebbd0d38aea68da73a00ca37	4701
KANSAS	c80e328393541a3181b258cdb4da4d00587c5045e8cf3bb6c8fdb7016b69cc2e	3166
IOWA	f85893dca466f779410f65cd904fdc4622de49e119ad4e7c7e4a291ceed1820b	2337
ILLINOIS	ae3eeabfd7eba3d9a4ccbfed6a9b8cff269dc43255906476282e0184cf81b7fd	2022
MISSOURI	d15dfc28abc3ee73b7d1f664a35980167ca96f6f90e034db2a6525c0b8ba61b1	2016

14.5.3.7.7. HASH_XXHASH64

The `hash_xxhash64` function returns a 64-bit hash value for the input value.

Syntax

```
hash_xxhash64( Source, Mod )
```

Copy

Arguments

- **Source**: The value to be hashed.
- **Mod**: An optional modulo value to be applied to the hash result, so that the output value is between `0` and `Mod - 1`.

Returns

The hash value of **Source**. If **Mod** is specified, the function returns the hash value modulo the value of **Mod**.

Examples

- `xxhash64("World")` returns as `1846988464401551951`
- `xxhash64("World", 100)` returns as `51 (1846988464401551951 % 100)`
- `xxhash64(datetime("2015-01-01"))` returns as `1380966698541616202`

14.5.3.8. INET Functions

A list of all INET functions supported by Cribl Search.

Name	Description
`ipv4_compare`	Compares two IPv4 strings.
`ipv4_is_in_range`	Checks if IPv4 string address is in IPv4-prefix notation range.
`ipv4_is_in_any_range`	Checks whether IPv4 string address is in any of the specified IPv4 address ranges.
`ipv4_is_match`	Matches two IPv4 strings.
`ipv4_is_private`	Checks if IPv4 string address belongs to a set of private network IPs.
`ipv4_netmask_suffix`	Returns the value of the IPv4 netmask suffix from IPv4 string address.
`ipv6_compare`	Compares two IPv6 or IPv4 network address strings.
`ipv6_is_match`	Matches two IPv6 or IPv4 network address strings.
`format_bytes`	Converts the input into a string that represents data size.
`format_ipv4`	Parses input with a netmask and returns string representing IPv4 address.
`format_ipv4_mask`	Parses input with a netmask and returns string representing IPv4 address as CIDR notation.

14.5.3.8.1. IPV4_COMPARE

The `ipv4_compare` function compares two IPv4 strings. The two IPv4 strings are parsed and compared while accounting for the combined IP-prefix mask calculated from argument prefixes, and the optional **PrefixMask** argument.

Syntax

```
ipv4_compare( Expr1, Expr2 [, PrefixMask ] )
```

Copy

Arguments

- **Expr1, Expr2**: A string expression representing an IPv4 address. Denote a subnet mask with a forward slash `/`.
- **PrefixMask**: An integer from 0 to 32 representing the number of most-significant bits that are taken into account.

Results

- `0`: If the long representation of the first IPv4 string argument is equal to the second IPv4 string argument
- `1`: If the long representation of the first IPv4 string argument is greater than the second IPv4 string argument
- `-1`: If the long representation of the first IPv4 string argument is less than the second IPv4 string argument
- `null`: If conversion for one of the two IPv4 strings wasn't successful.

Examples

This example returns `0`:

```
print ipv4_compare("127.0.0.1", "127.0.0.1")
```

Copy Run in Cribl Search

This example returns `-1`:

```
print ipv4_compare('192.168.1.1', '192.168.1.255')
```

Copy Run in Cribl Search

This example returns `0`:

```
print ipv4_compare('192.168.1.1/24', '192.168.1.255/24')
```

Copy Run in Cribl Search

This example returns `0`:

```
print ipv4_compare('192.168.1.1', '192.168.1.255', 24)`
```

Copy Run in Cribl Search

14.5.3.8.2. IPV4_IS_IN_RANGE

The `ipv4_is_in_range` function checks if IPv4 string address is in IPv4-prefix notation range.

Syntax

```
ipv4_is_in_range( Ipv4Address, Ipv4Range )
```

Copy

Arguments

- **Ipv4Address**: A string expression representing an IPv4 address.
- **Ipv4Range**: A string expression representing an IPv4 address with a subnet mask denoted with a forward slash `/`.

Results

- `true`: If the long representation of the first IPv4 string argument is in range of the second IPv4 string argument.
- `false`: Otherwise.
- `null`: If conversion for one of the two IPv4 strings wasn't successful.

Examples

This example returns `true`:

```
print ipv4_is_in_range("127.0.0.1", "127.0.0.1")
```

Copy Run in Cribl Search

This example returns `true`:

```
print ipv4_is_in_range('192.168.1.6', '192.168.1.1/24')
```

Copy Run in Cribl Search

This example returns `false`:

```
print ipv4_is_in_range('192.168.1.1', '192.168.2.1/24')
```

Copy | Run in Cribl Search

14.5.3.8.3. IPV4_IS_IN_ANY_RANGE

The `ipv4_is_in_any_range` function checks whether IPv4 string address is in any of the specified IPv4 address ranges.

Syntax

```
ipv4_is_in_any_range( Ipv4Address , Ipv4Range [, Ipv4Range ...] )
```

Copy

Arguments

- **Ipv4Address**: A string expression representing an IPv4 address.
- **Ipv4Range**: A string expression representing an IPv4 address with a subnet mask denoted with a forward slash `/`.

Results

- `true`: If the IPv4 address is in the range of any of the specified IPv4 networks.
- `false`: Otherwise.
- `null`: If conversion for one of the two IPv4 strings wasn't successful.

Examples

This example returns `true`:

```
print ipv4_is_in_any_range('192.168.1.6', '192.168.1.1/24', '10.0.0.1/8', '127.1.0.1/
```

Copy Run in Cribl Search

This example returns `false`:

```
print ipv4_is_in_any_range('192.168.1.1', '192.168.2.1/24', '10.0.0.1/8', '127.1.0.1/
```

Copy Run in Cribl Search

14.5.3.8.4. IPV4_IS_MATCH

The `ipv4_is_match` function matches two IPv4 strings. The two IPv4 strings are parsed and compared while accounting for the combined IP-prefix mask calculated from argument prefixes, and the optional **PrefixMask** argument.

Syntax

```
ipv4_is_match( Expr1, Expr2 [, PrefixMask ] )
```

Copy

Arguments

- **Expr1, Expr2**: A string expression representing an IPv4 address. Denote a subnet mask with a forward slash `/`.
- **PrefixMask**: An integer from 0 to 32 representing the number of most-significant bits that are taken into account.

Results

- `true`: If the long representation of the first IPv4 string argument is equal to the second IPv4 string argument.
- `false`: Otherwise.
- `null`: If conversion for one of the two IPv4 strings wasn't successful.

Examples

This example returns `true`:

```
print ipv4_is_match("127.0.0.1", "127.0.0.1")
```

Copy Run in Cribl Search

This example returns `false`:

```
print ipv4_is_match('192.168.1.1', '192.168.1.255')
```

Copy Run in Cribl Search

This example returns `true`:

```
print ipv4_is_match('192.168.1.1/24', '192.168.1.255/24')
```

Copy Run in Cribl Search

This example returns `true`:

```
print ipv4_is_match('192.168.1.1', '192.168.1.255', 24)
```

Copy Run in Cribl Search

14.5.3.8.5. IPV4_IS_PRIVATE

The `ipv4_is_private` function checks if IPv4 string address belongs to a set of private network IPs.

Private network addresses were originally defined to assist in delaying IPv4 address exhaustion. IP packets originating from or addressed to a private IP address cannot be routed through the public internet.

Syntax

```
ipv4_is_private( Expression )
```

Copy

Arguments

- **Expression**: A string expression representing an IPv4 address. Denote a subnet mask with a forward slash `/`.

Results

- `true`: If the IPv4 address belongs to any of the private network ranges.
- `false`: Otherwise.
- `null`: If parsing of the input as IPv4 address string wasn't successful.

Examples

This example returns `true`:

```
print ipv4_is_private('192.168.1.1/24')
```

Copy Run in Cribl Search

This example returns `true`:

```
print ipv4_is_private('10.1.2.3/24')
```

Copy Run in Cribl Search

This example returns `false`:

```
print ipv4_is_private('202.1.2.3')
```

Copy Run in Cribl Search

This example returns `false`:

```
print ipv4_is_private("127.0.0.1")
```

Copy Run in Cribl Search

14.5.3.8.6. IPV4_NETMASK_SUFFIX

The `ipv4_netmask_suffix` function returns the value of the IPv4 netmask suffix from IPv4 string address.

Private network addresses were originally defined to assist in delaying IPv4 address exhaustion. IP packets originating from or addressed to a private IP address cannot be routed through the public internet.

Syntax

```
ipv4_netmask_suffix( Expression )
```

Copy

Arguments

- **Expression**: A string expression representing an IPv4 address. Denote a subnet mask with a forward slash `/`.

Results

- The value of the netmask suffix of the IPv4 address. If suffix is not present in the input, a value of `32` (full netmask suffix) is returned.
- `null`: If parsing of the input as IPv4 address string wasn't successful.

Examples

This example returns `24`:

```
print ipv4_netmask_suffix('192.168.1.1/24')
```

Copy Run in Cribl Search

This example returns `32`:

```
print ipv4_netmask_suffix('192.168.1.1')
```

Copy Run in Cribl Search

14.5.3.8.7. IPV6_COMPARE

The `ipv6_compare` function compares two IPv6 or IPv4 network address strings. The two IPv6 strings are parsed and compared while accounting for the combined IP-prefix mask calculated from argument prefixes, and the optional **PrefixMask** argument.

Syntax

```
ipv6_compare( Expr1, Expr2 [, PrefixMask ] )
```

Copy

Arguments

- **Expr1, Expr2**: A string expression representing an IPv4 or IPv6 address. Denote a subnet mask with a forward slash `/`.
- **PrefixMask**: An integer from 0 to 128 representing the number of most-significant bits that are taken into account.

Results

- `0`: If the long representation of the first IPv6 string argument is equal to the second IPv6 string argument.
- `1`: If the long representation of the first IPv6 string argument is greater than the second IPv6 string argument.
- `-1`: If the long representation of the first IPv6 string argument is less than the second IPv6 string argument.
- `null`: If conversion for one of the two IPv6 strings wasn't successful.

Examples

This example returns `0`:

```
print ipv6_compare('::ffff:7f00:1', '127.0.0.1')
```

Copy Run in Cribl Search

This example returns `-1`:

```
print ipv6_compare('fe80::85d:e82c:9446:7994', 'fe80::85d:e82c:9446:7995')
```

Copy Run in Cribl Search

This example returns `0`:

```
print ipv6_compare('192.168.1.1/24', '192.168.1.255/24')
```

Copy Run in Cribl Search

This example returns `0`:

```
print ipv6_compare('fe80::85d:e82c:9446:7994/127', 'fe80::85d:e82c:9446:7995/127')
```

Copy Run in Cribl Search

This example returns `0`:

```
print ipv6_compare('fe80::85d:e82c:9446:7994', 'fe80::85d:e82c:9446:7995', 127)
```

Copy Run in Cribl Search

14.5.3.8.8. IPV6_IS_MATCH

The `ipv6_is_match` function matches two IPv6 or IPv4 network address strings. The two IPv6/IPv4 strings are parsed and compared while accounting for the combined IP-prefix mask calculated from argument prefixes, and the optional **PrefixMask** argument.

Syntax

```
ipv6_is_match( Expr1, Expr2 [, PrefixMask ] )
```

Copy

Arguments

- **Expr1, Expr2**: A string expression representing an IPv6 or IPv4 address. Denote a subnet mask with a forward slash `/`.
- **PrefixMask**: An integer from 0 to 128 representing the number of most-significant bits that are taken into account.

Results

- `true`: If the long representation of the first IPv6/IPv4 string argument is equal to the second IPv6/IPv4 string argument.
- `false`: Otherwise.
- `null`: If conversion for one of the two IP strings wasn't successful.

Examples

This example returns `true`:

```
print ipv6_is_match('::ffff:7f00:1', '127.0.0.1')
```

Copy Run in Cribl Search

This example returns `false`:

```
print ipv6_is_match('fe80::85d:e82c:9446:7994', 'fe80::85d:e82c:9446:7995')
```

Copy Run in Cribl Search

This example returns `true`:

```
print ipv6_is_match('192.168.1.1/24', '192.168.1.255/24')
```

Copy Run in Cribl Search

This example returns `true`:

```
print ipv6_is_match('fe80::85d:e82c:9446:7994/127', 'fe80::85d:e82c:9446:7995/127')
```

Copy Run in Cribl Search

This example returns `true`:

```
print ipv6_is_match('fe80::85d:e82c:9446:7994', 'fe80::85d:e82c:9446:7995', 127)
```

Copy Run in Cribl Search

14.5.3.8.9. FORMAT_BYTES

The `format_bytes` function converts the input into a string that represents data size.

```
// returns a string: "512 MB"
format_bytes(536870912)
```

Copy

Purpose

Use `format_bytes` to display large, raw byte values in a user-friendly way.

Syntax

```
format_bytes( ByteCount [, Precision [, TargetUnit ] ] )
```

Copy

Parameters

Name	Type	Required	Description
`ByteCount`	`int`	Yes	The value to convert into a data-size string.
`Precision`	`int`	No	The number of digits that the input value is rounded to after the decimal point. Default: `0`.
`TargetUnit`	`string`	No	The unit of the output data size: `Bytes`, `KB`, `MB`, `GB`, `TB`, `PB`, or `EB`. If empty, Cribl Search selects the unit, based on input value.

Returns

Returns a `string` that represents data size, using the specified (or automatically selected) unit.

If the conversion is unsuccessful, the function returns an empty string.

Examples

```
// returns "564 Bytes"
print format_bytes(564)
```

Copy Run in Cribl Search

```
// returns "10.1 KB"
print format_bytes(10332, 1)
```

Copy Run in Cribl Search

```
// returns "19 MB"
print format_bytes(20010332)
```

Copy Run in Cribl Search

```
// returns "19.08 MB"
print format_bytes(20010332, 2)
```

Copy Run in Cribl Search

```
// returns "19541 KB"
print format_bytes(20010332, 0, "KB")
```

Copy Run in Cribl Search

14.5.3.8.10. FORMAT_IPV4

The `format_ipv4` function parses input with a netmask and returns string representing IPv4 address.

Syntax

```
format_ipv4( Expression [, PrefixMask ] )
```

Arguments

- **Expression**: A string or number representation (in big-endian order) of the IPv4 address.
- **PrefixMask**: An integer from 0 to 32 representing the number of most-significant bits that are taken into account. If argument isn't specified, all bit-masks are used (32).

Results

If the conversion is successful, returns a `string` representing IPv4 address.

If the conversion fails, returns an empty `string`.

Examples

This example returns `"192.168.1.0"`:

```
print format_ipv4('192.168.1.255', 24)
```

Copy Run in Cribl Search

This example returns `"192.168.1.0"`:

```
print format_ipv4(3232236031, 24)
```

Copy Run in Cribl Search

14.5.3.8.11. FORMAT_IPV4_MASK

The `format_ipv4_mask` function parses input with a netmask and returns string representing IPv4 address as CIDR notation.

Syntax

```
format_ipv4_mask( Expression [, PrefixMask ] )
```

Arguments

- **Expression**: A string or number representation (in big-endian order) of the IPv4 address as CIDR notation.
- **PrefixMask**: An integer from 0 to 32 representing the number of most-significant bits that are taken into account. If argument isn't specified, all bit-masks are used (32).

Results

If the conversion is successful, returns a `string` representing the IPv4 address in CIDR notation.

If the conversion fails, returns an empty `string`.

Examples

This example returns `"192.168.1.0/24"`:

```
print format_ipv4_mask('192.168.1.255', 24)
```

Copy Run in Cribl Search

This example returns `"192.168.1.0/24"`:

```
print format_ipv4_mask(3232236031, 24)
```

Copy Run in Cribl Search

14.5.3.9. Mathematical Functions

A list of all mathematical functions supported by Cribl Search.

Name	Description
`abs`	Calculates the absolute value of the input.
`acos`	Calculates the angle whose cosine is the specified number.
`asin`	Calculates the angle whose sine is the specified number.
`atan`	Returns the angle whose tangent is the specified number.
`atan2`	Calculates the angle, in radians, between the positive x-axis and the ray from the origin to the point (y, x).
`beta_cdf`	Returns the standard cumulative beta distribution function.
`beta_inv`	Returns the inverse of the beta cumulative probability beta density function.
`beta_pdf`	Returns the probability density beta function.
`ceil`	Rounds up a numeric expression's value to the nearest integer.
`ceiling`	Rounds up a numeric expression's value to the nearest integer.
`cos`	Returns the cosine function.
`cot`	Calculates the trigonometric cotangent of the specified angle, in radians.
`degrees`	Converts angle value in radians into value in degrees.
`exp`	Calculates the base-e exponential function of x.
`exp2`	Calculates the base-2 exponential function of x.
`exp10`	Calculates the base-10 exponential function of x.
`gamma`	Computes gamma function.
`isfinite`	Returns whether input is a finite value.
`isinf`	Returns whether input is an infinite value.
`isnan`	Returns whether input is Not-a-Number (NaN) value.

Name	Description
log	Returns the natural logarithm function.
log2	Returns the (base-2) logarithm function.
log10	Returns the common (base-10) logarithm function.
loggamma	Computes log of absolute value of the loggamma function.
not	Reverses the value of its boolean argument.
pi	Returns the constant value of Pi.
pow	Returns a result of raising to power.
radians	Converts angle value in degrees into value in radians.
rand	Returns a random number.
range	Generates a dynamic array, holding a series of equally spaced values.
round	Returns the rounded source to the specified precision.
sign	Returns the sign of a numeric expression.
sin	Returns the sine of a numeric expression.
sqrt	Returns the square root function.
tan	Returns the tangent function.

14.5.3.9.1. Abs

The `abs` function calculates the absolute value of the input.

Syntax

```
abs( X )
```

Copy

Arguments

- **X**: An integer or real number, or a timespan value.

Returns

Absolute value of x.

Examples

```
print num = -9999999
| extend newField = abs( num )
```

Copy Run in Cribl Search

14.5.3.9.2. Acos

The `acos` function calculates the angle whose cosine is the specified number (the inverse operation of `cos`).

Syntax

```
acos( X )
```

Copy

Arguments

- **X**: A real number in range [-1, 1].

Results

The value of the arc cosine of **X**. Returns `null` if **X** < -1 or **X** > 1

Examples

This example returns `3.141592653589793`:

```
print num = -1
| extend newField = acos( num )
```

Copy Run in Cribl Search

14.5.3.9.3. Asin

The `asin` function calculates the angle whose sine is the specified number (the inverse operation of `sin`).

Syntax

```
asin( X )
```

Copy

Arguments

- **X**: A real number in range [-1, 1].

Returns

Returns the value of the arc sine of **X**. Returns `null` if **X** < -1 or **X** > 1.

Examples

This example returns `1.5707963267948966`;

```
print num = 1
| extend newField = asin( num )
```

Copy Run in Cribl Search

14.5.3.9.4. Atan

The `atan` function returns the angle whose tangent is the specified number (the inverse operation of `tan`).

Syntax

```
atan( X )
```

Copy

Arguments

- **X**: A real number.

Returns

The value of the arc tangent of **X**.

Examples

This example returns `1.5485777614681775`:

```
print num = 45
| extend newField = atan( num )
```

Copy Run in Cribl Search

14.5.3.9.5. ATAN2

The `atan2` function calculates the angle, in radians, between the positive x-axis and the ray from the origin to the point (y, x).

Syntax

```
atan2( Y, X )
```

Copy

Arguments

- **X**: X coordinate (a real number).
- **Y**: Y coordinate (a real number).

Returns

Returns the angle in radians between the positive x-axis and the ray from the origin to the point (y, x).

Examples

This example returns `1.571`:

```
print atan2( 1,0 )
```

Copy Run in Cribl Search

14.5.3.9.6. BETA_CDF

The `beta_cdf` function returns the standard cumulative beta distribution function.

The beta distribution is commonly used to study variation in the percentage of something across samples, such as the fraction of the day people spend watching television.

Syntax

```
beta_cdf( X, Alpha, Beta )
```

Copy

Arguments

- **X**: A value at which to evaluate the function.
- **Alpha**: A parameter of the distribution.
- **Beta**: A parameter of the distribution.

Returns

The cumulative beta distribution function.

Note:

- If any argument is nonnumeric, beta_cdf() returns null value.
- If x < 0 or x > 1, beta_cdf() returns NaN value.
- If alpha ≤ 0 or alpha > 10000, beta_cdf() returns the NaN value.
- If beta ≤ 0 or beta > 10000, beta_cdf() returns the NaN value.

Examples

```
dataset="cribl_search_sample" dataSource="access_combined"
| limit 100
| summarize combinations = count() by host, clientip
| extend betaDistrib = beta_cdf( combinations, 10, 20 )
```

Copy Run in Cribl Search

14.5.3.9.7. BETA_INV

The `beta_inv` function returns the inverse of the beta cumulative probability beta density function.

The beta distribution can be used in project planning to model probable completion times given an expected completion time and variability.

Syntax

```
beta_inv( Probability, Alpha, Beta )
```

Copy

Arguments

- **Probability**: A probability associated with the beta distribution.
- **Alpha**: A parameter of the distribution.
- **Beta**: A parameter of the distribution.

Returns

The inverse of the beta cumulative probability density function beta_cdf.

Note:

- If any argument is nonnumeric, **beta_inv** returns null value.
- If alpha ≤ 0 or beta ≤ 0, **beta_inv** returns the null value.
- If probability ≤ 0 or probability > 1, **beta_inv** returns the NaN value.
- Given a value for probability, **beta_inv** seeks that value x such that beta_cdf(x, alpha, beta) = probability.

Examples

```
dataset="cribl_search_sample" dataSource="access_combined"
| limit 100
| summarize combinations = count() by host, clientip
| extend invBetaDensity = beta_inv( combinations, 10, 20 )
```

Copy Run in Cribl Search

14.5.3.9.8. BETA_PDF

The `beta_pdf` function returns the probability density beta function.

The beta distribution is commonly used to study variation in the percentage of something across samples, such as the fraction of the day people spend watching television.

Syntax

```
beta_pdf( X, Alpha, Beta )
```

Copy

Arguments

- **X**: A value at which to evaluate the function.
- **Alpha**: A parameter of the distribution.
- **Beta**: A parameter of the distribution.

Returns

The probability beta density function.

Note:

- If any argument is nonnumeric, beta_pdf() returns null value.
- If x ≤ 0 or 1 ≤ x, beta_pdf() returns NaN value.
- If alpha ≤ 0 or beta ≤ 0, beta_pdf() returns the NaN value.

Examples

```
dataset="cribl_search_sample" dataSource="access_combined"
| limit 100
| summarize combinations = count() by host, clientip
| extend probBetaDensity = beta_pdf( combinations, 10, 20 )
```

Copy Run in Cribl Search

14.5.3.9.9. Ceil

The `ceil` function rounds up an input numeric expression's value to the nearest matching integer.

Alias: `ceiling` (`ceiling` and `ceil` are synonyms).

Syntax

```
ceil(number)
```

Copy

Arguments

Name	Type	Required	Description
number	int, long, or real	Yes	The value to round up.

Results

The smallest integer equal to, or greater than, the value of the specified numeric expression.

Examples

This example returns `100`:

```
print num = 99.01
| extend newField = ceil( num )
```

Copy Run in Cribl Search

14.5.3.9.10. Ceiling

The `ceiling` function rounds up an input numeric expression's value to the nearest matching integer.

Alias: `ceil` (`ceil` and `ceiling` are synonyms).

Syntax

```
ceiling(number)
```

Copy

Arguments

Name	Type	Required	Description
number	int, long, or real	Yes	The value to round up.

Results

The smallest integer equal to, or greater than, the value of the specified numeric expression.

Examples

This example returns `100`:

```
print num = 99.01
| extend newField = ceiling( num )
```

Copy Run in Cribl Search

14.5.3.9.11. Cos

The `cos` function returns the cosine of the specified numeric expression.

Syntax

```
cos( X )
```

Copy

Arguments

- **X**: A real number.

Examples

This example returns `0.5403023058681398`:

```
print num = 1
| extend newField = cos( num )
```

Copy Run in Cribl Search

14.5.3.9.12. Cot

The `cot` function calculates the trigonometric cotangent of the specified angle, in radians.

Syntax

```
cot( X )
```

Copy

Arguments

- X: A real number.

Results

The cotangent function value for X.

Examples

This example returns `0.6173696237835551`:

```
print num = 45
| extend newField = cot( num )
```

Copy Run in Cribl Search

14.5.3.9.13. Degrees

The `degrees` function converts angle value in radians into value in degrees, using formula `degrees = ( 180 / PI ) * angle_in_radians`.

Syntax

```
degrees( X )
```

Copy

Arguments

- **X**: Angle in radians (a real number).

Results

The corresponding angle in degrees for an angle specified in radians.

Examples

This example returns approximately `360` degrees:

```
print num = 6.283
| extend newField = degrees( num )
```

Copy Run in Cribl Search

14.5.3.9.14. Exp

The `exp` function calculates the base-e exponential function of x, which is e raised to the power x: `e^x`.

Syntax

```
exp( X )
```

Copy

Arguments

- **X**: A real number, value of the exponent.

Results

Exponential value of **X**.

Examples

This example returns `54.598`:

```
print exp( 4 )
```

Copy Run in Cribl Search

14.5.3.9.15. Exp2

The `exp2` function calculates the base-2 exponential function of x, which is 2 raised to the power x: `2^x`.

Syntax

```
exp2( X )
```

Copy

Arguments

- **X**: A real number, value of the exponent.

Results

Exponential value of **X**.

Examples

This example returns `16`:

```
print exp2( 4 )
```

Copy Run in Cribl Search

14.5.3.9.16. Exp10

The `exp10` function calculates the base-10 exponential function of x, which is 10 raised to the power x: `10^x`.

Syntax

```
exp10( X )
```

Copy

Arguments

- **X**: A real number, value of the exponent.

Results

Exponential value of **X**.

Examples

This example returns `10,000`:

```
print exp10( 4 )
```

Copy Run in Cribl Search

14.5.3.9.17. GAMMA

The `gamma` function computes gamma function.

Syntax

```
gamma( X )
```

Copy

Arguments

- **X**: Parameter for the gamma function.

Results

Gamma function of **X**.

Examples

This example returns `6`:

```
print gamma( 4 )
```

Copy Run in Cribl Search

14.5.3.9.18. ISFINITE

The `isfinite` function returns whether input is a finite value (is neither infinite nor NaN).

Syntax

```
isfinite( X )
```

Copy

Arguments

- **X**: A real number.

Results

A non-zero value (true) if **X** is finite, and zero (false) otherwise.

Examples

This returns `true`:

```
print isfinite( 420 )
```

Copy Run in Cribl Search

This returns `false`:

```
print isfinite( hello )
```

Copy Run in Cribl Search

14.5.3.9.19. ISINF

The `isinf` function returns whether input is an infinite (positive or negative) value.

Syntax

```
isinf( X )
```

Copy

Arguments

- **X**: A real number.

Results

A non-zero value (true) if **X** is a positive or negative infinite, and zero (false) otherwise.

Examples

This returns `false`:

```
print isinf( 420 )
```

Copy Run in Cribl Search

This returns `true`:

```
print x = 42/0
| extend y = isinf( x )
```

Copy Run in Cribl Search

This returns `true`:

```
print isinf( world )
```

Copy Run in Cribl Search

14.5.3.9.20. ISNAN

The `isnan` function returns whether input is Not-a-Number (NaN) value.

Syntax

```
isnan( X )
```

Copy

Arguments

- **X**: A real number.

Results

A non-zero value (true) if **X** is NaN, and zero (false) otherwise.

Examples

This returns `false`:

```
print isnan( 42 )
```

Copy Run in Cribl Search

This returns `true`:

```
print x = toint( 'pizza' )
| extend y = isnan( x )
```

Copy Run in Cribl Search

14.5.3.9.21. Log

The `log` function returns the natural logarithm function.

Syntax

```
log( X )
```

Copy

Arguments

- X: A real number greater than 0.

Results

- The natural logarithm is the base-e logarithm: the inverse of the natural exponential function (exp).
- `null` if the argument is negative or null or can't be converted to a `real` value.

Examples

This returns `4`:

```
print log( 54.598 )
```

Copy Run in Cribl Search

14.5.3.9.22. Log2

The `log2` function returns the (base-2) logarithm function.

Syntax

```
log2( X )
```

Copy

Arguments

- X: A real number greater than 0.

Results

- The logarithm is the base-2 logarithm: the inverse of the exponential function (exp) with base 2.
- `null` if the argument is negative or null or can't be converted to a `real` value.

Examples

This returns `4`:

```
print log2( 16 )
```

Copy Run in Cribl Search

14.5.3.9.23. Log10

The `log10` function returns the common (base-10) logarithm function.

Syntax

```
log10( X )
```

Copy

Arguments

- X: A real number greater than 0.

Results

- The common logarithm is the base-10 logarithm: the inverse of the exponential function (exp) with base 10.
- `null` if the argument is negative or null or can't be converted to a `real` value.

Examples

This returns `4`:

```
print log10( 10000 )
```

Copy Run in Cribl Search

14.5.3.9.24. LOGGAMMA

The `loggamma` function computes log of absolute value of the loggamma function.

Syntax

```
loggamma( X )
```

Copy

Arguments

- X: Parameter for the gamma function.

Results

Returns the natural logarithm of the absolute value of the gamma function of X.

Examples

This returns `4.787`:

```
print loggamma( 6 )
```

Copy Run in Cribl Search

14.5.3.9.25. Not

The `not` function reverses the value of its boolean argument.

Syntax

```
not( Expression )
```

Arguments

- **Expression**: A boolean expression to be reversed.

Results

Returns the reversed logical value of its boolean argument.

If the argument is `null`, or cannot be converted to `bool` (using the `tobool` function), returns `null`.

Examples

These examples return `false`:

```
print not( true )
```

Copy Run in Cribl Search

```
print not( "true" )
```

Copy Run in Cribl Search

```
print not( 1 )
```

Copy Run in Cribl Search

```
print not( 100 )
```

Copy Run in Cribl Search

These examples return `true`:

```
print not( false )
```

Copy Run in Cribl Search

```
print not( "false" )
```

Copy Run in Cribl Search

```
print not( 0 )
```

Copy Run in Cribl Search

These examples return `null`:

```
print not( "abc" )
```

Copy Run in Cribl Search

```
print not( null )
```

Copy Run in Cribl Search

14.5.3.9.26. Pi

The `pi` function returns the constant value of Pi.

Syntax

```
pi()
```

Copy

Results

The double value of Pi (3.1415926...).

Examples

This returns a rounded `3.142`:

```
print pi()
```

Copy Run in Cribl Search

14.5.3.9.27. Pow

The `pow` function returns a result of raising to power.

Syntax

```
pow( Base, Exponent )
```

Copy

Arguments

- **Base**: Base value.
- **Exponent**: Exponent value.

Results

Returns base raised to the power exponent: **Base** ^ **Exponent**.

Examples

This returns `387,420,489`:

```
print pow( 9,9 )
```

Copy Run in Cribl Search

14.5.3.9.28. RADIANS

The `radians` function converts angle value in degrees into value in radians, using formula `radians = (PI / 180 ) * angle_in_degrees`.

Syntax

```
radians( X )
```

Copy

Arguments

- X: Angle in degrees (a real number).

Results

The corresponding angle in radians for an angle specified in degrees.

Examples

This example returns an approximation of π:

```
print num = 180
| extend newField = radians( num )
```

Copy Run in Cribl Search

14.5.3.9.29. RAND

The `rand` function returns a random number.

Syntax

- `rand()` - returns a value of type `real` with a uniform distribution in the range [0.0, 1.0).
- `rand( N )` - returns a value of type `real` chosen with a uniform distribution from the set {0.0, 1.0, ..., N - 1}.

Examples

```
print rand()
```

Copy Run in Cribl Search

```
print rand( 1000 )
```

Copy Run in Cribl Search

14.5.3.9.30. RANGE

The `range` function generates a dynamic array, holding a series of equally spaced values.



To generate a series of events, use the `range` operator.

Syntax

```
range( Start, Stop[, Step] )
```

Copy

Arguments

- **Start**: The value of the first element in the resulting array.
- **Stop**: The value of the last element in the resulting array, or the least value that is greater than the last element in the resulting array and within an integer multiple of step from start.
- **Step**: The difference between two consecutive elements of the array. The default value for step is `1` for numeric and `1h` for `timespan` or `datetime`.

Results

Dynamic array whose values are: `Start`, `Start + Step`, ... up to and including `Stop`. The array will be truncated if the maximum number of values is reached.

Examples

This example returns `[1, 4, 7]`

```
print range( 1, 8, 3 )
```

Copy Run in Cribl Search

This example returns an array holding all days in the year 2015, as Unix time:

```
print range( datetime(2015-01-01), datetime(2015-12-31), 1d )
```

Copy Run in Cribl Search

This example returns `[1,2,3]`:

```
print range( 1, 3 )
```

Copy Run in Cribl Search

This example returns `1`:

```
print range( 1,1000000000 ) | mv-expand r | count
```

Copy Run in Cribl Search

14.5.3.9.31. Round

The `round` function returns the rounded source to the specified precision.

Syntax

```
round( Source [, Precision] )
```

Copy

Arguments

- **Source**: The source scalar the round is calculated on.
- **Precision**: Number of digits the source will be rounded to. (default value is 0)

Results

The rounded source to the specified precision.

Round is different than `bin` and `floor` in that the first rounds a number to a specific number of digits while the last rounds value to an integer multiple of a given bin size (round(2.15, 1) returns 2.2 while bin(2.15, 1) returns 2).

Examples

This example returns `2.2`:

```
print round( 2.15, 1 )
```

Copy Run in Cribl Search

This example returns `2`. It's equivalent to `print round( 2.15, 0 )`:

```
print round( 2.15 )
```

Copy Run in Cribl Search

This example returns `-100`:

```
print round( -50.55, -2 )
```

Copy Run in Cribl Search

This example returns `20`:

```
print round( 21.5, -1 )
```

Copy Run in Cribl Search

14.5.3.9.32. Sign

The `sign` function returns the sign of a numeric expression.

Syntax

```
sign( X )
```

Copy

Arguments

- X: A real number.

Results

The positive (+1) zero (0) or negative (-1) sign of the specified expression.

Examples

This returns `1` for positive:

```
print sign ( 10000 )
```

Copy Run in Cribl Search

This returns `-1` for negative:

```
print sign ( -9999 )
```

Copy Run in Cribl Search

14.5.3.9.33. Sin

The `sin` function returns the sine of a numeric expression.

Syntax

```
sin( X )
```

Copy

Arguments

- X: A real number.

Examples

This example returns `0.9092974268256817`:

```
print num = 2
| extend newField = sin( num )
```

Copy Run in Cribl Search

14.5.3.9.34. Sqrt

The `sqrt` function returns the square root function.

Syntax

```
sqrt( X )
```

Copy

Arguments

- X: A real number >= 0.

Returns

- A positive number such that `sqrt(x) * sqrt(x) == x`.
- `null` if the argument is negative or cannot be converted to a `real` value.

Examples

This returns `4`:

```
print sqrt ( 16 )
```

Copy Run in Cribl Search

This returns `null`:

```
print sqrt ( -64 )
```

Copy Run in Cribl Search

14.5.3.9.35. TAN

The `tan` function returns the tangent of a numeric expression.

Syntax

```
tan( X )
```

Copy

Arguments

- **X**: A real number.

Examples

This example returns `-1.995200412208242`:

```
print num = 90
| extend newField = tan( num )
```

Copy Run in Cribl Search

14.5.3.10. String Functions

A list of all string functions supported by Cribl Search.

Name	Description
`base64_decode_toarray`	Decodes a base64 string to an array of long values.
`base64_decode_tostring`	Decodes a base64 string to a UTF-8 string.
`base64_encode_fromarray`	Encodes a base64 string from a bytes array.
`base64_encode_tostring`	Encodes a string as base64 string.
`countof`	Counts occurrences of a substring in a string.
`extract`	Gets a match for an RE2 regular expression from a source string.
`extract_all`	Gets all matches for an RE2 regular expression from a source string.
`extract_json`	Gets a specified element out of a JSON text using a path expression.
`has_any_index`	Gets a match for an RE2 regular expression from a source string.
`indexof`	Reports the zero-based index of the first occurrence of a specified string within the input string.
`isempty`	Returns `true` if the argument is an empty string or is null.
`isnotempty` (`notempty`)	Returns `true` if the argument isn't an empty string, and it isn't null.
`isnotnull` (`notnull`)	Returns `true` if the argument is not null.
`isnull`	Indicates whether the argument evaluates to a null value.
`match_regex`	Searches a text string for a specific pattern defined by a regular expression.
`parse_csv`	Splits a given string representing a single record of comma-separated values.
`parse_ipv4`	Converts IPv4 string to long (signed 64-bit) number representation in big-endian order.
`parse_ipv4_mask`	Converts the input string of IPv4 and netmask to a signed, 64-bit wide, long number representation in big-endian order.

Name	Description
parse_ipv6	Converts IPv6 or IPv4 string to a canonical IPv6 string representation.
parse_ipv6_mask	Converts IPv6/IPv4 string and netmask to a canonical IPv6 string representation.
parse_json (todynamic)	Interprets a string as a JSON value and returns the value as dynamic.
parse_url	Parses an absolute URL string and returns a dynamic object that contains URL parts.
parse_urlquery	Returns a dynamic object that contains the Query parameters.
parse_version	Converts the input string representation of version to a comparable decimal number.
replace_regex	Replaces all RE2 regular expression matches with another string.
reverse	Reverses the order of the input string.
split	Splits a given string according to a given delimiter.
strcat	Concatenates between 1 and 64 arguments.
strcat_delim	Concatenates between 2 and 64 arguments, with a delimiter.
strcmp	Compares two strings.
strlen	Returns the length, in characters, of the input string.
strrep	Repeats given string specified number of times.
substring	Extracts a substring from a source string starting from some index to the end of the string.
tolower	Converts a string to lower case.
toupper	Converts a string to upper case.
translate	Replaces a set of characters with another set of characters in a given string.
trim	Removes all leading and trailing matches of the specified string or regular expression.
trim_end	Removes trailing match of the specified regular expression.
trim_start	Removes leading match of the specified regular expression.

Name	Description
`url_decode`	Converts encoded URL into a to regular URL representation.
`url_encode`	Converts characters of the input URL into a format that can be transmitted over the Internet.

14.5.3.10.1. BASE64_DECODE_TOARRAY

The `base64_decode_toarray` function decodes a base64 string to an array of single-character strings.

Syntax

```
base64_decode_toarray( String )
```

Copy

Arguments

- **String**: Input base64 string to be decoded from base64 to an array of single-character strings.

Results

Returns an array of single-character strings decoded from a base64 string.

Examples

This example returns an array of letters that spell out “Cribl”:

```
print dec=base64_decode_toarray("Q3JpYmw=")
```

Copy Run in Cribl Search

This example decodes a base64 encoding of an array that began as `['C',"420.5",'b','l']`:

```
print dec=base64_decode_toarray("QzQyMC41Ymw=")
```

Copy Run in Cribl Search

14.5.3.10.2. BASE64_DECODE_TOSTRING

The `base64_decode_tostring` function decodes a base64 string to a UTF-8 string.

Syntax

```
base64_decode_tostring( String )
```

Copy

Arguments

- **String**: Input string to be decoded from base64 to UTF-8 string.

Results

Returns UTF-8 **String** decoded from base64 string.

Trying to decode a base64 string that was generated from invalid UTF-8 encoding will return null.

Example

```
print
encoded_string=base64_encode_tostring("Cribl!$#@^%#. foo bar baz "),
decoded_string=base64_decode_tostring(encoded_string)
```

Copy Run in Cribl Search

14.5.3.10.3. BASE64_ENCODE_FROMARRAY

The `base64_encode_fromarray` function encodes a base64 string from an array of characters or strings.

Syntax

```
base64_encode_fromarray( BytesArray )
```

Copy

Arguments

- **BytesArray**: Input array of characters or strings to be concatenated and encoded into base64. (Numbers within the array will be stringified as individual numeric characters.)

Results

Returns the base64 string encoded from the array of characters.

Trying to encode a base64 string from an invalid character array, which was generated from invalid UTF-8-encoded string, will return `null`.

Examples

This example encodes an array of familiar characters into its base64 string equivalent:

```
print enc=base64_encode_fromarray(dynamic(['C',"ri",'b','l']))
```

Copy Run in Cribl Search

This example round-trips the input array to yield `["C","4","2","0",".","5","b","l"]`:

```
print enc=base64_encode_fromarray(dynamic(['C',"420.5",'b','l'])),
dec=base64_decode_toarray(enc)
```

Copy Run in Cribl Search

14.5.3.10.4. BASE64_ENCODE_TOSTRING

The `base64_encode_tostring` function encodes a string as base64 string.

Syntax

```
base64_encode_tostring( String )
```

Copy

Arguments

- **String**: Input string to be encoded as base64 string.

Results

Returns the **String** encoded as base64 string.

Example

```
print
encoded_string=base64_encode_tostring("Cribl!$#@^%#. foo bar baz "),
decoded_string=base64_decode_tostring(encoded_string)
```

Copy Run in Cribl Search

14.5.3.10.5. COUNTOF

The `countof` function counts occurrences of a substring in a string. Plain string matches may overlap; regex matches don't.

Syntax

```
countof( Source, Search [, Kind] )
```

Copy

Arguments

- **Source**: A string.
- **Search**: The plain string or regular expression to match inside source.
- **Kind**: `normal` or `regex`, defaults to `normal`.

Results

The number of times that the search string can be matched in the container. Plain string matches may overlap; regex matches don't.

Examples

This example returns `3`:

```
print countof("Hello, world!", "l")
```

Copy Run in Cribl Search

This example returns `1`:

```
print countof("Hello, world!", "ll")
```

Copy Run in Cribl Search

The next few examples show the different treatment of overlapping substrings in `normal` versus `regex` searches.

This example returns `3`:

```
print countof("aaa", "a")
```

Copy Run in Cribl Search

This example returns `3` (not `2`!) because it matches all overlapping occurrences:

```
print countof("aaaa", "aa")
```

Copy Run in Cribl Search

This example returns `2`:

```
print countof("ababa", "ab", "normal")
```

Copy Run in Cribl Search

This example returns `2`:

```
print countof("ababa", "aba")
```

Copy Run in Cribl Search

This example returns `1`, because the `regex` argument prevents matches on overlapping occurrences:

```
print countof("ababa", "aba", "regex")
```

Copy Run in Cribl Search

This example returns `2`:

```
print countof("abcabc", "a.c", "regex")
```

Copy Run in Cribl Search

This example returns `6`:

```
print countof("abcdefedcba", "[abc]", "regex")
```

Copy Run in Cribl Search

This example returns `2`:

```
print countof("abc1234abcd1234", "[0-9]+", "regex")
```

Copy Run in Cribl Search

14.5.3.10.6. Extract

The `extract` function gets a match for an RE2 regular expression from a source string. Optionally, convert the extracted substring to the indicated type.



To extract fields, field values, or key-value pairs from events, using a wide range of flexible options, see the `extract` operator.

Syntax

```
extract( Regex, CaptureGroup, Source [, TypeLiteral] )
```

Copy

Arguments

- **Regex**: An RE2 regular expression.
- **CaptureGroup**: A positive `int` constant indicating the capture group to extract. 0 stands for the entire match, 1 for the value matched by the first '('parenthesis')' in the regular expression, 2 or more for subsequent parentheses.
- **Source**: A string to search.
- **TypeLiteral**: An optional type literal (for example, `typeof(long)`). If provided, the extracted substring is converted to this type.

Results

If regex finds a match in **Source**: the substring matched against the indicated capture group **CaptureGroup**, optionally converted to **TypeLiteral**.

If there's no match: a blank string.

If the type conversion fails: `null`.

Examples

Extract a Single Field Value

This example works with Apache access log events of this form:

```
128.241.220.82 - - [07/Mar/2025:18:30:13 +0000] "GET /product.screen?product_id=Goats
```

Copy

You could extract the `JSESSIONID` value into a field called `sessionId` using this expression:

```
dataset="cribl_search_sample" dataSource="access_combined"
| limit 10000
| extend sessionId = extract(@'JSESSIONID=(.*?)\s', 1, _raw)
```

Copy Run in Cribl Search

Extract and Convert a Capture Group

This example works with VPC Flow Logs events of this form:

```
2 602320997947 eni-7vv3s9v4cng64k53i 10.0.0.138 10.0.0.138 22 3389 6 60 32460 1741637
```

Copy

By default, a Cribl Search Datatype rule parses a `start` field that identifies the session start time - in seconds, in Unix time - represented as a `string`. But this format makes it hard to identify when a session started. Using `extract`, we parse the session start time from the raw log, and also convert the result to a `datetime` object. This creates a new field called `sessionStart`, which represents the start time in human-readable form.

```
dataset="cribl_search_sample" dataSource="vpcflowlogs"
| limit 1000
// Extract the flow 'start' time and convert it from a string to a datetime object.
| extend sessionStart = extract(@'^(?:[^\s]+\s){10}([^\s]+)', 1, _raw, typeof(datetim
```

Copy Run in Cribl Search

Given the example event shown above, this expression would parse the start value of `1741638523` from the raw log, and show it as `2025-03-10T20:28:43.000Z`.

14.5.3.10.7. EXTRACT_ALL

The `extract_all` function gets all matches for an RE2 regular expression from a source string. Optionally, retrieve a subset of matching groups.

Syntax

```
extract_all(Regex, [CaptureGroups,] Source)
```

Copy

Arguments

- **Regex**: A regular expression containing between 1 and 16 capture groups.
    - Example of a valid regex: `@"(\d+)"`
    - Example of an invalid regex: `@"\d+"`
- **CaptureGroups**: A dynamic array constant that indicates the capture group to extract. Valid values are from 1 to the number of capturing groups in the regular expression. Named capture groups are allowed.
    - Named capture group syntax: `?<groupName>`
- **Source**: A string to search.

Results

- If **Regex** finds a match in **Source**: Returns dynamic array including all matches against the indicated capture groups **CaptureGroups**, or all of capturing groups in the **Regex**.
- If number of **CaptureGroups** is 1: The returned array has a single dimension of matched values.
- If number of **CaptureGroups** is more than 1: The returned array is a two-dimensional collection of multi-value matches per **CaptureGroups** selection, or all capture groups present in the regex if **CaptureGroups** is omitted.
- If there's no match: `null`.

Examples

Extract two capture groups

Breaks `interface_id` into two parts, `Family` and `Name`:

```
dataset="cribl_search_sample" | extend interfaceParts=extract_all(@"(?<Family>\w{3})\
```

Copy | Run in Cribl Search

Extract a single capture group

Returns hex-byte representation (two hex-digits) of the GUID. Let Id="82b8be2d-dfa7-4bd1-8f63-24ad26d31449":

```
| extend guid_bytes = extract_all(@"([\da-f]{2})", Id)
```

Copy

ID	guid_bytes
82b8be2d-dfa7-4bd1-8f63-24ad26d31449	["82","b8","be","2d","df","a7","4b","d1","8f","63","24","ad","26","d3",

Extract several capture groups

Uses a regular expression with three capturing groups to split each GUID part into first letter, last letter, and whatever is in the middle. Let Id="82b8be2d-dfa7-4bd1-8f63-24ad26d31449":

```
| extend guid_bytes = extract_all(@"(\w)(\w+)(\w)", Id)
```

Copy

ID	guid_bytes
82b8be2d-dfa7-4bd1-8f63-24ad26d31449	[["8","2b8be2","d"],["d","fa","7"],["4","bd","1"], ["8","f6","3"],["2","4ad26d3144","9"]]

Extract a subset of capture groups

Shows how to select a subset of capturing groups. The regular expression matches the first letter, last letter, and all the rest. The captureGroups parameter is used to select only the first and the last parts. Let Id="82b8be2d-dfa7-4bd1-8f63-24ad26d31449":

```
| extend guid_bytes = extract_all(@"(\w)(\w+)(\w)", dynamic([1,3]), Id)
```

Copy

ID	guid_bytes
82b8be2d-dfa7-4bd1-8f63-24ad26d31449	[["8","d"],["d","7"],["4","1"],["8","3"],["2","9"]]

Using named capture groups

You can use named capture groups of RE2 in `extract_all`. The **CaptureGroups** uses both capture group indexes and named capture group reference to fetch matching values. Let Id="82b8be2d-dfa7-4bd1-8f63-24ad26d31449":

```
| extend guid_bytes = extract_all(@"(?&lt;first>\w)(?&lt;middle>\w+)(?&lt;last>\w)",
```

Copy

ID	guid_bytes
82b8be2d-dfa7-4bd1-8f63-24ad26d31449	[["8","2b8be2","d"],["d","fa","7"],["4","bd","1"],["8","f6","3"],["2","4ad26d3144","9"]]

14.5.3.10.8. EXTRACT_JSON

The `extract_json` function gets a specified element out of a JSON text using a path expression. Optionally convert the extracted string to a specific type.

Syntax

```
extract_json( JsonPath, DataSource, Type )
```

Copy

Arguments

- **JsonPath**: A JSONPath string that defines an accessor into the JSON document. The `[ ]` notation and dot `.` notation are equivalent; see the examples below.
- **DataSource**: A JSON document.
- **Type**: An optional type literal (for example, `typeof(long)`). If provided, the extracted value is converted to this type.

Results

This function performs a JSONPath query into dataSource, which contains a valid JSON string, optionally converting that value to another type depending on the third argument.

Examples

Extract response times to integers:

```
dataset="cribl_internal_logs" response_time
| limit 10
| extend foo=extract_json("$.response_time", _raw, typeof(int))
```

Copy Run in Cribl Search

Extract hosts' available MB to integers:

```
extract_json("$.hosts[1].AvailableMB", EventText, typeof(int))
```

Copy

Same as the previous query, but with equivalent brackets notation:

```
extract_json("$['hosts'][1]['AvailableMB']", EventText, typeof(int))
```

Copy

14.5.3.10.9. HAS_ANY_INDEX

The `has_any_index` function searches an input string for items specified in an input array, and returns the array position (zero-based) of the first item found in the string.

Syntax

```
has_any_index( String, LookupArray )
```

Copy

Arguments

- **String**: A string.
- **LookupArray**: Array of scalar or literal expressions to look up. The values should be of type long, integer, double, decimal, string, or guid.

Results

Zero-based index position of the first item in **LookupArray** that is found in **String**.

Examples

This example matches the first lookup item:

```
print has_any_index("this is an example", dynamic(['this', 'example']))
```

Copy Run in Cribl Search

This example matches the last lookup item:

```
print has_any_index("this is an example", dynamic(['not', 'example']))
```

Copy Run in Cribl Search

This example matches none of the lookup items:

```
print has_any_index("this is an example", dynamic(['not', 'found']))
```

Copy Run in Cribl Search

This example matches within the range of integers:

```
print has_any_index("Example number 2", range(1, 3, 1))
```

Copy Run in Cribl Search

This example doesn't match against the empty lookup array:

```
print has_any_index("this is an example", dynamic([]))
```

Copy Run in Cribl Search

14.5.3.10.10. INDEXOF

The `indexof` function reports the zero-based index of the first occurrence of a specified string within the input string.

If the lookup or input string isn't of `string` type, the function forcibly casts the value to `string`.

Syntax

```
indexof( Source, Lookup [, StartIndex [, Length [, Occurrence ]]] )
```

Copy

Arguments

- **Source**: Input string.
- **Lookup**: String to look up.
- **StartIndex**: Search start position. A negative value will offset the starting search position from the end of the **Source** by this many steps: `abs(StartIndex)`.
- **Length**: Number of character positions to examine. A value of -1 means unlimited length.
- **Occurrence**: The number of the occurrence. Default is `1`.

Results

Zero-based index position of lookup.

- Returns -1 if the string isn't found in the input.
- For irrelevant inputs (occurrence < 0 or length < -1) - returns `null`.

Examples

This example returns `3`:

```
print indexof("Hello, world!", "lo")
```

Copy Run in Cribl Search

This example returns `17`, because the `StartIndex` value of `5` skips over the first match:

```
print indexof("Hello, world, hello!", "lo", 5)
```

Copy Run in Cribl Search

This example returns `2`:

```
print indexof("abcdefg", "cde")
```

Copy Run in Cribl Search

This example returns `2`:

```
print indexof("abcdefg", "cde", 1, 4)
```

Copy Run in Cribl Search

This example returns `-1` for not found. The search starts from index `1`, but stops after 2 characters, so the full lookup string can't be found:

```
print indexof("abcdefg", "cde", 1, 2)
```

Copy Run in Cribl Search

This example returns `-1` for not found. The `3` value supplied for `StartIndex` is beyond where the lookup string begins:

```
print indexof("abcdefg", "cde", 3, 4)
```

Copy Run in Cribl Search

This example returns `5`. The negative `StartIndex` begins the search at the `b` character, allowing the lookup string to match:

```
print indexof("abcdefg", "cde" ,-5)
```

Copy Run in Cribl Search

This example returns `4`. The first two arguments are forcibly cast to strings `12345` and `5`:

```
print indexof(1234567, 5, 1, 4)
```

Copy Run in Cribl Search

This example returns `2`:

```
print indexof("abcdefg", "cde", 2, -1)
```

Copy Run in Cribl Search

This example returns `9`:

```
print indexof("abcdefgabcdefg", "cde", 1, 11, 2)
```

Copy Run in Cribl Search

This example returns `-1` for not found. The third occurrence of the lookup string is outside the specified range:

```
print indexof("abcdefgabcdefg", "cde", 1, -1, 3)
```

Copy Run in Cribl Search

14.5.3.10.11. ISEMPTY

The `isempty` function returns `true` if the argument is an empty string, array, or object, or is null.

Syntax

```
isempty( [ Value ] )
```

Copy

Results

A returned boolean value of `true` indicates that the argument is empty or null.

x	isempty(x)
`""`	true
`"x"`	false
`parse_json("")`	true
`parse_json("[]")`	true
`parse_json("{}")`	true

Examples

Report on missing events:

```
dataset="cribl_internal_logs"
| where isempty(stats.eventsFound)
```

Copy Run in Cribl Search

Report on empty values in an arbitrary field:

```
dataset=myDataset
| where isempty(fieldName)
```

Copy

14.5.3.10.12. ISNOTEMPTY

The `isnotempty` function returns `true` if the argument isn't an empty string, array, or object, and isn't null.

Alias: `notempty`

Syntax

```
isnotempty( [ Value ] )
```

Copy

Results

A returned boolean value of `true` indicates that the argument is not empty or null.

x	isnotempty(x)
""	false
"x"	true
parse_json("")	false
parse_json("[]")	false
parse_json("{}")	false

Examples

This example reports on discovered events:

```
dataset="cribl_internal_logs"
| where isnotempty(stats.eventsFound)
```

Copy Run in Cribl Search

This example returns `false`, because the argument is an empty string:

```
isnotempty("")
```

Copy

14.5.3.10.13. ISNOTNULL

The `isnotnull` function returns `true` if the argument is not null.

Alias: `notnull`

Syntax

```
isnotnull( [ Value ] )
```

Copy

Example

This example returns `true`:

```
print isnotnull('Hello World!')
```

Copy Run in Cribl Search

This example would return all events in which a field named `PossiblyNull` is not null:

```
dataset=myDataset
| where isnotnull(PossiblyNull)
```

Copy

14.5.3.10.14. ISNULL

The `isnull` function evaluates its sole argument and returns a `bool` value indicating whether the argument evaluates to a null value.

Syntax

```
isnull( [ Expression ] )
```

Copy

Results

True or false, depending on whether the value is or is not null.

`string` values cannot be null. Use isempty to determine whether a value of type `string` is empty.

x	isnull(x)
""	false
“x”	false
parse_json("")	true
parse_json("[]")	false
parse_json("{}")	false

Example

This example returns `true`:

```
print isnull( parse_json("No JSON here") )
```

Copy Run in Cribl Search

14.5.3.10.15. MATCH_REGEX

The `match_regex` function searches a text string for a specific pattern defined by a regular expression. It returns a `bool` value indicating whether the pattern was found in the text. This function is commonly used for pattern matching and validation tasks in text processing and data extraction.

Syntax

```
match_regex(Field, Regex)
```

Copy

Arguments

- **Field**: The field or String to match against.
- **Regex**: An RE2 regular expression as a String wrapped in forward slashes, `"/regex/"`.

Results

Returns a `bool` value, where matches are `true` and non-matches are `false`.

Examples

This example checks for source addresses that include the substring `42`:

```
dataset="cribl_search_sample"
| where match_regex(srcaddr, "/42/")
```

Copy Run in Cribl Search

This example finds the Goats on the farm:

```
match_regex("Goats on a farm.", "/Goats/")
```

Copy

This example looks for the substring `is 2`:

```
match_regex("Number is 2.000000", @'/is (\d+)/')
```

Copy

14.5.3.10.16. PARSE_CSV

The `parse_csv` function splits a given string representing a single record of comma-separated values and returns a string array with these values.

Syntax

```
parse_csv( Source )
```

Copy

Arguments

- **Source**: The source string representing a single record of comma-separated values.

Results

A string array that contains the split values.

Embedded line feeds, commas, and quotes may be escaped using the double quotation mark `""`. This function doesn't support multiple records per row (only the first record is taken).

Examples

This example splits a simple comma-separated phrase to a simple array:

```
print theData="Hello, world" | extend parsed_data=parse_csv(theData) | render event
```

Copy Run in Cribl Search

This example:

```
parse_csv('aa,"b,b,b",cc,"Escaping quotes: ""Title""","line1\nline2"')
```

Copy

...returns:

```
[
  "aa",
  "b,b,b",
  "cc",
  "Escaping quotes: "Title"",
  "line1\nline2"
]
```

Copy

This example:

```
parse_csv('record1,a,b,c\nrecord2,x,y,z')
```

Copy

...returns:

```
[
  "record1",
  "a",
  "b",
  "c"
]
```

Copy

14.5.3.10.17. PARSE_IPV4

The `parse_ipv4` function converts IPv4 string to long (signed 64-bit) number representation in big-endian order.

Syntax

```
parse_ipv4( Expression )
```

Arguments

- **Expression**: String expression representing IPv4 that will be converted to long. Denote a subnet mask with a forward slash `/`.

Results

If the conversion is successful, returns a `long` number.

If the conversion fails, returns `null`.

Examples

This example returns `3232235778`:

```
print theData='192.168.1.2' | extend parsed_data=parse_ipv4(theData) | render event
```

Copy | Run in Cribl Search

This example also returns `3232235776`:

```
print theData='192.168.1.2/24' | extend parsed_data=parse_ipv4(theData) | render ever
```

Copy | Run in Cribl Search

This example returns `2130706433`:

```
parse_ipv4("127.0.0.1")`
```

Copy

This example returns `2130706432`:

```
parse_ipv4("127.0.0.1/24")
```

Copy

This example returns `true`:

```
parse_ipv4('192.1.168.1') < parse_ipv4('192.1.168.2')
```

Copy

14.5.3.10.18. PARSE_IPV4_MASK

The `parse_ipv4_mask` function converts the input string of IPv4 and netmask to a signed, 64-bit wide, long number representation in big-endian order.

Syntax

```
parse_ipv4_mask( Expression, PrefixMask )
```

Arguments

- **Expression**: String expression representing IPv4 that will be converted to long.
- **PrefixMask**: An integer from 0 to 32 representing the number of most-significant bits that are taken into account.

Results

If the type conversion is successful, returns a `long` number.

If the conversion fails, returns `null`.

Examples

This example returns `3232235776`:

```
print theData='192.168.1.2'  | extend theMask=24, parsed_data=parse_ipv4_mask(theData
```

Copy | Run in Cribl Search

This example returns `2130706432`:

```
parse_ipv4_mask("127.0.0.1", 24)
```

Copy

This example returns `parse_ipv4_mask('192.1.168.3', 31)`:

```
parse_ipv4_mask('192.1.168.2', 31)` returns as `parse_ipv4_mask('192.1.168.3', 31)
```

Copy

14.5.3.10.19. PARSE_IPV6

The `parse_ipv6` function converts IPv6 or IPv4 string to a canonical IPv6 string representation.

Syntax

```
parse_ipv6( Expression )
```

Arguments

- **Expression**: String expression representing IPv6/IPv4 network address that will be converted to canonical IPv6 representation. Denote a subnet mask with a forward slash `/`.

Results

If the conversion is successful, returns a `string` representing a canonical IPv6 network address.

If the conversion fails, returns `null`.

Examples

```
print theData='192.168.1.2'  | extend parsed_data=parse_ipv6(theData) | render event
```

Copy | Run in Cribl Search

```
print theData='abcd::ffff:c0a8:0102'  | extend parsed_data=parse_ipv6(theData) | renc
```

Copy | Run in Cribl Search

This example returns `'0000:0000:0000:0000:0000:ffff:7f00:0001'`:

```
parse_ipv6("127.0.0.1")
```

Copy

This example returns `'fe80:0000:0000:0000:085d:e82c:9446:7994'`:

```
parse_ipv6(":fe80::85d:e82c:9446:7994")
```

Copy

14.5.3.10.20. PARSE_IPV6_MASK

The `parse_ipv6_mask` function converts an IPv6/IPv4 string and netmask to a canonical IPv6 string representation.

Syntax

```
parse_ipv6_mask( Expression, PrefixMask )
```

Arguments

- **Expression**: String expression representing IPv6 that will be converted to long.
- **PrefixMask**: An integer from 0 to 128 representing the number of most-significant bits that are taken into account.

Results

If the conversion is successful, returns a `string` representing a canonical IPv4 or IPv6 network address.

If the conversion fails, returns `null`.

Examples

```
print theData='abcd::ffff:c0a8:0102'  | extend theMask=24, parsed_data=parse_ipv6_mas
```

Copy | Run in Cribl Search

This example returns `'0000:0000:0000:0000:0000:ffff:7f00:0000'`:

```
parse_ipv6_mask("127.0.0.1", 24)
```

Copy

This example returns `'fe80:0000:0000:0000:085d:e82c:9446:7900'`:

```
parse_ipv6_mask(":fe80::85d:e82c:9446:7994", 120)
```

Copy

14.5.3.10.21. PARSE_JSON

The `parse_json` function interprets a `string` as a JSON value and returns the value as `dynamic`. Where possible, it converts the value into relevant data types.



For strict parsing with no data type conversion, use the extract or extract_json function instead.

Alias: `todynamic`

This function is better than `extract_json` when you need to extract more than one element of a JSON compound object.

Syntax

```
parse_json( JSON )
```

Copy

Arguments

- **JSON**: An expression of type `string`. It represents a JSON-formatted value, or an expression of type dynamic, representing the actual `dynamic` value.

Results

An object of type `dynamic` that is determined by the value of **JSON**:

- If **JSON** is of type `dynamic`, its value is used as-is.
- If **JSON** is of type `string`, and is a properly formatted JSON string, then the string is parsed, and the value produced is returned.
- If **JSON** is of type `string`, but it isn't a properly formatted JSON string, then the returned value is an object of type `dynamic` that holds the original `string` value.

Example

```
print theData='{"theValue":123,"theString":"Hello!"}' | extend parsed_data=parse_jsor
```

Copy Run in Cribl Search

In the following example, when `context_custom_metrics` is a `string` that looks like this:

```
{"duration":{"value":118.0,"count":5.0,"min":100.0,"max":150.0,"stdDev":0.0,"sampled\
```

Copy

...then the following KQL fragment retrieves the value of the `duration` slot in the object, and from that it retrieves two slots, `duration.value` and `duration.min` (`118.0` and `110.0`, respectively):

```
dataset=myDataset
| extend d=parse_json(context_custom_metrics)
| extend duration_value=d.duration.value, duration_min=d["duration"]["min"]
```

Copy

14.5.3.10.22. PARSE_URL

The `parse_url` function parses an absolute URL `string` and returns a `dynamic` object that contains URL parts.

Syntax

```
parse_url( URL )
```

Copy

Arguments

- **URL**: A string representing a URL or the query part of the URL.

Results

An object of type `dynamic` that included the URL components: Scheme, Host, Port, Path, Username, Password, Query Parameters, Fragment.

Example

```
print theData="scheme://username:password@the.host.com:1234/this/is/a/path?k1=v1&k2=v
```

Copy Run in Cribl Search

```
print theData="scheme://username:password@the.host.com:1234/this/is/a/path?k1=v1&k2=v
```

Copy Run in Cribl Search

This example:

```
parse_url("scheme://username:password@host:1234/this/is/a/path?k1=v1&k2=v2#fragment")
```

Copy

...returns:

```
{
        "Scheme":"scheme",
        "Host":"host",
        "Port":"1234",
        "Path":"this/is/a/path",
        "Username":"username",
        "Password":"password",
        "Query Parameters":"{"k1":"v1", "k2":"v2"}",
        "Fragment":"fragment"
 }
```


Copy

14.5.3.10.23. PARSE_URLQUERY

The `parse_urlquery` function returns a `dynamic` object that contains URL query parameters from an input string.

Syntax

```
parse_urlquery( Query )
```

Copy

Arguments

- **Query**: A string represents a URL query. Format should follow URL query standards `key=value& ....`

Results

An object of type `dynamic` that includes URL query parameters from the input string.

Example

```
print theData="k1=v1&k2=v2&k3=v3" | extend parsed_data=parse_urlquery(theData), theQu
```

Copy Run in Cribl Search

This example:

```
parse_urlquery("k1=v1&k2=v2&k3=v3")
```

Copy

...returns:

```
{
  "Query Parameters":"{"k1":"v1", "k2":"v2", "k3":"v3"}",
}
```

Copy

14.5.3.10.24. PARSE_VERSION

The `parse_version` function converts the input string representation of a version number to a comparable decimal number.

Syntax

```
parse_version( Expression )
```

Arguments

- **Expression**: A scalar expression of type `string` that specifies the version to be parsed.
    - Input string must contain from one to four version parts, represented as numbers and separated with dots `.`.
    - Each part of version may contain up to eight digits, with the max value at 99999999.
    - If the number of parts is less than four, all the missing parts are considered as trailing (`1.0 == 1.0.0.0`).

Results

If the conversion is successful, returns a decimal.

If the conversion fails, returns `null`.

Example

This example converts the two input strings to decimal values, and then compares the values:

```
print theData="9.2", theData2="9.11.3" | extend v1=parse_version(theData), v2=parse_v
```

Copy | Run in Cribl Search

14.5.3.10.25. REPLACE_REGEX

The `replace_regex` function replaces all RE2 regular expression matches with another string.

Syntax

```
replace_regex( Text, Regex, Rewrite )
```

Copy

Arguments

- **Text**: A string.
- **Regex**: The RE2 regular expression to search text. The expression can contain capture groups in parentheses.
- **Rewrite**: The replacement regex for any match made by **Regex**. Use `\0` to refer to the whole match, `\1` for the first capture group, `\2` and so on for subsequent capture groups.

Results

Source after replacing all matches of **Regex** with evaluations of **Rewrite**. Matches do not overlap.

Examples

This example replaces the input string's "is" with "was":

```
print theText="Number is 2.000000"| extend theNewText=replace_regex(theText, @'is (\d
```

Copy Run in Cribl Search

This example returns `Number was: 2.000000`:

```
replace_regex("Number is 2.000000", @'is (\d+)', @'was: \1')
```

Copy

This example returns `Number was: 5.000000`:

```
replace_regex("Number is 5.000000", @'is (\d+)', @'was: \1')
```

Copy

14.5.3.10.26. Reverse

The `reverse` function reverses the order of the input `string`. If the input value isn't of type string, then the function forcibly casts the value to type `string`.

Syntax

```
reverse( Source )
```

Copy

Arguments

- **Source**: Input value.

Results

The reverse order of a string value.

Examples

This example returns `olleH`:

```
print str1="Hello" | extend newstr=reverse(str1)
```

Copy Run in Cribl Search

This example returns `ZYXWVUTSRQPONMLKJIHGFEDCBA`:

```
print reverse("ABCDEFGHIJKLMNOPQRSTUVWXYZ")
```

Copy Run in Cribl Search

14.5.3.10.27. Split

The `split` function splits a given string according to a given delimiter and returns a string array with the contained substrings. Optionally, a specific substring can be returned if it exists.

Syntax

```
split( Source, Delimiter [, RequestedIndex] )
```

Copy

Arguments

- **Source**: The source string that will be split according to the given delimiter.
- **Delimiter**: The delimiter that will be used to split the source string.
- **RequestedIndex**: An optional zero-based index `int`. If provided, the returned string array will contain the requested substring if it exists.

Results

A string array that contains the substrings of the given source string that are delimited by the given delimiter.

Examples

- `split("aa_bb", "_")` returns as `["aa","bb"]`
- `split("aaa_bbb_ccc", "_", 1)` returns as `["bbb"]`
- `split("", "_")` returns as `[""]`
- `split("a__b", "_")` returns as `["a","","b"]`
- `split("aabbcc", "bb")` returns as `["aa","cc"]`

Example Query: Split URL Path Segments

```
dataset=$vt_dummy
| extend url = '/api/v1/items/42'
| extend segments = split(url, '/'),
         resource = split(url, '/', 3),   // ["items"]
         id = split(url, '/', 4)          // ["42"]
```

Copy Run in Cribl Search

Example Query: Split Comma-Separated Values

```
dataset=$vt_dummy
| extend line = 'alpha,beta,gamma'
| extend parts = split(line, ','),
         second = split(line, ',', 1)    // ["beta"]
```

Copy Run in Cribl Search

Example Query: Isolate Filename Extension

```
dataset=$vt_dummy
| extend filename = 'awesome.log'
| extend basename = split(filename, '.', 0) // ["awesome"]
```

Copy Run in Cribl Search

14.5.3.10.28. Strcat

The `strcat` function concatenates between 1 and 64 arguments to a single string.

Syntax

```
strcat( Argument1, Argument2 [, ArgumentN ] )
```

Arguments

- **Argument1 ... ArgumentN**: Expressions to be concatenated.

If an argument is not of the `string` type, it's forcibly converted to `string`.

If an argument is `null`, it's converted to a blank string.

Results

Arguments concatenated to a single string.

Usage Note

Concatenate strings using the `strcat` or `strcat-delim` function. Do not rely on the `+` operator (with `"string1" + "string2"` notation).

Examples

The first two examples return `hello world`:

```
print str1="hello", str2="world" | extend newstr=strcat(str1," ", str2)
```

Copy Run in Cribl Search

```
print strcat("hello", " ", "world")
```

Copy Run in Cribl Search

This example returns `"The value is: "`:

```
print strcat('The value is: ', null)
```

14.5.3.10.29. STRCAT_DELIM

The `strcat_delim` function concatenates between 2 and 64 arguments, with the specified delimiter.

Syntax

```
strcat_delim( Delimiter, Argument1, Argument2 [, ArgumentN ] )
```

Arguments

- **Delimiter**: String expression, which will be used as separator.
- **Argument1 ... ArgumentN**: Expressions to be concatenated.

If an argument is not of the `string` type, it's forcibly converted to `string`.

If an argument is `null`, it's converted to a blank string.

Results

Arguments, concatenated to a single string with **Delimiter**.

Usage Note

Concatenate strings using the `strcat-delim` or `strcat` function. Do not rely on the `+` operator (with `"string1" + "string2"` notation).

Examples

```
print str1="hello", str2="world" | extend newstr=strcat_delim("|",str1,str2)
```

Copy Run in Cribl Search

```
print strcat_delim('-', 1, '2', 'A', 1s)
```

Copy Run in Cribl Search

14.5.3.10.30. Strcmp

The `strcmp` function compares two strings.

The function starts comparing the first character of each string. If they are equal to each other, it continues with the following pairs until the characters differ or until the end of the shorter string is reached.

Syntax

```
strcmp( String1, String2 )
```

Copy

Arguments

- **String1**: First input string for comparison.
- **String2**: Second input string for comparison.

Results

Returns an integral value indicating the relationship between the strings:

- `<0` : the first character that does not match has a lower value in **String1** than in **String2**
- `0` : the contents of both strings are equal
- `>0` : the first character that does not match has a greater value in **String1** than in **String2**

Examples

This example returns `-1` for lower value:

```
print str1="ABC", str2="ABCd" | extend match=strcmp(str1,str2)
```

Copy Run in Cribl Search

This example returns `0` for equality:

```
print strcmp(ABC,ABC)
```

Copy Run in Cribl Search

This example returns `1` for greater value:

```
print strcmp(abc,ABC)
```

Copy Run in Cribl Search

This example returns `1` for greater value:

```
print strcmp(abcde,abc)
```

Copy Run in Cribl Search

14.5.3.10.31. Strlen

The `strlen` function returns the length, in characters, of the input string.

Syntax

```
strlen( Source )
```

Copy

Arguments

- **Source**:The source string that will be measured for string length.

Results

Returns the length, in characters, of the input string.

This function counts Unicode code points.

Examples

This example returns `5`:

```
print str1="hello" | extend fieldlen=strlen(str1)
```

Copy Run in Cribl Search

14.5.3.10.32. Strrep

The `strrep` function repeats given string specified number of times. If first or third argument is not of a string type, it will be forcibly converted to string.

Syntax

```
strrep( Value, Multiplier, [ Delimiter ] )
```

Copy

Arguments

- **Value**: Input expression.
- **Multiplier**: Positive integer value (from 1 to 1024).
- **Delimiter**: An optional string expression (default: empty string).

Results

Value repeated for a specified number of times, concatenated with **Delimiter**.

If **Multiplier** is more than maximum allowed value (1024), input string will be repeated 1024 times.

Examples

This example returns `HelloHelloHello`:

```
print str1="Hello" | extend newstr=strrep(str1,3)
```

Copy Run in Cribl Search

This example returns `Hello-Hello-Hello`:

```
print str1="Hello" | extend newstr=strrep(str1,3,"-")
```

Copy Run in Cribl Search

This example returns `ABCABC`:

```
print strrep('ABC', 2)
```

Copy Run in Cribl Search

This example returns `123.123.123`:

```
print strrep(123,3,'.')
```

Copy Run in Cribl Search

This example returns `3 3`:

```
print strrep(3s,2,' ')
```

Copy Run in Cribl Search

14.5.3.10.33. Substring

The `substring` function extracts a substring from a source string starting from some index to the end of the string.

Optionally, the length of the requested substring can be specified.

Syntax

```
substring( Source, StartingIndex [, Length] )
```

Copy

Arguments

- **Source**: The source string that the substring will be taken from.
- **StartingIndex**: The zero-based starting character position of the requested substring. Can be a negative number, in which case the substring will be retrieved from the end of the source string.
- **Length**: An optional parameter that can be used to specify the requested number of characters in the substring.

Results

A substring from the given string. The substring starts at the **StartingIndex** (zero-based) character position and continues to the end of the string (or to **Length** characters, if specified).

Examples

This example returns `23456`:

```
print substring("123456", 1)
```

Copy Run in Cribl Search

This example returns `34`:

```
print substring("123456", 2, 2)
```

Copy Run in Cribl Search

This example returns `AB`:

```
print substring("ABCD", 0, 2)
```

Copy Run in Cribl Search

This example returns `56`:

```
print substring("123456", -2, 2)
```

Copy Run in Cribl Search

14.5.3.10.34. TOLOWER

The `tolower` function converts a string to lower case.

If the input string is `null`, the function returns a blank string.

Syntax

```
tolower( String )
```

Copy

Arguments

- **String**: A string.

Example

This example returns lowercase `hello, world`:

```
print str1="Hello, World" | extend newstr=tolower(str1)
```

Copy | Run in Cribl Search

14.5.3.10.35. Toupper

The `toupper` function converts a string to upper case.

If the input string is `null`, the function returns a blank string.

Syntax

```
toupper( String )
```

Copy

Arguments

- **String**: A string.

Example

This example returns uppercase `HELLO, WORLD`:

```
print str1="Hello, World" | extend newstr=toupper(str1)
```

Copy Run in Cribl Search

14.5.3.10.36. TRANSLATE

The `translate` function replaces a set of characters with another set of characters in a given string. The function searches for characters in the `SearchList` and replaces them with the corresponding characters in `ReplacementList`.

Syntax

```
translate( SearchList, ReplacementList, Source )
```

Copy

Arguments

- **SearchList**: The list of characters that should be replaced.
- **ReplacementList**: The list of characters that should replace the characters in `SearchList`.
- **Source**: A string to search.

Results

Source after replacing all occurrences of characters in `ReplacementList` with the corresponding characters in `SearchList`.

Examples

This example returns `xxx`:

```
print translate("abc", "x", "abc")
```

Copy Run in Cribl Search

This example returns `kusto`:

```
print translate("krasp", "otsku", "spark")
```

Copy Run in Cribl Search

This example returns `hello world`:

```
print translate("abcdefghijklmopqrstuvwxyz", "zyxwvutsrqpomlkjihgfedcba", "svool dlio
```

Copy Run in Cribl Search

This example also returns `hello world`, by calling `reverse`:

```
print translate("abcdefghijklmopqrstuvwxyz", reverse("abcdefghijklmopqrstuvwxyz"), "s
```

Copy Run in Cribl Search

14.5.3.10.37. Trim

The `trim` function removes all leading and trailing matches of the specified string or regular expression.

Syntax

```
trim( {Regex | String}, Source )
```

Copy

Arguments

- **Regex**: Regular expression or string to trim from the beginning and/or the end of **Source**. Pass a regular expression in the format `@'<regex>'`; pass a string the format `"<string>"`. If you omit this argument, the function applies regex to match all whitespace.
- **Source**: A string.

Results

Source, after trimming matches of **Regex** or **String** found in the beginning and/or the end of **Source**.

Examples

Add some leading characters with `strcat`, then remove them with `trim`:

```
print str1="ABC"
| extend str2=strcat("  >>",str1),
    thestr=trim("  >>",str2)
```

Copy Run in Cribl Search

Remove leading and trailing `-` characters, **Regex** first argument:

```
print trim(@"\-+", "---Hello, world!---")
```

Copy Run in Cribl Search

Automatically remove leading and trailing whitespace, using implicit regex:

```
dataset="$vt_dummy"
| extend string_to_trim = "   Hello, world!   "
| project
    string_to_trim,
    trimmed_string = trim(string_to_trim)
```

Copy Run in Cribl Search

14.5.3.10.38. TRIM_END

The `trim_end` function removes a trailing match of the specified regular expression.

Syntax

```
trim_end( Regex, Source )
```

Copy

Arguments

- **Regex**: String or regular expression to be trimmed from the end of **Source**.
- **Source**: A string.

Results

Source after trimming matches of **Regex** found at the end of **Source**.

Example

Remove trailing `-` characters:

```
print trim_end(@"\-+", "---Hello, world!---")
```

Copy Run in Cribl Search

14.5.3.10.39. TRIM_START

The `trim_start` function removes a leading match of the specified regular expression.

Syntax

```
trim_start( Regex, Source )
```

Copy

Arguments

- **Regex**: String or regular expression to be trimmed from the beginning of **Source**.
- **Source**: A string.

Results

Source after trimming matches of **Regex** found in the beginning of **Source**.

Example

Remove leading `-` characters:

```
print trim_start(@"\-+", "---Hello, world!---")
```

Copy Run in Cribl Search

14.5.3.10.40. URL_DECODE

The `url_decode` function converts encoded URL into a regular URL representation.

Syntax

```
url_decode( EncodedURL )
```

Copy

Arguments

- **EncodedURL**: Encoded URL (string).

Results

URL (string) in a regular representation.

Examples

This example decodes endpoints from API calls:

```
dataset="cribl_internal_logs" source="file:///opt/cribl/log/access.log"
| where match_regex(url, "/filterExp/")
| extend parsedUrl=url_decode(url)
```

Copy Run in Cribl Search

14.5.3.10.41. URL_ENCODE

The `url_encode` function converts characters of the input URL into a format that can be transmitted over the internet.

Syntax

```
url_encode( URL )
```

Copy

Arguments

- **URL**: Input URL (string).

Results

URL (string) converted into a format that can be transmitted over the internet.

Examples

This example encodes user names - for example, replacing spaces with their `%20` hexadecimal equivalents:

```
dataset="cribl_internal_logs" source="file:///opt/cribl/log/access.log" user="*"
| extend encodedName=url_encode(user)
```

Copy Run in Cribl Search

14.5.4. Statistical Functions

Statistical functions are used together with the `summarize`, `eventstats`, and `timestats` operators to aggregate your data. Cribl Search supports the following statistical functions:

Name	Description
`avg`	Calculates the average across the group.
`avgif`	Calculates the average across the group where a predicate evaluates to `true`.
`count`	Counts events per summarization group.
`countif`	Counts events based on a predicate.
`dcount`	Calculates an estimate of the number of distinct values.
`dcountif`	Calculates an estimate of the number of distinct values for those rows where a predicate evaluates to `true`.
`max`	Finds the maximum value across the group.
`maxif`	Finds the maximum value for which a predicate evaluates to `true`.
`min`	Finds the minimum value across the group.
`minif`	Finds the minimum value which a predicate evaluates to `true`.
`percentile`	Returns an estimate for the specified nearest-rank percentile of the population defined.
`stdev`	Calculates the standard deviation of an expression across the group.
`stdevif`	Calculates the standard deviation of an expression which a predicate evaluates to `true`.
`stdevp`	Calculates the standard deviation of an expression across the group, considering the group as a population.
`sum`	Calculates the sum of an expression across the group.
`sumif`	Calculates the sum of an expression for which a predicate evaluates to `true`.
`take_any`	Returns an arbitrary non-`null` value of an expression from each group.
`take_anyif`	Returns an arbitrary non-`null` value of an expression from rows where a predicate evaluates to `true`.
`variance`	Calculates the variance of an expression.

Name	Description
varianceif	Calculates the variance of an expression for which a predicate evaluates to `true`.
variancep	Calculates the variance of an expression across the group, considering the group as a population.

14.5.4.1. Avg

The `avg` aggregation function calculates the average (arithmetic mean) across the group.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
avg( Expression )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Records with `null` values are ignored and not included in the calculation. Wildcards are not supported for field names.

Results

Returns the average value of **Expression** across the group.

Examples

This example summarizes average byte count across the specified number of events:

```
dataset="cribl_search_sample" | limit 1000 | summarize AverageSessionBytes = avg(byte
```

Copy Run in Cribl Search

This example summarizes average byte count, and corresponding (small-sample) standard deviation, by source address:

```
dataset="cribl_search_sample" dataSource="vpcflowlogs" | summarize avg(bytes), stdev(
```

Copy Run in Cribl Search

This example summarizes average byte count, and two measures of variance (sample- and population-based), by source address:

```
dataset="cribl_search_sample" dataSource="vpcflowlogs"
| summarize avg(bytes), variance(bytes), variancep(bytes) by srcaddr
```

Copy Run in Cribl Search

14.5.4.2. AVGIF

The `avgif` aggregation function calculates the average of **Expression** across the group where **Predicate** evaluates to `true`.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
avgif( Expression, Predicate )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Records with `null` values are ignored and not included in the calculation. Wildcards are not supported for field names.
- **Predicate**: Predicate that if `true`, the **Expression** calculated value will be added to the average.

Results

Returns the average value of **Expression** across the group where Predicate evaluates to `true`.

Examples

This example returns average byte count from source address `10.0.0.164`:

```
dataset="cribl_search_sample"
| limit 1000
| summarize AverageSessionBytesForSrcAddr=avgif(bytes, srcaddr=="10.0.0.164")
```

Copy Run in Cribl Search

This example returns average byte count by private source address:

```
dataset="cribl_search_sample"
| limit 1000
| summarize AverageSessionBytesForPrivateAddr=avgif(bytes, ipv4_is_private(srcaddr))
```

Copy Run in Cribl Search

14.5.4.3. Count

The `count` aggregation function counts the number of non-null events per summarization group, or the total number of non-null events if summarization is done without grouping.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.



If you need to count boolean `true` values, use the `countif` aggregation function.

Syntax

```
count( [Expression] )
```

Copy

Arguments

- **Expression**: Optional. Expression used for aggregation calculation. Wildcards are not supported for field names.

Results

Returns a count of the events per summarization group (or in total, if summarization is done without grouping).

Example

This example summarizes the number of non-null events by source address:

```
dataset="cribl_search_sample"
| limit 1000
| summarize NumberOfEvents=count() by srcaddr
```

Copy Run in Cribl Search

14.5.4.4. COUNTIF

The `countif` aggregation function counts events based on a predicate.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.



If you need to count non-null values regardless of truthiness, use the `count` aggregation function.

Syntax

```
countif( Predicate )
```

Copy

Arguments

- **Predicate**: An expression used for aggregation calculation. Use any scalar expression that returns a `bool` value. Wildcards are not supported for field names.

Results

Returns a count of rows for which **Predicate** evaluates to `true`.

Examples

This example summarizes byte counts (with a minimum value of 11), by source address:

```
dataset="cribl_search_sample" dataSource="vpcflowlogs"
| summarize gtthan10Count=countif(bytes > 10) by srcaddr
```

Copy Run in Cribl Search

14.5.4.5. DCOUNT

The `dcount` aggregation function calculates an estimate of the number of distinct values that are taken by an expression in the summary group.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

> The `dcount()` aggregation function is primarily useful for estimating the cardinality of huge sets. It trades performance for accuracy, and might return a result that varies between executions. The order of inputs might have an effect on its output.

Syntax

```
dcount( Expression[, Accuracy] )
```

Copy

Arguments

- **Expression**: A scalar expression whose distinct values are to be counted. Wildcards are not supported for field names.
- **Accuracy**: Optional. An integer that defines the requested estimation accuracy. If unspecified, the default value is `1`.

Results

Returns an estimate of the number of distinct values of **Expression** in the group.

`dcount` doesn't count `null` toward the total. If every value in the group is `null`, `dcount` returns `0`.

Example

This example summarizes the estimated cardinality of destination ports by destination address:

```
dataset="cribl_search_sample"
| summarize distinctCountPorts=dcount(dstport) by dstaddr
```

Copy Run in Cribl Search

Estimation Accuracy

This function uses a variant of the HyperLogLog (HLL) algorithm, which does a stochastic estimation of set cardinality. The algorithm provides a knob that can be used to balance accuracy and execution time per memory size:

Accuracy	Error (%)	Entry count
0	1.6	212
1	0.8	214
2	0.4	216
3	0.28	217
4	0.2	218


The **Entry count** column is the number of 1-byte counters in the HLL implementation.

The algorithm includes some provisions for doing a perfect count (zero error), if the set cardinality is small enough:

- When the accuracy level is `1` - 1,000 values are returned
- When the accuracy level is `2` - 8,000 values are returned

The error bound is probabilistic, not a theoretical bound. The value is the standard deviation of error distribution (the sigma), and 99.7% of the estimations will have a relative error of under 3 x sigma.

The following image shows the probability distribution function of the relative estimation error, in percentages, for all supported accuracy settings:



14.5.4.6. DCOUNTIF

The `dcountif` aggregation function calculates an estimate of the number of distinct values of **Expression** of rows for which **Predicate** evaluates to `true`.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
dcountif( Expression, Predicate, [, Accuracy] )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Use any scalar expression that returns a `bool` value. Wildcards are not supported for field names.
- **Predicate**: Expression used to filter rows.
- **Accuracy**: Optional. An integer that defines the requested estimation accuracy. If unspecified, the default value is `1`.

Results

Returns an estimate of the number of distinct values of **Expression** of rows for which **Predicate** evaluates to `true` in the group.

`dcountif` doesn't count `null` toward the total. If every matching value in the group is `null`, `dcountif` returns `0`.

`dcountif` could return an error in cases where all or none of the rows pass the **Predicate** expression.

Example

This example summarizes the estimated cardinality of destination ports 80 and 443, by destination address:

```
dataset="cribl_search_sample"
| summarize distinctCountWebPorts=dcountif(dstport, dstport in (80,443)) by dstaddr
```

Copy Run in Cribl Search

Estimation Accuracy

This function uses a variant of the HyperLogLog (HLL) algorithm, which does a stochastic estimation of set cardinality. The algorithm provides a knob that can be used to balance accuracy and execution time per memory size:

Accuracy	Error (%)	Entry count
0	1.6	212
1	0.8	214
2	0.4	216
3	0.28	217
4	0.2	218


The **Entry count** column is the number of 1-byte counters in the HLL implementation.

The algorithm includes some provisions for doing a perfect count (zero error), if the set cardinality is small enough:

- When the accuracy level is `1` - 1,000 values are returned
- When the accuracy level is `2` - 8,000 values are returned

The error bound is probabilistic, not a theoretical bound. The value is the standard deviation of error distribution (the sigma), and 99.7% of the estimations will have a relative error of under 3 x sigma.

The following image shows the probability distribution function of the relative estimation error, in percentages, for all supported accuracy settings:



14.5.4.7. Max

The `max` aggregation function finds the maximum value across the group.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
max( Expression )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.

Results

Returns the maximum value of **Expression** across the group.

Numeric values are considered before alpha or alphanumeric values.

Example

This example summarizes the maximum traffic, in bytes, for each source address:

```
dataset="cribl_search_sample" dataSource="vpcflowlogs"
| summarize maxBytes=max(bytes) by srcaddr
```

Copy Run in Cribl Search

14.5.4.8. Maxif

The `maxif` aggregation function calculates the maximum value across the group for which **Predicate** evaluates to `true`.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
maxif( Expression, Predicate )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.
- **Predicate**: Expression that will be used to filter rows.

Results

Returns the maximum value of **Expression** across the group for which **Predicate** evaluates to `true`.

Numeric values are considered before alpha or alphanumeric values.

Example

This example returns the maximum byte count for source address `10.0.0.33`:

```
dataset="cribl_search_sample"
| limit 1000
| summarize maxif(bytes,srcaddr=="10.0.0.33")
```

Copy Run in Cribl Search

14.5.4.9. Min

The `min` aggregation function finds the minimum value across the group.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
min( Expression )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.

Results

Returns the minimum value of **Expression** across the group.

Numeric values are considered before alpha or alphanumeric values.

Example

This example summarizes the minimum traffic, in bytes, for each source port:

```
dataset="cribl_search_sample"
| limit 1000
| summarize min(bytes) by srcport
```

Copy Run in Cribl Search

14.5.4.10. Minif

The `minif` aggregation function calculates the minimum value across the group for which **Predicate** evaluates to `true`.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
minif( Expression, Predicate )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.
- **Predicate**: Expression that will be used to filter rows.

Results

Returns the minimum value of **Expression** across the group for which **Predicate** evaluates to `true`.

Numeric values are considered before alpha or alphanumeric values.

Examples

This example returns the minimum byte count for source address `10.0.0.33`:

```
dataset="cribl_search_sample" | limit 1000 | summarize minif(bytes,srcaddr=="10.0.0.3
```

Copy Run in Cribl Search

This example summarizes minimum byte counts by private source address:

```
dataset="cribl_search_sample"
| limit 1000
| summarize minif(bytes, ipv4_is_private(srcaddr)) by srcaddr
```

Copy Run in Cribl Search

14.5.4.11. Percentile

The `percentile` aggregation function returns an estimate for the specified nearest-rank percentile of the population defined by **Expression**. The accuracy depends on the density of population in the region of the percentile. The percentiles aggregate provides an approximate value using T-Digest.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
percentile( Expression, Percentile )
```

Copy

Arguments

- **Expression**: Expression that will be used for aggregation calculation. Does not support wildcards for field names.
- **Percentile**: A double constant that specifies the percentile.

Results

Returns an estimate for **Expression** of the specified percentiles in the group.

Examples

This example summarizes 95th-percentile traffic, in bytes, by source address, excluding low values:

```
dataset="cribl_search_sample" dataSource="vpcflowlogs"
| summarize perc95=percentile(bytes, 95) by srcaddr
| where perc95 > 100
```

Copy Run in Cribl Search

This example summarizes 95th-percentile traffic, in bytes, by destination address, excluding `null` values:

```
dataset="cribl_search_sample" datatype="aws_vpcflow"
| where isnotnull(bytes) and isnotnull(dstaddr)
| summarize p95=percentile(bytes, 95) by dstaddr
```

Copy Run in Cribl Search

14.5.4.12. Stdev

The `stdev` aggregation function calculates the standard deviation of **Expression** across the group, using Bessel's correction for a small data set that is considered a sample.

For a large data set that is representative of the population, use the stdevp aggregation function.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Used formula:

$$\sqrt{\frac{1}{n-1} \times \sum (X - \frac{\sum (X)}{n})^2}$$

stdev formula

Syntax

```
stdev( Expression )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.

Results

The standard deviation value of **Expression** across the group.

Example

This example summarizes average traffic in bytes, and two measures of standard deviation (sample- and population-based), by source address:

```
dataset="cribl_search_sample" dataSource="vpcflowlogs"
| summarize avg(bytes), stdev(bytes), stdevp(bytes) by srcaddr
```

Copy Run in Cribl Search

14.5.4.13. STDEVIF

The `stdevif` aggregation function calculates the stdev of **Expression** across the group for which **Predicate** evaluates to `true`.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
stdevif( Expression, Predicate )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.
- **Predicate**: When `true`, the **Expression** calculated value will be added to the standard deviation.

Results

Returns the standard deviation of **Expression** across the group for which **Predicate** evaluates to `true`.

Example

This example summarizes standard deviations in byte count, by source address, for events whose destination port is higher than `1024`:

```
dataset="cribl_search_sample" dataSource="vpcflowlogs"
| summarize stdevif(bytes, dstport>1024) by srcaddr
```

Copy Run in Cribl Search

14.5.4.14. STDEVP

The `stdevp` aggregation function calculates the standard deviation of **Expression** across the group, considering the group as a population for a large data set that is representative of the population.

For a small data set that is a sample, use the stdev aggregation function.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Used formula:

$$\sqrt{\frac{1}{N} \times \sum (X - \frac{\sum (X)}{N})^2}$$

stdevp formula

Syntax

```
stdevp( Expression )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.

Results

The standard deviation value of **Expression** across the group.

Example

This example summarizes average traffic in bytes, and two measures of standard deviation (sample- and population-based), by source address:

```
dataset="cribl_search_sample" dataSource="vpcflowlogs"
| summarize avg(bytes), stdev(bytes), stdevp(bytes) by srcaddr
```

14.5.4.15. Sum

The `sum` aggregation function calculates the sum of **Expression** across the group.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
sum( Expression )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.

Results

Returns the sum value of **Expression** across the group.

Example

This example sums up the total number of packets sent to each combination of destination address and destination port:

```
dataset="cribl_search_sample"
| summarize totalPackets=sum(packets) by dstaddr,dstport
```

Copy Run in Cribl Search

14.5.4.16. SUMIF

The `sumif` aggregation function calculates the sum of **Expression** for which **Predicate** evaluates to `true`.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
sumif( Expression, Predicate )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.
- **Predicate**: Expression that will be used to filter rows.

Results

Returns the sum of **Expression** across the group for which **Predicate** evaluates to `true`.

Examples

This example sums up the number of packets sent to destination address `10.8.20.30` through each destination port:

```
dataset="cribl_search_sample"
| summarize packetsToBob=sumif(packets, dstaddr=="10.8.20.30") by dstport
```

Copy Run in Cribl Search

14.5.4.17. TAKE_ANY

The `take_any` aggregation function returns an arbitrary non-`null` value of **Expression** from each group. Results are non-deterministic.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
take_any( Expression )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.

Usage

Use `take_any` when you need a sample value from each group and event order does not matter.

When sort order matters, sort events with `sort` or `order` and use `findfirst` or `findlast` instead.

String literals are valid expressions and return the literal value.

Wildcard and multi-column forms, such as `take_any(*)`, are not supported.

Column paths

You can reference nested fields with dot notation:

```
dataset=myDataset
| summarize take_any(my_field.my_value)
```

Copy

Bracket notation treats the value as a string literal, not a nested field path:

```
dataset=myDataset
| summarize take_any(["my_field.my_value"])
```

Copy

Examples

This example returns an arbitrary request method for each source port:

```
dataset="cribl_search_sample" dataSource=access*
| limit 1000
| summarize take_any(request_method) by srcport
```

Copy Run in Cribl Search

14.5.4.18. TAKE_ANYIF

The `take_anyif` aggregation function returns an arbitrary non-`null` value of **Expression** from rows where **Predicate** evaluates to `true`. Results are non-deterministic.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
take_anyif( Expression, Predicate )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.
- **Predicate**: Expression that will be used to filter rows.

Usage

Use `take_anyif` when you need a sample value from each group for rows that match a condition and event order does not matter.

When sort order matters, sort events with `sort` or `order` and use `findfirstif` or `findlastif` instead.

If **Predicate** is `null`, it evaluates to `false`.

Wildcard and multi-column forms are not supported.

Example

This example returns an arbitrary status code of 400 or higher for each host:

```
dataset=myDataset
| summarize take_anyif(status, status >= 400) by host
```

Copy

14.5.4.19. VARIANCE

The `variance` aggregation function calculates the variance of **Expression** across the group, considering the group as a sample.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Used formula:

$$\frac{1}{n-1} \times \sum (X - \frac{\sum(X)}{n})^2$$

variance formula

Syntax

```
variance( Expression )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.

Results

The variance value of **Expression** across the group.

Example

This example summarizes the average byte count, and corresponding variance, by source address:

```
dataset="cribl_search_sample" dataSource="vpcflowlogs"
| summarize avg(bytes), variance(bytes) by srcaddr
```

Copy Run in Cribl Search

14.5.4.20. VARIANCEIF

The `varianceif` aggregation function calculates the variance of **Expression** for which **Predicate** evaluates to `true`.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Syntax

```
varianceif( Expression, Predicate )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.
- **Predicate**: Predicate that if `true`, the **Expression** calculated value will be added to the variance.

Results

Returns the variance value of **Expression** across the group for which **Predicate** evaluates to `true`.

Example

This example summarizes the variance in byte count, by source address, for events whose destinatino port is higher than `1024`:

```
dataset="cribl_search_sample" dataSource="vpcflowlogs"
| summarize varianceif(bytes, dstport>1024) by srcaddr
```

Copy Run in Cribl Search

14.5.4.21. VARIANCEP

The `variancep` aggregation function calculates the variance of **Expression** across the group, considering the group as a population.

Use this function with the `summarize`, `eventstats`, and `timestats` operators.

Used formula:

$$\frac{1}{N} \times \sum (X - \frac{\sum (X)}{N})^2$$

variancep formula

Syntax

```
variancep( Expression )
```

Copy

Arguments

- **Expression**: Expression used for aggregation calculation. Wildcards are not supported for field names.

Results

The variance value of **Expression** across the group.

Example

```
dataset=myDataset
| summarize variancep(x)
```

Copy

14.5.5. Window Functions

Window functions operate on multiple rows (events) in a row set at a time. Unlike aggregation functions, window functions require that the rows in the row set be ordered or sorted.

Cribl Search supports window functions on queries that use the `extend` operator. With this combination, Cribl Search implicitly applies the `centralize` operator. Cribl Search does not support window functions on queries with the `project` or `where` operator.

The following window functions are available:

Name	Description
`next`	Returns the value of a specific field in a subsequent row.
`prev`	Returns the value of a specific field in a previous row.
`row_cumsum`	Calculates the cumulative sum for a specified field across all previous rows.
`row_number`	Assigns a unique row number to each row within the results.
`row_rank_dense`	Assigns a unique numerical position (rank) to each row within the results
`row_rank_min`	Assigns a minimal numerical position (rank) to each row within the results
`row_window_session`	Identifies the value at the beginning of each session for a specified field within the results.

14.5.5.1. Next

The `next` function returns the value of a specific field in a subsequent row. The subsequent row is located at a specified offset relative to the current row within the results.

Syntax

```
next(Field [, Offset ] [, DefaultValue ] )
```

Copy

Arguments

- **Field**: The field from which to get the values.
- **Offset**: The number of rows to move from the current row. Default is `1`.
- **DefaultValue**: The default value when there's no value in the later row. The default is `null`.

Scope

Cribl Search supports this function in the `extend` operator, but not in the `project` or `where` operator.

Examples

This example returns the time difference between adjacent events.

```
dataset="cribl_search_sample" dataSource="access*" host="web01.cribl.io"
 | limit 100
 | sort by _time asc
 | extend time_next_delta = next(_time) - (_time)
```

Copy Run in Cribl Search

This example filters for events with a time difference greater than 250 ms:

```
dataset=myDataset
| where SensorName == 'sensor-9'
| sort by Timestamp asc
| extend timeDiffInMilliseconds = datetime_diff('millisecond', next(Timestamp, 1), Ti
| where timeDiffInMilliseconds > 250
```

14.5.5.2. Prev

The `prev` function returns the value of a specific field in a previous row. The previous row is located at a specified offset relative to the current row within the results.

Syntax

```
prev(Field [, Offset ] [, DefaultValue ] )
```

Copy

Arguments

- **Field**: The field from which to get the values.
- **Offset**: The offset to go back in rows. The default is `1`.
- **DefaultValue**: The default value to be used when there are no previous rows from which to take the value. The default is `null`.

Scope

Cribl Search supports this function in the `extend` operator, but not in the `project` or `where` operator.

Examples

This example returns the time difference between adjacent events.

```
dataset="cribl_search_sample" dataSource="access*" host="web01.cribl.io"
 | limit 100
 | sort by _time asc
 | extend time_prev_delta = (_time) - prev(_time)
```

Copy Run in Cribl Search

This example filters for events with a time difference greater than 250 ms:

```
dataset=myDataset
| where SensorName == 'sensor-9'
| sort by Timestamp asc
| extend timeDiffInMilliseconds = datetime_diff('millisecond', Timestamp, prev(Timest
| where timeDiffInMilliseconds > 250
```

Copy

14.5.5.3. Row_cumsum

The `row_cumsum` function calculates the cumulative sum for a specified field across all previous rows.

Syntax

```
row_cumsum(Term [, Restart ] )
```

Copy

Arguments

- **Term**: An expression that indicates the value to be summed. Supports `int`, `long`, or `real`.
- **Restart**: An expression that returns a `bool` value to indicate when the accumulation operation should restart or be set back to 0. It can be used to indicate partitions in the data.

Scope

Cribl Search supports this function in the `extend` operator, but not in the `project` or `where` operator.

Examples

This first example returns total bytes per a specified host.

```
ddataset="cribl_search_sample" dataSource="access*" host="web01.cribl.io"
 | limit 100
 | sort by _time asc
 | extend total_bytes=row_cumsum(bytes)
 | project _time, bytes, total_bytes
```

Copy | Run in Cribl Search

This second example returns total bytes per a specified host, restarting the count when the `clientip` is identical in adjacent rows.

```
dataset="cribl_search_sample" dataSource="access*" host="web01.cribl.io"
 | limit 100
 | sort by _time asc
 | extend total_bytes_from_client=row_cumsum(bytes, clientip!=prev(clientip))
 | project _time, clientip, bytes, total_bytes_from_client
```

Copy Run in Cribl Search

14.5.5.4. ROW_NUMBER

The `row_number` function assigns a unique row number to each row within the results. The row index starts by default at 1 for the first row, and is incremented by 1 for each additional row. Optionally, the row index can start at a different value than 1.

Syntax

```
row_number(StartingIndex [, Restart ] )
```

Copy

Arguments

- **StartingIndex**: The value of the row index to start at or restart to. The default value is `1`. Supports `long`.
- **Restart**: An expression that returns a `bool` value to indicate when the numbering operation should restart to the **StartingIndex** value. The default is `false`.

Scope

Cribl Search supports this function in the `extend` operator, but not in the `project` or `where` operator.

Example

This example restarts the cumulative counter each time it encounters identical `clientip` values on adjacent rows.

```
dataset="cribl_search_sample" dataSource="access*" host="web01.cribl.io"
 | limit 100
 | sort by _time asc
 | extend rownum=row_number(0, clientip!=prev(clientip))
 | project _time, clientip, bytes, rownum
```

Copy Run in Cribl Search

14.5.5.5. ROW_RANK_DENSE

The `row_rank_dense` function assigns a unique numerical position (rank) to each row within the results, preserving the order even for rows with equal values. Unlike regular ranking, there are no gaps in the assigned ranks.

The row rank starts by default at 1 for the first row, and is incremented by 1 whenever the provided **Term** is different than the previous row's **Term**.

Syntax

```
row_rank_dense( Term [, Restart ] )
```

Copy

Arguments

- **Term**: An expression that indicates the value to consider for the rank. The rank is increased whenever the **Term** changes.
- **Restart**: An expression that returns a `bool` value to indicate when the ranking operation should restart to the **Term** value. The default is `false`.

Scope

Cribl Search supports this function in the `extend` operator, but not in the `project` or `where` operator.

Examples

This example uses `row_rank_dense` to return a count of distinct hosts, and also uses `row_rank_min` to rank the hosts.

```
dataset="cribl_search_sample" dataSource="access*"
 | limit 100
 | sort by host asc
 | extend row_rank_dense=row_rank_dense(host) // incremented from 1
 | extend row_rank_min=row_rank_min(host) // actual row number (starting from row 1)
 | project _time, host, row_rank_dense, row_rank_min
```

Copy Run in Cribl Search

This snippet partitions data by `appname`:

```
| extend Rank=row_rank_dense(appname, prev(appname) != appname)
```

Copy

14.5.5.6. ROW_RANK_MIN

The `row_rank_min` function assigns a minimal numerical position (rank) to each row within the results, considering rows with equal values to have the same rank.

The rank is the minimal row number that the current row's **Term** appears in.

Syntax

```
row_rank_min( Term [, Restart ] )
```

Copy

Arguments

- **Term**: An expression that indicates the value to consider for the rank. The rank is the minimal row number for **Term**.
- **Restart**: An expression that returns a `bool` value to indicate when the ranking operation should restart to the **Term** value. The default is `false`.

Scope

Cribl Search supports this function in the `extend` operator, but not in the `project` or `where` operator.

Examples

This example uses `[row_rank_min]` to return a ranking of hosts, and also uses `row_rank_dense` to count distinct hosts.

```
dataset="cribl_search_sample" dataSource="access*"
 | limit 100
 | sort by host asc
 | extend row_rank_dense=row_rank_dense(host) // incremented from 1
 | extend row_rank_min=row_rank_min(host) // actual row number (starting from row 1)
 | project _time, host, row_rank_dense, row_rank_min
```

Copy Run in Cribl Search

This snippet partitions data by `appname`:

```
| extend Rank=row_rank_min(appname, prev(appname) != appname)
```

Copy

14.5.5.7. ROW_WINDOW_SESSION

The `row_window_session` function identifies the value at the beginning of each session for a specified field within the results.

The function has the following conceptual calculation model:

1. Goes over the input sequence of **Expr** values in order.
2. For every value, determines if it establishes a new session.
3. If it establishes a new session, it emits the value of **Expr**. Otherwise, emits the previous value of **Expr**.

Syntax

```
row_window_session( Expr , MaxDistanceFromFirst , MaxDistanceBetweenNeighbors [, Rest
```

Copy

Arguments

- **Expr**: An expression whose values are grouped together in sessions. Null values produce null values, and the next value starts a new session. **Expr** must be a scalar expression of type `datetime`.
- **MaxDistanceFromFirst**: Establishes one criterion for starting a new session: The maximum distance between the current value of **Expr** and the value of **Expr** at the beginning of the session. It's a scalar constant of type `timespan`.
- **MaxDistanceBetweenNeighbors**: Establishes a second criterion for starting a new session: The maximum distance from one value of **Expr** to the next. It's a scalar constant of type `timespan`.
- **Restart**: An expression that returns a `bool` value to indicate when the operation should restart. If specified, every value that evaluates to `true` will immediately restart the session.

Scope

Cribl Search supports this function in the `extend` operator, but not in the `project` or `where` operator.

Example

```
| sort by ID asc, Timestamp asc
| extend SessionStarted = row_window_session(Timestamp, 1h, 5m, ID != prev(ID))
```

Copy

14.6. Virtual Tables

Use virtual tables to dynamically generate system information useful for troubleshooting, performance analysis, and testing.

Available Virtual Tables

Name	Description
`$vt_datasets`	Lists available Datasets. Useful for finding Datasets of a specific type or with specific name patterns.
`$vt_dataset_providers`	Lists available Dataset Providers. Useful for a quick overview of your Dataset Providers.
`$vt_dummy`	Generates dummy data. Useful for testing your queries.
`$vt_jobs`	Lists previously run searches. Useful for troubleshooting or performance analysis.
`$vt_list`	Lists available virtual tables. Useful for looking up the names and descriptions of other virtual tables.
`$vt_lookups`	Lists available lookups, or gets the contents of a specific lookup. Useful for searching through your lookup files.
`$vt_results`	Loads the results of one or more previous searches, so you can reuse them.

14.6.1. $VT_DATASETS

The `$vt_datasets` virtual table lists available Datasets.

```
// returns a list of all Datasets available to the current user
dataset="$vt_datasets"
```

Copy | Run in Cribl Search

Purpose

Use `$vt_datasets` to quickly find Datasets of a specific type or with specific name patterns.

Permissions

Search Member Type	Permissions
Admin	Can see all Datasets in their Organization.
Editor	Can see only those Datasets that they created themselves or that were shared with them.
User	Can see only those Datasets that were shared with them.

Syntax

```
dataset="$vt_datasets"
```

Copy | Run in Cribl Search

Returns

Returns one event for each available Dataset. Each event contains the following fields:

Field	Description
`id`	The Dataset ID.
`description`	The Dataset description.

Field	Description
`provider`	The `id`, `description`, and `type` of the Dataset Provider.

Examples

List all your S3 Datasets.

```
dataset="$vt_datasets"
  | where provider.type == "s3"
```

Copy Run in Cribl Search

Count the number of Datasets of each type.

```
dataset="$vt_datasets"
  | summarize count() by provider.type
```

Copy Run in Cribl Search

14.6.2. $VT_DATASET_PROVIDERS

The `$vt_dataset_providers` virtual table lists available Dataset Providers.

```
// returns a list of all Dataset Providers available to the current user
dataset="$vt_dataset_providers"
```

Copy | Run in Cribl Search

Purpose

Use `$vt_dataset_providers` for a quick overview of your Dataset Providers.

Permissions

Search Member Type	Permissions
Admin	Can see all Dataset Providers in their Organization.
Editor	Can see only those Dataset Providers that they created themselves or that were shared with them.
User	Can see only those Dataset Providers that were shared with them.

Syntax

```
dataset="$vt_dataset_providers"
```

Copy | Run in Cribl Search

Returns

Returns one event for each available Dataset Provider. Each event contains the following fields:

Field	Description
`id`	The ID of the Dataset Provider.
`description`	The description of the Dataset Provider.

Field	Description
`type`	The type of the Dataset Provider. For example, `cribl_edge`.

Examples

List all your S3 Dataset Providers.

```
dataset="$vt_dataset_providers"
  | where type == "s3"
```

Copy Run in Cribl Search

List all built-in Dataset Providers.

```
dataset="$vt_dataset_providers"
  | where type startswith "cribl"
```

Copy Run in Cribl Search

14.6.3. $VT_DUMMY

The `$vt_dummy` virtual table generates dummy events.

```
// returns 10 dummy events
dataset="$vt_dummy" event<10
```

Copy | Run in Cribl Search

Purpose

Use `$vt_dummy` to test your queries with dummy data.

The `event` predicate lets you specify the number of events, and the `second` predicate lets you simulate a long-running query. Using both lets you simulate a burst of events over a specific time range.

Permissions

All types of Search Members can use the `$vt_dummy` virtual table.

Syntax

```
dataset="$vt_dummy" event<5 second<3
```

Copy

Parameters

Name	Type	Required	Description
`NumberOfEvents`	`int`	No	The number of events to generate. If used together with `SearchRuntime`, generates the `NumberOfEvents` per second, over the course of the `SearchRuntime`. If not specified, generates one event.
`SearchRuntime`	`int`	No	The desired runtime of the simulated search, in seconds.

Returns

Returns dummy events according to the specified criteria. Each event contains the following fields:

Field	Description
`_time`	The event's timestamp.
`event`	The event's ordinal number.

Examples

Generate one dummy event, with an additional field `foo` set to `42`.

```
dataset="$vt_dummy"
  | extend foo=42
```

Copy Run in Cribl Search

Generate five dummy events.

```
dataset="$vt_dummy" event<5
```

Copy Run in Cribl Search

Generate one event per second, over the course of 10 seconds.

```
dataset="$vt_dummy" second<10
```

Copy Run in Cribl Search

Generate three events per second, over the course of 10 seconds.

```
dataset="$vt_dummy" event<3 and second<10
```

Copy Run in Cribl Search

14.6.4. $Vt_jobs

The `$vt_jobs` virtual table lists previously executed searches.

```
// returns a list of all searches that were run within the past hour and are availabl
dataset="$vt_jobs" earliest=-1h
```

Copy | Run in Cribl Search

Purpose

Use `$vt_jobs` for troubleshooting or performance analysis, or to monitor search activity in your Organization.

Permissions

Search Member Type	Permissions
Admin	Can see all searches in their Organization.
Editor or User	Can see only those searches that they ran themselves or that were shared with them.

Syntax

```
dataset="$vt_jobs"
```

Copy

Returns

Returns one event for every search run within the specified time range, filtered through any additional criteria you specify.

Each event contains fields with the search's details.

Examples

Aggregate searches from the past seven days by their status.

```
dataset="$vt_jobs" earliest=-7d
  | summarize count() by status
```

Copy Run in Cribl Search

14.6.5. $VT_LIST

The `$vt_list` virtual table lists available virtual tables.

```
// returns a list of all virtual tables available to the current user
dataset="$vt_list"
```

Copy | Run in Cribl Search

Purpose

Use `$vt_list` to quickly look up the names and descriptions of virtual tables available in Cribl Search.

Permissions

All types of Search Members can see the list of all virtual tables.

Syntax

```
dataset="$vt_list"
```

Copy

Returns

Returns one event for each of Cribl Search's virtual tables, containing the table's name and description.

Examples

List virtual tables whose names start with `$vt_object`.

```
dataset="$vt_list"
  | where name startswith "$vt_object"
```

Copy | Run in Cribl Search

14.6.6. $VT_LOOKUPS

The `$vt_lookups` virtual table lists available lookups, or gets the contents of a specific lookup.

```
// returns the contents of the service_names_port_numbers.csv lookup file
dataset="$vt_lookups" lookupFile="service_names_port_numbers"
```

Copy | Run in Cribl Search

Purpose

Use `$vt_lookups` to:

- Get a quick overview of all lookup files available to you.
- Search the contents of a specific lookup.

Permissions

All types of Search Members can see the list of all lookup files in the organization. For details about who can export to `$vt_lookups`, see Search Member Permissions.

Syntax

```
dataset="$vt_lookups"
  // optionally, get the contents of a specific lookup file:
  lookupFile="LookupName"
```

Copy

Parameters

Name	Type	Description
`LookupName`	`string`	The name of the lookup file whose content you want to access. Don't include the file extension.

Returns

Returns one event for each available lookup. Each event contains the following fields:

Field	Description
`name`	The name of the lookup.
`description`	The description of the lookup.
`rowCount`	The number of rows in the lookup.
`size`	The size of the lookup file, in bytes.
`compressed`	`true`: the lookup file is compressed. `false`: the lookup file is not compressed.

Examples

List all lookups available to the current user.

```
dataset="$vt_lookups"
```

Copy Run in Cribl Search

List available lookups that have more than 10,000 rows.

```
dataset="$vt_lookups"
  | where rowCount>10000
```

Copy Run in Cribl Search

Get only specific entries of the `service_names_port_numbers.csv` lookup file.

```
dataset="$vt_lookups" lookupFile="service_names_port_numbers"
 | where transport == "udp"
```

Copy Run in Cribl Search

14.6.7. $VT_RESULTS

The `$vt_results` virtual table retrieves the result sets of searches completed (or attempted) in the past.

```
// get the results of the search 1704236905683.wgocax, if available to the current us
dataset="$vt_results" jobId="1704236905683.wgocax"
```

Copy | Run in Cribl Search

Purpose

Use `$vt_results` to access the results of previously executed searches without having to rerun them. This can be particularly useful for iterative analysis or when you want to reference the results of multiple searches in a single query.

Mind that although `$vt_results` doesn't rerun the actual query, it **searches** the results of the specified searches, which can lead to minor credit consumption. This is different than opening a search from **History**, which only loads the cached results.

> Search Admins, Organization Admins, and Organization Owners can view the results of all searches in the Organization, for as long as they're kept in the history. Mind that results from the `decrypt` function are stored as decrypted plaintext. To reduce the visibility, consider adjusting the **Search history TTL** limit.

Permissions and Limits

Search Member Type	Permissions
Admin	Can access the results of all searches in the Organization.
Editor or User	Can access the results of only those searches that they ran themselves or that were shared with them.

You can access previous search results for as long as they're kept in the system. By default it's 7 days, but you can change this in **Settings** > **Search** > ****Limits** > **Search history TTL**.

`$vt_results` cannot access the results of searches that are still running.

Allow Incomplete Results in `$vt_results`

By default, `$vt_results` can access only the results of successfully completed searches. However, you precede this Dataset with the `set` statement's `allow_incomplete_results` option to also access the results of failed or canceled searches. This option is `false` by default. Set it to `true` using syntax like this:

```
set allow_incomplete_results=true;
dataset="$vt_results" jobId=<some-ID>
```

Copy

Syntax

```
dataset="$vt_results"
  // either:
  jobId="SearchId"
  // or:
  jobName="SavedSearchName" [execution > -NumberOfPreviousRuns]
```

Copy

Parameters

Name	Type	Description
`SearchId`	`string`	The ID of the search whose results you want to access. You can find the ID of every search in its **Details**, or in **History**. For multiple IDs, use square brackets and commas: `jobId=["SearchId1", "SearchId2"]`.
`SavedSearchName`	`string`	The **name** (not ID) of the saved search whose results you want to access. By default, you'll get the results of the latest execution that saved search, unless you use the `execution` parameter. For multiple names, use square brackets and commas, for example: `jobName=["SavedSearchName1", "SavedSearchName2"]`.

`NumberOfPreviousRuns`	`int`
	
	or
	
	`*`
		Which of the past executions of the saved search to load. If not specified, only the latest run is loaded.
		
		`execution = 0` (default) loads the last run.
		`execution = -1` loads the run before last.
		`execution > -1` loads the last two runs together.
		`execution > -2` loads the last three runs together.

Name	Type	Description
		`execution = *` loads all runs kept in history. Works only with the `SavedSearchName` specified.

Returns

Returns the results of the specified searches, in their original format.

Examples

Get the Results of Multiple Previous Searches

Get the results of all completed searches whose IDs are between `1704236905600` and `1704236906000`.

```
dataset="$vt_results"
  | where jobId>"1704236905600" and jobId<"1704236906000"
```

Copy Run in Cribl Search

Get the Results of a Previous Run of a Saved Search

Get the results of the last run of a saved search named `mySavedSearch`.

```
dataset="$vt_results" jobName="mySavedSearch" execution = 0

// or simply:

dataset="$vt_results" jobName="mySavedSearch"
```

Copy Run in Cribl Search

Get the run before last:

```
dataset="$vt_results" jobName="mySavedSearch" execution = -1
```

Copy Run in Cribl Search

Get the Results of Multiple Previous Runs of a Saved Search

Get the results of the last two executions of a saved search named `mySavedSearch`.

```
dataset="$vt_results" jobName="mySavedSearch" execution > -1
```

Copy | Run in Cribl Search

Get the last three runs:

```
dataset="$vt_results" jobName="mySavedSearch" execution > -2
```

Copy | Run in Cribl Search

14.7. Types

Supported types of data in Cribl Search.

Every data value (such as the value of an expression, or the parameter to a function) has a **type**.

The following table lists the types supported by Cribl Search, alongside additional aliases you can use to refer to them.

Type	Aliases
`bool`	`boolean`
`datetime`	`date`
`double`	`real`, `decimal`
`dynamic`	
`int`	`long`
`string`	
`timespan`	`time`

All types include the special `null` value, which represents the lack of data or a mismatch of data. For example, attempting to ingest the string `"abc"` into an `int` column results in `null`.

Unsupported types

The following table shows the types unsupported by Cribl Search:

Type	Alias
`float`	
`int16`	
`uint16`	
`uint32`	`uint`
`uint64`	`ulong`
`uint8`	`byte`

14.7.1. Bool

The `bool` data type can have one of two states: `true` or `false`, as well as the `null` value.

Alias: `boolean`.

`bool` Definition

A value is considered `true` in any of the following cases:

- If it's the actual `bool` value `true`.
- If it's one of the following case-insensitive strings: `'true'`, `'t'`, `'yes'`, `'y'`.
- If it's a numeric value equal to `1` (including `1.0`).

A value is considered `false` in any of the following cases:

- If it's the actual `bool` value `false`.
- If it's one of the following case-insensitive strings: `'false'`, `'f'`, `'no'`, `'n'`.
- If it's a numeric value equal to `0` (including `0.0`).

Any values that couldn't be converted to `bool` are considered `null`.

Comparing `bool` to Numbers

When comparing `bool` values to numbers, only `1` is considered `true`. For example:

Expression	Result
`true == 1`	`true`
`true == 100`	`false`

However, when converting a value to a `bool`, all non-zero numbers are converted to `true`:

Expression	Result
`tobool(100)`	`true`
`bool(-1)`	`true`
`iff(100, 1, 0)`	`1`

Expression	Result
`not(100)`	`false`

`bool` as a Filter

To search for any values that are considered `true`, filter on the literal `true` value:

- `dataset="foo" something=true`
- `dataset="foo" | where something==true`

These will match on:

- Booleans with value `true`.
- The following case-insensitive strings: `'true'`, `'t'`, `'yes'`, `'y'`.
- Numeric values equal to `1`.

To search for any values that are considered `false`, filter on the literal `false` value:

- `dataset="foo" something=false`
- `dataset="foo" | where something==false`

These will match on:

- Booleans with value `false`.
- The following case-insensitive strings: `'false'`, `'f'`, `'no'`, `'n'`.
- Numeric values equal to `0`.

Note that searching on `"true"` or `"false"` literals with quotes does a string match instead. This means that:

```
dataset="foo" | where something=="true"
```

Will match on `"true"` and `true`, but not on `1`, `"yes"` or any other `bool` values.

`bool` as Function Input

For any functions that take `bool` arguments, the values will be automatically converted to `true`, `false` or `null`, according to our `bool` definition. Mind that **all non-zero numbers are converted to `true`**.

For conditional functions, `null` is treated as `false`.

Expression	Result
`iif(true, 'true', 'false')`	`'true'`
`iif('yes', 'true', 'false')`	`'true'`
`iif(1, 'true', 'false')`	`'true'`
`iif(123, 'true', 'false')`	`'true'`
`iif('false', 'true', 'false')`	`'false'`
`iif(0, 'true', 'false')`	`'false'`
`iif('abc', 'true', 'false')`	`'false'`

`bool` and the Logical NOT Operator

Both the logical NOT `!` operator and the `not` function:

- Return `false` for all values considered `true` by the `bool` definition. Mind that **all non-zero numbers are converted to `true`**.
- Return `true` for all values considered `false` by the `bool` definition.
- Return `null` if passed `null`, or for any values that can't be converted to `true` or `false`.

Expression	Result
`not(true)`	`false`
`not('true')`	`false`
`not('yes')`	`false`
`not(1)`	`false`
`not(100)`	`false`
`not(false)`	`true`
`not('false')`	`true`
`not('no')`	`true`
`not(0)`	`true`

Expression	Result

14.7.2. Datetime

The `datetime (date)` data type represents an instant in time. A `datetime` value can be any of the following:

1. A complete timestamp, expressed in Unix time. Examples:
    - `1700511360` (a whole number, representing seconds)
    - `1700511420.123` (a fractional/decimal number, representing milliseconds)
2. Time only, assuming "today" UTC as the date. Examples:
    - `12:34`
    - `12:34:56`
    - `12:34:56.789`
3. Date only, assuming midnight UTC as the date line. Example:
    - `2025-01-23`
4. A combination of date and time. Examples:
    - `2025-01-23 12:34:56.789` (supports nonstandard format with space)
    - `2025-01-23T12:34:56.789Z` (supports ISO "Z" for time zone)
    - `2025-01-23T12:34:56.789+00:00` (supports ISO variation with offset)

14.7.3. Decimal

The `decimal` data type represents a 64-bit wide, double-precision, floating-point number.

Aliases: `double`, `real`.

- `decimal("123.4")` returns `123.4`
- `decimal("1e3")` returns `1000`
- `decimal("hello")` returns `null`

14.7.4. Double

The `double` data type represents a 64-bit wide, double-precision, floating-point number.

Aliases: `decimal`, `real`.

- `double("123.4")` returns `123.4`
- `double("1e3")` returns `1000`
- `double("hello")` returns `null`

14.7.5. Dynamic

The `dynamic` scalar data type is special in that it can take on any value of other scalar data types from the list below, as well as arrays and property bags.

Specifically, a `dynamic` value can be any of the following:

- A value of any of the primitive scalar data types: `bool`, `datetime`, `int`, `long`, `real`, `string`, and `timespan`.
- A **dynamic array** (an array of `dynamic` values), holding zero or more values with zero-based indexing.
- A **property bag** (or **dictionary**) that maps keys (unique `string` values) to `dynamic` values. A property bag has zero or more such mappings (called **slots**), indexed by the keys. Slots are unordered.
  Cribl Search doesn't attempt to preserve the order of key-to-value mappings in a property bag, and so you can't assume the order to be preserved. It's entirely possible for two property bags with the same set of mappings to yield different results when they are represented as `string` values.
- `null`.

`dynamic` Literals

A literal of type `dynamic` looks like this:

`dynamic(` *Value* `)`

Value can be:

- `null`, in which case the literal represents the null dynamic value: `dynamic(null)`.
- Another scalar data type literal, in which case the literal represents the `dynamic` literal of the "inner" type. For example, `dynamic(4)` is a dynamic value holding the value 4 of the long scalar data type.
- An array of dynamic or other literals: `[` *ListOfValues* `]`. For example, `dynamic([1, 2, "hello"])` is a dynamic array of three elements, two `long` values and one `string` value.
- A property bag: `{` *Key* `=` *Value* `...` `}`. For example, `dynamic({"a":1, "b":{"a":2}})` is a property bag with two slots, `a`, and `b`, with the second slot being another property bag.

`dynamic` Object Accessors

To subscript a dictionary (in other words, reference a key in a property bag), use either dot notation (`dict.key`) or bracket notation (`dict["key"]`). When the subscript is a string constant, both options are equivalent.

To use an expression as the subscript, use bracket notation. When using arithmetic expressions, the expression inside the brackets must be wrapped in parentheses.

In the examples below `dict` and `arr` are columns of dynamic type:

Expression	Accessor expression type	Meaning	Comments
`dict[col]`	Entity name (column)	Subscripts a dictionary using the values of the column `col` as the key	Column must be of type string
`arr[index]`	Entity index (column)	Subscripts an array using the values of the column `index` as the index	Column must be of type integer or boolean
`arr[-index]`	Entity index (column)	Retrieves the 'index'-th value from the end of the array	Column must be of type integer or boolean
`arr[(-1)]`	Entity index	Retrieves the last value in the array	
`arr[toint(indexAsString)]`	Function call	Casts the values of column `indexAsString` to int and use them to subscript an array	
`dict[['where']]`	Keyword used as entity name (column)	Subscripts a dictionary using the values of column `where` as the key	Entity names that are identical to some query language keywords must be quoted
`dict.['where']` or `dict['where']`	Constant	Subscripts a dictionary using `where` string as the key	

Casting `dynamic` Objects

After subscripting a dynamic object, you must cast the value to a simple type.

Expression	Value	Type
`X`	`parse_json('[100,101,102]')`	array
`X[0]`	`parse_json('100')`	dynamic
`toint(X[1])`	`101`	int

Expression	Value	Type
`Y`	`parse_json('{"a1":100, "a b c":"2015-01-01"}')`	dictionary
`Y.a1`	`parse_json('100')`	dynamic
`Y["a b c"]`	`parse_json("2015-01-01")`	dynamic
`todate(Y["a b c"])`	`datetime(2015-01-01)`	datetime

Cast functions are:

- tolong
- todouble
- todatetime
- totimespan
- tostring
- parse_json

Functions Over `dynamic` Types

Dynamic scalar functions allow you to manipulate objects by operating on `dynamic` values, including dynamic arrays and property bags.

Name	Description
`bag_has_key`	Checks whether a property bag contains a given key.
`bag_keys`	Lists all root keys of a property bag.
`bag_merge`	Merges multiple property bags, discarding duplicate keys.
`bag_pack`	Creates a property bag from an alternating list of keys and values.
`bag_pack_columns`	Creates a property bag from a list of columns.
`bag_remove_keys`	Removes key-value pairs from a property bag.
`bag_set_key`	Adds or overwrites a key-value pair in a property bag.
`bag_zip`	Creates a property bag from two dynamic arrays.
`make_bag`	Creates a property bag from multiple input bags.

Name	Description
make_bag_if	Creates a property bag from those input bags that meet the specified condition.
zip	Merges dynamic arrays, grouping elements by index.

The following string functions support `dynamic` types as well:

Function	Usage with dynamic data types
extractjson(`path,object`)	Uses path to navigate into object.
parse_json(`source`)	Turns a JSON string into a dynamic object.
range(`from,to,step`)	Generates an array of values.

14.7.6. Int

The `int` data type represents a signed, 64-bit wide, integer.

Aliases: `long`.

`int` Examples

- `int("123.456")` returns `123`
- `int("abc")` returns `null`

14.7.7. Long

The `long` data type represents a signed, 64-bit wide, integer.

Aliases: `int`.

`long` Examples

- `long("123.456")` returns `123`
- `long("abc")` returns `null`

14.7.8. Null

The `null` value in Cribl Search can indicate:

- The absence of a field or value.
- A type mismatch in a conversion, operation, or function. For example, `toint('abc')` and `123 / 'hello'` both evaluate to `null` because strings can't be converted to numbers.

`null` and Missing Fields

When an expression references a field that an event doesn't contain, Cribl Search returns `null` for that field instead of dropping the field from the event. This applies to the `project`, `extend`, and `summarize` operators.

For example, the `foo` field doesn't exist in the `$vt_dummy` Dataset, so the following query returns `bar` as `null` in every event:

```
dataset="$vt_dummy" event<5
| project event, bar=foo
```

Copy | Run in Cribl Search

Because Cribl Search keeps the field, every event in the results has the same set of fields, whether or not the source data supplied a value. To drop the events that have no value, filter them out with `isnotnull`.

`null` Literals

A `null` literal is represented in Cribl Search as `null`. For example:

- `where field==null`
- `extend result=iff(value > 100, value, null)`

`null` Equality and Inequality

Cribl Search supports the `null` value in equality/inequality comparisons. These comparisons are equivalent to using the `isnull` and `isnotnull` functions.



This is different from standard Kusto Query Language (KQL), which returns `null` if both sides of the comparison are `null`.

See the following examples:

Expression	Result
`5 == null`	`false`
`5 != null`	`true`
`null == 5`	`false`
`'abc' == null`	`false`
`'null' == null`	`false`
`0 == null`	`false`
`int('abc') == null`	`true`
`int('abc') == int('def')`	`true`

`null` and Strings

Cribl Search supports the `null` value in `string` comparisons.



This is different from standard Kusto Query Langauge (KQL), which does not allow the `null` value for strings.

See the following examples:

Expression	Result
`tostring(null)`	`null`
`string(null)`	`null`
`isnull('abc')`	`false`
`'abc' == null`	`false`

`null` and Binary Operators

Binary operators are those that perform an operation on two values. These operators include `and`, `or`, `==`, `!=`, `>=`, `<=`, numeric operators (`+`, `-`, `*`), and others.

If one or both of the values passed to the binary operator are `null`, then the output of the binary operator is also `null`. For example, `null + 10` returns `null`.

Exceptions to the rule above are:

- For the equality `==` and inequality `!=` operators, either or both sides of the operation can be `null`, and will return `true` or `false` rather than `null` (as described in `null` Equality and Inequality).
- For the logical `AND` operator, if one of the values is `false`, the result is also `false`.
- For the logical `OR` operator, if one of the values is `true`, the result is also `true`.

See the following examples:

Expression	Result
`5 > 3`	`true`
`null > 3`	`null`
`null > int('abc')`	`null`
`null == int('abc')`	`true`
`null >= int('abc')`	`true`
`null >= 3`	`null`
`null > int('abc')`	`null`
`10 + null`	`null`
`10 + 'abc'`	`null`
`10 - ''`	`null`
`10 - null`	`null`
`10 + unknown_field`	`null`
`10 - toint('abc')`	`null`
`null * 10`	`null`
`null > 3 and true`	`null`
`null > 3 and false`	`false`
`null > 3 or true`	`true`
`null > 3 or false`	`null`

`null` and the `where` Operator

The `where` operator treats `null` as `false`. This means that events with conditions evaluating to `null` won't appear in the search results.

For example, `dataset="foo" | where tobool("abc")` returns no results because `tobool("abc")` evaluates to `null`.

`null` and Distinct Counts

The `dcount` and `dcountif` aggregation functions don't count `null` toward the number of distinct values. If every value in a summary group is `null`, these functions return `0`.

`null` and the Logical `NOT` Operator

If the value passed to the logical `NOT` (`!`) operator is `null`, then the output is also `null`.

Expression	Result
`not(true)`	`false`
`not(false)`	`true`
`not(null)`	`null`
`not(int('abc'))`	`null`
`!int('abc')`	`null`

14.7.9. Real

The `real` data type represents a 64-bit wide, double-precision, floating-point number.

Aliases: `decimal`, `double`.

- `real("123.4")` returns `123.4`
- `real("1e3")` returns `1000`
- `real("hello")` returns `null`

14.7.10. String

The `string` data type represents a sequence of zero or more Unicode characters.

`string` Literals

There are several ways to encode literals of the `string` data type in a query text:

- Enclose the string in double-quotes `"`:
  `"This is a string literal. Single quote characters (') don't require escaping. Double quote characters (\") are escaped by a backslash (\\)."`
- Enclose the string in single-quotes `'`:
  `'Another string literal. Single quote characters (\') require escaping by a backslash (\\). Double quote characters (") do not require escaping.'`

In the two representations above, the backslash `\` character indicates escaping. The backslash is used to escape the enclosing quote characters, tab characters `\t`, newline characters `\n`, and itself `\\`.

The newline character `\n` and the return character `\r` can't be included as part of the string literal without being quoted.

Verbatim `string` Literals

Verbatim string literals are also supported. You specify them by prepending an asperand `@` character. In this form, the backslash character `\` stands for itself, and not as an escape character.

- Enclose in double-quotes `"`:
  `@"This is a verbatim string literal that ends with a backslash\. Double quote characters ("") are escaped by a double quote ("")."`
- Enclose in single-quotes `'`:
  `@'This is a verbatim string literal that ends with a backslash\. Single quote characters ('') are escaped by a single quote ('')."`

Concatenation

Joining two or more string literals is supported. For example:

```
dataset="$vt_dummy"
 | extend x = strcat('Hello', ', ', "world!")
```

Copy | Run in Cribl Search

Returns `x` as `Hello, world!`.

Obfuscation

Obfuscating strings is not supported, however, the query will not complain if attempted.

`string` Examples

- `string(123)` returns `"123"`
- `string("hello")` returns `"hello"`
- `string(null)` returns `null`

14.7.11. TIMESPAN

The `timespan(time)` data type represents a time interval, in seconds.



This representation differs from the standard Kusto `timespan` type, which represents a literal timespan.

`timespan` Literals

Literals of type `timespan` have the syntax `timespan(value)`, where a number of formats are supported for `value`, as indicated by the following table:

Value	Length of time
`2d`	2 days
`1.5h`	1.5 hour
`30m`	30 minutes
`10s`	10 seconds
`0.1s`	0.1 second
`100ms`	100 millisecond
`10microsecond`	10 microseconds
`1tick`	100ns
`time(15 seconds)`	15 seconds
`time(2)`	2 days
`time(0.12:34:56.7)`	`0d+12h+34m+56.7s`

The special form `time(null)` is the null value.

`timespan` Operators

Two values of type `timespan` may be added, subtracted, and divided. The last operation returns a value of type `real` representing the fractional number of times one value can fit the other.

Examples

The following examples calculate, in several ways, how many seconds are in a day:

- `1d / 1s`
- `time(1d) / time(1s)`
- `24 * 60 * time(00:01:00) / time(1s)`

14.8. Regex Matching

Regular expressions usage, with examples, supported flags, and syntax details.

Regex literals in Cribl Search queries use ECMA-style (JavaScript) regular expressions. If you test patterns in external tools such as Regex101, select the **ECMAScript (JavaScript)** flavor.

Note: Some Search scalar string functions use RE2 regex instead; see individual function documentation for details.

The `matches regex`, `search`, `where`, `in`, `!in`, `in~`, and `!in~` operators can use regex syntax to match against strings and regex literals.

To match against regex literals, the supported comparison operators are `==`, `=~`, `!=`, and `!~`.

Regex Examples

The examples below focus on using regular expressions with the `where` operator.

Match on String Values

Match a corresponding regex literal, with wildcard. This is case-sensitive by default:

```
dataset=myDataset
| summarize event_count=count() by State
| where State == /K.*S/
```

Copy

Case-insensitive version of the above query, using the `/i` flag:

```
dataset=myDataset
| summarize event_count=count() by State
| where State == /k.*s/i
```

Copy

Case-insensitive, using the `=~` operator instead of the `/i` flag:

```
dataset=myDataset
| summarize event_count=count() by State
| where State =~ /k.*s/
```

Copy

Match on `in` Lists or Combined Targets

Mix and match string targets with regex literal targets:

```
dataset="cribl_internal_logs" method=*
| limit 1000
| where method in ("GET", /^po.*/i)
```

Copy Run in Cribl Search

Same query, using the `in~` operator for implicit `/i`:

```
dataset="cribl_internal_logs" method=*
| limit 1000
| where method in~ ("GET", /^po.*/)
```

Copy Run in Cribl Search

An "or" query with | notation:

```
dataset="cribl_internal_logs" method=*
| limit 1000
| where method == /post|get/i
```

Copy Run in Cribl Search

A negation query:

```
dataset="cribl_internal_logs" method=*
| limit 1000
| where method != /post|get/i
```

Copy Run in Cribl Search

Find the string value `bar` in the field `foo`:

```
cribl foo = /bar/
```

Copy

Regex Flags

Evaluation is case-sensitive by default. You can ignore case by using the `/i` flag or `=~` operator, as shown in the examples below.

This operator supports any combination of the `/i`, `/m`, `/s`, and `/u` flags:

Flag	Description
`i`	Case-insensitive match.
`m`	Multi-line mode: Allows `^` and `$` to match next to newline characters.
`s`	Single-line ("dotall") mode: Allows `.` to match newline characters.
`u`	Unicode (full) mode; Allows matching against 4-byte Unicode characters.

Disambiguate Regex Characters

In some expressions, you might need to distinguish regex literal delimiters from division symbols. Consider this expression:

```
dataset=myDataset
| <query>
| where value == 10/20/5
```

Copy

The `/20/` portion **could** be a regular expression. But given the numeric characters surrounding it, Cribl Search interprets as division. However, a similar expression with non-numeric characters is ambiguous:

```
dataset=myDataset
| <query>
| where value == x/y/z
```

Copy

Here, Cribl Search would try to interpret `/y/` as a regular expression. You can disambiguate the expression as a series of divisions by inserting blank spaces, conceptually like this:

```
where value == x / y / z
```

Copy

But to insert the blank spaces within regex syntax, you'd use the `\s` character qualifier:

```
dataset=myDataset
| <query>
| where value == /x\s\/\sy\s\/\sz/
```

Copy



In the above style of regular expression, `/` must be escaped as `\/`.